

Apache Impala Guide

Contents

Introducing Apache Impala.....	16
Impala Benefits.....	16
How Impala Works with Apache Hadoop.....	16
Primary Impala Features.....	17
Impala Concepts and Architecture.....	17
Components of the Impala Server.....	17
The Impala Daemon.....	17
The Impala Statestore.....	18
The Impala Catalog Service.....	18
Developing Impala Applications.....	19
Overview of the Impala SQL Dialect.....	19
Overview of Impala Programming Interfaces.....	20
How Impala Fits Into the Hadoop Ecosystem.....	20
How Impala Works with Hive.....	21
Overview of Impala Metadata and the Metastore.....	21
How Impala Uses HDFS.....	21
How Impala Uses HBase.....	21
Planning for Impala Deployment.....	22
Impala Requirements.....	22
Supported Operating Systems.....	22
Hive Metastore and Related Configuration.....	22
Java Dependencies.....	22
Networking Configuration Requirements.....	23
Hardware Requirements.....	23
User Account Requirements.....	23
Guidelines for Designing Impala Schemas.....	24
Installing Impala.....	25
What is Included in an Impala Installation.....	26
Managing Impala.....	26
Post-Installation Configuration for Impala.....	27
Upgrading Impala.....	28
Upgrading Impala.....	28
Impala Upgrade Considerations.....	29
Grant REFRESH Privilege to Impala Roles with SELECT or INSERT Privilege when Upgrading to Impala 3.0.....	29
List of Reserved Words Updated in Impala 3.0.....	29
Decimal V2 Used by Default in Impala 3.0.....	29
Behavior of Column Aliases Changed in Impala 3.0.....	30
Default PARQUET_ARRAY_RESOLUTION Changed in Impala 3.0.....	30

Enable Clustering Hint for Inserts.....	30
Deprecated Query Options Removed in Impala 3.0.....	30
Fine-grained Privileges Added in Impala 3.0.....	30
refresh_after_connect Impala Shell Option Removed in Impala 3.0.....	30
Return Type Changed for EXTRACT and DATE_PART Functions in Impala 3.0.....	30
Port Change for SHUTDOWN Command.....	31
Change in Client Connection Timeout.....	31
Default Setting Changes.....	31
Starting Impala.....	31
Starting Impala from the Command Line.....	32
Modifying Impala Startup Options.....	32
Configuring Impala Startup Options through the Command Line.....	32
Checking the Values of Impala Configuration Options.....	35
Startup Options for catalogd Daemon.....	35
Impala Tutorials.....	35
Tutorials for Getting Started.....	35
Explore a New Impala Instance.....	36
Load CSV Data from Local Files.....	40
Point an Impala Table at Existing Data Files.....	43
Describe the Impala Table.....	44
Query the Impala Table.....	45
Data Loading and Querying Examples.....	45
Advanced Tutorials.....	48
Attaching an External Partitioned Table to an HDFS Directory Structure.....	48
Switching Back and Forth Between Impala and Hive.....	50
Cross Joins and Cartesian Products with the CROSS JOIN Operator.....	51
Dealing with Parquet Files with Unknown Schema.....	53
Download the Data Files into HDFS.....	53
Create Database and Tables.....	54
Examine Physical and Logical Schema.....	54
Analyze Data.....	56
Impala Administration.....	65
Setting Timeout Periods for Daemons, Queries, and Sessions.....	65
Increasing the Statestore Timeout.....	66
Setting the Idle Query and Idle Session Timeouts for impalad.....	66
Setting Timeout and Retries for Thrift Connections to the Backend Client.....	67
Cancelling a Query.....	67
Using Impala through a Proxy for High Availability.....	67
Overview of Proxy Usage and Load Balancing for Impala.....	68
Choosing the Load-Balancing Algorithm.....	68
Special Proxy Considerations for Clusters Using Kerberos.....	69
Special Proxy Considerations for TLS/SSL Enabled Clusters.....	70
Example of Configuring HAProxy Load Balancer for Impala.....	71
Managing Disk Space for Impala Data.....	73
Impala Security.....	78
Security Guidelines for Impala.....	79
Securing Impala Data and Log Files.....	80
Installation Considerations for Impala Security.....	80

Securing the Hive Metastore Database.....	81
Securing the Impala Web User Interface.....	81
Configuring TLS/SSL for Impala.....	81
Using the Command Line.....	81
Using TLS/SSL with Business Intelligence Tools.....	82
Specifying TLS/SSL Minimum Allowed Version and Ciphers.....	82
Impala Authorization.....	83
The Privilege Model.....	83
Object Ownership in Ranger.....	86
Starting Impala with Ranger Authorization Enabled.....	86
Managing Privileges.....	86
Setting Up Schema Objects for a Secure Impala Deployment.....	89
The DEFAULT Database in a Secure Deployment.....	89
Ranger Column Masking.....	89
Limitations on Mask Functions.....	90
Impala Authentication.....	90
Enabling Kerberos Authentication for Impala.....	90
Enabling LDAP Authentication for Impala.....	93
Using Multiple Authentication Methods with Impala.....	97
Configuring Impala Delegation for Clients.....	97
Auditing Impala Operations.....	99
Durability and Performance Considerations for Impala Auditing.....	99
Format of the Audit Log Files.....	99
Which Operations Are Audited.....	100
Viewing Lineage Information for Impala Data.....	100

Impala SQL Language Reference.....101

Comments.....	102
Data Types.....	102
ARRAY Complex Type (Impala 2.3 or higher only).....	102
BIGINT Data Type.....	106
BOOLEAN Data Type.....	107
CHAR Data Type (Impala 2.0 or higher only).....	108
DATE Data Type.....	110
DECIMAL Data Type (Impala 3.0 or higher only).....	111
DOUBLE Data Type.....	116
FLOAT Data Type.....	117
INT Data Type.....	118
MAP Complex Type (Impala 2.3 or higher only).....	119
REAL Data Type.....	123
SMALLINT Data Type.....	124
STRING Data Type.....	125
STRUCT Complex Type (Impala 2.3 or higher only).....	127
TIMESTAMP Data Type.....	133
TINYINT Data Type.....	139
VARCHAR Data Type (Impala 2.0 or higher only).....	140
Complex Types (Impala 2.3 or higher only).....	142
Literals.....	173
Numeric Literals.....	174
String Literals.....	175
Boolean Literals.....	176
Timestamp Literals.....	176
Date Literals.....	177
NULL.....	177
SQL Operators.....	178

Arithmetic Operators.....	178
BETWEEN Operator.....	181
Comparison Operators.....	182
EXISTS Operator.....	183
ILIKE Operator.....	187
IN Operator.....	188
IREGEXP Operator.....	190
IS DISTINCT FROM Operator.....	191
IS NULL Operator.....	193
IS TRUE Operator.....	194
LIKE Operator.....	195
Logical Operators.....	195
REGEXP Operator.....	198
RLIKE Operator.....	200
Impala Schema Objects and Object Names.....	201
Overview of Impala Aliases.....	201
Overview of Impala Databases.....	203
Overview of Impala Functions.....	204
Overview of Impala Identifiers.....	205
Overview of Impala Tables.....	206
Overview of Impala Views.....	209
Impala Transactions.....	213
Impala SQL Statements.....	213
DDL Statements.....	213
DML Statements.....	214
ALTER DATABASE Statement.....	215
ALTER TABLE Statement.....	215
ALTER VIEW Statement.....	230
COMMENT Statement.....	232
COMPUTE STATS Statement.....	232
CREATE DATABASE Statement.....	240
CREATE FUNCTION Statement.....	242
CREATE ROLE Statement (Impala 2.0 or higher only).....	248
CREATE TABLE Statement.....	248
CREATE VIEW Statement.....	265
DELETE Statement (Impala 2.8 or higher only).....	266
DESCRIBE Statement.....	268
DROP DATABASE Statement.....	280
DROP FUNCTION Statement.....	282
DROP ROLE Statement (Impala 2.0 or higher only).....	284
DROP STATS Statement.....	284
DROP TABLE Statement.....	289
DROP VIEW Statement.....	290
EXPLAIN Statement.....	291
GRANT Statement (Impala 2.0 or higher only).....	294
INSERT Statement.....	298
INVALIDATE METADATA Statement.....	307
LOAD DATA Statement.....	309
REFRESH Statement.....	312
REFRESH AUTHORIZATION Statement.....	314
REFRESH FUNCTIONS Statement.....	314
REVOKE Statement (Impala 2.0 or higher only).....	315
SELECT Statement.....	316
SET Statement.....	345
SHOW Statement.....	395
SHUTDOWN Statement.....	415

TRUNCATE TABLE Statement (Impala 2.3 or higher only).....	416
UPDATE Statement (Impala 2.8 or higher only).....	418
UPSERT Statement (Impala 2.8 or higher only).....	420
USE Statement.....	421
VALUES Statement.....	421
Optimizer Hints.....	422
Impala Built-In Functions.....	428
Impala Mathematical Functions.....	434
Impala Bit Functions.....	455
Impala Type Conversion Functions.....	467
Impala Date and Time Functions.....	478
Impala Conditional Functions.....	502
Impala String Functions.....	509
Impala Miscellaneous Functions.....	535
Impala Aggregate Functions.....	539
Impala Analytic Functions.....	569
User-Defined Functions (UDFs).....	588
UDF Concepts.....	589
Runtime Environment for UDFs.....	592
Installing the UDF Development Package.....	592
Writing User-Defined Functions (UDFs).....	593
Writing User-Defined Aggregate Functions (UDAFs).....	596
Building and Deploying UDFs.....	597
Performance Considerations for UDFs.....	598
Examples of Creating and Using UDFs.....	598
Security Considerations for User-Defined Functions.....	605
Limitations and Restrictions for Impala UDFs.....	605
SQL Differences Between Impala and Hive.....	606
HiveQL Features not Available in Impala.....	606
Semantic Differences Between Impala and HiveQL Features.....	607
Porting SQL from Other Database Systems to Impala.....	608
Porting DDL and DML Statements.....	608
Porting Data Types from Other Database Systems.....	608
SQL Statements to Remove or Adapt.....	610
SQL Constructs to Double-check.....	612
Next Porting Steps after Verifying Syntax and Semantics.....	613
UTF-8 Support.....	613
Turning ON the UTF-8 behavior.....	613
List of STRING Functions.....	613
Limitations.....	614

Tuning Impala for Performance..... 614

Impala Performance Guidelines and Best Practices.....	615
Performance Considerations for Join Queries.....	618
How Joins Are Processed when Statistics Are Unavailable.....	619
Overriding Join Reordering with STRAIGHT_JOIN.....	619
Examples of Join Order Optimization.....	619
Table and Column Statistics.....	625
Overview of Table Statistics.....	625
Overview of Column Statistics.....	626
How Table and Column Statistics Work for Partitioned Tables.....	627
Generating Table and Column Statistics.....	630
Detecting Missing Statistics.....	633
Manually Setting Table and Column Statistics with ALTER TABLE.....	635
Examples of Using Table and Column Statistics with Impala.....	637

Benchmarking Impala Queries.....	641
Controlling Impala Resource Usage.....	641
Runtime Filtering for Impala Queries (Impala 2.5 or higher only).....	641
Background Information for Runtime Filtering.....	642
Runtime Filtering Internals.....	642
File Format Considerations for Runtime Filtering.....	643
Wait Intervals for Runtime Filters.....	643
Query Options for Runtime Filtering.....	643
Runtime Filtering and Query Plans.....	644
Examples of Queries that Benefit from Runtime Filtering.....	645
Tuning and Troubleshooting Queries that Use Runtime Filtering.....	646
Limitations and Restrictions for Runtime Filtering.....	646
Using HDFS Caching with Impala (Impala 2.1 or higher only).....	646
Overview of HDFS Caching for Impala.....	647
Setting Up HDFS Caching for Impala.....	647
Enabling HDFS Caching for Impala Tables and Partitions.....	647
Loading and Removing Data with HDFS Caching Enabled.....	649
Administration for HDFS Caching with Impala.....	650
Performance Considerations for HDFS Caching with Impala.....	650
Detecting and Correcting HDFS Block Skew Conditions.....	651
Data Cache for Remote Reads.....	653
Testing Impala Performance.....	653
Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles.....	654
Using the EXPLAIN Plan for Performance Tuning.....	655
Using the SUMMARY Report for Performance Tuning.....	655
Using the Query Profile for Performance Tuning.....	656

Scalability Considerations for Impala..... 657

Impact of Many Tables or Partitions on Impala Catalog Performance and Memory Usage.....	657
Scalability Considerations for the Impala Statestore.....	658
Effect of Buffer Pool on Memory Usage (Impala 2.10 and higher).....	659
SQL Operations that Spill to Disk.....	660
Limits on Query Size and Complexity.....	663
Scalability Considerations for Impala I/O.....	663
Scalability Considerations for Table Layout.....	663
Kerberos-Related Network Overhead for Large Clusters.....	663
Avoiding CPU Hotspots for HDFS Cached Data.....	664
Scalability Considerations for File Handle Caching.....	664
Scaling Limits and Guidelines.....	665
Deployment Limits.....	665
Data Storage Limits.....	666
Schema Design Limits.....	666
Security Limits.....	666
Query Limits - Compile Time.....	666
Query Limits - Runtime Time.....	666
How to Configure Impala with Dedicated Coordinators.....	666
Determining the Optimal Number of Dedicated Coordinators.....	667
Deploying Dedicated Coordinators and Executors.....	669
Metadata Management.....	670
On-demand Metadata.....	670
Automatic Invalidation of Metadata Cache.....	671
Automatic Invalidation/Refresh of Metadata.....	671

Resource Management..... 675

Admission Control and Query Queuing.....	675
Concurrent Queries and Admission Control.....	675
Memory Limits and Admission Control.....	677
Setting Per-query Memory Limits.....	679
How Impala Admission Control Relates to Other Resource Management Tools.....	679
How Impala Schedules and Enforces Limits on Concurrent Queries.....	680
How Admission Control works with Impala Clients (JDBC, ODBC, HiveServer2).....	680
SQL and Schema Considerations for Admission Control.....	680
Guidelines for Using Admission Control.....	681
Configuring Admission Control.....	681
Configuring Admission Control in Command Line Interface.....	681
Configuring Cluster-wide Admission Control.....	684

Partitioning for Impala Tables.....685

When to Use Partitioned Tables.....	686
SQL Statements for Partitioned Tables.....	686
Static and Dynamic Partitioning Clauses.....	687
Refreshing a Single Partition.....	687
Permissions for Partition Subdirectories.....	687
Partition Pruning for Queries.....	688
Checking if Partition Pruning Happens for a Query.....	688
What SQL Constructs Work with Partition Pruning.....	688
Dynamic Partition Pruning.....	689
Partition Key Columns.....	691
Setting Different File Formats for Partitions.....	691
Managing Partitions.....	692
Using Partitioning with Kudu Tables.....	692
Keeping Statistics Up to Date for Partitioned Tables.....	693

How Impala Works with Hadoop File Formats.....695

Choosing the File Format for a Table.....	697
Using Text Data Files with Impala Tables.....	697
Query Performance for Impala Text Tables.....	698
Creating Text Tables.....	699
Data Files for Text Tables.....	699
Loading Data into Impala Text Tables.....	701
Using LZO-Compressed Text Files.....	702
Using bzip2, deflate, gzip, Snappy, or zstd Text Files.....	704
Using the Parquet File Format with Impala Tables.....	705
Creating Parquet Tables in Impala.....	705
Loading Data into Parquet Tables.....	706
Query Performance for Impala Parquet Tables.....	707
Compressions for Parquet Data Files.....	709
Parquet Tables for Impala Complex Types.....	712
Exchanging Parquet Data Files with Other Hadoop Components.....	712
How Parquet Data Files Are Organized.....	715
Compacting Data Files for Parquet Tables.....	716
Schema Evolution for Parquet Tables.....	716
Data Type Considerations for Parquet Tables.....	718
Using the ORC File Format with Impala Tables.....	719
Creating ORC Tables and Loading Data.....	719
Enabling Compression for ORC Tables.....	720
Query Performance for Impala ORC Tables.....	721
Data Type Considerations for ORC Tables.....	721

Using the Avro File Format with Impala Tables.....	722
Creating Avro Tables.....	722
Using a Hive-Created Avro Table in Impala.....	724
Specifying the Avro Schema through JSON.....	725
Loading Data into an Avro Table.....	725
Enabling Compression for Avro Tables.....	725
How Impala Handles Avro Schema Evolution.....	725
Data Type Considerations for Avro Tables.....	726
Query Performance for Impala Avro Tables.....	727
Using the Hudi File Format.....	727
Using the RCFile File Format with Impala Tables.....	728
Creating RCFile Tables and Loading Data.....	728
Enabling Compression for RCFile Tables.....	729
Query Performance for Impala RCFile Tables.....	730
Using the SequenceFile File Format with Impala Tables.....	730
Creating SequenceFile Tables and Loading Data.....	730
Enabling Compression for SequenceFile Tables.....	731
Query Performance for Impala SequenceFile Tables.....	732
Using Impala to Query Kudu Tables.....	733
Benefits of Using Kudu Tables with Impala.....	733
Configuring Impala for Use with Kudu.....	733
Cluster Topology for Kudu Tables.....	733
Kudu Replication Factor.....	734
Impala DDL Enhancements for Kudu Tables (CREATE TABLE and ALTER TABLE).....	734
Non-unique Primary Keys for Kudu Tables.....	734
Create a Kudu Table with a non-unique PRIMARY KEY.....	734
Verify the PRIMARY KEY is non-unique.....	734
Query Auto Incrementing Column.....	735
Create a Kudu table without a PRIMARY KEY attribute.....	735
Limitations.....	735
Primary Key Columns for Kudu Tables.....	735
Kudu-Specific Column Attributes for CREATE TABLE.....	736
Partitioning for Kudu Tables.....	740
Handling Date, Time, or Timestamp Data with Kudu.....	743
How Impala Handles Kudu Metadata.....	745
Working with Kudu Integrated with Hive Metastore.....	746
Loading Data into Kudu Tables.....	746
Impala DML Support for Kudu Tables (INSERT, UPDATE, DELETE, UPSERT).....	747
Multi-row Transactions for Kudu Tables.....	747
Using Multi-row Transaction Capability.....	748
Advantages of Using This Capability.....	748
Limitation.....	748
Consistency Considerations for Kudu Tables.....	749
Security Considerations for Kudu Tables.....	749
Impala Query Performance for Kudu Tables.....	749
Using Impala to Query HBase Tables.....	750
Overview of Using HBase with Impala.....	750
Configuring HBase for Use with Impala.....	751
Supported Data Types for HBase Columns.....	751
Performance Considerations for the Impala-HBase Integration.....	751
Use Cases for Querying HBase through Impala.....	757
Loading Data into an HBase Table.....	757

Limitations and Restrictions of the Impala and HBase Integration.....	757
Examples of Querying HBase Tables from Impala.....	758

Using Impala with Iceberg Tables..... 760

Overview of Iceberg features.....	760
Creating Iceberg tables with Impala.....	760
Iceberg V2 tables.....	762
Dropping Iceberg tables.....	762
Supported Data Types for Iceberg Columns.....	763
Schema evolution of Iceberg tables.....	763
Partitioning Iceberg tables.....	764
Inserting data into Iceberg tables.....	764
Delete data from Iceberg tables.....	765
Updating data int Iceberg tables.....	765
Loading data into Iceberg tables.....	765
Optimizing (Compacting) Iceberg tables.....	766
Time travel for Iceberg tables.....	766
Rolling Iceberg tables back to a previous state.....	767
Expiring snapshots.....	767
Cloning Iceberg tables (LIKE clause).....	768
Iceberg table properties.....	768
Iceberg manifest caching.....	769

Using Impala with Amazon S3 Object Store..... 769

Best Practices for Using Impala with S3.....	769
How Impala SQL Statements Work with S3.....	770
Specifying Impala Credentials to Access Data in S3.....	771
Loading Data into S3 for Impala Queries.....	771
Using Impala DML Statements for S3 Data.....	771
Manually Loading Data into Impala Tables in S3.....	771
Creating Impala Databases, Tables, and Partitions for Data Stored in S3.....	772
Internal and External Tables Located in S3.....	773
Running and Tuning Impala Queries for Data Stored in S3.....	773
Understanding and Tuning Impala Query Performance for S3 Data.....	774
Restrictions on Impala Support for S3.....	774

Using Impala with the Azure Data Lake Store (ADLS)..... 774

Prerequisites.....	775
How Impala SQL Statements Work with ADLS.....	775
Specifying Impala Credentials to Access Data in ADLS.....	775
Loading Data into ADLS for Impala Queries.....	777
Using Impala DML Statements for ADLS Data.....	777
Manually Loading Data into Impala Tables on ADLS.....	777
Creating Impala Databases, Tables, and Partitions for Data Stored on ADLS.....	777
Internal and External Tables Located on ADLS.....	779
Running and Tuning Impala Queries for Data Stored on ADLS.....	781
Understanding and Tuning Impala Query Performance for ADLS Data.....	782
Restrictions on Impala Support for ADLS.....	782
Best Practices for Using Impala with ADLS.....	782

Using Impala with Isilon Storage..... 783

Using Impala with Apache Ozone Storage..... 783**Using Impala Logging..... 784**

Locations and Names of Impala Log Files.....	785
Rotating Impala Logs.....	785
Changing Log Levels Dynamically.....	786
Reviewing Impala Logs.....	786
Understanding Impala Log Contents.....	787
Setting Logging Levels.....	787
Redacting Sensitive Information from Impala Log Files.....	787

Impala Client Access..... 788

Using the Impala Shell (impala-shell Command).....	790
impala-shell Configuration Options.....	791
Connecting to Impala Daemon from impala-shell.....	796
Running Commands and SQL Statements in impala-shell.....	798
impala-shell Command Reference.....	799
Configuring Impala to Work with ODBC.....	801
Configuring Impala to Work with JDBC.....	801
Configuring the JDBC Port.....	802
Choosing the JDBC Driver.....	802
Enabling Impala JDBC Support on Client Systems.....	802
Establishing JDBC Connections.....	803
Notes about JDBC and ODBC Interaction with Impala SQL Features.....	804
Kudu Considerations for DML Statements.....	804
Spooling Impala Query Results.....	804

Impala Fault Tolerance.....806

Impala Transparent Query Retries.....	806
Impala Node Blacklisting.....	807

Troubleshooting Impala..... 807

Troubleshooting Impala SQL Syntax Issues.....	807
Troubleshooting Crashes Caused by Memory Resource Limit.....	807
Troubleshooting I/O Capacity Problems.....	808
Impala Troubleshooting Quick Reference.....	808
Impala Web User Interface for Debugging.....	810
Configuring Debug Web UIs.....	811
Debug Web UI for impalad.....	811
Debug Web UI for statelord.....	814
Debug Web UI for catalogd.....	816
Breakpad Minidumps for Impala (Impala 2.6 or higher only).....	817
Enabling or Disabling Minidump Generation.....	817
Specifying the Location for Minidump Files.....	818
Controlling the Number of Minidump Files.....	818
Detecting Crash Events.....	818
Demonstration of Breakpad Feature.....	818

Ports Used by Impala.....820

Impala Reserved Words.....821

List of Reserved Words.....821

Impala Frequently Asked Questions..... 838**Impala Release Notes..... 838**

New Features in Apache Impala.....	838
New Features in Impala 4.0.....	838
New Features in Impala 3.4.....	838
New Features in Impala 3.3.....	840
New Features in Impala 3.2.....	843
New Features in Impala 3.1.....	844
New Features in Impala 3.0.....	844
New Features in Impala 2.12.....	844
New Features in Impala 2.11.....	844
New Features in Impala 2.10.....	844
New Features in Impala 2.9.....	844
New Features in Impala 2.8.....	845
New Features in Impala 2.7.....	847
New Features in Impala 2.6.....	847
New Features in Impala 2.5.....	849
New Features in Impala 2.4.....	852
New Features in Impala 2.3.....	852
New Features in Impala 2.8.....	854
New Features in Impala 2.1.....	856
New Features in Impala 2.0.....	856
New Features in Impala 1.4.....	858
New Features in Impala 1.3.2.....	859
New Features in Impala 1.3.1.....	860
New Features in Impala 1.3.....	860
New Features in Impala 1.2.4.....	861
New Features in Impala 1.2.3.....	861
New Features in Impala 1.2.2.....	861
New Features in Impala 1.2.1.....	862
New Features in Impala 1.2.0 (Beta).....	863
New Features in Impala 1.1.1.....	865
New Features in Impala 1.1.....	865
New Features in Impala 1.0.1.....	866
New Features in Impala 1.0.....	866
New Features in Version 0.7 of the Impala Beta Release.....	866
New Features in Version 0.6 of the Impala Beta Release.....	867
New Features in Version 0.5 of the Impala Beta Release.....	867
New Features in Version 0.4 of the Impala Beta Release.....	867
New Features in Version 0.3 of the Impala Beta Release.....	867
New Features in Version 0.2 of the Impala Beta Release.....	867
Incompatible Changes and Limitations in Apache Impala.....	867
Incompatible Changes Introduced in Impala 4.0.x.....	867
Incompatible Changes Introduced in Impala 3.4.x.....	868
Incompatible Changes Introduced in Impala 3.3.x.....	868
Incompatible Changes Introduced in Impala 3.2.x.....	868
Incompatible Changes Introduced in Impala 3.1.x.....	868
Incompatible Changes Introduced in Impala 3.0.x.....	868

Incompatible Changes Introduced in Impala 2.12.x.....	868
Incompatible Changes Introduced in Impala 2.11.x.....	868
Incompatible Changes Introduced in Impala 2.10.x.....	868
Incompatible Changes Introduced in Impala 2.9.x.....	869
Incompatible Changes Introduced in Impala 2.8.x.....	869
Incompatible Changes Introduced in Impala 2.7.x.....	869
Incompatible Changes Introduced in Impala 2.6.x.....	869
Incompatible Changes Introduced in Impala 2.5.x.....	870
Incompatible Changes Introduced in Impala 2.4.x.....	871
Incompatible Changes Introduced in Impala 2.3.x.....	871
Incompatible Changes Introduced in Impala 2.2.x.....	872
Incompatible Changes Introduced in Impala 2.1.x.....	872
Incompatible Changes Introduced in Impala 2.0.5.....	872
Incompatible Changes Introduced in Impala 2.0.4.....	872
Incompatible Changes Introduced in Impala 2.0.3.....	872
Incompatible Changes Introduced in Impala 2.0.2.....	872
Incompatible Changes Introduced in Impala 2.0.1.....	872
Incompatible Changes Introduced in Impala 2.0.0.....	873
Incompatible Changes Introduced in Impala 1.4.4.....	874
Incompatible Changes Introduced in Impala 1.4.3.....	874
Incompatible Changes Introduced in Impala 1.4.2.....	874
Incompatible Changes Introduced in Impala 1.4.1.....	874
Incompatible Changes Introduced in Impala 1.4.0.....	874
Incompatible Changes Introduced in Impala 1.3.3.....	875
Incompatible Changes Introduced in Impala 1.3.2.....	875
Incompatible Changes Introduced in Impala 1.3.1.....	875
Incompatible Changes Introduced in Impala 1.3.0.....	875
Incompatible Changes Introduced in Impala 1.2.4.....	876
Incompatible Changes Introduced in Impala 1.2.3.....	876
Incompatible Changes Introduced in Impala 1.2.2.....	876
Incompatible Changes Introduced in Impala 1.2.1.....	877
Incompatible Changes Introduced in Impala 1.2.0 (Beta).....	877
Incompatible Changes Introduced in Impala 1.1.1.....	877
Incompatible Change Introduced in Impala 1.1.....	878
Incompatible Changes Introduced in Impala 1.0.....	878
Known Issues and Workarounds in Impala.....	878
Impala Known Issues: Startup.....	878
Impala Known Issues: Performance.....	879
Impala Known Issues: JDBC and ODBC Drivers.....	879
Impala Known Issues: Security.....	879
Impala Known Issues: Resources.....	879
Impala Known Issues: Correctness.....	880
Impala Known Issues: Interoperability.....	881
Impala Known Issues: Limitations.....	882
Impala Known Issues: Miscellaneous.....	883
Impala Known Issues: Crashes and Hangs.....	883
Fixed Issues in Apache Impala.....	884
Issues Fixed in Impala 4.0.....	884
Issues Fixed in Impala 3.4.....	884
Issues Fixed in Impala 3.3.....	884
Issues Fixed in Impala 3.2.....	884
Issues Fixed in Impala 3.1.....	885
Issues Fixed in Impala 3.0.....	885
Issues Fixed in Impala 2.12.....	885
Issues Fixed in Impala 2.11.....	885
Issues Fixed in Impala 2.10.....	885

Issues Fixed in Impala 2.9.0.....	885
Issues Fixed in Impala 2.8.0.....	885
Issues Fixed in Impala 2.7.0.....	885
Issues Fixed in Impala 2.6.3.....	885
Issues Fixed in Impala 2.6.2.....	885
Issues Fixed in Impala 2.6.0.....	885
Issues Fixed in Impala 2.5.4.....	887
Issues Fixed in Impala 2.5.2.....	887
Issues Fixed in Impala 2.5.1.....	887
Issues Fixed in Impala 2.5.0.....	887
Issues Fixed in Impala 2.4.1.....	890
Issues Fixed in Impala 2.4.0.....	890
Issues Fixed in Impala 2.3.4.....	890
Issues Fixed in Impala 2.3.2.....	890
Issues Fixed in Impala 2.3.1.....	892
Issues Fixed in Impala 2.3.0.....	892
Issues Fixed in Impala 2.2.10.....	893
Issues Fixed in Impala 2.2.9.....	893
Issues Fixed in Impala 2.2.8.....	894
Issues Fixed in Impala 2.2.7.....	895
Issues Fixed in Impala Impala 2.2.5.....	896
Issues Fixed in Impala 2.2.3.....	897
Issues Fixed in Impala 2.2.1.....	898
Issues Fixed in Impala 2.2.0.....	898
Issues Fixed in Impala 2.1.10.....	900
Issues Fixed in Impala 2.1.7.....	900
Issues Fixed in Impala 2.1.6.....	900
Issues Fixed in Impala 2.1.5.....	901
Issues Fixed in Impala 2.1.4.....	901
Issues Fixed in Impala 2.1.3.....	902
Issues Fixed in Impala 2.1.2.....	903
Issues Fixed in Impala 2.1.1.....	903
Issues Fixed in Impala 2.1.0.....	904
Issues Fixed in Impala 2.0.5.....	904
Issues Fixed in Impala 2.0.4.....	904
Issues Fixed in Impala 2.0.3.....	905
Issues Fixed in Impala 2.0.2.....	905
Issues Fixed in Impala 2.0.1.....	906
Issues Fixed in Impala 2.0.0.....	906
Issues Fixed in Impala 1.4.4.....	908
Issues Fixed in Impala 1.4.3.....	908
Issues Fixed in Impala 1.4.2.....	908
Issues Fixed in Impala 1.4.1.....	908
Issues Fixed in Impala 1.4.0.....	909
Issues Fixed in Impala 1.3.3.....	910
Issues Fixed in Impala 1.3.2.....	910
Issues Fixed in Impala 1.3.1.....	911
Issues Fixed in Impala 1.3.0.....	912
Issues Fixed in the 1.2.4 Release.....	914
Issues Fixed in the 1.2.3 Release.....	915
Issues Fixed in the 1.2.2 Release.....	915
Issues Fixed in the 1.2.1 Release.....	916
Issues Fixed in the 1.2.0 Beta Release.....	917
Issues Fixed in the 1.1.1 Release.....	917
Issues Fixed in the 1.1.0 Release.....	918
Issues Fixed in the 1.0.1 Release.....	918

Issues Fixed in the 1.0 GA Release.....	920
Issues Fixed in Version 0.7 of the Beta Release.....	922
Issues Fixed in Version 0.6 of the Beta Release.....	923
Issues Fixed in Version 0.5 of the Beta Release.....	924
Issues Fixed in Version 0.4 of the Beta Release.....	924
Issues Fixed in Version 0.3 of the Beta Release.....	925
Issues Fixed in Version 0.2 of the Beta Release.....	925

Introducing Apache Impala

Impala provides fast, interactive SQL queries directly on your Apache Hadoop data stored in HDFS, HBase, or the Amazon Simple Storage Service (S3). In addition to using the same unified storage platform, Impala also uses the same metadata, SQL syntax (Hive SQL), ODBC driver, and user interface (Impala query UI in Hue) as Apache Hive. This provides a familiar and unified platform for real-time or batch-oriented queries.

Impala is an addition to tools available for querying big data. Impala does not replace the batch processing frameworks built on MapReduce such as Hive. Hive and other frameworks built on MapReduce are best suited for long running batch jobs, such as those involving batch processing of Extract, Transform, and Load (ETL) type jobs.

Note: Impala graduated from the Apache Incubator on November 15, 2017. In places where the documentation formerly referred to “Cloudera Impala”, now the official name is “Apache Impala”.

Impala Benefits

Impala provides:

- Familiar SQL interface that data scientists and analysts already know.
- Ability to query high volumes of data (“big data”) in Apache Hadoop.
- Distributed queries in a cluster environment, for convenient scaling and to make use of cost-effective commodity hardware.
- Ability to share data files between different components with no copy or export/import step; for example, to write with Pig, transform with Hive and query with Impala. Impala can read from and write to Hive tables, enabling simple data interchange using Impala for analytics on Hive-produced data.
- Single system for big data processing and analytics, so customers can avoid costly modeling and ETL just for analytics.

How Impala Works with Apache Hadoop

The Impala solution is composed of the following components:

- Clients - Entities including Hue, ODBC clients, JDBC clients, and the Impala Shell can all interact with Impala. These interfaces are typically used to issue queries or complete administrative tasks such as connecting to Impala.
- Hive Metastore - Stores information about the data available to Impala. For example, the metastore lets Impala know what databases are available and what the structure of those databases is. As you create, drop, and alter schema objects, load data into tables, and so on through Impala SQL statements, the relevant metadata changes are automatically broadcast to all Impala nodes by the dedicated catalog service introduced in Impala 1.2.
- Impala - This process, which runs on DataNodes, coordinates and executes queries. Each instance of Impala can receive, plan, and coordinate queries from Impala clients. Queries are distributed among Impala nodes, and these nodes then act as workers, executing parallel query fragments.
- HBase and HDFS - Storage for data to be queried.

Queries executed using Impala are handled as follows:

1. User applications send SQL queries to Impala through ODBC or JDBC, which provide standardized querying interfaces. The user application may connect to any `impalad` in the cluster. This `impalad` becomes the coordinator for the query.
2. Impala parses the query and analyzes it to determine what tasks need to be performed by `impalad` instances across the cluster. Execution is planned for optimal efficiency.
3. Services such as HDFS and HBase are accessed by local `impalad` instances to provide data.
4. Each `impalad` returns data to the coordinating `impalad`, which sends these results to the client.

Primary Impala Features

Impala provides support for:

- Most common SQL-92 features of Hive Query Language (HiveQL) including *SELECT*, *joins*, and *aggregate functions*.
- HDFS, HBase, and Amazon Simple Storage System (S3) storage, including:
 - *HDFS file formats*: delimited text files, Parquet, Avro, SequenceFile, and RCFile.
 - Compression codecs: Snappy, GZIP, Deflate, BZIP.
- Common data access interfaces including:
 - *JDBC driver*.
 - *ODBC driver*.
 - Hue Beeswax and the Impala Query UI.
- *impala-shell command-line interface*.
- *Kerberos authentication*.

Impala Concepts and Architecture

The following sections provide background information to help you become productive using Impala and its features. Where appropriate, the explanations include context to help understand how aspects of Impala relate to other technologies you might already be familiar with, such as relational database management systems and data warehouses, or other Hadoop components such as Hive, HDFS, and HBase.

Components of the Impala Server

The Impala server is a distributed, massively parallel processing (MPP) database engine. It consists of different daemon processes that run on specific hosts within your cluster.

The Impala Daemon

The core Impala component is the Impala daemon, physically represented by the `impalad` process. A few of the key functions that an Impala daemon performs are:

- Reads and writes to data files.
- Accepts queries transmitted from the `impala-shell` command, Hue, JDBC, or ODBC.
- Parallelizes the queries and distributes work across the cluster.
- Transmits intermediate query results back to the central coordinator.

Impala daemons can be deployed in one of the following ways:

- HDFS and Impala are co-located, and each Impala daemon runs on the same host as a DataNode.
- Impala is deployed separately in a compute cluster and reads remotely from HDFS, S3, ADLS, etc.

The Impala daemons are in constant communication with StateStore, to confirm which daemons are healthy and can accept new work.

They also receive broadcast messages from the `catalogd` daemon (introduced in Impala 1.2) whenever any Impala daemon in the cluster creates, alters, or drops any type of object, or when an `INSERT` or `LOAD DATA` statement is processed through Impala. This background communication minimizes the need for `REFRESH` or `INVALIDATE METADATA` statements that were needed to coordinate metadata across Impala daemons prior to Impala 1.2.

In Impala 2.9 and higher, you can control which hosts act as query coordinators and which act as query executors, to improve scalability for highly concurrent workloads on large clusters. See [How to Configure Impala with Dedicated Coordinators](#) on page 666 for details.

Note: Impala daemons should be deployed on nodes using the same Glibc version since different Glibc version supports different Unicode standard version and also ensure that the `en_US.UTF-8` locale is installed in the nodes. Not using the same Glibc version might result in inconsistent UTF-8 behavior when `UTF8_MODE` is set to true.

Related information: [Modifying Impala Startup Options](#) on page 32, [Starting Impala](#) on page 31, [Setting the Idle Query and Idle Session Timeouts for impalad](#) on page 66, [Ports Used by Impala](#) on page 820, [Using Impala through a Proxy for High Availability](#) on page 67

The Impala Statestore

The Impala component known as the StateStore checks on the health of all Impala daemons in a cluster, and continuously relays its findings to each of those daemons. It is physically represented by a daemon process named `statestored`. You only need such a process on one host in a cluster. If an Impala daemon goes offline due to hardware failure, network error, software issue, or other reason, the StateStore informs all the other Impala daemons so that future queries can avoid making requests to the unreachable Impala daemon.

Because the StateStore's purpose is to help when things go wrong and to broadcast metadata to coordinators, it is not always critical to the normal operation of an Impala cluster. If the StateStore is not running or becomes unreachable, the Impala daemons continue running and distributing work among themselves as usual when working with the data known to Impala. The cluster just becomes less robust if other Impala daemons fail, and metadata becomes less consistent as it changes while the StateStore is offline. When the StateStore comes back online, it re-establishes communication with the Impala daemons and resumes its monitoring and broadcasting functions.

If you issue a DDL statement while the StateStore is down, the queries that access the new object the DDL created will fail.

Most considerations for load balancing and high availability apply to the `impalad` daemon. The `statestored` and `catalogd` daemons do not have special requirements for high availability, because problems with those daemons do not result in data loss. If those daemons become unavailable due to an outage on a particular host, you can stop the Impala service, delete the **Impala StateStore** and **Impala Catalog Server** roles, add the roles on a different host, and restart the Impala service.

Related information:

[Scalability Considerations for the Impala Statestore](#) on page 658, [Modifying Impala Startup Options](#) on page 32, [Starting Impala](#) on page 31, [Increasing the Statestore Timeout](#) on page 66, [Ports Used by Impala](#) on page 820

The Impala Catalog Service

The Impala component known as the Catalog Service relays the metadata changes from Impala SQL statements to all the Impala daemons in a cluster. It is physically represented by a daemon process named `catalogd`. You only need such a process on one host in a cluster. Because the requests are passed through the StateStore daemon, it makes sense to run the `statestored` and `catalogd` services on the same host.

The catalog service avoids the need to issue `REFRESH` and `INVALIDATE METADATA` statements when the metadata changes are performed by statements issued through Impala. When you create a table, load data, and so on through Hive, you do need to issue `REFRESH` or `INVALIDATE METADATA` on an Impala daemon before executing a query there.

This feature touches a number of aspects of Impala:

- See [Installing Impala](#) on page 25, [Upgrading Impala](#) on page 28 and [Starting Impala](#) on page 31, for usage information for the `catalogd` daemon.
- The `REFRESH` and `INVALIDATE METADATA` statements are not needed when the `CREATE TABLE`, `INSERT`, or other table-changing or data-changing operation is performed through Impala. These statements are still needed if such operations are done through Hive or by manipulating data files directly in HDFS, but in those cases the statements only need to be issued on one Impala daemon rather than on all daemons. See [REFRESH Statement](#) on

page 312 and [INVALIDATE METADATA Statement](#) on page 307 for the latest usage information for those statements.

Use `##load_catalog_in_background` option to control when the metadata of a table is loaded.

- If set to `false`, the metadata of a table is loaded when it is referenced for the first time. This means that the first run of a particular query can be slower than subsequent runs. Starting in Impala 2.2, the default for `##load_catalog_in_background` is `false`.
- If set to `true`, the catalog service attempts to load metadata for a table even if no query needed that metadata. So metadata will possibly be already loaded when the first query that would need it is run. However, for the following reasons, we recommend not to set the option to `true`.
 - Background load can interfere with query-specific metadata loading. This can happen on startup or after invalidating metadata, with a duration depending on the amount of metadata, and can lead to a seemingly random long running queries that are difficult to diagnose.
 - Impala may load metadata for tables that are possibly never used, potentially increasing catalog size and consequently memory usage for both catalog service and Impala Daemon.

Most considerations for load balancing and high availability apply to the `impalad` daemon. The `statedored` and `catalogd` daemons do not have special requirements for high availability, because problems with those daemons do not result in data loss. If those daemons become unavailable due to an outage on a particular host, you can stop the Impala service, delete the **Impala StateStore** and **Impala Catalog Server** roles, add the roles on a different host, and restart the Impala service.

Note:

In Impala 1.2.4 and higher, you can specify a table name with `INVALIDATE METADATA` after the table is created in Hive, allowing you to make individual tables visible to Impala without doing a full reload of the catalog metadata. Impala 1.2.4 also includes other changes to make the metadata broadcast mechanism faster and more responsive, especially during Impala startup. See [New Features in Impala 1.2.4](#) on page 861 for details.

Related information: [Modifying Impala Startup Options](#) on page 32, [Starting Impala](#) on page 31, [Ports Used by Impala](#) on page 820

Developing Impala Applications

The core development language with Impala is SQL. You can also use Java or other languages to interact with Impala through the standard JDBC and ODBC interfaces used by many business intelligence tools. For specialized kinds of analysis, you can supplement the SQL built-in functions by writing [user-defined functions \(UDFs\)](#) in C++ or Java.

Overview of the Impala SQL Dialect

The Impala SQL dialect is highly compatible with the SQL syntax used in the Apache Hive component (HiveQL). As such, it is familiar to users who are already familiar with running SQL queries on the Hadoop infrastructure. Currently, Impala SQL supports a subset of HiveQL statements, data types, and built-in functions. Impala also includes additional built-in functions for common industry features, to simplify porting SQL from non-Hadoop systems.

For users coming to Impala from traditional database or data warehousing backgrounds, the following aspects of the SQL dialect might seem familiar:

- The [SELECT statement](#) includes familiar clauses such as `WHERE`, `GROUP BY`, `ORDER BY`, and `WITH`. You will find familiar notions such as [joins](#), [built-in functions](#) for processing strings, numbers, and dates, [aggregate functions](#), [subqueries](#), and [comparison operators](#) such as `IN ()` and `BETWEEN`. The `SELECT` statement is the place where SQL standards compliance is most important.
- From the data warehousing world, you will recognize the notion of [partitioned tables](#). One or more columns serve as partition keys, and the data is physically arranged so that queries that refer to the partition key columns in the `WHERE` clause can skip partitions that do not match the filter conditions. For example, if you have 10 years worth of data and use a clause such as `WHERE year = 2015`, `WHERE year > 2010`, or `WHERE year IN`

(2014, 2015), Impala skips all the data for non-matching years, greatly reducing the amount of I/O for the query.

- In Impala 1.2 and higher, [UDFs](#) let you perform custom comparisons and transformation logic during `SELECT` and `INSERT . . . SELECT` statements.

For users coming to Impala from traditional database or data warehousing backgrounds, the following aspects of the SQL dialect might require some learning and practice for you to become proficient in the Hadoop environment:

- Impala SQL is focused on queries and includes relatively little DML. There is no `UPDATE` or `DELETE` statement. Stale data is typically discarded (by `DROP TABLE` or `ALTER TABLE . . . DROP PARTITION` statements) or replaced (by `INSERT OVERWRITE` statements).
- All data creation is done by `INSERT` statements, which typically insert data in bulk by querying from other tables. There are two variations, `INSERT INTO` which appends to the existing data, and `INSERT OVERWRITE` which replaces the entire contents of a table or partition (similar to `TRUNCATE TABLE` followed by a new `INSERT`). Although there is an `INSERT . . . VALUES` syntax to create a small number of values in a single statement, it is far more efficient to use the `INSERT . . . SELECT` to copy and transform large amounts of data from one table to another in a single operation.
- You often construct Impala table definitions and data files in some other environment, and then attach Impala so that it can run real-time queries. The same data files and table metadata are shared with other components of the Hadoop ecosystem. In particular, Impala can access tables created by Hive or data inserted by Hive, and Hive can access tables and data produced by Impala. Many other Hadoop components can write files in formats such as Parquet and Avro, that can then be queried by Impala.
- Because Hadoop and Impala are focused on data warehouse-style operations on large data sets, Impala SQL includes some idioms that you might find in the import utilities for traditional database systems. For example, you can create a table that reads comma-separated or tab-separated text files, specifying the separator in the `CREATE TABLE` statement. You can create **external tables** that read existing data files but do not move or transform them.
- Because Impala reads large quantities of data that might not be perfectly tidy and predictable, it does not require length constraints on string data types. For example, you can define a database column as `STRING` with unlimited length, rather than `CHAR (1)` or `VARCHAR (64)`. (Although in Impala 2.0 and later, you can also use length-constrained `CHAR` and `VARCHAR` types.)

Related information: [Impala SQL Language Reference](#) on page 101, especially [Impala SQL Statements](#) on page 213 and [Impala Built-In Functions](#) on page 428

Overview of Impala Programming Interfaces

You can connect and submit requests to the Impala daemons through:

- The [impala-shell](#) interactive command interpreter.
- The [Hue](#) web-based user interface.
- [JDBC](#).
- [ODBC](#).

With these options, you can use Impala in heterogeneous environments, with JDBC or ODBC applications running on non-Linux platforms. You can also use Impala in combination with various Business Intelligence tools that use the JDBC and ODBC interfaces.

Each `impalad` daemon process, running on separate nodes in a cluster, listens to [several ports](#) for incoming requests. Requests from `impala-shell` and Hue are routed to the `impalad` daemons through the same port. The `impalad` daemons listen on separate ports for JDBC and ODBC requests.

How Impala Fits Into the Hadoop Ecosystem

Impala makes use of many familiar components within the Hadoop ecosystem. Impala can interchange data with other Hadoop components, as both a consumer and a producer, so it can fit in flexible ways into your ETL and ELT pipelines.

How Impala Works with Hive

A major Impala goal is to make SQL-on-Hadoop operations fast and efficient enough to appeal to new categories of users and open up Hadoop to new types of use cases. Where practical, it makes use of existing Apache Hive infrastructure that many Hadoop users already have in place to perform long-running, batch-oriented SQL queries.

In particular, Impala keeps its table definitions in a traditional MySQL or PostgreSQL database known as the **metastore**, the same database where Hive keeps this type of data. Thus, Impala can access tables defined or loaded by Hive, as long as all columns use Impala-supported data types, file formats, and compression codecs.

The initial focus on query features and performance means that Impala can read more types of data with the `SELECT` statement than it can write with the `INSERT` statement. To query data using the Avro, RCFile, or SequenceFile [file formats](#), you load the data using Hive.

The Impala query optimizer can also make use of [table statistics](#) and [column statistics](#). Originally, you gathered this information with the `ANALYZE TABLE` statement in Hive; in Impala 1.2.2 and higher, use the Impala [COMPUTE STATS](#) statement instead. `COMPUTE STATS` requires less setup, is more reliable, and does not require switching back and forth between `impala-shell` and the Hive shell.

Overview of Impala Metadata and the Metastore

As discussed in [How Impala Works with Hive](#) on page 21, Impala maintains information about table definitions in a central database known as the **metastore**. Impala also tracks other metadata for the low-level characteristics of data files:

- The physical locations of blocks within HDFS.

For tables with a large volume of data and/or many partitions, retrieving all the metadata for a table can be time-consuming, taking minutes in some cases. Thus, each Impala node caches all of this metadata to reuse for future queries against the same table.

If the table definition or the data in the table is updated, all other Impala daemons in the cluster must receive the latest metadata, replacing the obsolete cached metadata, before issuing a query against that table. In Impala 1.2 and higher, the metadata update is automatic, coordinated through the `catalogd` daemon, for all DDL and DML statements issued through Impala. See [The Impala Catalog Service](#) on page 18 for details.

For DDL and DML issued through Hive, or changes made manually to files in HDFS, you still use the `REFRESH` statement (when new data files are added to existing tables) or the `INVALIDATE METADATA` statement (for entirely new tables, or after dropping a table, performing an HDFS rebalance operation, or deleting data files). Issuing `INVALIDATE METADATA` by itself retrieves metadata for all the tables tracked by the metastore. If you know that only specific tables have been changed outside of Impala, you can issue `REFRESH table_name` for each affected table to only retrieve the latest metadata for those tables.

How Impala Uses HDFS

Impala uses the distributed filesystem HDFS as its primary data storage medium. Impala relies on the redundancy provided by HDFS to guard against hardware or network outages on individual nodes. Impala table data is physically represented as data files in HDFS, using familiar HDFS file formats and compression codecs. When data files are present in the directory for a new table, Impala reads them all, regardless of file name. New data is added in files with names controlled by Impala.

How Impala Uses HBase

HBase is an alternative to HDFS as a storage medium for Impala data. It is a database storage system built on top of HDFS, without built-in SQL support. Many Hadoop users already have it configured and store large (often sparse) data sets in it. By defining tables in Impala and mapping them to equivalent tables in HBase, you can query the contents of the HBase tables through Impala, and even perform join queries including both Impala and HBase tables. See [Using Impala to Query HBase Tables](#) on page 750 for details.

Planning for Impala Deployment

Before you set up Impala in production, do some planning to make sure that your hardware setup has sufficient capacity, that your cluster topology is optimal for Impala queries, and that your schema design and ETL processes follow the best practices for Impala.

Impala Requirements

To perform as expected, Impala depends on the availability of the software, hardware, and configurations described in the following sections.

Supported Operating Systems

Apache Impala runs on Linux systems only. See the `README.md` file for more information.

Hive Metastore and Related Configuration

Impala can interoperate with data stored in Hive, and uses the same infrastructure as Hive for tracking metadata about schema objects such as tables and columns. The following components are prerequisites for Impala:

- MySQL or PostgreSQL, to act as a metastore database for both Impala and Hive.

Always configure a **Hive metastore service** rather than connecting directly to the metastore database. The Hive metastore service is required to interoperate between different levels of metastore APIs if this is necessary for your environment, and using it avoids known issues with connecting directly to the metastore database.

See below for a summary of the metastore installation process.

- Hive (optional). Although only the Hive metastore database is required for Impala to function, you might install Hive on some client machines to create and load data into tables that use certain file formats. See [How Impala Works with Hadoop File Formats](#) on page 695 for details. Hive does not need to be installed on the same DataNodes as Impala; it just needs access to the same metastore database.

To install the metastore:

1. Install a MySQL or PostgreSQL database. Start the database if it is not started after installation.
2. Download the [MySQL connector](#) or the [PostgreSQL connector](#) and place it in the `/usr/share/java/` directory.
3. Use the appropriate command line tool for your database to create the metastore database.
4. Use the appropriate command line tool for your database to grant privileges for the metastore database to the `hive` user.
5. Modify `hive-site.xml` to include information matching your particular database: its URL, username, and password. You will copy the `hive-site.xml` file to the Impala Configuration Directory later in the Impala installation process.

Java Dependencies

Although Impala is primarily written in C++, it does use Java to communicate with various Hadoop components:

- The officially supported JVM for Impala is the Oracle JVM. Other JVMs might cause issues, typically resulting in a failure at `impalad` startup. In particular, the JamVM used by default on certain levels of Ubuntu systems can cause `impalad` to fail to start.
- Internally, the `impalad` daemon relies on the `JAVA_HOME` environment variable to locate the system Java libraries. Make sure the `impalad` service is not run from an environment with an incorrect setting for this variable.

- All Java dependencies are packaged in the `impala-dependencies.jar` file, which is located at `/usr/lib/impala/lib/`. These map to everything that is built under `fe/target/dependency`.

Networking Configuration Requirements

As part of ensuring best performance, Impala attempts to complete tasks on local data, as opposed to using network connections to work with remote data. To support this goal, Impala matches the **hostname** provided to each Impala daemon with the **IP address** of each DataNode by resolving the hostname flag to an IP address. For Impala to work with local data, use a single IP interface for the DataNode and the Impala daemon on each machine. Ensure that the Impala daemon's hostname flag resolves to the IP address of the DataNode. For single-homed machines, this is usually automatic, but for multi-homed machines, ensure that the Impala daemon's hostname resolves to the correct interface. Impala tries to detect the correct hostname at start-up, and prints the derived hostname at the start of the log in a message of the form:

```
Using hostname: impala-daemon-1.example.com
```

In the majority of cases, this automatic detection works correctly. If you need to explicitly set the hostname, do so by setting the `--hostname` flag.

Hardware Requirements

The memory allocation should be consistent across Impala executor nodes. A single Impala executor with a lower memory limit than the rest can easily become a bottleneck and lead to suboptimal performance.

This guideline does not apply to coordinator-only nodes.

Hardware Requirements for Optimal Join Performance

During join operations, portions of data from each joined table are loaded into memory. Data sets can be very large, so ensure your hardware has sufficient memory to accommodate the joins you anticipate completing.

While requirements vary according to data set size, the following is generally recommended:

- CPU

Impala version 2.2 and higher uses the SSSE3 instruction set, which is included in newer processors.

Note: This required level of processor is the same as in Impala version 1.x. The Impala 2.0 and 2.1 releases had a stricter requirement for the SSE4.1 instruction set, which has now been relaxed.

- Memory

128 GB or more recommended, ideally 256 GB or more. If the intermediate results during query processing on a particular node exceed the amount of memory available to Impala on that node, the query writes temporary work data to disk, which can lead to long query times. Note that because the work is parallelized, and intermediate results for aggregate queries are typically smaller than the original data, Impala can query and join tables that are much larger than the memory available on an individual node.

- JVM Heap Size for Catalog Server

4 GB or more recommended, ideally 8 GB or more, to accommodate the maximum numbers of tables, partitions, and data files you are planning to use with Impala.

- Storage

DataNodes with 12 or more disks each. I/O speeds are often the limiting factor for disk performance with Impala. Ensure that you have sufficient disk space to store the data Impala will be querying.

User Account Requirements

Impala creates and uses a user and group named `impala`. Do not delete this account or group and do not modify the account's or group's permissions and rights. Ensure no existing systems obstruct the functioning of these accounts and groups. For example, if you have scripts that delete user accounts not in a white-list, add these accounts to the list of permitted accounts.

For correct file deletion during `DROP TABLE` operations, Impala must be able to move files to the HDFS trashcan. You might need to create an HDFS directory `/user/impala`, writeable by the `impala` user, so that the trashcan can be created. Otherwise, data files might remain behind after a `DROP TABLE` statement.

Impala should not run as root. Best Impala performance is achieved using direct reads, but root is not permitted to use direct reads. Therefore, running Impala as root negatively affects performance.

By default, any user can connect to Impala and access all the associated databases and tables. You can enable authorization and authentication based on the Linux OS user who connects to the Impala server, and the associated groups for that user. [Impala Security](#) on page 78 for details. These security features do not change the underlying file permission requirements; the `impala` user still needs to be able to access the data files.

Guidelines for Designing Impala Schemas

The guidelines in this topic help you to construct an optimized and scalable schema, one that integrates well with your existing data management processes. Use these guidelines as a checklist when doing any proof-of-concept work, porting exercise, or before deploying to production.

If you are adapting an existing database or Hive schema for use with Impala, read the guidelines in this section and then see [Porting SQL from Other Database Systems to Impala](#) on page 608 for specific porting and compatibility tips.

Prefer binary file formats over text-based formats.

To save space and improve memory usage and query performance, use binary file formats for any large or intensively queried tables. Parquet file format is the most efficient for data warehouse-style analytic queries. Avro is the other binary file format that Impala supports, that you might already have as part of a Hadoop ETL pipeline.

Although Impala can create and query tables with the RCFile and SequenceFile file formats, such tables are relatively bulky due to the text-based nature of those formats, and are not optimized for data warehouse-style queries due to their row-oriented layout. Impala does not support `INSERT` operations for tables with these file formats.

Guidelines:

- For an efficient and scalable format for large, performance-critical tables, use the Parquet file format.
- To deliver intermediate data during the ETL process, in a format that can also be used by other Hadoop components, Avro is a reasonable choice.
- For convenient import of raw data, use a text table instead of RCFile or SequenceFile, and convert to Parquet in a later stage of the ETL process.

Use Snappy compression where practical.

Snappy compression involves low CPU overhead to decompress, while still providing substantial space savings. In cases where you have a choice of compression codecs, such as with the Parquet and Avro file formats, use Snappy compression unless you find a compelling reason to use a different codec.

Prefer numeric types over strings.

If you have numeric values that you could treat as either strings or numbers (such as `YEAR`, `MONTH`, and `DAY` for partition key columns), define them as the smallest applicable integer types. For example, `YEAR` can be `SMALLINT`, `MONTH` and `DAY` can be `TINYINT`. Although you might not see any difference in the way partitioned tables or text files are laid out on disk, using numeric types will save space in binary formats such as Parquet, and in memory when doing queries, particularly resource-intensive queries such as joins.

Partition, but do not over-partition.

Partitioning is an important aspect of performance tuning for Impala. Follow the procedures in [Partitioning for Impala Tables](#) on page 685 to set up partitioning for your biggest, most intensively queried tables.

If you are moving to Impala from a traditional database system, or just getting started in the Big Data field, you might not have enough data volume to take advantage of Impala parallel queries with your existing partitioning scheme. For example, if you have only a few tens of megabytes of data per day, partitioning by YEAR, MONTH, and DAY columns might be too granular. Most of your cluster might be sitting idle during queries that target a single day, or each node might have very little work to do. Consider reducing the number of partition key columns so that each partition directory contains several gigabytes worth of data.

For example, consider a Parquet table where each data file is 1 HDFS block, with a maximum block size of 1 GB. (In Impala 2.0 and later, the default Parquet block size is reduced to 256 MB. For this exercise, let's assume you have bumped the size back up to 1 GB by setting the query option `PARQUET_FILE_SIZE=1g`.) If you have a 10-node cluster, you need 10 data files (up to 10 GB) to give each node some work to do for a query. But each core on each machine can process a separate data block in parallel. With 16-core machines on a 10-node cluster, a query could process up to 160 GB fully in parallel. If there are only a few data files per partition, not only are most cluster nodes sitting idle during queries, so are most cores on those machines.

You can reduce the Parquet block size to as low as 128 MB or 64 MB to increase the number of files per partition and improve parallelism. But also consider reducing the level of partitioning so that analytic queries have enough data to work with.

Always compute stats after loading data.

Impala makes extensive use of statistics about data in the overall table and in each column, to help plan resource-intensive operations such as join queries and inserting into partitioned Parquet tables. Because this information is only available after data is loaded, run the `COMPUTE STATS` statement on a table after loading or replacing data in a table or partition.

Having accurate statistics can make the difference between a successful operation, or one that fails due to an out-of-memory error or a timeout. When you encounter performance or capacity issues, always use the `SHOW STATS` statement to check if the statistics are present and up-to-date for all tables in the query.

When doing a join query, Impala consults the statistics for each joined table to determine their relative sizes and to estimate the number of rows produced in each join stage. When doing an `INSERT` into a Parquet table, Impala consults the statistics for the source table to determine how to distribute the work of constructing the data files for each partition.

See [COMPUTE STATS Statement](#) on page 232 for the syntax of the `COMPUTE STATS` statement, and [Table and Column Statistics](#) on page 625 for all the performance considerations for table and column statistics.

Verify sensible execution plans with EXPLAIN and SUMMARY.

Before executing a resource-intensive query, use the `EXPLAIN` statement to get an overview of how Impala intends to parallelize the query and distribute the work. If you see that the query plan is inefficient, you can take tuning steps such as changing file formats, using partitioned tables, running the `COMPUTE STATS` statement, or adding query hints. For information about all of these techniques, see [Tuning Impala for Performance](#) on page 614.

After you run a query, you can see performance-related information about how it actually ran by issuing the `SUMMARY` command in `impala-shell`. Prior to Impala 1.4, you would use the `PROFILE` command, but its highly technical output was only useful for the most experienced users. `SUMMARY`, new in Impala 1.4, summarizes the most useful information for all stages of execution, for all nodes rather than splitting out figures for each node.

Installing Impala

Impala is an open-source analytic database for Apache Hadoop that returns rapid responses to queries.

Follow these steps to set up Impala on a cluster by building from source:

- Download the latest release. See [the Impala downloads page](#) for the link to the latest release.
- Check the `README.md` file for a pointer to the build instructions.

- Please check the MD5 and SHA1 and GPG signature, the latter by using the code signing keys of the release managers.
- Developers interested in working on Impala can clone the Impala source repository:

```
git clone https://gitbox.apache.org/repos/asf/impala.git
```

What is Included in an Impala Installation

Impala is made up of a set of components that can be installed on multiple nodes throughout your cluster. The key installation step for performance is to install the `impalad` daemon (which does most of the query processing work) on *all* DataNodes in the cluster.

Impala primarily consists of these executables, which should be available after you build from source:

- `impalad` - The Impala daemon. Plans and executes queries against HDFS, HBase, and Amazon S3 data. [Run one impalad process](#) on each node in the cluster that has a DataNode.
- `statestored` - Name service that tracks location and status of all `impalad` instances in the cluster. [Run one instance of this daemon](#) on a node in your cluster. Most production deployments run this daemon on the namenode.
- `catalogd` - Metadata coordination service that broadcasts changes from Impala DDL and DML statements to all affected Impala nodes, so that new tables, newly loaded data, and so on are immediately visible to queries submitted through any Impala node. (Prior to Impala 1.2, you had to run the `REFRESH` or `INVALIDATE METADATA` statement on each node to synchronize changed metadata. Now those statements are only required if you perform the DDL or DML through an external mechanism such as Hive or by uploading data to the Amazon S3 filesystem.) [Run one instance of this daemon](#) on a node in your cluster, preferably on the same host as the `statestored` daemon.
- `impala-shell` - [Command-line interface](#) for issuing queries to the Impala daemon. You install this on one or more hosts anywhere on your network, not necessarily DataNodes or even within the same cluster as Impala. It can connect remotely to any instance of the Impala daemon.

Before starting working with Impala, ensure that you have all necessary prerequisites. See [Impala Requirements](#) on page 22 for details.

Managing Impala

This section explains how to configure Impala to accept connections from applications that use popular programming APIs:

- [Post-Installation Configuration for Impala](#) on page 27
- [Configuring Impala to Work with ODBC](#) on page 801
- [Configuring Impala to Work with JDBC](#) on page 801

This type of configuration is especially useful when using Impala in combination with Business Intelligence tools, which use these standard interfaces to query different kinds of database and Big Data systems.

You can also configure these other aspects of Impala:

- [Impala Security](#) on page 78
- [Modifying Impala Startup Options](#) on page 32

Post-Installation Configuration for Impala

This section describes the mandatory and recommended configuration settings for Impala. If Impala is installed using cluster management software, some of these configurations might be completed automatically; you must still configure short-circuit reads manually. If you want to customize your environment, consider making the changes described in this topic.

- You must enable short-circuit reads, whether or not Impala was installed with cluster management software. This setting goes in the Impala configuration settings, not the Hadoop-wide settings.
- You must enable block location tracking, and you can optionally enable native checksumming for optimal performance.

Mandatory: Short-Circuit Reads

Enabling short-circuit reads allows Impala to read local data directly from the file system. This removes the need to communicate through the DataNodes, improving performance. This setting also minimizes the number of additional copies of data. Short-circuit reads requires `libhadoop.so` (the Hadoop Native Library) to be accessible to both the server and the client. `libhadoop.so` is not available if you have installed from a tarball. You must install from an `.rpm`, `.deb`, or parcel to use short-circuit local reads.

To configure DataNodes for short-circuit reads:

1. Copy the client `core-site.xml` and `hdfs-site.xml` configuration files from the Hadoop configuration directory to the Impala configuration directory. The default Impala configuration location is `/etc/impala/conf`.
2. On all Impala nodes, configure the following properties in Impala's copy of `hdfs-site.xml` as shown:

```
<property>
  <name>dfs.client.read.shortcircuit</name>
  <value>true</value>
</property>

<property>
  <name>dfs.domain.socket.path</name>
  <value>/var/run/hdfs-sockets/dn</value>
</property>

<property>
  <name>dfs.client.file-block-storage-locations.timeout.millis</name>
  <value>10000</value>
</property>
```

3. If `/var/run/hadoop-hdfs/` is group-writable, make sure its group is `root`.

Note: If you are also going to enable block location tracking, you can skip copying configuration files and restarting DataNodes and go straight to [Optional: Block Location Tracking](#). Configuring short-circuit reads and block location tracking require the same process of copying files and restarting services, so you can complete that process once when you have completed all configuration changes. Whether you copy files and restart services now or during configuring block location tracking, short-circuit reads are not enabled until you complete those final steps.

4. After applying these changes, restart all DataNodes.

Mandatory: Block Location Tracking

Enabling block location metadata allows Impala to know which disk data blocks are located on, allowing better utilization of the underlying disks. Impala will not start unless this setting is enabled.

To enable block location tracking:

1. For each DataNode, adding the following to the `hdfs-site.xml` file:

```
<property>
  <name>dfs.datanode.hdfs-blocks-metadata.enabled</name>
  <value>true</value>
</property>
```

2. Copy the client `core-site.xml` and `hdfs-site.xml` configuration files from the Hadoop configuration directory to the Impala configuration directory. The default Impala configuration location is `/etc/impala/conf`.
3. After applying these changes, restart all DataNodes.

Optional: Native Checksumming

Enabling native checksumming causes Impala to use an optimized native library for computing checksums, if that library is available.

To enable native checksumming:

If you installed from packages, the native checksumming library is installed and setup correctly. In such a case, no additional steps are required. Conversely, if you installed by other means, such as with tarballs, native checksumming may not be available due to missing shared objects. Finding the message "Unable to load native-hadoop library for your platform... using builtin-java classes where applicable" in the Impala logs indicates native checksumming may be unavailable. To enable native checksumming, you must build and install `libhadoop.so` (the Hadoop Native Library).

Upgrading Impala

Upgrading Impala involves building or acquiring new Impala-related binaries, and then restarting Impala services.

Upgrading Impala

- Shut down all Impala-related daemons on all relevant hosts in the cluster:

1. Stop `impalad` on each Impala node in your cluster:

```
$ sudo service impala-server stop
```

2. Stop any instances of the state store in your cluster:

```
$ sudo service impala-state-store stop
```

3. Stop any instances of the catalog service in your cluster:

```
$ sudo service impala-catalog stop
```

- Follow the build procedure in the `README.md` file to produce new Impala binaries.
- Replace the binaries for all Impala-related daemons on all relevant hosts in the cluster.
- Check if there are new recommended or required configuration settings to put into place in the configuration files, typically under `/etc/impala/conf`. See [Post-Installation Configuration for Impala](#) on page 27 for settings related to performance and scalability.
- Restart all Impala-related daemons on all relevant hosts in the cluster:
 1. Restart the Impala state store service on the desired nodes in your cluster. Expect to see a process named `statestored` if the service started successfully.

```
$ sudo service impala-state-store start
```

```
$ ps ax | grep [s]tatestored
6819 ?      Sl      0:07 /usr/lib/impala/sbin/statestored -log_dir=/
var/log/impala -state_store_port=24000
```

Restart the state store service *before* the Impala server service to avoid “Not connected” errors when you run `impala-shell`.

2. Restart the Impala catalog service on whichever host it runs on in your cluster. Expect to see a process named `catalogd` if the service started successfully.

```
$ sudo service impala-catalog restart
$ ps ax | grep [c]atalogd
6068 ?      Sl      4:06 /usr/lib/impala/sbin/catalogd
```

3. Restart the Impala daemon service on each node in your cluster. Expect to see a process named `impalad` if the service started successfully.

```
$ sudo service impala-server start
$ ps ax | grep [i]mpalad
7936 ?      Sl      0:12 /usr/lib/impala/sbin/impalad -log_dir=/var/
log/impala -state_store_port=24000
-state_store_host=127.0.0.1 -be_port=22000
```

Note:

If the services did not start successfully (even though the `sudo service` command might display [OK]), check for errors in the Impala log file, typically in `/var/log/impala`.

Impala Upgrade Considerations

Grant REFRESH Privilege to Impala Roles with SELECT or INSERT Privilege when Upgrading to Impala 3.0

To use the fine grained privileges feature in Impala 3.0, if a role has the `SELECT` or `INSERT` privilege on an object in Impala before upgrading to Impala 3.0, grant that role the `REFRESH` privilege after the upgrade.

List of Reserved Words Updated in Impala 3.0

The list of *reserved words* in Impala was updated in Impala 3.0. If you need to use a reserved word as an identifier, e.g. a table name, enclose the word in back-ticks.

If you need to use the reserved words from previous versions of Impala, set the `impalad` and `catalogd` startup flag.

```
##reserved_words_version=2.11.0
```

Note that this startup option will be deprecated in a future release.

Decimal V2 Used by Default in Impala 3.0

In Impala, two different implementations of `DECIMAL` types are supported. Starting in Impala 3.0, `DECIMAL V2` is used by default. See *DECIMAL Type* for detail information.

If you need to continue using the first version of the `DECIMAL` type for the backward compatibility of your queries, set the `DECIMAL_V2` query option to `FALSE`:

```
SET DECIMAL_V2=FALSE;
```

Behavior of Column Aliases Changed in Impala 3.0

To conform to the SQL standard, Impala no longer performs alias substitution in the subexpressions of `GROUP BY`, `HAVING`, and `ORDER BY`. See [Overview of Impala Aliases](#) for examples of supported and unsupported aliases syntax.

Default PARQUET_ARRAY_RESOLUTION Changed in Impala 3.0

The default value for the `PARQUET_ARRAY_RESOLUTION` was changed to `THREE_LEVEL` in Impala 3.0, to match the Parquet standard 3-level encoding.

See [PARQUET_ARRAY_RESOLUTION Query Option \(Impala 2.9 or higher only\)](#) for the information about the query option.

Enable Clustering Hint for Inserts

In Impala 3.0, the `clustered` hint is enabled by default. The hint adds a local sort by the partitioning columns to a query plan.

The `clustered` hint is only effective for HDFS and Kudu tables.

As in previous versions, the `noclustered` hint prevents clustering. If a table has ordering columns defined, the `noclustered` hint is ignored with a warning.

Deprecated Query Options Removed in Impala 3.0

The following query options have been deprecated for several releases and removed:

- `DEFAULT_ORDER_BY_LIMIT`
- `ABORT_ON_DEFAULT_LIMIT_EXCEEDED`
- `V_CPU_CORES`
- `RESERVATION_REQUEST_TIMEOUT`
- `RM_INITIAL_MEM`
- `SCAN_NODE_CODEGEN_THRESHOLD`
- `MAX_IO_BUFFERS`
- `RM_INITIAL_MEM`
- `DISABLE_CACHED_READS`

Fine-grained Privileges Added in Impala 3.0

Starting in Impala 3.0, finer grained privileges are enforced, such as the `REFRESH`, `CREATE`, `DROP`, and `ALTER` privileges. In particular, running `REFRESH` or `INVALIDATE METADATA` now requires the new `REFRESH` privilege. Users who did not previously have the `ALL` privilege will no longer be able to run `REFRESH` or `INVALIDATE METADATA` after an upgrade. Those users need to have the `REFRESH` or `ALL` privilege granted to run `REFRESH` or `INVALIDATE METADATA`.

See [GRANT Statement \(Impala 2.0 or higher only\)](#) for the new privileges, the scope, and other information about the new privileges.

refresh_after_connect Impala Shell Option Removed in Impala 3.0

The deprecated `##refresh_after_connect` option was removed from Impala Shell in Impala 3.0

Return Type Changed for EXTRACT and DATE_PART Functions in Impala 3.0

The following changes were made to the `EXTRACT` and `DATE_PART` functions:

- The output type of the `EXTRACT` and `DATE_PART` functions was changed to `BIGINT`.

- Extracting the millisecond part from a `TIMESTAMP` returns the seconds component and the milliseconds component. For example, `EXTRACT (CAST('2006-05-12 18:27:28.123456789' AS TIMESTAMP), 'MILLISECOND')` will return 28123.

Port Change for SHUTDOWN Command

If you used the `SHUTDOWN` command in Impala 3.1, and specified a port explicitly, change the port number parameter, in Impala 3.2, to use the `KRPC` port.

Change in Client Connection Timeout

The default behavior of client connection timeout changed.

In Impala 3.2 and lower, client waited indefinitely to open the new session if the maximum number of threads specified by `--fe_service_threads` has been allocated.

In Impala 3.3 and higher, a new startup flag, `--accepted_client_cnxn_timeout`, was added to control how the server should treat new connection requests if we have run out of the configured number of server threads.

If `--accepted_client_cnxn_timeout > 0`, new connection requests are rejected after the specified timeout.

If `--accepted_client_cnxn_timeout=0`, clients waits indefinitely to connect to Impala. You can use this setting to restore the pre-Impala 3.3 behavior.

The default timeout is 5 minutes.

Default Setting Changes

Release Changed	Setting	Default Value
Impala 2.12	<code>##compact_catalog_topicimpalac</code> flag	<code>1 hour</code>
Impala 2.12	<code>##max_cached_file_handlesimpalad</code> flag	<code>20000</code>
Impala 3.0	<code>PARQUET_ARRAY_RESOLUTION</code> query option	<code>THREE_LEVEL</code>
Impala 3.0	<code>DECIMAL_V2</code>	<code>TRUE</code>

Starting Impala

To activate Impala if it is installed but not yet started:

1. Set any necessary configuration options for the Impala services. See [Modifying Impala Startup Options](#) on page 32 for details.
2. Start one instance of the Impala statestore. The statestore helps Impala to distribute work efficiently, and to continue running in the event of availability problems for other Impala nodes. If the statestore becomes unavailable, Impala continues to function.
3. Start one instance of the Impala catalog service.
4. Start the main Impala daemon services.

Once Impala is running, you can conduct interactive experiments using the instructions in [Impala Tutorials](#) on page 35 and try [Using the Impala Shell \(impala-shell Command\)](#) on page 790.

Starting Impala from the Command Line

To start the Impala state store and Impala from the command line or a script, you can either use the `service` command or you can start the daemons directly through the `impalad`, `statestore`, and `catalogd` executables.

Start the Impala statestore and then start `impalad` instances. You can modify the values the service initialization scripts use when starting the statestore and Impala by editing `/etc/default/impala`.

Start the statestore service using a command similar to the following:

```
$ sudo service impala-state-store start
```

Start the catalog service using a command similar to the following:

```
$ sudo service impala-catalog start
```

Start the Impala daemon services using a command similar to the following:

```
$ sudo service impala-server start
```

Note:

In Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to Impala 2.5 the requirement to reload functions after a restart applied to both C++ and Java functions.

If any of the services fail to start, review:

- [Reviewing Impala Logs](#) on page 786
- [Troubleshooting Impala](#) on page 807

Modifying Impala Startup Options

The configuration options for the Impala daemons let you choose which hosts and ports to use for the services that run on a single host, specify directories for logging, control resource usage and security, and specify other aspects of the Impala software.

Configuring Impala Startup Options through the Command Line

The Impala server, `statestore`, and `catalog` services start up using values provided in a defaults file, `/etc/default/impala`.

This file includes information about many resources used by Impala. Most of the defaults included in this file should be effective in most cases. For example, typically you would not change the definition of the `CLASSPATH` variable, but you would always set the address used by the `statestore` server. Some of the content you might modify includes:

```
IMPALA_STATE_STORE_HOST=127.0.0.1
IMPALA_STATE_STORE_PORT=24000
IMPALA_BACKEND_PORT=22000
IMPALA_LOG_DIR=/var/log/impala
IMPALA_CATALOG_SERVICE_HOST=...
IMPALA_STATE_STORE_HOST=...
```



```
export IMPALA_STATE_STORE_ARGS=${IMPALA_STATE_STORE_ARGS:- \
  -log_dir=${IMPALA_LOG_DIR} -state_store_port=${IMPALA_STATE_STORE_PORT}}
IMPALA_SERVER_ARGS=" \
  -log_dir=${IMPALA_LOG_DIR} \
  -catalog_service_host=${IMPALA_CATALOG_SERVICE_HOST} \
  -state_store_port=${IMPALA_STATE_STORE_PORT} \
  -state_store_host=${IMPALA_STATE_STORE_HOST} \
  -be_port=${IMPALA_BACKEND_PORT}"
export ENABLE_CORE_DUMPS=${ENABLE_COREDUMPS:-false}
```

To use alternate values, edit the defaults file, then restart all the Impala-related services so that the changes take effect. Restart the Impala server using the following commands:

```
$ sudo service impala-server restart
Stopping Impala Server:           [ OK ]
Starting Impala Server:           [ OK ]
```

Restart the Impala StateStore using the following commands:

```
$ sudo service impala-state-store restart
Stopping Impala State Store Server: [ OK ]
Starting Impala State Store Server: [ OK ]
```

Restart the Impala Catalog Service using the following commands:

```
$ sudo service impala-catalog restart
Stopping Impala Catalog Server:    [ OK ]
Starting Impala Catalog Server:    [ OK ]
```

Some common settings to change include:

- StateStore address. Where practical, put the `statestore` on a separate host not running the `impalad` daemon. In that recommended configuration, the `impalad` daemon cannot refer to the `statestore` server using the loopback address. If the `statestore` is hosted on a machine with an IP address of 192.168.0.27, change:

```
IMPALA_STATE_STORE_HOST=127.0.0.1
```

to:

```
IMPALA_STATE_STORE_HOST=192.168.0.27
```

- Catalog server address (including both the hostname and the port number). Update the value of the `IMPALA_CATALOG_SERVICE_HOST` variable. Where practical, run the catalog server on the same host as the `statestore`. In that recommended configuration, the `impalad` daemon cannot refer to the catalog server using the loopback address. If the catalog service is hosted on a machine with an IP address of 192.168.0.27, add the following line:

```
IMPALA_CATALOG_SERVICE_HOST=192.168.0.27:26000
```

The `/etc/default/impala` defaults file currently does not define an `IMPALA_CATALOG_ARGS` environment variable, but if you add one it will be recognized by the service startup/shutdown script. Add a definition for this variable to `/etc/default/impala` and add the option `##catalog_service_host=hostname`. If the port is different than the default 26000, also add the option `##catalog_service_port=port`.

- Memory limits. You can limit the amount of memory available to Impala. For example, to allow Impala to use no more than 70% of system memory, change:

```
export IMPALA_SERVER_ARGS=${IMPALA_SERVER_ARGS:- \
  -log_dir=${IMPALA_LOG_DIR} \
  -state_store_port=${IMPALA_STATE_STORE_PORT} \
  -state_store_host=${IMPALA_STATE_STORE_HOST} \
  -be_port=${IMPALA_BACKEND_PORT}}
```

to:

```
export IMPALA_SERVER_ARGS=${IMPALA_SERVER_ARGS:- \
  -log_dir=${IMPALA_LOG_DIR} -state_store_port=
${IMPALA_STATE_STORE_PORT} \
  -state_store_host=${IMPALA_STATE_STORE_HOST} \
  -be_port=${IMPALA_BACKEND_PORT} -mem_limit=70%}
```

You can specify the memory limit using absolute notation such as 500m or 2G, or as a percentage of physical memory such as 60%.

Note: Queries that exceed the specified memory limit are aborted. Percentage limits are based on the physical memory of the machine and do not consider cgroups.

- Core dump enablement. To enable core dumps, change:

```
export ENABLE_CORE_DUMPS=${ENABLE_COREDUMPS:-false}
```

to:

```
export ENABLE_CORE_DUMPS=${ENABLE_COREDUMPS:-true}
```

Note:

- The location of core dump files may vary according to your operating system configuration.
- Other security settings may prevent Impala from writing core dumps even when this option is enabled.
- Authorization. Specify the `##server_name` option as part of the `IMPALA_SERVER_ARGS` and `IMPALA_CATALOG_ARGS` settings to enable the core Impala support for authorization. See [#unique_92](#) for details.
- Auditing for successful or blocked Impala queries, another aspect of security. Specify the `##audit_event_log_dir=directory_path` option and optionally the `##max_audit_event_log_file_size=number_of_queries` and `##abort_on_failed_audit_event` options as part of the `IMPALA_SERVER_ARGS` settings, for each Impala node, to enable and customize auditing. See [Auditing Impala Operations](#) on page 99 for details.
- Password protection for the Impala web UI, which listens on port 25000 by default. This feature involves adding some or all of the `##webserver_password_file`, `##webserver_authentication_domain`, and `##webserver_certificate_file` options to the `IMPALA_SERVER_ARGS` and `IMPALA_STATE_STORE_ARGS` settings. See [Security Guidelines for Impala](#) on page 79 for details.
- Another setting you might add to `IMPALA_SERVER_ARGS` is a comma-separated list of query options and values:

```
##default_query_options='option=value,option=value,...'
```

These options control the behavior of queries performed by this `impalad` instance. The option values you specify here override the default values for [Impala query options](#), as shown by the `SET` statement in `impala-shell`.

- During troubleshooting, the appropriate support channel might direct you to change other values, particularly for `IMPALA_SERVER_ARGS`, to work around issues or gather debugging information.

Note:

These startup options for the `impalad` daemon are different from the command-line options for the `impala-shell` command. For the `impala-shell` options, see [impala-shell Configuration Options](#) on page 791.

Checking the Values of Impala Configuration Options

You can check the current runtime value of all these settings through the Impala web interface, available by default at `http://impala_hostname:25000/varz` for the `impalad` daemon, `http://impala_hostname:25010/varz` for the `statestored` daemon, or `http://impala_hostname:25020/varz` for the `catalogd` daemon.

Startup Options for catalogd Daemon

The `catalogd` daemon implements the Impala Catalog service, which broadcasts metadata changes to all the Impala nodes when Impala creates a table, inserts data, or performs other kinds of DDL and DML operations.

Use `##load_catalog_in_background` option to control when the metadata of a table is loaded.

- If set to `false`, the metadata of a table is loaded when it is referenced for the first time. This means that the first run of a particular query can be slower than subsequent runs. Starting in Impala 2.2, the default for `##load_catalog_in_background` is `false`.
- If set to `true`, the catalog service attempts to load metadata for a table even if no query needed that metadata. So metadata will possibly be already loaded when the first query that would need it is run. However, for the following reasons, we recommend not to set the option to `true`.
 - Background load can interfere with query-specific metadata loading. This can happen on startup or after invalidating metadata, with a duration depending on the amount of metadata, and can lead to a seemingly random long running queries that are difficult to diagnose.
 - Impala may load metadata for tables that are possibly never used, potentially increasing catalog size and consequently memory usage for both catalog service and Impala Daemon.

Impala Tutorials

This section includes tutorial scenarios that demonstrate how to begin using Impala once the software is installed. It focuses on techniques for loading data, because once you have some data in tables and can query that data, you can quickly progress to more advanced Impala features.

Note:

Where practical, the tutorials take you from “ground zero” to having the desired Impala tables and data. In some cases, you might need to download additional files from outside sources, set up additional software components, modify commands or scripts to fit your own configuration, or substitute your own sample data.

Before trying these tutorial lessons, install Impala using one of these procedures:

- If you already have some Apache Hadoop environment set up and just need to add Impala to it, follow the installation process described in [Installing Impala](#) on page 25. Make sure to also install the Hive metastore service if you do not already have Hive configured.

Tutorials for Getting Started

These tutorials demonstrate the basics of using Impala. They are intended for first-time users, and for trying out Impala on any new cluster to make sure the major components are working correctly.

Explore a New Impala Instance

This tutorial demonstrates techniques for finding your way around the tables and databases of an unfamiliar (possibly empty) Impala instance.

When you connect to an Impala instance for the first time, you use the `SHOW DATABASES` and `SHOW TABLES` statements to view the most common types of objects. Also, call the `version()` function to confirm which version of Impala you are running; the version number is important when consulting documentation and dealing with support issues.

A completely empty Impala instance contains no tables, but still has two databases:

- `default`, where new tables are created when you do not specify any other database.
- `_impala_builtins`, a system database used to hold all the built-in functions.

The following example shows how to see the available databases, and the tables in each. If the list of databases or tables is long, you can use wildcard notation to locate specific databases or tables based on their names.

```
$ impala-shell -i localhost --quiet
Starting Impala Shell without Kerberos authentication
Welcome to the Impala shell. Press TAB twice to see a list of available
  commands.
...
(Shell
    build version: Impala Shell v3.4.x (hash) built on
    date)
[localhost:21000] > select version();
+-----+
| version() |
+-----+
| impalad version ...
| Built on ...
+-----+
[localhost:21000] > show databases;
+-----+
| name |
+-----+
| _impala_builtins
| ctas
| d1
| d2
| d3
| default
| explain_plans
| external_table
| file_formats
| tpc
+-----+
[localhost:21000] > select current_database();
+-----+
| current_database() |
+-----+
| default |
+-----+
[localhost:21000] > show tables;
+-----+
| name |
+-----+
| ex_t
| t1
+-----+
[localhost:21000] > show tables in d3;

[localhost:21000] > show tables in tpc;
```

```

+-----+
| name |
+-----+
| city |
| customer |
| customer_address |
| customer_demographics |
| household_demographics |
| item |
| promotion |
| store |
| store2 |
| store_sales |
| ticket_view |
| time_dim |
| tpc_tables |
+-----+
[localhost:21000] > show tables in tpc like 'customer*';
+-----+
| name |
+-----+
| customer |
| customer_address |
| customer_demographics |
+-----+

```

Once you know what tables and databases are available, you descend into a database with the `USE` statement. To understand the structure of each table, you use the `DESCRIBE` command. Once inside a database, you can issue statements such as `INSERT` and `SELECT` that operate on particular tables.

The following example explores a database named `TPC` whose name we learned in the previous example. It shows how to filter the table names within a database based on a search string, examine the columns of a table, and run queries to examine the characteristics of the table data. For example, for an unfamiliar table you might want to know the number of rows, the number of different values for a column, and other properties such as whether the column contains any `NULL` values. When sampling the actual data values from a table, use a `LIMIT` clause to avoid excessive output if the table contains more rows or distinct values than you expect.

```

[localhost:21000] > use tpc;
[localhost:21000] > show tables like '*view*';
+-----+
| name |
+-----+
| ticket_view |
+-----+
[localhost:21000] > describe city;
+-----+
| name | type | comment |
+-----+
| id | int | |
| name | string | |
| countrycode | string | |
| district | string | |
| population | int | |
+-----+
[localhost:21000] > select count(*) from city;
+-----+
| count(*) |
+-----+
| 0 |
+-----+
[localhost:21000] > desc customer;
+-----+
| name | type | comment |
+-----+

```

```

+-----+-----+
| c_customer_sk | int |
| c_customer_id | string |
| c_current_cdemo_sk | int |
| c_current_hdemo_sk | int |
| c_current_addr_sk | int |
| c_first_shipto_date_sk | int |
| c_first_sales_date_sk | int |
| c_salutation | string |
| c_first_name | string |
| c_last_name | string |
| c_preferred_cust_flag | string |
| c_birth_day | int |
| c_birth_month | int |
| c_birth_year | int |
| c_birth_country | string |
| c_login | string |
| c_email_address | string |
| c_last_review_date | string |
+-----+-----+
[localhost:21000] > select count(*) from customer;
+-----+
| count(*) |
+-----+
| 100000 |
+-----+
[localhost:21000] > select count(distinct c_birth_month) from customer;
+-----+
| count(distinct c_birth_month) |
+-----+
| 12 |
+-----+
[localhost:21000] > select count(*) from customer where c_email_address is
null;
+-----+
| count(*) |
+-----+
| 0 |
+-----+
[localhost:21000] > select distinct c_salutation from customer limit 10;
+-----+
| c_salutation |
+-----+
| Mr. |
| Ms. |
| Dr. |
| Miss |
| Sir |
| Mrs. |
+-----+

```

When you graduate from read-only exploration, you use statements such as `CREATE DATABASE` and `CREATE TABLE` to set up your own database objects.

The following example demonstrates creating a new database holding a new table. Although the last example ended inside the TPC database, the new `EXPERIMENTS` database is not nested inside TPC; all databases are arranged in a single top-level list.

```

[localhost:21000] > create database experiments;
[localhost:21000] > show databases;
+-----+
| name |
+-----+

```

```

+-----+
|_impala_builtins|
|ctas            |
|d1              |
|d2              |
|d3              |
|default         |
|experiments     |
|explain_plans   |
|external_table  |
|file_formats    |
|tpc             |
+-----+
[localhost:21000] > show databases like 'exp*';
+-----+
| name          |
+-----+
| experiments   |
| explain_plans |
+-----+

```

The following example creates a new table, T1. To illustrate a common mistake, it creates this table inside the wrong database, the TPC database where the previous example ended. The `ALTER TABLE` statement lets you move the table to the intended database, `EXPERIMENTS`, as part of a rename operation. The `USE` statement is always needed to switch to a new database, and the `current_database()` function confirms which database the session is in, to avoid these kinds of mistakes.

```

[localhost:21000] > create table t1 (x int);

[localhost:21000] > show tables;
+-----+
| name          |
+-----+
| city          |
| customer      |
| customer_address |
| customer_demographics |
| household_demographics |
| item          |
| promotion     |
| store         |
| store2        |
| store_sales   |
| t1            |
| ticket_view   |
| time_dim      |
| tpc_tables    |
+-----+
[localhost:21000] > select current_database();
+-----+
| current_database() |
+-----+
| tpc                |
+-----+
[localhost:21000] > alter table t1 rename to experiments.t1;
[localhost:21000] > use experiments;
[localhost:21000] > show tables;
+-----+
| name          |
+-----+
| t1            |
+-----+
[localhost:21000] > select current_database();

```

```
+-----+
| current_database() |
+-----+
| experiments        |
+-----+
```

For your initial experiments with tables, you can use ones with just a few columns and a few rows, and text-format data files.

Note: As you graduate to more realistic scenarios, you will use more elaborate tables with many columns, features such as partitioning, and file formats such as Parquet. When dealing with realistic data volumes, you will bring in data using `LOAD DATA` or `INSERT ... SELECT` statements to operate on millions or billions of rows at once.

The following example sets up a couple of simple tables with a few rows, and performs queries involving sorting, aggregate functions and joins.

```
[localhost:21000] > insert into t1 values (1), (3), (2), (4);
[localhost:21000] > select x from t1 order by x desc;
+----+
| x  |
+----+
| 4  |
| 3  |
| 2  |
| 1  |
+----+

[localhost:21000] > select min(x), max(x), sum(x), avg(x) from t1;
+-----+-----+-----+-----+
| min(x) | max(x) | sum(x) | avg(x) |
+-----+-----+-----+-----+
| 1      | 4      | 10     | 2.5    |
+-----+-----+-----+-----+

[localhost:21000] > create table t2 (id int, word string);
[localhost:21000] > insert into t2 values (1, "one"), (3, "three"), (5,
'five');
[localhost:21000] > select word from t1 join t2 on (t1.x = t2.id);
+-----+
| word  |
+-----+
| one   |
| three |
+-----+
```

After completing this tutorial, you should now know:

- How to tell which version of Impala is running on your system.
- How to find the names of databases in an Impala instance, either displaying the full list or searching for specific names.
- How to find the names of tables in an Impala database, either displaying the full list or searching for specific names.
- How to switch between databases and check which database you are currently in.
- How to learn the column names and types of a table.
- How to create databases and tables, insert small amounts of test data, and run simple queries.

Load CSV Data from Local Files

This scenario illustrates how to create some very small tables, suitable for first-time users to experiment with Impala SQL features. `TAB1` and `TAB2` are loaded with data from files in HDFS. A subset of data is copied from `TAB1` into `TAB3`.

Populate HDFS with the data you want to query. To begin this process, create one or more new subdirectories underneath your user directory in HDFS. The data for each table resides in a separate subdirectory. Substitute your own username for `username` where appropriate. This example uses the `-p` option with the `mkdir` operation to create any necessary parent directories if they do not already exist.

```
$ whoami
username
$ hdfs dfs -ls /user
Found 3 items
drwxr-xr-x   - username username          0 2013-04-22 18:54 /user/
username
drwxrwx---   - mapred   mapred           0 2013-03-15 20:11 /user/history
drwxr-xr-x   - hue      supergroup      0 2013-03-15 20:10 /user/hive

$ hdfs dfs -mkdir -p /user/username/sample_data/tab1 /user/username/
sample_data/tab2
```

Here is some sample data, for two tables named TAB1 and TAB2.

Copy the following content to `.csv` files in your local filesystem:

`tab1.csv`:

```
1,true,123.123,2012-10-24 08:55:00
2,false,1243.5,2012-10-25 13:40:00
3,false,24453.325,2008-08-22 09:33:21.123
4,false,243423.325,2007-05-12 22:32:21.33454
5,true,243.325,1953-04-22 09:11:33
```

`tab2.csv`:

```
1,true,12789.123
2,false,1243.5
3,false,24453.325
4,false,2423.3254
5,true,243.325
60,false,243565423.325
70,true,243.325
80,false,243423.325
90,true,243.325
```

Put each `.csv` file into a separate HDFS directory using commands like the following, which use paths available in the Impala Demo VM:

```
$ hdfs dfs -put tab1.csv /user/username/sample_data/tab1
$ hdfs dfs -ls /user/username/sample_data/tab1
Found 1 items
-rw-r--r--   1 username username          192 2013-04-02 20:08 /user/username/
sample_data/tab1/tab1.csv

$ hdfs dfs -put tab2.csv /user/username/sample_data/tab2
$ hdfs dfs -ls /user/username/sample_data/tab2
Found 1 items
-rw-r--r--   1 username username          158 2013-04-02 20:09 /user/username/
sample_data/tab2/tab2.csv
```

The name of each data file is not significant. In fact, when Impala examines the contents of the data directory for the first time, it considers all files in the directory to make up the data of the table, regardless of how many files there are or what the files are named.

To understand what paths are available within your own HDFS filesystem and what the permissions are for the various directories and files, issue `hdfs dfs -ls /` and work your way down the tree doing `-ls` operations for the various directories.

Use the `impala-shell` command to create tables, either interactively or through a SQL script.

The following example shows creating three tables. For each table, the example shows creating columns with various attributes such as Boolean or integer types. The example also includes commands that provide information about how the data is formatted, such as rows terminating with commas, which makes sense in the case of importing data from a `.csv` file. Where we already have `.csv` files containing data in the HDFS directory tree, we specify the location of the directory containing the appropriate `.csv` file. Impala considers all the data from all the files in that directory to represent the data for the table.

```
DROP TABLE IF EXISTS tab1;
-- The EXTERNAL clause means the data is located outside the central
-- location
-- for Impala data files and is preserved when the associated Impala table
-- is dropped.
-- We expect the data to already exist in the directory specified by the
-- LOCATION clause.
CREATE EXTERNAL TABLE tab1
(
  id INT,
  col_1 BOOLEAN,
  col_2 DOUBLE,
  col_3 TIMESTAMP
)
ROW FORMAT DELIMITED FIELDS TERMINATED BY ','
LOCATION '/user/username/sample_data/tab1';

DROP TABLE IF EXISTS tab2;
-- TAB2 is an external table, similar to TAB1.
CREATE EXTERNAL TABLE tab2
(
  id INT,
  col_1 BOOLEAN,
  col_2 DOUBLE
)
ROW FORMAT DELIMITED FIELDS TERMINATED BY ','
LOCATION '/user/username/sample_data/tab2';

DROP TABLE IF EXISTS tab3;
-- Leaving out the EXTERNAL clause means the data will be managed
-- in the central Impala data directory tree. Rather than reading
-- existing data files when the table is created, we load the
-- data after creating the table.
CREATE TABLE tab3
(
  id INT,
  col_1 BOOLEAN,
  col_2 DOUBLE,
  month INT,
  day INT
)
ROW FORMAT DELIMITED FIELDS TERMINATED BY ',';
```

Note: Getting through these `CREATE TABLE` statements successfully is an important validation step to confirm everything is configured correctly with the Hive metastore and HDFS permissions. If you receive any errors during the `CREATE TABLE` statements:

- Make sure you followed the installation instructions closely, in [Installing Impala](#) on page 25.

- Make sure the `hive.metastore.warehouse.dir` property points to a directory that Impala can write to. The ownership should be `hive:hive`, and the `impala` user should also be a member of the `hive` group.

Point an Impala Table at Existing Data Files

A convenient way to set up data for Impala to access is to use an external table, where the data already exists in a set of HDFS files and you just point the Impala table at the directory containing those files. For example, you might run in `impala-shell` a `*.sql` file with contents similar to the following, to create an Impala table that accesses an existing data file used by Hive.

The following examples set up 2 tables, referencing the paths and sample data from the sample TPC-DS kit for Impala. For historical reasons, the data physically resides in an HDFS directory tree under `/user/hive`, although this particular data is entirely managed by Impala rather than Hive. When we create an external table, we specify the directory containing one or more data files, and Impala queries the combined content of all the files inside that directory. Here is how we examine the directories and files within the HDFS filesystem:

```
$ cd ~/username/datasets
$ ./tpcds-setup.sh
... Downloads and unzips the kit, builds the data and loads it into HDFS ...
$ hdfs dfs -ls /user/hive/tpcds/customer
Found 1 items
-rw-r--r--    1 username supergroup    13209372  2013-03-22  18:09 /user/hive/tpcds/customer/customer.dat
$ hdfs dfs -cat /user/hive/tpcds/customer/customer.dat | more
1|AAAAAAAAABAAAAAA|980124|7135|32946|2452238|2452208|Mr.|Javier|Lewis|Y|9|
12|1936|CHILE||Javie
r.Lewis@VFAXlnZEvOx.org|2452508|
2|AAAAAAAAACAAAAAA|819667|1461|31655|2452318|2452288|Dr.|Amy|Moses|Y|9|4|
1966|TOGO||Amy.Moses@
Ovk9KjHH.com|2452318|
3|AAAAAAAAADAAAAAA|1473522|6247|48572|2449130|2449100|Miss|Latisha|Hamilton|
N|18|9|1979|NIUE||
Latisha.Hamilton@V.com|2452313|
4|AAAAAAAAAEAAAAAA|1703214|3986|39558|2450030|2450000|Dr.|Michael|White|N|7|
6|1983|MEXICO||Mic
hael.White@i.org|2452361|
5|AAAAAAAFAAAAAAA|953372|4470|36368|2449438|2449408|Sir|Robert|Moran|N|8|5|
1956|FIJI||Robert.
Moran@Hh.edu|2452469|
...
```

Here is a SQL script to set up Impala tables pointing to some of these data files in HDFS. (The script in the VM sets up tables like this through Hive; ignore those tables for purposes of this demonstration.) Save the following as `customer_setup.sql`:

```
--
-- store_sales fact table and surrounding dimension tables only
--
create database tpcds;
use tpcds;

drop table if exists customer;
create external table customer
(
    c_customer_sk          int,
    c_customer_id          string,
    c_current_cdemo_sk     int,
    c_current_hdemo_sk     int,
    c_current_addr_sk      int,
    c_first_shipto_date_sk int,
    c_first_sales_date_sk  int,
    c_salutation            string,
```

```

    c_first_name      string,
    c_last_name       string,
    c_preferred_cust_flag string,
    c_birth_day        int,
    c_birth_month      int,
    c_birth_year       int,
    c_birth_country    string,
    c_login            string,
    c_email_address    string,
    c_last_review_date string
)
row format delimited fields terminated by '|'
location '/user/hive/tpcds/customer';

drop table if exists customer_address;
create external table customer_address
(
    ca_address_sk      int,
    ca_address_id      string,
    ca_street_number   string,
    ca_street_name     string,
    ca_street_type     string,
    ca_suite_number    string,
    ca_city            string,
    ca_county          string,
    ca_state           string,
    ca_zip            string,
    ca_country         string,
    ca_gmt_offset      float,
    ca_location_type   string
)
row format delimited fields terminated by '|'
location '/user/hive/tpcds/customer_address';

```

We would run this script with a command such as:

```
impala-shell -i localhost -f customer_setup.sql
```

Describe the Impala Table

Now that you have updated the database metadata that Impala caches, you can confirm that the expected tables are accessible by Impala and examine the attributes of one of the tables. We created these tables in the database named `default`. If the tables were in a database other than the default, we would issue a command `use db_name` to switch to that database before examining or querying its tables. We could also qualify the name of a table by prepending the database name, for example `default.customer` and `default.customer_name`.

```

[impala-host:21000] > show databases
Query finished, fetching results ...
default
Returned 1 row(s) in 0.00s
[impala-host:21000] > show tables
Query finished, fetching results ...
customer
customer_address
Returned 2 row(s) in 0.00s
[impala-host:21000] > describe customer_address
+-----+-----+-----+
| name          | type   | comment |
+-----+-----+-----+
| ca_address_sk | int    |         |
| ca_address_id | string |         |
| ca_street_number | string |         |

```

ca_street_name	string		
ca_street_type	string		
ca_suite_number	string		
ca_city	string		
ca_county	string		
ca_state	string		
ca_zip	string		
ca_country	string		
ca_gmt_offset	float		
ca_location_type	string		

-----+-----+-----+-----+
Returned 13 row(s) in 0.01

Query the Impala Table

You can query data contained in the tables. Impala coordinates the query execution across a single node or multiple nodes depending on your configuration, without the overhead of running MapReduce jobs to perform the intermediate processing.

There are a variety of ways to execute queries on Impala:

- Using the `impala-shell` command in interactive mode:

```
$ impala-shell -i impala-host
Connected to localhost:21000
[impala-host:21000] > select count(*) from customer_address;
50000
Returned 1 row(s) in 0.37s
```

- Passing a set of commands contained in a file:

```
$ impala-shell -i impala-host -f myquery.sql
Connected to localhost:21000
50000
Returned 1 row(s) in 0.19s
```

- Passing a single command to the `impala-shell` command. The query is executed, the results are returned, and the shell exits. Make sure to quote the command, preferably with single quotation marks to avoid shell expansion of characters such as `*`.

```
$ impala-shell -i impala-host -q 'select count(*) from customer_address'
Connected to localhost:21000
50000
Returned 1 row(s) in 0.29s
```

Data Loading and Querying Examples

This section describes how to create some sample tables and load data into them. These tables can then be queried using the Impala shell.

Loading Data

Loading data involves:

- Establishing a data set. The example below uses `.csv` files.
- Creating tables to which to load data.
- Loading the data into the tables you created.

Sample Queries

To run these sample queries, create a SQL query file `query.sql`, copy and paste each query into the query file, and then run the query file using the shell. For example, to run `query.sql` on `impala-host`, you might use the command:

```
impala-shell.sh -i impala-host -f query.sql
```

The examples and results below assume you have loaded the sample data into the tables as described above.

Example: Examining Contents of Tables

Let's start by verifying that the tables do contain the data we expect. Because Impala often deals with tables containing millions or billions of rows, when examining tables of unknown size, include the `LIMIT` clause to avoid huge amounts of unnecessary output, as in the final query. (If your interactive query starts displaying an unexpected volume of data, press `Ctrl-C` in `impala-shell` to cancel the query.)

```
SELECT * FROM tab1;
SELECT * FROM tab2;
SELECT * FROM tab2 LIMIT 5;
```

Results:

id	col_1	col_2	col_3
1	true	123.123	2012-10-24 08:55:00
2	false	1243.5	2012-10-25 13:40:00
3	false	24453.325	2008-08-22 09:33:21.123000000
4	false	243423.325	2007-05-12 22:32:21.334540000
5	true	243.325	1953-04-22 09:11:33

id	col_1	col_2
1	true	12789.123
2	false	1243.5
3	false	24453.325
4	false	2423.3254
5	true	243.325
60	false	243565423.325
70	true	243.325
80	false	243423.325
90	true	243.325

id	col_1	col_2
1	true	12789.123
2	false	1243.5
3	false	24453.325
4	false	2423.3254
5	true	243.325

Example: Aggregate and Join

```
SELECT tab1.col_1, MAX(tab2.col_2), MIN(tab2.col_2)
FROM tab2 JOIN tab1 USING (id)
GROUP BY col_1 ORDER BY 1 LIMIT 5;
```

Results:

col_1	max(tab2.col_2)	min(tab2.col_2)
false	24453.325	1243.5
true	12789.123	243.325

Example: Subquery, Aggregate and Joins

```
SELECT tab2.*
FROM tab2,
(SELECT tab1.col_1, MAX(tab2.col_2) AS max_col2
FROM tab2, tab1
WHERE tab1.id = tab2.id
GROUP BY col_1) subquery1
WHERE subquery1.max_col2 = tab2.col_2;
```

Results:

id	col_1	col_2
1	true	12789.123
3	false	24453.325

Example: INSERT Query

```
INSERT OVERWRITE TABLE tab3
SELECT id, col_1, col_2, MONTH(col_3), DAYOFMONTH(col_3)
FROM tab1 WHERE YEAR(col_3) = 2012;
```

Query TAB3 to check the result:

```
SELECT * FROM tab3;
```

Results:

id	col_1	col_2	month	day
1	true	123.123	10	24
2	false	1243.5	10	25

Advanced Tutorials

These tutorials walk you through advanced scenarios or specialized features.

Attaching an External Partitioned Table to an HDFS Directory Structure

This tutorial shows how you might set up a directory tree in HDFS, put data files into the lowest-level subdirectories, and then use an Impala external table to query the data files from their original locations.

The tutorial uses a table with web log data, with separate subdirectories for the year, month, day, and host. For simplicity, we use a tiny amount of CSV data, loading the same data into each partition.

First, we make an Impala partitioned table for CSV data, and look at the underlying HDFS directory structure to understand the directory structure to re-create elsewhere in HDFS. The columns `field1`, `field2`, and `field3` correspond to the contents of the CSV data files. The `year`, `month`, `day`, and `host` columns are all represented as subdirectories within the table structure, and are not part of the CSV files. We use `STRING` for each of these columns so that we can produce consistent subdirectory names, with leading zeros for a consistent length.

```
create database external_partitions;
use external_partitions;
create table logs (field1 string, field2 string, field3 string)
  partitioned by (year string, month string, day string, host string)
  row format delimited fields terminated by ',';
insert into logs partition (year="2013", month="07", day="28", host="host1")
  values ("foo","foo","foo");
insert into logs partition (year="2013", month="07", day="28", host="host2")
  values ("foo","foo","foo");
insert into logs partition (year="2013", month="07", day="29", host="host1")
  values ("foo","foo","foo");
insert into logs partition (year="2013", month="07", day="29", host="host2")
  values ("foo","foo","foo");
insert into logs partition (year="2013", month="08", day="01", host="host1")
  values ("foo","foo","foo");
```

Back in the Linux shell, we examine the HDFS directory structure. (Your Impala data directory might be in a different location; for historical reasons, it is sometimes under the HDFS path `/user/hive/warehouse`.) We use the `hdfs dfs -ls` command to examine the nested subdirectories corresponding to each partitioning column, with separate subdirectories at each level (with `=` in their names) representing the different values for each partitioning column. When we get to the lowest level of subdirectory, we use the `hdfs dfs -cat` command to examine the data file and see CSV-formatted data produced by the `INSERT` statement in Impala.

```
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db
Found 1 items
drwxrwxrwt - impala hive          0 2013-08-07 12:24 /user/impala/
warehouse/external_partitions.db/logs
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs
Found 1 items
drwxr-xr-x - impala hive          0 2013-08-07 12:24 /user/impala/
warehouse/external_partitions.db/logs/year=2013
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs/year=2013
Found 2 items
drwxr-xr-x - impala hive          0 2013-08-07 12:23 /user/impala/
warehouse/external_partitions.db/logs/year=2013/month=07
drwxr-xr-x - impala hive          0 2013-08-07 12:24 /user/impala/
warehouse/external_partitions.db/logs/year=2013/month=08
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs/year=2013/
month=07
Found 2 items
drwxr-xr-x - impala hive          0 2013-08-07 12:22 /user/impala/
warehouse/external_partitions.db/logs/year=2013/month=07/day=28
```



```

drwxr-xr-x  - impala hive          0 2013-08-07 12:23 /user/impala/
warehouse/external_partitions.db/logs/year=2013/month=07/day=29
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs/year=2013/
month=07/day=28
Found 2 items
drwxr-xr-x  - impala hive          0 2013-08-07 12:21 /user/impala/
warehouse/external_partitions.db/logs/year=2013/month=07/day=28/host=host1
drwxr-xr-x  - impala hive          0 2013-08-07 12:22 /user/impala/
warehouse/external_partitions.db/logs/year=2013/month=07/day=28/host=host2
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs/year=2013/
month=07/day=28/host=host1
Found 1 items
-rw-r--r--   3 impala hive          12 2013-08-07 12:21 /user/impala/
warehouse/external_partiti
ons.db/logs/year=2013/month=07/day=28/
host=host1/3981726974111751120--8907184999369517436_822630111_data.0
$ hdfs dfs -cat /user/impala/warehouse/external_partitions.db/logs/
year=2013/month=07/day=28/\
host=host1/3981726974111751120--8 907184999369517436_822630111_data.0
foo,foo,foo

```

Still in the Linux shell, we use `hdfs dfs -mkdir` to create several data directories outside the HDFS directory tree that Impala controls (`/user/impala/warehouse` in this example, maybe different in your case). Depending on your configuration, you might need to log in as a user with permission to write into this HDFS directory tree; for example, the commands shown here were run while logged in as the `hdfs` user.

```

$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=28/
host=host1
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=28/
host=host2
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=28/
host=host1
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=29/
host=host1
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=08/day=01/
host=host1

```

We make a tiny CSV file, with values different than in the `INSERT` statements used earlier, and put a copy within each subdirectory that we will use as an Impala partition.

```

$ cat >dummy_log_data
bar,baz,bletch
$ hdfs dfs -mkdir -p /user/impala/data/external_partitions/year=2013/
month=08/day=01/host=host1
$ hdfs dfs -mkdir -p /user/impala/data/external_partitions/year=2013/
month=07/day=28/host=host1
$ hdfs dfs -mkdir -p /user/impala/data/external_partitions/year=2013/
month=07/day=28/host=host2
$ hdfs dfs -mkdir -p /user/impala/data/external_partitions/year=2013/
month=07/day=29/host=host1
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=07/
day=28/host=host1
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=07/
day=28/host=host2
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=07/
day=29/host=host1
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=08/
day=01/host=host1

```

Back in the `impala-shell` interpreter, we move the original Impala-managed table aside, and create a new *external* table with a `LOCATION` clause pointing to the directory under which we have set up all the partition subdirectories and data files.

```
use external_partitions;
alter table logs rename to logs_original;
create external table logs (field1 string, field2 string, field3 string)
  partitioned by (year string, month string, day string, host string)
  row format delimited fields terminated by ','
  location '/user/impala/data/logs';
```

Because partition subdirectories and data files come and go during the data lifecycle, you must identify each of the partitions through an `ALTER TABLE` statement before Impala recognizes the data files they contain.

```
alter table logs add partition
  (year="2013",month="07",day="28",host="host1")
alter table log_type add partition
  (year="2013",month="07",day="28",host="host2");
alter table log_type add partition
  (year="2013",month="07",day="29",host="host1");
alter table log_type add partition
  (year="2013",month="08",day="01",host="host1");
```

We issue a `REFRESH` statement for the table, always a safe practice when data files have been manually added, removed, or changed. Then the data is ready to be queried. The `SELECT *` statement illustrates that the data from our trivial CSV file was recognized in each of the partitions where we copied it. Although in this case there are only a few rows, we include a `LIMIT` clause on this test query just in case there is more data than we expect.

```
refresh log_type;
select * from log_type limit 100;
```

field1	field2	field3	year	month	day	host
bar	baz	bletch	2013	07	28	host1
bar	baz	bletch	2013	08	01	host1
bar	baz	bletch	2013	07	29	host1
bar	baz	bletch	2013	07	28	host2

Switching Back and Forth Between Impala and Hive

Sometimes, you might find it convenient to switch to the Hive shell to perform some data loading or transformation operation, particularly on file formats such as `RCFile`, `SequenceFile`, and `Avro` that Impala currently can query but not write to.

Whenever you create, drop, or alter a table or other kind of object through Hive, the next time you switch back to the `impala-shell` interpreter, issue a one-time `INVALIDATE METADATA` statement so that Impala recognizes the new or changed object.

Whenever you load, insert, or change data in an existing table through Hive (or even through manual HDFS operations such as the `hdfs` command), the next time you switch back to the `impala-shell` interpreter, issue a one-time `REFRESH table_name` statement so that Impala recognizes the new or changed data.

For examples showing how this process works for the `REFRESH` statement, look at the examples of creating `RCFile` and `SequenceFile` tables in Impala, loading data through Hive, and then querying the data through Impala. See [Using the RCFile File Format with Impala Tables](#) on page 728 and [Using the SequenceFile File Format with Impala Tables](#) on page 730 for those examples.

For examples showing how this process works for the `INVALIDATE METADATA` statement, look at the example of creating and loading an `Avro` table in Hive, and then querying the data through Impala. See [Using the Avro File Format with Impala Tables](#) on page 722 for that example.

Note:

Originally, Impala did not support UDFs, but this feature is available in Impala starting in Impala 1.2. Some `INSERT ... SELECT` transformations that you originally did through Hive can now be done through Impala. See [User-Defined Functions \(UDFs\)](#) on page 588 for details.

Prior to Impala 1.2, the `REFRESH` and `INVALIDATE METADATA` statements needed to be issued on each Impala node to which you connected and issued queries. In Impala 1.2 and higher, when you issue either of those statements on any Impala node, the results are broadcast to all the Impala nodes in the cluster, making it truly a one-step operation after each round of DDL or ETL operations in Hive.

Cross Joins and Cartesian Products with the CROSS JOIN Operator

Originally, Impala restricted join queries so that they had to include at least one equality comparison between the columns of the tables on each side of the join operator. With the huge tables typically processed by Impala, any mis-coded query that produced a full Cartesian product as a result set could consume a huge amount of cluster resources.

In Impala 1.2.2 and higher, this restriction is lifted when you use the `CROSS JOIN` operator in the query. You still cannot remove all `WHERE` clauses from a query like `SELECT * FROM t1 JOIN t2` to produce all combinations of rows from both tables. But you can use the `CROSS JOIN` operator to explicitly request such a Cartesian product. Typically, this operation is applicable for smaller tables, where the result set still fits within the memory of a single Impala node.

The following example sets up data for use in a series of comic books where characters battle each other. At first, we use an equijoin query, which only allows characters from the same time period and the same planet to meet.

```
[localhost:21000] > create table heroes (name string, era string, planet
string);
[localhost:21000] > create table villains (name string, era string, planet
string);
[localhost:21000] > insert into heroes values
> ('Tesla', '20th century', 'Earth'),
> ('Pythagoras', 'Antiquity', 'Earth'),
> ('Zopzar', 'Far Future', 'Mars');
Inserted 3 rows in 2.28s
[localhost:21000] > insert into villains values
> ('Caligula', 'Antiquity', 'Earth'),
> ('John Dillinger', '20th century', 'Earth'),
> ('Xibulor', 'Far Future', 'Venus');
Inserted 3 rows in 1.93s
[localhost:21000] > select concat(heroes.name, ' vs. ', villains.name) as
battle
> from heroes join villains
> where heroes.era = villains.era and heroes.planet =
villains.planet;
+-----+
| battle |
+-----+
| Tesla vs. John Dillinger |
| Pythagoras vs. Caligula |
+-----+
Returned 2 row(s) in 0.47s
```

Readers demanded more action, so we added elements of time travel and space travel so that any hero could face any villain. Prior to Impala 1.2.2, this type of query was impossible because all joins had to reference matching values between the two tables:

```
[localhost:21000] > -- Cartesian product not possible in Impala 1.1.
> select concat(heroes.name, ' vs. ', villains.name) as
battle from heroes join villains;
```

```
ERROR: NotImplementedException: Join between 'heroes' and 'villains'
requires at least one conjunctive equality predicate between the two tables
```

With Impala 1.2.2, we rewrite the query slightly to use `CROSS JOIN` rather than `JOIN`, and now the result set includes all combinations:

```
[localhost:21000] > -- Cartesian product available in Impala 1.2.2 with the
CROSS JOIN syntax.
                    > select concat(heroes.name, ' vs. ', villains.name) as
battle from heroes cross join villains;
```

battle
Tesla vs. Caligula
Tesla vs. John Dillinger
Tesla vs. Xibulor
Pythagoras vs. Caligula
Pythagoras vs. John Dillinger
Pythagoras vs. Xibulor
Zopzar vs. Caligula
Zopzar vs. John Dillinger
Zopzar vs. Xibulor

```
Returned 9 row(s) in 0.33s
```

The full combination of rows from both tables is known as the Cartesian product. This type of result set is often used for creating grid data structures. You can also filter the result set by including `WHERE` clauses that do not explicitly compare columns between the two tables. The following example shows how you might produce a list of combinations of year and quarter for use in a chart, and then a shorter list with only selected quarters.

```
[localhost:21000] > create table x_axis (x int);
[localhost:21000] > create table y_axis (y int);
[localhost:21000] > insert into x_axis values (1),(2),(3),(4);
Inserted 4 rows in 2.14s
[localhost:21000] > insert into y_axis values (2010),(2011),(2012),(2013),
(2014);
Inserted 5 rows in 1.32s
[localhost:21000] > select y as year, x as quarter from x_axis cross join
y_axis;
```

year	quarter
2010	1
2011	1
2012	1
2013	1
2014	1
2010	2
2011	2
2012	2
2013	2
2014	2
2010	3
2011	3
2012	3
2013	3
2014	3
2010	4
2011	4
2012	4
2013	4
2014	4

```

+-----+-----+
Returned 20 row(s) in 0.38s
[localhost:21000] > select y as year, x as quarter from x_axis cross join
y_axis where x in (1,3);
+-----+-----+
| year | quarter |
+-----+-----+
| 2010 | 1        |
| 2011 | 1        |
| 2012 | 1        |
| 2013 | 1        |
| 2014 | 1        |
| 2010 | 3        |
| 2011 | 3        |
| 2012 | 3        |
| 2013 | 3        |
| 2014 | 3        |
+-----+-----+
Returned 10 row(s) in 0.39s

```

Dealing with Parquet Files with Unknown Schema

As data pipelines start to include more aspects such as NoSQL or loosely specified schemas, you might encounter situations where you have data files (particularly in Parquet format) where you do not know the precise table definition. This tutorial shows how you can build an Impala table around data that comes from non-Impala or even non-SQL sources, where you do not have control of the table layout and might not be familiar with the characteristics of the data.

The data used in this tutorial represents airline on-time arrival statistics, from October 1987 through April 2008. See the details on the [2009 ASA Data Expo web site](#). You can also see the [explanations of the columns](#); for purposes of this exercise, wait until after following the tutorial before examining the schema, to better simulate a real-life situation where you cannot rely on assumptions and assertions about the ranges and representations of data values.

Download the Data Files into HDFS

First, we download and unpack the data files. There are 8 files totalling 1.4 GB.

```

$ wget -O airlines_parquet.tar.gz https://home.apache.org/~arodoni/
airlines_parquet.tar.gz
$ wget https://home.apache.org/~arodoni/airlines_parquet.tar.gz.sha512
$ shasum -a 512 -c airlines_parquet.tar.gz.sha512
airlines_parquet.tar.gz: OK

$ tar xvzf airlines_parquet.tar.gz

$ cd airlines_parquet/

$ du -kch *.parq
253M  4345e5eef217aalb-c8f16177f35fd983_1150363067_data.0.parq
14M   4345e5eef217aalb-c8f16177f35fd983_1150363067_data.1.parq
253M  4345e5eef217aalb-c8f16177f35fd984_501176748_data.0.parq
64M   4345e5eef217aalb-c8f16177f35fd984_501176748_data.1.parq
184M  4345e5eef217aalb-c8f16177f35fd985_1199995767_data.0.parq
241M  4345e5eef217aalb-c8f16177f35fd986_2086627597_data.0.parq
212M  4345e5eef217aalb-c8f16177f35fd987_1048668565_data.0.parq
152M  4345e5eef217aalb-c8f16177f35fd988_1432111844_data.0.parq
1.4G  total

```

Next, we put the Parquet data files in HDFS, all together in a single directory, with permissions on the directory and the files so that the `impala` user will be able to read them.

After unpacking, we saw the largest Parquet file was 253 MB. When copying Parquet files into HDFS for Impala to use, for maximum query performance, make sure that each file resides in a single HDFS data block. Therefore, we pick a size larger than any single file and specify that as the block size, using the argument `-Ddfs.block.size=253m` on the `hdfs dfs -put` command.

```
$ sudo -u hdfs hdfs dfs -mkdir -p /user/impala/staging/airlines
$ sudo -u hdfs hdfs dfs -Ddfs.block.size=253m -put *.parq /user/impala/staging/airlines
$ sudo -u hdfs hdfs dfs -ls /user/impala/staging
Found 1 items

$ sudo -u hdfs hdfs dfs -ls /user/impala/staging/airlines
Found 8 items
```

Create Database and Tables

With the files in an accessible location in HDFS, you create a database table that uses the data in those files:

- The `CREATE EXTERNAL` syntax and the `LOCATION` attribute point Impala at the appropriate HDFS directory.
- The `LIKE PARQUET 'path_to_any_parquet_file'` clause means we skip the list of column names and types; Impala automatically gets the column names and data types straight from the data files. (Currently, this technique only works for Parquet files.)
- Ignore the warning about lack of `READ_WRITE` access to the files in HDFS; the `impala` user can read the files, which will be sufficient for us to experiment with queries and perform some copy and transform operations into other tables.

```
$ impala-shell
> CREATE DATABASE airlines_data;
USE airlines_data;
CREATE EXTERNAL TABLE airlines_external
LIKE PARQUET 'hdfs:staging/airlines/4345e5eef217a1b-c8f16177f35fd983_1150363067_data.0.parq'
STORED AS PARQUET LOCATION 'hdfs:staging/airlines';
WARNINGS: Impala does not have READ_WRITE access to path 'hdfs://myhost.com:8020/user/impala/staging'
```

Examine Physical and Logical Schema

With the table created, we examine its physical and logical characteristics to confirm that the data is really there and in a format and shape that we can work with.

- The `SHOW TABLE STATS` statement gives a very high-level summary of the table, showing how many files and how much total data it contains. Also, it confirms that the table is expecting all the associated data files to be in Parquet format. (The ability to work with all kinds of HDFS data files in different formats means that it is possible to have a mismatch between the format of the data files, and the format that the table expects the data files to be in.)
- The `SHOW FILES` statement confirms that the data in the table has the expected number, names, and sizes of the original Parquet files.
- The `DESCRIBE` statement (or its abbreviation `DESC`) confirms the names and types of the columns that Impala automatically created after reading that metadata from the Parquet file.
- The `DESCRIBE FORMATTED` statement prints out some extra detail along with the column definitions. The pieces we care about for this exercise are:
 - The containing database for the table.
 - The location of the associated data files in HDFS.
 - The table is an external table so Impala will not delete the HDFS files when we finish the experiments and drop the table.

- The table is set up to work exclusively with files in the Parquet format.

```
> SHOW TABLE STATS airlines_external;
```

#Rows	#Files	Size	Bytes Cached	Cache Replication	Format
Incremental stats	Location			EC Policy	
-1	8	1.34GB	NOT CACHED	NOT CACHED	PARQUET
false	/user/impala/staging/airlines		NONE		

```
> SHOW FILES IN airlines_external;
```

Path	Size	Partition	EC Policy
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd983_1150363067_data.0.parq	252.99MB		NONE
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd983_1150363067_data.1.parq	13.43MB		NONE
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd984_501176748_data.0.parq	252.84MB		NONE
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd984_501176748_data.1.parq	63.92MB		NONE
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd985_1199995767_data.0.parq	183.64MB		NONE
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd986_2086627597_data.0.parq	240.04MB		NONE
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd987_1048668565_data.0.parq	211.35MB		NONE
/user/impala/staging/airlines/4345e5eef217aalb-c8f16177f35fd988_1432111844_data.0.parq	151.46MB		NONE

```
> DESCRIBE airlines_external;
```

name	type	comment
year	int	Inferred from Parquet file.
month	int	Inferred from Parquet file.
day	int	Inferred from Parquet file.
dayofweek	int	Inferred from Parquet file.
dep_time	int	Inferred from Parquet file.
crs_dep_time	int	Inferred from Parquet file.
arr_time	int	Inferred from Parquet file.
crs_arr_time	int	Inferred from Parquet file.
carrier	string	Inferred from Parquet file.
flight_num	int	Inferred from Parquet file.
tail_num	int	Inferred from Parquet file.
actual_elapsed_time	int	Inferred from Parquet file.
crs_elapsed_time	int	Inferred from Parquet file.
airtime	int	Inferred from Parquet file.
arrdelay	int	Inferred from Parquet file.
depdelay	int	Inferred from Parquet file.
origin	string	Inferred from Parquet file.
dest	string	Inferred from Parquet file.
distance	int	Inferred from Parquet file.

```

| taxi_in          | int      | Inferred from Parquet file. |
| taxi_out         | int      | Inferred from Parquet file. |
| cancelled        | int      | Inferred from Parquet file. |
| cancellation_code | string   | Inferred from Parquet file. |
| diverted         | int      | Inferred from Parquet file. |
| carrier_delay    | int      | Inferred from Parquet file. |
| weather_delay    | int      | Inferred from Parquet file. |
| nas_delay        | int      | Inferred from Parquet file. |
| security_delay   | int      | Inferred from Parquet file. |
| late_aircraft_delay | int     | Inferred from Parquet file. |
+-----+-----+-----+

> DESCRIBE FORMATTED airlines_external;
+-----+-----+
| name                                | type                                |
+-----+-----+
...
| # Detailed Table Information        | NULL                               |
| Database:                          | airlines_data                     |
| Owner:                             | impala                            |
...
| Location:                          | /user/impala/staging/airlines     |
| Table Type:                        | EXTERNAL_TABLE                    |
...
| # Storage Information               | NULL                               |
| SerDe Library:                     |                                    |
| org.apache.hadoop.hive ql.io.parquet.serde.ParquetHiveSerDe |
| InputFormat:                       |                                    |
| org.apache.hadoop.hive ql.io.parquet.MapredParquetInputFormat |
| OutputFormat:                      |                                    |
| org.apache.hadoop.hive ql.io.parquet.MapredParquetOutputFormat |
...

```

Analyze Data

Now that we are confident that the connections are solid between the Impala table and the underlying Parquet files, we run some initial queries to understand the characteristics of the data: the overall number of rows, and the ranges and how many different values are in certain columns.

```

> SELECT COUNT(*) FROM airlines_external;
+-----+
| count(*) |
+-----+
| 123534969 |
+-----+

```

The `NDV()` function returns a number of distinct values, which, for performance reasons, is an estimate when there are lots of different values in the column, but is precise when the cardinality is less than 16 K. Use `NDV()` function for this kind of exploration rather than `COUNT(DISTINCT colname)`, because Impala can evaluate multiple `NDV()` functions in a single query, but only a single instance of `COUNT DISTINCT`.

```

> SELECT NDV(carrier), NDV(flight_num), NDV(tail_num),
        NDV(origin), NDV(dest) FROM airlines_external;
+-----+-----+-----+-----+-----+
| ndv(carrier) | ndv(flight_num) | ndv(tail_num) | ndv(origin) | ndv(dest) |
+-----+-----+-----+-----+-----+
| 29           | 8463            | 3             | 342         | 349       |
+-----+-----+-----+-----+-----+

> SELECT tail_num, COUNT(*) AS howmany FROM airlines_external
        GROUP BY tail_num;
+-----+

```



```

| tail_num | howmany |
+-----+
| NULL    | 123122001 |
| 715     | 1         |
| 0       | 406405    |
| 112     | 6562      |
+-----+

> SELECT DISTINCT dest FROM airlines_external
   WHERE dest NOT IN (SELECT origin FROM airlines_external);
+-----+
| dest |
+-----+
| CBM  |
| SKA  |
| LAR  |
| RCA  |
| LBF  |
+-----+

> SELECT DISTINCT dest FROM airlines_external
   WHERE dest NOT IN (SELECT DISTINCT origin FROM airlines_external);
+-----+
| dest |
+-----+
| CBM  |
| SKA  |
| LAR  |
| RCA  |
| LBF  |
+-----+

> SELECT DISTINCT origin FROM airlines_external
   WHERE origin NOT IN (SELECT DISTINCT dest FROM airlines_external);
Fetched 0 row(s) in 2.63

```

With the above queries, we see that there are modest numbers of different airlines, flight numbers, and origin and destination airports. Two things jump out from this query: the number of `tail_num` values is much smaller than we might have expected, and there are more destination airports than origin airports. Let's dig further. What we find is that most `tail_num` values are `NULL`. It looks like this was an experimental column that wasn't filled in accurately. We make a mental note that if we use this data as a starting point, we'll ignore this column. We also find that certain airports are represented in the `ORIGIN` column but not the `DEST` column; now we know that we cannot rely on the assumption that those sets of airport codes are identical.

Note: The first `SELECT DISTINCT DEST` query takes almost 40 seconds. We expect all queries on such a small data set, less than 2 GB, to take a few seconds at most. The reason is because the expression `NOT IN (SELECT origin FROM airlines_external)` produces an intermediate result set of 123 million rows, then runs 123 million comparisons on each data node against the tiny set of destination airports. The way the `NOT IN` operator works internally means that this intermediate result set with 123 million rows might be transmitted across the network to each data node in the cluster. Applying another `DISTINCT` inside the `NOT IN` subquery means that the intermediate result set is only 340 items, resulting in much less network traffic and fewer comparison operations. The more efficient query with the added `DISTINCT` is approximately 7 times as fast.

Next, we try doing a simple calculation, with results broken down by year. This reveals that some years have no data in the `airtime` column. That means we might be able to use that column in queries involving certain date ranges, but we cannot count on it to always be reliable. The question of whether a column contains any `NULL` values, and if so what is their number, proportion, and distribution, comes up again and again when doing initial exploration of a data set.

```

> SELECT year, SUM(airtime) FROM airlines_external
   GROUP BY year ORDER BY year DESC;

```

year	sum(airtime)
2008	713050445
2007	748015545
2006	720372850
2005	708204026
2004	714276973
2003	665706940
2002	549761849
2001	590867745
2000	583537683
1999	561219227
1998	538050663
1997	536991229
1996	519440044
1995	513364265
1994	NULL
1993	NULL
1992	NULL
1991	NULL
1990	NULL
1989	NULL
1988	NULL
1987	NULL

With the notion of NULL values in mind, let's come back to the `tail_num` column that we discovered had a lot of NULLs. Let's quantify the NULL and non-NULL values in that column for better understanding. First, we just count the overall number of rows versus the non-NULL values in that column. That initial result gives the appearance of relatively few non-NULL values, but we can break it down more clearly in a single query. Once we have the `COUNT(*)` and the `COUNT(colname)` numbers, we can encode that initial query in a `WITH` clause, then run a follow-on query that performs multiple arithmetic operations on those values. Seeing that only one-third of one percent of all rows have non-NULL values for the `tail_num` column clearly illustrates that column is not of much use.

```
> SELECT COUNT(*) AS 'rows', COUNT(tail_num) AS 'non-null tail numbers'
   FROM airlines_external;
```

rows	non-null tail numbers
123534969	412968

```
> WITH t1 AS
  (SELECT COUNT(*) AS 'rows', COUNT(tail_num) AS 'nonnull'
   FROM airlines_external)
SELECT `rows`, `nonnull`, `rows` - `nonnull` AS 'nulls',
  (`nonnull` / `rows`) * 100 AS 'percentage non-null'
FROM t1;
```

rows	nonnull	nulls	percentage non-null
123534969	412968	123122001	0.3342923897119365

By examining other columns using these techniques, we can form a mental picture of the way data is distributed throughout the table, and which columns are most significant for query purposes. For this tutorial, we focus mostly on the fields likely to hold discrete values, rather than columns such as `actual_elapsed_time` whose names suggest they hold measurements. We would dig deeper into those columns once we had a clear picture of which questions were worthwhile to ask, and what kinds of trends we might look for. For the final piece of initial

exploration, let's look at the `year` column. A simple `GROUP BY` query shows that it has a well-defined range, a manageable number of distinct values, and relatively even distribution of rows across the different years.

```
> SELECT MIN(year), MAX(year), NDV(year) FROM airlines_external;
+-----+-----+-----+
| min(year) | max(year) | ndv(year) |
+-----+-----+-----+
| 1987      | 2008      | 22         |
+-----+-----+-----+
```

```
> SELECT year, COUNT(*) howmany FROM airlines_external
   GROUP BY year ORDER BY year DESC;
+-----+-----+
| year | howmany |
+-----+-----+
| 2008 | 7009728 |
| 2007 | 7453215 |
| 2006 | 7141922 |
| 2005 | 7140596 |
| 2004 | 7129270 |
| 2003 | 6488540 |
| 2002 | 5271359 |
| 2001 | 5967780 |
| 2000 | 5683047 |
| 1999 | 5527884 |
| 1998 | 5384721 |
| 1997 | 5411843 |
| 1996 | 5351983 |
| 1995 | 5327435 |
| 1994 | 5180048 |
| 1993 | 5070501 |
| 1992 | 5092157 |
| 1991 | 5076925 |
| 1990 | 5270893 |
| 1989 | 5041200 |
| 1988 | 5202096 |
| 1987 | 1311826 |
+-----+-----+
```

We could go quite far with the data in this initial raw format, just as we downloaded it from the web. If the data set proved to be useful and worth persisting in Impala for extensive queries, we might want to copy it to an internal table, letting Impala manage the data files and perhaps reorganizing a little for higher efficiency. In this next stage of the tutorial, we copy the original data into a partitioned table, still in Parquet format. Partitioning based on the `year` column lets us run queries with clauses such as `WHERE year = 2001` or `WHERE year BETWEEN 1989 AND 1999`, which can dramatically cut down on I/O by ignoring all the data from years outside the desired range. Rather than reading all the data and then deciding which rows are in the matching years, Impala can zero in on only the data files from specific `year` partitions. To do this, Impala physically reorganizes the data files, putting the rows from each year into data files in a separate HDFS directory for each `year` value. Along the way, we'll also get rid of the `tail_num` column that proved to be almost entirely `NULL`.

The first step is to create a new table with a layout very similar to the original `airlines_external` table. We'll do that by reverse-engineering a `CREATE TABLE` statement for the first table, then tweaking it slightly to include a `PARTITION BY` clause for `year`, and excluding the `tail_num` column. The `SHOW CREATE TABLE` statement gives us the starting point.

Although we could edit that output into a new SQL statement, all the ASCII box characters make such editing inconvenient. To get a more stripped-down `CREATE TABLE` to start with, we restart the `impala-shell` command with the `-B` option, which turns off the box-drawing behavior.

```
$ impala-shell -i localhost -B -d airlines_data;
```

```

> SHOW CREATE TABLE airlines_external;
"CREATE EXTERNAL TABLE airlines_data.airlines_external (
  year INT COMMENT 'inferred from: optional int32 year',
  month INT COMMENT 'inferred from: optional int32 month',
  day INT COMMENT 'inferred from: optional int32 day',
  dayofweek INT COMMENT 'inferred from: optional int32 dayofweek',
  dep_time INT COMMENT 'inferred from: optional int32 dep_time',
  crs_dep_time INT COMMENT 'inferred from: optional int32 crs_dep_time',
  arr_time INT COMMENT 'inferred from: optional int32 arr_time',
  crs_arr_time INT COMMENT 'inferred from: optional int32 crs_arr_time',
  carrier STRING COMMENT 'inferred from: optional binary carrier',
  flight_num INT COMMENT 'inferred from: optional int32 flight_num',
  tail_num INT COMMENT 'inferred from: optional int32 tail_num',
  actual_elapsed_time INT COMMENT 'inferred from: optional int32
actual_elapsed_time',
  crs_elapsed_time INT COMMENT 'inferred from: optional int32
crs_elapsed_time',
  airtime INT COMMENT 'inferred from: optional int32 airtime',
  arrdelay INT COMMENT 'inferred from: optional int32 arrdelay',
  depdelay INT COMMENT 'inferred from: optional int32 depdelay',
  origin STRING COMMENT 'inferred from: optional binary origin',
  dest STRING COMMENT 'inferred from: optional binary dest',
  distance INT COMMENT 'inferred from: optional int32 distance',
  taxi_in INT COMMENT 'inferred from: optional int32 taxi_in',
  taxi_out INT COMMENT 'inferred from: optional int32 taxi_out',
  cancelled INT COMMENT 'inferred from: optional int32 cancelled',
  cancellation_code STRING COMMENT 'inferred from: optional binary
cancellation_code',
  diverted INT COMMENT 'inferred from: optional int32 diverted',
  carrier_delay INT COMMENT 'inferred from: optional int32 carrier_delay',
  weather_delay INT COMMENT 'inferred from: optional int32 weather_delay',
  nas_delay INT COMMENT 'inferred from: optional int32 nas_delay',
  security_delay INT COMMENT 'inferred from: optional int32 security_delay',
  late_aircraft_delay INT COMMENT 'inferred from: optional int32
late_aircraft_delay'
)
STORED AS PARQUET
LOCATION 'hdfs://a1730.example.com:8020/user/impala/staging/airlines'
TBLPROPERTIES ('numFiles'='0', 'COLUMN_STATS_ACCURATE'='false',
  'transient_lastDdlTime'='1439425228', 'numRows'='-1', 'totalSize'='0',
  'rawDataSize'='-1')"
```

After copying and pasting the CREATE TABLE statement into a text editor for fine-tuning, we quit and restart `impala-shell` without the `-B` option, to switch back to regular output.

Next we run the CREATE TABLE statement that we adapted from the SHOW CREATE TABLE output. We kept the STORED AS PARQUET clause because we want to rearrange the data somewhat but still keep it in the high-performance Parquet format. The LOCATION and TBLPROPERTIES clauses are not relevant for this new table, so we edit those out. Because we are going to partition the new table based on the year column, we move that column name (and its type) into a new PARTITIONED BY clause.

```

> CREATE TABLE airlines_data.airlines
(month INT,
  day INT,
  dayofweek INT,
  dep_time INT,
  crs_dep_time INT,
  arr_time INT,
  crs_arr_time INT,
  carrier STRING,
  flight_num INT,
  actual_elapsed_time INT,
  crs_elapsed_time INT,
```

```

airtime INT,
arrdelay INT,
depdelay INT,
origin STRING,
dest STRING,
distance INT,
taxi_in INT,
taxi_out INT,
cancelled INT,
cancellation_code STRING,
diverted INT,
carrier_delay INT,
weather_delay INT,
nas_delay INT,
security_delay INT,
late_aircraft_delay INT)
PARTITIONED BY (year INT)
STORED AS PARQUET
;

```

Next, we copy all the rows from the original table into this new one with an INSERT statement. (We edited the CREATE TABLE statement to make an INSERT statement with the column names in the same order.) The only change is to add a PARTITION(year) clause, and move the year column to the very end of the SELECT list of the INSERT statement. Specifying PARTITION(year), rather than a fixed value such as PARTITION(year=2000), means that Impala figures out the partition value for each row based on the value of the very last column in the SELECT list. This is the first SQL statement that legitimately takes any substantial time, because the rows from different years are shuffled around the cluster; the rows that go into each partition are collected on one node, before being written to one or more new data files.

```

> INSERT INTO airlines_data.airlines
PARTITION (year)
SELECT
  month,
  day,
  dayofweek,
  dep_time,
  crs_dep_time,
  arr_time,
  crs_arr_time,
  carrier,
  flight_num,
  actual_elapsed_time,
  crs_elapsed_time,
  airtime,
  arrdelay,
  depdelay,
  origin,
  dest,
  distance,
  taxi_in,
  taxi_out,
  cancelled,
  cancellation_code,
  diverted,
  carrier_delay,
  weather_delay,
  nas_delay,
  security_delay,
  late_aircraft_delay,
  year
FROM airlines_data.airlines_external;

```

Once partitioning or join queries come into play, it's important to have statistics that Impala can use to optimize queries on the corresponding tables. The `COMPUTE INCREMENTAL STATS` statement is the way to collect statistics for partitioned tables. Then the `SHOW TABLE STATS` statement confirms that the statistics are in place for each partition, and also illustrates how many files and how much raw data is in each partition.

```
> COMPUTE INCREMENTAL STATS airlines;
```

```
+-----+
| summary                                     |
+-----+
| Updated 22 partition(s) and 27 column(s). |
+-----+
```

```
> SHOW TABLE STATS airlines;
```

```
+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+
+-----+
| year   | #Rows   | #Files | Size   | Bytes Cached | Cache Replication |
| Format | Incremental stats | Location | EC Policy |
+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+
+-----+
| 1987   | 1311826 | 1      | 11.75MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1987 | NONE
| 1988   | 5202096 | 1      | 44.04MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1988 | NONE
| 1989   | 5041200 | 1      | 46.07MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1989 | NONE
| 1990   | 5270893 | 1      | 46.25MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1990 | NONE
| 1991   | 5076925 | 1      | 46.77MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1991 | NONE
| 1992   | 5092157 | 1      | 48.21MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1992 | NONE
| 1993   | 5070501 | 1      | 47.46MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1993 | NONE
| 1994   | 5180048 | 1      | 47.47MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1994 | NONE
| 1995   | 5327435 | 1      | 62.40MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1995 | NONE
| 1996   | 5351983 | 1      | 62.93MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1996 | NONE
| 1997   | 5411843 | 1      | 65.05MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1997 | NONE
| 1998   | 5384721 | 1      | 62.21MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1998 | NONE
| 1999   | 5527884 | 1      | 65.10MB | NOT CACHED   | NOT CACHED
| PARQUET | true    |        |         |              |
airline_data.db/airlines/year=1999 | NONE
```

```

| 2000 | 5683047 | 1 | 67.68MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2000 | NONE | | | | |
| 2001 | 5967780 | 1 | 74.03MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2001 | NONE | | | | |
| 2002 | 5271359 | 1 | 74.00MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2002 | NONE | | | | |
| 2003 | 6488540 | 1 | 99.35MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2003 | NONE | | | | |
| 2004 | 7129270 | 1 | 123.29MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2004 | NONE | | | | |
| 2005 | 7140596 | 1 | 120.72MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2005 | NONE | | | | |
| 2006 | 7141922 | 1 | 121.88MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2006 | NONE | | | | |
| 2007 | 7453215 | 1 | 130.87MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2007 | NONE | | | | |
| 2008 | 7009728 | 1 | 123.14MB | NOT CACHED | NOT CACHED
| PARQUET | true | | | | |
| airline_data.db/airlines/year=2008 | NONE | | | | |
| Total | 123534969 | 22 | 1.55GB | 0B | |
| | | | | | |
+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+
+-----+

```

At this point, we sanity check the partitioning we did. All the partitions have exactly one file, which is on the low side. A query that includes a clause `WHERE year=2004` will only read a single data block; that data block will be read and processed by a single data node; therefore, for a query targeting a single year, all the other nodes in the cluster will sit idle while all the work happens on a single machine. It's even possible that by chance (depending on HDFS replication factor and the way data blocks are distributed across the cluster), that multiple year partitions selected by a filter such as `WHERE year BETWEEN 1999 AND 2001` could all be read and processed by the same data node. The more data files each partition has, the more parallelism you can get and the less probability of “hotspots” occurring on particular nodes, therefore a bigger performance boost by having a big cluster.

However, the more data files, the less data goes in each one. The overhead of dividing the work in a parallel query might not be worth it if each node is only reading a few megabytes. 50 or 100 megabytes is a decent size for a Parquet data block; 9 or 37 megabytes is on the small side. Which is to say, the data distribution we ended up with based on this partitioning scheme is on the borderline between sensible (reasonably large files) and suboptimal (few files in each partition). The way to see how well it works in practice is to run the same queries against the original flat table and the new partitioned table, and compare times.

Spoiler: in this case, with my particular 4-node cluster with its specific distribution of data blocks and my particular exploratory queries, queries against the partitioned table do consistently run faster than the same queries against the unpartitioned table. But I could not be sure that would be the case without some real measurements. Here are some queries I ran to draw that conclusion, first against `airlines_external` (no partitioning), then against `AIRLINES` (partitioned by year). The `AIRLINES` queries are consistently faster. Changing the volume of data, changing the size of the cluster, running queries that did or didn't refer to the partition key columns, or other factors could change the results to favor one table layout or the other.

Note: If you find the volume of each partition is only in the low tens of megabytes, consider lowering the granularity of partitioning. For example, instead of partitioning by year, month, and day, partition by year and month or even just

by year. The ideal layout to distribute work efficiently in a parallel query is many tens or even hundreds of megabytes per Parquet file, and the number of Parquet files in each partition somewhat higher than the number of data nodes.

```
> SELECT SUM(airtime) FROM airlines_external;
+-----+
| 8662859484 |
+-----+

> SELECT SUM(airtime) FROM airlines;
+-----+
| 8662859484 |
+-----+

> SELECT SUM(airtime) FROM airlines_external WHERE year = 2005;
+-----+
| 708204026 |
+-----+

> SELECT SUM(airtime) FROM airlines WHERE year = 2005;
+-----+
| 708204026 |
+-----+
```

Now we can finally analyze this data set that from the raw data files and we didn't know what columns they contained. Let's see whether the `airtime` of a flight tends to be different depending on the day of the week. We can see that the average is a little higher on day number 6; perhaps Saturday is a busy flying day and planes have to circle for longer at the destination airport before landing.

```
> SELECT dayofweek, AVG(airtime) FROM airlines
   GROUP BY dayofweek ORDER BY dayofweek;
+-----+-----+
| dayofweek | avg(airtime) |
+-----+-----+
| 1         | 102.1560425016671 |
| 2         | 102.1582931538807 |
| 3         | 102.2170009256653 |
| 4         | 102.37477661846   |
| 5         | 102.2697358763511 |
| 6         | 105.3627448363705 |
| 7         | 103.4144351202054 |
+-----+-----+
```

To see if the apparent trend holds up over time, let's do the same breakdown by day of week, but also split up by year. Now we can see that day number 6 consistently has a higher average air time in each year. We can also see that the average air time increased over time across the board. And the presence of `NULL` for this column in years 1987 to 1994 shows that queries involving this column need to be restricted to a date range of 1995 and higher.

```
> SELECT year, dayofweek, AVG(airtime) FROM airlines
   GROUP BY year, dayofweek ORDER BY year DESC, dayofweek;
+-----+-----+-----+
| year | dayofweek | avg(airtime) |
+-----+-----+-----+
| 2008 | 1         | 103.1821651651355 |
| 2008 | 2         | 103.2149301386094 |
| 2008 | 3         | 103.0585076622796 |
| 2008 | 4         | 103.4671383539038 |
| 2008 | 5         | 103.5575385182659 |
| 2008 | 6         | 107.4006306562128 |
| 2008 | 7         | 104.8648851041755 |
| 2007 | 1         | 102.2196114337825 |
| 2007 | 2         | 101.9317791906348 |
| 2007 | 3         | 102.0964767689043 |
+-----+-----+-----+
```


2007	4	102.6215927201686
2007	5	102.4289399000661
2007	6	105.1477448215756
2007	7	103.6305945644095
...		
1996	1	99.33860750862108
1996	2	99.54225446396656
1996	3	99.41129336113134
1996	4	99.5110373340348
1996	5	99.22120745027595
1996	6	101.1717447111921
1996	7	99.95410136133704
1995	1	96.93779698300494
1995	2	96.93458674589712
1995	3	97.00972311337051
1995	4	96.90843832024412
1995	5	96.78382115425562
1995	6	98.70872826057003
1995	7	97.85570478374616
1994	1	NULL
1994	2	NULL
1994	3	NULL
...		
1987	5	NULL
1987	6	NULL
1987	7	NULL

Impala Administration

As an administrator, you monitor Impala's use of resources and take action when necessary to keep Impala running smoothly and avoid conflicts with other Hadoop components running on the same cluster. When you detect that an issue has happened or could happen in the future, you reconfigure Impala or other components such as HDFS or even the hardware of the cluster itself to resolve or avoid problems.

Related tasks:

As an administrator, you can expect to perform installation, upgrade, and configuration tasks for Impala on all machines in a cluster. See [Installing Impala](#) on page 25, [Upgrading Impala](#) on page 28, and [Managing Impala](#) on page 26 for details.

For security tasks typically performed by administrators, see [Impala Security](#) on page 78.

Administrators also decide how to allocate cluster resources so that all Hadoop components can run smoothly together. For Impala, this task primarily involves:

- Deciding how many Impala queries can run concurrently and with how much memory, through the admission control feature. See [Admission Control and Query Queuing](#) on page 675 for details.
- Dividing cluster resources such as memory between Impala and other components, using YARN for overall resource management, and Llama to mediate resource requests from Impala to YARN. See [Resource Management](#) on page 675 for details.

Setting Timeout Periods for Daemons, Queries, and Sessions

Depending on how busy your cluster is, you might increase or decrease various timeout values. Increase timeouts if Impala is cancelling operations prematurely, when the system is responding slower than usual but the operations are still successful if given extra time. Decrease timeouts if operations are idle or hanging for long periods, and the idle or hung operations are consuming resources and reducing concurrency.

Increasing the Statestore Timeout

If you have an extensive Impala schema, for example with hundreds of databases, tens of thousands of tables, and so on, you might encounter timeout errors during startup as the Impala catalog service broadcasts metadata to all the Impala nodes using the statestore service. To avoid such timeout errors on startup, increase the statestore timeout value from its default of 10 seconds. Specify the timeout value using the `--statestore_subscriber_timeout_seconds` option for the statestore service, using the configuration instructions in [Modifying Impala Startup Options](#) on page 32. The symptom of this problem is messages in the `impalad` log such as:

```
Connection with state-store lost
Trying to re-register with state-store
```

See [Scalability Considerations for the Impala Statestore](#) on page 658 for more details about statestore operation and settings on clusters with a large number of Impala-related objects such as tables and partitions.

Setting the Idle Query and Idle Session Timeouts for impalad

To keep long-running queries or idle sessions from tying up cluster resources, you can set timeout intervals for both individual queries, and entire sessions.

Note:

The timeout clock for queries and sessions only starts ticking when the query or session is idle.

For queries, this means the query has results ready but is waiting for a client to fetch the data. A query can run for an arbitrary time without triggering a timeout, because the query is computing results rather than sitting idle waiting for the results to be fetched. The timeout period is intended to prevent unclosed queries from consuming resources and taking up slots in the admission count of running queries, potentially preventing other queries from starting.

For sessions, this means that no query has been submitted for some period of time.

Use the following startup options for the `impalad` daemon to specify timeout values:

- `--idle_query_timeout`

Specifies the time in seconds after which an idle query is cancelled. This could be a query whose results were all fetched but was never closed, or one whose results were partially fetched and then the client program stopped requesting further results. This condition is most likely to occur in a client program using the JDBC or ODBC interfaces, rather than in the interactive `impala-shell` interpreter. Once a query is cancelled, the client program cannot retrieve any further results from the query.

You can reduce the idle query timeout by using the `QUERY_TIMEOUT_S` query option. Any non-zero value specified for the `--idle_query_timeout` startup option serves as an upper limit for the `QUERY_TIMEOUT_S` query option. See [QUERY_TIMEOUT_S Query Option \(Impala 2.0 or higher only\)](#) on page 385 about the query option.

A zero value for `--idle_query_timeout` disables query timeouts.

Cancelled queries are closed, but the client can still fetch their exception details. If the query was in a good state when cancelled, it will present an error like "Query 6f49e509bfa5b347:207d8ef900000000 expired due to client inactivity", otherwise it will show the relevant error.

- `--idle_session_timeout`

Specifies the time in seconds after which an idle session expires. A session is idle when no activity is occurring for any of the queries in that session, and the session has not started any new queries. Once a session is expired, you cannot issue any new query requests to it. The session remains open, but the only operation you can perform is to close it.

The default value of 0 specifies sessions never expire.

You can override the `--idle_session_timeout` value with the [IDLE_SESSION_TIMEOUT Query Option \(Impala 2.12 or higher only\)](#) on page 363 at the session level.

For instructions on changing `impalad` startup options, see [Modifying Impala Startup Options](#) on page 32.

Note:

Impala checks periodically for idle sessions and queries to cancel. The actual idle time before cancellation might be up to 50% greater than the specified configuration setting. For example, if the timeout setting was 60, the session or query might be cancelled after being idle between 60 and 90 seconds.

Setting Timeout and Retries for Thrift Connections to the Backend Client

Impala connections to the backend client are subject to failure in cases when the network is momentarily overloaded. To avoid failed queries due to transient network problems, you can configure the number of Thrift connection retries using the following option:

- The `--backend_client_connection_num_retries` option specifies the number of times Impala will try connecting to the backend client after the first connection attempt fails. By default, `impalad` will attempt three re-connections before it returns a failure.

You can configure timeouts for sending and receiving data from the backend client. Therefore, if for some reason a query hangs, instead of waiting indefinitely for a response, Impala will terminate the connection after a configurable timeout.

- The `--backend_client_rpc_timeout_ms` option can be used to specify the number of milliseconds Impala should wait for a response from the backend client before it terminates the connection and signals a failure. The default value for this property is 300000 milliseconds, or 5 minutes.

Cancelling a Query

Occasionally, an Impala query might run for an unexpectedly long time, tying up resources in the cluster. This section describes the options to terminate such runaway queries.

Setting a Time Limit on Query Execution

An Impala administrator can set a default value of the `EXEC_TIME_LIMIT_S` query option for a resource pool. If a user accidentally runs a large query that executes for longer than the limit, it will be automatically terminated after the time limit expires to free up resources.

You can override the default value per query or per session if you do not want to apply the default `EXEC_TIME_LIMIT_S` value to a specific query or a session. See [EXEC_TIME_LIMIT_S Query Option \(Impala 2.12 or higher only\)](#) on page 357 for the details of the query option.

Interactively Cancelling a Query

You can cancel the query explicitly, independent of the timeout period, by going into the web UI for the `impalad` host (on port 25000 by default), and using the link on the `/queries` tab to cancel the running query.

Various client applications let you interactively cancel queries submitted or monitored through those applications. For example:

- Press `^C` in `impala-shell`.
- Click **Cancel** from the **Watchpage** in Hue.

Using Impala through a Proxy for High Availability

For most clusters that have multiple users and production availability requirements, you might want to set up a load-balancing proxy server to relay requests to and from Impala.

Set up a software package of your choice to perform these functions.

Note:

Most considerations for load balancing and high availability apply to the `impalad` daemon. The `statelord` and `catalogd` daemons do not have special requirements for high availability, because problems with those daemons do not result in data loss. If those daemons become unavailable due to an outage on a particular host, you can stop the Impala service, delete the **Impala StateStore** and **Impala Catalog Server** roles, add the roles on a different host, and restart the Impala service.

Overview of Proxy Usage and Load Balancing for Impala

Using a load-balancing proxy server for Impala has the following advantages:

- Applications connect to a single well-known host and port, rather than keeping track of the hosts where the `impalad` daemon is running.
- If any host running the `impalad` daemon becomes unavailable, application connection requests still succeed because you always connect to the proxy server rather than a specific host running the `impalad` daemon.
- The coordinator node for each Impala query potentially requires more memory and CPU cycles than the other nodes that process the query. The proxy server can issue queries so that each connection uses a different coordinator node. This load-balancing technique lets the `impalad` nodes share this additional work, rather than concentrating it on a single machine.

The following setup steps are a general outline that apply to any load-balancing proxy software:

1. Select and download the load-balancing proxy software or other load-balancing hardware appliance. It should only need to be installed and configured on a single host, typically on an edge node.
2. Configure the load balancer (typically by editing a configuration file). In particular:
 - To relay Impala requests back and forth, set up a port that the load balancer will listen on.
 - Select a load balancing algorithm. See [Choosing the Load-Balancing Algorithm](#) on page 68 for load balancing algorithm options.
 - For Kerberized clusters, follow the instructions in [Special Proxy Considerations for Clusters Using Kerberos](#) on page 69.
3. If you are using Hue or JDBC-based applications, you typically set up load balancing for both ports 21000 and 21050 because these client applications connect through port 21050 while the `impala-shell` command connects through port 21000. See [Ports Used by Impala](#) on page 820 for when to use port 21000, 21050, or another value depending on what type of connections you are load balancing.
4. Run the load-balancing proxy server, pointing it at the configuration file that you set up.
5. For any scripts, jobs, or configuration settings for applications that formerly connected to a specific `impalad` to run Impala SQL statements, change the connection information (such as the `-i` option in `impala-shell`) to point to the load balancer instead.

Note: The following sections use the HAProxy software as a representative example of a load balancer that you can use with Impala.

Choosing the Load-Balancing Algorithm

Load-balancing software offers a number of algorithms to distribute requests. Each algorithm has its own characteristics that make it suitable in some situations but not others.

Leastconn

Connects sessions to the coordinator with the fewest connections, to balance the load evenly. Typically used for workloads consisting of many independent, short-running queries. In configurations with only a few client machines, this setting can avoid having all requests go to only a small set of coordinators.

Recommended for Impala with F5.

Source IP Persistence

Sessions from the same IP address always go to the same coordinator. A good choice for Impala workloads containing a mix of queries and DDL statements, such as `CREATE TABLE` and `ALTER TABLE`. Because the metadata changes from a DDL statement take time to propagate across the cluster, prefer to use the Source IP Persistence in this case. If you are unable to choose Source IP Persistence, run the DDL and subsequent queries that depend on the results of the DDL through the same session, for example by running `impala-shell -f script_file` to submit several statements through a single session.

Required for setting up high availability with Hue.

Round-robin

Distributes connections to all coordinator nodes. Typically not recommended for Impala.

You might need to perform benchmarks and load testing to determine which setting is optimal for your use case. Always set up using two load-balancing algorithms: Source IP Persistence for Hue and Leastconn for others.

Special Proxy Considerations for Clusters Using Kerberos

In a cluster using Kerberos, applications check host credentials to verify that the host they are connecting to is the same one that is actually processing the request.

In Impala 2.11 and lower versions, once you enable a proxy server in a Kerberized cluster, users will not be able to connect to individual impala daemons directly from `impala-shell`.

In Impala 2.12 and higher versions, when you enable a proxy server in a Kerberized cluster, users have an option to connect to Impala daemons directly from `impala-shell` using the `-b/--kerberos_host_fqdn` `impala-shell` flag. This option can be used for testing or troubleshooting purposes, but not recommended for live production environments as it defeats the purpose of a load balancer/proxy.

Example:

```
impala-shell -i impalad-1.mydomain.com -k -b loadbalancer-1.mydomain.com
```

Alternatively, with the fully qualified configurations:

```
impala-shell --impalad=impalad-1.mydomain.com:21000 --kerberos --kerberos_host_fqdn=loadbalancer-1.mydomain.com
```

See [impala-shell Configuration Options](#) on page 791 for information about the option.

To validate the load-balancing proxy server, perform these extra Kerberos setup steps:

1. This section assumes you are starting with a Kerberos-enabled cluster. See [Enabling Kerberos Authentication for Impala](#) on page 90 for instructions for setting up Impala with Kerberos. See the documentation for your Apache Hadoop distribution for general steps to set up Kerberos.
2. Choose the host you will use for the proxy server. Based on the Kerberos setup procedure, it should already have an entry `impala/proxy_host@realm` in its keytab. If not, go back over the initial Kerberos configuration steps for the keytab on each host running the `impalad` daemon.
3. Copy the keytab file from the proxy host to all other hosts in the cluster that run the `impalad` daemon. Put the keytab file in a secure location on each of these other hosts.
4. Add an entry `impala/actual_hostname@realm` to the keytab on each host running the `impalad` daemon.

- For each `impalad` node, merge the existing keytab with the proxy's keytab using `ktutil`, producing a new keytab file. For example:

```
$ ktutil
ktutil: read_kt proxy.keytab
ktutil: read_kt impala.keytab
ktutil: write_kt proxy_impala.keytab
ktutil: quit
```

- To verify that the keytabs are merged, run the command:

```
klist -k keytabfile
```

The command lists the credentials for both `principal` and `be_principal` on all nodes.

- Make sure that the `impala` user has the permission to read this merged keytab file.
- For each coordinator `impalad` host in the cluster that participates in the load balancing, add the following configuration options to receive client connections coming through the load balancer proxy server:

```
--principal=impala/proxy_host@realm
--be_principal=impala/actual_host@realm
--keytab_file=path_to_merged_keytab
```

The `--principal` setting prevents a client from connecting to a coordinator `impalad` using a principal other than one specified.

Note: Every host has different `--be_principal` because the actual host name is different on each host. Specify the fully qualified domain name (FQDN) for the proxy host, not the IP address. Use the exact FQDN as returned by a reverse DNS lookup for the associated IP address.

- Restart Impala to make the changes take effect. Restart the `impalad` daemons on all hosts in the cluster, as well as the `statestored` and `catalogd` daemons.

Client Connection to Proxy Server in Kerberized Clusters

When a client connect to Impala, the service principal specified by the client must match the `--principal` setting of the Impala proxy server. And the client should connect to the proxy server port.

In `hue.ini`, set the following to configure Hue to automatically connect to the proxy server:

```
[impala]
server_host=proxy_host
impala_principal=impala/proxy_host
```

The following are the JDBC connection string formats when connecting through the load balancer with the load balancer's host name in the principal:

```
jdbc:hive2://proxy_host:load_balancer_port/;principal=impala/_HOST@realm
jdbc:hive2://proxy_host:load_balancer_port/;principal=impala/proxy_host@realm
```

When starting `impala-shell`, specify the service principal via the `-b` or `--kerberos_host_fqdn` flag.

Special Proxy Considerations for TLS/SSL Enabled Clusters

When TLS/SSL is enabled for Impala, the client application, whether `impala-shell`, Hue, or something else, expects the certificate common name (CN) to match the hostname that it is connected to. With no load balancing proxy server, the hostname and certificate CN are both that of the `impalad` instance. However, with a proxy server, the certificate presented by the `impalad` instance does not match the load balancing proxy server hostname. If you try to

load-balance a TLS/SSL-enabled Impala installation without additional configuration, you see a certificate mismatch error when a client attempts to connect to the load balancing proxy host.

You can configure a proxy server in several ways to load balance TLS/SSL enabled Impala:

TLS/SSL Bridging

In this configuration, the proxy server presents a TLS/SSL certificate to the client, decrypts the client request, then re-encrypts the request before sending it to the backend `impalad`. The client and server certificates can be managed separately. The request or resulting payload is encrypted in transit at all times.

TLS/SSL Passthrough

In this configuration, traffic passes through to the backend `impalad` instance with no interaction from the load balancing proxy server. Traffic is still encrypted end-to-end.

The same server certificate, utilizing either wildcard or Subject Alternate Name (SAN), must be installed on each `impalad` instance.

TLS/SSL Offload

In this configuration, all traffic is decrypted on the load balancing proxy server, and traffic between the backend `impalad` instances is unencrypted. This configuration presumes that cluster hosts reside on a trusted network and only external client-facing communication need to be encrypted in-transit.

Refer to your load balancer documentation for the steps to set up Impala and the load balancer using one of the options above.

Example of Configuring HAProxy Load Balancer for Impala

If you are not already using a load-balancing proxy, you can experiment with [HAProxy](#) a free, open source load balancer. This example shows how you might install and configure that load balancer on a Red Hat Enterprise Linux system.

- Install the load balancer:

```
yum install haproxy
```

- Set up the configuration file: `/etc/haproxy/haproxy.cfg`. See the following section for a sample configuration file.
- Run the load balancer (on a single host, preferably one not running `impalad`):

```
/usr/sbin/haproxy -f /etc/haproxy/haproxy.cfg
```

- In `impala-shell`, JDBC applications, or ODBC applications, connect to the listener port of the proxy host, rather than port 21000 or 21050 on a host actually running `impalad`. The sample configuration file sets haproxy to listen on port 25003, therefore you would send all requests to `haproxy_host:25003`.

This is the sample `haproxy.cfg` used in this example:

```
global
    # To have these messages end up in /var/log/haproxy.log you will
    # need to:
    #
    # 1) configure syslog to accept network log events.  This is done
    #    by adding the '-r' option to the SYSLOGD_OPTIONS in
    #    /etc/sysconfig/syslog
    #
    # 2) configure local2 events to go to the /var/log/haproxy.log
```

```

# file. A line like the following can be added to
# /etc/sysconfig/syslog
#
# local2.* /var/log/haproxy.log
#
log 127.0.0.1 local0
log 127.0.0.1 local1 notice
chroot /var/lib/haproxy
pidfile /var/run/haproxy.pid
maxconn 4000
user haproxy
group haproxy
daemon

# turn on stats unix socket
#stats socket /var/lib/haproxy/stats

#-----
# common defaults that all the 'listen' and 'backend' sections will
# use if not designated in their block
#
# You might need to adjust timing values to prevent timeouts.
#
# The timeout values should be dependant on how you use the cluster
# and how long your queries run.
#-----
defaults
    mode http
    log global
    option httplog
    option dontlognull
    option http-server-close
    option forwardfor except 127.0.0.0/8
    option redispatch
    retries 3
    maxconn 3000
    timeout connect 5000
    timeout client 3600s
    timeout server 3600s

#
# This sets up the admin page for HA Proxy at port 25002.
#
listen stats :25002
    balance
    mode http
    stats enable
    stats auth username:password

# Setup for Impala.
# Impala client connect to load_balancer_host:25003.
# HAProxy will balance connections among the list of servers listed below.
# The list of Impalad is listening at port 21000 for beeswax (impala-shell)
# or original ODBC driver.
# For JDBC or ODBC version 2.x driver, use port 21050 instead of 21000.
listen impala :25003
    mode tcp
    option tcplog
    balance leastconn

server symbolic_name_1 impala-host-1.example.com:21000 check
server symbolic_name_2 impala-host-2.example.com:21000 check
server symbolic_name_3 impala-host-3.example.com:21000 check
server symbolic_name_4 impala-host-4.example.com:21000 check

```



```
# Setup for Hue or other JDBC-enabled applications.
# In particular, Hue requires sticky sessions.
# The application connects to load_balancer_host:21051, and HAProxy balances
# connections to the associated hosts, where Impala listens for
# JDBC requests at port 21050.
listen impalajdbc :21051
    mode tcp
    option tcplog
    balance source

    server symbolic_name_5 impala-host-1.example.com:21050 check
    server symbolic_name_6 impala-host-2.example.com:21050 check
    server symbolic_name_7 impala-host-3.example.com:21050 check
    server symbolic_name_8 impala-host-4.example.com:21050 check
```

Important: Hue requires the `check` option at end of each line in the above file to ensure HAProxy can detect any unreachable Impalad server, and failover can be successful. Without the TCP check, you may hit an error when the `impalad` daemon to which Hue tries to connect is down.

Note: If your JDBC or ODBC application connects to Impala through a load balancer such as haproxy, be cautious about reusing the connections. If the load balancer has set up connection timeout values, either check the connection frequently so that it never sits idle longer than the load balancer timeout value, or check the connection validity before using it and create a new one if the connection has been closed.

Managing Disk Space for Impala Data

Although Impala typically works with many large files in an HDFS storage system with plenty of capacity, there are times when you might perform some file cleanup to reclaim space, or advise developers on techniques to minimize space consumption and file duplication.

- Use compact binary file formats where practical. Numeric and time-based data in particular can be stored in more compact form in binary data files. Depending on the file format, various compression and encoding features can reduce file size even further. You can specify the `STORED AS` clause as part of the `CREATE TABLE` statement, or `ALTER TABLE` with the `SET FILEFORMAT` clause for an existing table or partition within a partitioned table. See [How Impala Works with Hadoop File Formats](#) on page 695 for details about file formats, especially [Using the Parquet File Format with Impala Tables](#) on page 705. See [CREATE TABLE Statement](#) on page 248 and [ALTER TABLE Statement](#) on page 215 for syntax details.
- You manage underlying data files differently depending on whether the corresponding Impala table is defined as an [internal](#) or [external](#) table:
 - Use the `DESCRIBE FORMATTED` statement to check if a particular table is internal (managed by Impala) or external, and to see the physical location of the data files in HDFS. See [DESCRIBE Statement](#) on page 268 for details.
 - For Impala-managed (“internal”) tables, use `DROP TABLE` statements to remove data files. See [DROP TABLE Statement](#) on page 289 for details.
 - For tables not managed by Impala (“external” tables), use appropriate HDFS-related commands such as `hadoop fs`, `hdfs dfs`, or `distcp`, to create, move, copy, or delete files within HDFS directories that are accessible by the `impala` user. Issue a `REFRESH table_name` statement after adding or removing any files from the data directory of an external table. See [REFRESH Statement](#) on page 312 for details.
 - Use external tables to reference HDFS data files in their original location. With this technique, you avoid copying the files, and you can map more than one Impala table to the same set of data files. When you drop the Impala table, the data files are left undisturbed. See [External Tables](#) on page 207 for details.
 - Use the `LOAD DATA` statement to move HDFS files into the data directory for an Impala table from inside Impala, without the need to specify the HDFS path of the destination directory. This technique works for both internal and external tables. See [LOAD DATA Statement](#) on page 309 for details.
- Make sure that the HDFS trashcan is configured correctly. When you remove files from HDFS, the space might not be reclaimed for use by other files until sometime later, when the trashcan is emptied. See [DROP TABLE](#)

[Statement](#) on page 289 for details. See [User Account Requirements](#) on page 23 for permissions needed for the HDFS trashcan to operate correctly.

- Drop all tables in a database before dropping the database itself. See [DROP DATABASE Statement](#) on page 280 for details.
- Clean up temporary files after failed INSERT statements. If an INSERT statement encounters an error, and you see a directory named `.impala_insert_staging` or `_impala_insert_staging` left behind in the data directory for the table, it might contain temporary data files taking up space in HDFS. You might be able to salvage these data files, for example if they are complete but could not be moved into place due to a permission error. Or, you might delete those files through commands such as `hadoop fs` or `hdfs dfs`, to reclaim space before re-trying the INSERT. Issue `DESCRIBE FORMATTED table_name` to see the HDFS path where you can check for temporary files.
- If you use the Amazon Simple Storage Service (S3) as a place to offload data to reduce the volume of local storage, Impala 2.2.0 and higher can query the data directly from S3. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details.

Configuring Scratch Space for Spilling to Disk

Impala uses intermediate files during large sort, join, aggregation, or analytic function operations. The files are removed when the operation finishes. You can specify locations of the intermediate files by starting the `impalad` daemon with the `--scratch_dirs="path_to_directory"` configuration option. By default, intermediate files are stored in the directory `/tmp/impala-scratch`.

- You can specify a single directory or a comma-separated list of directories.
- You can specify an optional capacity quota per scratch directory using the colon (:) as the delimiter.

The capacity quota of `-1` or `0` is the same as no quota for the directory.

- The scratch directories must be on the local filesystem, not in HDFS.
- You might specify different directory paths for different hosts, depending on the capacity and speed of the available storage devices.

If there is less than 1 GB free on the filesystem where that directory resides, Impala still runs, but writes a warning message to its log.

Impala successfully starts (with a warning written to the log) if it cannot create or read and write files in one of the scratch directories.

The following are examples for specifying scratch directories.

Config option	Description
<code>--scratch_dirs=/dir1,/dir2</code>	Use <code>/dir1</code> and <code>/dir2</code> as scratch directories with no capacity quota.
<code>--scratch_dirs=/dir1,/dir2:25G</code>	Use <code>/dir1</code> and <code>/dir2</code> as scratch directories with no capacity quota on <code>/dir1</code> and the 25GB quota on <code>/dir2</code> .
<code>--scratch_dirs=/dir1:5MB,/dir2</code>	Use <code>/dir1</code> and <code>/dir2</code> as scratch directories with the capacity quota of 5MB on <code>/dir1</code> and no quota on <code>/dir2</code> .
<code>--scratch_dirs=/dir1:-1,/dir2:0</code>	Use <code>/dir1</code> and <code>/dir2</code> as scratch directories with no capacity quota.

Allocation from a scratch directory will fail if the specified limit for the directory is exceeded.

If Impala encounters an error reading or writing files in a scratch directory during a query, Impala logs the error, and the query fails.

Priority Based Scratch Directory Selection

The location of the intermediate files are configured by starting the `impalad` daemon with the flag `--scratch_dirs="path_to_directory"`. Currently this startup flag uses the configured scratch directories

in a round robin fashion. Automatic selection of scratch directories in a round robin fashion may not always be ideal in every situation since these directories could come from different classes of storage system volumes having different performance characteristics (SSD vs HDD, local storage vs network attached storage, etc.). To optimize your workload, you have an option to configure the priority of the scratch directories based on your storage system configuration.

The scratch directories will be selected for spilling based on how you configure the priorities of the directories and if you provide the same priority for multiple directories then the directories will be selected in a round robin fashion.

The valid formats for specifying the priority directories are as shown here:

```
dir-path:limit:priority
dir-path::priority
```

Example:

```
/dir1:200GB:0
/dir1::0
```

The following formats use the default priority:

```
/dir1
/dir1:200GB
/dir1:200GB:
```

In the example below, dir1 will be used as a spill victim until it is full and then dir2, dir3, and dir4 will be used in a round robin fashion.

```
--scratch_dirs="/dir1:200GB:0, /dir2:1024GB:1, /dir3:1024GB:1, /
dir4:1024GB:1"
```

Increasing Scratch Capacity

You can compress the data spilled to disk to increase the effective scratch capacity. You typically more than double capacity using compression and reduce spilling to disk. Use the `--disk_spill_compression_codec` and `--disk_spill_punch_holes` startup options. The `--disk_spill_compression_codec` takes any value supported by the `COMPRESSION_CODEC` query option. The value is not case-sensitive. A value of `ZSTD` or `LZ4` is recommended (default is `NONE`).

For example:

```
--disk_spill_compression_codec=LZ4
--disk_spill_punch_holes=true
```

If you set `--disk_spill_compression_codec` to a value other than `NONE`, you must set `--disk_spill_punch_holes` to `true`.

The hole punching feature supported by many filesystems is used to reclaim space in scratch files during execution of a query that spills to disk. This results in lower scratch space requirements in many cases, especially when combined with disk spill compression. When this option is not enabled, scratch space is still recycled by a query, but less effectively in many cases.

You can specify a compression level for `ZSTD` only. For example:

```
--disk_spill_compression_codec=ZSTD:10
--disk_spill_punch_holes=true
```

Compression levels from 1 up to 22 (default 3) are supported for `ZSTD`. The lower the compression level, the faster the speed at the cost of compression ratio.

Configure Impala Daemon to spill to S3

Impala occasionally needs to use persistent storage for writing intermediate files during large sorts, joins, aggregations, or analytic function operations. If your workload results in large volumes of intermediate data being written, it is recommended to configure the heavy spilling queries to use a remote storage location rather than the local one. The advantage of using remote storage for scratch space is that it is elastic and can handle any amount of spilling.

Before you begin

Identify the URL for an S3 bucket to which you want your new Impala to write the temporary data. If you use the S3 bucket that is associated with the environment, navigate to the S3 bucket and copy the URL. If you want to use an external S3 bucket, you must first configure your environment to use the external S3 bucket with the correct read/write permissions.

Configuring the Start-up Option in Impala daemon

You can use the Impalad start option `scratch_dirs` to specify the locations of the intermediate files. The format of the option is:

```
--scratch_dirs="remote_dir, local_buffer_dir (,local_dir...)"
```

where `local_buffer_dir` and `local_dir` conform to the earlier descriptions for scratch directories.

With the option specified above:

- You can specify only one remote directory. When you configure a remote directory, you must specify a local buffer directory as the buffer. However you can use multiple local directories with the remote directory. If you specify multiple local directories, the first local directory would be used as the local buffer directory.
- If you configure both remote and local directories, the remote directory is only used when the local directories are fully utilized.
- The size of a remote intermediate file could affect the query performance, and the value can be set by `--remote_tmp_file_size=size` in the start-up option. The default size of a remote intermediate file is 16MB while the maximum is 512MB.

Examples

- A remote scratch dir with a local buffer dir, file size 64MB.

```
--scratch_dirs=s3a://remote_dir,/local_buffer_dir --  
remote_tmp_file_size=64M
```

- A remote scratch dir with a local buffer dir limited to 256MB, and one local dir limited to 10GB.

```
--scratch_dirs=s3a://remote_dir,/local_buffer_dir:256M,/local_dir:10G
```

- A remote scratch dir with a local buffer dir, and multiple prioritized local dirs.

```
--scratch_dirs=s3a://remote_dir,/local_buffer_dir,/local_dir_1:5G:1,/local_dir_2:5G:2
```

Configure Impala Daemon to spill to HDFS

Impala occasionally needs to use persistent storage for writing intermediate files during large sorts, joins, aggregations, or analytic function operations. If your workload results in large volumes of intermediate data being written, it is recommended to configure the heavy spilling queries to use a remote storage location rather than the local one. The advantage of using remote storage for scratch space is that it is elastic and can handle any amount of spilling.

Before you begin

- Identify the HDFS scratch directory where you want your new Impala to write the temporary data.

- Identify the IP address, host name, or service identifier of HDFS.
- Identify the port number of the HDFS NameNode (if not-default).
- Configure Impala to write temporary data to disk during query processing.

Configuring the Start-up Option in Impala daemon

You can use the Impalad start option `scratch_dirs` to specify the locations of the intermediate files.

Use the following format for this start up option:

```
--scratch_dirs="hdfs://authority/path(:max_bytes), local_buffer_dir
(,local_dir...)"
```

- Where `hdfs://authority/path` is the remote directory.
- `authority` may include `ip_address` or `hostname` and `port`, or `service_id`.
- `max_bytes` is optional.

Using the above format:

- You can specify only one remote directory. When you configure a remote directory, you must specify a local buffer directory as the buffer. However you can use multiple local directories with the remote directory. If you specify multiple local directories, the first local directory would be used as the local buffer directory.
- If you configure both remote and local directories, the remote directory is only used when the local directories are fully utilized.
- The size of a remote intermediate file could affect the query performance, and the value can be set by `--remote_tmp_file_size=size` in the start-up option. The default size of a remote intermediate file is 16MB while the maximum is 512MB.

Examples

- A HDFS scratch dir with one local buffer dir, file size 64MB. The space of HDFS scratch dir is limited to 300G.

```
--scratch_dirs=hdfs://10.0.0.49:20500/tmp:300G,/local_buffer_dir --
remote_tmp_file_size=64M
```

- A HDFS scratch dir with one local buffer dir limited to 512MB, and one local dir limited to 10GB. The space of HDFS scratch dir is limited to 300G. The HDFS NameNode uses its default port (8020).

```
--scratch_dirs=hdfs://hdfsnn/tmp:300G,/local_buffer_dir:512M,/
local_dir:10G
```

- A HDFS scratch dir with one local buffer dir, and multiple prioritized local dirs. The space of HDFS scratch dir is unlimited. The HDFS service identifier is `hdfs1`.

```
--scratch_dirs=hdfs://hdfs1/tmp,/local_buffer_dir,/local_dir_1:5G:1,/
local_dir_2:5G:2
```

Even though `max_bytes` is optional, it is highly recommended to configure for spilling to HDFS because the HDFS cluster space is limited.

Configure Impala Daemon to spill to Ozone

Before you begin

- Identify the Ozone scratch directory where you want your new Impala to write the temporary data.
- Identify the IP address, host name, or service identifier of Ozone.
- Identify the port number of the Ozone Manager (if not-default).

Configuring the Start-up Option in Impala daemon

You can use the Impalad start option `scratch_dirs` to specify the locations of the intermediate files.

```
--scratch_dirs="ofs://authority/path(:max_bytes), local_buffer_dir
(,local_dir...)"
```

- Where `ofs://authority/path` is the remote directory.
- `authority` may include `ip_address` or `hostname` and `port`, or `service_id`.
- `max_bytes` is optional.

Using the above format:

- You can specify only one remote directory. When you configure a remote directory, you must specify a local buffer directory as the buffer. However you can use multiple local directories with the remote directory. If you specify multiple local directories, the first local directory would be used as the local buffer directory.
- If you configure both remote and local directories, the remote directory is only used when the local directories are fully utilized.
- The size of a remote intermediate file could affect the query performance, and the value can be set by `--remote_tmp_file_size=size` in the start-up option. The default size of a remote intermediate file is 16MB while the maximum is 512MB.

Examples

- An Ozone scratch dir with one local buffer dir, file size 64MB. The space of Ozone scratch dir is limited to 300G.

```
--scratch_dirs=ofs://10.0.0.49:29000/tmp:300G,/local_buffer_dir --
remote_tmp_file_size=64M
```

- An Ozone scratch dir with one local buffer dir limited to 512MB, and one local dir limited to 10GB. The space of Ozone scratch dir is limited to 300G. The Ozone Manager uses its default port (9862).

```
--scratch_dirs=ofs://ozonemgr/tmp:300G,/local_buffer_dir:512M,/
local_dir:10G
```

- An Ozone scratch dir with one local buffer dir, and multiple prioritized local dirs. The space of Ozone scratch dir is unlimited. The Ozone service identifier is `ozone1`.

```
--scratch_dirs=ofs://ozone1/tmp,/local_buffer_dir,/local_dir_1:5G:1,/
local_dir_2:5G:2
```

Even though `max_bytes` is optional, it is highly recommended to configure for spilling to Ozone because the Ozone cluster space is limited.

Impala Security

Impala includes a fine-grained authorization framework for Hadoop, based on Apache Ranger. Ranger authorization was added in Impala 3.3.0. Together with the Kerberos authentication framework, Ranger takes Hadoop security to a new level needed for the requirements of highly regulated industries such as healthcare, financial services, and government. Impala also includes an auditing capability which was added in Impala 1.1.1; Impala generates the audit data which can be consumed, filtered, and visualized by cluster-management components focused on governance.

The Impala security features have several objectives. At the most basic level, security prevents accidents or mistakes that could disrupt application processing, delete or corrupt data, or reveal data to unauthorized users. More advanced security features and practices can harden the system against malicious users trying to gain unauthorized access or perform other disallowed operations. The auditing feature provides a way to confirm that no unauthorized access occurred, and detect whether any such attempts were made. This is a critical set of features for production deployments in large organizations that handle important or sensitive data. It sets the stage for multi-tenancy, where multiple applications run concurrently and are prevented from interfering with each other.

The material in this section presumes that you are already familiar with administering secure Linux systems. That is, you should know the general security practices for Linux and Hadoop, and their associated commands and configuration files. For example, you should know how to create Linux users and groups, manage Linux group membership, set Linux and HDFS file permissions and ownership, and designate the default permissions and ownership for new files. You should be familiar with the configuration of the nodes in your Hadoop cluster, and know how to apply configuration changes or run a set of commands across all the nodes.

The security features are divided into these broad categories:

authorization

Which users are allowed to access which resources, and what operations are they allowed to perform? Impala relies on the open source Ranger project for authorization. By default (when authorization is not enabled), Impala does all read and write operations with the privileges of the `impala` user, which is suitable for a development/test environment but not for a secure production environment. When authorization is enabled, Impala uses the OS user ID of the user who runs `impala-shell` or other client program, and associates various privileges with each user. See [Impala Authorization](#) on page 83 for details about setting up and managing authorization.

authentication

How does Impala verify the identity of the user to confirm that they really are allowed to exercise the privileges assigned to that user? Impala relies on the Kerberos subsystem for authentication. See [Enabling Kerberos Authentication for Impala](#) on page 90 for details about setting up and managing authentication.

auditing

What operations were attempted, and did they succeed or not? This feature provides a way to look back and diagnose whether attempts were made to perform unauthorized operations. You use this information to track down suspicious activity, and to see where changes are needed in authorization policies. The audit data produced by this feature can be collected and presented in a user-friendly form by cluster-management software. See [Auditing Impala Operations](#) on page 99 for details about setting up and managing auditing.

Security Guidelines for Impala

The following are the major steps to harden a cluster running Impala against accidents and mistakes, or malicious attackers trying to access sensitive data:

- Secure the `root` account. The `root` user can tamper with the `impalad` daemon, read and write the data files in HDFS, log into other user accounts, and access other system services that are beyond the control of Impala.
- Restrict membership in the `sudoers` list (in the `/etc/sudoers` file). The users who can run the `sudo` command can do many of the same things as the `root` user.
- Ensure the Hadoop ownership and permissions for Impala data files are restricted.
- Ensure the Hadoop ownership and permissions for Impala log files are restricted.
- Ensure that the Impala web UI (available by default on port 25000 on each Impala node) is password-protected. See [Impala Web User Interface for Debugging](#) on page 810 for details.

- Create a policy file that specifies which Impala privileges are available to users in particular Hadoop groups (which by default map to Linux OS groups). Create the associated Linux groups using the `groupadd` command if necessary.
- The Impala authorization feature makes use of the HDFS file ownership and permissions mechanism; for background information, see the [HDFS Permissions Guide](#). Set up users and assign them to groups at the OS level, corresponding to the different categories of users with different access levels for various databases, tables, and HDFS locations (URIs). Create the associated Linux users using the `useradd` command if necessary, and add them to the appropriate groups with the `usermod` command.
- Design your databases, tables, and views with database and table structure to allow policy rules to specify simple, consistent rules. For example, if all tables related to an application are inside a single database, you can assign privileges for that database and use the `*` wildcard for the table name. If you are creating views with different privileges than the underlying base tables, you might put the views in a separate database so that you can use the `*` wildcard for the database containing the base tables, while specifying the precise names of the individual views. (For specifying table or database names, you either specify the exact name or `*` to mean all the databases on a server, or all the tables and views in a database.)
- Enable authorization by running the `impalad` daemons with the `-server_name` and `-authorization_policy_file` options on all nodes. (The authorization feature does not apply to the `statestored` daemon, which has no access to schema objects or data files.)
- Set up authentication using Kerberos, to make sure users really are who they say they are.

Securing Impala Data and Log Files

One aspect of security is to protect files from unauthorized access at the filesystem level. For example, if you store sensitive data in HDFS, you specify permissions on the associated files and directories in HDFS to restrict read and write permissions to the appropriate users and groups.

If you issue queries containing sensitive values in the `WHERE` clause, such as financial account numbers, those values are stored in Impala log files in the Linux filesystem and you must secure those files also. For the locations of Impala log files, see [Using Impala Logging](#) on page 784.

All Impala read and write operations are performed under the filesystem privileges of the `impala` user. The `impala` user must be able to read all directories and data files that you query, and write into all the directories and data files for `INSERT` and `LOAD DATA` statements. At a minimum, make sure the `impala` user is in the `hive` group so that it can access files and directories shared between Impala and Hive. See [User Account Requirements](#) on page 23 for more details.

Setting file permissions is necessary for Impala to function correctly, but is not an effective security practice by itself:

- The way to ensure that only authorized users can submit requests for databases and tables they are allowed to access is to set up Ranger authorization, as explained in [Impala Authorization](#) on page 83. With authorization enabled, the checking of the user ID and group is done by Impala, and unauthorized access is blocked by Impala itself. The actual low-level read and write requests are still done by the `impala` user, so you must have appropriate file and directory permissions for that user ID.
- You must also set up Kerberos authentication, as described in [Enabling Kerberos Authentication for Impala](#) on page 90, so that users can only connect from trusted hosts. With Kerberos enabled, if someone connects a new host to the network and creates user IDs that match your privileged IDs, they will be blocked from connecting to Impala at all from that host.

Installation Considerations for Impala Security

Impala 1.1 comes set up with all the software and settings needed to enable security when you run the `impalad` daemon with the new security-related options (`-server_name` and `-authorization_policy_file`). You do not need to change any environment variables or install any additional JAR files.

Securing the Hive Metastore Database

It is important to secure the Hive metastore, so that users cannot access the names or other information about databases and tables through the Hive client or by querying the metastore database. Do this by turning on Hive metastore security, using the instructions in the documentation for your Apache Hadoop distribution for securing different Hive components:

- Secure the Hive Metastore.
- In addition, allow access to the metastore only from the HiveServer2 server, and then disable local access to the HiveServer2 server.

Securing the Impala Web User Interface

The instructions in this section presume you are familiar with the [.htpasswd mechanism](#) commonly used to password-protect pages on web servers.

Password-protect the Impala web UI that listens on port 25000 by default. Set up a `.htpasswd` file in the `$IMPALA_HOME` directory, or start both the `impalad` and `statestored` daemons with the `--webserver_password_file` option to specify a different location (including the filename).

This file should only be readable by the Impala process and machine administrators, because it contains (hashed) versions of passwords. The username / password pairs are not derived from Unix usernames, Kerberos users, or any other system. The `domain` field in the password file must match the domain supplied to Impala by the new command-line option `--webserver_authentication_domain`. The default is `mydomain.com`.

Impala also supports using HTTPS for secure web traffic. To do so, set `--webserver_certificate_file` to refer to a valid `.pem` TLS/SSL certificate file. Impala will automatically start using HTTPS once the TLS/SSL certificate has been read and validated. A `.pem` file is basically a private key, followed by a signed TLS/SSL certificate; make sure to concatenate both parts when constructing the `.pem` file.

If Impala cannot find or parse the `.pem` file, it prints an error message and quits.

Note:

If the private key is encrypted using a passphrase, Impala will ask for that passphrase on startup, which is not useful for a large cluster. In that case, remove the passphrase and make the `.pem` file readable only by Impala and administrators.

When you turn on TLS/SSL for the Impala web UI, the associated URLs change from `http://` prefixes to `https://`. Adjust any bookmarks or application code that refers to those URLs.

Configuring TLS/SSL for Impala

Impala supports TLS/SSL network encryption, between Impala and client programs, and between the Impala-related daemons running on different nodes in the cluster. This feature is important when you also use other features such as Kerberos authentication or Ranger authorization, where credentials are being transmitted back and forth.

Using the Command Line

To enable TLS/SSL for client applications to connect to Impala, add both of the following flags to the `impalad` startup options:

- `--ssl_server_certificate`: The full path to the server certificate, on the local filesystem.
- `--ssl_private_key`: The full path to the server private key, on the local filesystem.

In Impala 2.3 and higher, Impala can also use SSL for its own internal communication between the `impalad`, `statestored`, and `catalogd` daemons. To enable this additional SSL encryption, set the `--ssl_server_certificate` and `--ssl_private_key` flags in the startup options for `impalad`,

catalogd, and statestored, and also add the `--ssl_client_ca_certificate` flag for all three of those daemons.



Warning: In Impala 2.3.1 and lower versions, you could enable Kerberos authentication between Impala internal components, or SSL encryption between Impala internal components, but not both at the same time. This restriction has now been lifted. See [IMPALA-2598](#) to see the maintenance releases for different levels of Impala where the fix has been published.

If either of these flags are set, both must be set. In that case, Impala starts listening for Beeswax and HiveServer2 requests on SSL-secured ports only. (The port numbers stay the same; see [Ports Used by Impala](#) on page 820 for details.)

Since Impala uses passphrase-less certificates in PEM format, you can reuse a host's existing Java keystore by using the `openssl` toolkit to convert it to the PEM format.

Configuring TLS/SSL Communication for the Impala Shell

With TLS/SSL enabled for Impala, start `impala-shell` with the following options:

- `--ssl`: Enables TLS/SSL for `impala-shell`.
- `--ca_cert`: The local pathname pointing to the third-party CA certificate, or to a copy of the server certificate for self-signed server certificates.

If `--ca_cert` is not set, `impala-shell` enables TLS/SSL, but does not validate the server certificate. This is useful for connecting to a known-good Impala that is only running over TLS/SSL, when a copy of the certificate is not available (such as when debugging customer installations).

For `impala-shell` to successfully connect to an Impala cluster that has the minimum allowed TLS/SSL version set to 1.2 (`--ssl_minimum_version=tlsv1.2`), the Python version on the cluster that `impala-shell` runs on must be 2.7.9 or higher (or a vendor-provided Python version with the required support. Some vendors patched Python 2.7.5 versions on Red Hat Enterprise Linux 7 and derivatives).

Using TLS/SSL with Business Intelligence Tools

You can use Kerberos authentication, TLS/SSL encryption, or both to secure connections from JDBC and ODBC applications to Impala. See [Configuring Impala to Work with JDBC](#) on page 801 and [Configuring Impala to Work with ODBC](#) on page 801 for details.

Prior to Impala 2.5, the Hive JDBC driver did not support connections that use both Kerberos authentication and SSL encryption. If your cluster is running an older release that has this restriction, use an alternative JDBC driver that supports both of these security features.

Specifying TLS/SSL Minimum Allowed Version and Ciphers

Depending on your cluster configuration and the security practices in your organization, you might need to restrict the allowed versions of TLS/SSL used by Impala. Older TLS/SSL versions might have vulnerabilities or lack certain features. In Impala 2.10, you can use startup options for the `impalad`, `catalogd`, and `statestored` daemons to specify a minimum allowed version of TLS/SSL.

Specify one of the following values for the `--ssl_minimum_version` configuration setting:

- `tlsv1`: Allow any TLS version of 1.0 or higher.
- `tlsv1.1`: Allow any TLS version of 1.1 or higher.
- `tlsv1.2`: Allow any TLS version of 1.2 or higher.

The default version was changed from 'tlsv1' to 'tlsv1.2' starting in Impala 4.0

Along with specifying the version, you can also specify the allowed set of TLS ciphers by using the `--ssl_cipher_list` configuration setting. The argument to this option is a list of keywords, separated by colons, commas, or spaces, and optionally including other notation. For example:

```
--ssl_cipher_list="RC4-SHA,RC4-MD5"
```

See the output of `man ciphers` for the full set of keywords and notation allowed in the argument string. Since Impala 4.2 the default value of `--ssl_cipher_list` is a set of ciphers based on Mozilla's intermediate compatibility recommendations from https://wiki.mozilla.org/Security/Server_Side_TLS. Prior to Impala 4.2 the default was unset, and Impala used the default cipher list for the underlying platform.

Impala Authorization

Authorization determines which users are allowed to access which resources, and what operations they are allowed to perform. You use Apache Ranger for authorization. By default, when authorization is not enabled, Impala does all read and write operations with the privileges of the `impala` user, which is suitable for a development/test environment but not for a secure production environment. When authorization is enabled, Impala uses the OS user ID of the user who runs `impala-shell` or other client programs, and associates various privileges with each user.

The Privilege Model

Privileges can be granted on different objects in the schema. Any privilege that can be granted is associated with a level in the object hierarchy. If a privilege is granted on a parent object in the hierarchy, the child object automatically inherits it. This is the same privilege model as Hive and other database systems.

The objects in the Impala schema hierarchy are:

```
Server
  URI
  Database
    Table
      Column
```

The table-level privileges apply to views as well. Anywhere you specify a table name, you can specify a view name instead.

In Impala 2.3 and higher, you can specify privileges for individual columns.

The table below lists the minimum level of privileges and the scope required to execute SQL statements in Impala 3.0 and higher. The following notations are used:

- The **SERVER** resource type in Ranger implies all databases, all tables, all columns, all UDFs, and all URIs.
- **ANY** denotes the `SELECT`, `INSERT`, `CREATE`, `ALTER`, `DROP`, *or* `REFRESH` privilege.
- **ALL** privilege denotes the `SELECT`, `INSERT`, `CREATE`, `ALTER`, `DROP`, *and* `REFRESH` privileges.
- The owner of an object effectively has the **ALL** privilege on the object.
- The parent levels of the specified scope are implicitly supported where a scope refers to the specific level in the object hierarchy that the privilege is granted. For example, if a privilege is listed with the **TABLE** scope, the same privilege granted on **DATABASE** and **SERVER** will allow the user to execute the specified SQL statement.

SQL Statement	Privileges	Object Type / Resource Type
SELECT	SELECT	TABLE
WITH SELECT	SELECT	TABLE
EXPLAIN SELECT	SELECT	TABLE
INSERT	INSERT	TABLE
EXPLAIN INSERT	INSERT	TABLE
TRUNCATE	INSERT	TABLE

LOAD	INSERT	TABLE
	ALL	URI
CREATE DATABASE	CREATE	SERVER
CREATE DATABASE LOCATION	CREATE	SERVER
	ALL	URI
CREATE TABLE	CREATE	DATABASE
CREATE TABLE LIKE	CREATE	DATABASE
	SELECT, INSERT, <i>or</i> REFRESH	TABLE
CREATE TABLE AS SELECT	CREATE	DATABASE
	INSERT	DATABASE
	SELECT	TABLE
EXPLAIN CREATE TABLE AS SELECT	CREATE	DATABASE
	INSERT	DATABASE
	SELECT	TABLE
CREATE TABLE LOCATION	CREATE	TABLE
	ALL	URI
CREATE VIEW	CREATE	DATABASE
	SELECT	TABLE
ALTER DATABASE SET OWNER	ALL WITH GRANT	DATABASE
ALTER TABLE	ALTER	TABLE
ALTER TABLE SET LOCATION	ALTER	TABLE
	ALL	URI
ALTER TABLE RENAME	CREATE	DATABASE
	ALL	TABLE
ALTER TABLE SET OWNER	ALL WITH GRANT	TABLE
ALTER VIEW	ALTER	TABLE
	SELECT	TABLE
ALTER VIEW RENAME	CREATE	DATABASE
	ALL	TABLE
ALTER VIEW SET OWNER	ALL WITH GRANT	VIEW
DROP DATABASE	DROP	DATABASE
DROP TABLE	DROP	TABLE
DROP VIEW	DROP	TABLE

CREATE FUNCTION	CREATE	DATABASE
	ALL	URI
DROP FUNCTION	DROP	DATABASE
COMPUTE STATS	ALTER and SELECT	TABLE
DROP STATS	ALTER	TABLE
INVALIDATE METADATA	REFRESH	SERVER
INVALIDATE METADATA <table>	REFRESH	TABLE
REFRESH <table>	REFRESH	TABLE
REFRESH AUTHORIZATION	REFRESH	SERVER
REFRESH FUNCTIONS	REFRESH	DATABASE
COMMENT ON DATABASE	ALTER	DATABASE
COMMENT ON TABLE	ALTER	TABLE
COMMENT ON VIEW	ALTER	TABLE
COMMENT ON COLUMN	ALTER	TABLE
DESCRIBE DATABASE	SELECT, INSERT, <i>or</i> REFRESH	DATABASE
DESCRIBE <table/view>	SELECT, INSERT, <i>or</i> REFRESH	TABLE
If the user has the SELECT privilege at the COLUMN level, only the columns the user has access will show.	SELECT	COLUMN
USE	ANY	TABLE
SHOW DATABASES	ANY	TABLE
SHOW TABLES	ANY	TABLE
SHOW FUNCTIONS	SELECT, INSERT, <i>or</i> REFRESH	DATABASE
SHOW PARTITIONS	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW TABLE STATS	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW COLUMN STATS	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW FILES	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW CREATE TABLE	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW CREATE VIEW	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW CREATE FUNCTION	SELECT, INSERT, <i>or</i> REFRESH	DATABASE
SHOW RANGE PARTITIONS (Kudu only)	SELECT, INSERT, <i>or</i> REFRESH	TABLE
UPDATE (Kudu only)	ALL	TABLE
EXPLAIN UPDATE (Kudu only)	ALL	TABLE
UPSERT (Kudu only)	ALL	TABLE

WITH UPSERT (Kudu only)	ALL	TABLE
EXPLAIN UPSERT (Kudu only)	ALL	TABLE
DELETE (Kudu only)	ALL	TABLE
EXPLAIN DELETE (Kudu only)	ALL	TABLE

Privileges are managed via the GRANT and REVOKE SQL statements that require the Ranger service enabled.

If you change privileges outside of Impala, e.g. adding a user, removing a user, modifying privileges, you must clear the Impala Catalog server cache by running the REFRESH AUTHORIZATION statement. REFRESH AUTHORIZATION is not required if you make the changes to privileges within Impala.

Object Ownership in Ranger

Object ownership for tables, views and databases is enabled by default in Impala.

To define owner specific privileges, go to ranger UI and define appropriate policies on the {OWNER} user.

The CREATE statements implicitly make the user running the statement the owner of the object. For example, if *User A* creates a database, *foo*, via the CREATE DATABASE statement, *User A* now owns the *foo* database and is authorized to perform any operation on the *foo* database.

An ownership can be transferred to another user or role via the ALTER DATABASE, ALTER TABLE, or ALTER VIEW with the SET OWNER clause.

Note: Currently, due to a known issue ([IMPALA-8937](#)), until the ownership information is fully loaded in the coordinator catalog cache, the owner of a table might not be able to see the table when executing the SHOW TABLES statement. The owner can still query the table.

Starting Impala with Ranger Authorization Enabled

To enable authorization in an Impala cluster using Ranger:

1. Add the following options to the IMPALA_SERVER_ARGS and the IMPALA_CATALOG_ARGS settings in the /etc/default/impala configuration file:
 - -server_name: Specify the same name for all impalad nodes and the catalogd in the cluster.
 - -ranger_service_type=hive
 - -ranger_app_id: Set it to the Ranger application id.
 - -authorization_provider=ranger
2. Restart the catalogd and all impalad daemons.

Managing Privileges

You set up privileges through the GRANT and REVOKE statements in either Impala or Hive.

For information about using the Impala GRANT and REVOKE statements, see [GRANT Statement \(Impala 2.0 or higher only\)](#) on page 294 and [REVOKE Statement \(Impala 2.0 or higher only\)](#) on page 315.

Changing Privileges from Outside of Impala

If you make a change to privileges in Ranger from outside of Impala, e.g. adding a user, removing a user, modifying privileges, there are two options to propagate the change:

- Use the ranger.plugin.hive.policy.pollIntervalMs property to specify how often to do a Ranger refresh. The property is specified in ranger-hive-security.xml in the conf directory under your Impala home directory.
- Run the INVALIDATE METADATA or REFRESH AUTHORIZATION statement to force a refresh.

If you make a change to privileges within Impala, INVALIDATE METADATA is not required.



Warning: As `INVALIDATE METADATA` is an expensive operation, you should use it judiciously.

Granting Privileges on URI

URIs represent the file paths you specify as part of statements such as `CREATE EXTERNAL TABLE` and `LOAD DATA`. Typically, you specify what look like UNIX paths, but these locations can also be prefixed with `hdfs://` to make clear that they are really URIs. To set privileges for a URI, specify the name of a directory, and the privilege applies to all the files in that directory and any directories underneath it.

URIs must start with `hdfs://`, `s3a://`, `adl://`, or `file:///`. If a URI starts with an absolute path, the path will be appended to the default filesystem prefix. For example, if you specify:

```
GRANT ALL ON URI '/tmp';
```

The above statement effectively becomes the following where the default filesystem is HDFS.

```
GRANT ALL ON URI 'hdfs://localhost:20500/tmp';
```

When defining URIs for HDFS, you must also specify the NameNode. For example:

```
GRANT ALL ON URI file:///path/to/dir TO <role>
GRANT ALL ON URI hdfs://namenode:port/path/to/dir TO <role>
```



Warning: Because the NameNode host and port must be specified, it is strongly recommended that you use High Availability (HA). This ensures that the URI will remain constant even if the NameNode changes. For example:

```
GRANT ALL ON URI hdfs://ha-nn-uri/path/to/dir TO <role>
```

Examples of Setting up Authorization for Security Scenarios

The following examples show how to set up authorization to grant privileges on objects to groups of users via roles.

A User with No Privileges

If a user has no privileges at all, that user cannot access any schema objects in the system. The error messages do not disclose the names or existence of objects that the user is not authorized to read.

This is the experience you want a user to have if they somehow log into a system where they are not an authorized Impala user. Or in a real deployment, a user might have no privileges because they are not a member of any of the authorized groups.

Examples of Privileges for Administrative Users

In this example, the SQL statements grant the `entire_server` role all privileges on both the databases and URIs within the server.

```
CREATE ROLE entire_server;
GRANT ROLE entire_server TO GROUP admin_group;
GRANT ALL ON SERVER server1 TO ROLE entire_server;
```

A User with Privileges for Specific Databases and Tables

If a user has privileges for specific tables in specific databases, the user can access those things but nothing else. They can see the tables and their parent databases in the output of `SHOW TABLES`

and `SHOW DATABASES`, `USE` the appropriate databases, and perform the relevant actions (`SELECT` and/or `INSERT`) based on the table privileges. To actually create a table requires the `ALL` privilege at the database level, so you might define separate roles for the user that sets up a schema and other users or applications that perform day-to-day operations on the tables.

```
CREATE ROLE one_database;
GRANT ROLE one_database TO GROUP admin_group;
GRANT ALL ON DATABASE db1 TO ROLE one_database;

CREATE ROLE instructor;
GRANT ROLE instructor TO GROUP trainers;
GRANT ALL ON TABLE db1.lesson TO ROLE instructor;

# This particular course is all about queries, so the students
# can SELECT but not INSERT or CREATE/DROP.
CREATE ROLE student;
GRANT ROLE student TO GROUP visitors;
GRANT SELECT ON TABLE db1.training TO ROLE student;
```

Privileges for Working with External Data Files

When data is being inserted through the `LOAD DATA` statement or is referenced from an HDFS location outside the normal Impala database directories, the user also needs appropriate permissions on the URIs corresponding to those HDFS locations.

In this example:

- The `external_table` role can insert into and query the Impala table, `external_table.sample`.
- The `staging_dir` role can specify the HDFS path `/user/impala-user/external_data` with the `LOAD DATA` statement. When Impala queries or loads data files, it operates on all the files in that directory, not just a single file, so any Impala `LOCATION` parameters refer to a directory rather than an individual file.

```
CREATE ROLE external_table;
GRANT ROLE external_table TO GROUP impala_users;
GRANT ALL ON TABLE external_table.sample TO ROLE external_table;

CREATE ROLE staging_dir;
GRANT ROLE staging_dir TO GROUP impala_users;
GRANT ALL ON URI 'hdfs://127.0.0.1:8020/user/impala-user/external_data' TO ROLE staging_dir;
```

Separating Administrator Responsibility from Read and Write Privileges

To create a database, you need the full privilege on that database while day-to-day operations on tables within that database can be performed with lower levels of privilege on a specific table. Thus, you might set up separate roles for each database or application: an administrative one that could create or drop the database, and a user-level one that can access only the relevant tables.

In this example, the responsibilities are divided between users in 3 different groups:

- Members of the `supergroup` group have the `training_sysadmin` role and so can set up a database named `training`.
- Members of the `impala_users` group have the `instructor` role and so can create, insert into, and query any tables in the `training` database, but cannot create or drop the database itself.

- Members of the `visitor` group have the `student` role and so can query those tables in the `training` database.

```
CREATE ROLE training_sysadmin;
GRANT ROLE training_sysadmin TO GROUP supergroup;
GRANT ALL ON DATABASE training TO ROLE training_sysadmin;

CREATE ROLE instructor;
GRANT ROLE instructor TO GROUP impala_users;
GRANT ALL ON TABLE training.course1 TO ROLE instructor;

CREATE ROLE student;
GRANT ROLE student TO GROUP visitor;
GRANT SELECT ON TABLE training.course1 TO ROLE student;
```

Setting Up Schema Objects for a Secure Impala Deployment

In your role definitions, you must specify privileges at the level of individual databases and tables, or all databases or all tables within a database. To simplify the structure of these rules, plan ahead of time how to name your schema objects so that data with different authorization requirements are divided into separate databases.

If you are adding security on top of an existing Impala deployment, you can rename tables or even move them between databases using the `ALTER TABLE` statement.

The DEFAULT Database in a Secure Deployment

Because of the extra emphasis on granular access controls in a secure deployment, you should move any important or sensitive information out of the `DEFAULT` database into a named database. Sometimes you might need to give privileges on the `DEFAULT` database for administrative reasons, for example, as a place you can reliably specify with a `USE` statement when preparing to drop a database.

Ranger Column Masking

Ranger column masking hides sensitive columnar data in Impala query output. For example, you can define a policy that reveals only the first or last four characters of column data. Column masking is enabled by default. The Impala behavior mimics Hive behavior with respect to column masking. For more information, see the [Apache Ranger documentation](#).

The following table lists all supported, built-in mask types for defining column masking in a policy using the Ranger REST API.

Type	Name	Description	Transformer
MASK	Redact	Replace lowercase with 'x', uppercase with 'X', digits with '0'	<code>mask({col})</code>
MASK_SHOW_LAST_4	Partial mask: show last 4	Show last 4 characters; replace rest with 'x'	<code>mask_show_last_n({col}, 4, 'x', 'x', 'x', -1, '1')</code>
MASK_SHOW_FIRST_4	Partial mask: show first 4	Show first 4 characters; replace rest with 'x'	<code>mask_show_first_n({col}, 4, 'x', 'x', 'x', -1, '1')</code>
MASK_HASH	Hash	Hash the value	<code>mask_hash({col})</code>
MASK_NULL	Nullify	Replace with NULL	N/A
MASK_NONE	Unmasked (retain original value)	No masking	N/A

Type	Name	Description	Transformer
MASK_DATE_SHOW_YEAR	Date: show only year	Date: show only year	mask({col}, 'x', 'x', 'x', -1, '1', 1, 0, -1)
CUSTOM	Custom	Custom	N/A

Limitations on Mask Functions

The mask functions in Hive are implemented through GenericUDFs. Even though Impala users can call Hive UDFs, Impala does not yet support Hive GenericUDFs, so you cannot use Hive's mask functions in Impala. However, Impala has builtin mask functions that are implemented through overloads. In Impala, when using mask functions, not all parameter combinations are supported. These mask functions are introduced in Impala 3.4

The following list includes all the implemented overloads.

- Overloads used by Ranger default masking policies,
- Overloads with simple arguments,
- Overload with all arguments in `int` type for full functionality. Char argument needs to be converted to their ASCII value.

To list the available overloads, use the following query:

```
show functions in _impala_builtins like "mask*";
```

Note:

- An error message that states "*No matching function with signature: mask...*" implies that Impala does not contain the corresponding overload.

Impala Authentication

Authentication is the mechanism to ensure that only specified hosts and users can connect to Impala. It also verifies that when clients connect to Impala, they are connected to a legitimate server. This feature prevents spoofing such as *impersonation* (setting up a phony client system with the same account and group names as a legitimate user) and *man-in-the-middle attacks* (intercepting application requests before they reach Impala and eavesdropping on sensitive information in the requests or the results).

Impala supports authentication using either Kerberos or LDAP.

You can also make proxy connections to Impala through Apache Knox.

Note: Regardless of the authentication mechanism used, Impala always creates HDFS directories and data files owned by the same user (typically `impala`). To implement user-level access to different databases, tables, columns, partitions, and so on, use the Sentry authorization feature, as explained in [Impala Authorization](#) on page 83.

Once you are finished setting up authentication, move on to authorization, which involves specifying what databases, tables, HDFS directories, and so on can be accessed by particular users when they connect through Impala. See [Impala Authorization](#) on page 83 for details.

Enabling Kerberos Authentication for Impala

Impala supports an enterprise-grade authentication system called Kerberos. Kerberos provides strong security benefits including capabilities that render intercepted authentication packets unusable by an attacker. It virtually eliminates the threat of impersonation by never sending a user's credentials in cleartext over the network. For more information on Kerberos, visit the [MIT Kerberos website](#).

The rest of this topic assumes you have a working [Kerberos Key Distribution Center \(KDC\)](#) set up. To enable Kerberos, you first create a Kerberos principal for each host running `impalad` or `statestored`.

Note: Regardless of the authentication mechanism used, Impala always creates HDFS directories and data files owned by the same user (typically `impala`). To implement user-level access to different databases, tables, columns, partitions, and so on, use the Sentry authorization feature, as explained in [Impala Authorization](#) on page 83.

An alternative form of authentication you can use is LDAP, described in [Enabling LDAP Authentication for Impala](#) on page 93.

Requirements for Using Impala with Kerberos

On version 5 of Red Hat Enterprise Linux and comparable distributions, some additional setup is needed for the `impala-shell` interpreter to connect to a Kerberos-enabled Impala cluster:

```
sudo yum install python-devel openssl-devel python-pip
sudo pip-python install ssl
```

Important:

If you plan to use Impala in your cluster, you must configure your KDC to allow tickets to be renewed, and you must configure `krb5.conf` to request renewable tickets. Typically, you can do this by adding the `max_renewable_life` setting to your realm in `kdc.conf`, and by adding the `renew_lifetime` parameter to the `libdefaults` section of `krb5.conf`. For more information about renewable tickets, see the [Kerberos documentation](#).

Start all `impalad` and `statestored` daemons with the `##principal` and `##keytab-file` flags set to the principal and full path name of the keytab file containing the credentials for the principal.

To enable Kerberos in the Impala shell, start the `impala-shell` command using the `-k` flag.

To enable Impala to work with Kerberos security on your Hadoop cluster, make sure you perform the installation and configuration steps in [Authentication in Hadoop](#). Note that when Kerberos security is enabled in Impala, a web browser that supports Kerberos HTTP SPNEGO is required to access the Impala web console (for example, Firefox, Internet Explorer, or Chrome).

If the NameNode, Secondary NameNode, DataNode, JobTracker, TaskTrackers, ResourceManager, NodeManagers, HttpFS, Oozie, Impala, or Impala statestore services are configured to use Kerberos HTTP SPNEGO authentication, and two or more of these services are running on the same host, then all of the running services must use the same HTTP principal and keytab file used for their HTTP endpoints.

Configuring Impala to Support Kerberos Security

Enabling Kerberos authentication for Impala involves steps that can be summarized as follows:

- Creating service principals for Impala and the HTTP service. Principal names take the form: `serviceName/fully.qualified.domain.name@KERBEROS.REALM`.

In Impala 2.0 and later, `user()` returns the full Kerberos principal string, such as `user@example.com`, in a Kerberized environment.

- Creating, merging, and distributing key tab files for these principals.
- Editing `/etc/default/impala` to accommodate Kerberos authentication.

Enabling Kerberos for Impala

1. Create an Impala service principal, specifying the name of the OS user that the Impala daemons run under, the fully qualified domain name of each node running `impalad`, and the realm name. For example:

```
$ kadmin
kadmin: addprinc -requires_preauth -randkey impala/
impala_host.example.com@TEST.EXAMPLE.COM
```

2. Create an HTTP service principal. For example:

```
kadmin: addprinc -randkey HTTP/impala_host.example.com@TEST.EXAMPLE.COM
```

Note: The HTTP component of the service principal must be uppercase as shown in the preceding example.

3. Create keytab files with both principals. For example:

```
kadmin: xst -k impala.keytab impala/impala_host.example.com
kadmin: xst -k http.keytab HTTP/impala_host.example.com
kadmin: quit
```

4. Use `ktutil` to read the contents of the two keytab files and then write those contents to a new file. For example:

```
$ ktutil
ktutil: rkt impala.keytab
ktutil: rkt http.keytab
ktutil: wkt impala-http.keytab
ktutil: quit
```

5. (Optional) Test that credentials in the merged keytab file are valid, and that the “renew until” date is in the future. For example:

```
$ klist -e -k -t impala-http.keytab
```

6. Copy the `impala-http.keytab` file to the Impala configuration directory. Change the permissions to be only read for the file owner and change the file owner to the `impala` user. By default, the Impala user and group are both named `impala`. For example:

```
$ cp impala-http.keytab /etc/impala/conf
$ cd /etc/impala/conf
$ chmod 400 impala-http.keytab
$ chown impala:impala impala-http.keytab
```

7. Add Kerberos options to the Impala defaults file, `/etc/default/impala`. Add the options for both the `impalad` and `statestored` daemons, using the `IMPALA_SERVER_ARGS` and `IMPALA_STATE_STORE_ARGS` variables. For example, you might add:

```
-kerberos_reinit_interval=60
-principal=impala_1/impala_host.example.com@TEST.EXAMPLE.COM
-keytab_file=/path/to/impala.keytab
```

For more information on changing the Impala defaults specified in `/etc/default/impala`, see [Modifying Impala Startup Options](#).

Note: Restart `impalad` and `statestored` for these configuration changes to take effect.

Enabling Kerberos for Impala with a Proxy Server

A common configuration for Impala with High Availability is to use a proxy server to submit requests to the actual `impalad` daemons on different hosts in the cluster. This configuration avoids connection problems in case of machine failure, because the proxy server can route new requests through one of the remaining hosts in the cluster. This configuration also helps with load balancing, because the additional overhead of being the “coordinator node” for each query is spread across multiple hosts.

Although you can set up a proxy server with or without Kerberos authentication, typically users set up a secure Kerberized configuration. For information about setting up a proxy server for Impala, including Kerberos-specific steps, see [Using Impala through a Proxy for High Availability](#) on page 67.

Using a Web Browser to Access a URL Protected by Kerberos HTTP SPNEGO

Your web browser must support Kerberos HTTP SPNEGO. For example, Chrome, Firefox, or Internet Explorer.

To configure Firefox to access a URL protected by Kerberos HTTP SPNEGO:

1. Open the advanced settings Firefox configuration page by loading the `about:config` page.
2. Use the **Filter** text box to find `network.negotiate-auth.trusted-uris`.

3. Double-click the `network.negotiate-auth.trusted-uris` preference and enter the hostname or the domain of the web server that is protected by Kerberos HTTP SPNEGO. Separate multiple domains and hostnames with a comma.
4. Click **OK**.

Enabling Impala Delegation for Kerberos Users

See [Configuring Impala Delegation for Clients](#) on page 97 for details about the delegation feature that lets certain users submit queries using the credentials of other users.

Using TLS/SSL with Business Intelligence Tools

You can use Kerberos authentication, TLS/SSL encryption, or both to secure connections from JDBC and ODBC applications to Impala. See [Configuring Impala to Work with JDBC](#) on page 801 and [Configuring Impala to Work with ODBC](#) on page 801 for details.

Prior to Impala 2.5, the Hive JDBC driver did not support connections that use both Kerberos authentication and SSL encryption. If your cluster is running an older release that has this restriction, use an alternative JDBC driver that supports both of these security features.

Enabling Access to Internal Impala APIs for Kerberos Users

For applications that need direct access to Impala APIs, without going through the HiveServer2 or Beeswax interfaces, you can specify a list of Kerberos users who are allowed to call those APIs. By default, the `impala` and `hdfs` users are the only ones authorized for this kind of access. Any users not explicitly authorized through the `internal_principals_whitelist` configuration setting are blocked from accessing the APIs. This setting applies to all the Impala-related daemons, although currently it is primarily used for HDFS to control the behavior of the catalog server.

Mapping Kerberos Principals to Short Names for Impala

In Impala 2.6 and higher, Impala recognizes the `auth_to_local` setting, specified through the HDFS configuration setting `hadoop.security.auth_to_local`. This feature is disabled by default, to avoid an unexpected change in security-related behavior. To enable it:

- Specify `##load_auth_to_local_rules=true` in the `impalad` and `catalogd` configuration settings.

Enabling LDAP Authentication for Impala

Authentication is the process of allowing only specified named users to access the server (in this case, the Impala server). This feature is crucial for any production deployment, to prevent misuse, tampering, or excessive load on the server. Impala uses LDAP for authentication, verifying the credentials of each user who connects through `impala-shell`, Hue, a Business Intelligence tool, JDBC or ODBC application, and so on.

Note: Regardless of the authentication mechanism used, Impala always creates HDFS directories and data files owned by the same user (typically `impala`). To implement user-level access to different databases, tables, columns, partitions, and so on, use the Sentry authorization feature, as explained in [Impala Authorization](#) on page 83.

An alternative form of authentication you can use is Kerberos, described in [Enabling Kerberos Authentication for Impala](#) on page 90.

Requirements for Using Impala with LDAP

Authentication against LDAP servers is available in Impala 1.2.2 and higher. Impala 1.4.0 adds support for secure LDAP authentication through SSL and TLS.

The Impala LDAP support lets you use Impala with systems such as Active Directory that use LDAP behind the scenes.

Consideration for Connections Between Impala Components

Only client-Impala connections can be authenticated by LDAP.

You must use the Kerberos authentication mechanism for connections between internal Impala components, such as between the `impalad`, `statedored`, and `catalogd` daemons. See [Enabling Kerberos Authentication for Impala](#) on page 90 on how to set up Kerberos for Impala.

Enabling LDAP in Command Line Interface

To enable LDAP authentication, start the `impalad` with the following startup options for:

<code>--enable_ldap_auth</code>	Enables LDAP-based authentication between the client and Impala.
<code>--ldap_uri</code>	Sets the URI of the LDAP server to use. Typically, the URI is prefixed with <code>ldap://</code> . You can specify secure SSL-based LDAP transport by using the prefix <code>ldaps://</code> . The URI can optionally specify the port, for example: <code>ldap://ldap_server.example.com:389</code> or <code>ldaps://ldap_server.example.com:636</code> . (389 and 636 are the default ports for non-SSL and SSL LDAP connections, respectively.)
<code>--ldap_search_bind_authentication</code>	Allows to switch between search and simple bind user lookup methods when authenticating, the default value is <code>false</code> which is simple bind.

Bind User Credentials

The bind user is used to run the user/group searches, the credentials can be configured with the following flags:

<code>--ldap_allow_anonymous_binds</code>	When true, LDAP authentication with a blank password (an 'anonymous bind') is allowed by Impala. The default value is <code>false</code> .
<code>--ldap_bind_dn</code>	Distinguished name of the user to bind as when doing user or group searches. Only required if user or group filters are being used and the LDAP server is not configured to allow anonymous searches.
<code>--ldap_bind_password_cmd</code>	A Unix command whose output returns the password to use with <code>--ldap_bind_dn</code> . The output of the command will be truncated to 1024 bytes and trimmed of trailing whitespace.

Simple Bind User Authentication

When Impala connects to LDAP it issues a bind call to the LDAP server to authenticate as the connected user. Impala clients, including the Impala shell, provide the short name of the user to Impala. This is necessary so that Impala can use Ranger for role-based access, which uses short names.

However, LDAP servers often require more complex, structured usernames for authentication. Impala supports three ways of transforming the short name (for example, 'henry') to a more complicated string. If necessary, specify one of the following configuration options when starting the `impalad` daemon.

Note: The `--ldap_domain`, `--ldap_baseDN` and `--ldap_bind_pattern` options are mutually exclusive, and Impala does not start if more than one of these options are specified.

<code>--ldap_domain</code>	Replaces the username with a string <code>username@ldap_domain</code> .
----------------------------	---

<code>--ldap_baseDN</code>	Replaces the username with a “distinguished name” (DN) of the form: <code>uid=userid,ldap_baseDN</code> . (This is equivalent to a Hive option).
<code>--ldap_bind_pattern</code>	This is the most general option, and replaces the username with the string <code>ldap_bind_pattern</code> where all instances of the string <code>#UID</code> are replaced with <code>userid</code> . For example, an <code>ldap_bind_pattern</code> of <code>"user=#UID,OU=foo,CN=bar"</code> with a username of <code>henry</code> will construct a bind name of <code>"user=henry,OU=foo,CN=bar"</code> .
<code>--ldap_user_filter</code>	A comma separated list of usernames. If specified, users must be on this list for authentication to succeed
<code>--ldap_group_filter</code>	If specified, users must belong to one of these groups for authentication to succeed.
<code>--ldap_group_dn_pattern</code>	Colon separated list of patterns for the 'distinguished name' use to search for groups in the directory. Each pattern may contain a <code>%s</code> which will be substituted with each group name from <code>--ldap_group_filter</code> when doing group searches.
<code>--ldap_group_membership_key</code>	The LDAP attribute on group entries that indicates its members.
<code>--ldap_group_class_key</code>	The LDAP objectClass each of the groups in <code>--ldap_group_filter</code> implements in LDAP.

Search Bind User Authentication

When Search Bind authentication is enabled Impala first tries to bind with the configured bind user, then executes an LDAP Search operation to find if the user exists. Once the search succeeds the DN is retrieved from the LDAP search results and another LDAP bind request is executed, this time with the connecting user to verify the password.

This authentication method allows to authenticate users existing in different LDAP subtrees when these users' parent tree is configured as base DN.

<code>--ldap_user_search_basedn</code>	The 'distinguished name' DN that will be used to search for the authenticating user, this field is required for search bind authentication.
<code>--ldap_group_search_basedn</code>	The 'distinguished name' DN that will be used to search for the authenticating group. If left empty, group checks will not be performed.
<code>--ldap_user_filter</code>	LDAP filter that will be used during LDAP search, it can contain <code>{0}</code> pattern which will be replaced with the username. The default value is <code>(&(objectClass=user)(sAMAccountName={0}))</code> .
<code>--ldap_group_filter</code>	LDAP filter that will be used during LDAP group search, it can contain <code>{1}</code> pattern which will be replaced with the username and/or <code>{0}</code> which will

be replaced with the user DN. The default value is `(&(objectClass=group)(member={0}))`.

Note: The behaviour of this flag has been changed between Impala 4.1 and Impala 4.2 to comply with Spring LDAP. Previously `{0}` was for username and `{1}` for user dn, these parameters were swapped, now `{0}` is for user dn and `{1}` is for username.

Secure LDAP Connections

To avoid sending credentials over the wire in cleartext, you must configure a secure connection between both the client and Impala, and between Impala and the LDAP server. The secure connection could use SSL or TLS.

Secure LDAP connections through SSL:

For SSL-enabled LDAP connections, specify a prefix of `ldaps://` instead of `ldap://`. Also, the default port for SSL-enabled LDAP connections is 636 instead of 389.

<code>--ldap_passwords_in_clear_ok</code>	Allows LDAP passwords to be sent in the clear (without TLS/SSL) over the network, when set to <code>true</code> . This option should not be used in production environments.
---	--

Secure LDAP connections through TLS:

[TLS](#), the successor to the SSL protocol, is supported by most modern LDAP servers. Unlike SSL connections, TLS connections can be made on the same server port as non-TLS connections. To secure all connections using TLS, specify the following flags as startup options to the `impalad` daemon.

<code>--ldap_tls</code>	Tells Impala to start a TLS connection to the LDAP server, and to fail authentication if it cannot be done.
<code>--ldap_ca_certificate</code>	Specifies the location of the certificate in standard .PEM format. Store this certificate on the local filesystem, in a location that only the <code>impala</code> user and other trusted users can read.

LDAP Authentication for `impala-shell`

To connect to Impala using LDAP authentication, you specify command-line options to the `impala-shell` command interpreter and enter the password when prompted:

<code>-l</code>	Enables LDAP authentication.
<code>-u</code>	Sets the user. Per Active Directory, the user is the short username, not the full LDAP distinguished name. If your LDAP settings include a search base, use the <code>--ldap_bind_pattern</code> on the <code>impalad</code> daemon to translate the short username from <code>impala-shell</code> automatically to the fully qualified name.
<code>--auth_creds_ok_in_clear</code>	If set, LDAP authentication may be used with an insecure connection to Impala. This flag is required when SSL between <code>impala-shell</code> and Impala Server is not configured. Authentication credentials will therefore be sent unencrypted, and may be vulnerable to attack.

Note: `impala-shell` automatically prompts for the password.

See [Configuring Impala to Work with JDBC](#) on page 801 for the format to use with the JDBC connection string for servers using LDAP authentication.

Enabling LDAP for Impala in Hue

Enabling LDAP for Impala in Hue in the Command Line Interface

LDAP authentication for the Impala app in Hue can be enabled by setting the following properties under the `[impala]` section in `hue.ini`.

auth_username	LDAP username of Hue user to be authenticated.
auth_password	LDAP password of Hue user to be authenticated.

These login details are only used by Impala to authenticate to LDAP. The Impala service trusts Hue to have already validated the user being impersonated, rather than simply passing on the credentials.

Enabling Impala Delegation for LDAP Users

See [Configuring Impala Delegation for Clients](#) on page 97 for details about the delegation feature that lets certain users submit queries using the credentials of other users.

LDAP Restrictions for Impala

The LDAP support is preliminary. It currently has only been tested against Active Directory.

Using Multiple Authentication Methods with Impala

Impala 2.0 and later automatically handles both Kerberos and LDAP authentication. Each `impalad` daemon can accept both Kerberos and LDAP requests through the same port. No special actions need to be taken if some users authenticate through Kerberos and some through LDAP.

Prior to Impala 2.0, you had to configure each `impalad` to listen on a specific port depending on the kind of authentication, then configure your network load balancer to forward each kind of request to a `DataNode` that was set up with the appropriate authentication type. Once the initial request was made using either Kerberos or LDAP authentication, Impala automatically handled the process of coordinating the work across multiple nodes and transmitting intermediate results back to the coordinator node.

Configuring Impala Delegation for Clients

When users submit Impala queries through a separate client application, such as Hue or a business intelligence tool, typically all requests are treated as coming from the same user. In Impala 1.2 and higher, Impala supports “delegation” where users whose names you specify can delegate the execution of a query to another user. The query runs with the privileges of the delegated user, not the original authenticated user.

Starting in Impala 3.1 and higher, you can delegate using groups. Instead of listing a large number of delegated users, you can create a group of those users and specify the delegated group name in the `impalad` startup option. The client sends the delegated user name, and Impala performs an authorization to see if the delegated user belongs to a delegated group.

The name of the delegated user is passed using the HiveServer2 protocol configuration property `impala.doas.user` when the client connects to Impala.

Currently, the delegation feature is available only for Impala queries submitted through application interfaces such as Hue and BI tools. For example, Impala cannot issue queries using the privileges of the HDFS user.



Attention:

- When the delegation is enabled in Impala, the Impala clients should take an extra caution to prevent unauthorized access for the delegate-able users.
- Impala requires Apache Ranger on the cluster to enable delegation.

The delegation feature is enabled by the startup options for `impalad`: `##authorized_proxy_user_config` and `##authorized_proxy_group_config`.

The syntax for the options are:

```
##authorized_proxy_user_config=authenticated_user1=delegated_user1,delegated_user2,...;
```

```
##authorized_proxy_group_config=authenticated_user1=delegated_group1,delegated_group2,...
```

- The list of authorized users/groups are delimited with `;`
- The list of delegated users/groups are delimited with `,` by default.
- Use the `##authorized_proxy_user_config_delimiter` startup option to override the default user delimiter (the comma character) to another character.
- Use the `##authorized_proxy_group_config_delimiter` startup option to override the default group delimiter (the comma character) to another character.
- Wildcard (`*`) is supported to delegated to any users or any groups, e.g.
`##authorized_proxy_group_config=hue=*`. Make sure to use single quotes or escape characters to ensure that any `*` characters do not undergo wildcard expansion when specified in command-line arguments.

When you start Impala with the

```
##authorized_proxy_user_config=authenticated_user=delegated_user or
##authorized_proxy_group_config=authenticated_user=delegated_group
```

option:

- Authentication is based on the user on the left hand side (*authenticated_user*).
- Authorization is based on the right hand side user(s) or group(s) (*delegated_user*, *delegated_group*).
- When opening a client connection, the client must provide a delegated username via the HiveServer2 protocol property, `impala.doas.user` or `DelegationUID`.

When the client connects over HTTP, the `doAs` parameter can be specified in the HTTP path, e.g. `/?doAs=delegated_user`.

- It is not necessary for *authenticated_user* to have the permission to access/edit files.
- It is not necessary for the delegated users to have access to the service via Kerberos.
- *delegated_user* and *delegated_group* must exist in the OS.
- For group delegation, use the JNI-based mapping providers for group delegation, such as `JniBasedUnixGroupsMappingWithFallback` and `JniBasedUnixGroupsNetgroupMappingWithFallback`.
- `ShellBasedUnixGroupsNetgroupMapping` and `ShellBasedUnixGroupsMapping` Hadoop group mapping providers are not supported in Impala group delegation by default. To enable them, flag `enable_shell_based_groups_mapping` needs to be enabled.
- In Impala, `user()` returns *authenticated_user* and `effective_user()` returns the delegated user that the client specified.

The user or group delegation process works as follows:

1. The `impalad` daemon starts with one of the following options:

- `##authorized_proxy_user_config=authenticated_user=delegated_user`
- `##authorized_proxy_group_config=authenticated_user=delegated_group`

2. A client connects to Impala via the HiveServer2 protocol with the `impala.doas.user` configuration property, e.g. connected user is *authenticated_user* with `impala.doas.user=delegated_user`.

3. The client user *authenticated_user* sends a request to Impala as the delegated user *delegated_user*.

4. Impala checks authorization:

- In user delegation, Impala checks if *delegated_user* is in the list of authorized delegate users for the user *authenticated_user*.
- In group delegation, Impala checks if *delegated_user* belongs to one of the delegated groups for the user *authenticated_user*, *delegated_group* in this example.

5. If the user is an authorized delegated user for *authenticated_user*, the request is executed as the delegate user *delegated_user*.

See [Modifying Impala Startup Options](#) on page 32 for details about adding or changing `impalad` startup options.

See [this blog post](#) for background information about the delegation capability in HiveServer2.

To set up authentication for the delegated users:

- On the server side, configure either user/password authentication through LDAP, or Kerberos authentication, for all the delegated users. See [Enabling LDAP Authentication for Impala](#) on page 93 or [Enabling Kerberos Authentication for Impala](#) on page 90 for details.
- On the client side, to learn how to enable delegation, consult the documentation for the ODBC driver you are using.

Auditing Impala Operations

To monitor how Impala data is being used within your organization, ensure that your Impala authorization and authentication policies are effective. To detect attempts at intrusion or unauthorized access to Impala data, you can use the auditing feature in Impala 1.2.1 and higher:

- Enable auditing by including the option `##audit_event_log_dir=directory_path` in your `impalad` startup options. The log directory must be a local directory on the server, not an HDFS directory.
- Decide how many queries will be represented in each audit event log file. By default, Impala starts a new audit event log file every 5000 queries. To specify a different number, include the option `##max_audit_event_log_file_size=number_of_queries` in the `impalad` startup options.
- In Impala 2.9 and higher, you can control how many audit event log files are kept on each host. Specify the option `##max_audit_event_log_files=number_of_log_files` in the `impalad` startup options. Once the limit is reached, older files are rotated out using the same mechanism as for other Impala log files. The default value for this setting is 0, representing an unlimited number of audit event log files.
- Use a cluster manager with governance capabilities to filter, visualize, and produce reports based on the audit logs collected from all the hosts in the cluster.

Durability and Performance Considerations for Impala Auditing

The auditing feature only imposes performance overhead while auditing is enabled.

Because any Impala host can process a query, enable auditing on all hosts where the `impalad` daemon runs. Each host stores its own log files, in a directory in the local filesystem. The log data is periodically flushed to disk (through an `fsync()` system call) to avoid loss of audit data in case of a crash.

The runtime overhead of auditing applies to whichever host serves as the coordinator for the query, that is, the host you connect to when you issue the query. This might be the same host for all queries, or different applications or users might connect to and issue queries through different hosts.

To avoid excessive I/O overhead on busy coordinator hosts, Impala syncs the audit log data (using the `fsync()` system call) periodically rather than after every query. Currently, the `fsync()` calls are issued at a fixed interval, every 5 seconds.

By default, Impala avoids losing any audit log data in the case of an error during a logging operation (such as a disk full error), by immediately shutting down `impalad` on the host where the auditing problem occurred. You can override this setting by specifying the option `##abort_on_failed_audit_event=false` in the `impalad` startup options.

Format of the Audit Log Files

The audit log files represent the query information in JSON format, one query per line. Typically, rather than looking at the log files themselves, you should use cluster-management software to consolidate the log data from all Impala hosts and filter and visualize the results in useful ways. (If you do examine the raw log data, you might run the files through a JSON pretty-printer first.)

All the information about schema objects accessed by the query is encoded in a single nested record on the same line. For example, the audit log for an `INSERT . . . SELECT` statement records that a select operation occurs on the source table and an insert operation occurs on the destination table. The audit log for a query against a view records the base table accessed by the view, or multiple base tables in the case of a view that includes a join query. Every Impala operation that corresponds to a SQL statement is recorded in the audit logs, whether the operation succeeds or fails. Impala records more information for a successful operation than for a failed one, because an unauthorized query is stopped immediately, before all the query planning is completed.

The information logged for each query includes:

- Client session state:
 - Session ID
 - User name
 - Network address of the client connection
- SQL statement details:
 - Query ID
 - Statement Type - DML, DDL, and so on
 - SQL statement text
 - Execution start time, in local time
 - Execution Status - Details on any errors that were encountered
 - Target Catalog Objects:
 - Object Type - Table, View, or Database
 - Fully qualified object name
 - Privilege - How the object is being used (`SELECT`, `INSERT`, `CREATE`, and so on)

Which Operations Are Audited

The following types of SQL operations are recorded in the audit log:

- Queries that are prevented due to lack of authorization.
- Queries that Impala can analyze and parse to determine that they are authorized. The audit data is recorded immediately after Impala finishes its analysis, before the query is actually executed.
- Queries whose results are available to be fetched by clients.
- Finished DDL operations.

The audit log does not contain entries for queries that could not be parsed and analyzed. For example, a query that fails due to a syntax error is not recorded in the audit log.

The audit log does not contain queries that fail due to a reference to a table that does not exist.

Certain statements in the `impala-shell` interpreter, such as `CONNECT`, `SUMMARY`, `PROFILE`, `SET`, and `QUIT`, do not correspond to actual SQL queries, and these statements are not recorded in the audit log.

Viewing Lineage Information for Impala Data

Lineage is a feature that helps you track where data originated, and how data propagates through the system through SQL statements such as `SELECT`, `INSERT`, and `CREATE TABLE AS SELECT`.

This type of tracking is important in high-security configurations, especially in highly regulated industries such as healthcare, pharmaceuticals, financial services and intelligence. For such kinds of sensitive data, it is important to know all the places in the system that contain that data or other data derived from it; to verify who has accessed that data; and to be able to doublecheck that the data used to make a decision was processed correctly and not tampered with.

Column Lineage

Column lineage tracks information in fine detail, at the level of particular columns rather than entire tables.

For example, if you have a table with information derived from web logs, you might copy that data into other tables as part of the ETL process. The ETL operations might involve transformations through expressions and function calls, and rearranging the columns into more or fewer tables (*normalizing* or *denormalizing* the data). Then for reporting, you might issue queries against multiple tables and views. In this example, column lineage helps you determine that data that entered the system as `RAW_LOGS.FIELD1` was then turned into `WEBSITE_REPORTS.IP_ADDRESS` through an `INSERT . . . SELECT` statement. Or, conversely, you could start with a reporting query against a view, and trace the origin of the data in a field such as `TOP_10_VISITORS.USER_ID` back to the underlying table and even further back to the point where the data was first loaded into Impala.

When you have tables where you need to track or control access to sensitive information at the column level, see [Impala Authorization](#) on page 83 for how to implement column-level security. You set up authorization using the Ranger framework, create views that refer to specific sets of columns, and then assign authorization privileges to those views rather than the underlying tables.

Lineage Data for Impala

The lineage feature is enabled by default. When lineage logging is enabled, the serialized column lineage graph is computed for each query and stored in a specialized log file in JSON format.

Impala records queries in the lineage log if they complete successfully, or fail due to authorization errors. For write operations such as `INSERT` and `CREATE TABLE AS SELECT`, the statement is recorded in the lineage log only if it successfully completes. Therefore, the lineage feature tracks data that was accessed by successful queries, or that was attempted to be accessed by unsuccessful queries that were blocked due to authorization failure. These kinds of queries represent data that really was accessed, or where the attempted access could represent malicious activity.

Impala does not record in the lineage log queries that fail due to syntax errors or that fail or are cancelled before they reach the stage of requesting rows from the result set.

To enable or disable this feature, set or remove the `-lineage_event_log_dir` configuration option for the `impalad` daemon.

Impala SQL Language Reference

Impala uses SQL as its query language. To protect user investment in skills development and query design, Impala provides a high degree of compatibility with the Hive Query Language (HiveQL):

- Because Impala uses the same metadata store as Hive to record information about table structure and properties, Impala can access tables defined through the native Impala `CREATE TABLE` command, or tables created using the Hive data definition language (DDL).
- Impala supports data manipulation (DML) statements similar to the DML component of HiveQL.
- Impala provides many *built-in functions* with the same names and parameter types as their HiveQL equivalents.

Impala supports most of the same *statements and clauses* as HiveQL, including, but not limited to `JOIN`, `AGGREGATE`, `DISTINCT`, `UNION ALL`, `ORDER BY`, `LIMIT` and (uncorrelated) subquery in the `FROM` clause. Impala also supports `INSERT INTO` and `INSERT OVERWRITE`.

Impala supports data types with the same names and semantics as the equivalent Hive data types: `STRING`, `TINYINT`, `SMALLINT`, `INT`, `BIGINT`, `FLOAT`, `DOUBLE`, `BOOLEAN`, `STRING`, `TIMESTAMP`.

For full details about Impala SQL syntax and semantics, see [Impala SQL Statements](#) on page 213.

Most HiveQL `SELECT` and `INSERT` statements run unmodified with Impala. For information about Hive syntax not available in Impala, see [SQL Differences Between Impala and Hive](#) on page 606.

For a list of the built-in functions available in Impala queries, see [Impala Built-In Functions](#) on page 428.

Comments

Impala supports the familiar styles of SQL comments:

- All text from a `--` sequence to the end of the line is considered a comment and ignored. This type of comment can occur on a single line by itself, or after all or part of a statement.
- All text from a `/*` sequence to the next `*/` sequence is considered a comment and ignored. This type of comment can stretch over multiple lines. This type of comment can occur on one or more lines by itself, in the middle of a statement, or before or after a statement.

For example:

```
-- This line is a comment about a table.
create table ...;

/*
This is a multi-line comment about a query.
*/
select ...;

select * from t /* This is an embedded comment about a query. */ where ...;

select * from t -- This is a trailing comment within a multi-line command.
where ...;
```

Data Types

Impala supports a set of data types that you can use for table columns, expression values, and function arguments and return values.

Note: Currently, Impala supports only scalar types, not composite or nested types. Accessing a table containing any columns with unsupported types causes an error.

For the notation to write literals of each of these data types, see [Literals](#) on page 173.

Impala supports a limited set of implicit casts to avoid undesired results from unexpected casting behavior.

- Impala does not implicitly cast between string and numeric or Boolean types. Always use `CAST ()` for these conversions.
- Impala does perform implicit casts among the numeric types, when going from a smaller or less precise type to a larger or more precise one. For example, Impala will implicitly convert a `SMALLINT` to a `BIGINT` or `FLOAT`, but to convert from `DOUBLE` to `FLOAT` or `INT` to `TINYINT` requires a call to `CAST ()` in the query.
- Impala does perform implicit casts from `STRING` to `TIMESTAMP`. Impala has a restricted set of literal formats for the `TIMESTAMP` data type and the `FROM_UNIXTIME ()` format string; see [TIMESTAMP Data Type](#) on page 133 for details.

See the topics under this section for full details on implicit and explicit casting for each data type, and see [Impala Type Conversion Functions](#) on page 467 for details about the `CAST ()` function.

ARRAY Complex Type (Impala 2.3 or higher only)

A complex data type that can represent an arbitrary number of ordered elements. The elements can be scalars or another complex type (`ARRAY`, `STRUCT`, or `MAP`).

Syntax:

```
column_name ARRAY < type >
```

```
type ::= primitive_type | complex_type
```

Usage notes:

Because complex types are often used in combination, for example an ARRAY of STRUCT elements, if you are unfamiliar with the Impala complex types, start with [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for background information and usage examples.

The elements of the array have no names. You refer to the value of the array item using the ITEM pseudocolumn, or its position in the array with the POS pseudocolumn. See [ITEM and POS Pseudocolumns](#) on page 157 for information about these pseudocolumns.

Each row can have a different number of elements (including none) in the array for that row.

When an array contains items of scalar types, you can use aggregation functions on the array elements without using join notation. For example, you can find the COUNT(), AVG(), SUM(), and so on of numeric array elements, or the MAX() and MIN() of any scalar array elements by referring to `table_name.array_column` in the FROM clause of the query. When you need to cross-reference values from the array with scalar values from the same row, such as by including a GROUP BY clause to produce a separate aggregated result for each row, then the join clause is required.

A common usage pattern with complex types is to have an array as the top-level type for the column: an array of structs, an array of maps, or an array of arrays. For example, you can model a denormalized table by creating a column that is an ARRAY of STRUCT elements; each item in the array represents a row from a table that would normally be used in a join query. This kind of data structure lets you essentially denormalize tables by associating multiple rows from one table with the matching row in another table.

You typically do not create more than one top-level ARRAY column, because if there is some relationship between the elements of multiple arrays, it is convenient to model the data as an array of another complex type element (either STRUCT or MAP).

You can pass a multi-part qualified name to DESCRIBE to specify an ARRAY, STRUCT, or MAP column and visualize its structure as if it were a table. For example, if table T1 contains an ARRAY column A1, you could issue the statement DESCRIBE t1.a1. If table T1 contained a STRUCT column S1, and a field F1 within the STRUCT was a MAP, you could issue the statement DESCRIBE t1.s1.f1. An ARRAY is shown as a two-column table, with ITEM and POS columns. A STRUCT is shown as a table with each field representing a column in the table. A MAP is shown as a two-column table, with KEY and VALUE columns.

Added in: Impala 2.3.0

Restrictions:

- Columns with this data type can only be used in tables or partitions with the Parquet or ORC file format.
- Columns with this data type cannot be used as partition key columns in a partitioned table.
- The COMPUTE STATS statement does not produce any statistics for columns of this data type.
- The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.
- See [Limitations and Restrictions for Complex Types](#) on page 146 for a full list of limitations and associated guidelines about complex type columns.

Kudu considerations:

Currently, the data types CHAR, ARRAY, MAP, and STRUCT cannot be used with Kudu tables.

Examples:

Note: Many of the complex type examples refer to tables such as CUSTOMER and REGION adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 165 for the table definitions.

The following example shows how to construct a table with various kinds of ARRAY columns, both at the top level and nested within other complex types. Whenever the ARRAY consists of a scalar value, such as in the PETS column or the CHILDREN field, you can see that future expansion is limited. For example, you could not easily evolve the

schema to record the kind of pet or the child's birthday alongside the name. Therefore, it is more common to use an ARRAY whose elements are of STRUCT type, to associate multiple fields with each array element.

Note: Practice the CREATE TABLE and query notation for complex type columns using empty tables, until you can visualize a complex data structure and construct corresponding SQL statements reliably.

```
CREATE TABLE array_demo
(
  id BIGINT,
  name STRING,
  -- An ARRAY of scalar type as a top-level column.
  pets ARRAY <STRING>,

  -- An ARRAY with elements of complex type (STRUCT).
  places_lived ARRAY < STRUCT <
    place: STRING,
    start_year: INT
  >>,

  -- An ARRAY as a field (CHILDREN) within a STRUCT.
  -- (The STRUCT is inside another ARRAY, because it is rare
  -- for a STRUCT to be a top-level column.)
  marriages ARRAY < STRUCT <
    spouse: STRING,
    children: ARRAY <STRING>
  >>,

  -- An ARRAY as the value part of a MAP.
  -- The first MAP field (the key) would be a value such as
  -- 'Parent' or 'Grandparent', and the corresponding array would
  -- represent 2 parents, 4 grandparents, and so on.
  ancestors MAP < STRING, ARRAY <STRING> >
)
STORED AS PARQUET;
```

The following example shows how to examine the structure of a table containing one or more ARRAY columns by using the DESCRIBE statement. You can visualize each ARRAY as its own two-column table, with columns ITEM and POS.

```
DESCRIBE array_demo;
+-----+-----+
| name      | type                                     |
+-----+-----+
| id        | bigint                                 |
| name      | string                                 |
| pets      | array<string>                          |
| marriages | array<struct<                           |
|           |   spouse:string,                      |
|           |   children:array<string>              |
|           | >>                                    |
| places_lived | array<struct<                          |
|           |   place:string,                      |
|           |   start_year:int                    |
|           | >>                                    |
| ancestors | map<string,array<string>>              |
+-----+-----+

DESCRIBE array_demo.pets;
+-----+-----+
| name | type |
+-----+-----+
| item | string |
```



```

| pos | bigint |
+-----+-----+

DESCRIBE array_demo.marriages;
+-----+-----+
| name | type |
+-----+-----+
| item | struct<
|      |   spouse:string,
|      |   children:array<string>
|      | >
| pos  | bigint
+-----+-----+

DESCRIBE array_demo.places_lived;
+-----+-----+
| name | type |
+-----+-----+
| item | struct<
|      |   place:string,
|      |   start_year:int
|      | >
| pos  | bigint
+-----+-----+

DESCRIBE array_demo.ancestors;
+-----+-----+
| name | type |
+-----+-----+
| key  | string
| value| array<string>
+-----+-----+

```

The following example shows queries involving ARRAY columns containing elements of scalar or complex types. You “unpack” each ARRAY column by referring to it in a join query, as if it were a separate table with ITEM and POS columns. If the array element is a scalar type, you refer to its value using the ITEM pseudocolumn. If the array element is a STRUCT, you refer to the STRUCT fields using dot notation and the field names. If the array element is another ARRAY or a MAP, you use another level of join to unpack the nested collection elements.

```

-- Array of scalar values.
-- Each array element represents a single string, plus we know its position
-- in the array.
SELECT id, name, pets.pos, pets.item FROM array_demo, array_demo.pets;

-- Array of structs.
-- Now each array element has named fields, possibly of different types.
-- You can consider an ARRAY of STRUCT to represent a table inside another
-- table.
SELECT id, name, places_lived.pos, places_lived.item.place,
       places_lived.item.start_year
FROM array_demo, array_demo.places_lived;

-- The .ITEM name is optional for array elements that are structs.
-- The following query is equivalent to the previous one, with .ITEM
-- removed from the column references.
SELECT id, name, places_lived.pos, places_lived.place,
       places_lived.start_year
FROM array_demo, array_demo.places_lived;

-- To filter specific items from the array, do comparisons against the .POS
-- or .ITEM
-- pseudocolumns, or names of struct fields, in the WHERE clause.

```

```

SELECT id, name, pets.item FROM array_demo, array_demo.pets
  WHERE pets.pos in (0, 1, 3);

SELECT id, name, pets.item FROM array_demo, array_demo.pets
  WHERE pets.item LIKE 'Mr. %';

SELECT id, name, places_lived.pos, places_lived.place,
       places_lived.start_year
  FROM array_demo, array_demo.places_lived
 WHERE places_lived.place like '%California%';

```

Related information:

[Complex Types \(Impala 2.3 or higher only\)](#) on page 142, [STRUCT Complex Type \(Impala 2.3 or higher only\)](#) on page 127, [MAP Complex Type \(Impala 2.3 or higher only\)](#) on page 119

BIGINT Data Type

An 8-byte integer data type used in CREATE TABLE and ALTER TABLE statements.

Syntax:

In the column definition of a CREATE TABLE statement:

```
column_name BIGINT
```

Range: -9223372036854775808 .. 9223372036854775807. There is no UNSIGNED subtype.

Conversions: Impala automatically converts to a floating-point type (FLOAT or DOUBLE) automatically.

Use CAST() to convert to TINYINT, SMALLINT, INT, STRING, or TIMESTAMP. Casting an integer or floating-point value N to TIMESTAMP produces a value that is N seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `##use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting TIMESTAMP represents a date and time in the local time zone.

Examples:

```

CREATE TABLE t1 (x BIGINT);
SELECT CAST(1000 AS BIGINT);

```

Usage notes:

BIGINT is a convenient type to use for column declarations because you can use any kind of integer values in INSERT statements and they are promoted to BIGINT where necessary. However, BIGINT also requires the most bytes of any integer type on disk and in memory, meaning your queries are not as efficient and scalable as possible if you overuse this type. Therefore, prefer to use the smallest integer type with sufficient range to hold all input values, and CAST() when necessary to the appropriate type.

For a convenient and automated way to check the bounds of the BIGINT type, call the functions MIN_BIGINT() and MAX_BIGINT().

If an integer value is too large to be represented as a BIGINT, use a DECIMAL instead with sufficient digits of precision.

NULL considerations: Casting any non-numeric value to this type produces a NULL value.

Partitioning: Prefer to use this type for a partition key column. Impala can process the numeric type more efficiently than a STRING representation of the value.

HBase considerations: This data type is fully compatible with HBase tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as an 8-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 174, [TINYINT Data Type](#) on page 139, [SMALLINT Data Type](#) on page 124, [INT Data Type](#) on page 118, [BIGINT Data Type](#) on page 106, [DECIMAL Data Type \(Impala 3.0 or higher only\)](#) on page 111, [Impala Mathematical Functions](#) on page 434

BOOLEAN Data Type

A data type used in `CREATE TABLE` and `ALTER TABLE` statements, representing a single true/false choice.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name BOOLEAN
```

Range: TRUE or FALSE. Do not use quotation marks around the TRUE and FALSE literal values. You can write the literal values in uppercase, lowercase, or mixed case. The values queried from a table are always returned in lowercase, true or false.

Conversions: Impala does not automatically convert any other type to BOOLEAN. All conversions must use an explicit call to the `CAST()` function.

You can use `CAST()` to convert any integer or floating-point type to BOOLEAN: a value of 0 represents false, and any non-zero value is converted to true.

```
SELECT CAST(42 AS BOOLEAN) AS nonzero_int, CAST(99.44 AS BOOLEAN) AS
nonzero_decimal,
       CAST(000 AS BOOLEAN) AS zero_int, CAST(0.0 AS BOOLEAN) AS zero_decimal;
+-----+-----+-----+-----+
| nonzero_int | nonzero_decimal | zero_int | zero_decimal |
+-----+-----+-----+-----+
| true        | true            | false    | false        |
+-----+-----+-----+-----+
```

When you cast the opposite way, from BOOLEAN to a numeric type, the result becomes either 1 or 0:

```
SELECT CAST(true AS INT) AS true_int, CAST(true AS DOUBLE) AS true_double,
       CAST(false AS INT) AS false_int, CAST(false AS DOUBLE) AS false_double;
+-----+-----+-----+-----+
| true_int | true_double | false_int | false_double |
+-----+-----+-----+-----+
| 1        | 1           | 0         | 0            |
+-----+-----+-----+-----+
```

You can cast DECIMAL values to BOOLEAN, with the same treatment of zero and non-zero values as the other numeric types. You cannot cast a BOOLEAN to a DECIMAL.

You cannot cast a STRING value to BOOLEAN, although you can cast a BOOLEAN value to STRING, returning '1' for true values and '0' for false values.

Although you can cast a `TIMESTAMP` to a `BOOLEAN` or a `BOOLEAN` to a `TIMESTAMP`, the results are unlikely to be useful. Any non-zero `TIMESTAMP` (that is, any value other than `1970-01-01 00:00:00`) becomes TRUE when converted to `BOOLEAN`, while `1970-01-01 00:00:00` becomes FALSE. A value of FALSE becomes `1970-01-01 00:00:00` when converted to `BOOLEAN`, and TRUE becomes one second past this epoch date, that is, `1970-01-01 00:00:01`.

NULL considerations: An expression of this type produces a NULL value if any argument of the expression is NULL.

Partitioning:

Do not use a BOOLEAN column as a partition key. Although you can create such a table, subsequent operations produce errors:

```
[localhost:21000] > create table truth_table (assertion string) partitioned
by (truth boolean);
[localhost:21000] > insert into truth_table values ('Pigs can fly',false);
ERROR: AnalysisException: INSERT into table with BOOLEAN partition column
(truth) is not supported: partitioning.truth_table
```

Examples:

```
SELECT 1 < 2;
SELECT 2 = 5;
SELECT 100 < NULL, 100 > NULL;
CREATE TABLE assertions (claim STRING, really BOOLEAN);
INSERT INTO assertions VALUES
  ("1 is less than 2", 1 < 2),
  ("2 is the same as 5", 2 = 5),
  ("Grass is green", true),
  ("The moon is made of green cheese", false);
SELECT claim FROM assertions WHERE really = TRUE;
```

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Kudu considerations:

Currently, the data types `BOOLEAN`, `FLOAT`, and `DOUBLE` cannot be used for primary key columns in Kudu tables.

Related information: [Boolean Literals](#) on page 176, [SQL Operators](#) on page 178, [Impala Conditional Functions](#) on page 502

CHAR Data Type (Impala 2.0 or higher only)

A fixed-length character type, padded with trailing spaces if necessary to achieve the specified length. If values are longer than the specified length, Impala truncates any trailing characters.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name CHAR(length)
```

The maximum *length* you can specify is 255.

Semantics of trailing spaces:

- When you store a CHAR value shorter than the specified length in a table, queries return the value padded with trailing spaces if necessary; the resulting value has the same length as specified in the column definition.
- Leading spaces in CHAR are preserved within the data file.

- If you store a CHAR value containing trailing spaces in a table, those trailing spaces are not stored in the data file. When the value is retrieved by a query, the result could have a different number of trailing spaces. That is, the value includes however many spaces are needed to pad it to the specified length of the column.
- If you compare two CHAR values that differ only in the number of trailing spaces, those values are considered identical.
- When comparing or processing CHAR values:
 - CAST() truncates any longer string to fit within the defined length. For example:

```
SELECT CAST('x' AS CHAR(4)) = CAST('x      ' AS CHAR(4)); -- Returns
TRUE.
```

- If a CHAR value is shorter than the specified length, it is padded on the right with spaces until it matches the specified length.
- CHAR_LENGTH() returns the length including any trailing spaces.
- LENGTH() returns the length excluding trailing spaces.
- CONCAT() returns the length including trailing spaces.

Partitioning: This type can be used for partition key columns. Because of the efficiency advantage of numeric values over character-based values, if the partition key is a string representation of a number, prefer to use an integer type with sufficient range (INT, BIGINT, and so on) where practical.

HBase considerations: This data type cannot be used with HBase tables.

Parquet considerations:

- This type can be read from and written to Parquet files.
- There is no requirement for a particular level of Parquet.
- Parquet files generated by Impala and containing this type can be freely interchanged with other components such as Hive and MapReduce.
- Any trailing spaces, whether implicitly or explicitly specified, are not written to the Parquet data files.
- Parquet data files might contain values that are longer than allowed by the CHAR(*n*) length limit. Impala ignores any extra trailing characters when it processes those values during a query.

Text table considerations:

Text data files might contain values that are longer than allowed for a particular CHAR(*n*) column. Any extra trailing characters are ignored when Impala processes those values during a query. Text data files can also contain values that are shorter than the defined length limit, and Impala pads them with trailing spaces up to the specified length. Any text data files produced by Impala INSERT statements do not include any trailing blanks for CHAR columns.

Avro considerations:

The Avro specification allows string values up to 2⁶⁴ bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths. In Impala 2.5 and higher, Impala truncates CHAR and VARCHAR values in Avro tables to (2³¹)-1 bytes. If a query encounters a STRING value longer than (2³¹)-1 bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Compatibility:

This type is available using Impala 2.0 or higher.

Some other database systems make the length specification optional. For Impala, the length is required.

Internal details: Represented in memory as a byte array with the same size as the length specification. Values that are shorter than the specified length are padded on the right with trailing spaces.

Added in: Impala 2.0.0

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the COMPUTE STATS statement.

UDF considerations: This type cannot be used for the argument or return type of a user-defined function (UDF) or user-defined aggregate function (UDA).

Kudu considerations:

Currently, the data types CHAR, ARRAY, MAP, and STRUCT cannot be used with Kudu tables.

Performance consideration:

The CHAR type currently does not have the Impala Codegen support, and we recommend using VARCHAR or STRING over CHAR as the performance gain of Codegen outweighs the benefits of fixed width CHAR.

Restrictions:

Because the blank-padding behavior requires allocating the maximum length for each value in memory, for scalability reasons, you should avoid declaring CHAR columns that are much longer than typical values in that column.

All data in CHAR and VARCHAR columns must be in a character encoding that is compatible with UTF-8. If you have binary data from another database system (that is, a BLOB type), use a STRING column to hold it.

When an expression compares a CHAR with a STRING or VARCHAR, the CHAR value is implicitly converted to STRING first, with trailing spaces preserved.

This behavior differs from other popular database systems. To get the expected result of TRUE, cast the expressions on both sides to CHAR values of the appropriate length. For example:

```
SELECT CAST('foo ' AS CHAR(5)) = CAST('foo' AS CHAR(3)); -- Returns TRUE.
```

This behavior is subject to change in future releases.

Related information:

[STRING Data Type](#) on page 125, [VARCHAR Data Type \(Impala 2.0 or higher only\)](#) on page 140, [String Literals](#) on page 175, [Impala String Functions](#) on page 509

DATE Data Type

Use the DATE data type to store date values. The DATE type is supported for Avro, HBase, Kudu, Parquet, and Text.

Range:

0001-01-01 to 9999-12-31

Literals and expressions:

The DATE literals are in the form of DATE 'YYYY-MM-DD'. For example, DATE '2013-01-01'

Parquet and Avro considerations:

Parquet and Avro use DATE logical type for dates. The DATE logical type annotates an INT32 that stores the number of days from the Unix epoch, January 1, 1970. This representation introduces an interoperability issue between Impala and older versions of Hive:

If Hive versions lower than 3.1 wrote dates earlier than 1582-10-15 to a Parquet or Avro table, those dates would be read back incorrectly by Impala and vice versa. In Hive 3.1 and higher, this is no longer an issue.

Explicit casting between DATE and other data types:

DATE type can only be converted to/from DATE, TIMESTAMP, or STRING types as described below.

Cast from	Cast to	Result
TIMESTAMP	DATE	The date component of the TIMESTAMP is returned, and the time of the day component of the TIMESTAMP is ignored.

Cast from	Cast to	Result
STRING	DATE	<p>The DATE value of yyyy-MM-dd is returned.</p> <p>The STRING value must be in the yyyy-MM-dd or yyyy-MM-dd HH:mm:ss.SSSSSSSS pattern.</p> <p>If the time component is present in STRING, it is silently ignored.</p> <p>If the STRING value does not match the above formats, an error is returned.</p>
DATE	TIMESTAMP	The year, month, and day of the DATE is returned along with the time of day component set to 00:00:00.
DATE	STRING	The STRING value, 'yyyy-MM-dd', is returned.

Implicit casting between DATE and other types:

Implicit casting is supported:

- From STRING to DATE if the source STRING value is in the yyyy-MM-dd or yyyy-MM-dd HH:mm:ss.SSSSSSSS pattern.
- From DATE to TIMESTAMP.

Added in:

The DATE type is available in Impala 3.3 and higher.

Kudu considerations:

In Impala 3.4, you can read and write DATE values to Kudu tables.

DECIMAL Data Type (Impala 3.0 or higher only)

The DECIMAL data type is a numeric data type with fixed scale and precision.

The data type is useful for storing and doing operations on precise decimal values.

Syntax:

```
DECIMAL[ (precision[ , scale] ) ]
```

Precision:

precision represents the total number of digits that can be represented regardless of the location of the decimal point.

This value must be between 1 and 38, specified as an integer literal.

The default precision is 9.

Scale:

scale represents the number of fractional digits.

This value must be less than or equal to the precision, specified as an integer literal.

The default scale is 0.

When the precision and the scale are omitted, a DECIMAL is treated as DECIMAL(9, 0).

Range:

The range of DECIMAL type is $-10^{38} + 1$ through $10^{38} - 1$.

The largest value is represented by DECIMAL(38, 0).

The most precise fractional value (between 0 and 1, or 0 and -1) is represented by `DECIMAL(38, 38)`, with 38 digits to the right of the decimal point. The value closest to 0 would be .0000...1 (37 zeros and the final 1). The value closest to 1 would be .999... (9 repeated 38 times).

Memory and disk storage:

Only the precision determines the storage size for `DECIMAL` values, and the scale setting has no effect on the storage size. The following table describes the in-memory storage once the values are loaded into memory.

Precision	In-memory Storage
1 - 9	4 bytes
10 - 18	8 bytes
19 - 38	16 bytes

The on-disk representation varies depending on the file format of the table.

Text, RCFile, and SequenceFile tables use ASCII-based formats as below:

- Leading zeros are not stored.
- Trailing zeros are stored.
- Each `DECIMAL` value takes up as many bytes as the precision of the value, plus:
 - One extra byte if the decimal point is present.
 - One extra byte for negative values.

Parquet and Avro tables use binary formats and offer more compact storage for `DECIMAL` values. In these tables, Impala stores each value in fewer bytes where possible depending on the precision specified for the `DECIMAL` column. To conserve space in large tables, use the smallest-precision `DECIMAL` type.

Precision and scale in arithmetic operations:

For all arithmetic operations, the resulting precision is at most 38.

If the resulting precision would be greater than 38, Impala truncates the result from the back, but keeps at least 6 fractional digits in scale and rounds.

For example, `DECIMAL(38, 20) * DECIMAL(38, 20)` returns `DECIMAL(38, 6)`. According to the table below, the resulting precision and scale would be (77, 40), but they are higher than the maximum precision and scale for `DECIMAL`. So, Impala sets the precision to the maximum allowed 38, and truncates the scale to 6.

When you use `DECIMAL` values in arithmetic operations, the precision and scale of the result value are determined as follows. For better readability, the following terms are used in the table below:

- P1, P2: Input precisions
- S1, S2: Input scales
- L1, L2: Leading digits in input `DECIMAL`s, i.e., $L1 = P1 - S1$ and $L2 = P2 - S2$

Operation	Resulting Precision	Resulting Scale
Addition and Subtraction	$\max(L1, L2) + \max(S1, S2) + 1$ 1 is for carry-over.	$\max(S1, S2)$
Multiplication	$P1 + P2 + 1$	$S1 + S2$
Division	$L1 + S2 + \max(S1 + P2 + 1, 6)$	$\max(S1 + P2 + 1, 6)$
Modulo	$\min(L1, L2) + \max(S1, S2)$	$\max(S1, S2)$

Precision and scale in functions:

When you use DECIMAL values in built-in functions, the precision and scale of the result value are determined as follows:

- The result of the SUM aggregate function on a DECIMAL value is:
 - Precision: 38
 - Scale: The same scale as the input column
- The result of AVG aggregate function on a DECIMAL value is:
 - Precision: 38
 - Scale: max(Scale of input column, 6)

Implicit conversions in DECIMAL assignments:

Impala enforces strict conversion rules in decimal assignments like in INSERT and UNION statements, or in functions like COALESCE.

If there is not enough precision and scale in the destination, Impala fails with an error.

Impala performs implicit conversions between DECIMAL and other numeric types as below:

- DECIMAL is implicitly converted to DOUBLE or FLOAT when necessary even with a loss of precision. It can be necessary, for example when inserting a DECIMAL value into a DOUBLE column. For example:

```
CREATE TABLE flt(c FLOAT);
INSERT INTO flt SELECT CAST(1e37 AS DECIMAL(38, 0));
SELECT CAST(c AS DECIMAL(38, 0)) FROM flt;
```

```
Result: 9999999933815812510711506376257961984
```

The result has a loss of information due to implicit casting. This is why we discourage using the DOUBLE and FLOAT types in general.

- DOUBLE and FLOAT cannot be implicitly converted to DECIMAL. An error is returned.
- DECIMAL is implicitly converted to DECIMAL if all digits fit in the resulting DECIMAL.

For example, the following query returns an error because the resulting type that guarantees that all digits fit cannot be determined.

```
SELECT GREATEST (CAST(1 AS DECIMAL(38, 0)), CAST(2 AS DECIMAL(38, 37)));
```

- Integer values can be implicitly converted to DECIMAL when there is enough room in the DECIMAL to guarantee that all digits fit. The integer types require the following numbers of digits to the left of the decimal point when converted to DECIMAL:
 - BIGINT: 19 digits
 - INT: 10 digits
 - SMALLINT: 5 digits
 - TINYINT: 3 digits

For example:

```
CREATE TABLE decimals_10_8 (x DECIMAL(10, 8));
INSERT INTO decimals_10_8 VALUES (CAST(1 AS TINYINT));
```

The above INSERT statement fails because TINYINT requires room for 3 digits to the left of the decimal point in the DECIMAL.

```
CREATE TABLE decimals_11_8(x DECIMAL(11, 8));
INSERT INTO decimals_11_8 VALUES (CAST(1 AS TINYINT));
```

The above INSERT statement succeeds because there is enough room for 3 digits to the left of the decimal point that TINYINT requires.

In UNION, the resulting precision and scales are determined as follows.

- Precision: $\max(L1, L2) + \max(S1, S2)$

If the resulting type does not fit in the DECIMAL type, an error is returned. See the first example below.

- Scale: $\max(S1, S2)$

Examples for UNION:

- `DECIMAL(20, 0) UNION DECIMAL(20, 20)` would require a `DECIMAL(40, 20)` to fit all the digits. Since this is larger than the max precision for DECIMAL, Impala returns an error. One way to fix the error is to cast both operands to the desired type, for example `DECIMAL(38, 18)`.
- `DECIMAL(20, 2) UNION DECIMAL(8, 6)` returns `DECIMAL(24, 6)`.
- `INT UNION DECIMAL(9, 4)` returns `DECIMAL(14, 4)`.

INT has the precision 10 and the scale 0, so it is treated as `DECIMAL(10, 0) UNION DECIMAL(9, 4)`.

Casting between DECIMAL and other data types:

To avoid potential conversion errors, use CAST to explicitly convert between DECIMAL and other types in decimal assignments like in INSERT and UNION statements, or in functions like COALESCE:

- You can cast the following types to DECIMAL: FLOAT, TINYINT, SMALLINT, INT, BIGINT, STRING
- You can cast DECIMAL to the following types: FLOAT, TINYINT, SMALLINT, INT, BIGINT, STRING, BOOLEAN, TIMESTAMP

Impala performs CAST between DECIMAL and other numeric types as below:

- Precision: If you cast a value with bigger precision than the precision of the destination type, Impala returns an error. For example, `CAST(123456 AS DECIMAL(3, 0))` returns an error because all digits do not fit into `DECIMAL(3, 0)`
- Scale: If you cast a value with more fractional digits than the scale of the destination type, the fractional digits are rounded. For example, `CAST(1.239 AS DECIMAL(3, 2))` returns `1.24`.

Casting STRING to DECIMAL:

You can cast STRING of numeric characters in columns, literals, or expressions to DECIMAL as long as number fits within the specified target DECIMAL type without overflow.

- If scale in STRING > scale in DECIMAL, the fractional digits are rounded to the DECIMAL scale.

For example, `CAST('98.678912' AS DECIMAL(15, 1))` returns `98.7`.

- If # leading digits in STRING > # leading digits in DECIMAL, an error is returned.

For example, `CAST('123.45' AS DECIMAL(2, 2))` returns an error.

Exponential notation is supported when casting from STRING.

For example, `CAST('1.0e6' AS DECIMAL(32, 0))` returns `1000000`.

Casting any non-numeric value, such as 'ABC' to the DECIMAL type returns an error.

Casting DECIMAL to TIMESTAMP:

Casting a DECIMAL value N to TIMESTAMP produces a value that is N seconds past the start of the epoch date (January 1, 1970).

DECIMAL vs FLOAT consideration:

The FLOAT and DOUBLE types can cause problems or unexpected behavior due to inability to precisely represent certain fractional values, for example dollar and cents values for currency. You might find output values slightly different than you inserted, equality tests that do not match precisely, or unexpected values for GROUP BY columns. The DECIMAL type can help reduce unexpected behavior and rounding errors, but at the expense of some performance overhead for assignments and comparisons.

Literals and expressions:

Because the DECIMAL type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Compatibility with older version of DECIMAL:

This version of DECIMAL type is the default in Impala 3.0 and higher. The key differences between this version of DECIMAL and the previous DECIMAL V1 in Impala 2.x include the following.

	DECIMAL in Impala 3.0 or higher	DECIMAL in Impala 2.12 or lower
Overall behavior	Returns either the result or an error.	Returns either the result or NULL with a warning.
Overflow behavior	Aborts with an error.	Issues a warning and returns NULL.
Truncation / rounding behavior in arithmetic	Truncates and rounds digits from the back.	Truncates digits from the front.
String cast	Truncates from the back and rounds.	Truncates from the back.

If you need to continue using the first version of the DECIMAL type for the backward compatibility of your queries, set the `DECIMAL_V2` query option to `FALSE`:

```
SET DECIMAL_V2=FALSE;
```

Compatibility with other databases:

Use the DECIMAL data type in Impala for applications where you used the NUMBER data type in Oracle.

The Impala DECIMAL type does not support the Oracle idioms of `*` for scale.

The Impala DECIMAL type does not support negative values for precision.

DOUBLE Data Type

A double precision floating-point data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name DOUBLE
```

Range: 4.94065645841246544e-324d .. 1.79769313486231570e+308, positive or negative

Precision: 15 to 17 significant digits, depending on usage. The number of significant digits does not depend on the position of the decimal point.

Representation: The values are stored in 8 bytes, using *IEEE 754 Double Precision Binary Floating Point* format.

Conversions: Impala does not automatically convert DOUBLE to any other type. You can use `CAST()` to convert DOUBLE values to `FLOAT`, `TINYINT`, `SMALLINT`, `INT`, `BIGINT`, `STRING`, `TIMESTAMP`, or `BOOLEAN`. You can use exponential notation in DOUBLE literals or when casting from `STRING`, for example `1.0e6` to represent one million. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `##use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Usage notes:

The data type `REAL` is an alias for `DOUBLE`.

Impala does not evaluate NaN (not a number) as equal to any other numeric values, including other NaN values. For example, the following statement, which evaluates equality between two NaN values, returns `false`:

```
SELECT CAST( 'nan' AS DOUBLE)=CAST( 'nan' AS DOUBLE) ;
```

Examples:

```
CREATE TABLE t1 (x DOUBLE);
SELECT CAST(1000.5 AS DOUBLE) ;
```

Partitioning: Because fractional values of this type are not always represented precisely, when this type is used for a partition key column, the underlying HDFS directories might not be named exactly as you expect. Prefer to partition on a DECIMAL column instead.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as an 8-byte value.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Restrictions:

Due to the way arithmetic on FLOAT and DOUBLE columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for aggregate function calls such as `SUM()` and `AVG()` for FLOAT and DOUBLE columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the DECIMAL data type for such operations instead of FLOAT or DOUBLE.

The inability to exactly represent certain floating-point values means that DECIMAL is sometimes a better choice than DOUBLE or FLOAT when precision is critical, particularly when transferring data from other database systems that use different representations or file formats.

Kudu considerations:

Currently, the data types BOOLEAN, FLOAT, and DOUBLE cannot be used for primary key columns in Kudu tables.

Related information:

[Numeric Literals](#) on page 174, [Impala Mathematical Functions](#) on page 434, [FLOAT Data Type](#) on page 117

FLOAT Data Type

A single precision floating-point data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name FLOAT
```

Range: 1.40129846432481707e-45 .. 3.40282346638528860e+38, positive or negative

Precision: 6 to 9 significant digits, depending on usage. The number of significant digits does not depend on the position of the decimal point.

Representation: The values are stored in 4 bytes, using [IEEE 754 Single Precision Binary Floating Point](#) format.

Conversions: Impala automatically converts FLOAT to more precise DOUBLE values, but not the other way around. You can use CAST() to convert FLOAT values to TINYINT, SMALLINT, INT, BIGINT, STRING, TIMESTAMP, or BOOLEAN. You can use exponential notation in FLOAT literals or when casting from STRING, for example 1.0e6 to represent one million. Casting an integer or floating-point value N to TIMESTAMP produces a value that is N seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `##use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting TIMESTAMP represents a date and time in the local time zone.

Usage notes:

Impala does not evaluate NaN (not a number) as equal to any other numeric values, including other NaN values. For example, the following statement, which evaluates equality between two NaN values, returns false:

```
SELECT CAST('nan' AS FLOAT)=CAST('nan' AS FLOAT);
```

Examples:

```
CREATE TABLE t1 (x FLOAT);
SELECT CAST(1000.5 AS FLOAT);
```

Partitioning: Because fractional values of this type are not always represented precisely, when this type is used for a partition key column, the underlying HDFS directories might not be named exactly as you expect. Prefer to partition on a DECIMAL column instead.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 4-byte value.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the COMPUTE STATS statement.

Restrictions:

Due to the way arithmetic on FLOAT and DOUBLE columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for aggregate function calls such as SUM() and AVG() for FLOAT and DOUBLE columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the DECIMAL data type for such operations instead of FLOAT or DOUBLE.

The inability to exactly represent certain floating-point values means that DECIMAL is sometimes a better choice than DOUBLE or FLOAT when precision is critical, particularly when transferring data from other database systems that use different representations or file formats.

Kudu considerations:

Currently, the data types BOOLEAN, FLOAT, and DOUBLE cannot be used for primary key columns in Kudu tables.

Related information:

[Numeric Literals](#) on page 174, [Impala Mathematical Functions](#) on page 434, [DOUBLE Data Type](#) on page 116

INT Data Type

A 4-byte integer data type used in CREATE TABLE and ALTER TABLE statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name INT
```

Range: -2147483648 .. 2147483647. There is no `UNSIGNED` subtype.

Conversions: Impala automatically converts to a larger integer type (`BIGINT`) or a floating-point type (`FLOAT` or `DOUBLE`) automatically. Use `CAST()` to convert to `TINYINT`, `SMALLINT`, `STRING`, or `TIMESTAMP`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `##use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Usage notes:

The data type `INTEGER` is an alias for `INT`.

For a convenient and automated way to check the bounds of the `INT` type, call the functions `MIN_INT()` and `MAX_INT()`.

If an integer value is too large to be represented as a `INT`, use a `BIGINT` instead.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

Examples:

```
CREATE TABLE t1 (x INT);
SELECT CAST(1000 AS INT);
```

Partitioning: Prefer to use this type for a partition key column. Impala can process the numeric type more efficiently than a `STRING` representation of the value.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations:

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 4-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 174, [TINYINT Data Type](#) on page 139, [SMALLINT Data Type](#) on page 124, [INT Data Type](#) on page 118, [BIGINT Data Type](#) on page 106, [DECIMAL Data Type \(Impala 3.0 or higher only\)](#) on page 111, [Impala Mathematical Functions](#) on page 434

MAP Complex Type (Impala 2.3 or higher only)

A complex data type representing an arbitrary set of key-value pairs. The key part is a scalar type, while the value part can be a scalar or another complex type (`ARRAY`, `STRUCT`, or `MAP`).

Syntax:

```
column_name MAP < primitive_type, type >

type ::= primitive_type | complex_type
```

Usage notes:

Because complex types are often used in combination, for example an ARRAY of STRUCT elements, if you are unfamiliar with the Impala complex types, start with [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for background information and usage examples.

The MAP complex data type represents a set of key-value pairs. Each element of the map is indexed by a primitive type such as BIGINT or STRING, letting you define sequences that are not continuous or categories with arbitrary names. You might find it convenient for modelling data produced in other languages, such as a Python dictionary or Java HashMap, where a single scalar value serves as the lookup key.

In a big data context, the keys in a map column might represent a numeric sequence of events during a manufacturing process, or TIMESTAMP values corresponding to sensor observations. The map itself is inherently unordered, so you choose whether to make the key values significant (such as a recorded TIMESTAMP) or synthetic (such as a random global universal ID).

Note: Behind the scenes, the MAP type is implemented in a similar way as the ARRAY type. Impala does not enforce any uniqueness constraint on the KEY values, and the KEY values are processed by looping through the elements of the MAP rather than by a constant-time lookup. Therefore, this type is primarily for ease of understanding when importing data and algorithms from non-SQL contexts, rather than optimizing the performance of key lookups.

You can pass a multi-part qualified name to DESCRIBE to specify an ARRAY, STRUCT, or MAP column and visualize its structure as if it were a table. For example, if table T1 contains an ARRAY column A1, you could issue the statement DESCRIBE t1.a1. If table T1 contained a STRUCT column S1, and a field F1 within the STRUCT was a MAP, you could issue the statement DESCRIBE t1.s1.f1. An ARRAY is shown as a two-column table, with ITEM and POS columns. A STRUCT is shown as a table with each field representing a column in the table. A MAP is shown as a two-column table, with KEY and VALUE columns.

Added in: Impala 2.3.0

Restrictions:

- Columns with this data type can only be used in tables or partitions with the Parquet or ORC file format.
- Columns with this data type cannot be used as partition key columns in a partitioned table.
- The COMPUTE STATS statement does not produce any statistics for columns of this data type.
- The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.
- See [Limitations and Restrictions for Complex Types](#) on page 146 for a full list of limitations and associated guidelines about complex type columns.

Kudu considerations:

Currently, the data types CHAR, ARRAY, MAP, and STRUCT cannot be used with Kudu tables.

Examples:

Note: Many of the complex type examples refer to tables such as CUSTOMER and REGION adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 165 for the table definitions.

The following example shows a table with various kinds of MAP columns, both at the top level and nested within other complex types. Each row represents information about a specific country, with complex type fields of various levels of nesting to represent different information associated with the country: factual measurements such as area and population, notable people in different categories, geographic features such as cities, points of interest within each city, and mountains with associated facts. Practice the CREATE TABLE and query notation for complex type columns using empty tables, until you can visualize a complex data structure and construct corresponding SQL statements reliably.

```
create TABLE map_demo
(
  country_id BIGINT,

  -- Numeric facts about each country, looked up by name.
  -- For example, 'Area':1000, 'Population':999999.
```



```

-- Using a MAP instead of a STRUCT because there could be
-- a different set of facts for each country.
    metrics MAP <STRING, BIGINT>,

-- MAP whose value part is an ARRAY.
-- For example, the key 'Famous Politicians' could represent an array of 10
    elements,
-- while the key 'Famous Actors' could represent an array of 20 elements.
    notables MAP <STRING, ARRAY <STRING>>,

-- MAP that is a field within a STRUCT.
-- (The STRUCT is inside another ARRAY, because it is rare
-- for a STRUCT to be a top-level column.)
-- For example, city #1 might have points of interest with key 'Zoo',
-- representing an array of 3 different zoos.
-- City #2 might have completely different kinds of points of interest.
-- Because the set of field names is potentially large, and most entries
    could be blank,
-- a MAP makes more sense than a STRUCT to represent such a sparse data
    structure.
    cities ARRAY < STRUCT <
        name: STRING,
        points_of_interest: MAP <STRING, ARRAY <STRING>>
    >>,

-- MAP that is an element within an ARRAY. The MAP is inside a STRUCT field
    to associate
-- the mountain name with all the facts about the mountain.
-- The "key" of the map (the first STRING field) represents the name of some
    fact whose value
-- can be expressed as an integer, such as 'Height', 'Year First Climbed',
    and so on.
    mountains ARRAY < STRUCT < name: STRING, facts: MAP <STRING, INT > > >
)
STORED AS PARQUET;

```

```
DESCRIBE map_demo;
```

name	type
country_id	bigint
metrics	map<string,bigint>
notables	map<string,array<string>>
cities	array<struct< name:string, points_of_interest:map<string,array<string>> >>
mountains	array<struct< name:string, facts:map<string,int> >>

```
DESCRIBE map_demo.metrics;
```

name	type
key	string
value	bigint

```
DESCRIBE map_demo.notables;
```

name	type
key	string
value	array<string>

```
DESCRIBE map_demo.notables.value;
```

name	type
item	string
pos	bigint

```
DESCRIBE map_demo.cities;
```

name	type
item	struct< name:string, points_of_interest:map<string,array<string>> >
pos	bigint

```
DESCRIBE map_demo.cities.item.points_of_interest;
```

name	type
key	string
value	array<string>

```
DESCRIBE map_demo.cities.item.points_of_interest.value;
```

name	type
item	string
pos	bigint

```
DESCRIBE map_demo.mountains;
```

name	type
item	struct< name:string, facts:map<string,int> >
pos	bigint

```
DESCRIBE map_demo.mountains.item.facts;
```

name	type
key	string
value	int

The following example shows a table that uses a variety of data types for the MAP “key” field. Typically, you use BIGINT or STRING to use numeric or character-based keys without worrying about exceeding any size or length constraints.

```
CREATE TABLE map_demo_obscure
(
  id BIGINT,
  m1 MAP <INT, INT>,
  m2 MAP <SMALLINT, INT>,
  m3 MAP <TINYINT, INT>,
  m4 MAP <TIMESTAMP, INT>,
  m5 MAP <BOOLEAN, INT>,
  m6 MAP <CHAR(5), INT>,
  m7 MAP <VARCHAR(25), INT>,
  m8 MAP <FLOAT, INT>,
  m9 MAP <DOUBLE, INT>,
  m10 MAP <DECIMAL(12,2), INT>
)
STORED AS PARQUET;
```

```
CREATE TABLE celebrities (name STRING, birth_year MAP < STRING, SMALLINT >)
  STORED AS PARQUET;
-- A typical row might represent values with 2 different birth years, such
  as:
-- ("Joe Movie Star", { "real": 1972, "claimed": 1977 })

CREATE TABLE countries (name STRING, famous_leaders MAP < INT, STRING >)
  STORED AS PARQUET;
-- A typical row might represent values with different leaders, with key
  values corresponding to their numeric sequence, such as:
-- ("United States", { 1: "George Washington", 3: "Thomas Jefferson", 16:
  "Abraham Lincoln" })

CREATE TABLE airlines (name STRING, special_meals MAP < STRING, MAP <
  STRING, STRING > >) STORED AS PARQUET;
-- A typical row might represent values with multiple kinds of meals, each
  with several components:
-- ("Elegant Airlines",
--   {
--     "vegetarian": { "breakfast": "pancakes", "snack": "cookies",
--     "dinner": "rice pilaf" },
--     "gluten free": { "breakfast": "oatmeal", "snack": "fruit", "dinner":
--     "chicken" }
--   } )
```

Related information:

[Complex Types \(Impala 2.3 or higher only\)](#) on page 142, [ARRAY Complex Type \(Impala 2.3 or higher only\)](#) on page 102, [STRUCT Complex Type \(Impala 2.3 or higher only\)](#) on page 127

REAL Data Type

An alias for the DOUBLE data type. See [DOUBLE Data Type](#) on page 116 for details.

Examples:

These examples show how you can use the type names REAL and DOUBLE interchangeably, and behind the scenes Impala treats them always as DOUBLE.

```
[localhost:21000] > create table r1 (x real);
[localhost:21000] > describe r1;
```

```

+-----+-----+-----+
| name | type  | comment |
+-----+-----+-----+
| x     | double |          |
+-----+-----+-----+
[localhost:21000] > insert into r1 values (1.5), (cast (2.2 as double));
[localhost:21000] > select cast (1e6 as real);
+-----+-----+-----+
| cast(1000000.0 as double) |
+-----+-----+-----+
| 1000000                   |
+-----+-----+-----+

```

SMALLINT Data Type

A 2-byte integer data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name SMALLINT
```

Range: -32768 .. 32767. There is no `UNSIGNED` subtype.

Conversions: Impala automatically converts to a larger integer type (`INT` or `BIGINT`) or a floating-point type (`FLOAT` or `DOUBLE`) automatically. Use `CAST()` to convert to `TINYINT`, `STRING`, or `TIMESTAMP`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `##use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Usage notes:

For a convenient and automated way to check the bounds of the `SMALLINT` type, call the functions `MIN_SMALLINT()` and `MAX_SMALLINT()`.

If an integer value is too large to be represented as a `SMALLINT`, use an `INT` instead.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

Examples:

```
CREATE TABLE t1 (x SMALLINT);
SELECT CAST(1000 AS SMALLINT);
```

Parquet considerations:

Physically, Parquet files represent `TINYINT` and `SMALLINT` values as 32-bit integers. Although Impala rejects attempts to insert out-of-range values into such columns, if you create a new table with the `CREATE TABLE ... LIKE PARQUET` syntax, any `TINYINT` or `SMALLINT` columns in the original table turn into `INT` columns in the new table.

Partitioning: Prefer to use this type for a partition key column. Impala can process the numeric type more efficiently than a `STRING` representation of the value.

HBase considerations: This data type is fully compatible with HBase tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 2-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 174, [TINYINT Data Type](#) on page 139, [SMALLINT Data Type](#) on page 124, [INT Data Type](#) on page 118, [BIGINT Data Type](#) on page 106, [DECIMAL Data Type \(Impala 3.0 or higher only\)](#) on page 111, [Impala Mathematical Functions](#) on page 434

STRING Data Type

A data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` and `ALTER TABLE` statements:

```
column_name STRING
```

Length:

If you need to manipulate string values with precise or maximum lengths, in Impala 2.0 and higher you can declare columns as `VARCHAR(max_length)` or `CHAR(length)`, but for best performance use `STRING` where practical.

Take the following considerations for `STRING` lengths:

- The hard limit on the size of a `STRING` and the total size of a row is 2 GB.
If a query tries to process or create a string larger than this limit, it will return an error to the user.
- The limit is 1 GB on `STRING` when writing to Parquet files.
- Queries operating on strings with 32 KB or less will work reliably and will not hit significant performance or memory problems (unless you have very complex queries, very many columns, etc.)
- Performance and memory consumption may degrade with strings larger than 32 KB.
- The row size, i.e. the total size of all string and other columns, is subject to lower limits at various points in query execution that support spill-to-disk. A few examples for lower row size limits are:
 - Rows coming from the right side of any hash join
 - Rows coming from either side of a hash join that spills to disk
 - Rows being sorted by the `SORT` operator without a limit
 - Rows in a grouping aggregation

In Impala 2.9 and lower, the default limit of the row size in the above cases is 8 MB.

In Impala 2.10 and higher, the max row size is configurable on a per-query basis with the `MAX_ROW_SIZE` query option. Rows up to `MAX_ROW_SIZE` (which defaults to 512 KB) can always be processed in the above cases.

Rows larger than `MAX_ROW_SIZE` are processed on a best-effort basis. See [MAX_ROW_SIZE](#) for more details.

Character sets:

For full support in all Impala subsystems, restrict string values to the ASCII character set. Although some UTF-8 character data can be stored in Impala and retrieved through queries, UTF-8 strings containing non-ASCII characters are not guaranteed to work properly in combination with many SQL aspects, including but not limited to:

- `CHAR/VARCHAR` truncating/padding.
- Comparison operators.
- The `ORDER BY` clause.
- Values in partition key columns.

For any national language aspects such as collation order or interpreting extended ASCII variants such as ISO-8859-1 or ISO-8859-2 encodings, Impala does not include such metadata with the table definition. If you need to sort, manipulate, or display data depending on those national language characteristics of string data, use logic on the application side.

If you just need Hive-compatible string function behaviors on UTF-8 encoded strings, turn on the query option `UTF8_MODE`. See more in [UTF-8 Support](#) on page 613.

Conversions:

- Impala does not automatically convert `STRING` to any numeric type. Impala does automatically convert `STRING` to `TIMESTAMP` if the value matches one of the accepted `TIMESTAMP` formats; see [TIMESTAMP Data Type](#) on page 133 for details.
- You can use `CAST ()` to convert `STRING` values to `TINYINT`, `SMALLINT`, `INT`, `BIGINT`, `FLOAT`, `DOUBLE`, or `TIMESTAMP`.
- You cannot directly cast a `STRING` value to `BOOLEAN`. You can use a `CASE` expression to evaluate string values such as `'T'`, `'true'`, and so on and return Boolean `true` and `false` values as appropriate.
- You can cast a `BOOLEAN` value to `STRING`, returning `'1'` for true values and `'0'` for false values.

Partitioning:

Although it might be convenient to use `STRING` columns for partition keys, even when those columns contain numbers, for performance and scalability it is much better to use numeric columns as partition keys whenever practical. Although the underlying HDFS directory name might be the same in either case, the in-memory storage for the partition key columns is more compact, and computations are faster, if partition key columns such as `YEAR`, `MONTH`, `DAY` and so on are declared as `INT`, `SMALLINT`, and so on.

Zero-length strings: For purposes of clauses such as `DISTINCT` and `GROUP BY`, Impala considers zero-length strings (`" "`), `NULL`, and space to all be different values.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Avro considerations:

The Avro specification allows string values up to 2^{64} bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths. In Impala 2.5 and higher, Impala truncates `CHAR` and `VARCHAR` values in Avro tables to $(2^{31})-1$ bytes. If a query encounters a `STRING` value longer than $(2^{31})-1$ bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Column statistics considerations: Because the values of this type have variable size, none of the column statistics fields are filled in until you run the `COMPUTE STATS` statement.

Examples:

The following examples demonstrate double-quoted and single-quoted string literals, and required escaping for quotation marks within string literals:

```
SELECT 'I am a single-quoted string';
SELECT "I am a double-quoted string";
SELECT 'I\'m a single-quoted string with an apostrophe';
SELECT "I\'m a double-quoted string with an apostrophe";
SELECT 'I am a "short" single-quoted string containing quotes';
SELECT "I am a \"short\" double-quoted string containing quotes";
```

The following examples demonstrate calls to string manipulation functions to concatenate strings, convert numbers to strings, or pull out substrings:

```
SELECT CONCAT("Once upon a time, there were ", CAST(3 AS STRING), ' little pigs.');
```

```
SELECT SUBSTR("hello world",7,5);
```

The following examples show how to perform operations on `STRING` columns within a table:

```
CREATE TABLE t1 (s1 STRING, s2 STRING);
INSERT INTO t1 VALUES ("hello", 'world'), (CAST(7 AS STRING), "wonders");
SELECT s1, s2, length(s1) FROM t1 WHERE s2 LIKE 'w%';
```

Related information:

[String Literals](#) on page 175, [CHAR Data Type \(Impala 2.0 or higher only\)](#) on page 108, [VARCHAR Data Type \(Impala 2.0 or higher only\)](#) on page 140, [Impala String Functions](#) on page 509, [Impala Date and Time Functions](#) on page 478

STRUCT Complex Type (Impala 2.3 or higher only)

A complex data type, representing multiple fields of a single item. Frequently used as the element type of an ARRAY or the VALUE part of a MAP.

Syntax:

```
column_name STRUCT < name : type [COMMENT 'comment_string'], ... >
type ::= primitive_type | complex_type
```

The names and number of fields within the STRUCT are fixed. Each field can be a different type. A field within a STRUCT can also be another STRUCT, or an ARRAY or a MAP, allowing you to create nested data structures with a maximum nesting depth of 100.

A STRUCT can be the top-level type for a column, or can itself be an item within an ARRAY or the value part of the key-value pair in a MAP.

When a STRUCT is used as an ARRAY element or a MAP value, you use a join clause to bring the ARRAY or MAP elements into the result set, and then refer to `array_name.ITEM.field` or `map_name.VALUE.field`. In the case of a STRUCT directly inside an ARRAY or MAP, you can omit the `.ITEM` and `.VALUE` pseudocolumns and refer directly to `array_name.field` or `map_name.field`.

Usage notes:

Because complex types are often used in combination, for example an ARRAY of STRUCT elements, if you are unfamiliar with the Impala complex types, start with [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for background information and usage examples.

A STRUCT is similar conceptually to a table row: it contains a fixed number of named fields, each with a predefined type. To combine two related tables, while using complex types to minimize repetition, the typical way to represent that data is as an ARRAY of STRUCT elements.

Because a STRUCT has a fixed number of named fields, it typically does not make sense to have a STRUCT as the type of a table column. In such a case, you could just make each field of the STRUCT into a separate column of the table. The STRUCT type is most useful as an item of an ARRAY or the value part of the key-value pair in a MAP. A nested type column with a STRUCT at the lowest level lets you associate a variable number of row-like objects with each row of the table.

The STRUCT type is straightforward to reference within a query. You do not need to include the STRUCT column in a join clause or give it a table alias, as is required for the ARRAY and MAP types. You refer to the individual fields using dot notation, such as `struct_column_name.field_name`, without any pseudocolumn such as `ITEM` or `VALUE`.

You can pass a multi-part qualified name to `DESCRIBE` to specify an ARRAY, STRUCT, or MAP column and visualize its structure as if it were a table. For example, if table `T1` contains an ARRAY column `A1`, you could issue the statement `DESCRIBE t1.a1`. If table `T1` contained a STRUCT column `S1`, and a field `F1` within the STRUCT was a MAP, you could issue the statement `DESCRIBE t1.s1.f1`. An ARRAY is shown as a two-column table, with `ITEM` and `POS` columns. A STRUCT is shown as a table with each field representing a column in the table. A MAP is shown as a two-column table, with `KEY` and `VALUE` columns.

Internal details:

Within the Parquet data file, the values for each STRUCT field are stored adjacent to each other, so that they can be encoded and compressed using all the Parquet techniques for storing sets of similar or repeated values. The adjacency applies even when the STRUCT values are part of an ARRAY or MAP. During a query, Impala avoids unnecessary I/O by reading only the portions of the Parquet data file containing the requested STRUCT fields.

Added in: Impala 2.3.0

Restrictions:

- Columns with this data type can only be used in tables or partitions with the Parquet or ORC file format.
- Columns with this data type cannot be used as partition key columns in a partitioned table.
- The `COMPUTE STATS` statement does not produce any statistics for columns of this data type.
- The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.
- See [Limitations and Restrictions for Complex Types](#) on page 146 for a full list of limitations and associated guidelines about complex type columns.

Kudu considerations:

Currently, the data types `CHAR`, `ARRAY`, `MAP`, and `STRUCT` cannot be used with Kudu tables.

Examples:

Note: Many of the complex type examples refer to tables such as `CUSTOMER` and `REGION` adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 165 for the table definitions.

The following example shows a table with various kinds of `STRUCT` columns, both at the top level and nested within other complex types. Practice the `CREATE TABLE` and query notation for complex type columns using empty tables, until you can visualize a complex data structure and construct corresponding SQL statements reliably.

```
CREATE TABLE struct_demo
(
  id BIGINT,
  name STRING,

  -- A STRUCT as a top-level column. Demonstrates how the table ID column
  -- and the ID field within the STRUCT can coexist without a name conflict.
  employee_info STRUCT < employer: STRING, id: BIGINT, address: STRING >,

  -- A STRUCT as the element type of an ARRAY.
  places_lived ARRAY < STRUCT <street: STRING, city: STRING, country: STRING
  >>,

  -- A STRUCT as the value portion of the key-value pairs in a MAP.
  memorable_moments MAP < STRING, STRUCT < year: INT, place: STRING,
  details: STRING >>,

  -- A STRUCT where one of the fields is another STRUCT.
  current_address STRUCT < street_address: STRUCT <street_number: INT,
  street_name: STRING, street_type: STRING>, country: STRING, postal_code:
  STRING >
)
STORED AS PARQUET;
```

The following example shows how to examine the structure of a table containing one or more `STRUCT` columns by using the `DESCRIBE` statement. You can visualize each `STRUCT` as its own table, with columns named the same as each field of the `STRUCT`. If the `STRUCT` is nested inside another complex type, such as `ARRAY`, you can extend the qualified name passed to `DESCRIBE` until the output shows just the `STRUCT` fields.

```
DESCRIBE struct_demo;
+-----+-----+
| name          | type          |
+-----+-----+
| id            | bigint        |
| name          | string        |
| employee_info | struct<
```


	employer:string, id:bigint, address:string >
places_lived	array<struct< street:string, city:string, country:string >>
memorable_moments	map<string,struct< year:int, place:string, details:string >>
current_address	struct< street_address:struct< street_number:int, street_name:string, street_type:string >, country:string, postal_code:string >

The top-level column `EMPLOYEE_INFO` is a `STRUCT`. Describing `table_name.struct_name` displays the fields of the `STRUCT` as if they were columns of a table:

```
DESCRIBE struct_demo.employee_info;
```

name	type
employer	string
id	bigint
address	string

Because `PLACES_LIVED` is a `STRUCT` inside an `ARRAY`, the initial `DESCRIBE` shows the structure of the `ARRAY`:

```
DESCRIBE struct_demo.places_lived;
```

name	type
item	struct< street:string, city:string, country:string >
pos	bigint

Ask for the details of the `ITEM` field of the `ARRAY` to see just the layout of the `STRUCT`:

```
DESCRIBE struct_demo.places_lived.item;
```

name	type
street	string
city	string

country	string

Likewise, MEMORABLE_MOMENTS has a STRUCT inside a MAP, which requires an extra level of qualified name to see just the STRUCT part:

```
DESCRIBE struct_demo.memorable_moments;
```

name	type
key	string
value	struct< year:int, place:string, details:string >

For a MAP, ask to see the VALUE field to see the corresponding STRUCT fields in a table-like structure:

```
DESCRIBE struct_demo.memorable_moments.value;
```

name	type
year	int
place	string
details	string

For a STRUCT inside a STRUCT, we can see the fields of the outer STRUCT:

```
DESCRIBE struct_demo.current_address;
```

name	type
street_address	struct< street_number:int, street_name:string, street_type:string >
country	string
postal_code	string

Then we can use a further qualified name to see just the fields of the inner STRUCT:

```
DESCRIBE struct_demo.current_address.street_address;
```

name	type
street_number	int
street_name	string
street_type	string

The following example shows how to examine the structure of a table containing one or more STRUCT columns by using the DESCRIBE statement. You can visualize each STRUCT as its own table, with columns named the same as each field of the STRUCT. If the STRUCT is nested inside another complex type, such as ARRAY, you can extend the qualified name passed to DESCRIBE until the output shows just the STRUCT fields.

```
DESCRIBE struct_demo;
```

name	type	comment
id	bigint	
name	string	
employee_info	struct< employer:string, id:bigint, address:string >	
places_lived	array<struct< street:string, city:string, country:string >>	
memorable_moments	map<string,struct< year:int, place:string, details:string >>	
current_address	struct< street_address:struct< street_number:int, street_name:string, street_type:string >, country:string, postal_code:string >	

```
SELECT id, employee_info.id FROM struct_demo;
```

```
SELECT id, employee_info.id AS employee_id FROM struct_demo;
```

```
SELECT id, employee_info.id AS employee_id, employee_info.employer  
FROM struct_demo;
```

```
SELECT id, name, street, city, country  
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, places_lived.pos, places_lived.street, places_lived.city,  
places_lived.country  
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, pl.pos, pl.street, pl.city, pl.country  
FROM struct_demo, struct_demo.places_lived AS pl;
```

```
SELECT id, name, places_lived.pos, places_lived.street, places_lived.city,  
places_lived.country  
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, pos, street, city, country  
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, memorable_moments.key,  
memorable_moments.value.year,
```

```

    memorable_moments.value.place,
    memorable_moments.value.details
FROM struct_demo, struct_demo.memorable_moments
WHERE memorable_moments.key IN ('Birthday','Anniversary','Graduation');

SELECT id, name, mm.key, mm.value.year, mm.value.place, mm.value.details
  FROM struct_demo, struct_demo.memorable_moments AS mm
WHERE mm.key IN ('Birthday','Anniversary','Graduation');

SELECT id, name, memorable_moments.key, memorable_moments.value.year,
       memorable_moments.value.place, memorable_moments.value.details
  FROM struct_demo, struct_demo.memorable_moments
WHERE key IN ('Birthday','Anniversary','Graduation');

SELECT id, name, key, value.year, value.place, value.details
  FROM struct_demo, struct_demo.memorable_moments
WHERE key IN ('Birthday','Anniversary','Graduation');

SELECT id, name, key, year, place, details
  FROM struct_demo, struct_demo.memorable_moments
WHERE key IN ('Birthday','Anniversary','Graduation');

SELECT id, name,
       current_address.street_address.street_number,
       current_address.street_address.street_name,
       current_address.street_address.street_type,
       current_address.country,
       current_address.postal_code
  FROM struct_demo;

```

For example, this table uses a struct that encodes several data values for each phone number associated with a person. Each person can have a variable-length array of associated phone numbers, and queries can refer to the category field to locate specific home, work, mobile, and so on kinds of phone numbers.

```

CREATE TABLE contact_info_many_structs
(
  id BIGINT, name STRING,
  phone_numbers ARRAY < STRUCT <category:STRING, country_code:STRING,
  area_code:SMALLINT, full_number:STRING, mobile:BOOLEAN, carrier:STRING > >
) STORED AS PARQUET;

```

Because structs are naturally suited to composite values where the fields have different data types, you might use them to decompose things such as addresses:

```

CREATE TABLE contact_info_detailed_address
(
  id BIGINT, name STRING,
  address STRUCT < house_number:INT, street:STRING, street_type:STRING,
  apartment:STRING, city:STRING, region:STRING, country:STRING >
);

```

In a big data context, splitting out data fields such as the number part of the address and the street name could let you do analysis on each field independently. For example, which streets have the largest number range of addresses, what are the statistical properties of the street names, which areas have a higher proportion of “Roads”, “Courts” or “Boulevards”, and so on.

Related information:

[Complex Types \(Impala 2.3 or higher only\)](#) on page 142, [ARRAY Complex Type \(Impala 2.3 or higher only\)](#) on page 102, [MAP Complex Type \(Impala 2.3 or higher only\)](#) on page 119

TIMESTAMP Data Type

In Impala, the `TIMESTAMP` data type holds a value of date and time. It can be decomposed into year, month, day, hour, minute and seconds fields, but with no time zone information available, it does not correspond to any specific point in time.

Internally, the resolution of the time portion of a `TIMESTAMP` value is in nanoseconds.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name TIMESTAMP

timestamp [+ | -] INTERVAL interval
DATE_ADD (timestamp, INTERVAL interval time_unit)
```

Range: 1400-01-01 to 9999-12-31

Out of range `TIMESTAMP` values are converted to `NULL`.

The range of Impala `TIMESTAMP` is different from the Hive `TIMESTAMP` type. Refer to [Hive documentation](#) for detail.

INTERVAL expressions:

You can perform date arithmetic by adding or subtracting a specified number of time units, using the `INTERVAL` keyword and the `+` operator, the `-` operator, `date_add()` or `date_sub()`.

The following units are supported for `time_unit` in the `INTERVAL` clause:

- `YEAR[S]`
- `MONTH[S]`
- `WEEK[S]`
- `DAY[S]`
- `HOURL[S]`
- `MINUTE[S]`
- `SECOND[S]`
- `MILLISECOND[S]`
- `MICROSECOND[S]`
- `NANOSECOND[S]`

You can only specify one time unit in each interval expression, for example `INTERVAL 3 DAYS` or `INTERVAL 25 HOURS`, but you can produce any granularity by adding together successive `INTERVAL` values, such as `timestamp_value + INTERVAL 3 WEEKS - INTERVAL 1 DAY + INTERVAL 10 MICROSECONDS`.

Internal details: Represented in memory as a 16-byte value.

Time zones:

By default, Impala stores and interprets `TIMESTAMP` values in UTC time zone when writing to data files, reading from data files, or converting to and from system time values through functions.

When you set the `##use_local_tz_for_unix_timestamp_conversions` startup flag to `TRUE`, Impala treats the `TIMESTAMP` values specified in the local time zone. The local time zone is determined in the following order with the `TIMEZONE` query option takes the highest precedence:

1. The `TIMEZONE` query option
2. `$TZ` environment variable
3. System time zone where the impalad coordinator runs

The `##use_local_tz_for_unix_timestamp_conversions` setting can be used to fix discrepancy in INTERVAL operations. For example, a `TIMESTAMP + INTERVAL n-hours` can be affected by Daylight Saving Time, which Impala does not consider by default as these operations are applied as if the timestamp was in UTC. You can use the `--use_local_tz_for_unix_timestamp_conversions` setting to fix the issue.

See [Customizing Time Zones](#) on page 137 for configuring to use custom time zone database and aliases.

See [Impala Date and Time Functions](#) for the list of functions affected by the `--use_local_tz_for_unix_timestamp_conversions` setting.

Time zone handling between Impala and Hive:

Interoperability between Hive and Impala is different depending on the file format.

- *Text*

For text tables, `TIMESTAMP` values can be written and read interchangeably by Impala and Hive as Hive reads and writes `TIMESTAMP` values without converting with respect to time zones.

- *Parquet*

Note: This section only applies to `INT96 TIMESTAMP`. See [Data Type Considerations for Parquet Tables](#) on page 718 for information about Parquet data types.

When Hive writes to Parquet data files, the `TIMESTAMP` values are normalized to UTC from the local time zone of the host where the data was written. On the other hand, Impala does not make any time zone adjustment when it writes or reads `INT96 TIMESTAMP` values to Parquet files. This difference in time zone handling can cause potentially inconsistent results when Impala processes `TIMESTAMP` values in the Parquet files written by Hive.

To avoid incompatibility problems or having to code workarounds, you can specify one or both of these Impala startup flags:

- `#use_local_tz_for_unix_timestamp_conversions=true`
- `#convert_legacy_hive_parquet_utc_timestamps=true`

When the `##convert_legacy_hive_parquet_utc_timestamps` setting is enabled, Impala recognizes the Parquet data files written by Hive, and applies the same UTC-to-local-timezone conversion logic during the query as Hive does.

In Impala 3.0 and lower, the `##convert_legacy_hive_parquet_utc_timestamps` setting had a severe impact on multi-threaded performance. The new time zone implementation in Impala 3.1 eliminated most of the performance overhead and made Impala scale well to multiple threads. The `##convert_legacy_hive_parquet_utc_timestamps` setting is turned off by default for a performance reason. To avoid unexpected incompatibility problems, you should turn on the option when processing `TIMESTAMP` columns in Parquet files written by Hive.

Hive currently cannot write `INT64 TIMESTAMP` values.

In Impala 3.2 and higher, `INT64 TIMESTAMP` values annotated with the `TIMESTAMP_MILLIS` or `TIMESTAMP_MICROS OriginalType` are assumed to be always UTC normalized, so the UTC to local conversion will be always done. `INT64 TIMESTAMP` annotated with the `TIMESTAMP LogicalType` specifies whether UTC to local conversion is necessary depending on the Parquet metadata.

Conversions:

Impala automatically converts `STRING` literals of the correct format into `TIMESTAMP` values. Timestamp values are accepted in the format `'YYYY#MM#dd HH:mm:ss.SSSSSS'`, and can consist of just the date, or just the time, with or without the fractional second portion. For example, you can specify `TIMESTAMP` values such as `'1966#07#30'`, `'08:30:00'`, or `'1985#09#25 17:45:30.005'`.

Leading zeroes are not required in the numbers representing the date component, such as month and date, or the time component, such as hour, minute, and second. For example, Impala accepts both `'2018#1#1 01:02:03'` and `'2018#01#01 1:2:3'` as valid.

In `STRING` to `TIMESTAMP` conversions, leading and trailing white spaces, such as a space, a tab, a newline, or a carriage return, are ignored. For example, Impala treats the following as equivalent: `'1999#12#01 01:02:03 '`, `'1999#12#01 01:02:03'`, `'1999#12#01 01:02:03\r\n'`.

When you convert or cast a `STRING` literal to `TIMESTAMP`, you can use the following separators between the date part and the time part:

- One or more space characters

Example: `CAST('2001-01-09 01:05:01' AS TIMESTAMP)`

- The character “T”

Example: `CAST('2001-01-09T01:05:01' AS TIMESTAMP)`

Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `##use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

In Impala 1.3 and higher, the `FROM_UNIXTIME()` and `UNIX_TIMESTAMP()` functions allow a wider range of format strings, with more flexibility in element order, repetition of letter placeholders, and separator characters. In Impala 2.3 and higher, the `UNIX_TIMESTAMP()` function also allows a numeric timezone offset to be specified as part of the input string. See [Impala Date and Time Functions](#) on page 478 for details.

In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the “[Year 2038 problem](#)” or “[Y2K38 problem](#)”). This change affects the `FROM_UNIXTIME()` and `UNIX_TIMESTAMP()` functions. You might need to change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST()` calls to SQL statements that call these functions.

Partitioning:

Although you cannot use a `TIMESTAMP` column as a partition key, you can extract the individual years, months, days, hours, and so on and partition based on those columns. Because the partition key column values are represented in HDFS directory names, rather than as fields in the data files themselves, you can also keep the original `TIMESTAMP` values if desired, without duplicating data or wasting storage space. See [Partition Key Columns](#) on page 691 for more details on partitioning with date and time values.

```
[localhost:21000] > create table timeline (event string) partitioned by
(happened timestamp);
ERROR: AnalysisException: Type 'TIMESTAMP' is not supported as partition-
column type in column: happened
```

NULL considerations: Casting any unrecognized `STRING` value to this type produces a `NULL` value.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet consideration: `INT96` encoded Parquet timestamps are supported in Impala. `INT64` timestamps are supported in Impala 3.2 and higher.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Kudu considerations:

In Impala 2.9 and higher, you can include `TIMESTAMP` columns in Kudu tables, instead of representing the date and time as a `BIGINT` value. The behavior of `TIMESTAMP` for Kudu tables has some special considerations:

- Any nanoseconds in the original 96-bit value produced by Impala are not stored, because Kudu represents date/time columns using 64-bit values. The nanosecond portion of the value is rounded, not truncated. Therefore, a `TIMESTAMP` value that you store in a Kudu table might not be bit-for-bit identical to the value returned by a query.
- The conversion between the Impala 96-bit representation and the Kudu 64-bit representation introduces some performance overhead when reading or writing `TIMESTAMP` columns. You can minimize the overhead during writes by performing inserts through the Kudu API. Because the overhead during reads applies to each query, you might continue to use a `BIGINT` column to represent date/time values in performance-critical applications.
- The Impala `TIMESTAMP` type has a narrower range for years than the underlying Kudu data type. Impala can represent years 1400-9999. If year values outside this range are written to a Kudu table by a non-Impala client, Impala returns `NULL` by default when reading those `TIMESTAMP` values during a query. Or, if the `ABORT_ON_ERROR` query option is enabled, the query fails when it encounters a value with an out-of-range year.

Restrictions:

If you cast a `STRING` with an unrecognized format to a `TIMESTAMP`, the result is `NULL` rather than an error. Make sure to test your data pipeline to be sure any textual date and time values are in a format that Impala `TIMESTAMP` can recognize.

Currently, Avro tables cannot contain `TIMESTAMP` columns. If you need to store date and time values in Avro tables, as a workaround you can use a `STRING` representation of the values, convert the values to `BIGINT` with the `UNIX_TIMESTAMP()` function, or create separate numeric columns for individual date and time fields using the `EXTRACT()` function.

Examples:

The following examples demonstrate using `TIMESTAMP` values with built-in functions:

```
select cast('1966-07-30' as timestamp);
select cast('1985-09-25 17:45:30.005' as timestamp);
select cast('08:30:00' as timestamp);
select hour('1970-01-01 15:30:00');           -- Succeeds, returns 15.
select hour('1970-01-01 15:30');             -- Returns NULL because seconds
  field required.
select hour('1970-01-01 27:30:00');           -- Returns NULL because hour
  value out of range.
select dayofweek('2004-06-13');              -- Returns 1, representing
  Sunday.
select dayname('2004-06-13');                -- Returns 'Sunday'.
select date_add('2004-06-13', 365);           -- Returns 2005-06-13 with zeros
  for hh:mm:ss fields.
select day('2004-06-13');                    -- Returns 13.
select datediff('1989-12-31','1984-09-01');  -- How many days between these 2
  dates?
select now();                                -- Returns current date and time
  in local timezone.
```

The following examples demonstrate using `TIMESTAMP` values with HDFS-backed tables:

```
create table dates_and_times (t timestamp);
insert into dates_and_times values
  ('1966-07-30'), ('1985-09-25 17:45:30.005'), ('08:30:00'), (now());
```

The following examples demonstrate using `TIMESTAMP` values with Kudu tables:

```
create table timestamp_t (x int primary key, s string, t timestamp, b
  bigint)
  partition by hash (x) partitions 16
  stored as kudu;

-- The default value of now() has microsecond precision, so the final 3
  digits
```



```
-- representing nanoseconds are all zero.
insert into timestamp_t values (1, cast(now() as string), now(),
    unix_timestamp(now()));

-- Values with 1-499 nanoseconds are rounded down in the Kudu TIMESTAMP
column.
insert into timestamp_t values (2, cast(now() + interval 100 nanoseconds as
    string), now() + interval 100 nanoseconds, unix_timestamp(now() + interval
    100 nanoseconds));
insert into timestamp_t values (3, cast(now() + interval 499 nanoseconds as
    string), now() + interval 499 nanoseconds, unix_timestamp(now() + interval
    499 nanoseconds));

-- Values with 500-999 nanoseconds are rounded up in the Kudu TIMESTAMP
column.
insert into timestamp_t values (4, cast(now() + interval 500 nanoseconds as
    string), now() + interval 500 nanoseconds, unix_timestamp(now() + interval
    500 nanoseconds));
insert into timestamp_t values (5, cast(now() + interval 501 nanoseconds as
    string), now() + interval 501 nanoseconds, unix_timestamp(now() + interval
    501 nanoseconds));

-- The string representation shows how underlying Impala TIMESTAMP can have
nanosecond precision.
-- The TIMESTAMP column shows how timestamps in a Kudu table are rounded to
microsecond precision.
-- The BIGINT column represents seconds past the epoch and so if not
affected much by nanoseconds.
select s, t, b from timestamp_t order by t;
+-----+-----+-----+
| s                | t                | b                |
+-----+-----+-----+
| 2017-05-31 15:30:05.107157000 | 2017-05-31 15:30:05.107157000 | 1496244605 |
| 2017-05-31 15:30:28.868151100 | 2017-05-31 15:30:28.868151000 | 1496244628 |
| 2017-05-31 15:34:33.674692499 | 2017-05-31 15:34:33.674692000 | 1496244873 |
| 2017-05-31 15:35:04.769166500 | 2017-05-31 15:35:04.769167000 | 1496244904 |
| 2017-05-31 15:35:33.033082501 | 2017-05-31 15:35:33.033083000 | 1496244933 |
+-----+-----+-----+
```

Added in: Available in all versions of Impala.

Related information:

- [Timestamp Literals](#) on page 176.
- To convert to or from different date formats, or perform date arithmetic, use the date and time functions described in [Impala Date and Time Functions](#) on page 478. In particular, the `from_unixtime()` function requires a case-sensitive format string such as "YYYY-MM-dd HH:mm:ss.SSSS", matching one of the allowed variations of a TIMESTAMP value (date plus time, only date, only time, optional fractional seconds).
- See [SQL Differences Between Impala and Hive](#) on page 606 for details about differences in TIMESTAMP handling between Impala and Hive.

Customizing Time Zones

Starting in Impala 3.1, you can customize the time zone definitions used in Impala.

- By default, Impala uses the OS's time zone database located in `/usr/share/zoneinfo`. This directory contains the IANA timezone database in a compiled binary format. The contents of the `zoneinfo` directory is controlled by the OS's package manager.
- Use the following start-up flags to customize the time zone definitions.
 - `##hdfs_zone_info_zip`: This flag allows Impala administrators to specify a custom timezone database. The flag should be set to a shared (not necessarily HDFS) path that points to a zip archive of a custom IANA timezone database. The timezone database is expected to be in a compiled binary format. If the startup flag is set, Impala will use the specified timezone database instead of the default `/usr/share/zoneinfo` database. The timezone db upgrade process is described in detail below.
 - `##hdfs_zone_alias_conf`: This flag allows Impala administrators to specify definitions for custom timezone aliases. The flag should be set to a shared (not necessarily HDFS) path that specifies a config file containing custom timezone alias definitions. This config file can be used as a workaround for users who want to keep using their legacy timezone names. Configuring custom aliases is described in detail below.

Upgrading custom IANA time zone database:

1. Download latest IANA time zone database distribution:

```
git clone https://github.com/eggert/tz
```

Alternatively, download a specific tzdb version from:

```
https://www.iana.org/time-zones/repository
```

2. Build timezone tools:

```
cd tz
make TOPDIR=tzdata install
```

3. Generate the compiled binary time zone database:

```
./zic -d ./tzdata/etc/zoneinfo africa antarctica asia australasia backward
backzone etcetera europe factory northamerica pacificnew southamerica
systemv
```

4. Create zip archive:

```
pushd ./tzdata/etc
zip -r zoneinfo.zip zoneinfo
popd
```

5. Copy the time zone database to HDFS:

```
hdfs dfs -mkdir -p /tzdb/latest
hdfs dfs -copyFromLocal ./tzdata/etc/zoneinfo.zip /tzdb/latest
```

6. Set the `##hdfs_zone_info_zip` startup flag to `/tzdb/latest/zoneinfo.zip` as an `impalad` safety valve.
7. Perform a full restart of Impala service.

Configuring custom time zone aliases:

1. Create a `tzalias.conf` config file that contains time zone alias definitions formatted as `ALIAS = DEFINITION`. For example:

```
#
# Define aliases for existing timezone names:
#
Universal Coordinated Time = UTC
Mideast/Riyadh89 = Asia/Riyadh
PDT = America/Los_Angeles
```

```
#
# Define aliases as UTC offsets in seconds:
#
GMT-01:00 = 3600
GMT+01:00 = -3600
```

2. Copy the config file to HDFS:

```
hdfs dfs -mkdir -p /tzdb
hdfs dfs -copyFromLocal tzalias.conf /tzdb
```

3. Set the `##hdfs_zone_alias_conf` startup flag to `/tzdb/tzalias.conf` as an `impalad` safety valve.
4. Perform a full restart of Impala service.

Added in: Impala 3.1

TINYINT Data Type

A 1-byte integer data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name TINYINT
```

Range: -128 .. 127. There is no `UNSIGNED` subtype.

Conversions: Impala automatically converts to a larger integer type (`SMALLINT`, `INT`, or `BIGINT`) or a floating-point type (`FLOAT` or `DOUBLE`) automatically. Use `CAST()` to convert to `STRING` or `TIMESTAMP`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `##use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Impala does not return column overflows as `NULL`, so that customers can distinguish between `NULL` data and overflow conditions similar to how they do so with traditional database systems. Impala returns the largest or smallest value in the range for the type. For example, valid values for a `tinyint` range from -128 to 127. In Impala, a `tinyint` with a value of -200 returns -128 rather than `NULL`. A `tinyint` with a value of 200 returns 127.

Usage notes:

For a convenient and automated way to check the bounds of the `TINYINT` type, call the functions `MIN_TINYINT()` and `MAX_TINYINT()`.

If an integer value is too large to be represented as a `TINYINT`, use a `SMALLINT` instead.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

Examples:

```
CREATE TABLE t1 (x TINYINT);
SELECT CAST(100 AS TINYINT);
```

Parquet considerations:

Physically, Parquet files represent `TINYINT` and `SMALLINT` values as 32-bit integers. Although Impala rejects attempts to insert out-of-range values into such columns, if you create a new table with the `CREATE TABLE ... LIKE PARQUET` syntax, any `TINYINT` or `SMALLINT` columns in the original table turn into `INT` columns in the new table.

HBase considerations: This data type is fully compatible with HBase tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 1-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 174, [TINYINT Data Type](#) on page 139, [SMALLINT Data Type](#) on page 124, [INT Data Type](#) on page 118, [BIGINT Data Type](#) on page 106, [DECIMAL Data Type \(Impala 3.0 or higher only\)](#) on page 111, [Impala Mathematical Functions](#) on page 434

VARCHAR Data Type (Impala 2.0 or higher only)

A variable-length character type, truncated during processing if necessary to fit within the specified length.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name VARCHAR(max_length)
```

The maximum length you can specify is 65,535.

Partitioning: This type can be used for partition key columns. Because of the efficiency advantage of numeric values over character-based values, if the partition key is a string representation of a number, prefer to use an integer type with sufficient range (`INT`, `BIGINT`, and so on) where practical.

HBase considerations: This data type cannot be used with HBase tables.

Parquet considerations:

- This type can be read from and written to Parquet files.
- There is no requirement for a particular level of Parquet.
- Parquet files generated by Impala and containing this type can be freely interchanged with other components such as Hive and MapReduce.
- Parquet data files can contain values that are longer than allowed by the `VARCHAR(n)` length limit. Impala ignores any extra trailing characters when it processes those values during a query.

Text table considerations:

Text data files can contain values that are longer than allowed by the `VARCHAR(n)` length limit. Any extra trailing characters are ignored when Impala processes those values during a query.

Avro considerations:

The Avro specification allows string values up to 2^{64} bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths. In Impala 2.5 and higher, Impala truncates `CHAR` and `VARCHAR` values in Avro tables to $(2^{31})-1$ bytes. If a query encounters a `STRING` value longer than $(2^{31})-1$ bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Schema evolution considerations:

You can use `ALTER TABLE ... CHANGE` to switch column data types to and from `VARCHAR`. You can convert from `STRING` to `VARCHAR(n)`, or from `VARCHAR(n)` to `STRING`, or from `CHAR(n)` to `VARCHAR(n)`, or from `VARCHAR(n)` to `CHAR(n)`. When switching back and forth between `VARCHAR` and `CHAR`, you can also change the length value. This schema evolution works the same for tables using any file format. If a table contains values longer than the maximum length defined for a `VARCHAR` column, Impala does not return an error. Any extra trailing characters are ignored when Impala processes those values during a query.

Compatibility:

This type is available in Impala 2.0 or higher.

Internal details: Represented in memory as a byte array with the minimum size needed to represent each value.

Added in: Impala 2.0.0

Column statistics considerations: Because the values of this type have variable size, none of the column statistics fields are filled in until you run the `COMPUTE STATS` statement.

Kudu considerations:

Currently, the data types `CHAR`, `ARRAY`, `MAP`, and `STRUCT` cannot be used with Kudu tables.

Restrictions:

All data in `CHAR` and `VARCHAR` columns must be in a character encoding that is compatible with UTF-8. If you have binary data from another database system (that is, a `BLOB` type), use a `STRING` column to hold it.

Examples:

The following examples show how long and short `VARCHAR` values are treated. Values longer than the maximum specified length are truncated by `CAST()`, or when queried from existing data files. Values shorter than the maximum specified length are represented as the actual length of the value, with no extra padding as seen with `CHAR` values.

```
create table varchar_1 (s varchar(1));
create table varchar_4 (s varchar(4));
create table varchar_20 (s varchar(20));

insert into varchar_1 values (cast('a' as varchar(1))), (cast('b' as
  varchar(1))), (cast('hello' as varchar(1))), (cast('world' as varchar(1)));
insert into varchar_4 values (cast('a' as varchar(4))), (cast('b' as
  varchar(4))), (cast('hello' as varchar(4))), (cast('world' as varchar(4)));
insert into varchar_20 values (cast('a' as varchar(20))), (cast('b'
  as varchar(20))), (cast('hello' as varchar(20))), (cast('world' as
  varchar(20)));

select * from varchar_1;
+----+
| s |
+----+
| a |
| b |
| h |
| w |
+----+
select * from varchar_4;
+-----+
| s |
+-----+
| a |
| b |
| hell |
| worl |
+-----+
[localhost:21000] > select * from varchar_20;
+-----+
| s |
+-----+
| a |
| b |
| hello |
| world |
+-----+
select concat(['',s,'']) as s from varchar_20;
+-----+
| s |
+-----+
| [a] |
```

```

| [b] |
| [hello] |
| [world] |
+-----+

```

The following example shows how identical VARCHAR values compare as equal, even if the columns are defined with different maximum lengths. Both tables contain 'a' and 'b' values. The longer 'hello' and 'world' values from the VARCHAR_20 table were truncated when inserted into the VARCHAR_1 table.

```

select s from varchar_1 join varchar_20 using (s);
+-----+
| s      |
+-----+
| a      |
| b      |
+-----+

```

The following examples show how VARCHAR values are freely interchangeable with STRING values in contexts such as comparison operators and built-in functions:

```

select length(cast('foo' as varchar(100))) as length;
+-----+
| length |
+-----+
| 3      |
+-----+
select cast('xyz' as varchar(5)) > cast('abc' as varchar(10)) as greater;
+-----+
| greater |
+-----+
| true    |
+-----+

```

UDF considerations: This type cannot be used for the argument or return type of a user-defined function (UDF) or user-defined aggregate function (UDA).

Related information:

[STRING Data Type](#) on page 125, [CHAR Data Type \(Impala 2.0 or higher only\)](#) on page 108, [String Literals](#) on page 175, [Impala String Functions](#) on page 509

Complex Types (Impala 2.3 or higher only)

Complex types (also referred to as *nested types*) let you represent multiple data values within a single row/column position. They differ from the familiar column types such as BIGINT and STRING, known as *scalar types* or *primitive types*, which represent a single data value within a given row/column position. Impala supports the complex types ARRAY, MAP, and STRUCT in Impala 2.3 and higher. The Hive UNION type is not currently supported.

Once you understand the basics of complex types, refer to the individual type topics when you need to refresh your memory about syntax and examples:

- [ARRAY Complex Type \(Impala 2.3 or higher only\)](#) on page 102
- [STRUCT Complex Type \(Impala 2.3 or higher only\)](#) on page 127
- [MAP Complex Type \(Impala 2.3 or higher only\)](#) on page 119

Benefits of Impala Complex Types

The reasons for using Impala complex types include the following:

- You already have data produced by Hive or other non-Impala component that uses the complex type column names. You might need to convert the underlying data to Parquet to use it with Impala.

- Your data model originates with a non-SQL programming language or a NoSQL data management system. For example, if you are representing Python data expressed as nested lists, dictionaries, and tuples, those data structures correspond closely to Impala ARRAY, MAP, and STRUCT types.
- Your analytic queries involving multiple tables could benefit from greater locality during join processing. By packing more related data items within each HDFS data block, complex types let join queries avoid the network overhead of the traditional Hadoop shuffle or broadcast join techniques.

The Impala complex type support produces result sets with all scalar values, and the scalar components of complex types can be used with all SQL clauses, such as GROUP BY, ORDER BY, all kinds of joins, subqueries, and inline views. The ability to process complex type data entirely in SQL reduces the need to write application-specific code in Java or other programming languages to deconstruct the underlying data structures.

Overview of Impala Complex Types

The ARRAY and MAP types are closely related: they represent collections with arbitrary numbers of elements, where each element is the same type. In contrast, STRUCT groups together a fixed number of items into a single element. The parts of a STRUCT element (the *fields*) can be of different types, and each field has a name.

The elements of an ARRAY or MAP, or the fields of a STRUCT, can also be other complex types. You can construct elaborate data structures with up to 100 levels of nesting. For example, you can make an ARRAY whose elements are STRUCTs. Within each STRUCT, you can have some fields that are ARRAY, MAP, or another kind of STRUCT. The Impala documentation uses the terms complex and nested types interchangeably; for simplicity, it primarily uses the term complex types, to encompass all the properties of these types.

When visualizing your data model in familiar SQL terms, you can think of each ARRAY or MAP as a miniature table, and each STRUCT as a row within such a table. By default, the table represented by an ARRAY has two columns, POS to represent ordering of elements, and ITEM representing the value of each element. Likewise, by default, the table represented by a MAP encodes key-value pairs, and therefore has two columns, KEY and VALUE.

The ITEM and VALUE names are only required for the very simplest kinds of ARRAY and MAP columns, ones that hold only scalar values. When the elements within the ARRAY or MAP are of type STRUCT rather than a scalar type, then the result set contains columns with names corresponding to the STRUCT fields rather than ITEM or VALUE.

You write most queries that process complex type columns using familiar join syntax, even though the data for both sides of the join resides in a single table. The join notation brings together the scalar values from a row with the values from the complex type columns for that same row. The final result set contains all scalar values, allowing you to do all the familiar filtering, aggregation, ordering, and so on for the complex data entirely in SQL or using business intelligence tools that issue SQL queries.

Behind the scenes, Impala ensures that the processing for each row is done efficiently on a single host, without the network traffic involved in broadcast or shuffle joins. The most common type of join query for tables with complex type columns is INNER JOIN, which returns results only in those cases where the complex type contains some elements. Therefore, most query examples in this section use either the INNER JOIN clause or the equivalent comma notation.

Note:

Although Impala can query complex types that are present in Parquet files, Impala currently cannot create new Parquet files containing complex types. Therefore, the discussion and examples presume that you are working with existing Parquet data produced through Hive, Spark, or some other source. See [Constructing Parquet/ORC Files with Complex Columns Using Hive](#) on page 167 for examples of constructing Parquet data files with complex type columns.

For learning purposes, you can create empty tables with complex type columns and practice query syntax, even if you do not have sample data with the required structure.

Design Considerations for Complex Types

When planning to use Impala complex types, and designing the Impala schema, first learn how this kind of schema differs from traditional table layouts from the relational database and data warehousing fields. Because you might have already encountered complex types in a Hadoop context while using Hive for ETL, also learn how to write high-performance analytic queries for complex type data using Impala SQL syntax.

How Complex Types Differ from Traditional Data Warehouse Schemas

Complex types let you associate arbitrary data structures with a particular row. If you are familiar with schema design for relational database management systems or data warehouses, a schema with complex types has the following differences:

- Logically, related values can now be grouped tightly together in the same table.

In traditional data warehousing, related values were typically arranged in one of two ways:

- Split across multiple normalized tables. Foreign key columns specified which rows from each table were associated with each other. This arrangement avoided duplicate data and therefore the data was compact, but join queries could be expensive because the related data had to be retrieved from separate locations. (In the case of distributed Hadoop queries, the joined tables might even be transmitted between different hosts in a cluster.)
- Flattened into a single denormalized table. Although this layout eliminated some potential performance issues by removing the need for join queries, the table typically became larger because values were repeated. The extra data volume could cause performance issues in other parts of the workflow, such as longer ETL cycles or more expensive full-table scans during queries.

Complex types represent a middle ground that addresses these performance and volume concerns. By physically locating related data within the same data files, complex types increase locality and reduce the expense of join queries. By associating an arbitrary amount of data with a single row, complex types avoid the need to repeat lengthy values such as strings. Because Impala knows which complex type values are associated with each row, you can save storage by avoiding artificial foreign key values that are only used for joins. The flexibility of the `STRUCT`, `ARRAY`, and `MAP` types lets you model familiar constructs such as fact and dimension tables from a data warehouse, and wide tables representing sparse matrixes.

Physical Storage for Complex Types in Parquet

Physically, the scalar and complex columns in each row are located adjacent to each other in the same Parquet data file, ensuring that they are processed on the same host rather than being broadcast across the network when cross-referenced within a query. This co-location simplifies the process of copying, converting, and backing all the columns up at once. Because of the column-oriented layout of Parquet files, you can still query only the scalar columns of a table without imposing the I/O penalty of reading the (possibly large) values of the composite columns.

Within each Parquet data file, the constituent parts of complex type columns are stored in column-oriented format:

- Each field of a `STRUCT` type is stored like a column, with all the scalar values adjacent to each other and encoded, compressed, and so on using the Parquet space-saving techniques.
- For an `ARRAY` containing scalar values, all those values (represented by the `ITEM` pseudocolumn) are stored adjacent to each other.
- For a `MAP`, the values of the `KEY` pseudocolumn are stored adjacent to each other. If the `VALUE` pseudocolumn is a scalar type, its values are also stored adjacent to each other.
- If an `ARRAY` element, `STRUCT` field, or `MAP VALUE` part is another complex type, the column-oriented storage applies to the next level down (or the next level after that, and so on for deeply nested types) where the final elements, fields, or values are of scalar types.

The numbers represented by the `POS` pseudocolumn of an `ARRAY` are not physically stored in the data files. They are synthesized at query time based on the order of the `ARRAY` elements associated with each row.

File Format Support for Impala Complex Types

Currently, Impala queries support complex type data in the Parquet and ORC file formats. See [Using the Parquet File Format with Impala Tables](#) on page 705 for details about the performance benefits and physical layout of Parquet file format.

Because Impala does not parse the data structures containing nested types for unsupported formats such as text, Avro, SequenceFile, or RCFile, you cannot use data files in these formats with Impala, even if the query does not refer to the nested type columns. Also, if a table using an unsupported format originally contained nested type columns, and then those columns were dropped from the table using `ALTER TABLE . . . DROP COLUMN`, any existing data files in the table still contain the nested type data and Impala queries on that table will generate errors.

The one exception to the preceding rule is `COUNT (*)` queries on RCFile tables that include complex types. Such queries are allowed in Impala 2.6 and higher.

You can perform DDL operations for tables involving complex types in most file formats other than Parquet or ORC. You cannot create tables in Impala with complex types using text files.

You can have a partitioned table with complex type columns that uses a format other than Parquet or ORC, and use `ALTER TABLE` to change the file format to Parquet/ORC for individual partitions. When you put Parquet/ORC files into those partitions, Impala can execute queries against that data as long as the query does not involve any of the non-Parquet and non-ORC partitions.

If you use the `parquet-tools` command to examine the structure of a Parquet data file that includes complex types, you see that both `ARRAY` and `MAP` are represented as a `Bag` in Parquet terminology, with all fields marked `Optional` because Impala allows any column to be nullable.

Impala supports either 2-level and 3-level encoding within each Parquet data file. When constructing Parquet data files outside Impala, use either encoding style but do not mix 2-level and 3-level encoding within the same data file.

Choosing Between Complex Types and Normalized Tables

Choosing between multiple normalized fact and dimension tables, or a single table containing complex types, is an important design decision.

- If you are coming from a traditional database or data warehousing background, you might be familiar with how to split up data between tables. Your business intelligence tools might already be optimized for dealing with this kind of multi-table scenario through join queries.
- If you are pulling data from Impala into an application written in a programming language that has data structures analogous to the complex types, such as Python or Java, complex types in Impala could simplify data interchange and improve understandability and reliability of your program logic.
- You might already be faced with existing infrastructure or receive high volumes of data that assume one layout or the other. For example, complex types are popular with web-oriented applications, for example to keep information about an online user all in one place for convenient lookup and analysis, or to deal with sparse or constantly evolving data fields.
- If some parts of the data change over time while related data remains constant, using multiple normalized tables lets you replace certain parts of the data without reloading the entire data set. Conversely, if you receive related data all bundled together, such as in JSON files, using complex types can save the overhead of splitting the related items across multiple tables.
- From a performance perspective:
 - In Parquet or ORC tables, Impala can skip columns that are not referenced in a query, avoiding the I/O penalty of reading the embedded data. When complex types are nested within a column, the data is physically divided at a very granular level; for example, a query referring to data nested multiple levels deep in a complex type column does not have to read all the data from that column, only the data for the relevant parts of the column type hierarchy.
 - Complex types avoid the possibility of expensive join queries when data from fact and dimension tables is processed in parallel across multiple hosts. All the information for a row containing complex types is typically to be in the same data block, and therefore does not need to be transmitted across the network when joining fields that are all part of the same row.
 - The tradeoff with complex types is that fewer rows fit in each data block. Whether it is better to have more data blocks with fewer rows, or fewer data blocks with many rows, depends on the distribution of your data and the characteristics of your query workload. If the complex columns are rarely referenced, using them might lower efficiency. If you are seeing low parallelism due to a small volume of data (relatively few data blocks) in each table partition, increasing the row size by including complex columns might produce more data blocks and thus spread the work more evenly across the cluster. See [Scalability Considerations for Impala](#) on page 657 for more on this advanced topic.

Differences Between Impala and Hive Complex Types

Impala can query Parquet and ORC tables containing ARRAY, STRUCT, and MAP columns produced by Hive. There are some differences to be aware of between the Impala SQL and HiveQL syntax for complex types, primarily for queries.

Impala supports a subset of the syntax that Hive supports for specifying ARRAY, STRUCT, and MAP types in the CREATE TABLE statements.

Because Impala STRUCT columns include user-specified field names, you use the NAMED_STRUCT() constructor in Hive rather than the STRUCT() constructor when you populate an Impala STRUCT column using a Hive INSERT statement.

The Hive UNION type is not currently supported in Impala.

While Impala usually aims for a high degree of compatibility with HiveQL query syntax, Impala syntax differs from Hive for queries involving complex types. The differences are intended to provide extra flexibility for queries involving these kinds of tables.

- Impala uses dot notation for referring to element names or elements within complex types, and join notation for cross-referencing scalar columns with the elements of complex types within the same row, rather than the LATERAL VIEW clause and EXPLODE() function of HiveQL.
- Using join notation lets you use all the kinds of join queries with complex type columns. For example, you can use a LEFT OUTER JOIN, LEFT ANTI JOIN, or LEFT SEMI JOIN query to evaluate different scenarios where the complex columns do or do not contain any elements.
- You can include references to collection types inside subqueries and inline views. For example, you can construct a FROM clause where one of the “tables” is a subquery against a complex type column, or use a subquery against a complex type column as the argument to an IN or EXISTS clause.
- The Impala pseudocolumn POS lets you retrieve the position of elements in an array along with the elements themselves, equivalent to the POSEXplode() function of HiveQL. You do not use index notation to retrieve a single array element in a query; the join query loops through the array elements and you use WHERE clauses to specify which elements to return.
- Join clauses involving complex type columns do not require an ON or USING clause. Impala implicitly applies the join key so that the correct array entries or map elements are associated with the correct row from the table.
- Impala does not currently support the UNION complex type.

Limitations and Restrictions for Complex Types

Complex type columns can only be used in tables or partitions with the Parquet or ORC file format.

Complex type columns cannot be used as partition key columns in a partitioned table.

When you use complex types with the ORDER BY, GROUP BY, HAVING, or WHERE clauses, you cannot refer to the column name by itself. Instead, you refer to the names of the scalar values within the complex type, such as the ITEM, POS, KEY, or VALUE pseudocolumns, or the field names from a STRUCT.

The maximum depth of nesting for complex types is 100 levels.

The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.

For ideal performance and scalability, use small or medium-sized collections, where all the complex columns contain at most a few hundred megabytes per row. Remember, all the columns of a row are stored in the same HDFS data block, whose size in Parquet files typically ranges from 256 MB to 1 GB.

Including complex type columns in a table introduces some overhead that might make queries that do not reference those columns somewhat slower than Impala queries against tables without any complex type columns. Expect at most a 2x slowdown compared to tables that do not have any complex type columns.

Currently, the COMPUTE STATS statement does not collect any statistics for columns containing complex types. Impala uses heuristics to construct execution plans involving complex type columns.

Currently, Impala built-in functions and user-defined functions cannot accept complex types as parameters or produce them as function return values. (When the complex type values are materialized in an Impala result set, the result set contains the scalar components of the values, such as the POS or ITEM for an ARRAY, the KEY or VALUE for a MAP, or the fields of a STRUCT; these scalar data items *can* be used with built-in functions and UDFs as usual.)

Impala currently cannot write new data files containing complex type columns. Therefore, although the SELECT statement works for queries involving complex type columns, you cannot use a statement form that writes data to complex type columns, such as CREATE TABLE AS SELECT or INSERT ... SELECT. To create data files containing complex type data, use the Hive INSERT statement, or another ETL mechanism such as MapReduce jobs, Spark jobs, Pig, and so on.

Currently, Impala can query complex type columns only from Parquet/ORC tables or Parquet/ORC partitions within partitioned tables. Although you can use complex types in tables with Avro, text, and other file formats as part of your ETL pipeline, for example as intermediate tables populated through Hive, doing analytics through Impala requires that the data eventually ends up in a Parquet/ORC table. The requirement for Parquet/ORC data files means that you can use complex types with Impala tables hosted on other kinds of file storage systems such as Isilon and Amazon S3, but you cannot use Impala to query complex types from HBase tables. See [File Format Support for Impala Complex Types](#) on page 144 for more details.

Using Complex Types from SQL

When using complex types through SQL in Impala, you learn the notation for < > delimiters for the complex type columns in CREATE TABLE statements, and how to construct join queries to “unpack” the scalar values nested inside the complex data structures. You might need to condense a traditional RDBMS or data warehouse schema into a smaller number of Parquet tables, and use Hive, Spark, Pig, or other mechanism outside Impala to populate the tables with data.

Complex Type Syntax for DDL Statements

The definition of *data_type*, as seen in the CREATE TABLE and ALTER TABLE statements, now includes complex types in addition to primitive types:

```
primitive_type
| array_type
| map_type
| struct_type
```

Unions are not currently supported.

Array, struct, and map column type declarations are specified in the CREATE TABLE statement. You can also add or change the type of complex columns through the ALTER TABLE statement.

Currently, Impala queries allow complex types only in tables that use the Parquet or ORC format. If an Impala query encounters complex types in a table or partition using other file formats, the query returns a runtime error.

You can use ALTER TABLE ... SET FILEFORMAT PARQUET to change the file format of an existing table containing complex types to Parquet, after which Impala can query it. Make sure to load Parquet files into the table after changing the file format, because the ALTER TABLE ... SET FILEFORMAT statement does not convert existing data to the new file format.

Partitioned tables can contain complex type columns. All the partition key columns must be scalar types.

Because use cases for Impala complex types require that you already have Parquet/ORC data files produced outside of Impala, you can use the Impala CREATE TABLE LIKE PARQUET syntax to produce a table with columns that match the structure of an existing Parquet file, including complex type columns for nested data structures. Remember to include the STORED AS PARQUET clause in this case, because even with CREATE TABLE LIKE PARQUET, the default file format of the resulting table is still text.

Because Impala currently does not support writing Parquet files with complex type columns, you cannot use the CREATE TABLE AS SELECT syntax to create a table with nested type columns.

Note:

Once you have a table set up with complex type columns, use the `DESCRIBE` and `SHOW CREATE TABLE` statements to see the correct notation with `<` and `>` delimiters and comma and colon separators within the complex type definitions. If you do not have existing data with the same layout as the table, you can query the empty table to practice with the notation for the `SELECT` statement. In the `SELECT` list, you use dot notation and pseudocolumns such as `ITEM`, `KEY`, and `VALUE` for referring to items within the complex type columns. In the `FROM` clause, you use join notation to construct table aliases for any referenced `ARRAY` and `MAP` columns.

For example, when defining a table that holds contact information, you might represent phone numbers differently depending on the expected layout and relationships of the data, and how well you can predict those properties in advance.

Here are different ways that you might represent phone numbers in a traditional relational schema, with equivalent representations using complex types.

The traditional, simplest way to represent phone numbers in a relational table is to store all contact info in a single table, with all columns having scalar types, and each potential phone number represented as a separate column. In this example, each person can only have these 3 types of phone numbers. If the person does not have a particular kind of phone number, the corresponding column is `NULL` for that row.

```
CREATE TABLE contacts_fixed_phones
(
  id BIGINT
  , name STRING
  , address STRING
  , home_phone STRING
  , work_phone STRING
  , mobile_phone STRING
) STORED AS PARQUET;
```

Figure 1: Traditional Relational Representation of Phone Numbers: Single Table

Using a complex type column to represent the phone numbers adds some extra flexibility. Now there could be an unlimited number of phone numbers. Because the array elements have an order but not symbolic names, you could decide in advance that `phone_number[0]` is the home number, `[1]` is the work number, `[2]` is the mobile number, and so on. (In subsequent examples, you will see how to create a more flexible naming scheme using other complex type variations, such as a `MAP` or an `ARRAY` where each element is a `STRUCT`.)

```
CREATE TABLE contacts_array_of_phones
(
  id BIGINT
  , name STRING
  , address STRING
  , phone_number ARRAY < STRING >
) STORED AS PARQUET;
```

Figure 2: An Array of Phone Numbers

Another way to represent an arbitrary set of phone numbers is with a `MAP` column. With a `MAP`, each element is associated with a key value that you specify, which could be a numeric, string, or other scalar type. This example uses a `STRING` key to give each phone number a name, such as `'home'` or `'mobile'`. A query could filter the data based on the key values, or display the key values in reports.

```
CREATE TABLE contacts_unlimited_phones
(
  id BIGINT, name STRING, address STRING, phone_number MAP < STRING, STRING >
) STORED AS PARQUET;
```

Figure 3: A Map of Phone Numbers

If you are an experienced database designer, you already know how to work around the limitations of the single-table schema from [Figure 1: Traditional Relational Representation of Phone Numbers: Single Table](#) on page 148. By normalizing the schema, with the phone numbers in their own table, you can associate an arbitrary set of phone numbers with each person, and associate additional details with each phone number, such as whether it is a home, work, or mobile phone.

The flexibility of this approach comes with some drawbacks. Reconstructing all the data for a particular person requires a join query, which might require performance tuning on Hadoop because the data from each table might be transmitted from a different host. Data management tasks such as backups and refreshing the data require dealing with multiple tables instead of a single table.

This example illustrates a traditional database schema to store contact info normalized across 2 tables. The fact table establishes the identity and basic information about person. A dimension table stores information only about phone numbers, using an ID value to associate each phone number with a person ID from the fact table. Each person can have 0, 1, or many phones; the categories are not restricted to a few predefined ones; and the phone table can contain as many columns as desired, to represent all sorts of details about each phone number.

```
CREATE TABLE fact_contacts (id BIGINT, name STRING, address STRING) STORED
AS PARQUET;
CREATE TABLE dim_phones
(
    contact_id BIGINT
    , category STRING
    , international_code STRING
    , area_code STRING
    , exchange STRING
    , extension STRING
    , mobile BOOLEAN
    , carrier STRING
    , current BOOLEAN
    , service_start_date TIMESTAMP
    , service_end_date TIMESTAMP
)
STORED AS PARQUET;
```

Figure 4: Traditional Relational Representation of Phone Numbers: Normalized Tables

To represent a schema equivalent to the one from [Figure 4: Traditional Relational Representation of Phone Numbers: Normalized Tables](#) on page 149 using complex types, this example uses an ARRAY where each array element is a STRUCT. As with the earlier complex type examples, each person can have an arbitrary set of associated phone numbers. Making each array element into a STRUCT lets us associate multiple data items with each phone number, and give a separate name and type to each data item. The STRUCT fields of the ARRAY elements reproduce the columns of the dimension table from the previous example.

You can do all the same kinds of queries with the complex type schema as with the normalized schema from the previous example. The advantages of the complex type design are in the areas of convenience and performance. Now your backup and ETL processes only deal with a single table. When a query uses a join to cross-reference the information about a person with their associated phone numbers, all the relevant data for each row resides in the same HDFS data block, meaning each row can be processed on a single host without requiring network transmission.

```
CREATE TABLE contacts_detailed_phones
(
    id BIGINT, name STRING, address STRING
    , phone ARRAY < STRUCT <
        category: STRING
```

```

    , international_code: STRING
    , area_code: STRING
    , exchange: STRING
    , extension: STRING
    , mobile: BOOLEAN
    , carrier: STRING
    , current: BOOLEAN
    , service_start_date: TIMESTAMP
    , service_end_date: TIMESTAMP
  >>
) STORED AS PARQUET;

```

Figure 5: Phone Numbers Represented as an Array of Structs

SQL Statements that Support Complex Types

The Impala SQL statements that support complex types are currently [CREATE TABLE](#), [ALTER TABLE](#), [DESCRIBE](#), [LOAD DATA](#), and [SELECT](#). That is, currently Impala can create or alter tables containing complex type columns, examine the structure of a table containing complex type columns, import existing data files containing complex type columns into a table, and query Parquet/ORC tables containing complex types.

Impala currently cannot write new data files containing complex type columns. Therefore, although the `SELECT` statement works for queries involving complex type columns, you cannot use a statement form that writes data to complex type columns, such as `CREATE TABLE AS SELECT` or `INSERT ... SELECT`. To create data files containing complex type data, use the Hive `INSERT` statement, or another ETL mechanism such as MapReduce jobs, Spark jobs, Pig, and so on.

DDL Statements and Complex Types

Column specifications for complex or nested types use `<` and `>` delimiters:

```

-- What goes inside the < > for an ARRAY is a single type, either a scalar
-- or another
-- complex type (ARRAY, STRUCT, or MAP).
CREATE TABLE array_t
(
  id BIGINT,
  a1 ARRAY <STRING>,
  a2 ARRAY <BIGINT>,
  a3 ARRAY <TIMESTAMP>,
  a4 ARRAY <STRUCT <f1: STRING, f2: INT, f3: BOOLEAN>>
)
STORED AS PARQUET;

-- What goes inside the < > for a MAP is two comma-separated types
-- specifying the types of the key-value pair:
-- a scalar type representing the key, and a scalar or complex type
-- representing the value.
CREATE TABLE map_t
(
  id BIGINT,
  m1 MAP <STRING, STRING>,
  m2 MAP <STRING, BIGINT>,
  m3 MAP <BIGINT, STRING>,
  m4 MAP <BIGINT, BIGINT>,
  m5 MAP <STRING, ARRAY <STRING>>
)
STORED AS PARQUET;

-- What goes inside the < > for a STRUCT is a comma-separated list of
-- fields, each field defined as

```

```
-- name:type. The type can be a scalar or a complex type. The field names
-- for each STRUCT do not clash
-- with the names of table columns or fields in other STRUCTs. A STRUCT is
-- most often used inside
-- an ARRAY or a MAP rather than as a top-level column.
CREATE TABLE struct_t
(
  id BIGINT,
  s1 STRUCT <f1: STRING, f2: BIGINT>,
  s2 ARRAY <STRUCT <f1: INT, f2: TIMESTAMP>>,
  s3 MAP <BIGINT, STRUCT <name: STRING, birthday: TIMESTAMP>>
)
STORED AS PARQUET;
```

Queries and Complex Types

The result set of an Impala query can contain both scalar and complex types. A query can either retrieve the complex values directly or “unpack” the elements and fields within a complex type using join queries, with the limitation that direct retrieval is currently not supported for complex types where collections (maps or arrays) are embedded within structs or structs are embedded within collections.

Here are some complex types that are supported in the select list:

- STRUCT<i: INT>
- STRUCT<s: STRUCT<i: INT>>
- ARRAY<INT>
- ARRAY<ARRAY<INT>>
- ARRAY<MAP<INT>>

And here are some that are not supported in the select list:

- STRUCT<a: ARRAY<INT>>
- ARRAY<STRUCT<i: INT>>
- MAP<INT, STRUCT<s: STRING>>

Because of backward compatibility with earlier versions of Impala that did not support complex types in the result set, queries using SELECT * skip complex types by default. To include complex types in SELECT * queries, set the EXPAND_COMPLEX_TYPES query option to true (see the [EXPAND_COMPLEX_TYPES Query Option](#) on page 395).

The following example shows how referring directly to a column with a complex type where a struct is embedded in a collection (an array) returns an error, while SELECT * on the same table succeeds, but only retrieves the scalar columns. Note that if EXPAND_COMPLEX_TYPES is true, the SELECT * query also fails with the same error.

Note: Many of the complex type examples refer to tables such as CUSTOMER and REGION adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 165 for the table definitions.

```
SELECT c_orders FROM customer LIMIT 1;
ERROR: AnalysisException: STRUCT type inside collection types is not
supported.

-- Original column has several scalar and one complex column.
DESCRIBE customer;
+-----+-----+
| name      | type                                     |
+-----+-----+
| c_custkey | bigint                                 |
| c_name    | string                                |
| ...      | ...                                   |
| c_orders  | array<struct<                           |
|           |   o_orderkey:bigint,                   |
```

```

|         | o_orderstatus:string, |
|         | o_totalprice:decimal(12,2), |
| ...     | >>                    |
+-----+-----+

-- When we SELECT * from that table, only the scalar columns come back in
-- the result set.
CREATE TABLE select_star_customer STORED AS PARQUET AS SELECT * FROM
customer;
+-----+
| summary |
+-----+
| Inserted 150000 row(s) |
+-----+

-- The c_orders column, being of complex type, was not included in the
-- SELECT * result set.
DESC select_star_customer;
+-----+-----+
| name      | type      |
+-----+-----+
| c_custkey | bigint    |
| c_name    | string    |
| c_address | string    |
| c_nationkey | smallint |
| c_phone   | string    |
| c_acctbal | decimal(12,2) |
| c_mktsegment | string  |
| c_comment | string    |
+-----+-----+

```

References to fields within STRUCT columns use dot notation. If the field name is unambiguous, you can omit qualifiers such as table name, column name, or even the ITEM or VALUE pseudocolumn names for STRUCT elements inside an ARRAY or a MAP.

```
SELECT id, address.city FROM customers WHERE address.zip = 94305;
```

References to elements within ARRAY columns use the ITEM pseudocolumn:

```
select r_name, r_nations.item.n_name from region, region.r_nations limit 7;
```

r_name	item.n_name
EUROPE	UNITED KINGDOM
EUROPE	RUSSIA
EUROPE	ROMANIA
EUROPE	GERMANY
EUROPE	FRANCE
ASIA	VIETNAM
ASIA	CHINA

References to fields within MAP columns use the KEY and VALUE pseudocolumns. In this example, once the query establishes the alias MAP_FIELD for a MAP column with a STRING key and an INT value, the query can refer to MAP_FIELD.KEY and MAP_FIELD.VALUE, which have zero, one, or many instances for each row from the containing table.

```
DESCRIBE table_0;
```

name	type
------	------


```

+-----+-----+
| field_0 | string |
| field_1 | map<string,int> |
| ... |
SELECT field_0, map_field.key, map_field.value
  FROM table_0, table_0.field_1 AS map_field
WHERE length(field_0) = 1
LIMIT 10;
+-----+-----+-----+
| field_0 | key      | value |
+-----+-----+-----+
| b       | gshsgkvd | NULL  |
| b       | twrtcxbj6 | 18    |
| b       | 2vp5     | 39    |
| b       | fh0s     | 13    |
| v       | 2        | 41    |
| v       | 8b58mz   | 20    |
| v       | hw       | 16    |
| v       | 65l388pyt | 29    |
| v       | 03k68g91z | 30    |
| v       | r2hlg5b  | NULL  |
+-----+-----+-----+

```

When complex types are nested inside each other, you use a combination of joins, pseudocolumn names, and dot notation to refer to specific fields at the appropriate level. This is the most frequent form of query syntax for complex columns, because the typical use case involves two levels of complex types, such as an ARRAY of STRUCT elements.

```

SELECT id, phone_numbers.area_code FROM contact_info_many_structs INNER JOIN
  contact_info_many_structs.phone_numbers phone_numbers LIMIT 3;

```

You can express relationships between ARRAY and MAP columns at different levels as joins. You include comparison operators between fields at the top level and within the nested type columns so that Impala can do the appropriate join operation.

Note: Many of the complex type examples refer to tables such as CUSTOMER and REGION adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 165 for the table definitions.

For example, the following queries work equivalently. They each return customer and order data for customers that have at least one order.

```

SELECT c.c_name, o.o_orderkey FROM customer c, c.c_orders o LIMIT 5;
+-----+-----+
| c_name          | o_orderkey |
+-----+-----+
| Customer#000072578 | 558821    |
| Customer#000072578 | 2079810   |
| Customer#000072578 | 5768068   |
| Customer#000072578 | 1805604   |
| Customer#000072578 | 3436389   |
+-----+-----+

SELECT c.c_name, o.o_orderkey FROM customer c INNER JOIN c.c_orders o LIMIT
  5;
+-----+-----+
| c_name          | o_orderkey |
+-----+-----+
| Customer#000072578 | 558821    |
| Customer#000072578 | 2079810   |
| Customer#000072578 | 5768068   |
+-----+-----+

```

Customer#000072578	1805604
Customer#000072578	3436389

The following query using an outer join returns customers that have orders, plus customers with no orders (no entries in the C_ORDERS array):

```
SELECT c.c_custkey, o.o_orderkey
FROM customer c LEFT OUTER JOIN c.c_orders o
LIMIT 5;
```

c_custkey	o_orderkey
60210	NULL
147873	NULL
72578	558821
72578	2079810
72578	5768068

The following query returns *only* customers that have no orders. (With LEFT ANTI JOIN or LEFT SEMI JOIN, the query can only refer to columns from the left-hand table, because by definition there is no matching information in the right-hand table.)

```
SELECT c.c_custkey, c.c_name
FROM customer c LEFT ANTI JOIN c.c_orders o
LIMIT 5;
```

c_custkey	c_name
60210	Customer#000060210
147873	Customer#000147873
141576	Customer#000141576
85365	Customer#000085365
70998	Customer#000070998

You can also perform correlated subqueries to examine the properties of complex type columns for each row in the result set.

Count the number of orders per customer. Note the correlated reference to the table alias C. The COUNT(*) operation applies to all the elements of the C_ORDERS array for the corresponding row, avoiding the need for a GROUP BY clause.

```
select c_name, howmany FROM customer c, (SELECT COUNT(*) howmany FROM
c.c_orders) v limit 5;
```

c_name	howmany
Customer#000030065	15
Customer#000065455	18
Customer#000113644	21
Customer#000111078	0
Customer#000024621	0

Count the number of orders per customer, ignoring any customers that have not placed any orders:

```
SELECT c_name, howmany_orders
```

```

FROM
  customer c,
  (SELECT COUNT(*) howmany_orders FROM c.c_orders) subq1
WHERE howmany_orders > 0
LIMIT 5;

```

c_name	howmany_orders
Customer#000072578	7
Customer#000046378	26
Customer#000069815	11
Customer#000079058	12
Customer#000092239	26

Count the number of line items in each order. The reference to C.C_ORDERS in the FROM clause is needed because the O_ORDERKEY field is a member of the elements in the C_ORDERS array. The subquery labelled SUBQ1 is correlated: it is re-evaluated for the C_ORDERS.O_LINEITEMS array from each row of the CUSTOMERS table.

```

SELECT c_name, o_orderkey, howmany_line_items
FROM
  customer c,
  c.c_orders t2,
  (SELECT COUNT(*) howmany_line_items FROM c.c_orders.o_lineitems) subq1
WHERE howmany_line_items > 0
LIMIT 5;

```

c_name	o_orderkey	howmany_line_items
Customer#000020890	1884930	95
Customer#000020890	4570754	95
Customer#000020890	3771072	95
Customer#000020890	2555489	95
Customer#000020890	919171	95

Get the number of orders, the average order price, and the maximum items in any order per customer. For this example, the subqueries labelled SUBQ1 and SUBQ2 are correlated: they are re-evaluated for each row from the original CUSTOMER table, and only apply to the complex columns associated with that row.

```

SELECT c_name, howmany, average_price, most_items
FROM
  customer c,
  (SELECT COUNT(*) howmany, AVG(o_totalprice) average_price FROM c.c_orders)
  subq1,
  (SELECT MAX(l_quantity) most_items FROM c.c_orders.o_lineitems ) subq2
LIMIT 5;

```

c_name	howmany	average_price	most_items
Customer#000030065	15	128908.34	50.00
Customer#000088191	0	NULL	NULL
Customer#000101555	10	164250.31	50.00
Customer#000022092	0	NULL	NULL
Customer#000036277	27	166040.06	50.00

For example, these queries show how to access information about the ARRAY elements within the CUSTOMER table from the “nested TPC-H” schema, starting with the initial ARRAY elements and progressing to examine the STRUCT fields of the ARRAY, and then the elements nested within another ARRAY of STRUCT:

```
-- How many orders does each customer have?
```

```
-- The type of the ARRAY column doesn't matter, this is just counting the
elements.
```

```
SELECT c_custkey, count(*)
  FROM customer, customer.c_orders
 GROUP BY c_custkey
 LIMIT 5;
```

c_custkey	count(*)
61081	21
115987	15
69685	19
109124	15
50491	12

```
-- How many line items are part of each customer order?
-- Now we examine a field from a STRUCT nested inside the ARRAY.
SELECT c_custkey, c_orders.o_orderkey, count(*)
  FROM customer, customer.c_orders c_orders, c_orders.o_lineitems
 GROUP BY c_custkey, c_orders.o_orderkey
 LIMIT 5;
```

c_custkey	o_orderkey	count(*)
63367	4985959	7
53989	1972230	2
143513	5750498	5
17849	4857989	1
89881	1046437	1

```
-- What are the line items in each customer order?
-- One of the STRUCT fields inside the ARRAY is another
-- ARRAY containing STRUCT elements. The join finds
-- all the related items from both levels of ARRAY.
SELECT c_custkey, o_orderkey, l_partkey
  FROM customer, customer.c_orders, c_orders.o_lineitems
 LIMIT 5;
```

c_custkey	o_orderkey	l_partkey
113644	2738497	175846
113644	2738497	27309
113644	2738497	175873
113644	2738497	88559
113644	2738497	8032

Pseudocolumns for ARRAY and MAP Types

Each element in an ARRAY type has a position, indexed starting from zero, and a value. Each element in a MAP type represents a key-value pair. Impala provides pseudocolumns that let you retrieve this metadata as part of a query, or filter query results by including such things in a WHERE clause. You refer to the pseudocolumns as part of qualified column names in queries:

- **ITEM:** The value of an array element. If the ARRAY contains STRUCT elements, you can refer to either `array_name.ITEM.field_name` or use the shorthand `array_name.field_name`.
- **POS:** The position of an element within an array.
- **KEY:** The value forming the first part of a key-value pair in a map. It is not necessarily unique.

- **VALUE:** The data item forming the second part of a key-value pair in a map. If the **VALUE** part of the **MAP** element is a **STRUCT**, you can refer to either `map_name.VALUE.field_name` or use the shorthand `map_name.field_name`.

ITEM and POS Pseudocolumns

When an **ARRAY** column contains **STRUCT** elements, you can refer to a field within the **STRUCT** using a qualified name of the form `array_column.field_name`. If the **ARRAY** contains scalar values, Impala recognizes the special name `array_column.ITEM` to represent the value of each scalar array element. For example, if a column contained an **ARRAY** where each element was a **STRING**, you would use `array_name.ITEM` to refer to each scalar value in the **SELECT** list, or the **WHERE** or other clauses.

This example shows a table with two **ARRAY** columns whose elements are of the scalar type **STRING**. When referring to the values of the array elements in the **SELECT** list, **WHERE** clause, or **ORDER BY** clause, you use the **ITEM** pseudocolumn because within the array, the individual elements have no defined names.

```
create TABLE persons_of_interest
(
  person_id BIGINT,
  aliases ARRAY <STRING>,
  associates ARRAY <STRING>,
  real_name STRING
)
STORED AS PARQUET;

-- Get all the aliases of each person.
SELECT real_name, aliases.ITEM
  FROM persons_of_interest, persons_of_interest.aliases
 ORDER BY real_name, aliases.item;

-- Search for particular associates of each person.
SELECT real_name, associates.ITEM
  FROM persons_of_interest, persons_of_interest.associates
 WHERE associates.item LIKE '% MacGuffin';
```

Because an array is inherently an ordered data structure, Impala recognizes the special name `array_column.POS` to represent the numeric position of each element within the array. The **POS** pseudocolumn lets you filter or reorder the result set based on the sequence of array elements.

The following example uses a table from a flattened version of the TPC-H schema. The **REGION** table only has a few rows, such as one row for Europe and one for Asia. The row for each region represents all the countries in that region as an **ARRAY** of **STRUCT** elements:

```
[localhost:21000] > desc region;
+-----+
+-----+-----+
| name      | type      |
+-----+-----+
| r_regionkey | smallint  |
| r_name      | string    |
| r_comment   | string    |
| r_nations   | array<struct<n_nationkey:smallint,n_name:string,n_comment:string>> |
+-----+-----+
```

To find the countries within a specific region, you use a join query. To find out the order of elements in the array, you also refer to the POS pseudocolumn in the select list:

```
[localhost:21000] > SELECT r1.r_name, r2.n_name, r2.POS
> FROM region r1 INNER JOIN r1.r_nations r2
> WHERE r1.r_name = 'ASIA';
```

r_name	n_name	pos
ASIA	VIETNAM	0
ASIA	CHINA	1
ASIA	JAPAN	2
ASIA	INDONESIA	3
ASIA	INDIA	4

Once you know the positions of the elements, you can use that information in subsequent queries, for example to change the ordering of results from the complex type column or to filter certain elements from the array:

```
[localhost:21000] > SELECT r1.r_name, r2.n_name, r2.POS
> FROM region r1 INNER JOIN r1.r_nations r2
> WHERE r1.r_name = 'ASIA'
> ORDER BY r2.POS DESC;
```

r_name	n_name	pos
ASIA	INDIA	4
ASIA	INDONESIA	3
ASIA	JAPAN	2
ASIA	CHINA	1
ASIA	VIETNAM	0

```
[localhost:21000] > SELECT r1.r_name, r2.n_name, r2.POS
> FROM region r1 INNER JOIN r1.r_nations r2
> WHERE r1.r_name = 'ASIA' AND r2.POS BETWEEN 1 and 3;
```

r_name	n_name	pos
ASIA	CHINA	1
ASIA	JAPAN	2
ASIA	INDONESIA	3

KEY and VALUE Pseudocolumns

The MAP data type is suitable for representing sparse or wide data structures, where each row might only have entries for a small subset of named fields. Because the element names (the map keys) vary depending on the row, a query must be able to refer to both the key and the value parts of each key-value pair. The KEY and VALUE pseudocolumns let you refer to the parts of the key-value pair independently within the query, as `map_column.KEY` and `map_column.VALUE`.

The KEY must always be a scalar type, such as STRING, BIGINT, or TIMESTAMP. It can be NULL. Values of the KEY field are not necessarily unique within the same MAP. You apply any required DISTINCT, GROUP BY, and other clauses in the query, and loop through the result set to process all the values matching any specified keys.

The VALUE can be either a scalar type or another complex type. If the VALUE is a STRUCT, you can construct a qualified name `map_column.VALUE.struct_field` to refer to the individual fields inside the value part. If the VALUE is an ARRAY or another MAP, you must include another join condition that establishes a table alias for `map_column.VALUE`, and then construct another qualified name using that alias, for example `table_alias.ITEM` or `table_alias.KEY` and `table_alias.VALUE`.

The following example shows different ways to access a MAP column using the KEY and VALUE pseudocolumns. The DETAILS column has a STRING first part with short, standardized values such as 'Recurring', 'Lucid', or 'Anxiety'. This is the “key” that is used to look up particular kinds of elements from the MAP. The second part, also a STRING, is a longer free-form explanation. Impala gives you the standard pseudocolumn names KEY and VALUE for the two parts, and you apply your own conventions and interpretations to the underlying values.

Note: If you find that the single-item nature of the VALUE makes it difficult to model your data accurately, the solution is typically to add some nesting to the complex type. For example, to have several sets of key-value pairs, make the column an ARRAY whose elements are MAP. To make a set of key-value pairs that holds more elaborate information, make a MAP column whose VALUE part contains an ARRAY or a STRUCT.

```
CREATE TABLE dream_journal
(
  dream_id BIGINT,
  details MAP <STRING,STRING>
)
STORED AS PARQUET;

-- What are all the types of dreams that are recorded?
SELECT DISTINCT details.KEY FROM dream_journal, dream_journal.details;

-- How many lucid dreams were recorded?
-- Because there is no GROUP BY, we count the 'Lucid' keys across all rows.
SELECT COUNT(details.KEY)
  FROM dream_journal, dream_journal.details
 WHERE details.KEY = 'Lucid';

-- Print a report of a subset of dreams, filtering based on both the lookup
  key
-- and the detailed value.
SELECT dream_id, details.KEY AS "Dream Type", details.VALUE AS "Dream
  Summary"
  FROM dream_journal, dream_journal.details
 WHERE
  details.KEY IN ('Happy', 'Pleasant', 'Joyous')
  AND details.VALUE LIKE '%childhood%';
```

The following example shows a more elaborate version of the previous table, where the VALUE part of the MAP entry is a STRUCT rather than a scalar type. Now instead of referring to the VALUE pseudocolumn directly, you use dot notation to refer to the STRUCT fields inside it.

```
CREATE TABLE better_dream_journal
(
  dream_id BIGINT,
  details MAP <STRING,STRUCT <summary: STRING, when_happened: TIMESTAMP,
  duration: DECIMAL(5,2), woke_up: BOOLEAN> >
)
STORED AS PARQUET;

-- Do more elaborate reporting and filtering by examining multiple
  attributes within the same dream.
SELECT dream_id, details.KEY AS "Dream Type", details.VALUE.summary AS
  "Dream Summary", details.VALUE.duration AS "Duration"
  FROM better_dream_journal, better_dream_journal.details
 WHERE
  details.KEY IN ('Anxiety', 'Nightmare')
  AND details.VALUE.duration > 60
  AND details.VALUE.woke_up = TRUE;

-- Remember that if the ITEM or VALUE contains a STRUCT, you can reference
```

```
-- the STRUCT fields directly without the .ITEM or .VALUE qualifier.
SELECT dream_id, details.KEY AS "Dream Type", details.summary AS "Dream
  Summary", details.duration AS "Duration"
  FROM better_dream_journal, better_dream_journal.details
 WHERE
   details.KEY IN ('Anxiety', 'Nightmare')
   AND details.duration > 60
   AND details.woke_up = TRUE;
```

Loading Data Containing Complex Types

Because the Impala INSERT statement does not currently support creating new data with complex type columns, or copying existing complex type values from one table to another, you primarily use Impala to query Parquet/ORC tables with complex types where the data was inserted through Hive, or create tables with complex types where you already have existing Parquet/ORC data files.

If you have created a Hive table with the Parquet/ORC file format and containing complex types, use the same table for Impala queries with no changes. If you have such a Hive table in some other format, use a Hive CREATE TABLE AS SELECT ... STORED AS PARQUET or INSERT ... SELECT statement to produce an equivalent Parquet table that Impala can query.

If you have existing Parquet data files containing complex types, located outside of any Impala or Hive table, such as data files created by Spark jobs, you can use an Impala CREATE TABLE ... STORED AS PARQUET statement, followed by an Impala LOAD DATA statement to move the data files into the table. As an alternative, you can use an Impala CREATE EXTERNAL TABLE statement to create a table pointing to the HDFS directory that already contains the Parquet or ORC data files.

The simplest way to get started with complex type data is to take a denormalized table containing duplicated values, and use an INSERT ... SELECT statement to copy the data into a Parquet table and condense the repeated values into complex types. With the Hive INSERT statement, you use the COLLECT_LIST(), NAMED_STRUCT(), and MAP() constructor functions within a GROUP BY query to produce the complex type values. COLLECT_LIST() turns a sequence of values into an ARRAY. NAMED_STRUCT() uses the first, third, and so on arguments as the field names for a STRUCT, to match the field names from the CREATE TABLE statement.

Note: Because Hive currently cannot construct individual rows using complex types through the INSERT ... VALUES syntax, you prepare the data in flat form in a separate table, then copy it to the table with complex columns using INSERT ... SELECT and the complex type constructors. See [Constructing Parquet/ORC Files with Complex Columns Using Hive](#) on page 167 for examples.

Using Complex Types as Nested Types

The ARRAY, STRUCT, and MAP types can be the top-level types for “nested type” columns. That is, each of these types can contain other complex or scalar types, with multiple levels of nesting to a maximum depth of 100. For example, you can have an array of structures, a map containing other maps, a structure containing an array of other structures, and so on. At the lowest level, there are always scalar types making up the fields of a STRUCT, elements of an ARRAY, and keys and values of a MAP.

Schemas involving complex types typically use some level of nesting for the complex type columns.

For example, to model a relationship like a dimension table and a fact table, you typically use an ARRAY where each array element is a STRUCT. The STRUCT fields represent what would traditionally be columns in a separate joined table. It makes little sense to use a STRUCT as the top-level type for a column, because you could just make the fields of the STRUCT into regular table columns.

Perhaps the only use case for a top-level STRUCT would be to allow STRUCT fields with the same name as columns to coexist in the same table. The following example shows how a table could have a column named ID, and two separate STRUCT fields also named ID. Because the STRUCT fields are always referenced using qualified names, the identical ID names do not cause a conflict.

```
CREATE TABLE struct_namespaces
(
  id BIGINT
```



```

    , s1 STRUCT < id: BIGINT, field1: STRING >
    , s2 STRUCT < id: BIGINT, when_happened: TIMESTAMP >
  )
  STORED AS PARQUET;

select id, s1.id, s2.id from struct_namespaces;

```

It is common to make the value portion of each key-value pair in a MAP a STRUCT, ARRAY of STRUCT, or other complex type variation. That way, each key in the MAP can be associated with a flexible and extensible data structure. The key values are not predefined ahead of time (other than by specifying their data type). Therefore, the MAP can accommodate a rapidly evolving schema, or sparse data structures where each row contains only a few data values drawn from a large set of possible choices.

Although you can use an ARRAY of scalar values as the top-level column in a table, such a simple array is typically of limited use for analytic queries. The only property of the array elements, aside from the element value, is the ordering sequence available through the POS pseudocolumn. To record any additional item about each array element, such as a TIMESTAMP or a symbolic name, you use an ARRAY of STRUCT rather than of scalar values.

If you are considering having multiple ARRAY or MAP columns, with related items under the same position in each ARRAY or the same key in each MAP, prefer to use a STRUCT to group all the related items into a single ARRAY or MAP. Doing so avoids the additional storage overhead and potential duplication of key values from having an extra complex type column. Also, because each ARRAY or MAP that you reference in the query SELECT list requires an additional join clause, minimizing the number of complex type columns also makes the query easier to read and maintain, relying more on dot notation to refer to the relevant fields rather than a sequence of join clauses.

For example, here is a table with several complex type columns all at the top level and containing only scalar types. To retrieve every data item for the row requires a separate join for each ARRAY or MAP column. The fields of the STRUCT can be referenced using dot notation, but there is no real advantage to using the STRUCT at the top level rather than just making separate columns FIELD1 and FIELD2.

```

CREATE TABLE complex_types_top_level
(
  id BIGINT,
  a1 ARRAY<INT>,
  a2 ARRAY<STRING>,
  s STRUCT<field1: INT, field2: STRING>,
  -- Numeric lookup key for a string value.
  m1 MAP<INT,STRING>,
  -- String lookup key for a numeric value.
  m2 MAP<STRING,INT>
)
STORED AS PARQUET;

```

```
describe complex_types_top_level;
```

name	type
id	bigint
a1	array<int>
a2	array<string>
s	struct< field1:int, field2:string >
m1	map<int,string>
m2	map<string,int>

```

select
  id,
  a1.item,

```

```

    a2.item,
    s.field1,
    s.field2,
    m1.key,
    m1.value,
    m2.key,
    m2.value
from
    complex_types_top_level,
    complex_types_top_level.a1,
    complex_types_top_level.a2,
    complex_types_top_level.m1,
    complex_types_top_level.m2;

```

For example, here is a table with columns containing an ARRAY of STRUCT, a MAP where each key value is a STRUCT, and a MAP where each key value is an ARRAY of STRUCT.

```

CREATE TABLE nesting_demo
(
    user_id BIGINT,
    family_members ARRAY < STRUCT < name: STRING, email: STRING, date_joined:
TIMESTAMP >>,
    foo map < STRING, STRUCT < f1: INT, f2: INT, f3: TIMESTAMP, f4: BOOLEAN
>>,
    gameplay MAP < STRING , ARRAY < STRUCT <
        name: STRING, highest: BIGINT, lives_used: INT, total_spent:
DECIMAL(16,2)
    >>>
)
STORED AS PARQUET;

```

The DESCRIBE statement rearranges the < and > separators and the field names within each STRUCT for easy readability:

```
DESCRIBE nesting_demo;
```

name	type
user_id	bigint
family_members	array<struct< name:string, email:string, date_joined:timestamp >>
foo	map<string,struct< f1:int, f2:int, f3:timestamp, f4:boolean >>
gameplay	map<string,array<struct< name:string, highest:bigint, lives_used:int, total_spent:decimal(16,2) >>>

To query the complex type columns, you use join notation to refer to the lowest-level scalar values. If the value is an ARRAY element, the fully qualified name includes the ITEM pseudocolumn. If the value is inside a MAP, the fully qualified name includes the KEY or VALUE pseudocolumn. Each reference to a different ARRAY or MAP (even if nested inside another complex type) requires an additional join clause.

```
SELECT
-- The lone scalar field doesn't require any dot notation or join clauses.
  user_id
-- Retrieve the fields of a STRUCT inside an ARRAY.
-- The FAMILY_MEMBERS name refers to the FAMILY_MEMBERS table alias defined
  later in the FROM clause.
  , family_members.item.name
  , family_members.item.email
  , family_members.item.date_joined
-- Retrieve the KEY and VALUE fields of a MAP, with the value being a STRUCT
  consisting of more fields.
-- The FOO name refers to the FOO table alias defined later in the FROM
  clause.
  , foo.key
  , foo.value.f1
  , foo.value.f2
  , foo.value.f3
  , foo.value.f4
-- Retrieve the KEY fields of a MAP, and expand the VALUE part into ARRAY
  items consisting of STRUCT fields.
-- The GAMEPLAY name refers to the GAMEPLAY table alias defined later in the
  FROM clause (referring to the MAP item).
-- The GAME_N name refers to the GAME_N table alias defined later in the
  FROM clause (referring to the ARRAY
  inside the MAP item's VALUE part.)
  , gameplay.key
  , game_n.name
  , game_n.highest
  , game_n.lives_used
  , game_n.total_spent
FROM
  nesting_demo
  , nesting_demo.family_members AS family_members
  , nesting_demo.foo AS foo
  , nesting_demo.gameplay AS gameplay
  , nesting_demo.gameplay.value AS game_n;
```

Once you understand the notation to refer to a particular data item in the SELECT list, you can use the same qualified name to refer to that data item in other parts of the query, such as the WHERE clause, ORDER BY or GROUP BY clauses, or calls to built-in functions. For example, you might frequently retrieve the VALUE part of each MAP item in the SELECT list, while choosing the specific MAP items by running comparisons against the KEY part in the WHERE clause.

Accessing Complex Type Data in Flattened Form Using Views

The layout of complex and nested types is largely a physical consideration. The complex type columns reside in the same data files rather than in separate normalized tables, for your convenience in managing related data sets and performance in querying related data sets. You can use views to treat tables with complex types as if they were flattened. By putting the join logic and references to the complex type columns in the view definition, you can query the same tables using existing queries intended for tables containing only scalar columns. This technique also lets you use tables with complex types with BI tools that are not aware of the data types and query notation for accessing complex type columns.

For example, the variation of the TPC-H schema containing complex types has a table `REGION`. This table has 5 rows, corresponding to 5 regions such as `NORTH AMERICA` and `AFRICA`. Each row has an `ARRAY` column, where each array item is a `STRUCT` containing details about a country in that region.

```
DESCRIBE region;
+-----+-----+
| name      | type      |
+-----+-----+
| r_regionkey | smallint  |
| r_name     | string    |
| r_comment  | string    |
| r_nations  | array<struct<
|              n_nationkey:smallint,
|              n_name:string,
|              n_comment:string
|              >>
+-----+-----+
```

The same data could be represented in traditional denormalized form, as a single table where the information about each region is repeated over and over, alongside the information about each country. The nested complex types let us avoid the repetition, while still keeping the data in a single table rather than normalizing across multiple tables.

To use this table with a JDBC or ODBC application that expected scalar columns, we could create a view that represented the result set as a set of scalar columns (three columns from the original table, plus three more from the `STRUCT` fields of the array elements). In the following examples, any column with an `R_*` prefix is taken unchanged from the original table, while any column with an `N_*` prefix is extracted from the `STRUCT` inside the `ARRAY`.

```
CREATE VIEW region_view AS
SELECT
  r_regionkey,
  r_name,
  r_comment,
  array_field.item.n_nationkey AS n_nationkey,
  array_field.item.n_name AS n_name,
  array_field.n_comment AS n_comment
FROM
  region, region.r_nations AS array_field;
```

Then we point the application queries at the view rather than the original table. From the perspective of the view, there are 25 rows in the result set, one for each nation in each region, and queries can refer freely to fields related to the region or the nation.

```
-- Retrieve info such as the nation name from the original R_NATIONS array
  elements.
select n_name from region_view where r_name in ('EUROPE', 'ASIA');
+-----+
| n_name      |
+-----+
| UNITED KINGDOM |
| RUSSIA        |
| ROMANIA       |
| GERMANY        |
| FRANCE        |
| VIETNAM        |
| CHINA          |
| JAPAN          |
| INDONESIA      |
| INDIA          |
+-----+

-- UNITED STATES in AMERICA and UNITED KINGDOM in EUROPE.
```

```

SELECT DISTINCT r_name FROM region_view WHERE n_name LIKE 'UNITED%';
+-----+
| r_name |
+-----+
| AMERICA |
| EUROPE  |
+-----+

-- For conciseness, we only list some view columns in the SELECT list.
-- SELECT * would bring back all the data, unlike SELECT *
-- queries on the original table with complex type columns.
SELECT r_regionkey, r_name, n_nationkey, n_name FROM region_view LIMIT 7;
+-----+-----+-----+-----+
| r_regionkey | r_name | n_nationkey | n_name |
+-----+-----+-----+-----+
| 3           | EUROPE | 23          | UNITED KINGDOM |
| 3           | EUROPE | 22          | RUSSIA         |
| 3           | EUROPE | 19          | ROMANIA        |
| 3           | EUROPE | 7           | GERMANY        |
| 3           | EUROPE | 6           | FRANCE         |
| 2           | ASIA   | 21          | VIETNAM        |
| 2           | ASIA   | 18          | CHINA          |
+-----+-----+-----+-----+

```

Tutorials and Examples for Complex Types

The following examples illustrate the query syntax for some common use cases involving complex type columns.

Sample Schema and Data for Experimenting with Impala Complex Types

The tables used for earlier examples of complex type syntax are trivial ones with no actual data. The more substantial examples of the complex type feature use these tables, adapted from the schema used for TPC-H testing:

```

SHOW TABLES;
+-----+
| name |
+-----+
| customer |
| part |
| region |
| supplier |
+-----+

DESCRIBE customer;
+-----+-----+
| name | type |
+-----+-----+
| c_custkey | bigint |
| c_name | string |
| c_address | string |
| c_nationkey | smallint |
| c_phone | string |
| c_acctbal | decimal(12,2) |
| c_mktsegment | string |
| c_comment | string |
| c_orders | array<struct<
|           |     o_orderkey:bigint,
|           |     o_orderstatus:string,
|           |     o_totalprice:decimal(12,2),
|           |     o_orderdate:string,
|           |     o_orderpriority:string,
|           |     o_clerk:string,
|           |     o_shippriority:int,
+-----+-----+

```

```

o_comment:string,
o_lineitems:array<struct<
  l_partkey:bigint,
  l_suppkey:bigint,
  l_linenumber:int,
  l_quantity:decimal(12,2),
  l_extendedprice:decimal(12,2),
  l_discount:decimal(12,2),
  l_tax:decimal(12,2),
  l_returnflag:string,
  l_linestatus:string,
  l_shipdate:string,
  l_commitdate:string,
  l_receiptdate:string,
  l_shipinstruct:string,
  l_shipmode:string,
  l_comment:string
>>
>>

```

```
DESCRIBE part;
```

name	type
p_partkey	bigint
p_name	string
p_mfgr	string
p_brand	string
p_type	string
p_size	int
p_container	string
p_retailprice	decimal(12,2)
p_comment	string

```
DESCRIBE region;
```

name	type
r_regionkey	smallint
r_name	string
r_comment	string
r_nations	array<struct<n_nationkey:smallint,n_name:string,n_comment:string>>

```
DESCRIBE supplier;
```

name	type
s_suppkey	bigint
s_name	string
s_address	string
s_nationkey	smallint
s_phone	string
s_acctbal	decimal(12,2)

s_comment	string
s_partsupps	array<struct<ps_partkey:bigint, ps_availqty:int,ps_supplycost:decimal(12,2), ps_comment:string>>

The volume of data used in the following examples is:

```
SELECT count(*) FROM customer;
```

```
+-----+
| count(*) |
+-----+
| 150000   |
+-----+
```

```
SELECT count(*) FROM part;
```

```
+-----+
| count(*) |
+-----+
| 200000   |
+-----+
```

```
SELECT count(*) FROM region;
```

```
+-----+
| count(*) |
+-----+
| 5         |
+-----+
```

```
SELECT count(*) FROM supplier;
```

```
+-----+
| count(*) |
+-----+
| 10000    |
+-----+
```

Constructing Parquet/ORC Files with Complex Columns Using Hive

The following examples demonstrate the Hive syntax to transform flat data (tables with all scalar columns) into Parquet/ORC tables where Impala can query the complex type columns. Each example shows the full sequence of steps, including switching back and forth between Impala and Hive. Although the source table can use any file format, the destination table must use the Parquet/ORC file format. We take Parquet in the following examples. You can replace Parquet with ORC to do the same things in ORC file format.

Create table with ARRAY in Impala, load data in Hive, query in Impala:

This example shows the cycle of creating the tables and querying the complex data in Impala, and using Hive (either the hive shell or beeline) for the data loading step. The data starts in flattened, denormalized form in a text table. Hive writes the corresponding Parquet data, including an ARRAY column. Then Impala can run analytic queries on the Parquet table, using join notation to unpack the ARRAY column.

```
/* Initial DDL and loading of flat, denormalized data happens in impala-
shell */CREATE TABLE flat_array (country STRING, city STRING);INSERT INTO
flat_array VALUES
('Canada', 'Toronto') , ('Canada', 'Vancouver') , ('Canada', "St. John
\s"')
, ('Canada', 'Saint John') , ('Canada', 'Montreal') , ('Canada',
'Halifax')
, ('Canada', 'Winnipeg') , ('Canada', 'Calgary') , ('Canada', 'Saskatoon')
, ('Canada', 'Ottawa') , ('Canada', 'Yellowknife') , ('France', 'Paris')
, ('France', 'Nice') , ('France', 'Marseilles') , ('France', 'Cannes')
```

```
, ('Greece', 'Athens') , ('Greece', 'Piraeus') , ('Greece', 'Hania')
, ('Greece', 'Heraklion') , ('Greece', 'Rethymnon') , ('Greece', 'Fira');

CREATE TABLE complex_array (country STRING, city ARRAY <STRING>) STORED AS
PARQUET;
```

```
/* Conversion to Parquet and complex and/or nested columns happens in Hive
*/

INSERT INTO complex_array SELECT country, collect_list(city) FROM flat_array
GROUP BY country;
Query ID = dev_20151108160808_84477ff2-82bd-4ba4-9a77-554fa7b8c0cb
Total jobs = 1
Launching Job 1 out of 1
...
```

```
/* Back to impala-shell again for analytic queries */

REFRESH complex_array;
SELECT country, city.item FROM complex_array, complex_array.city
```

country	item
Canada	Toronto
Canada	Vancouver
Canada	St. John's
Canada	Saint John
Canada	Montreal
Canada	Halifax
Canada	Winnipeg
Canada	Calgary
Canada	Saskatoon
Canada	Ottawa
Canada	Yellowknife
France	Paris
France	Nice
France	Marseilles
France	Cannes
Greece	Athens
Greece	Piraeus
Greece	Hania
Greece	Heraklion
Greece	Rethymnon
Greece	Fira

Create table with **STRUCT** and **ARRAY** in Impala, load data in Hive, query in Impala:

This example shows the cycle of creating the tables and querying the complex data in Impala, and using Hive (either the hive shell or beeline) for the data loading step. The data starts in flattened, denormalized form in a text table. Hive writes the corresponding Parquet data, including a **STRUCT** column with an **ARRAY** field. Then Impala can run analytic queries on the Parquet table, using join notation to unpack the **ARRAY** field from the **STRUCT** column.

```
/* Initial DDL and loading of flat, denormalized data happens in impala-
shell */

CREATE TABLE flat_struct_array (continent STRING, country STRING, city
STRING);
INSERT INTO flat_struct_array VALUES
```



```

    ('North America', 'Canada', 'Toronto') , ('North America', 'Canada',
'Vancouver')
    , ('North America', 'Canada', "St. John's") , ('North America', 'Canada',
'Saint John')
    , ('North America', 'Canada', 'Montreal') , ('North America', 'Canada',
'Halifax')
    , ('North America', 'Canada', 'Winnipeg') , ('North America', 'Canada',
'Calgary')
    , ('North America', 'Canada', 'Saskatoon') , ('North America', 'Canada',
'Ottawa')
    , ('North America', 'Canada', 'Yellowknife') , ('Europe', 'France',
'Paris')
    , ('Europe', 'France', 'Nice') , ('Europe', 'France', 'Marseilles')
    , ('Europe', 'France', 'Cannes') , ('Europe', 'Greece', 'Athens')
    , ('Europe', 'Greece', 'Piraeus') , ('Europe', 'Greece', 'Hania')
    , ('Europe', 'Greece', 'Heraklion') , ('Europe', 'Greece', 'Rethymnon')
    , ('Europe', 'Greece', 'Fira');

```

```

CREATE TABLE complex_struct_array (continent STRING, country STRUCT <name:
STRING, city: ARRAY <STRING> >) STORED AS PARQUET;

```

```

/* Conversion to Parquet and complex and/or nested columns happens in Hive
*/

```

```

INSERT INTO complex_struct_array SELECT continent, named_struct('name',
country, 'city', collect_list(city)) FROM flat_array_array GROUP BY
continent, country;

```

Query ID = dev_20151108163535_11a4fa53-0003-4638-97e6-ef13cdb8e09e

Total jobs = 1

Launching Job 1 out of 1

...

```

/* Back to impala-shell again for analytic queries */

```

```

REFRESH complex_struct_array;

```

```

SELECT t1.continent, t1.country.name, t2.item
FROM complex_struct_array t1, t1.country.city t2

```

continent	country.name	item
Europe	France	Paris
Europe	France	Nice
Europe	France	Marseilles
Europe	France	Cannes
Europe	Greece	Athens
Europe	Greece	Piraeus
Europe	Greece	Hania
Europe	Greece	Heraklion
Europe	Greece	Rethymnon
Europe	Greece	Fira
North America	Canada	Toronto
North America	Canada	Vancouver
North America	Canada	St. John's
North America	Canada	Saint John
North America	Canada	Montreal
North America	Canada	Halifax
North America	Canada	Winnipeg
North America	Canada	Calgary
North America	Canada	Saskatoon
North America	Canada	Ottawa

North America	Canada	Yellowknife
+-----+	+-----+	+-----+

Flattening Normalized Tables into a Single Table with Complex Types

One common use for complex types is to embed the contents of one table into another. The traditional technique of denormalizing results in a huge number of rows with some column values repeated over and over. With complex types, you can keep the same number of rows as in the original normalized table, and put all the associated data from the other table in a single new column.

In this flattening scenario, you might frequently use a column that is an `ARRAY` consisting of `STRUCT` elements, where each field within the `STRUCT` corresponds to a column name from the table that you are combining.

The following example shows a traditional normalized layout using two tables, and then an equivalent layout using complex types in a single table.

```
/* Traditional relational design */

-- This table just stores numbers, allowing us to look up details about the
-- employee
-- and details about their vacation time using a three-table join query.
CREATE table employee_vacations
(
  employee_id BIGINT,
  vacation_id BIGINT
)
STORED AS PARQUET;

-- Each kind of information to track gets its own "fact table".
CREATE table vacation_details
(
  vacation_id BIGINT,
  vacation_start TIMESTAMP,
  duration INT
)
STORED AS PARQUET;

-- Any time we print a human-readable report, we join with this table to
-- display info about employee #1234.
CREATE TABLE employee_contact
(
  employee_id BIGINT,
  name STRING,
  address STRING,
  phone STRING,
  email STRING,
  address_type STRING /* 'home', 'work', 'remote', etc. */
)
STORED AS PARQUET;

/* Equivalent flattened schema using complex types */

-- For analytic queries using complex types, we can bundle the dimension
-- table
-- and multiple fact tables into a single table.
CREATE TABLE employee_vacations_nested_types
(
  -- We might still use the employee_id for other join queries.
  -- The table needs at least one scalar column to serve as an identifier
  -- for the complex type columns.
  employee_id BIGINT,
```


name	type	comment
c_custkey	bigint	
c_name	string	
c_address	string	
c_nationkey	smallint	
c_phone	string	
c_acctbal	decimal(12,2)	
c_mktsegment	string	
c_comment	string	
c_orders	array<struct< o_orderkey:bigint, o_orderstatus:string, o_totalprice:decimal(12,2), o_orderdate:string, o_orderpriority:string, o_clerk:string, o_shippriority:int, o_comment:string, o_lineitems:array<struct< l_partkey:bigint, l_suppkey:bigint, l_linenummer:int, l_quantity:decimal(12,2), l_extendedprice:decimal(12,2), l_discount:decimal(12,2), l_tax:decimal(12,2), l_returnflag:string, l_linestatus:string, l_shipdate:string, l_commitdate:string, l_receiptdate:string, l_shipinstruct:string, l_shipmode:string, l_comment:string >> >>	

```
describe customer_ctlp;
```

name	type	comment
c_custkey	bigint	Inferred from Parquet
c_name	string	Inferred from Parquet
c_address	string	Inferred from Parquet
c_nationkey	int	Inferred from Parquet
c_phone	string	Inferred from Parquet
c_acctbal	decimal(12,2)	Inferred from Parquet
c_mktsegment	string	Inferred from Parquet
c_comment	string	Inferred from Parquet
c_orders	array<struct<	Inferred from Parquet

```

|      |      |      o_orderkey:bigint,      |
|      |      |      o_orderstatus:string,   |
|      |      |      o_totalprice:decimal(12,2), |
|      |      |      o_orderdate:string,     |
|      |      |      o_orderpriority:string,  |
|      |      |      o_clerk:string,         |
|      |      |      o_shippriority:int,     |
|      |      |      o_comment:string,       |
|      |      |      o_lineitems:array<struct<
|      |      |          l_partkey:bigint,   |
|      |      |          l_suppkey:bigint,   |
|      |      |          l_linenum: int,     |
|      |      |          l_quantity:decimal(12,2), |
|      |      |          l_extendedprice:decimal(12,2), |
|      |      |          l_discount:decimal(12,2), |
|      |      |          l_tax:decimal(12,2), |
|      |      |          l_returnflag:string, |
|      |      |          l_linestatus:string, |
|      |      |          l_shipdate:string,   |
|      |      |          l_commitdate:string, |
|      |      |          l_receiptdate:string, |
|      |      |          l_shipinstruct:string, |
|      |      |          l_shipmode:string,   |
|      |      |          l_comment:string
|      |      |      >>
|      |      |  >>
+-----+
+-----+

```

Literals

Each of the Impala data types has corresponding notation for literal values of that type. You specify literal values in SQL statements, such as in the `SELECT` list or `WHERE` clause of a query, or as an argument to a function call. See [Data Types](#) on page 102 for a complete list of types, ranges, and conversion rules.

Numeric Literals

To write literals for the integer types (TINYINT, SMALLINT, INT, and BIGINT), use a sequence of digits with optional leading zeros.

To write literals for the floating-point types (DECIMAL, FLOAT, and DOUBLE), use a sequence of digits with an optional decimal point (. character). To preserve accuracy during arithmetic expressions, Impala interprets floating-point literals as the DECIMAL type with the smallest appropriate precision and scale, until required by the context to convert the result to FLOAT or DOUBLE.

Integer values are promoted to floating-point when necessary, based on the context.

You can also use exponential notation by including an e character. For example, 1e6 is 1 times 10 to the power of 6 (1 million). A number in exponential notation is always interpreted as floating-point.

When Impala encounters a numeric literal, it considers the type to be the “smallest” that can accurately represent the value. The type is promoted to larger or more accurate types if necessary, based on subsequent parts of an expression.

For example, you can see by the types Impala defines for the following table columns how it interprets the corresponding numeric literals:

```
[localhost:21000] > create table ten as select 10 as x;
+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc ten;
+-----+-----+-----+
| name | type   | comment |
+-----+-----+-----+
| x    | tinyint |         |
+-----+-----+-----+

[localhost:21000] > create table four_k as select 4096 as x;
+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc four_k;
+-----+-----+-----+
| name | type   | comment |
+-----+-----+-----+
| x    | smallint |         |
+-----+-----+-----+

[localhost:21000] > create table one_point_five as select 1.5 as x;
+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc one_point_five;
+-----+-----+-----+
| name | type           | comment |
+-----+-----+-----+
| x    | decimal(2,1)  |         |
+-----+-----+-----+

[localhost:21000] > create table one_point_three_three_three as select 1.333
as x;
+-----+
```

```

| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc one_point_three_three_three;
+-----+-----+-----+
| name | type          | comment |
+-----+-----+-----+
| x     | decimal(4,3)  |          |
+-----+-----+-----+

```

String Literals

String literals are quoted using either single or double quotation marks. You can use either kind of quotes for string literals, even both kinds for different literals within the same statement.

Quoted literals are considered to be of type `STRING`. To use quoted literals in contexts requiring a `CHAR` or `VARCHAR` value, `CAST()` the literal to a `CHAR` or `VARCHAR` of the appropriate length.

Escaping special characters:

To encode special characters within a string literal, precede them with the backslash (`\`) escape character:

- `\t` represents a tab.
- `\n` represents a newline or linefeed. This might cause extra line breaks in `impala-shell` output.
- `\r` represents a carriage return. This might cause unusual formatting (making it appear that some content is overwritten) in `impala-shell` output.
- `\b` represents a backspace. This might cause unusual formatting (making it appear that some content is overwritten) in `impala-shell` output.
- `\0` represents an ASCII nul character (not the same as a SQL `NULL`). This might not be visible in `impala-shell` output.
- `\Z` represents a DOS end-of-file character. This might not be visible in `impala-shell` output.
- `\%` and `_` can be used to escape wildcard characters within the string passed to the `LIKE` operator.
- `\` followed by 3 octal digits represents the ASCII code of a single character; for example, `\101` is ASCII 65, the character `A`.
- Use two consecutive backslashes (`\\`) to prevent the backslash from being interpreted as an escape character.
- Use the backslash to escape single or double quotation mark characters within a string literal, if the literal is enclosed by the same type of quotation mark.
- If the character following the `\` does not represent the start of a recognized escape sequence, the character is passed through unchanged.

Quotes within quotes:

To include a single quotation character within a string value, enclose the literal with either single or double quotation marks, and optionally escape the single quote as a `\'` sequence. Earlier releases required escaping a single quote inside double quotes. Continue using escape sequences in this case if you also need to run your SQL code on older versions of Impala.

To include a double quotation character within a string value, enclose the literal with single quotation marks, no escaping is necessary in this case. Or, enclose the literal with double quotation marks and escape the double quote as a `\"` sequence.

```

[localhost:21000] > select "What\'s happening?" as single_within_double,
                        >      'I\'m not sure.' as single_within_single,
                        >      "Homer wrote \"The Iliad\"." as
double_within_double,
                        >      'Homer also wrote "The Odyssey".' as
double_within_single;
+-----+-----+-----+
+-----+-----+-----+

```

```

| single_within_double | single_within_single | double_within_double |
double_within_single |
+-----+-----+-----+
+-----+
| What's happening?   | I'm not sure.         | Homer wrote "The Iliad". |
Homer also wrote "The Odyssey". |
+-----+-----+-----+
+-----+

```

Field terminator character in CREATE TABLE:

Note: The CREATE TABLE clauses FIELDS TERMINATED BY, ESCAPED BY, and LINES TERMINATED BY have special rules for the string literal used for their argument, because they all require a single character. You can use a regular character surrounded by single or double quotation marks, an octal sequence such as '\054' (representing a comma), or an integer in the range '-127'..'128' (with quotation marks but no backslash), which is interpreted as a single-byte ASCII character. Negative values are subtracted from 256; for example, FIELDS TERMINATED BY '-2' sets the field delimiter to ASCII code 254, the “Icelandic Thorn” character used as a delimiter by some data formats.

impala-shell considerations:

When dealing with output that includes non-ASCII or non-printable characters such as linefeeds and backspaces, use the `impala-shell` options to save to a file, turn off pretty printing, or both rather than relying on how the output appears visually. See [impala-shell Configuration Options](#) on page 791 for a list of `impala-shell` options.

Boolean Literals

For BOOLEAN values, the literals are TRUE and FALSE, with no quotation marks and case-insensitive.

Examples:

```

select true;
select * from t1 where assertion = false;
select case bool_col when true then 'yes' when false 'no' else 'null' end
from t1;

```

Timestamp Literals

Impala automatically converts STRING literals of the correct format into TIMESTAMP values. Timestamp values are accepted in the format 'yyyy#MM#dd HH:mm:ss.SSSSSS', and can consist of just the date, or just the time, with or without the fractional second portion. For example, you can specify TIMESTAMP values such as '1966#07#30', '08:30:00', or '1985#09#25 17:45:30.005'.

Leading zeroes are not required in the numbers representing the date component, such as month and date, or the time component, such as hour, minute, and second. For example, Impala accepts both '2018#1#1 01:02:03' and '2018#01#01 1:2:3' as valid.

In STRING to TIMESTAMP conversions, leading and trailing white spaces, such as a space, a tab, a newline, or a carriage return, are ignored. For example, Impala treats the following as equivalent: '1999#12#01 01:02:03', '1999#12#01 01:02:03', '1999#12#01 01:02:03\r\n\t'.

When you convert or cast a STRING literal to TIMESTAMP, you can use the following separators between the date part and the time part:

- One or more space characters

Example: CAST('2001-01-09 01:05:01' AS TIMESTAMP)

- The character “T”

Example: CAST('2001-01-09T01:05:01' AS TIMESTAMP)

You can also use `INTERVAL` expressions to add or subtract from timestamp literal values, such as `CAST('1966#07#30' AS TIMESTAMP) + INTERVAL 5 YEARS + INTERVAL 3 DAYS`. See [TIMESTAMP Data Type](#) on page 133 for details.

Depending on your data pipeline, you might receive date and time data as text, in notation that does not exactly match the format for Impala `TIMESTAMP` literals. See [Impala Date and Time Functions](#) on page 478 for functions that can convert between a variety of string literals (including different field order, separators, and timezone notation) and equivalent `TIMESTAMP` or numeric values.

Date Literals

The `DATE` literals are in the form of `DATE 'YYYY-MM-DD'`. For example, `DATE '2013-01-01'`

NULL

The notion of `NULL` values is familiar from all kinds of database systems, but each SQL dialect can have its own behavior and restrictions on `NULL` values. For Big Data processing, the precise semantics of `NULL` values are significant: any misunderstanding could lead to inaccurate results or misformatted data, that could be time-consuming to correct for large data sets.

- `NULL` is a different value than an empty string. The empty string is represented by a string literal with nothing inside, `" "` or `' '`.
- In a delimited text file, the `NULL` value is represented by the special token `\N`.
- When Impala inserts data into a partitioned table, and the value of one of the partitioning columns is `NULL` or the empty string, the data is placed in a special partition that holds only these two kinds of values. When these values are returned in a query, the result is `NULL` whether the value was originally `NULL` or an empty string. This behavior is compatible with the way Hive treats `NULL` values in partitioned tables. Hive does not allow empty strings as partition keys, and it returns a string value such as `__HIVE_DEFAULT_PARTITION__` instead of `NULL` when such values are returned from a query. For example:

```
create table t1 (i int) partitioned by (x int, y string);
-- Select an INT column from another table, with all rows going into a
  special HDFS subdirectory
-- named __HIVE_DEFAULT_PARTITION__. Depending on whether one or both of
  the partitioning keys
-- are null, this special directory name occurs at different levels of the
  physical data directory
-- for the table.
insert into t1 partition(x=NULL, y=NULL) select c1 from some_other_table;
insert into t1 partition(x, y=NULL) select c1, c2 from some_other_table;
insert into t1 partition(x=NULL, y) select c1, c3 from some_other_table;
```

- There is no `NOT NULL` clause when defining a column to prevent `NULL` values in that column.
- There is no `DEFAULT` clause to specify a non-`NULL` default value.
- If an `INSERT` operation mentions some columns but not others, the unmentioned columns contain `NULL` for all inserted rows.
- In Impala 1.2.1 and higher, all `NULL` values come at the end of the result set for `ORDER BY ... ASC` queries, and at the beginning of the result set for `ORDER BY ... DESC` queries. In effect, `NULL` is considered greater than all other values for sorting purposes. The original Impala behavior always put `NULL` values at the end, even for `ORDER BY ... DESC` queries. The new behavior in Impala 1.2.1 makes Impala more compatible with other popular database systems. In Impala 1.2.1 and higher, you can override or specify the sorting behavior for `NULL` by adding the clause `NULLS FIRST` or `NULLS LAST` at the end of the `ORDER BY` clause.

Note: Because the `NULLS FIRST` and `NULLS LAST` keywords are not currently available in Hive queries, any views you create using those keywords will not be available through Hive.

- In all other contexts besides sorting with `ORDER BY`, comparing a `NULL` to anything else returns `NULL`, making the comparison meaningless. For example, `10 > NULL` produces `NULL`, `10 < NULL` also produces `NULL`, `5 BETWEEN 1 AND NULL` produces `NULL`, and so on.

Several built-in functions serve as shorthand for evaluating expressions and returning NULL, 0, or some other substitution value depending on the expression result: `ifnull()`, `isnull()`, `nvl()`, `nullif()`, `nullifzero()`, and `zeroifnull()`. See [Impala Conditional Functions](#) on page 502 for details.

Kudu considerations:

Columns in Kudu tables have an attribute that specifies whether or not they can contain NULL values. A column with a NULL attribute can contain nulls. A column with a NOT NULL attribute cannot contain any nulls, and an INSERT, UPDATE, or UPSERT statement will skip any row that attempts to store a null in a column designated as NOT NULL. Kudu tables default to the NULL setting for each column, except columns that are part of the primary key.

In addition to columns with the NOT NULL attribute, Kudu tables also have restrictions on NULL values in columns that are part of the primary key for a table. No column that is part of the primary key in a Kudu table can contain any NULL values.

SQL Operators

SQL operators are a class of comparison functions that are widely used within the WHERE clauses of SELECT statements.

Arithmetic Operators

The arithmetic operators use expressions with a left-hand argument, the operator, and then (in most cases) a right-hand argument.

Syntax:

```
left_hand_arg binary_operator right_hand_arg
unary_operator single_arg
```

- **+** and **-**: Can be used either as unary or binary operators.
 - With unary notation, such as `+5`, `-2.5`, or `-col_name`, they multiply their single numeric argument by `+1` or `-1`. Therefore, unary `+` returns its argument unchanged, while unary `-` flips the sign of its argument. Although you can double up these operators in expressions such as `++5` (always positive) or `--2` or `+-2` (both always negative), you cannot double the unary minus operator because `--` is interpreted as the start of a comment. (You can use a double unary minus operator if you separate the `-` characters, for example with a space or parentheses.)
 - With binary notation, such as `2+2`, `5-2.5`, or `col1 + col2`, they add or subtract respectively the right-hand argument to (or from) the left-hand argument. Both arguments must be of numeric types.
- ***** and **/**: Multiplication and division respectively. Both arguments must be of numeric types.

When multiplying, the shorter argument is promoted if necessary (such as `SMALLINT` to `INT` or `BIGINT`, or `FLOAT` to `DOUBLE`), and then the result is promoted again to the next larger type. Thus, multiplying a `TINYINT` and an `INT` produces a `BIGINT` result. Multiplying a `FLOAT` and a `FLOAT` produces a `DOUBLE` result. Multiplying a `FLOAT` and a `DOUBLE` or a `DOUBLE` and a `DOUBLE` produces a `DECIMAL(38,17)`, because `DECIMAL` values can represent much larger and more precise values than `DOUBLE`.

When dividing, Impala always treats the arguments and result as `DOUBLE` values to avoid losing precision. If you need to insert the results of a division operation into a `FLOAT` column, use the `CAST()` function to convert the result to the correct type.

- **DIV**: Integer division. Arguments are not promoted to a floating-point type, and any fractional result is discarded. For example, `13 DIV 7` returns 1, `14 DIV 7` returns 2, and `15 DIV 7` returns 2. This operator is the same as the `QUOTIENT()` function.
- **%**: Modulo operator. Returns the remainder of the left-hand argument divided by the right-hand argument. Both arguments must be of one of the integer types.

- `&`, `|`, `~`, and `^`: Bitwise operators that return the logical AND, logical OR, NOT, or logical XOR (exclusive OR) of their argument values. Both arguments must be of one of the integer types. If the arguments are of different type, the argument with the smaller type is implicitly extended to match the argument with the longer type.

You can chain a sequence of arithmetic expressions, optionally grouping them with parentheses.

The arithmetic operators generally do not have equivalent calling conventions using functional notation. For example, prior to Impala 2.2, there is no `MOD()` function equivalent to the `%` modulo operator. Conversely, there are some arithmetic functions that do not have a corresponding operator. For example, for exponentiation you use the `POW()` function, but there is no `**` exponentiation operator. See [Impala Mathematical Functions](#) on page 434 for the arithmetic functions you can use.

Complex type considerations:

To access a column with a complex type (ARRAY, STRUCT, or MAP) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an ARRAY of STRUCT items). The array is unpacked inside the query using join notation. The array elements are referenced using the `ITEM` pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as `SUM()` and `AVG()` are computed using the numeric `R_NATIONKEY` field, and the general-purpose `MAX()` and `MIN()` values are computed from the string `N_NAME` field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7

EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```

select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;

```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a STRUCT type that is an item within an ARRAY column. Once the scalar numeric value R_NATIONKEY is extracted, it can be used in an arithmetic expression, such as multiplying by 10:

```

-- The SMALLINT is a field within an array of structs.
describe region;

```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string	

```

|          | >>          |          |
+-----+-----+-----+

-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey * 10
  from region, region.r_nations as nation
 where nation.item.n_nationkey < 5;
+-----+-----+-----+
| r_name      | item.n_name | nation.item.n_nationkey * 10 |
+-----+-----+-----+
| AMERICA     | CANADA      | 30                           |
| AMERICA     | BRAZIL      | 20                           |
| AMERICA     | ARGENTINA   | 10                           |
| MIDDLE EAST | EGYPT       | 40                           |
| AFRICA      | ALGERIA     | 0                            |
+-----+-----+-----+

```

BETWEEN Operator

In a WHERE clause, compares an expression to both a lower and upper bound. The comparison is successful if the expression is greater than or equal to the lower bound, and less than or equal to the upper bound. If the bound values are switched, so the lower bound is greater than the upper bound, does not match any values.

Syntax:

```
expression BETWEEN lower_bound AND upper_bound
```

Data types: Typically used with numeric data types. Works with any data type, although not very practical for BOOLEAN values. (BETWEEN false AND true will match all BOOLEAN values.) Use CAST() if necessary to ensure the lower and upper bound values are compatible types. Call string or date/time functions if necessary to extract or transform the relevant portion to compare, especially if the value can be transformed into a number.

Usage notes:

Be careful when using short string operands. A longer string that starts with the upper bound value will not be included, because it is considered greater than the upper bound. For example, BETWEEN 'A' and 'M' would not match the string value 'Midway'. Use functions such as upper(), lower(), substr(), trim(), and so on if necessary to ensure the comparison works as expected.

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

```

-- Retrieve data for January through June, inclusive.
select c1 from t1 where month between 1 and 6;

-- Retrieve data for names beginning with 'A' through 'M' inclusive.
-- Only test the first letter to ensure all the values starting with 'M' are
  matched.
-- Do a case-insensitive comparison to match names with various
  capitalization conventions.
select last_name from customers where upper(substr(last_name,1,1)) between
  'A' and 'M';

-- Retrieve data for only the first week of each month.

```

```
select count(distinct visitor_id)) from web_traffic where
  dayofmonth(when_viewed) between 1 and 7;
```

The following example shows how to do a BETWEEN comparison using a numeric field of a STRUCT type that is an item within an ARRAY column. Once the scalar numeric value R_NATIONKEY is extracted, it can be used in a comparison operator:

```
-- The SMALLINT is a field within an array of structs.
describe region;
+-----+-----+-----+
| name          | type                                | comment |
+-----+-----+-----+
| r_regionkey    | smallint                           |         |
| r_name         | string                             |         |
| r_comment      | string                             |         |
| r_nations      | array<struct<                       |         |
|                |   n_nationkey:smallint,            |         |
|                |   n_name:string,                  |         |
|                |   n_comment:string                |         |
|                | >>                                |         |
+-----+-----+-----+

-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
from region, region.r_nations as nation
where nation.item.n_nationkey between 3 and 5
+-----+-----+-----+
| r_name        | item.n_name | item.n_nationkey |
+-----+-----+-----+
| AMERICA       | CANADA      | 3                 |
| MIDDLE EAST   | EGYPT       | 4                 |
| AFRICA        | ETHIOPIA    | 5                 |
+-----+-----+-----+
```

Comparison Operators

Impala supports the familiar comparison operators for checking equality and sort order for the column data types:

Syntax:

```
left_hand_expression comparison_operator right_hand_expression
```

- =, !=, <>: apply to all types.
- <, <=, >, >=: apply to all types; for BOOLEAN, TRUE is considered greater than FALSE.

Alternatives:

The IN and BETWEEN operators provide shorthand notation for expressing combinations of equality, less than, and greater than comparisons with a single operator.

Because comparing any value to NULL produces NULL rather than TRUE or FALSE, use the IS NULL and IS NOT NULL operators to check if a value is NULL or not.

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a STRUCT type that is an item within an ARRAY column. Once the scalar numeric value R_NATIONKEY is extracted, it can be used with a comparison operator such as <:

```
-- The SMALLINT is a field within an array of structs.
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
from region, region.r_nations as nation
where nation.item.n_nationkey < 5
```

r_name	item.n_name	item.n_nationkey
AMERICA	CANADA	3
AMERICA	BRAZIL	2
AMERICA	ARGENTINA	1
MIDDLE EAST	EGYPT	4
AFRICA	ALGERIA	0

EXISTS Operator

The EXISTS operator tests whether a subquery returns any results. You typically use it to find values from one table that have corresponding values in another table.

The converse, NOT EXISTS, helps to find all the values from one table that do not have any corresponding values in another table.

Syntax:

```
EXISTS (subquery)
NOT EXISTS (subquery)
```

Usage notes:

The subquery can refer to a different table than the outer query block, or the same table. For example, you might use EXISTS or NOT EXISTS to check the existence of parent/child relationships between two columns of the same table.

You can also use operators and function calls within the subquery to test for other kinds of relationships other than strict equality. For example, you might use a call to COUNT() in the subquery to check whether the number of matching values is higher or lower than some limit. You might call a UDF in the subquery to check whether values in one table matches a hashed representation of those same values in a different table.

NULL considerations:

If the subquery returns any value at all (even NULL), EXISTS returns TRUE and NOT EXISTS returns false.

The following example shows how even when the subquery returns only NULL values, EXISTS still returns TRUE and thus matches all the rows from the table in the outer query block.

```
[localhost:21000] > create table all_nulls (x int);
[localhost:21000] > insert into all_nulls values (null), (null), (null);
[localhost:21000] > select y from t2 where exists (select x from all_nulls);
+----+
| y |
+----+
| 2 |
| 4 |
| 6 |
+----+
```

However, if the table in the subquery is empty and so the subquery returns an empty result set, EXISTS returns FALSE:

```
[localhost:21000] > create table empty (x int);
[localhost:21000] > select y from t2 where exists (select x from empty);
[localhost:21000] >
```

Added in: Impala 2.0.0

Restrictions:

Correlated subqueries used in EXISTS and IN operators cannot include a LIMIT clause.

Prior to Impala 2.6, the NOT EXISTS operator required a correlated subquery. In Impala 2.6 and higher, NOT EXISTS works with uncorrelated queries also.

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

The following examples refer to these simple tables containing small sets of integers or strings:

```
[localhost:21000] > create table t1 (x int);
[localhost:21000] > insert into t1 values (1), (2), (3), (4), (5), (6);

[localhost:21000] > create table t2 (y int);
[localhost:21000] > insert into t2 values (2), (4), (6);

[localhost:21000] > create table t3 (z int);
[localhost:21000] > insert into t3 values (1), (3), (5);

[localhost:21000] > create table month_names (m string);
[localhost:21000] > insert into month_names values
> ('January'), ('February'), ('March'),
> ('April'), ('May'), ('June'), ('July'),
> ('August'), ('September'), ('October'),
> ('November'), ('December');
```

The following example shows a correlated subquery that finds all the values in one table that exist in another table. For each value X from T1, the query checks if the Y column of T2 contains an identical value, and the EXISTS operator returns TRUE or FALSE as appropriate in each case.

```
localhost:21000] > select x from t1 where exists (select y from t2 where
t1.x = y);
```



```

+----+
|  x  |
+----+
|  2  |
|  4  |
|  6  |
+----+

```

An uncorrelated query is less interesting in this case. Because the subquery always returns TRUE, all rows from T1 are returned. If the table contents were changed so that the subquery did not match any rows, none of the rows from T1 would be returned.

```

[localhost:21000] > select x from t1 where exists (select y from t2 where y
> 5);
+----+
|  x  |
+----+
|  1  |
|  2  |
|  3  |
|  4  |
|  5  |
|  6  |
+----+

```

The following example shows how an uncorrelated subquery can test for the existence of some condition within a table. By using LIMIT 1 or an aggregate function, the query returns a single result or no result based on whether the subquery matches any rows. Here, we know that T1 and T2 contain some even numbers, but T3 does not.

```

[localhost:21000] > select "contains an even number" from t1 where exists
(select x from t1 where x % 2 = 0) limit 1;
+-----+
| 'contains an even number' |
+-----+
| contains an even number  |
+-----+
[localhost:21000] > select "contains an even number" as assertion from t1
where exists (select x from t1 where x % 2 = 0) limit 1;
+-----+
| assertion                |
+-----+
| contains an even number  |
+-----+
[localhost:21000] > select "contains an even number" as assertion from t2
where exists (select x from t2 where y % 2 = 0) limit 1;
ERROR: AnalysisException: couldn't resolve column reference: 'x'
[localhost:21000] > select "contains an even number" as assertion from t2
where exists (select y from t2 where y % 2 = 0) limit 1;
+-----+
| assertion                |
+-----+
| contains an even number  |
+-----+
[localhost:21000] > select "contains an even number" as assertion from t3
where exists (select z from t3 where z % 2 = 0) limit 1;
[localhost:21000] >

```

The following example finds numbers in one table that are 1 greater than numbers from another table. The EXISTS notation is simpler than an equivalent CROSS JOIN between the tables. (The example then also illustrates how the same test could be performed using an IN operator.)

```
[localhost:21000] > select x from t1 where exists (select y from t2 where x
= y + 1);
+----+
| x |
+----+
| 3 |
| 5 |
+----+
[localhost:21000] > select x from t1 where x in (select y + 1 from t2);
+----+
| x |
+----+
| 3 |
| 5 |
+----+
```

The following example finds values from one table that do not exist in another table.

```
[localhost:21000] > select x from t1 where not exists (select y from t2
where x = y);
+----+
| x |
+----+
| 1 |
| 3 |
| 5 |
+----+
```

The following example uses the NOT EXISTS operator to find all the leaf nodes in tree-structured data. This simplified “tree of life” has multiple levels (class, order, family, and so on), with each item pointing upward through a PARENT pointer. The example runs an outer query and a subquery on the same table, returning only those items whose ID value is *not* referenced by the PARENT of any other item.

```
[localhost:21000] > create table tree (id int, parent int, name string);
[localhost:21000] > insert overwrite tree values
> (0, null, "animals"),
> (1, 0, "placentals"),
> (2, 0, "marsupials"),
> (3, 1, "bats"),
> (4, 1, "cats"),
> (5, 2, "kangaroos"),
> (6, 4, "lions"),
> (7, 4, "tigers"),
> (8, 5, "red kangaroo"),
> (9, 2, "wallabies");
[localhost:21000] > select name as "leaf node" from tree one
> where not exists (select parent from tree two where
one.id = two.parent);
+-----+
| leaf node |
+-----+
| bats      |
| lions     |
| tigers    |
| red kangaroo |
| wallabies |
+-----+
```

Related information:

[Subqueries in Impala SELECT Statements](#) on page 335

ILIKE Operator

A case-insensitive comparison operator for `STRING` data, with basic wildcard capability using `_` to match a single character and `%` to match multiple characters. The argument expression must match the entire string value. Typically, it is more efficient to put any `%` wildcard match at the end of the string.

This operator, available in Impala 2.5 and higher, is the equivalent of the `LIKE` operator, but with case-insensitive comparisons.

Syntax:

```
string_expression ILIKE wildcard_expression
string_expression NOT ILIKE wildcard_expression
```

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP` directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key or value portion of a `MAP`) as part of a join query that refers to the scalar value using the appropriate dot notation or `ITEM`, `KEY`, or `VALUE` pseudocolumn names.

Examples:

In the following examples, strings that are the same except for differences in uppercase and lowercase match successfully with `ILIKE`, but do not match with `LIKE`:

```
select 'fooBar' ilike 'FOOBAR';
+-----+
| 'fooBar' ilike 'FOOBAR' |
+-----+
| true                     |
+-----+

select 'fooBar' like 'FOOBAR';
+-----+
| 'fooBar' like 'FOOBAR'  |
+-----+
| false                   |
+-----+

select 'FOOBAR' ilike 'f%';
+-----+
| 'FOOBAR' ilike 'f%'     |
+-----+
| true                    |
+-----+

select 'FOOBAR' like 'f%';
+-----+
| 'FOOBAR' like 'f%'      |
+-----+
| false                   |
+-----+

select 'ABCXYZ' not ilike 'ab_xyz';
+-----+
| not 'ABCXYZ' ilike 'ab_xyz' |
+-----+
| false                     |
+-----+
```

```

select 'ABCXYZ' not like 'ab_xyz';
+-----+
| not 'abcxyz' like 'ab_xyz' |
+-----+
| true                        |
+-----+

```

Related information:

For case-sensitive comparisons, see [LIKE Operator](#) on page 195. For a more general kind of search operator using regular expressions, see [REGEXP Operator](#) on page 198 or its case-insensitive counterpart [IREGEXP Operator](#) on page 190.

IN Operator

The **IN** operator compares an argument value to a set of values, and returns **TRUE** if the argument matches any value in the set. The **NOT IN** operator reverses the comparison, and checks if the argument value is not part of a set of values.

Syntax:

```

expression IN (expression [, expression])
expression IN (subquery)

expression NOT IN (expression [, expression])
expression NOT IN (subquery)

```

The left-hand expression and the set of comparison values must be of compatible types.

The left-hand expression must consist only of a single value, not a tuple. Although the left-hand expression is typically a column name, it could also be some other value. For example, the **WHERE** clauses **WHERE id IN (5)** and **WHERE 5 IN (id)** produce the same results.

The set of values to check against can be specified as constants, function calls, column names, or other expressions in the query text. The maximum number of expressions in the **IN** list is 9999. (The maximum number of elements of a single expression is 10,000 items, and the **IN** operator itself counts as one.)

In Impala 2.0 and higher, the set of values can also be generated by a subquery. **IN** can evaluate an unlimited number of results using a subquery.

Usage notes:

Any expression using the **IN** operator could be rewritten as a series of equality tests connected with **OR**, but the **IN** syntax is often clearer, more concise, and easier for Impala to optimize. For example, with partitioned tables, queries frequently use **IN** clauses to filter data by comparing the partition key columns to specific values.

NULL considerations:

If there really is a matching non-null value, **IN** returns **TRUE**:

```

[localhost:21000] > select 1 in (1,null,2,3);
+-----+
| 1 in (1, null, 2, 3) |
+-----+
| true                |
+-----+
[localhost:21000] > select 1 not in (1,null,2,3);
+-----+
| 1 not in (1, null, 2, 3) |
+-----+
| false                  |
+-----+

```

If the searched value is not found in the comparison values, and the comparison values include NULL, the result is NULL:

```
[localhost:21000] > select 5 in (1,null,2,3);
+-----+
| 5 in (1, null, 2, 3) |
+-----+
| NULL                |
+-----+
[localhost:21000] > select 5 not in (1,null,2,3);
+-----+
| 5 not in (1, null, 2, 3) |
+-----+
| NULL                    |
+-----+
[localhost:21000] > select 1 in (null);
+-----+
| 1 in (null) |
+-----+
| NULL       |
+-----+
[localhost:21000] > select 1 not in (null);
+-----+
| 1 not in (null) |
+-----+
| NULL           |
+-----+
```

If the left-hand argument is NULL, IN always returns NULL. This rule applies even if the comparison values include NULL.

```
[localhost:21000] > select null in (1,2,3);
+-----+
| null in (1, 2, 3) |
+-----+
| NULL              |
+-----+
[localhost:21000] > select null not in (1,2,3);
+-----+
| null not in (1, 2, 3) |
+-----+
| NULL                  |
+-----+
[localhost:21000] > select null in (null);
+-----+
| null in (null) |
+-----+
| NULL          |
+-----+
[localhost:21000] > select null not in (null);
+-----+
| null not in (null) |
+-----+
| NULL              |
+-----+
```

Added in: Available in earlier Impala releases, but new capabilities were added in Impala 2.0.0

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY,

or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a STRUCT type that is an item within an ARRAY column. Once the scalar numeric value R_NATIONKEY is extracted, it can be used in an arithmetic expression, such as multiplying by 10:

```
-- The SMALLINT is a field within an array of structs.
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
from region, region.r_nations as nation
where nation.item.n_nationkey in (1,3,5)
```

r_name	item.n_name	item.n_nationkey
AMERICA	CANADA	3
AMERICA	ARGENTINA	1
AFRICA	ETHIOPIA	5

Restrictions:

Correlated subqueries used in EXISTS and IN operators cannot include a LIMIT clause.

Examples:

```
-- Using IN is concise and self-documenting.
SELECT * FROM t1 WHERE c1 IN (1,2,10);
-- Equivalent to series of = comparisons ORed together.
SELECT * FROM t1 WHERE c1 = 1 OR c1 = 2 OR c1 = 10;

SELECT c1 AS "starts with vowel" FROM t2 WHERE upper(substr(c1,1,1)) IN
('A','E','I','O','U');
```

```
SELECT COUNT(DISTINCT(visitor_id)) FROM web_traffic WHERE month IN
('January','June','July');
```

Related information:

[Subqueries in Impala SELECT Statements](#) on page 335

IREGEXP Operator

Tests whether a value matches a regular expression, using case-insensitive string comparisons. Uses the POSIX regular expression syntax where ^ and \$ match the beginning and end of the string, . represents any single character,

* represents a sequence of zero or more items, + represents a sequence of one or more items, ? produces a non-greedy match, and so on.

This operator, available in Impala 2.5 and higher, is the equivalent of the REGEXP operator, but with case-insensitive comparisons.

Syntax:

```
string_expression IREGEXP regular_expression
```

Usage notes:

The | symbol is the alternation operator, typically used within () to match different sequences. The () groups do not allow backreferences. To retrieve the part of a value matched within a () section, use the [regexp_extract\(\)](#) built-in function. (Currently, there is not any case-insensitive equivalent for the [regexp_extract\(\)](#) function.)

In Impala 1.3.1 and higher, the REGEXP and RLIKE operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by .*. See [REGEXP Operator](#) on page 198 for examples. Previously, these operators only succeeded when the regular expression matched the entire target string. This change improves compatibility with the regular expression support for popular database systems. There is no change to the behavior of the [regexp_extract\(\)](#) and [regexp_replace\(\)](#) built-in functions.

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including .*? for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0](#) on page 873 for details.

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

The following examples demonstrate the syntax for the IREGEXP operator.

```
select 'abcABCaabbcc' iregexp '^[a-c]+$';
+-----+
| 'abcabcaabbcc' iregexp '[a-c]+' |
+-----+
| true                             |
+-----+
```

Related information:

[REGEXP Operator](#) on page 198

IS DISTINCT FROM Operator

The IS DISTINCT FROM operator, and its converse the IS NOT DISTINCT FROM operator, test whether or not values are identical. IS NOT DISTINCT FROM is similar to the = operator, and IS DISTINCT FROM is similar to the != operator, except that NULL values are treated as identical. Therefore, IS NOT DISTINCT FROM returns true rather than NULL, and IS DISTINCT FROM returns false rather than NULL, when comparing two NULL values. If one of the values being compared is NULL and the other is not, IS DISTINCT FROM returns true and IS NOT DISTINCT FROM returns false, again instead of returning NULL in both cases.

Syntax:

```

expression1 IS DISTINCT FROM expression2

expression1 IS NOT DISTINCT FROM expression2
expression1 <=> expression2

```

The operator `<=>` is an alias for `IS NOT DISTINCT FROM`. It is typically used as a NULL-safe equality operator in join queries. That is, `A <=> B` is true if A equals B or if both A and B are NULL.

Usage notes:

This operator provides concise notation for comparing two values and always producing a true or false result, without treating NULL as a special case. Otherwise, to unambiguously distinguish between two values requires a compound expression involving `IS [NOT] NULL` tests of both operands in addition to the `=` or `!=` operator.

The `<=>` operator, used like an equality operator in a join query, is more efficient than the equivalent clause: `IF (A IS NULL OR B IS NULL, A IS NULL AND B IS NULL, A = B)`. The `<=>` operator can use a hash join, while the `IF` expression cannot.

Examples:

The following examples show how `IS DISTINCT FROM` gives output similar to the `!=` operator, and `IS NOT DISTINCT FROM` gives output similar to the `=` operator. The exception is when the expression involves a NULL value on one side or both sides, where `!=` and `=` return NULL but the `IS [NOT] DISTINCT FROM` operators still return true or false.

```

select 1 is distinct from 0, 1 != 0;
+-----+-----+
| 1 is distinct from 0 | 1 != 0 |
+-----+-----+
| true                | true   |
+-----+-----+

select 1 is distinct from 1, 1 != 1;
+-----+-----+
| 1 is distinct from 1 | 1 != 1 |
+-----+-----+
| false               | false  |
+-----+-----+

select 1 is distinct from null, 1 != null;
+-----+-----+
| 1 is distinct from null | 1 != null |
+-----+-----+
| true                   | NULL     |
+-----+-----+

select null is distinct from null, null != null;
+-----+-----+
| null is distinct from null | null != null |
+-----+-----+
| false                     | NULL       |
+-----+-----+

select 1 is not distinct from 0, 1 = 0;
+-----+-----+
| 1 is not distinct from 0 | 1 = 0 |
+-----+-----+
| false                   | false  |
+-----+-----+

```



```

select 1 is not distinct from 1, 1 = 1;
+-----+-----+
| 1 is not distinct from 1 | 1 = 1 |
+-----+-----+
| true                     | true  |
+-----+-----+

select 1 is not distinct from null, 1 = null;
+-----+-----+
| 1 is not distinct from null | 1 = null |
+-----+-----+
| false                      | NULL    |
+-----+-----+

select null is not distinct from null, null = null;
+-----+-----+
| null is not distinct from null | null = null |
+-----+-----+
| true                          | NULL       |
+-----+-----+

```

The following example shows how `IS DISTINCT FROM` considers `CHAR` values to be the same (not distinct from each other) if they only differ in the number of trailing spaces. Therefore, sometimes the result of an `IS [NOT] DISTINCT FROM` operator differs depending on whether the values are `STRING/VARCHAR` or `CHAR`.

```

select
  'x' is distinct from 'x ' as string_with_trailing_spaces,
  cast('x' as char(5)) is distinct from cast('x ' as char(5)) as
  char_with_trailing_spaces;
+-----+-----+
| string_with_trailing_spaces | char_with_trailing_spaces |
+-----+-----+
| true                      | false                     |
+-----+-----+

```

IS NULL Operator

The `IS NULL` operator, and its converse the `IS NOT NULL` operator, test whether a specified value is [NULL](#). Because using `NULL` with any of the other comparison operators such as `=` or `!=` also returns `NULL` rather than `TRUE` or `FALSE`, you use a special-purpose comparison operator to check for this special condition.

In Impala 2.11 and higher, you can use the operators `IS UNKNOWN` and `IS NOT UNKNOWN` as synonyms for `IS NULL` and `IS NOT NULL`, respectively.

Syntax:

```

expression IS NULL
expression IS NOT NULL

expression IS UNKNOWN
expression IS NOT UNKNOWN

```

Usage notes:

In many cases, `NULL` values indicate some incorrect or incomplete processing during data ingestion or conversion. You might check whether any values in a column are `NULL`, and if so take some followup action to fill them in.

With sparse data, often represented in “wide” tables, it is common for most values to be `NULL` with only an occasional non-`NULL` value. In those cases, you can use the `IS NOT NULL` operator to identify the rows containing any data at all for a particular column, regardless of the actual value.

With a well-designed database schema, effective use of NULL values and IS NULL and IS NOT NULL operators can save having to design custom logic around special values such as 0, -1, 'N/A', empty string, and so on. NULL lets you distinguish between a value that is known to be 0, false, or empty, and a truly unknown value.

Complex type considerations:

The IS [NOT] UNKNOWN operator, as with the IS [NOT] NULL operator, is not applicable to complex type columns (STRUCT, ARRAY, or MAP). Using a complex type column with this operator causes a query error.

Examples:

```
-- If this value is non-zero, something is wrong.
select count(*) from employees where employee_id is null;

-- With data from disparate sources, some fields might be blank.
-- Not necessarily an error condition.
select count(*) from census where household_income is null;

-- Sometimes we expect fields to be null, and followup action
-- is needed when they are not.
select count(*) from web_traffic where weird_http_code is not null;
```

IS TRUE Operator

This variation of the IS operator tests for truth or falsity, with right-hand arguments [NOT] TRUE, [NOT] FALSE, and [NOT] UNKNOWN.

Syntax:

```
expression IS TRUE
expression IS NOT TRUE

expression IS FALSE
expression IS NOT FALSE
```

Usage notes:

This IS TRUE and IS FALSE forms are similar to doing equality comparisons with the Boolean values TRUE and FALSE, except that IS TRUE and IS FALSE always return either TRUE or FALSE, even if the left-hand side expression returns NULL.

These operators let you simplify Boolean comparisons that must also check for NULL, for example `X != 10 AND X IS NOT NULL` is equivalent to `(X != 10) IS TRUE`.

In Impala 2.11 and higher, you can use the operators IS [NOT] TRUE and IS [NOT] FALSE as equivalents for the built-in functions ISTRUE(), ISNOTTRUE(), ISFALSE(), and ISNOTFALSE().

Complex type considerations:

The IS [NOT] TRUE and IS [NOT] FALSE operators are not applicable to complex type columns (STRUCT, ARRAY, or MAP). Using a complex type column with these operators causes a query error.

Added in: Impala 2.11.0

Examples:

```
select assertion, b, b is true, b is false, b is unknown
from boolean_test;
```

assertion	b	istrue(b)	isfalse(b)	b is null
2 + 2 = 4	true	true	false	false

2 + 2 = 5	false	false	true	false
1 = null	NULL	false	false	true
null = null	NULL	false	false	true

LIKE Operator

A comparison operator for STRING data, with basic wildcard capability using the underscore (_) to match a single character and the percent sign (%) to match multiple characters. The argument expression must match the entire string value. Typically, it is more efficient to put any % wildcard match at the end of the string.

Syntax:

```
string_expression LIKE wildcard_expression
string_expression NOT LIKE wildcard_expression
```

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

```
select distinct c_last_name from customer where c_last_name like 'Mc%' or
c_last_name like 'Mac%';
select count(c_last_name) from customer where c_last_name like 'M%';
select c_email_address from customer where c_email_address like '%.edu';

-- We can find 4-letter names beginning with 'M' by calling functions...
select distinct c_last_name from customer where length(c_last_name) = 4 and
substr(c_last_name,1,1) = 'M';
-- ...or in a more readable way by matching M followed by exactly 3
characters.
select distinct c_last_name from customer where c_last_name like 'M___';
```

For case-insensitive comparisons, see [ILIKE Operator](#) on page 187. For a more general kind of search operator using regular expressions, see [REGEXP Operator](#) on page 198 or its case-insensitive counterpart [IREGEXP Operator](#) on page 190.

Logical Operators

Logical operators return a BOOLEAN value, based on a binary or unary logical operation between arguments that are also Booleans. Typically, the argument expressions use [comparison operators](#).

Syntax:

```
boolean_expression binary_logical_operator boolean_expression
unary_logical_operator boolean_expression
```

The Impala logical operators are:

- **AND:** A binary operator that returns `true` if its left-hand and right-hand arguments both evaluate to `true`, `NULL` if either argument is `NULL`, and `false` otherwise.
- **OR:** A binary operator that returns `true` if either of its left-hand and right-hand arguments evaluate to `true`, `NULL` if one argument is `NULL` and the other is either `NULL` or `false`, and `false` otherwise.
- **NOT:** A unary operator that flips the state of a Boolean expression from `true` to `false`, or `false` to `true`. If the argument expression is `NULL`, the result remains `NULL`. (When NOT is used this way as a unary logical operator, it works differently than the `IS NOT NULL` comparison operator, which returns `true` when applied to a `NULL`.)

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a STRUCT type that is an item within an ARRAY column. Once the scalar numeric value R_NATIONKEY is extracted, it can be used in an arithmetic expression, such as multiplying by 10:

```
-- The SMALLINT is a field within an array of structs.
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
  from region, region.r_nations as nation
 where
   nation.item.n_nationkey between 3 and 5
   or nation.item.n_nationkey < 15;
```

r_name	item.n_name	item.n_nationkey
EUROPE	UNITED KINGDOM	23
EUROPE	RUSSIA	22
EUROPE	ROMANIA	19
ASIA	VIETNAM	21
ASIA	CHINA	18
AMERICA	UNITED STATES	24
AMERICA	PERU	17
AMERICA	CANADA	3
MIDDLE EAST	SAUDI ARABIA	20
MIDDLE EAST	EGYPT	4
AFRICA	MOZAMBIQUE	16
AFRICA	ETHIOPIA	5

Examples:

These examples demonstrate the AND operator:

```
[localhost:21000] > select true and true;
+-----+
| true and true |
+-----+
| true          |
+-----+
[localhost:21000] > select true and false;
```

```

+-----+
| true and false |
+-----+
| false          |
+-----+
[localhost:21000] > select false and false;
+-----+
| false and false |
+-----+
| false           |
+-----+
[localhost:21000] > select true and null;
+-----+
| true and null   |
+-----+
| NULL           |
+-----+
[localhost:21000] > select (10 > 2) and (6 != 9);
+-----+
| (10 > 2) and (6 != 9) |
+-----+
| true              |
+-----+

```

These examples demonstrate the OR operator:

```

[localhost:21000] > select true or true;
+-----+
| true or true   |
+-----+
| true           |
+-----+
[localhost:21000] > select true or false;
+-----+
| true or false  |
+-----+
| true           |
+-----+
[localhost:21000] > select false or false;
+-----+
| false or false |
+-----+
| false          |
+-----+
[localhost:21000] > select true or null;
+-----+
| true or null   |
+-----+
| true           |
+-----+
[localhost:21000] > select null or true;
+-----+
| null or true   |
+-----+
| true           |
+-----+
[localhost:21000] > select false or null;
+-----+
| false or null  |
+-----+
| NULL           |
+-----+
[localhost:21000] > select (1 = 1) or ('hello' = 'world');

```

```

+-----+
| (1 = 1) or ('hello' = 'world') |
+-----+
| true                             |
+-----+
[localhost:21000] > select (2 + 2 != 4) or (-1 > 0);
+-----+
| (2 + 2 != 4) or (-1 > 0) |
+-----+
| false                     |
+-----+

```

These examples demonstrate the NOT operator:

```

[localhost:21000] > select not true;
+-----+
| not true |
+-----+
| false    |
+-----+
[localhost:21000] > select not false;
+-----+
| not false |
+-----+
| true      |
+-----+
[localhost:21000] > select not null;
+-----+
| not null |
+-----+
| NULL     |
+-----+
[localhost:21000] > select not (1=1);
+-----+
| not (1 = 1) |
+-----+
| false       |
+-----+

```

REGEXP Operator

Tests whether a value matches a regular expression. Uses the POSIX regular expression syntax where `^` and `$` match the beginning and end of the string, `.` represents any single character, `*` represents a sequence of zero or more items, `+` represents a sequence of one or more items, `?` produces a non-greedy match, and so on.

Syntax:

```
string_expression REGEXP regular_expression
```

Usage notes:

The `RLIKE` operator is a synonym for `REGEXP`.

The `|` symbol is the alternation operator, typically used within `()` to match different sequences. The `()` groups do not allow backreferences. To retrieve the part of a value matched within a `()` section, use the [regexp_extract\(\)](#) built-in function.

In Impala 1.3.1 and higher, the `REGEXP` and `RLIKE` operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by `.``*`. See [REGEXP Operator](#) on page 198 for examples. Previously, these operators only succeeded when the regular expression matched the entire target string. This change improves compatibility with the regular expression

support for popular database systems. There is no change to the behavior of the `regexp_extract()` and `regexp_replace()` built-in functions.

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `.*?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0](#) on page 873 for details.

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

The following examples demonstrate the identical syntax for the REGEXP and RLIKE operators.

```
-- Find all customers whose first name starts with 'J', followed by 0 or
-- more of any character.
select c_first_name, c_last_name from customer where c_first_name regexp
'^J.*';
select c_first_name, c_last_name from customer where c_first_name rlike
'^J.*';

-- Find 'Macdonald', where the first 'a' is optional and the 'D' can be
-- upper- or lowercase.
-- The ^...$ are required, to match the start and end of the value.
select c_first_name, c_last_name from customer where c_last_name regexp
'^Ma?c[Dd]onald$';
select c_first_name, c_last_name from customer where c_last_name rlike '^Ma?
c[Dd]onald$';

-- Match multiple character sequences, either 'Mac' or 'Mc'.
select c_first_name, c_last_name from customer where c_last_name regexp
'^((Mac|Mc)donald$)';
select c_first_name, c_last_name from customer where c_last_name rlike
'^((Mac|Mc)donald$)';

-- Find names starting with 'S', then one or more vowels, then 'r', then any
-- other characters.
-- Matches 'Searcy', 'Sorenson', 'Sauer'.
select c_first_name, c_last_name from customer where c_last_name regexp
'^S[aeiou]+r.*$';
select c_first_name, c_last_name from customer where c_last_name rlike
'^S[aeiou]+r.*$';

-- Find names that end with 2 or more vowels: letters from the set
-- a,e,i,o,u.
select c_first_name, c_last_name from customer where c_last_name regexp
'.*[aeiou]{2,}$';
select c_first_name, c_last_name from customer where c_last_name rlike
'.*[aeiou]{2,}$';

-- You can use letter ranges in the [] blocks, for example to find names
-- starting with A, B, or C.
select c_first_name, c_last_name from customer where c_last_name regexp
'^[A-C].*';
select c_first_name, c_last_name from customer where c_last_name rlike '^[A-
C].*';
```

```
-- If you are not sure about case, leading/trailing spaces, and so on, you
-- can process the
-- column using string functions first.
select c_first_name, c_last_name from customer where
  lower(trim(c_last_name)) regexp '^de.*';
select c_first_name, c_last_name from customer where
  lower(trim(c_last_name)) rlike '^de.*';
```

Related information:

For regular expression matching with case-insensitive comparisons, see [IREGEXP Operator](#) on page 190.

RLIKE Operator

Synonym for the REGEXP operator. See [REGEXP Operator](#) on page 198 for details.

Examples:

The following examples demonstrate the identical syntax for the REGEXP and RLIKE operators.

```
-- Find all customers whose first name starts with 'J', followed by 0 or
-- more of any character.
select c_first_name, c_last_name from customer where c_first_name regexp
  '^J.*';
select c_first_name, c_last_name from customer where c_first_name rlike
  '^J.*';

-- Find 'Macdonald', where the first 'a' is optional and the 'D' can be
-- upper- or lowercase.
-- The ^...$ are required, to match the start and end of the value.
select c_first_name, c_last_name from customer where c_last_name regexp
  '^Ma?c[Dd]onald$';
select c_first_name, c_last_name from customer where c_last_name rlike '^Ma?
c[Dd]onald$';

-- Match multiple character sequences, either 'Mac' or 'Mc'.
select c_first_name, c_last_name from customer where c_last_name regexp
  '^(Mac|Mc)donald$';
select c_first_name, c_last_name from customer where c_last_name rlike
  '^(Mac|Mc)donald$';

-- Find names starting with 'S', then one or more vowels, then 'r', then any
-- other characters.
-- Matches 'Searcy', 'Sorenson', 'Sauer'.
select c_first_name, c_last_name from customer where c_last_name regexp
  '^S[aeiou]+r.*$';
select c_first_name, c_last_name from customer where c_last_name rlike
  '^S[aeiou]+r.*$';

-- Find names that end with 2 or more vowels: letters from the set
-- a,e,i,o,u.
select c_first_name, c_last_name from customer where c_last_name regexp
  '.*[aeiou]{2,}$';
select c_first_name, c_last_name from customer where c_last_name rlike
  '.*[aeiou]{2,}$';

-- You can use letter ranges in the [] blocks, for example to find names
-- starting with A, B, or C.
select c_first_name, c_last_name from customer where c_last_name regexp
  '^[A-C].*';
select c_first_name, c_last_name from customer where c_last_name rlike '^[A-
C].*';
```



```
-- If you are not sure about case, leading/trailing spaces, and so on, you
-- can process the
-- column using string functions first.
select c_first_name, c_last_name from customer where
  lower(trim(c_last_name)) regexp '^de.*';
select c_first_name, c_last_name from customer where
  lower(trim(c_last_name)) rlike '^de.*';
```

Impala Schema Objects and Object Names

With Impala, you work with schema objects that are familiar to database users: primarily databases, tables, views, and functions. The SQL syntax to work with these objects is explained in [Impala SQL Statements](#) on page 213. This section explains the conceptual knowledge you need to work with these objects and the various ways to specify their names.

Within a table, partitions can also be considered a kind of object. Partitioning is an important subject for Impala, with its own documentation section covering use cases and performance considerations. See [Partitioning for Impala Tables](#) on page 685 for details.

Impala does not have a counterpart of the “tablespace” notion from some database systems. By default, all the data files for a database, table, or partition are located within nested folders within the HDFS file system. You can also specify a particular HDFS location for a given Impala table or partition. The raw data for these objects is represented as a collection of data files, providing the flexibility to load data by simply moving files into the expected HDFS location.

Information about the schema objects is held in the [metastore](#) database. This database is shared between Impala and Hive, allowing each to create, drop, and query each other's databases, tables, and so on. When Impala makes a change to schema objects through a CREATE, ALTER, DROP, INSERT, or LOAD DATA statement, it broadcasts those changes to all nodes in the cluster through the [catalog service](#). When you make such changes through Hive or directly through manipulating HDFS files, you use the [REFRESH](#) or [INVALIDATE METADATA](#) statements on the Impala side to recognize the newly loaded data, new tables, and so on.

Overview of Impala Aliases

When you write the names of tables, columns, or column expressions in a query, you can assign an alias at the same time. Then you can specify the alias rather than the original name when making other references to the table or column in the same statement. You typically specify aliases that are shorter, easier to remember, or both than the original names. The aliases are printed in the query header, making them useful for self-documenting output.

To set up an alias, add the AS *alias* clause immediately after any table, column, or expression name in the SELECT list or FROM list of a query. The AS keyword is optional; you can also specify the alias immediately after the original name.

```
-- Make the column headers of the result set easier to understand.
SELECT c1 AS name, c2 AS address, c3 AS phone FROM table_with_terse_columns;
SELECT SUM(ss_xyz_dollars_net) AS total_sales FROM
  table_with_cryptic_columns;
-- The alias can be a quoted string for extra readability.
SELECT c1 AS "Employee ID", c2 AS "Date of hire" FROM t1;
-- The AS keyword is optional.
SELECT c1 "Employee ID", c2 "Date of hire" FROM t1;

-- The table aliases assigned in the FROM clause can be used both earlier
-- in the query (the SELECT list) and later (the WHERE clause).
SELECT one.name, two.address, three.phone
  FROM census one, building_directory two, phonebook three
 WHERE one.id = two.id and two.id = three.id;
```

```
-- The aliases c1 and c2 let the query handle columns with the same names
-- from 2 joined tables.
-- The aliases t1 and t2 let the query abbreviate references to long or
-- cryptically named tables.
SELECT t1.column_n AS c1, t2.column_n AS c2 FROM long_name_table AS t1,
       very_long_name_table2 AS t2
       WHERE c1 = c2;
SELECT t1.column_n c1, t2.column_n c2 FROM table1 t1, table2 t2
       WHERE c1 = c2;
```

From Impala 3.0, the alias substitution logic has changed.

You can specify column aliases with or without the AS keyword, and with no quotation marks, single quotation marks, or double quotation marks. Some kind of quotation marks are required if the column alias contains any spaces or other problematic characters. The alias text is displayed in the `impala-shell` output as all-lowercase. For example:

```
[localhost:21000] > select c1 First_Column from t;
[localhost:21000] > select c1 as First_Column from t;
+-----+
| first_column |
+-----+
...

[localhost:21000] > select c1 'First Column' from t;
[localhost:21000] > select c1 as 'First Column' from t;
+-----+
| first column |
+-----+
...

[localhost:21000] > select c1 "First Column" from t;
[localhost:21000] > select c1 as "First Column" from t;
+-----+
| first column |
+-----+
...
```

From Impala 3.0, the alias substitution logic in the `GROUP BY`, `HAVING`, and `ORDER BY` clauses has become more consistent with standard SQL behavior, as follows. Aliases are now only legal at the top level, and not in subexpressions. The following statements are allowed:

```
SELECT int_col / 2 AS x
FROM t
GROUP BY x;

SELECT int_col / 2 AS x
FROM t
ORDER BY x;

SELECT NOT bool_col AS nb
FROM t
GROUP BY nb
HAVING nb;
```

And the following statements are NOT allowed:

```
SELECT int_col / 2 AS x
FROM t
GROUP BY x / 2;
```

```

SELECT int_col / 2 AS x
FROM t
ORDER BY -x;

SELECT int_col / 2 AS x
FROM t
GROUP BY x
HAVING x > 3;

```

To use an alias name that matches one of the Impala reserved keywords (listed in [Impala Reserved Words](#) on page 821), surround the identifier with either single or double quotation marks, or `` characters (backticks).

Aliases follow the same rules as identifiers when it comes to case insensitivity. Aliases can be longer than identifiers (up to the maximum length of a Java string) and can include additional characters such as spaces and dashes when they are quoted using backtick characters.

Complex type considerations:

Queries involving the complex types (ARRAY, STRUCT, and MAP), typically make extensive use of table aliases. These queries involve join clauses where the complex type column is treated as a joined table. To construct two-part or three-part qualified names for the complex column elements in the FROM list, sometimes it is syntactically required to construct a table alias for the complex column where it is referenced in the join clause. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details and examples.

Alternatives:

Another way to define different names for the same tables or columns is to create views. See [Overview of Impala Views](#) on page 209 for details.

Overview of Impala Databases

In Impala, a database is a logical container for a group of tables. Each database defines a separate namespace. Within a database, you can refer to the tables inside it using their unqualified names. Different databases can contain tables with identical names.

Creating a database is a lightweight operation. There are minimal database-specific properties to configure, such as LOCATION and COMMENT.

You can change the owner of a database with the ALTER DATABASE statement.

Typically, you create a separate database for each project or application, to avoid naming conflicts between tables and to make clear which tables are related to each other. The USE statement lets you switch between databases. Unqualified references to tables, views, and functions refer to objects within the current database. You can also refer to objects in other databases by using qualified names of the form *dbname.object_name*.

Each database is physically represented by a directory in HDFS. When you do not specify a LOCATION attribute, the directory is located in the Impala data directory with the associated tables managed by Impala. When you do specify a LOCATION attribute, any read and write operations for tables in that database are relative to the specified HDFS directory.

There is a special database, named default, where you begin when you connect to Impala. Tables created in default are physically located one level higher in HDFS than all the user-created databases.

Impala includes another predefined database, _impala_builtins, that serves as the location for the [built-in functions](#). To see the built-in functions, use a statement like the following:

```

show functions in _impala_builtins;
show functions in _impala_builtins like '*substring*';

```

Related statements:

[CREATE DATABASE Statement](#) on page 240, [DROP DATABASE Statement](#) on page 280, [USE Statement](#) on page 421, [SHOW DATABASES](#) on page 401

Overview of Impala Functions

Functions let you apply arithmetic, string, or other computations and transformations to Impala data. You typically use them in `SELECT` lists and `WHERE` clauses to filter and format query results so that the result set is exactly what you want, with no further processing needed on the application side.

Scalar functions return a single result for each input row. See [Impala Built-In Functions](#) on page 428.

```
[localhost:21000] > select name, population from country where continent =
'North America' order by population desc limit 4;
[localhost:21000] > select upper(name), population from country where
continent = 'North America' order by population desc limit 4;
```

upper(name)	population
USA	320000000
MEXICO	122000000
CANADA	25000000
GUATEMALA	16000000

Aggregate functions combine the results from multiple rows: either a single result for the entire table, or a separate result for each group of rows. Aggregate functions are frequently used in combination with `GROUP BY` and `HAVING` clauses in the `SELECT` statement. See [Impala Aggregate Functions](#) on page 539.

```
[localhost:21000] > select continent, sum(population) as howmany from
country group by continent order by howmany desc;
```

continent	howmany
Asia	4298723000
Africa	1110635000
Europe	742452000
North America	565265000
South America	406740000
Oceania	38304000

User-defined functions (UDFs) let you code your own logic. They can be either scalar or aggregate functions. UDFs let you implement important business or scientific logic using high-performance code for Impala to automatically parallelize. You can also use UDFs to implement convenience functions to simplify reporting or porting SQL from other database systems. See [User-Defined Functions \(UDFs\)](#) on page 588.

```
[localhost:21000] > select rot13('Hello world!') as 'Weak obfuscation';
```

weak obfuscation
Uryyb jbeyq!

```
[localhost:21000] > select likelihood_of_new_subatomic_particle(sensor1,
sensor2, sensor3) as probability
> from experimental_results group by experiment;
```

Each function is associated with a specific database. For example, if you issue a `USE somedb` statement followed by `CREATE FUNCTION somefunc`, the new function is created in the `somedb` database, and you could refer to it through the fully qualified name `somedb.somefunc`. You could then issue another `USE` statement and create a function with the same name in a different database.

Impala built-in functions are associated with a special database named `_impala_builtins`, which lets you refer to them from any database without qualifying the name.

```
[localhost:21000] > show databases;
+-----+
| name |
+-----+
| _impala_builtins |
| analytic_functions |
| avro_testing |
| data_file_size |
+-----+
...
[localhost:21000] > show functions in _impala_builtins like '*subs*';
+-----+-----+
| return type | signature |
+-----+-----+
| STRING      | substr(STRING, BIGINT) |
| STRING      | substr(STRING, BIGINT, BIGINT) |
| STRING      | substring(STRING, BIGINT) |
| STRING      | substring(STRING, BIGINT, BIGINT) |
+-----+-----+
```

Related statements: [CREATE FUNCTION Statement](#) on page 242, [DROP FUNCTION Statement](#) on page 282

Overview of Impala Identifiers

Identifiers are the names of databases, tables, or columns that you specify in a SQL statement. The rules for identifiers govern what names you can give to things you create, the notation for referring to names containing unusual characters, and other aspects such as case sensitivity.

- The minimum length of an identifier is 1 character.
- The maximum length of an identifier is currently 128 characters except for column names which can contain 767 characters, enforced by the metastore database.
- An identifier must start with an alphanumeric or underscore character except for column names which can start with any unicode characters. Quoting the identifier with backticks has no effect on the allowed characters in the name.
- An identifier can contain only ASCII characters except for column names which can contain unicode characters.
- To use an identifier name that matches one of the Impala reserved keywords (listed in [Impala Reserved Words](#) on page 821), surround the identifier with `` characters (backticks). Quote the reserved word even if it is part of a fully qualified name. The following example shows how a reserved word can be used as a column name if it is quoted with backticks in the CREATE TABLE statement, and how the column name must also be quoted with backticks in a query:

```
[localhost:21000] > create table reserved (`data` string);

[localhost:21000] > select data from reserved;
ERROR: AnalysisException: Syntax error in line 1:
select data from reserved
      ^
Encountered: DATA
Expected: ALL, CASE, CAST, DISTINCT, EXISTS, FALSE, IF, INTERVAL, NOT,
NULL, STRAIGHT_JOIN, TRUE, IDENTIFIER
CAUSED BY: Exception: Syntax error

[localhost:21000] > select reserved.data from reserved;
ERROR: AnalysisException: Syntax error in line 1:
select reserved.data from reserved
              ^
Encountered: DATA
Expected: IDENTIFIER
CAUSED BY: Exception: Syntax error
```

```
[localhost:21000] > select reserved.`data` from reserved;

[localhost:21000] >
```

Important: Because the list of reserved words grows over time as new SQL syntax is added, consider adopting coding conventions (especially for any automated scripts or in packaged applications) to always quote all identifiers with backticks. Quoting all identifiers protects your SQL from compatibility issues if new reserved words are added in later releases.

- Impala identifiers are always case-insensitive. That is, tables named `t1` and `T1` always refer to the same table, regardless of quote characters. Internally, Impala always folds all specified table and column names to lowercase. This is why the column headers in query output are always displayed in lowercase.

See [Overview of Impala Aliases](#) on page 201 for how to define shorter or easier-to-remember aliases if the original names are long or cryptic identifiers. Aliases follow the same rules as identifiers when it comes to case insensitivity. Aliases can be longer than identifiers (up to the maximum length of a Java string) and can include additional characters such as spaces and dashes when they are quoted using backtick characters.

Another way to define different names for the same tables or columns is to create views. See [Overview of Impala Views](#) on page 209 for details.

Overview of Impala Tables

Tables are the primary containers for data in Impala. They have the familiar row and column layout similar to other database systems, plus some features such as partitioning often associated with higher-end data warehouse systems.

Logically, each table has a structure based on the definition of its columns, partitions, and other properties.

Physically, each table that uses HDFS storage is associated with a directory in HDFS. The table data consists of all the data files underneath that directory:

- [Internal tables](#) are managed by Impala, and use directories inside the designated Impala work area.
- [External tables](#) use arbitrary HDFS directories, where the data files are typically shared between different Hadoop components.
- Large-scale data is usually handled by partitioned tables, where the data files are divided among different HDFS subdirectories.

Impala tables can also represent data that is stored in HBase, in the Amazon S3 filesystem (Impala 2.2 or higher), on Isilon storage devices (Impala 2.2.3 or higher), or in Apache Ozone (Impala 4.2 or higher). See [Using Impala to Query HBase Tables](#) on page 750, [Using Impala with Amazon S3 Object Store](#) on page 769, [Using Impala with Isilon Storage](#) on page 783, and [Using Impala with Apache Ozone Storage](#) on page 783 for details about those special kinds of tables.

Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.

Related statements: [CREATE TABLE Statement](#) on page 248, [DROP TABLE Statement](#) on page 289, [ALTER TABLE Statement](#) on page 215, [INSERT Statement](#) on page 298, [LOAD DATA Statement](#) on page 309, [SELECT Statement](#) on page 316

Internal Tables

The default kind of table produced by the `CREATE TABLE` statement is known as an internal table. (Its counterpart is the external table, produced by the `CREATE EXTERNAL TABLE` syntax.)

- Impala creates a directory in HDFS to hold the data files.
- You can create data in internal tables by issuing `INSERT` or `LOAD DATA` statements.
- If you add or replace data using HDFS operations, issue the `REFRESH` command in `impala-shell` so that Impala recognizes the changes in data files, block locations, and so on.

- When you issue a `DROP TABLE` statement, Impala physically removes all the data files from the directory.
- To see whether a table is internal or external, and its associated HDFS location, issue the statement `DESCRIBE FORMATTED table_name`. The `Table Type` field displays `MANAGED_TABLE` for internal tables and `EXTERNAL_TABLE` for external tables. The `Location` field displays the path of the table directory as an HDFS URI.
- When you issue an `ALTER TABLE` statement to rename an internal table, all data files are moved into the new HDFS directory for the table. The files are moved even if they were formerly in a directory outside the Impala data directory, for example in an internal table with a `LOCATION` attribute pointing to an outside HDFS directory.

Examples:

You can switch a table from internal to external, or from external to internal, by using the `ALTER TABLE` statement:

```
-- Switch a table from internal to external.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');

-- Switch a table from external to internal.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='FALSE');
```

If the Kudu service is integrated with the Hive Metastore, the above operations are not supported.

Related information:

[External Tables](#) on page 207, [CREATE TABLE Statement](#) on page 248, [DROP TABLE Statement](#) on page 289, [ALTER TABLE Statement](#) on page 215, [DESCRIBE Statement](#) on page 268

External Tables

The syntax `CREATE EXTERNAL TABLE` sets up an Impala table that points at existing data files, potentially in HDFS locations outside the normal Impala data directories.. This operation saves the expense of importing the data into a new table when you already have the data files in a known location in HDFS, in the desired file format.

- You can use Impala to query the data in this table.
- You can create data in external tables by issuing `INSERT` or `LOAD DATA` statements.
- If you add or replace data using HDFS operations, issue the `REFRESH` command in `impala-shell` so that Impala recognizes the changes in data files, block locations, and so on.
- When you issue a `DROP TABLE` statement in Impala, that removes the connection that Impala has with the associated data files, but does not physically remove the underlying data. You can continue to use the data files with other Hadoop components and HDFS operations.
- To see whether a table is internal or external, and its associated HDFS location, issue the statement `DESCRIBE FORMATTED table_name`. The `Table Type` field displays `MANAGED_TABLE` for internal tables and `EXTERNAL_TABLE` for external tables. The `Location` field displays the path of the table directory as an HDFS URI.
- When you issue an `ALTER TABLE` statement to rename an external table, all data files are left in their original locations.
- You can point multiple external tables at the same HDFS directory by using the same `LOCATION` attribute for each one. The tables could have different column definitions, as long as the number and types of columns are compatible with the schema evolution considerations for the underlying file type. For example, for text data files, one table might define a certain column as a `STRING` while another defines the same column as a `BIGINT`.

Examples:

You can switch a table from internal to external, or from external to internal, by using the `ALTER TABLE` statement:

```
-- Switch a table from internal to external.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');

-- Switch a table from external to internal.
```

```
ALTER TABLE table_name SET TBLPROPERTIES( 'EXTERNAL' = 'FALSE' );
```

If the Kudu service is integrated with the Hive Metastore, the above operations are not supported.

Related information:

[Internal Tables](#) on page 206, [CREATE TABLE Statement](#) on page 248, [DROP TABLE Statement](#) on page 289, [ALTER TABLE Statement](#) on page 215, [DESCRIBE Statement](#) on page 268

File Formats

Each table has an associated file format, which determines how Impala interprets the associated data files. See [How Impala Works with Hadoop File Formats](#) on page 695 for details.

You set the file format during the `CREATE TABLE` statement, or change it later using the `ALTER TABLE` statement. Partitioned tables can have a different file format for individual partitions, allowing you to change the file format used in your ETL process for new data without going back and reconverting all the existing data in the same table.

Any `INSERT` statements produce new data files with the current file format of the table. For existing data files, changing the file format of the table does not automatically do any data conversion. You must use `TRUNCATE TABLE` or `INSERT OVERWRITE` to remove any previous data files that use the old file format. Then you use the `LOAD DATA` statement, `INSERT ... SELECT`, or other mechanism to put data files of the correct format into the table.

The default file format, text, is the most flexible and easy to produce when you are just getting started with Impala. The Parquet file format offers the highest query performance and uses compression to reduce storage requirements; therefore, where practical, use Parquet for Impala tables with substantial amounts of data. Also, the complex types (ARRAY, STRUCT, and MAP) available in Impala 2.3 and higher are currently only supported with the Parquet file type. Based on your existing ETL workflow, you might use other file formats such as Avro, possibly doing a final conversion step to Parquet to take advantage of its performance for analytic queries.

Kudu Tables

By default, tables stored in Apache Kudu are treated specially, because Kudu manages its data independently of HDFS files.

All metadata that Impala needs is stored in the HMS.

When Kudu is not integrated with the HMS, when you create a Kudu table through Impala, the table is assigned an internal Kudu table name of the form `impala::db_name.table_name`. You can see the Kudu-assigned name in the output of `DESCRIBE FORMATTED`, in the `kudu.table_name` field of the table properties.

For Impala-Kudu managed tables, `ALTER TABLE ... RENAME` renames both the Impala and the Kudu table.

For Impala-Kudu external tables, `ALTER TABLE ... RENAME` renames just the Impala table. To change the Kudu table that an Impala external table points to, use `ALTER TABLE impala_name SET TBLPROPERTIES('kudu.table_name' = 'different_kudu_table_name')`. The underlying Kudu table must already exist.

In practice, external tables are typically used to access underlying Kudu tables that were created outside of Impala, that is, through the Kudu API.

The `SHOW TABLE STATS` output for a Kudu table shows Kudu-specific details about the layout of the table. Instead of information about the number and sizes of files, the information is divided by the Kudu tablets. For each tablet, the output includes the fields # Rows (although this number is not currently computed), Start Key, Stop Key, Leader Replica, and # Replicas. The output of `SHOW COLUMN STATS`, illustrating the distribution of values within each column, is the same for Kudu tables as for HDFS-backed tables.

If the Kudu service is not integrated with the Hive Metastore, the distinction between internal and external tables has some special details for Kudu tables. Tables created entirely through Impala are internal tables. The table name as represented within Kudu includes notation such as an `impala::` prefix and the Impala database name. External Kudu tables are those created by a non-Impala mechanism, such as a user application calling the Kudu APIs. For

these tables, the `CREATE EXTERNAL TABLE` syntax lets you establish a mapping from Impala to the existing Kudu table:

```
CREATE EXTERNAL TABLE impala_name STORED AS KUDU
  TBLPROPERTIES('kudu.table_name' = 'original_kudu_name');
```

External Kudu tables differ in one important way from other external tables: adding or dropping a column or range partition changes the data in the underlying Kudu table, in contrast to an HDFS-backed external table where existing data files are left untouched.

Overview of Impala Views

Views are lightweight logical constructs that act as aliases for queries. You can specify a view name in a query (a `SELECT` statement or the `SELECT` portion of an `INSERT` statement) where you would usually specify a table name.

A view lets you:

- Issue complicated queries with compact and simple syntax:

```
-- Take a complicated reporting query, plug it into a CREATE VIEW
  statement...
create view v1 as select c1, c2, avg(c3) from t1 group by c3 order by c1
  desc limit 10;
-- ... and now you can produce the report with 1 line of code.
select * from v1;
```

- Reduce maintenance, by avoiding the duplication of complicated queries across multiple applications in multiple languages:

```
create view v2 as select t1.c1, t1.c2, t2.c3 from t1 join t2 on (t1.id =
  t2.id);
-- This simple query is safer to embed in reporting applications than the
  longer query above.
-- The view definition can remain stable even if the structure of the
  underlying tables changes.
select c1, c2, c3 from v2;
```

- Build a new, more refined query on top of the original query by adding new clauses, select-list expressions, function calls, and so on:

```
create view average_price_by_category as select category, avg(price) as
  avg_price from products group by category;
create view expensive_categories as select category, avg_price from
  average_price_by_category order by avg_price desc limit 10000;
create view top_10_expensive_categories as select category, avg_price from
  expensive_categories limit 10;
```

This technique lets you build up several more or less granular variations of the same query, and switch between them when appropriate.

- Set up aliases with intuitive names for tables, columns, result sets from joins, and so on:

```
-- The original tables might have cryptic names inherited from a legacy
  system.
create view action_items as select rrptsk as assignee, treq as due_date,
  dmisc as notes from vxy_t1_br;
-- You can leave original names for compatibility, build new applications
  using more intuitive ones.
select assignee, due_date, notes from action_items;
```

- Swap tables with others that use different file formats, partitioning schemes, and so on without any downtime for data copying or conversion:

```
create table slow (x int, s string) stored as textfile;
create view report as select s from slow where x between 20 and 30;
-- Query is kind of slow due to inefficient table definition, but it
  works.
select * from report;

create table fast (s string) partitioned by (x int) stored as parquet;
-- ...Copy data from SLOW to FAST. Queries against REPORT view continue to
  work...

-- After changing the view definition, queries will be faster due to
  partitioning,
-- binary format, and compression in the new table.
alter view report as select s from fast where x between 20 and 30;
select * from report;
```

- Avoid coding lengthy subqueries and repeating the same subquery text in many other queries.
- Set up fine-grained security where a user can query some columns from a table but not other columns. Because Impala 2.3 and higher support column-level authorization, this technique is no longer required. If you formerly implemented column-level security through views, see the documentation for Apache Sentry for details about the column-level authorization feature.

The SQL statements that configure views are [CREATE VIEW Statement](#) on page 265, [ALTER VIEW Statement](#) on page 230, and [DROP VIEW Statement](#) on page 290. You can specify view names when querying data ([SELECT Statement](#) on page 316) and copying data from one table to another ([INSERT Statement](#) on page 298). The [WITH](#) clause creates an inline view, that only exists for the duration of a single query.

```
[localhost:21000] > create view trivial as select * from customer;
[localhost:21000] > create view some_columns as select c_first_name,
  c_last_name, c_login from customer;
[localhost:21000] > select * from some_columns limit 5;
Query finished, fetching results ...
```

c_first_name	c_last_name	c_login
Javier	Lewis	
Amy	Moses	
Latisha	Hamilton	
Michael	White	
Robert	Moran	

```
[localhost:21000] > create view ordered_results as select * from
  some_columns order by c_last_name desc, c_first_name desc limit 1000;
[localhost:21000] > select * from ordered_results limit 5;
Query: select * from ordered_results limit 5
Query finished, fetching results ...
```

c_first_name	c_last_name	c_login
Thomas	Zuniga	
Sarah	Zuniga	
Norma	Zuniga	
Lloyd	Zuniga	
Lisa	Zuniga	

```
Returned 5 row(s) in 0.48s
```

The previous example uses descending order for `ORDERED_RESULTS` because in the sample TPCD-H data, there are some rows with empty strings for both `C_FIRST_NAME` and `C_LAST_NAME`, making the lowest-ordered names unuseful in a sample query.

```
create view visitors_by_day as select day, count(distinct visitors) as
  howmany from web_traffic group by day;
create view top_10_days as select day, howmany from visitors_by_day order by
  howmany limit 10;
select * from top_10_days;
```

Usage notes:

To see the definition of a view, issue a `DESCRIBE FORMATTED` statement, which shows the query from the original `CREATE VIEW` statement:

```
[localhost:21000] > create view v1 as select * from t1;
[localhost:21000] > describe formatted v1;
Query finished, fetching results ...
```

name	type	comment
# col_name	data_type	comment
x	int	None
y	int	None
s	string	None
# Detailed Table Information	NULL	NULL
Database:	views	NULL
Owner:	doc_demo	NULL
CreateTime:	Mon Jul 08 15:56:27 EDT 2013	NULL
LastAccessTime:	UNKNOWN	NULL
Protect Mode:	None	NULL
Retention:	0	NULL
Table Type:	VIRTUAL_VIEW	NULL
Table Parameters:	NULL	NULL
	transient_lastDdlTime	1373313387
	NULL	NULL
# Storage Information	NULL	NULL
SerDe Library:	null	NULL
InputFormat:	null	NULL
OutputFormat:	null	NULL
Compressed:	No	NULL
Num Buckets:	0	NULL
Bucket Columns:	[]	NULL
Sort Columns:	[]	NULL
	NULL	NULL
# View Information	NULL	NULL
View Original Text:	SELECT * FROM t1	NULL
View Expanded Text:	SELECT * FROM t1	NULL

Prior to Impala 1.4.0, it was not possible to use the `CREATE TABLE LIKE view_name` syntax. In Impala 1.4.0 and higher, you can create a table with the same column definitions as a view using the `CREATE TABLE LIKE` technique. Although `CREATE TABLE LIKE` normally inherits the file format of the original table, a view has no underlying file format, so `CREATE TABLE LIKE view_name` produces a text table by default. To specify a different file format, include a `STORED AS file_format` clause at the end of the `CREATE TABLE LIKE` statement.

Complex type considerations:

For tables containing complex type columns (ARRAY, STRUCT, or MAP), you typically use join queries to refer to the complex values. You can use views to hide the join notation, making such tables seem like traditional denormalized tables, and making those tables queryable by business intelligence tools that do not have built-in support for those complex types. See [Accessing Complex Type Data in Flattened Form Using Views](#) on page 163 for details.

The `STRAIGHT_JOIN` hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or `WHERE`-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

Restrictions:

- You cannot insert into an Impala view. (In some database systems, this operation is allowed and inserts rows into the base table.) You can use a view name on the right-hand side of an `INSERT` statement, in the `SELECT` part.
- If a view applies to a partitioned table, any partition pruning considers the clauses on both the original query and any additional `WHERE` predicates in the query that refers to the view. Prior to Impala 1.4, only the `WHERE` clauses on the original query from the `CREATE VIEW` statement were used for partition pruning.
- An `ORDER BY` clause without an additional `LIMIT` clause is ignored in any view definition. If you need to sort the entire result set from a view, use an `ORDER BY` clause in the `SELECT` statement that queries the view. You can still make a simple “top 10” report by combining the `ORDER BY` and `LIMIT` clauses in the same view definition:

```
[localhost:21000] > create table unsorted (x bigint);
[localhost:21000] > insert into unsorted values (1), (9), (3), (7), (5),
(8), (4), (6), (2);
[localhost:21000] > create view sorted_view as select x from unsorted
order by x;
[localhost:21000] > select x from sorted_view; -- ORDER BY clause in view
has no effect.
```

x
1
9
3
7
5
8
4
6
2

```
[localhost:21000] > select x from sorted_view order by x; -- View query
requires ORDER BY at outermost level.
```

x
1
2
3
4
5
6
7
8
9

```
[localhost:21000] > create view top_3_view as select x from unsorted order
by x limit 3;
[localhost:21000] > select x from top_3_view; -- ORDER BY and LIMIT
together in view definition are preserved.
```

x
1
2
3

```
+---+
| 1 |
| 2 |
| 3 |
+---+
```

- The TABLESAMPLE clause of the SELECT statement does not apply to a table reference derived from a view, a subquery, or anything other than a real base table. This clause only works for tables backed by HDFS or HDFS-like data files, therefore it does not apply to Kudu or HBase tables.

Related statements: [CREATE VIEW Statement](#) on page 265, [ALTER VIEW Statement](#) on page 230, [DROP VIEW Statement](#) on page 290

Impala Transactions

A transaction is a single logical operation on the data. Impala supports transactions that satisfy a level of consistency that improves the integrity and reliability of the data before and after a transaction.

Specifically, Impala provides atomicity and isolation of insert operations on transactional tables. A single table insert is either committed in full or not committed, and the results of the insert operation are not visible to other query operations until the operation is committed.

For single table, the inserts are ordered, so if Impala doesn't see a committed insert, it won't see any insert committed after it.

For insert-only transactional tables, you can perform the following statements: CREATE TABLE, DROP TABLE, TRUNCATE, INSERT, SELECT

All transactions in Impala automatically commit at the end of the statement. Currently, Impala does not support multi-statement transactions.

Insert-only tables must be the managed and file-format based tables, such as Parquet, Avro, and text.

Note: Impala does not support changing transactional properties of tables. For example, you cannot alter a transactional table to a non-transactional table.

Impala SQL Statements

The Impala SQL dialect supports a range of standard elements, plus some extensions for Big Data use cases related to data loading and data warehousing.

Note:

In the `impala-shell` interpreter, a semicolon at the end of each statement is required. Since the semicolon is not actually part of the SQL syntax, we do not include it in the syntax definition of each statement, but we do show it in examples intended to be run in `impala-shell`.

DDL Statements

DDL refers to “Data Definition Language”, a subset of SQL statements that change the structure of the database schema in some way, typically by creating, deleting, or modifying schema objects such as databases, tables, and views. Most Impala DDL statements start with the keywords CREATE, DROP, or ALTER.

The Impala DDL statements are:

- [ALTER TABLE Statement](#) on page 215
- [ALTER VIEW Statement](#) on page 230
- [COMPUTE STATS Statement](#) on page 232
- [CREATE DATABASE Statement](#) on page 240
- [CREATE FUNCTION Statement](#) on page 242

- [CREATE ROLE Statement \(Impala 2.0 or higher only\)](#) on page 248
- [CREATE TABLE Statement](#) on page 248
- [CREATE VIEW Statement](#) on page 265
- [DROP DATABASE Statement](#) on page 280
- [DROP FUNCTION Statement](#) on page 282
- [DROP ROLE Statement \(Impala 2.0 or higher only\)](#) on page 284
- [DROP TABLE Statement](#) on page 289
- [DROP VIEW Statement](#) on page 290
- [GRANT Statement \(Impala 2.0 or higher only\)](#) on page 294
- [REVOKE Statement \(Impala 2.0 or higher only\)](#) on page 315

After Impala executes a DDL command, information about available tables, columns, views, partitions, and so on is automatically synchronized between all the Impala nodes in a cluster. (Prior to Impala 1.2, you had to issue a `REFRESH` or `INVALIDATE METADATA` statement manually on the other nodes to make them aware of the changes.)

If the timing of metadata updates is significant, for example if you use round-robin scheduling where each query could be issued through a different Impala node, you can enable the [SYNC_DDL](#) query option to make the DDL statement wait until all nodes have been notified about the metadata changes.

See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about how Impala DDL statements interact with tables and partitions stored in the Amazon S3 filesystem.

Although the `INSERT` statement is officially classified as a DML (data manipulation language) statement, it also involves metadata changes that must be broadcast to all Impala nodes, and so is also affected by the `SYNC_DDL` query option.

Because the `SYNC_DDL` query option makes each DDL operation take longer than normal, you might only enable it before the last DDL operation in a sequence. For example, if you are running a script that issues multiple of DDL operations to set up an entire new schema, add several new partitions, and so on, you might minimize the performance overhead by enabling the query option only before the last `CREATE`, `DROP`, `ALTER`, or `INSERT` statement. The script only finishes when all the relevant metadata changes are recognized by all the Impala nodes, so you could connect to any node and issue queries through it.

The classification of DDL, DML, and other statements is not necessarily the same between Impala and Hive. Impala organizes these statements in a way intended to be familiar to people familiar with relational databases or data warehouse products. Statements that modify the metastore database, such as `COMPUTE STATS`, are classified as DDL. Statements that only query the metastore database, such as `SHOW` or `DESCRIBE`, are put into a separate category of utility statements.

Note: The query types shown in the Impala debug web user interface might not match exactly the categories listed here. For example, currently the `USE` statement is shown as DDL in the debug web UI. The query types shown in the debug web UI are subject to change, for improved consistency.

Related information:

The other major classifications of SQL statements are data manipulation language (see [DML Statements](#) on page 214) and queries (see [SELECT Statement](#) on page 316).

DML Statements

DML refers to “Data Manipulation Language”, a subset of SQL statements that modify the data stored in tables. Because Impala focuses on query performance and leverages the append-only nature of HDFS storage, currently Impala only supports a small set of DML statements:

- [DELETE Statement \(Impala 2.8 or higher only\)](#) on page 266. Works for Kudu tables only.
- [INSERT Statement](#) on page 298.
- [LOAD DATA Statement](#) on page 309. Does not apply for HBase or Kudu tables.
- [UPDATE Statement \(Impala 2.8 or higher only\)](#) on page 418. Works for Kudu tables only.
- [UPSERT Statement \(Impala 2.8 or higher only\)](#) on page 420. Works for Kudu tables only.

INSERT in Impala is primarily optimized for inserting large volumes of data in a single statement, to make effective use of the multi-megabyte HDFS blocks. This is the way in Impala to create new data files. If you intend to insert one or a few rows at a time, such as using the `INSERT . . . VALUES` syntax, that technique is much more efficient for Impala tables stored in HBase. See [Using Impala to Query HBase Tables](#) on page 750 for details.

LOAD DATA moves existing data files into the directory for an Impala table, making them immediately available for Impala queries. This is one way in Impala to work with data files produced by other Hadoop components. (CREATE EXTERNAL TABLE is the other alternative; with external tables, you can query existing data files, while the files remain in their original location.)

In Impala 2.8 and higher, Impala does support the UPDATE, DELETE, and UPSERT statements for Kudu tables. For HDFS or S3 tables, to simulate the effects of an UPDATE or DELETE statement in other database systems, typically you use INSERT or CREATE TABLE AS SELECT to copy data from one table to another, filtering out or changing the appropriate rows during the copy operation.

You can also achieve a result similar to UPDATE by using Impala tables stored in HBase. When you insert a row into an HBase table, and the table already contains a row with the same value for the key column, the older row is hidden, effectively the same as a single-row UPDATE.

Impala can perform DML operations for tables or partitions stored in the Amazon S3 filesystem with Impala 2.6 and higher. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details.

Related information:

The other major classifications of SQL statements are data definition language (see [DDL Statements](#) on page 213) and queries (see [SELECT Statement](#) on page 316).

ALTER DATABASE Statement

The ALTER DATABASE statement changes the characteristics of a database.

Use the SET OWNER clause to transfer the ownership of the database from the current owner to another user or a role.

The database owner is originally set to the user who creates the database. The term OWNER is used to differentiate between the ALL privilege that is explicitly granted via the GRANT statement and a privilege that is implicitly granted by the CREATE DATABASE statement.

Syntax:

```
ALTER DATABASE database_name SET OWNER USER user_name;
```

Statement type: DDL

Cancellation: Cannot be cancelled.

Added in: Impala 3.1

ALTER TABLE Statement

The ALTER TABLE statement changes the structure or properties of an existing Impala table.

In Impala, this is primarily a logical operation that updates the table metadata in the metastore database that Impala shares with Hive. Most ALTER TABLE operations do not actually rewrite, move, and so on the actual data files. (The RENAME TO clause is the one exception; it can cause HDFS files to be moved to different paths.) When you do an ALTER TABLE operation, you typically need to perform corresponding physical filesystem operations, such as rewriting the data files to include extra fields, or converting them to a different file format.

Syntax:

```
ALTER TABLE [old_db_name.]old_table_name RENAME TO  
[new_db_name.]new_table_name
```

```

ALTER TABLE name ADD [IF NOT EXISTS] COLUMNS (col_spec[, col_spec ...])
ALTER TABLE name REPLACE COLUMNS (col_spec[, col_spec ...])

ALTER TABLE name ADD COLUMN [IF NOT EXISTS] col_spec
ALTER TABLE name DROP [COLUMN] column_name
ALTER TABLE name CHANGE column_name col_spec

ALTER TABLE name SET OWNER USER user_name

-- Kudu tables only.
ALTER TABLE name ALTER [COLUMN] column_name
    { SET kudu_storage_attr attr_value
      | DROP DEFAULT }

kudu_storage_attr ::= { DEFAULT | BLOCK_SIZE | ENCODING | COMPRESSION }

-- Non-Kudu tables only.
ALTER TABLE name ALTER [COLUMN] column_name
    SET COMMENT 'comment_text'

ALTER TABLE name ADD [IF NOT EXISTS] PARTITION (partition_spec)
    [location_spec]
    [cache_spec]
ALTER TABLE name ADD [IF NOT EXISTS] RANGE PARTITION kudu_partition_spec

ALTER TABLE name DROP [IF EXISTS] PARTITION (partition_spec)
    [PURGE]
ALTER TABLE name DROP [IF EXISTS] RANGE PARTITION kudu_partition_spec

ALTER TABLE name RECOVER PARTITIONS

ALTER TABLE name [PARTITION (partition_spec)]
    SET { FILEFORMAT file_format
          | ROW FORMAT row_format
          | LOCATION 'hdfs_path_of_directory'
          | TBLPROPERTIES (table_properties)
          | SERDEPROPERTIES (serde_properties) }

ALTER TABLE name colname
    ('statsKey'='val', ...)

statsKey ::= numDVs | numNulls | avgSize | maxSize

ALTER TABLE name [PARTITION (partition_spec)] SET { CACHED IN
    'pool_name' [WITH REPLICATION = integer] | UNCACHED }

new_name ::= [new_database.]new_table_name

col_spec ::= col_name type_name COMMENT 'column-comment' [kudu_attributes]

kudu_attributes ::= { [NOT] NULL | ENCODING codec | COMPRESSION algorithm |
    DEFAULT constant | BLOCK_SIZE number }

partition_spec ::= simple_partition_spec | complex_partition_spec

simple_partition_spec ::= partition_col=constant_value

complex_partition_spec ::= comparison_expression_on_partition_col

kudu_partition_spec ::= constant_range_operator
    VALUES range_operator constant | VALUE = constant

cache_spec ::= CACHED IN 'pool_name' [WITH REPLICATION = integer] | UNCACHED

```



```
location_spec ::= LOCATION 'hdfs_path_of_directory'

table_properties ::= 'name'='value'[, 'name'='value' ...]

serde_properties ::= 'name'='value'[, 'name'='value' ...]

file_format ::= { PARQUET | TEXTFILE | RCFILE | SEQUENCEFILE | AVRO }

row_format ::= DELIMITED
    [FIELDS TERMINATED BY 'char' [ESCAPED BY 'char']]
    [LINES TERMINATED BY 'char']
```

Statement type: DDL

Complex type considerations:

In Impala 2.3 and higher, the `ALTER TABLE` statement can change the metadata for tables containing complex types (ARRAY, STRUCT, and MAP). For example, you can use an `ADD COLUMNS`, `DROP COLUMN`, or `CHANGE` clause to modify the table layout for complex type columns. Although Impala queries only work for complex type columns in Parquet tables, the complex type support in the `ALTER TABLE` statement applies to all file formats. For example, you can use Impala to update metadata for a staging table in a non-Parquet file format where the data is populated by Hive. Or you can use `ALTER TABLE SET FILEFORMAT` to change the format of an existing table to Parquet so that Impala can query it. Remember that changing the file format for a table does not convert the data files within the table; you must prepare any Parquet data files containing complex types outside Impala, and bring them into the table using `LOAD DATA` or updating the table's `LOCATION` property. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types.

Usage notes:

Whenever you specify partitions in an `ALTER TABLE` statement, through the `PARTITION` (*partition_spec*) clause, you must include all the partitioning columns in the specification.

Most of the `ALTER TABLE` operations work the same for internal tables (managed by Impala) as for external tables (with data files located in arbitrary locations). The exception is renaming a table; for an external table, the underlying data directory is not renamed or moved.

To drop or alter multiple partitions:

In Impala 2.8 and higher, the expression for the partition clause with a `DROP` or `SET` operation can include comparison operators such as `<`, `IN`, or `BETWEEN`, and Boolean operators such as `AND` and `OR`.

For example, you might drop a group of partitions corresponding to a particular date range after the data “ages out”:

```
alter table historical_data drop partition (year < 1995);
alter table historical_data drop partition (year = 1996 and month between 1
and 6);
```

For tables with multiple partition keys columns, you can specify multiple conditions separated by commas, and the operation only applies to the partitions that match all the conditions (similar to using an `AND` clause):

```
alter table historical_data drop partition (year < 1995, last_name like 'A
%');
```

This technique can also be used to change the file format of groups of partitions, as part of an ETL pipeline that periodically consolidates and rewrites the underlying data files in a different file format:

```
alter table fast_growing_data partition (year = 2016, month in (10,11,12))
set fileformat parquet;
```

Note:

The extended syntax involving comparison operators and multiple partitions applies to the `SET FILEFORMAT`, `SET TBLPROPERTIES`, `SET SERDEPROPERTIES`, and `SET [UN]CACHED` clauses. You can also use this syntax with the `PARTITION` clause in the `COMPUTE INCREMENTAL STATS` statement, and with the `PARTITION` clause of the `SHOW FILES` statement. Some forms of `ALTER TABLE` still only apply to one partition at a time: the `SET LOCATION` and `ADD PARTITION` clauses. The `PARTITION` clauses in the `LOAD DATA` and `INSERT` statements also only apply to one partition at a time.

A DDL statement that applies to multiple partitions is considered successful (resulting in no changes) even if no partitions match the conditions. The results are the same as if the `IF EXISTS` clause was specified.

The performance and scalability of this technique is similar to issuing a sequence of single-partition `ALTER TABLE` statements in quick succession. To minimize bottlenecks due to communication with the metastore database, or causing other DDL operations on the same table to wait, test the effects of performing `ALTER TABLE` statements that affect large numbers of partitions.

Amazon S3 considerations:

You can specify an `s3a://` prefix on the `LOCATION` attribute of a table or partition to make Impala query data from the Amazon S3 filesystem. In Impala 2.6 and higher, Impala automatically handles creating or removing the associated folders when you issue `ALTER TABLE` statements with the `ADD PARTITION` or `DROP PARTITION` clauses.

In Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about reading and writing S3 data with Impala.

HDFS caching (CACHED IN clause):

If you specify the `CACHED IN` clause, any existing or future data files in the table directory or the partition subdirectories are designated to be loaded into memory with the HDFS caching mechanism. See [Using HDFS Caching with Impala \(Impala 2.1 or higher only\)](#) on page 646 for details about using the HDFS caching feature.

In Impala 2.2 and higher, the optional `WITH REPLICATION` clause for `CREATE TABLE` and `ALTER TABLE` lets you specify a *replication factor*, the number of hosts on which to cache the same data blocks. When Impala processes a cached data block, where the cache replication factor is greater than 1, Impala randomly selects a host that has a cached copy of that data block. This optimization avoids excessive CPU usage on a single host when the same cached data block is processed multiple times. Where practical, specify a value greater than or equal to the HDFS block replication factor.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

To rename a table (RENAME TO clause):

The `RENAME TO` clause lets you change the name of an existing table, and optionally which database it is located in.

For internal tables, this operation physically renames the directory within HDFS that contains the data files; the original directory name no longer exists. By qualifying the table names with database names, you can use this technique to move an internal table (and its associated data directory) from one database to another. For example:

```
create database d1;
create database d2;
create database d3;
use d1;
create table mobile (x int);
use d2;
```

```
-- Move table from another database to the current one.
alter table d1.mobile rename to mobile;
use d1;
-- Move table from one database to another.
alter table d2.mobile rename to d3.mobile;
```

To change the owner of a table:

```
ALTER TABLE name SET OWNER USER user_name;
```

The table owner is originally set to the user who creates the table. The term OWNER is used to differentiate between the ALL privilege that is explicitly granted via the GRANT statement and a privilege that is implicitly granted by the CREATE TABLE statement.

Use the ALTER TABLE SET OWNER to transfer the ownership from the current owner to another user.

To change the physical location where Impala looks for data files associated with a table or partition:

```
ALTER TABLE table_name [PARTITION (partition_spec)] SET LOCATION
'hdfs_path_of_directory';
```

The path you specify is the full HDFS path where the data files reside, or will be created. Impala does not create any additional subdirectory named after the table. Impala does not move any data files to this new location or change any data files that might already exist in that directory.

To set the location for a single partition, include the PARTITION clause. Specify all the same partitioning columns for the table, with a constant value for each, to precisely identify the single partition affected by the statement:

```
create table p1 (s string) partitioned by (month int, day int);
-- Each ADD PARTITION clause creates a subdirectory in HDFS.
alter table p1 add partition (month=1, day=1);
alter table p1 add partition (month=1, day=2);
alter table p1 add partition (month=2, day=1);
alter table p1 add partition (month=2, day=2);
-- Redirect queries, INSERT, and LOAD DATA for one partition
-- to a specific different directory.
alter table p1 partition (month=1, day=1) set location '/usr/external_data/
new_years_day';
```

Note: If you are creating a partition for the first time and specifying its location, for maximum efficiency, use a single ALTER TABLE statement including both the ADD PARTITION and LOCATION clauses, rather than separate statements with ADD PARTITION and SET LOCATION clauses.

To automatically detect new partition directories added through Hive or HDFS operations:

In Impala 2.3 and higher, the RECOVER PARTITIONS clause scans a partitioned table to detect if any new partition directories were added outside of Impala, such as by Hive ALTER TABLE statements or by `hdfs dfs` or `hadoop fs` commands. The RECOVER PARTITIONS clause automatically recognizes any data files present in these new directories, the same as the REFRESH statement does.

For example, here is a sequence of examples showing how you might create a partitioned table in Impala, create new partitions through Hive, copy data files into the new partitions with the `hdfs` command, and have Impala recognize the new partitions and new data:

In Impala, create the table, and a single partition for demonstration purposes:

```
create database recover_partitions;
use recover_partitions;
create table t1 (s string) partitioned by (yy int, mm int);
insert into t1 partition (yy = 2016, mm = 1) values ('Partition exists');
```

```
show files in t1;
+-----+-----+
| Path                                     | Size |
| Partition                               |      |
+-----+-----+
| /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=1/data.txt | 17B   |
| yy=2016/mm=1 |
+-----+-----+
quit;
```

In Hive, create some new partitions. In a real use case, you might create the partitions and populate them with data as the final stages of an ETL pipeline.

```
hive> use recover_partitions;
OK
hive> alter table t1 add partition (yy = 2016, mm = 2);
OK
hive> alter table t1 add partition (yy = 2016, mm = 3);
OK
hive> quit;
```

For demonstration purposes, manually copy data (a single row) into these new partitions, using manual HDFS operations:

```
$ hdfs dfs -ls /user/hive/warehouse/recover_partitions.db/t1/yy=2016/
Found 3 items
drwxr-xr-x - impala   hive 0 2016-05-09 16:06 /user/hive/warehouse/
recover_partitions.db/t1/yy=2016/mm=1
drwxr-xr-x - jrussell hive 0 2016-05-09 16:14 /user/hive/warehouse/
recover_partitions.db/t1/yy=2016/mm=2
drwxr-xr-x - jrussell hive 0 2016-05-09 16:13 /user/hive/warehouse/
recover_partitions.db/t1/yy=2016/mm=3

$ hdfs dfs -cp /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=1/
data.txt \
  /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=2/data.txt
$ hdfs dfs -cp /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=1/
data.txt \
  /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=3/data.txt
```

```
hive> select * from t1;
OK
Partition exists  2016  1
Partition exists  2016  2
Partition exists  2016  3
hive> quit;
```

In Impala, initially the partitions and data are not visible. Running `ALTER TABLE` with the `RECOVER PARTITIONS` clause scans the table data directory to find any new partition directories, and the data files inside them:

```
select * from t1;
+-----+-----+-----+
| s          | yy   | mm   |
+-----+-----+-----+
| Partition exists | 2016 | 1    |
+-----+-----+-----+

alter table t1 recover partitions;
select * from t1;
+-----+-----+-----+
| s          | yy   | mm   |
+-----+-----+-----+
| Partition exists | 2016 | 1    |
| Partition exists | 2016 | 3    |
| Partition exists | 2016 | 2    |
+-----+-----+-----+
```

To change the key-value pairs of the `TBLPROPERTIES` and `SERDEPROPERTIES` fields:

```
ALTER TABLE table_name SET TBLPROPERTIES ('key1'='value1',
'key2'='value2'[, ...]);
ALTER TABLE table_name SET SERDEPROPERTIES ('key1'='value1',
'key2'='value2'[, ...]);
```

The `TBLPROPERTIES` clause is primarily a way to associate arbitrary user-specified data items with a particular table.

The `SERDEPROPERTIES` clause sets up metadata defining how tables are read or written, needed in some cases by Hive but not used extensively by Impala. You would use this clause primarily to change the delimiter in an existing text table or partition, by setting the `'serialization.format'` and `'field.delim'` property values to the new delimiter character. The `SERDEPROPERTIES` clause does not change the existing data in the table. The change only affects the future insert into the table.

Use the `DESCRIBE FORMATTED` statement to see the current values of these properties for an existing table. See [CREATE TABLE Statement](#) on page 248 for more details about these clauses.

To specify a sort order for new records that are added to the table:

```
ALTER TABLE table_name SORT BY [LEXICAL|ZORDER](column_name1[, column_name2
...]);
```

Specifying the sort order is optional. The default sort order is `LEXICAL`. Setting the `SORT BY` property will not rewrite existing data files, but subsequent inserts will be ordered. Sorting is always ascending.

Use the `DESCRIBE FORMATTED` statement to see the current sort properties (`'sort.columns'` and `'sort.order'`) for an existing table. They can also be set using `SET TBLPROPERTIES`.

For details about sort order see [CREATE TABLE Statement](#) on page 248.

To manually set or update table or column statistics:

Although for most tables the `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement is all you need to keep table and column statistics up to date for a table, sometimes for a very large table or one that is updated frequently, the length of time to recompute all the statistics might make it impractical to run those statements as often

as needed. As a workaround, you can use the `ALTER TABLE` statement to set table statistics at the level of the entire table or a single partition, or column statistics at the level of the entire table.

You can set the `numrows` value for table statistics by changing the `TBLPROPERTIES` setting for a table or partition. For example:

```
create table analysis_data stored as parquet as select * from raw_data;
Inserted 1000000000 rows in 181.98s
compute stats analysis_data;
insert into analysis_data select * from smaller_table_we_forgot_before;
Inserted 1000000 rows in 15.32s
-- Now there are 1001000000 rows. We can update this single data point in
the stats.
alter table analysis_data set tblproperties('numRows'='1001000000',
'STATS_GENERATED_VIA_STATS_TASK'='true');
```

```
-- If the table originally contained 1 million rows, and we add another
partition with 30 thousand rows,
-- change the numRows property for the partition and the overall table.
alter table partitioned_data partition(year=2009, month=4) set tblproperties
('numRows'='30000', 'STATS_GENERATED_VIA_STATS_TASK'='true');
alter table partitioned_data set tblproperties ('numRows'='1030000',
'STATS_GENERATED_VIA_STATS_TASK'='true');
```

In Impala 2.6 and higher, you can use the `SET COLUMN STATS` clause to set a specific stats value for a particular column.

You specify a case-insensitive symbolic name for the kind of statistics: `numDVs`, `numNulls`, `avgSize`, `maxSize`. The key names and values are both quoted. This operation applies to an entire table, not a specific partition. For example:

```
create table t1 (x int, s string);
insert into t1 values (1, 'one'), (2, 'two'), (2, 'deux');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
x	INT	-1	-1	4	4
s	STRING	-1	-1	-1	-1

```
alter table t1 set column stats x ('numDVs'='2','numNulls'='0');
alter table t1 set column stats s ('numdvs'='3','maxsize'='4');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
x	INT	2	0	4	4
s	STRING	3	-1	4	-1

To reorganize columns for a table:

You can add multiple columns at a time using the `ALTER TABLE` statement. If you specify the `IF NOT EXISTS` clause, Impala silently ignores the `ADD` request and does not return an error if a column with the same name exists in the table.

When you replace columns, all the original column definitions are discarded.

You might use these statements if you receive a new set of data files with different data types or columns in a different order. The data files are retained, so if the new columns are incompatible with the old ones, use `INSERT OVERWRITE` or `LOAD DATA OVERWRITE` to replace all the data before issuing any further queries.

For example, here is how you might add columns to an existing table. The first `ALTER TABLE` adds two new columns, and the second `ALTER TABLE` adds one new column. A single Impala query reads both the old and new data files, containing different numbers of columns. For any columns not present in a particular data file, all the column values are considered to be `NULL`.

```
create table t1 (x int);
insert into t1 values (1), (2);

alter table t1 add columns (s string, t timestamp);
insert into t1 values (3, 'three', now());

alter table t1 add columns (b boolean);
insert into t1 values (4, 'four', now(), true);

select * from t1 order by x;
```

x	s	t	b
1	NULL	NULL	NULL
2	NULL	NULL	NULL
3	three	2016-05-11 11:19:45.054457000	NULL
4	four	2016-05-11 11:20:20.260733000	true

You might use the `CHANGE` clause to rename a single column, or to treat an existing column as a different type than before, such as to switch between treating a column as `STRING` and `TIMESTAMP`, or between `INT` and `BIGINT`. You can only drop a single column at a time; to drop multiple columns, issue multiple `ALTER TABLE` statements, or define the new set of columns with a single `ALTER TABLE ... REPLACE COLUMNS` statement.

The following examples show some safe operations to drop or change columns. Dropping the final column in a table lets Impala ignore the data causing any disruption to existing data files. Changing the type of a column works if existing data values can be safely converted to the new type. The type conversion rules depend on the file format of the underlying table. For example, in a text table, the same value can be interpreted as a `STRING` or a numeric value, while in a binary format such as Parquet, the rules are stricter and type conversions only work between certain sizes of integers.

```
create table optional_columns (x int, y int, z int, a1 int, a2 int);
insert into optional_columns values (1,2,3,0,0), (2,3,4,100,100);

-- When the last column in the table is dropped, Impala ignores the
-- values that are no longer needed. (Dropping A1 but leaving A2
-- would cause problems, as we will see in a subsequent example.)
alter table optional_columns drop column a2;
alter table optional_columns drop column a1;

select * from optional_columns;
```

x	y	z
1	2	3
2	3	4

```
create table int_to_string (s string, x int);
insert into int_to_string values ('one', 1), ('two', 2);

-- What was an INT column will now be interpreted as STRING.
-- This technique works for text tables but not other file formats.
```

```
-- The second X represents the new name of the column, which we keep the
  same.
alter table int_to_string change x x string;

-- Once the type is changed, we can insert non-integer values into the X
  column
-- and treat that column as a string, for example by uppercasing or
  concatenating.
insert into int_to_string values ('three', 'trois');
select s, upper(x) from int_to_string;
```

s	upper(x)
one	1
two	2
three	TROIS

Remember that Impala does not actually do any conversion for the underlying data files as a result of `ALTER TABLE` statements. If you use `ALTER TABLE` to create a table layout that does not agree with the contents of the underlying files, you must replace the files yourself, such as using `LOAD DATA` to load a new set of data files, or `INSERT OVERWRITE` to copy from another table and replace the original data.

The following example shows what happens if you delete the middle column from a Parquet table containing three columns. The underlying data files still contain three columns of data. Because the columns are interpreted based on their positions in the data file instead of the specific column names, a `SELECT *` query now reads the first and second columns from the data file, potentially leading to unexpected results or conversion errors. For this reason, if you expect to someday drop a column, declare it as the last column in the table, where its data can be ignored by queries after the column is dropped. Or, re-run your ETL process and create new data files if you drop or change the type of a column in a way that causes problems with existing data files.

```
-- Parquet table showing how dropping a column can produce unexpected
  results.
create table p1 (s1 string, s2 string, s3 string) stored as parquet;

insert into p1 values ('one', 'un', 'uno'), ('two', 'deux', 'dos'),
  ('three', 'trois', 'tres');
select * from p1;
```

s1	s2	s3
one	un	uno
two	deux	dos
three	trois	tres

```
alter table p1 drop column s2;
-- The S3 column contains unexpected results.
-- Because S2 and S3 have compatible types, the query reads
-- values from the dropped S2, because the existing data files
-- still contain those values as the second column.
select * from p1;
```

s1	s3
one	un
two	deux
three	trois


```
-- Parquet table showing how dropping a column can produce conversion
errors.
create table p2 (s1 string, x int, s3 string) stored as parquet;

insert into p2 values ('one', 1, 'uno'), ('two', 2, 'dos'), ('three', 3,
'tres');
select * from p2;
+-----+-----+-----+
| s1      | x  | s3      |
+-----+-----+-----+
| one     | 1  | uno     |
| two     | 2  | dos     |
| three   | 3  | tres    |
+-----+-----+-----+

alter table p2 drop column x;
select * from p2;
WARNINGS:
File 'hdfs_filename' has an incompatible Parquet schema for column
'add_columns.p2.s3'.
Column type: STRING, Parquet schema:
optional int32 x [i:1 d:1 r:0]

File 'hdfs_filename' has an incompatible Parquet schema for column
'add_columns.p2.s3'.
Column type: STRING, Parquet schema:
optional int32 x [i:1 d:1 r:0]
```

In Impala 2.6 and higher, if an Avro table is created without column definitions in the `CREATE TABLE` statement, and columns are later added through `ALTER TABLE`, the resulting table is now queryable. Missing values from the newly added columns now default to `NULL`.

To change the file format that Impala expects data to be in, for a table or partition:

Use an `ALTER TABLE ... SET FILEFORMAT` clause. You can include an optional `PARTITION (col1=val1, col2=val2, ...)` clause so that the file format is changed for a specific partition rather than the entire table.

Because this operation only changes the table metadata, you must do any conversion of existing data using regular Hadoop techniques outside of Impala. Any new data created by the Impala `INSERT` statement will be in the new format. You cannot specify the delimiter for Text files; the data files must be comma-delimited.

To set the file format for a single partition, include the `PARTITION` clause. Specify all the same partitioning columns for the table, with a constant value for each, to precisely identify the single partition affected by the statement:

```
create table p1 (s string) partitioned by (month int, day int);
-- Each ADD PARTITION clause creates a subdirectory in HDFS.
alter table p1 add partition (month=1, day=1);
alter table p1 add partition (month=1, day=2);
alter table p1 add partition (month=2, day=1);
alter table p1 add partition (month=2, day=2);
-- Queries and INSERT statements will read and write files
-- in this format for this specific partition.
alter table p1 partition (month=2, day=2) set fileformat parquet;
```

To change the row format with different delimiter characters:

Use the `SET ROW FORMAT DELIMITED` clause to ingest data files that use a different delimiter character or a different line end character. When specifying delimiter and line end characters with the `FIELDS TERMINATED BY`, `ESCAPED BY`, and `LINES TERMINATED BY` clauses, you can use the following:

- A regular ASCII character surrounded by single or double quotation marks.
- An octal sequence, such as `'\054'` representing a comma or `'\0'` for ASCII null (hex 00).

- Special characters, such as:
 - '\t' for tab
 - '\n' for newline or linefeed
 - '\r' for carriage return
- An integer in the range '-127'..'128' (with quotation marks but no backslash)

Negative values are subtracted from 256. For example, `FIELDS TERMINATED BY '-2'` sets the field delimiter to ASCII code 254.

For more examples of text tables, see [Using Text Data Files with Impala Tables](#) on page 697.

For the `ESCAPED BY` clause, choose an escape character that is not used anywhere else in the file. The character following the escape character is taken literally as part of a field value.

Surrounding field values with quotation marks does not help Impala to parse fields with embedded delimiter characters as the quotation marks are considered to be part of the column value.

If you want to use `\` as the escape character, specify the clause in `impala-shell` as `ESCAPED BY '\\'`.

To add or drop partitions for a table, the table must already be partitioned (that is, created with a `PARTITIONED BY` clause). The partition is a physical directory in HDFS, with a name that encodes a particular column value (the **partition key**). The Impala `INSERT` statement already creates the partition if necessary, so the `ALTER TABLE ... ADD PARTITION` is primarily useful for importing data by moving or copying existing data files into the HDFS directory corresponding to a partition. (You can use the `LOAD DATA` statement to move files into the partition directory, or `ALTER TABLE ... PARTITION (...) SET LOCATION` to point a partition at a directory that already contains data files.

The `DROP PARTITION` clause is used to remove the HDFS directory and associated data files for a particular set of partition key values; for example, if you always analyze the last 3 months worth of data, at the beginning of each month you might drop the oldest partition that is no longer needed. Removing partitions reduces the amount of metadata associated with the table and the complexity of calculating the optimal query plan, which can simplify and speed up queries on partitioned tables, particularly join queries. Here is an example showing the `ADD PARTITION` and `DROP PARTITION` clauses.

To avoid errors while adding or dropping partitions whose existence is not certain, add the optional `IF [NOT] EXISTS` clause between the `ADD` or `DROP` keyword and the `PARTITION` keyword. That is, the entire clause becomes `ADD IF NOT EXISTS PARTITION` or `DROP IF EXISTS PARTITION`. The following example shows how partitions can be created automatically through `INSERT` statements, or manually through `ALTER TABLE` statements. The `IF [NOT] EXISTS` clauses let the `ALTER TABLE` statements succeed even if a new requested partition already exists, or a partition to be dropped does not exist.

Inserting 2 year values creates 2 partitions:

```
create table partition_t (s string) partitioned by (y int);
insert into partition_t (s,y) values ('two thousand',2000), ('nineteen
  ninety',1990);
show partitions partition_t;
```

y	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format
Incremental stats						
1990	-1	1	16B	NOT CACHED	NOT CACHED	TEXT
2000	-1	1	13B	NOT CACHED	NOT CACHED	TEXT
Total	-1	2	29B	0B		

```
+-----+-----+-----+-----+-----+-----+-----+
+-----+
```

Without the `IF NOT EXISTS` clause, an attempt to add a new partition might fail:

```
alter table partition_t add partition (y=2000);
ERROR: AnalysisException: Partition spec already exists: (y=2000).
```

The `IF NOT EXISTS` clause makes the statement succeed whether or not there was already a partition with the specified key value:

```
alter table partition_t add if not exists partition (y=2000);
alter table partition_t add if not exists partition (y=2010);
show partitions partition_t;
```

y	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format
Incremental stats						
1990	-1	1	16B	NOT CACHED	NOT CACHED	TEXT
false						
2000	-1	1	13B	NOT CACHED	NOT CACHED	TEXT
false						
2010	-1	0	0B	NOT CACHED	NOT CACHED	TEXT
false						
Total	-1	2	29B	0B		

Likewise, the `IF EXISTS` clause lets `DROP PARTITION` succeed whether or not the partition is already in the table:

```
alter table partition_t drop if exists partition (y=2000);
alter table partition_t drop if exists partition (y=1950);
show partitions partition_t;
```

y	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format
Incremental stats						
1990	-1	1	16B	NOT CACHED	NOT CACHED	TEXT
false						
2010	-1	0	0B	NOT CACHED	NOT CACHED	TEXT
false						
Total	-1	1	16B	0B		

The optional `PURGE` keyword, available in Impala 2.3 and higher, is used with the `DROP PARTITION` clause to remove associated HDFS data files immediately rather than going through the HDFS trashcan mechanism. Use this keyword when dropping a partition if it is crucial to remove the data as quickly as possible to free up space, or if there

is a problem with the trashcan, such as the trash cannot being configured or being in a different HDFS encryption zone than the data files.

```
-- Create an empty table and define the partitioning scheme.
create table part_t (x int) partitioned by (month int);
-- Create an empty partition into which you could copy data files from some
  other source.
alter table part_t add partition (month=1);
-- After changing the underlying data, issue a REFRESH statement to make the
  data visible in Impala.
refresh part_t;
-- Later, do the same for the next month.
alter table part_t add partition (month=2);

-- Now you no longer need the older data.
alter table part_t drop partition (month=1);
-- If the table was partitioned by month and year, you would issue a
  statement like:
-- alter table part_t drop partition (year=2003,month=1);
-- which would require 12 ALTER TABLE statements to remove a year's worth of
  data.

-- If the data files for subsequent months were in a different file format,
-- you could set a different file format for the new partition as you create
  it.
alter table part_t add partition (month=3) set fileformat=parquet;
```

The value specified for a partition key can be an arbitrary constant expression, without any references to columns. For example:

```
alter table time_data add partition (month=concat('Decem','ber'));
alter table sales_data add partition (zipcode = cast(9021 * 10 as string));
```

Note:

An alternative way to reorganize a table and its associated data files is to use `CREATE TABLE` to create a variation of the original table, then use `INSERT` to copy the transformed or reordered data to the new table. The advantage of `ALTER TABLE` is that it avoids making a duplicate copy of the data files, allowing you to reorganize huge volumes of data in a space-efficient way using familiar Hadoop techniques.

To switch a table between internal and external:

You can switch a table from internal to external, or from external to internal, by using the `ALTER TABLE` statement:

```
-- Switch a table from internal to external.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');

-- Switch a table from external to internal.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='FALSE');
```

If the Kudu service is integrated with the Hive Metastore, the above operations are not supported.

Cancellation: Cannot be cancelled.

HDFS permissions:

Most `ALTER TABLE` clauses do not actually read or write any HDFS files, and so do not depend on specific HDFS permissions. For example, the `SET FILEFORMAT` clause does not actually check the file format existing data files or convert them to the new format, and the `SET LOCATION` clause does not require any special permissions on the new location. (Any permission-related failures would come later, when you actually query or insert into the table.)

In general, `ALTER TABLE` clauses that do touch HDFS files and directories require the same HDFS permissions as corresponding `CREATE`, `INSERT`, or `SELECT` statements. The permissions allow the user ID that the `impalad` daemon runs under, typically the `impala` user, to read or write files or directories, or (in the case of the execute bit) descend into a directory. The `RENAME TO` clause requires read, write, and execute permission in the source and destination database directories and in the table data directory, and read and write permission for the data files within the table. The `ADD PARTITION` and `DROP PARTITION` clauses require write and execute permissions for the associated partition directory.

Kudu considerations:

Because of the extra constraints and features of Kudu tables, such as the `NOT NULL` and `DEFAULT` attributes for columns, `ALTER TABLE` has specific requirements related to Kudu tables:

- In an `ADD COLUMNS` operation, you can specify the `NULL`, `NOT NULL`, and `DEFAULT default_value` column attributes.
- In Impala 2.9 and higher, you can also specify the `ENCODING`, `COMPRESSION`, and `BLOCK_SIZE` attributes when adding a column.
- If you add a column with a `NOT NULL` attribute, it must also have a `DEFAULT` attribute, so the default value can be assigned to that column for all existing rows.
- The `DROP COLUMN` clause works the same for a Kudu table as for other kinds of tables.
- Although you can change the name of a column with the `CHANGE` clause, you cannot change the type of a column in a Kudu table.
- You cannot change the nullability of existing columns in a Kudu table.
- In Impala 2.10, you can change the default value, encoding, compression, or block size of existing columns in a Kudu table by using the `SET` clause.
- You cannot use the `REPLACE COLUMNS` clause with a Kudu table.
- The `RENAME TO` clause for a Kudu table only affects the name stored in the metastore database that Impala uses to refer to the table. To change which underlying Kudu table is associated with an Impala table name, you must change the `TBLPROPERTIES` property of the table: `SET TBLPROPERTIES('kudu.table_name'='kudu_tbl_name')`. You can only change underlying Kudu tables for the external tables.

The following are some examples of using the `ADD COLUMNS` clause for a Kudu table:

```
CREATE TABLE t1 ( x INT, PRIMARY KEY (x) )
PARTITION BY HASH (x) PARTITIONS 16
STORED AS KUDU

ALTER TABLE t1 ADD COLUMNS (y STRING ENCODING prefix_encoding);
ALTER TABLE t1 ADD COLUMNS (z INT DEFAULT 10);
ALTER TABLE t1 ADD COLUMNS (a STRING NOT NULL DEFAULT '', t TIMESTAMP
COMPRESSION default_compression);
```

The following are some examples of modifying column defaults and storage attributes for a Kudu table:

```
create table kt (x bigint primary key, s string default 'yes', t timestamp)
stored as kudu;

-- You can change the default value for a column, which affects any rows
-- inserted after this change is made.
alter table kt alter column s set default 'no';

-- You can remove the default value for a column, which affects any rows
-- inserted after this change is made. If the column is nullable, any
-- future inserts default to NULL for this column. If the column is marked
-- NOT NULL, any future inserts must specify a value for the column.
alter table kt alter column s drop default;
```

```

insert into kt values (1, 'foo', now());
-- Because of the DROP DEFAULT above, omitting S from the insert
-- gives it a value of NULL.
insert into kt (x, t) values (2, now());

select * from kt;
+-----+-----+-----+-----+
| x | s | t |
+-----+-----+-----+
| 2 | NULL | 2017-10-02 00:03:40.652156000 |
| 1 | foo | 2017-10-02 00:03:04.346185000 |
+-----+-----+-----+

-- Other storage-related attributes can also be changed for columns.
-- These changes take effect for any newly inserted rows, or rows
-- rearranged due to compaction after deletes or updates.
alter table kt alter column s set encoding prefix_encoding;
-- The COLUMN keyword is optional in the syntax.
alter table kt alter x set block_size 2048;
alter table kt alter column t set compression zlib;

desc kt;
+-----+-----+-----+-----+-----+-----+
| name | type | comment | primary_key | nullable | default_value |
| encoding | compression | block_size |
+-----+-----+-----+-----+-----+
| x | bigint | | true | false | |
| AUTO_ENCODING | DEFAULT_COMPRESSION | 2048 |
| s | string | | false | true | |
| PREFIX_ENCODING | DEFAULT_COMPRESSION | 0 |
| t | timestamp | | false | true | |
| AUTO_ENCODING | ZLIB | 0 |
+-----+-----+-----+-----+-----+

```

Kudu tables all use an underlying partitioning mechanism. The partition syntax is different than for non-Kudu tables. You can use the `ALTER TABLE` statement to add and drop *range partitions* from a Kudu table. Any new range must not overlap with any existing ranges. Dropping a range removes all the associated rows from the table. See [Partitioning for Kudu Tables](#) on page 740 for details.

Related information:

[Overview of Impala Tables](#) on page 206, [CREATE TABLE Statement](#) on page 248, [DROP TABLE Statement](#) on page 289, [Partitioning for Impala Tables](#) on page 685, [Internal Tables](#) on page 206, [External Tables](#) on page 207

ALTER VIEW Statement

The `ALTER VIEW` statement changes the characteristics of a view.

Because a view is a logical construct, an alias for a query, with no physical data behind it, `ALTER VIEW` only involves changes to metadata in the metastore database, not any data files in HDFS.

To see the definition of the updated view, issue a `DESCRIBE FORMATTED` statement.

Syntax:

```

ALTER VIEW [database_name.]view_name
  [(column_name [COMMENT 'column_comment'][, ...])]
  AS select_statement;

ALTER VIEW [database_name.]view_name

```

```

    RENAME TO [database_name.]view_name;

ALTER VIEW [database_name.]view_name SET OWNER USER user_name;

ALTER VIEW [database_name.]view_name
    SET TBLPROPERTIES ('name' = 'value'[, 'name' = 'value' ...]);

ALTER VIEW [database_name.]view_name
    UNSET TBLPROPERTIES ('name'[, ...]);

```

- The AS clause associates the view with a different query.

An optional list of column names can be specified with or without the column-level comments.

For example:

```

ALTER VIEW v1 AS SELECT x, UPPER(s) s FROM t2;
ALTER VIEW v1 (c1, c2) AS SELECT x, UPPER(s) s FROM t2;
ALTER VIEW v7 (c1 COMMENT 'Comment for c1', c2) AS SELECT t1.c1, t1.c2
FROM t1;

```

- The RENAME TO clause changes the name of the view, moves the view to a different database, or both.

For example:

```

ALTER VIEW db1.v1 RENAME TO db2.v2; -- Move the view to a different
database with a new name.
ALTER VIEW db1.v1 RENAME TO db1.v2; -- Rename the view in the same
database.
ALTER VIEW db1.v1 RENAME TO db2.v1; -- Move the view to a difference
database with the same view name.

```

- The SET OWNER clause transfers the ownership of the view from the current owner to another user.

The view owner is originally set to the user who creates the view. The term OWNER is used to differentiate between the ALL privilege that is explicitly granted via the GRANT statement and a privilege that is implicitly granted by the CREATE VIEW statement.

- The SET TBLPROPERTIES clause is primarily a way to associate arbitrary user-specified data items with a particular view.

You can associate arbitrary items of metadata with a table by specifying the TBLPROPERTIES clause. This clause takes a comma-separated list of key-value pairs and stores those items in the metastore database. You can also unset the view properties later with an UNSET TBLPROPERTIES clause.

For example:

```

ALTER VIEW v1 SET TBLPROPERTIES ('tblp1' = '1', 'tblp2' = '2');
ALTER VIEW v1 UNSET TBLPROPERTIES ('tblp1', 'tblp2');

```

Statement type: DDL

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See the documentation for your Apache Hadoop distribution for details.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Overview of Impala Views](#) on page 209, [CREATE VIEW Statement](#) on page 265, [DROP VIEW Statement](#) on page 290

COMMENT Statement

The COMMENT statement adds, changes, or removes a comment about a database, a table, or a column.

You can alternatively use the CREATE and ALTER statements to add comments to the objects.

You can view the comment on a database, a table, or a column using the SHOW or DESCRIBE statement.

Syntax:

```
COMMENT ON DATABASE db_name IS { 'comment' | NULL }
```

```
COMMENT ON TABLE [db_name.]table_name IS { 'comment' | NULL }
```

```
COMMENT ON COLUMN [db_name.]table_name.column_name IS { 'comment' | NULL }
```

Parameters:

- *db_name*: Specify the database name if not for the current database.
- NULL: If given for the comment, removes the existing comment.
- The *comment* string can be up to 256 characters long.

Privileges required:

To add a comment, the ALTER privilege on the object is required.

To view a comment, the SELECT, INSERT, or REFRESH on the object is required.

Usage notes:

Added in: Impala 3.1

COMPUTE STATS Statement

The COMPUTE STATS statement gathers information about volume and distribution of data in a table and all associated columns and partitions. The information is stored in the metastore database, and used by Impala to help optimize queries. For example, if Impala can determine that a table is large or small, or has many or few distinct values it can organize and parallelize the work appropriately for a join query or insert operation. For details about the kinds of information gathered by this statement, see [Table and Column Statistics](#) on page 625.

Syntax:

```
COMPUTE STATS [db_name.]table_name [ ( column_list ) ] [TABLESAMPLE  
SYSTEM(percentage) [REPEATABLE(seed)]]
```

```
column_list ::= column_name [ , column_name , ... ]
```

```
COMPUTE INCREMENTAL STATS [db_name.]table_name [PARTITION (partition_spec)]  
[ ( column_list ) ]
```

```
partition_spec ::= simple_partition_spec | complex_partition_spec
```

```
simple_partition_spec ::= partition_col=constant_value
```

```
complex_partition_spec ::= comparison_expression_on_partition_col
```


The `PARTITION` clause is only allowed in combination with the `INCREMENTAL` clause. It is optional for `COMPUTE INCREMENTAL STATS`, and required for `DROP INCREMENTAL STATS`. Whenever you specify partitions through the `PARTITION (partition_spec)` clause in a `COMPUTE INCREMENTAL STATS` or `DROP INCREMENTAL STATS` statement, you must include all the partitioning columns in the specification, and specify constant values for all the partition key columns.

Usage notes:

Originally, Impala relied on users to run the Hive `ANALYZE TABLE` statement, but that method of gathering statistics proved unreliable and difficult to use. The Impala `COMPUTE STATS` statement was built to improve the reliability and user-friendliness of this operation. `COMPUTE STATS` does not require any setup steps or special configuration. You only run a single Impala `COMPUTE STATS` statement to gather both table and column statistics, rather than separate Hive `ANALYZE TABLE` statements for each kind of statistics.

For non-incremental `COMPUTE STATS` statement, the columns for which statistics are computed can be specified with an optional comma-separated list of columns.

If no column list is given, the `COMPUTE STATS` statement computes column-level statistics for all columns of the table. This adds potentially unneeded work for columns whose stats are not needed by queries. It can be especially costly for very wide tables and unneeded large string fields.

`COMPUTE STATS` returns an error when a specified column cannot be analyzed, such as when the column does not exist, the column is of an unsupported type for `COMPUTE STATS`, e.g. columns of complex types, or the column is a partitioning column.

If an empty column list is given, no column is analyzed by `COMPUTE STATS`.

In Impala 2.12 and higher, an optional `TABLESAMPLE` clause immediately after a table reference specifies that the `COMPUTE STATS` operation only processes a specified percentage of the table data. For tables that are so large that a full `COMPUTE STATS` operation is impractical, you can use `COMPUTE STATS` with a `TABLESAMPLE` clause to extrapolate statistics from a sample of the table data. See [Table and Column Statistics](#) about the experimental stats extrapolation and sampling features.

The `COMPUTE INCREMENTAL STATS` variation is a shortcut for partitioned tables that works on a subset of partitions rather than the entire table. The incremental nature makes it suitable for large tables with many partitions, where a full `COMPUTE STATS` operation takes too long to be practical each time a partition is added or dropped. See [#unique_312](#) for full usage details.

Important:

For a particular table, use either `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS`, but never combine the two or alternate between them. If you switch from `COMPUTE STATS` to `COMPUTE INCREMENTAL STATS` during the lifetime of a table, or vice versa, drop all statistics by running `DROP STATS` before making the switch.

When you run `COMPUTE INCREMENTAL STATS` on a table for the first time, the statistics are computed again from scratch regardless of whether the table already has statistics. Therefore, expect a one-time resource-intensive operation for scanning the entire table when running `COMPUTE INCREMENTAL STATS` for the first time on a given table.

In Impala 3.0 and lower, approximately 400 bytes of metadata per column per partition are needed for caching. Tables with a big number of partitions and many columns can add up to a significant memory overhead as the metadata must be cached on the `catalogd` host and on every `impalad` host that is eligible to be a coordinator. If this metadata for all tables exceeds 2 GB, you might experience service downtime. In Impala 3.1 and higher, the issue was alleviated with an improved handling of incremental stats.

`COMPUTE INCREMENTAL STATS` only applies to partitioned tables. If you use the `INCREMENTAL` clause for an unpartitioned table, Impala automatically uses the original `COMPUTE STATS` statement. Such tables display `false` under the `Incremental stats` column of the `SHOW TABLE STATS` output.

Note:

Because many of the most performance-critical and resource-intensive operations rely on table and column statistics to construct accurate and efficient plans, `COMPUTE STATS` is an important step at the end of your ETL process. Run

COMPUTE STATS on all tables as your first step during performance tuning for slow queries, or troubleshooting for out-of-memory conditions:

- Accurate statistics help Impala construct an efficient query plan for join queries, improving performance and reducing memory usage.
- Accurate statistics help Impala distribute the work effectively for insert operations into Parquet tables, improving performance and reducing memory usage.
- Accurate statistics help Impala estimate the memory required for each query, which is important when you use resource management features, such as admission control and the YARN resource management framework. The statistics help Impala to achieve high concurrency, full utilization of available memory, and avoid contention with workloads from other Hadoop components.
- In Impala 2.8 and higher, when you run the COMPUTE STATS or COMPUTE INCREMENTAL STATS statement against a Parquet table, Impala automatically applies the query option setting MT_DOP=4 to increase the amount of intra-node parallelism during this CPU-intensive operation. See [MT_DOP Query Option](#) on page 374 for details about what this query option does and how to use it with CPU-intensive SELECT statements.

Computing stats for groups of partitions:

In Impala 2.8 and higher, you can run COMPUTE INCREMENTAL STATS on multiple partitions, instead of the entire table or one partition at a time. You include comparison operators other than = in the PARTITION clause, and the COMPUTE INCREMENTAL STATS statement applies to all partitions that match the comparison expression.

For example, the INT_PARTITIONS table contains 4 partitions. The following COMPUTE INCREMENTAL STATS statements affect some but not all partitions, as indicated by the Updated *n* partition(s) messages. The partitions that are affected depend on values in the partition key column X that match the comparison expression in the PARTITION clause.

```
show partitions int_partitions;
+-----+-----+-----+-----+-----+-----+-----+
+-----+...
| x      | #Rows | #Files | Size | Bytes Cached | Cache Replication | Format
| ...
+-----+-----+-----+-----+-----+-----+-----+
+-----+...
| 99     | -1    | 0      | 0B   | NOT CACHED   | NOT CACHED        | PARQUET
| ...
| 120    | -1    | 0      | 0B   | NOT CACHED   | NOT CACHED        | TEXT
| ...
| 150    | -1    | 0      | 0B   | NOT CACHED   | NOT CACHED        | TEXT
| ...
| 200    | -1    | 0      | 0B   | NOT CACHED   | NOT CACHED        | TEXT
| ...
| Total  | -1    | 0      | 0B   | 0B           |                    |
| ...
+-----+-----+-----+-----+-----+-----+-----+
+-----+...

compute incremental stats int_partitions partition (x < 100);
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 1 column(s). |
+-----+

compute incremental stats int_partitions partition (x in (100, 150, 200));
+-----+
| summary |
+-----+
| Updated 2 partition(s) and 1 column(s). |
+-----+
```

```

compute incremental stats int_partitions partition (x between 100 and 175);
+-----+
| summary |
+-----+
| Updated 2 partition(s) and 1 column(s). |
+-----+

compute incremental stats int_partitions partition (x in (100, 150, 200) or
x < 100);
+-----+
| summary |
+-----+
| Updated 3 partition(s) and 1 column(s). |
+-----+

compute incremental stats int_partitions partition (x != 150);
+-----+
| summary |
+-----+
| Updated 3 partition(s) and 1 column(s). |
+-----+

```

Complex type considerations:

Currently, the statistics created by the `COMPUTE STATS` statement do not include information about complex type columns. The column stats metrics for complex columns are always shown as -1. For queries involving complex type columns, Impala uses heuristics to estimate the data distribution within such columns.

HBase considerations:

`COMPUTE STATS` works for HBase tables also. The statistics gathered for HBase tables are somewhat different than for HDFS-backed tables, but that metadata is still used for optimization when HBase tables are involved in join queries.

Amazon S3 considerations:

`COMPUTE STATS` also works for tables where data resides in the Amazon Simple Storage Service (S3). See [Using Impala with Amazon S3 Object Store](#) on page 769 for details.

Performance considerations:

The statistics collected by `COMPUTE STATS` are used to optimize join queries `INSERT` operations into Parquet tables, and other resource-intensive kinds of SQL statements. See [Table and Column Statistics](#) on page 625 for details.

For large tables, the `COMPUTE STATS` statement itself might take a long time and you might need to tune its performance. The `COMPUTE STATS` statement does not work with the `EXPLAIN` statement, or the `SUMMARY` command in `impala-shell`. You can use the `PROFILE` statement in `impala-shell` to examine timing information for the statement as a whole. If a basic `COMPUTE STATS` statement takes a long time for a partitioned table, consider switching to the `COMPUTE INCREMENTAL STATS` syntax so that only newly added partitions are analyzed each time.

Examples:

This example shows two tables, T1 and T2, with a small number distinct values linked by a parent-child relationship between T1.ID and T2.PARENT. T1 is tiny, while T2 has approximately 100K rows. Initially, the statistics includes physical measurements such as the number of files, the total size, and size measurements for fixed-length columns such as with the `INT` type. Unknown values are represented by -1. After running `COMPUTE STATS` for each table, much more information is available through the `SHOW STATS` statements. If you were running a join query involving both of these tables, you would need statistics for both tables to get the most effective optimization for the query.

```
[localhost:21000] > show table stats t1;
```

Query: show table stats t1

#Rows	#Files	Size	Format
-1	1	33B	TEXT

Returned 1 row(s) in 0.02s

[localhost:21000] > show table stats t2;

Query: show table stats t2

#Rows	#Files	Size	Format
-1	28	960.00KB	TEXT

Returned 1 row(s) in 0.01s

[localhost:21000] > show column stats t1;

Query: show column stats t1

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
id	INT	-1	-1	4	4
s	STRING	-1	-1	-1	-1

Returned 2 row(s) in 1.71s

[localhost:21000] > show column stats t2;

Query: show column stats t2

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
parent	INT	-1	-1	4	4
s	STRING	-1	-1	-1	-1

Returned 2 row(s) in 0.01s

[localhost:21000] > compute stats t1;

Query: compute stats t1

summary
Updated 1 partition(s) and 2 column(s).

Returned 1 row(s) in 5.30s

[localhost:21000] > show table stats t1;

Query: show table stats t1

#Rows	#Files	Size	Format
3	1	33B	TEXT

Returned 1 row(s) in 0.01s

[localhost:21000] > show column stats t1;

Query: show column stats t1

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
id	INT	3	-1	4	4
s	STRING	3	-1	-1	-1

Returned 2 row(s) in 0.02s

[localhost:21000] > compute stats t2;

Query: compute stats t2

summary
Updated 1 partition(s) and 2 column(s).

```

+-----+
Returned 1 row(s) in 5.70s
[localhost:21000] > show table stats t2;
Query: show table stats t2
+-----+-----+-----+-----+
| #Rows | #Files | Size      | Format |
+-----+-----+-----+-----+
| 98304 | 1      | 960.00KB | TEXT  |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.03s
[localhost:21000] > show column stats t2;
Query: show column stats t2
+-----+-----+-----+-----+-----+-----+-----+
| Column | Type   | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+-----+
| parent | INT    | 3                | -1     | 4        | 4        |
| s      | STRING | 6                | -1     | 14       | 9.3      |
+-----+-----+-----+-----+-----+-----+-----+
Returned 2 row(s) in 0.01s

```

The following example shows how to use the `INCREMENTAL` clause, available in Impala 2.1.0 and higher. The `COMPUTE INCREMENTAL STATS` syntax lets you collect statistics for newly added or changed partitions, without rescanning the entire table.

```

-- Initially the table has no incremental stats, as indicated
-- 'false' under Incremental stats.
show table stats item_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
| i_category | #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+-----+
| Books      | -1    | 1      | 223.74KB | NOT CACHED  | PARQUET | false             |
| Children   | -1    | 1      | 230.05KB | NOT CACHED  | PARQUET | false             |
| Electronics | -1    | 1      | 232.67KB | NOT CACHED  | PARQUET | false             |
| Home       | -1    | 1      | 232.56KB | NOT CACHED  | PARQUET | false             |
| Jewelry     | -1    | 1      | 223.72KB | NOT CACHED  | PARQUET | false             |
| Men        | -1    | 1      | 231.25KB | NOT CACHED  | PARQUET | false             |
| Music      | -1    | 1      | 237.90KB | NOT CACHED  | PARQUET | false             |
| Shoes      | -1    | 1      | 234.90KB | NOT CACHED  | PARQUET | false             |
| Sports     | -1    | 1      | 227.97KB | NOT CACHED  | PARQUET | false             |
| Women      | -1    | 1      | 226.27KB | NOT CACHED  | PARQUET | false             |
| Total      | -1    | 10     | 2.25MB   | 0B          | PARQUET | false             |
+-----+-----+-----+-----+-----+-----+-----+

-- After the first COMPUTE INCREMENTAL STATS,
-- all partitions have stats. The first
-- COMPUTE INCREMENTAL STATS scans the whole
-- table, discarding any previous stats from
-- a traditional COMPUTE STATS statement.
compute incremental stats item_partitioned;
+-----+-----+
| summary |
+-----+-----+
| Updated 10 partition(s) and 21 column(s). |
+-----+-----+
show table stats item_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
| i_category | #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+-----+

```

```

+-----+-----+-----+-----+-----+-----+-----+
+-----+
| Books      | 1733 | 1    | 223.74KB | NOT CACHED | PARQUET | true |
| Children   | 1786 | 1    | 230.05KB | NOT CACHED | PARQUET | true |
| Electronics | 1812 | 1    | 232.67KB | NOT CACHED | PARQUET | true |
| Home       | 1807 | 1    | 232.56KB | NOT CACHED | PARQUET | true |
| Jewelry    | 1740 | 1    | 223.72KB | NOT CACHED | PARQUET | true |
| Men        | 1811 | 1    | 231.25KB | NOT CACHED | PARQUET | true |
| Music      | 1860 | 1    | 237.90KB | NOT CACHED | PARQUET | true |
| Shoes      | 1835 | 1    | 234.90KB | NOT CACHED | PARQUET | true |
| Sports     | 1783 | 1    | 227.97KB | NOT CACHED | PARQUET | true |
| Women      | 1790 | 1    | 226.27KB | NOT CACHED | PARQUET | true |
| Total      | 17957 | 10   | 2.25MB   | 0B         |         |      |
+-----+-----+-----+-----+-----+-----+-----+
+-----+

-- Add a new partition...
alter table item_partitioned add partition (i_category='Camping');
-- Add or replace files in HDFS outside of Impala,
-- rendering the stats for a partition obsolete.
!import_data_into_sports_partition.sh
refresh item_partitioned;
drop incremental stats item_partitioned partition (i_category='Sports');
-- Now some partitions have incremental stats
-- and some do not.
show table stats item_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| i_category | #Rows | #Files | Size      | Bytes Cached | Format |
| Incremental stats
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| Books      | 1733 | 1    | 223.74KB | NOT CACHED | PARQUET | true |
| Camping    | -1   | 1    | 408.02KB | NOT CACHED | PARQUET | false |
| Children   | 1786 | 1    | 230.05KB | NOT CACHED | PARQUET | true |
| Electronics | 1812 | 1    | 232.67KB | NOT CACHED | PARQUET | true |
| Home       | 1807 | 1    | 232.56KB | NOT CACHED | PARQUET | true |
| Jewelry    | 1740 | 1    | 223.72KB | NOT CACHED | PARQUET | true |
| Men        | 1811 | 1    | 231.25KB | NOT CACHED | PARQUET | true |
| Music      | 1860 | 1    | 237.90KB | NOT CACHED | PARQUET | true |
| Shoes      | 1835 | 1    | 234.90KB | NOT CACHED | PARQUET | true |
| Sports     | -1   | 1    | 227.97KB | NOT CACHED | PARQUET | false |
| Women      | 1790 | 1    | 226.27KB | NOT CACHED | PARQUET | true |
| Total      | 17957 | 11   | 2.65MB   | 0B         |         |      |
+-----+-----+-----+-----+-----+-----+-----+
+-----+

-- After another COMPUTE INCREMENTAL STATS,
-- all partitions have incremental stats, and only the 2
-- partitions without incremental stats were scanned.
compute incremental stats item_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| summary
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| Updated 2 partition(s) and 21 column(s).
+-----+-----+-----+-----+-----+-----+-----+
+-----+
show table stats item_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| i_category | #Rows | #Files | Size      | Bytes Cached | Format |
| Incremental stats
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| Books      | 1733 | 1    | 223.74KB | NOT CACHED | PARQUET | true |

```

Camping	5328	1	408.02KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	1783	1	227.97KB	NOT CACHED	PARQUET	true
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	11	2.65MB	0B		

File format considerations:

The `COMPUTE STATS` statement works with tables created with any of the file formats supported by Impala. See [How Impala Works with Hadoop File Formats](#) on page 695 for details about working with the different file formats. The following considerations apply to `COMPUTE STATS` depending on the file format of the table.

The `COMPUTE STATS` statement works with text tables with no restrictions. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with Parquet tables. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with Avro tables without restriction in Impala 2.2 and higher. In earlier releases, `COMPUTE STATS` worked only for Avro tables created through Hive, and required the `CREATE TABLE` statement to use SQL-style column names and types rather than an Avro-style schema specification.

The `COMPUTE STATS` statement works with RCFile tables with no restrictions. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with SequenceFile tables with no restrictions. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with partitioned tables, whether all the partitions use the same file format, or some partitions are defined through `ALTER TABLE` to use different file formats.

Statement type: DDL

Cancellation: Certain multi-stage statements (`CREATE TABLE AS SELECT` and `COMPUTE STATS`) can be cancelled during some stages, when running `INSERT` or `SELECT` operations internally. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

Restrictions:

Note: Prior to Impala 1.4.0, `COMPUTE STATS` counted the number of NULL values in each column and recorded that figure in the metastore database. Because Impala does not currently use the NULL count during query planning, Impala 1.4.0 and higher speeds up the `COMPUTE STATS` statement by skipping this NULL counting.

Internal details:

Behind the scenes, the `COMPUTE STATS` statement executes two statements: one to count the rows of each partition in the table (or the entire table if unpartitioned) through the `COUNT(*)` function, and another to count the approximate number of distinct values in each column through the `NDV()` function. You might see these queries in your monitoring and diagnostic displays. The same factors that affect the performance, scalability, and execution of other queries (such as parallel execution, memory usage, admission control, and timeouts) also apply to the queries run by the `COMPUTE STATS` statement.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permission for all affected files in the source directory: all files in the case of an unpartitioned table or a partitioned table in the case of

COMPUTE STATS; or all the files in partitions without incremental stats in the case of COMPUTE INCREMENTAL STATS. It must also have read and execute permissions for all relevant directories holding the data files. (Essentially, COMPUTE STATS requires the same permissions as the underlying SELECT queries it runs against the table.)

Kudu considerations:

The COMPUTE STATS statement applies to Kudu tables. Impala only computes the number of rows for the whole Kudu table, partition level row counts are not available.

Related information:

[DROP STATS Statement](#) on page 284, [SHOW TABLE STATS Statement](#) on page 406, [SHOW COLUMN STATS Statement](#) on page 408, [Table and Column Statistics](#) on page 625

CREATE DATABASE Statement

Creates a new database.

In Impala, a database is both:

- A logical construct for grouping together related tables, views, and functions within their own namespace. You might use a separate database for each application, set of related tables, or round of experimentation.
- A physical construct represented by a directory tree in HDFS. Tables (internal tables), partitions, and data files are all located under this directory. You can perform HDFS-level operations such as backing it up and measuring space usage, or remove it with a DROP DATABASE statement.

Syntax:

```
CREATE (DATABASE|SCHEMA) [IF NOT EXISTS] database_name [COMMENT
'database_comment']
[LOCATION hdfs_path];
```

Statement type: DDL

Usage notes:

A database is physically represented as a directory in HDFS, with a filename extension .db, under the main Impala data directory. If the associated HDFS directory does not exist, it is created for you. All databases and their associated directories are top-level objects, with no physical or logical nesting.

After creating a database, to make it the current database within an `impala-shell` session, use the USE statement. You can refer to tables in the current database without prepending any qualifier to their names.

When you first connect to Impala through `impala-shell`, the database you start in (before issuing any CREATE DATABASE or USE statements) is named `default`.

Impala includes another predefined database, `_impala_builtins`, that serves as the location for the [built-in functions](#). To see the built-in functions, use a statement like the following:

```
show functions in _impala_builtins;
show functions in _impala_builtins like '*substring*';
```

After creating a database, your `impala-shell` session or another `impala-shell` connected to the same node can immediately access that database. To access the database through the Impala daemon on a different node, issue the `INVALIDATE METADATA` statement first while connected to that other node.

Setting the LOCATION attribute for a new database is a way to work with sets of files in an HDFS directory structure outside the default Impala data directory, as opposed to setting the LOCATION attribute for each individual table.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

Hive considerations:

When you create a database in Impala, the database can also be used by Hive. When you create a database in Hive, issue an `INVALIDATE METADATA` statement in Impala to make Impala permanently aware of the new database.

The `SHOW DATABASES` statement lists all databases, or the databases whose name matches a wildcard pattern. In Impala 2.5 and higher, the `SHOW DATABASES` output includes a second column that displays the associated comment, if any, for each database.

Amazon S3 considerations:

To specify that any tables created within a database reside on the Amazon S3 system, you can include an `s3a://` prefix on the `LOCATION` attribute. In Impala 2.6 and higher, Impala automatically creates any required folders as the databases, tables, and partitions are created, and removes them when they are dropped.

In Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about reading and writing S3 data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for the parent HDFS directory under which the database is located.

Examples:

```
create database first_db;
use first_db;
create table t1 (x int);

create database second_db;
use second_db;
-- Each database has its own namespace for tables.
-- You can reuse the same table names in each database.
create table t1 (s string);

create database temp;

-- You can either USE a database after creating it,
-- or qualify all references to the table name with the name of the
  database.
-- Here, tables T2 and T3 are both created in the TEMP database.

create table temp.t2 (x int, y int);
use database temp;
create table t3 (s string);

-- You cannot drop a database while it is selected by the USE statement.
drop database temp;
ERROR: AnalysisException: Cannot drop current default database: temp

-- The always-available database 'default' is a convenient one to USE
-- before dropping a database you created.
use default;

-- Before dropping a database, first drop all the tables inside it,
-- or in Impala 2.3 and higher use the CASCADE clause.
drop database temp;
ERROR: ImpalaRuntimeException: Error making 'dropDatabase' RPC to Hive
  Metastore:
CAUSED BY: InvalidOperationException: Database temp is not empty
show tables in temp;
```

```

+-----+
|  name  |
+-----+
|   t3   |
+-----+

-- Impala 2.3 and higher:
drop database temp cascade;

-- Earlier releases:
drop table temp.t3;
drop database temp;

```

Related information:

[Overview of Impala Databases](#) on page 203, [DROP DATABASE Statement](#) on page 280, [USE Statement](#) on page 421, [SHOW DATABASES](#) on page 401, [Overview of Impala Tables](#) on page 206

CREATE FUNCTION Statement

Creates a user-defined function (UDF), which you can use to implement custom logic during SELECT or INSERT operations.

Syntax:

The syntax is different depending on whether you create a scalar UDF, which is called once for each row and implemented by a single function, or a user-defined aggregate function (UDA), which is implemented by multiple functions that compute intermediate results across sets of rows.

In Impala 2.5 and higher, the syntax is also different for creating or dropping scalar Java-based UDFs. The statements for Java UDFs use a new syntax, without any argument types or return type specified. Java-based UDFs created using the new syntax persist across restarts of the Impala catalog server, and can be shared transparently between Impala and Hive.

To create a persistent scalar C++ UDF with CREATE FUNCTION:

```

CREATE FUNCTION [IF NOT EXISTS]
  [db_name.]function_name([arg_type[, arg_type...])
  RETURNS return_type
  LOCATION 'hdfs_path_to_dot_so'
  SYMBOL='symbol_name'

```

To create a persistent Java UDF with CREATE FUNCTION:

```

CREATE FUNCTION [IF NOT EXISTS] [db_name.]function_name
  LOCATION 'hdfs_path_to_jar'
  SYMBOL='class_name'

```

To create a persistent UDA, which must be written in C++, issue a CREATE AGGREGATE FUNCTION statement:

```

CREATE [AGGREGATE] FUNCTION [IF NOT EXISTS]
  [db_name.]function_name([arg_type[, arg_type...])
  RETURNS return_type
  [INTERMEDIATE type_spec]
  LOCATION 'hdfs_path'
  [INIT_FN='function']
  [UPDATE_FN='function']
  [MERGE_FN='function']
  [PREPARE_FN='function']
  [CLOSEFN='function']
  [SERIALIZE_FN='function']
  [FINALIZE_FN='function']

```

Statement type: DDL

Varargs notation:

Note:

Variable-length argument lists are supported for C++ UDFs, but currently not for Java UDFs.

If the underlying implementation of your function accepts a variable number of arguments:

- The variable arguments must go last in the argument list.
- The variable arguments must all be of the same type.
- You must include at least one instance of the variable arguments in every function call invoked from SQL.
- You designate the variable portion of the argument list in the `CREATE FUNCTION` statement by including `...` immediately after the type name of the first variable argument. For example, to create a function that accepts an `INT` argument, followed by a `BOOLEAN`, followed by one or more `STRING` arguments, your `CREATE FUNCTION` statement would look like:

```
CREATE FUNCTION func_name (INT, BOOLEAN, STRING ...)
  RETURNS type LOCATION 'path' SYMBOL='entry_point';
```

See [Variable-Length Argument Lists](#) on page 595 for how to code a C++ UDF to accept variable-length argument lists.

Scalar and aggregate functions:

The simplest kind of user-defined function returns a single scalar value each time it is called, typically once for each row in the result set. This general kind of function is what is usually meant by UDF. User-defined aggregate functions (UDAs) are a specialized kind of UDF that produce a single value based on the contents of multiple rows. You usually use UDAs in combination with a `GROUP BY` clause to condense a large result set into a smaller one, or even a single row summarizing column values across an entire table.

You create UDAs by using the `CREATE AGGREGATE FUNCTION` syntax. The clauses `INIT_FN`, `UPDATE_FN`, `MERGE_FN`, `SERIALIZE_FN`, `FINALIZE_FN`, and `INTERMEDIATE` only apply when you create a UDA rather than a scalar UDF.

The `*_FN` clauses specify functions to call at different phases of function processing.

- **Initialize:** The function you specify with the `INIT_FN` clause does any initial setup, such as initializing member variables in internal data structures. This function is often a stub for simple UDAs. You can omit this clause and a default (no-op) function will be used.
- **Update:** The function you specify with the `UPDATE_FN` clause is called once for each row in the original result set, that is, before any `GROUP BY` clause is applied. A separate instance of the function is called for each different value returned by the `GROUP BY` clause. The final argument passed to this function is a pointer, to which you write an updated value based on its original value and the value of the first argument.
- **Merge:** The function you specify with the `MERGE_FN` clause is called an arbitrary number of times, to combine intermediate values produced by different nodes or different threads as Impala reads and processes data files in parallel. The final argument passed to this function is a pointer, to which you write an updated value based on its original value and the value of the first argument.
- **Serialize:** The function you specify with the `SERIALIZE_FN` clause frees memory allocated to intermediate results. It is required if any memory was allocated by the `Allocate` function in the `Init`, `Update`, or `Merge` functions, or if the intermediate type contains any pointers. See [the UDA code samples](#) for details.
- **Finalize:** The function you specify with the `FINALIZE_FN` clause does any required teardown for resources acquired by your UDF, such as freeing memory, closing file handles if you explicitly opened any files, and so on. This function is often a stub for simple UDAs. You can omit this clause and a default (no-op) function will be used. It is required in UDAs where the final return type is different than the intermediate type, or if any memory was allocated by the `Allocate` function in the `Init`, `Update`, or `Merge` functions. See [the UDA code samples](#) for details.

If you use a consistent naming convention for each of the underlying functions, Impala can automatically determine the names based on the first such clause, so the others are optional.

For end-to-end examples of UDAs, see [User-Defined Functions \(UDFs\)](#) on page 588.

Complex type considerations:

Currently, Impala UDFs cannot accept arguments or return values of the Impala complex types (STRUCT, ARRAY, or MAP).

Usage notes:

- When authorization is enabled, the `CREATE FUNCTION` statement requires:
 - The `CREATE` privilege on the database.
 - The `ALL` privilege on `URI` where `URI` is the value you specified for the `LOCATION` in the `CREATE FUNCTION` statement.
- You can write Impala UDFs in either C++ or Java. C++ UDFs are new to Impala, and are the recommended format for high performance utilizing native code. Java-based UDFs are compatible between Impala and Hive, and are most suited to reusing existing Hive UDFs. (Impala can run Java-based Hive UDFs but not Hive UDAs.)
- Impala 2.5 introduces UDF improvements to persistence for both C++ and Java UDFs, and better compatibility between Impala and Hive for Java UDFs. See [User-Defined Functions \(UDFs\)](#) on page 588 for details.
- The body of the UDF is represented by a `.so` or `.jar` file, which you store in HDFS and the `CREATE FUNCTION` statement distributes to each Impala node.
- Impala calls the underlying code during SQL statement evaluation, as many times as needed to process all the rows from the result set. All UDFs are assumed to be deterministic, that is, to always return the same result when passed the same argument values. Impala might or might not skip some invocations of a UDF if the result value is already known from a previous call. Therefore, do not rely on the UDF being called a specific number of times, and do not return different result values based on some external factor such as the current time, a random number function, or an external data source that could be updated while an Impala query is in progress.
- The names of the function arguments in the UDF are not significant, only their number, positions, and data types.
- You can overload the same function name by creating multiple versions of the function, each with a different argument signature. For security reasons, you cannot make a UDF with the same name as any built-in function.
- In the UDF code, you represent the function return result as a `struct`. This `struct` contains 2 fields. The first field is a `boolean` representing whether the value is `NULL` or not. (When this field is `true`, the return value is interpreted as `NULL`.) The second field is the same type as the specified function return type, and holds the return value when the function returns something other than `NULL`.
- In the UDF code, you represent the function arguments as an initial pointer to a UDF context structure, followed by references to zero or more `structs`, corresponding to each of the arguments. Each `struct` has the same 2 fields as with the return value, a `boolean` field representing whether the argument is `NULL`, and a field of the appropriate type holding any non-`NULL` argument value.
- For sample code and build instructions for UDFs, see the sample UDFs in the Impala github repo.
- Because the file representing the body of the UDF is stored in HDFS, it is automatically available to all the Impala nodes. You do not need to manually copy any UDF-related files between servers.
- Because Impala currently does not have any `ALTER FUNCTION` statement, if you need to rename a function, move it to a different database, or change its signature or other properties, issue a `DROP FUNCTION` statement for the original function followed by a `CREATE FUNCTION` with the desired properties.
- Because each UDF is associated with a particular database, either issue a `USE` statement before doing any `CREATE FUNCTION` statements, or specify the name of the function as `db_name.function_name`.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

Compatibility:

Impala can run UDFs that were created through Hive, as long as they refer to Impala-compatible data types (not composite or nested column types). Hive can run Java-based UDFs that were created through Impala, but not Impala UDFs written in C++.

The Hive `current_user()` function cannot be called from a Java UDF through Impala.

Persistence:

In Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to Impala 2.5 the requirement to reload functions after a restart applied to both C++ and Java functions.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

For additional examples of all kinds of user-defined functions, see [User-Defined Functions \(UDFs\)](#) on page 588.

The following example shows how to take a Java jar file and make all the functions inside one of its classes into UDFs under a single (overloaded) function name in Impala. Each `CREATE FUNCTION` or `DROP FUNCTION` statement applies to all the overloaded Java functions with the same name. This example uses the signatureless syntax for `CREATE FUNCTION` and `DROP FUNCTION`, which is available in Impala 2.5 and higher.

At the start, the jar file is in the local filesystem. Then it is copied into HDFS, so that it is available for Impala to reference through the `CREATE FUNCTION` statement and queries that refer to the Impala function name.

```
$ jar -tvf udf-examples.jar
 0 Mon Feb 22 04:06:50 PST 2016 META-INF/
122 Mon Feb 22 04:06:48 PST 2016 META-INF/MANIFEST.MF
 0 Mon Feb 22 04:06:46 PST 2016 org/
 0 Mon Feb 22 04:06:46 PST 2016 org/apache/
 0 Mon Feb 22 04:06:46 PST 2016 org/apache/impala/
2460 Mon Feb 22 04:06:46 PST 2016 org/apache/impala/
IncompatibleUdfTest.class
 541 Mon Feb 22 04:06:46 PST 2016 org/apache/impala/TestUdfException.class
3438 Mon Feb 22 04:06:46 PST 2016 org/apache/impala/JavaUdfTest.class
5872 Mon Feb 22 04:06:46 PST 2016 org/apache/impala/TestUdf.class
...
$ hdfs dfs -put udf-examples.jar /user/impala/udfs
$ hdfs dfs -ls /user/impala/udfs
Found 2 items
-rw-r--r--  3 jrussell supergroup          853 2015-10-09 14:05 /user/impala/
udfs/hello_world.jar
-rw-r--r--  3 jrussell supergroup       7366 2016-06-08 14:25 /user/impala/
udfs/udf-examples.jar
```

In `impala-shell`, the `CREATE FUNCTION` refers to the HDFS path of the jar file and the fully qualified class name inside the jar. Each of the functions inside the class becomes an Impala function, each one overloaded under the specified Impala function name.

```
[localhost:21000] > create function testudf location '/user/impala/udfs/udf-
examples.jar' symbol='org.apache.impala.TestUdf';
[localhost:21000] > show functions;
+-----+-----+-----+-----+
+-----+
| return type | signature                                | binary type | is
persistent |
+-----+-----+-----+-----+
+-----+
```

BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN, BOOLEAN)	JAVA	true
DOUBLE	testudf(DOUBLE)	JAVA	true
DOUBLE	testudf(DOUBLE, DOUBLE)	JAVA	true
DOUBLE	testudf(DOUBLE, DOUBLE, DOUBLE)	JAVA	true
FLOAT	testudf(FLOAT)	JAVA	true
FLOAT	testudf(FLOAT, FLOAT)	JAVA	true
FLOAT	testudf(FLOAT, FLOAT, FLOAT)	JAVA	true
INT	testudf(INT)	JAVA	true
DOUBLE	testudf(INT, DOUBLE)	JAVA	true
INT	testudf(INT, INT)	JAVA	true
INT	testudf(INT, INT, INT)	JAVA	true
SMALLINT	testudf(SMALLINT)	JAVA	true
SMALLINT	testudf(SMALLINT, SMALLINT)	JAVA	true
SMALLINT	testudf(SMALLINT, SMALLINT, SMALLINT)	JAVA	true
STRING	testudf(STRING)	JAVA	true
STRING	testudf(STRING, STRING)	JAVA	true
STRING	testudf(STRING, STRING, STRING)	JAVA	true
TINYINT	testudf(TINYINT)	JAVA	true

These are all simple functions that return their single arguments, or sum, concatenate, and so on their multiple arguments. Impala determines which overloaded function to use based on the number and types of the arguments.

```

insert into bigint_x values (1), (2), (4), (3);
select testudf(x) from bigint_x;
+-----+
| udfs.testudf(x) |
+-----+
| 1                |
| 2                |
| 4                |
| 3                |
+-----+

insert into int_x values (1), (2), (4), (3);
select testudf(x, x+1, x*x) from int_x;
+-----+

```

```

| udfs.testudf(x, x + 1, x * x) |
+-----+
| 4 |
| 9 |
| 25 |
| 16 |
+-----+

select testudf(x) from string_x;
+-----+
| udfs.testudf(x) |
+-----+
| one |
| two |
| four |
| three |
+-----+

select testudf(x,x) from string_x;
+-----+
| udfs.testudf(x, x) |
+-----+
| oneone |
| twotwo |
| fourfour |
| threethree |
+-----+

```

The previous example used the same Impala function name as the name of the class. This example shows how the Impala function name is independent of the underlying Java class or function names. A second `CREATE FUNCTION` statement results in a set of overloaded functions all named `my_func`, to go along with the overloaded functions all named `testudf`.

```

create function my_func location '/user/impala/udfs/udf-examples.jar'
    symbol='org.apache.impala.TestUdf';

show functions;
+-----+-----+-----+-----+
| return type | signature | binary type | is |
| persistent | | | |
+-----+-----+-----+-----+
| BIGINT | my_func(BIGINT) | JAVA | true |
| BOOLEAN | my_func(BOOLEAN) | JAVA | true |
| BOOLEAN | my_func(BOOLEAN, BOOLEAN) | JAVA | true |
| ... | | | |
| BIGINT | testudf(BIGINT) | JAVA | true |
| BOOLEAN | testudf(BOOLEAN) | JAVA | true |
| BOOLEAN | testudf(BOOLEAN, BOOLEAN) | JAVA | true |
| ... | | | |

```

The corresponding `DROP FUNCTION` statement with no signature drops all the overloaded functions with that name.

```
drop function my_func;
```

```

show functions;
+-----+-----+-----+-----+
| return type | signature | binary type | is
persistent |          |             |
+-----+-----+-----+-----+
| BIGINT      | testudf(BIGINT) | JAVA      | true
| BOOLEAN    | testudf(BOOLEAN) | JAVA      | true
| BOOLEAN    | testudf(BOOLEAN, BOOLEAN) | JAVA      | true
...

```

The signatureless `CREATE FUNCTION` syntax for Java UDFs ensures that the functions shown in this example remain available after the Impala service (specifically, the Catalog Server) are restarted.

Related information:

[User-Defined Functions \(UDFs\)](#) on page 588 for more background information, usage instructions, and examples for Impala UDFs; [DROP FUNCTION Statement](#) on page 282

CREATE ROLE Statement (Impala 2.0 or higher only)

The `CREATE ROLE` statement creates a role to which privileges can be granted. Privileges can be granted to roles, which can then be assigned to users. A user that has been assigned a role will only be able to exercise the privileges of that role. Only users that have administrative privileges can create/drop roles.

Syntax:

```
CREATE ROLE role_name
```

Required privileges:

Only administrative users for Ranger can use this statement.

Compatibility:

Impala makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Hive, and Hive makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Impala.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Impala Authorization](#) on page 83, [GRANT Statement \(Impala 2.0 or higher only\)](#) on page 294, [REVOKE Statement \(Impala 2.0 or higher only\)](#) on page 315, [DROP ROLE Statement \(Impala 2.0 or higher only\)](#) on page 284, [SHOW Statement](#) on page 395

CREATE TABLE Statement

Creates a new table and specifies its characteristics. While creating a table, you optionally specify aspects such as:

- Whether the table is internal or external.
- The columns and associated data types.
- The columns used for physically partitioning the data.
- The file format for data files.
- The HDFS directory where the data files are located.

Syntax:

The general syntax for creating a table and specifying its columns is as follows:

Explicit column definitions:

```
CREATE [EXTERNAL] TABLE [IF NOT EXISTS] [db_name.]table_name
  (col_name data_type
   [constraint_specification]
   [COMMENT 'col_comment']
   [, ...]
  )
[PARTITIONED BY (col_name data_type [COMMENT 'col_comment'], ...)]
[SORT BY ([column [, column ...]])]
[COMMENT 'table_comment']
[ROW FORMAT row_format]
[WITH SERDEPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
[STORED AS file_format]
[LOCATION 'hdfs_path']
[CACHED IN 'pool_name' [WITH REPLICATION = integer] | UNCACHED]
[TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
```

CREATE TABLE AS SELECT:

```
CREATE [EXTERNAL] TABLE [IF NOT EXISTS] db_name.table_name
[PARTITIONED BY (col_name[, ...])]
[SORT BY ([column [, column ...]])]
[COMMENT 'table_comment']
[ROW FORMAT row_format]
[WITH SERDEPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
[STORED AS ctas_file_format]
[LOCATION 'hdfs_path']
  [CACHED IN 'pool_name' [WITH REPLICATION = integer] | UNCACHED]
[TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
AS
select_statement
```

primitive_type:

```
TINYINT
| SMALLINT
| INT
| BIGINT
| BOOLEAN
| FLOAT
| DOUBLE
| DECIMAL
| STRING
| CHAR
| VARCHAR
| TIMESTAMP
```

complex_type:

```
struct_type
| array_type
| map_type
```

```
struct_type: STRUCT < name : primitive_or_complex_type [COMMENT
'comment_string'], ... >
```

```
array_type: ARRAY < primitive_or_complex_type >
```

```
map_type: MAP < primitive_type, primitive_or_complex_type >
```

```

constraint_specification:
    PRIMARY KEY (col_name, ...) [DISABLE] [NOVALIDATE] [RELY],
    [foreign_key_specification, ...]

foreign_key_specification:
    FOREIGN KEY (col_name, ...) REFERENCES table_name(col_name, ...) [DISABLE]
    [NOVALIDATE] [RELY]

row_format:
    DELIMITED [FIELDS TERMINATED BY 'char' [ESCAPED BY 'char']]
    [LINES TERMINATED BY 'char']

file_format:
    PARQUET
    | TEXTFILE
    | AVRO
    | SEQUENCEFILE
    | RCFILE

ctas_file_format:
    PARQUET
    | TEXTFILE

```

Column definitions inferred from data file:

```

CREATE [EXTERNAL] TABLE [IF NOT EXISTS] [db_name.]table_name
    LIKE PARQUET 'hdfs_path_of_parquet_file'
    [PARTITIONED BY (col_name data_type [COMMENT 'col_comment'], ...)]
    [SORT BY ([column [, column ...]])]
    [COMMENT 'table_comment']
    [ROW FORMAT row_format]
    [WITH SERDEPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
    [STORED AS file_format]
    [LOCATION 'hdfs_path']
    [CACHED IN 'pool_name' [WITH REPLICATION = integer] | UNCACHED]
    [TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]

data_type:
    primitive_type
    | array_type
    | map_type
    | struct_type

```

Internal Kudu tables:

```

CREATE TABLE [IF NOT EXISTS] [db_name.]table_name
    (col_name data_type
    [kudu_column_attribute ...]
    [COMMENT 'col_comment']
    [, ...]
    [PRIMARY KEY (col_name[, ...])])
    [PARTITION BY kudu_partition_clause]
    [COMMENT 'table_comment']
    STORED AS KUDU
    [TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]

```

Kudu column attributes:

```

    PRIMARY KEY
    | [NOT] NULL
    | ENCODING codec

```

```

| COMPRESSION algorithm
| DEFAULT constant
| BLOCK_SIZE number

```

kudu_partition_clause:

```

kudu_partition_clause ::= [ hash_clause [, ...] ] [, range_clause ]

hash_clause ::=
  HASH [ (pk_col [, ...]) ]
  PARTITIONS n

range_clause ::=
  RANGE [ (pk_col [, ...]) ]
  (
    {
      PARTITION constant_expression range_comparison_operator
    VALUES range_comparison_operator constant_expression
      | PARTITION VALUE = constant_expression_or_tuple
    }
    [, ...]
  )

range_comparison_operator ::= { < | <= }

```

External Kudu tables:

In Impala 3.4 and earlier, you can create an external Kudu table based on a pre-existing Kudu schema using the table property 'kudu.table_name'='internal_kudu_name'.

```

CREATE EXTERNAL TABLE [IF NOT EXISTS] [db_name.]table_name
  [COMMENT 'col_comment']
  STORED AS KUDU
  [TBLPROPERTIES ('kudu.table_name'='internal_kudu_name',
    'key1'='value1',...)]

```

Alternatively, in Impala 3.4 and higher, you can also create an external Kudu table as follows:

```

CREATE EXTERNAL TABLE [IF NOT EXISTS] [db_name.]table_name
  (col_name data_type
  [kudu_column_attribute ...]
  [COMMENT 'col_comment']
  [, ...]
  [PRIMARY KEY (col_name[, ...])])
  )
  [PARTITION BY kudu_partition_clause]
  [COMMENT 'table_comment']
  STORED AS KUDU
  [TBLPROPERTIES ('external.table.purge'='true', 'key1'='value1',...)]

```

- Use a Hive metastore (HMS) 3 or later.
- Provide column specifications to define the schema when you create the table, similar to creating an internal table.
- Omit the kudu.table_name table property as there is no pre-existing schema.
- Include the required external.table.purge property.

Only the schema metadata is stored in HMS when you create an external table; however, using this create table syntax, drop table on the Kudu external table deletes the data stored outside HMS in Kudu as well as the metadata (schema) inside HMS. Likewise, renaming the table changes the name of the table in HMS and in Kudu. Kudu synchronizes changes to the actual data and metadata; consequently, operations such as dropping a table or altering a table name simulate internal table operations.

CREATE TABLE AS SELECT for Kudu tables:

```
CREATE TABLE [IF NOT EXISTS] db_name.table_name
  [PRIMARY KEY (col_name[, ...])]
  [PARTITION BY kudu_partition_clause]
  [COMMENT 'table_comment']
  STORED AS KUDU
  [TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
AS
  select_statement
```

Statement type: DDL**Column definitions:**

Depending on the form of the CREATE TABLE statement, the column definitions are required or not allowed.

With the CREATE TABLE AS SELECT and CREATE TABLE LIKE syntax, you do not specify the columns at all; the column names and types are derived from the source table, query, or data file.

With the basic CREATE TABLE syntax, you must list one or more columns, its name, type, optionally constraints, and optionally a comment, in addition to any columns used as partitioning keys. There is one exception where the column list is not required: when creating an Avro table with the STORED AS AVRO clause, you can omit the list of columns and specify the same metadata as part of the TBLPROPERTIES clause.

Constraints:

Constraints are advisory and intended for estimating cardinality during query planning in a future release; there is no attempt to enforce constraints. Add primary and foreign key information after column definitions. Do not include a constraint name; the constraint name is generated internally as a UUID. The following constraint states are supported:

- DISABLE
- NOVALIDATE
- RELY

The ENABLE, VALIDATE, and NORELY options are not supported. The foreign key must be defined as the primary key in the referenced table.

Constraint examples:

```
CREATE TABLE pk(col1 INT, col2 STRING, PRIMARY KEY(col1, col2));
```

```
CREATE TABLE fk(id INT, col1 INT, col2 STRING, PRIMARY KEY(id),
  FOREIGN KEY(col1, col2) REFERENCES pk(col1, col2));
```

```
CREATE TABLE pk(id INT, PRIMARY KEY(id) DISABLE, NOVALIDATE, RELY);
```

```
CREATE TABLE fk(id INT, col1 INT, col2 STRING, PRIMARY KEY(id),
  FOREIGN KEY(col1, col2) REFERENCES pk(col1, col2));
```

Complex type considerations:

The Impala complex types (STRUCT, ARRAY, or MAP) are available in Impala 2.3 and higher. Because you can nest these types (for example, to make an array of maps or a struct with an array field), these types are also sometimes referred to as nested types. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for usage details.

Impala can create tables containing complex type columns, with any supported file format. Because currently Impala can only query complex type columns in Parquet tables, creating tables with complex type columns and other file formats such as text is of limited use. For example, you might create a text table including some columns with complex types with Impala, and use Hive as part of your to ingest the nested type data and copy it to an identical Parquet table. Or you might create a partitioned table containing complex type columns using one file format, and use

`ALTER TABLE` to change the file format of individual partitions to Parquet; Impala can then query only the Parquet-format partitions in that table.

Partitioned tables can contain complex type columns. All the partition key columns must be scalar types.

Internal and external tables (**EXTERNAL** and **LOCATION** clauses):

By default, Impala creates an internal table, where Impala manages the underlying data files for the table, and physically deletes the data files when you drop the table. If you specify the **EXTERNAL** clause, Impala treats the table as an “external” table, where the data files are typically produced outside Impala and queried from their original locations in HDFS, and Impala leaves the data files in place when you drop the table. For details about internal and external tables, see [Overview of Impala Tables](#) on page 206.

Typically, for an external table you include a **LOCATION** clause to specify the path to the HDFS directory where Impala reads and writes files for the table. For example, if your data pipeline produces Parquet files in the HDFS directory `/user/etl/destination`, you might create an external table as follows:

```
CREATE EXTERNAL TABLE external_parquet (c1 INT, c2 STRING, c3 TIMESTAMP)
  STORED AS PARQUET LOCATION '/user/etl/destination';
```

Although the **EXTERNAL** and **LOCATION** clauses are often specified together, **LOCATION** is optional for external tables, and you can also specify **LOCATION** for internal tables. The difference is all about whether Impala “takes control” of the underlying data files and moves them when you rename the table, or deletes them when you drop the table. For more about internal and external tables and how they interact with the **LOCATION** attribute, see [Overview of Impala Tables](#) on page 206.

Partitioned tables (**PARTITIONED BY** clause):

The **PARTITIONED BY** clause divides the data files based on the values from one or more specified columns. Impala queries can use the partition metadata to minimize the amount of data that is read from disk or transmitted across the network, particularly during join queries. For details about partitioning, see [Partitioning for Impala Tables](#) on page 685.

Note:

All Kudu tables require partitioning, which involves different syntax than non-Kudu tables. See the **PARTITION BY** clause, rather than **PARTITIONED BY**, for Kudu tables.

In Impala 2.10 and higher, the **PARTITION BY** clause is optional for Kudu tables. If the clause is omitted, Impala automatically constructs a single partition that is not connected to any column. Because such a table cannot take advantage of Kudu features for parallelized queries and query optimizations, omitting the **PARTITION BY** clause is only appropriate for small lookup tables.

Prior to Impala 2.5, you could use a partitioned table as the source and copy data from it, but could not specify any partitioning clauses for the new table. In Impala 2.5 and higher, you can now use the **PARTITIONED BY** clause with a `CREATE TABLE AS SELECT` statement. See the examples under the following discussion of the `CREATE TABLE AS SELECT` syntax variation.

Sorted tables (**SORT BY** clause):

The optional **SORT BY** clause lets you specify zero or more columns that are sorted in ascending order in the data files created by each Impala `INSERT` or `CREATE TABLE AS SELECT` operation. There are two orderings to choose from: **LEXICAL** and **ZORDER**. The default ordering is **LEXICAL**, which can be used for any number of sort columns. **ZORDER** can only be used to sort more than one column.

Creating data files that are sorted is most useful for Parquet tables, where the metadata stored inside each file includes the minimum and maximum values for each column in the file. (The statistics apply to each row group within the file; for simplicity, Impala writes a single row group in each file.) Grouping data values together in relatively narrow ranges within each data file makes it possible for Impala to quickly skip over data files that do not contain value ranges indicated in the **WHERE** clause of a query, and can improve the effectiveness of Parquet encoding and compression.

This clause is not applicable for Kudu tables or HBase tables. Although it works for other HDFS file formats besides Parquet, the more efficient layout is most evident with Parquet tables, because each Parquet data file includes statistics about the data values in that file.

The `SORT BY` columns cannot include any partition key columns for a partitioned table, because those column values are not represented in the underlying data files.

Because data files can arrive in Impala tables by mechanisms that do not respect the `SORT BY` clause, such as `LOAD DATA` or ETL tools that create HDFS files, Impala does not guarantee or rely on the data being sorted. The sorting aspect is only used to create a more efficient layout for Parquet files generated by Impala, which helps to optimize the processing of those Parquet files during Impala queries. During an `INSERT` or `CREATE TABLE AS SELECT` operation, the sorting occurs when the `SORT BY` clause applies to the destination table for the data, regardless of whether the source table has a `SORT BY` clause.

For example, when creating a table intended to contain census data, you might define sort columns such as last name and state. If a data file in this table contains a narrow range of last names, for example from Smith to Smythe, Impala can quickly detect that this data file contains no matches for a `WHERE` clause such as `WHERE last_name = 'Jones'` and avoid reading the entire file.

```
CREATE TABLE census_data (last_name STRING, first_name STRING, state STRING,
    address STRING)
    SORT BY LEXICAL (last_name, state)
    STORED AS PARQUET;
```

Likewise, if an existing table contains data without any sort order, you can reorganize the data in a more efficient way by using `INSERT` or `CREATE TABLE AS SELECT` to copy that data into a new table with a `SORT BY` clause:

```
CREATE TABLE sorted_census_data
    SORT BY (last_name, state)
    STORED AS PARQUET
    AS SELECT last_name, first_name, state, address
    FROM unsorted_census_data;
```

The metadata for the `SORT BY` clause is stored in the `TBLPROPERTIES` fields for the table. Other SQL engines that can interoperate with Impala tables, such as Hive and Spark SQL, do not recognize this property when inserting into a table that has a `SORT BY` clause.

Transactional tables:

In the version 3.3 and higher, when integrated with Hive 3, Impala can create, read, and insert into transactional tables.

To create a table that supports transactions, use the `TBLPROPERTIES` clause and set the `'transactional'` and `'transactional_properties'` as below. Currently, Impala only supports insert-only transactional tables.

```
TBLPROPERTIES('transactional'='true',
    'transactional_properties'='insert_only')
```

When integrated with Hive3 and the `DEFAULT_TRANSACTIONAL_TYPE` query option is set to `INSERT_ONLY`, tables are created as insert-only transactional table by default.

Transactional tables are not supported for Kudu and HBase.

Kudu considerations:

Because Kudu tables do not support clauses related to HDFS and S3 data files and partitioning mechanisms, the syntax associated with the `STORED AS KUDU` clause is shown separately in the above syntax descriptions. Kudu tables have their own syntax for `CREATE TABLE`, `CREATE EXTERNAL TABLE`, and `CREATE TABLE AS SELECT`. Prior to Impala 2.10, all internal Kudu tables require a `PARTITION BY` clause, different than the `PARTITIONED BY` clause for HDFS-backed tables.

Here are some examples of creating empty Kudu tables:

```
-- Single partition. Only for Impala 2.10 and higher.
-- Only suitable for small lookup tables.
CREATE TABLE kudu_no_partition_by_clause
(
  id bigint PRIMARY KEY, s STRING, b BOOLEAN
)
STORED AS KUDU;

-- Single-column primary key.
CREATE TABLE kudu_t1 (id BIGINT PRIMARY key, s STRING, b BOOLEAN)
  PARTITION BY HASH (id) PARTITIONS 20 STORED AS KUDU;

-- Multi-column primary key.
CREATE TABLE kudu_t2 (id BIGINT, s STRING, b BOOLEAN, PRIMARY KEY (id,s))
  PARTITION BY HASH (s) PARTITIONS 30 STORED AS KUDU;

-- Meaningful primary key column is good for range partitioning.
CREATE TABLE kudu_t3 (id BIGINT, year INT, s STRING,
  b BOOLEAN, PRIMARY KEY (id,year))
  PARTITION BY HASH (id) PARTITIONS 20,
  RANGE (year) (PARTITION 1980 <= VALUES < 1990,
    PARTITION 1990 <= VALUES < 2000,
    PARTITION VALUE = 2001,
    PARTITION 2001 < VALUES)
  STORED AS KUDU;
```

Here is an example of creating an external Kudu table based on an pre-existing table identified by the table property:

```
-- Inherits column definitions from original table.
-- For tables created through Impala, the kudu.table_name property
-- comes from DESCRIBE FORMATTED output from the original table.
CREATE EXTERNAL TABLE external_t1 STORED AS KUDU
  TBLPROPERTIES ('kudu.table_name'='kudu_tbl_created_via_api');
```

In Impala 3.4 and higher, by default HMS implicitly translates internal Kudu tables to external Kudu tables with the 'external.table.purge' property set to true. You can explicitly create such external Kudu tables similar to the way you create internal Kudu tables. You must set the table property 'external.table.purge' to true. Here is an example of creating an external Kudu table:

```
CREATE EXTERNAL TABLE myextkudutbl (
  id int PRIMARY KEY,
  name string)
  PARTITION BY HASH PARTITIONS 8
  STORED AS KUDU
  TBLPROPERTIES ('external.table.purge'='true');
```

Operations on the resulting external table in Impala, HMS, and Kudu table metadata is synchronized. HMS-Kudu integration does not need to be enabled for external table synchronization. Such synchronized tables behave similar to internal tables. For example, dropping a table removes the underlying Kudu table data as well as the table metadata in HMS.

If you want to drop only the HMS metadata and not drop the Kudu table, you can set `external.table.purge` to false, as shown in the following example:

```
ALTER TABLE myextkudutbl set
tblproperties('external.table.purge'='false');
```

Here is an example of CREATE TABLE AS SELECT syntax for a Kudu table:

```
-- The CTAS statement defines the primary key and partitioning scheme.
-- The rest of the column definitions are derived from the select list.
CREATE TABLE ctas_t1
  PRIMARY KEY (id) PARTITION BY HASH (id) PARTITIONS 10
  STORED AS KUDU
  AS SELECT id, s FROM kudu_t1;
```

The following CREATE TABLE clauses are not supported for Kudu tables:

- PARTITIONED BY (Kudu tables use the clause PARTITION BY instead)
- LOCATION
- ROWFORMAT
- CACHED IN | UNCACHED
- WITH SERDEPROPERTIES

For more on the PRIMARY KEY clause, see [Primary Key Columns for Kudu Tables](#) on page 735 and [PRIMARY KEY Attribute](#) on page 736.

For more on creating a Kudu table with a specific replication factor, see [Kudu Replication Factor](#) on page 734.

For more on the NULL and NOT NULL attributes, see [NULL / NOT NULL Attribute](#) on page 738.

For more on the ENCODING attribute, see [ENCODING Attribute](#) on page 739.

For more on the COMPRESSION attribute, see [COMPRESSION Attribute](#) on page 740.

For more on the DEFAULT attribute, see [DEFAULT Attribute](#) on page 738.

For more on the BLOCK_SIZE attribute, see [BLOCK_SIZE Attribute](#) on page 740.

Partitioning for Kudu tables (PARTITION BY clause)

For Kudu tables, you specify logical partitioning across one or more columns using the PARTITION BY clause. In contrast to partitioning for HDFS-based tables, multiple values for a partition key column can be located in the same partition. The optional HASH clause lets you divide one or a set of partition key columns into a specified number of buckets. You can use more than one HASH clause, specifying a distinct set of partition key columns for each. The optional RANGE clause further subdivides the partitions, based on a set of comparison operations for the partition key columns.

Here are some examples of the PARTITION BY HASH syntax:

```
-- Apply hash function to 1 primary key column.
create table hash_t1 (x bigint, y bigint, s string, primary key (x,y))
  partition by hash (x) partitions 10
  stored as kudu;

-- Apply hash function to a different primary key column.
create table hash_t2 (x bigint, y bigint, s string, primary key (x,y))
  partition by hash (y) partitions 10
  stored as kudu;

-- Apply hash function to both primary key columns.
-- In this case, the total number of partitions is 10.
create table hash_t3 (x bigint, y bigint, s string, primary key (x,y))
  partition by hash (x,y) partitions 10
  stored as kudu;
```



```
-- When the column list is omitted, apply hash function to all primary key
columns.
create table hash_t4 (x bigint, y bigint, s string, primary key (x,y))
  partition by hash partitions 10
  stored as kudu;

-- Hash the X values independently from the Y values.
-- In this case, the total number of partitions is 10 x 20.
create table hash_t5 (x bigint, y bigint, s string, primary key (x,y))
  partition by hash (x) partitions 10, hash (y) partitions 20
  stored as kudu;
```

Here are some examples of the `PARTITION BY RANGE` syntax:

```
-- Create partitions that cover every possible value of X.
-- Ranges that span multiple values use the keyword VALUES between
-- a pair of < and <= comparisons.
create table range_t1 (x bigint, s string, s2 string, primary key (x, s))
  partition by range (x)
  (
    partition 0 <= values <= 49, partition 50 <= values <= 100,
    partition values < 0, partition 100 < values
  )
  stored as kudu;

-- Create partitions that cover some possible values of X.
-- Values outside the covered range(s) are rejected.
-- New range partitions can be added through ALTER TABLE.
create table range_t2 (x bigint, s string, s2 string, primary key (x, s))
  partition by range (x)
  (
    partition 0 <= values <= 49, partition 50 <= values <= 100
  )
  stored as kudu;

-- A range can also specify a single specific value, using the keyword VALUE
-- with an = comparison.
create table range_t3 (x bigint, s string, s2 string, primary key (x, s))
  partition by range (s)
  (
    partition value = 'Yes', partition value = 'No', partition value =
    'Maybe'
  )
  stored as kudu;

-- Using multiple columns in the RANGE clause and tuples inside the
partition spec
-- only works for partitions specified with the VALUE= syntax.
create table range_t4 (x bigint, s string, s2 string, primary key (x, s))
  partition by range (x,s)
  (
    partition value = (0,'zero'), partition value = (1,'one'), partition
    value = (2,'two')
  )
  stored as kudu;
```

Here are some examples combining both `HASH` and `RANGE` syntax for the `PARTITION BY` clause:

```
-- Values from each range partition are hashed into 10 associated buckets.
-- Total number of partitions in this case is 10 x 2.
create table combined_t1 (x bigint, s string, s2 string, primary key (x, s))
  partition by hash (x) partitions 10, range (x)
  (
    partition 0 <= values <= 49, partition 50 <= values <= 100
  )
  stored as kudu;

-- The hash partitioning and range partitioning can apply to different
columns.
-- But all the columns used in either partitioning scheme must be from the
primary key.
create table combined_t2 (x bigint, s string, s2 string, primary key (x, s))
  partition by hash (s) partitions 10, range (x)
  (
    partition 0 <= values <= 49, partition 50 <= values <= 100
  )
  stored as kudu;
```

For more usage details and examples of the Kudu partitioning syntax, see [Using Impala to Query Kudu Tables](#) on page 733.

Specifying file format (STORED AS and ROW FORMAT clauses):

The `STORED AS` clause identifies the format of the underlying data files. Currently, Impala can query more types of file formats than it can create or insert into. Use Hive to perform any create or data load operations that are not currently available in Impala. For example, Impala can create an Avro, SequenceFile, or RCFile table but cannot insert data into it. There are also Impala-specific procedures for using compression with each kind of file format. For details about working with data files of various formats, see [How Impala Works with Hadoop File Formats](#) on page 695.

Note: In Impala 1.4.0 and higher, Impala can create Avro tables, which formerly required doing the `CREATE TABLE` statement in Hive. See [Using the Avro File Format with Impala Tables](#) on page 722 for details and examples.

By default (when no `STORED AS` clause is specified), data files in Impala tables are created as text files with Ctrl-A (hex 01) characters as the delimiter. Specify the `ROW FORMAT DELIMITED` clause to produce or ingest data files that use a different delimiter character such as tab or |, or a different line end character such as carriage return or newline. When specifying delimiter and line end characters with the `FIELDS TERMINATED BY` and `LINES TERMINATED BY` clauses, use `'\t'` for tab, `'\n'` for newline or linefeed, `'\r'` for carriage return, and `\0` for ASCII nul (hex 00). For more examples of text tables, see [Using Text Data Files with Impala Tables](#) on page 697.

The `ESCAPED BY` clause applies both to text files that you create through an `INSERT` statement to an Impala `TEXTFILE` table, and to existing data files that you put into an Impala table directory. (You can ingest existing data files either by creating the table with `CREATE EXTERNAL TABLE ... LOCATION`, the `LOAD DATA` statement, or through an HDFS operation such as `hdfs dfs -put file hdfs_path`.) Choose an escape character that is not used anywhere else in the file, and put it in front of each instance of the delimiter character that occurs within a field value. Surrounding field values with quotation marks does not help Impala to parse fields with embedded delimiter characters; the quotation marks are considered to be part of the column value. If you want to use `\` as the escape character, specify the clause in `impala-shell` as `ESCAPED BY '\\'`.

Note: The `CREATE TABLE` clauses `FIELDS TERMINATED BY`, `ESCAPED BY`, and `LINES TERMINATED BY` have special rules for the string literal used for their argument, because they all require a single character. You can use a regular character surrounded by single or double quotation marks, an octal sequence such as `'\054'` (representing a comma), or an integer in the range `'-127'..'128'` (with quotation marks but no backslash), which is interpreted as a single-byte ASCII character. Negative values are subtracted from 256; for example, `FIELDS TERMINATED BY '-2'` sets the field delimiter to ASCII code 254, the “Icelandic Thorn” character used as a delimiter by some data formats.

Cloning tables (LIKE clause):

To create an empty table with the same columns, comments, and other attributes as another table, use the following variation. The `CREATE TABLE ... LIKE` form allows a restricted set of clauses, currently only the `LOCATION`, `COMMENT`, and `STORED AS` clauses.

```
CREATE [EXTERNAL] TABLE [IF NOT EXISTS] [db_name.]table_name
  LIKE { [db_name.]table_name | PARQUET 'hdfs_path_of_parquet_file' }
  [COMMENT 'table_comment']
  [STORED AS file_format]
  [LOCATION 'hdfs_path']
```

Note:

To clone the structure of a table and transfer data into it in a single operation, use the `CREATE TABLE AS SELECT` syntax described in the next subsection.

When you clone the structure of an existing table using the `CREATE TABLE ... LIKE` syntax, the new table keeps the same file format as the original one, so you only need to specify the `STORED AS` clause if you want to use a different file format, or when specifying a view as the original table. (Creating a table “like” a view produces a text table by default.)

Although normally Impala cannot create an HBase table directly, Impala can clone the structure of an existing HBase table with the `CREATE TABLE ... LIKE` syntax, preserving the file format and metadata from the original table.

There are some exceptions to the ability to use `CREATE TABLE ... LIKE` with an Avro table. For example, you cannot use this technique for an Avro table that is specified with an Avro schema but no columns. When in doubt, check if a `CREATE TABLE ... LIKE` operation works in Hive; if not, it typically will not work in Impala either.

If the original table is partitioned, the new table inherits the same partition key columns. Because the new table is initially empty, it does not inherit the actual partitions that exist in the original one. To create partitions in the new table, insert data or issue `ALTER TABLE ... ADD PARTITION` statements.

Prior to Impala 1.4.0, it was not possible to use the `CREATE TABLE LIKE view_name` syntax. In Impala 1.4.0 and higher, you can create a table with the same column definitions as a view using the `CREATE TABLE LIKE` technique. Although `CREATE TABLE LIKE` normally inherits the file format of the original table, a view has no underlying file format, so `CREATE TABLE LIKE view_name` produces a text table by default. To specify a different file format, include a `STORED AS file_format` clause at the end of the `CREATE TABLE LIKE` statement.

Because `CREATE TABLE ... LIKE` only manipulates table metadata, not the physical data of the table, issue `INSERT INTO TABLE` statements afterward to copy any data from the original table into the new one, optionally converting the data to a new file format. (For some file formats, Impala can do a `CREATE TABLE ... LIKE` to create the table, but Impala cannot insert data in that file format; in these cases, you must load the data in Hive. See [How Impala Works with Hadoop File Formats](#) on page 695 for details.)

CREATE TABLE AS SELECT:

The `CREATE TABLE AS SELECT` syntax is a shorthand notation to create a table based on column definitions from another table, and copy data from the source table to the destination table without issuing any separate `INSERT` statement. This idiom is so popular that it has its own acronym, “CTAS”.

The following examples show how to copy data from a source table T1 to a variety of destinations tables, applying various transformations to the table properties, table layout, or the data itself as part of the operation:

```
-- Sample table to be the source of CTAS operations.
CREATE TABLE t1 (x INT, y STRING);
INSERT INTO t1 VALUES (1, 'one'), (2, 'two'), (3, 'three');

-- Clone all the columns and data from one table to another.
CREATE TABLE clone_of_t1 AS SELECT * FROM t1;
+-----+
| summary |
+-----+
```

```

| Inserted 3 row(s) |
+-----+

-- Clone the columns and data, and convert the data to a different file
  format.
CREATE TABLE parquet_version_of_t1 STORED AS PARQUET AS SELECT * FROM t1;
+-----+
| summary          |
+-----+
| Inserted 3 row(s) |
+-----+

-- Copy only some rows to the new table.
CREATE TABLE subset_of_t1 AS SELECT * FROM t1 WHERE x >= 2;
+-----+
| summary          |
+-----+
| Inserted 2 row(s) |
+-----+

-- Same idea as CREATE TABLE LIKE: clone table layout but do not copy any
  data.
CREATE TABLE empty_clone_of_t1 AS SELECT * FROM t1 WHERE 1=0;
+-----+
| summary          |
+-----+
| Inserted 0 row(s) |
+-----+

-- Reorder and rename columns and transform the data.
CREATE TABLE t5 AS SELECT upper(y) AS s, x+1 AS a, 'Entirely new column' AS
  n FROM t1;
+-----+
| summary          |
+-----+
| Inserted 3 row(s) |
+-----+
SELECT * FROM t5;
+-----+-----+-----+
| s      | a  | n                               |
+-----+-----+-----+
| ONE    | 2  | Entirely new column            |
| TWO    | 3  | Entirely new column            |
| THREE  | 4  | Entirely new column            |
+-----+-----+-----+

```

See [SELECT Statement](#) on page 316 for details about query syntax for the SELECT portion of a CREATE TABLE AS SELECT statement.

The newly created table inherits the column names that you select from the original table, which you can override by specifying column aliases in the query. Any column or table comments from the original table are not carried over to the new table.

Note: When using the STORED AS clause with a CREATE TABLE AS SELECT statement, the destination table must be a file format that Impala can write to: currently, text or Parquet. You cannot specify an Avro, SequenceFile, or RCFile table as the destination table for a CTAS operation.

Prior to Impala 2.5 you could use a partitioned table as the source and copy data from it, but could not specify any partitioning clauses for the new table. In Impala 2.5 and higher, you can now use the PARTITIONED BY clause with a CREATE TABLE AS SELECT statement. The following example demonstrates how you can copy data from an unpartitioned table in a CREATE TABLE AS SELECT operation, creating a new partitioned table in the process. The main syntax consideration is the column order in the PARTITIONED BY clause and the select list: the partition key columns must be listed last in the select list, in the same order as in the PARTITIONED BY clause. Therefore,

in this case, the column order in the destination table is different from the source table. You also only specify the column names in the `PARTITIONED BY` clause, not the data types or column comments.

```
create table partitions_no (year smallint, month tinyint, s string);
insert into partitions_no values (2016, 1, 'January 2016'),
    (2016, 2, 'February 2016'), (2016, 3, 'March 2016');

-- Prove that the source table is not partitioned.
show partitions partitions_no;
ERROR: AnalysisException: Table is not partitioned:
    ctas_partition_by.partitions_no

-- Create new table with partitions based on column values from source
table.
create table partitions_yes partitioned by (year, month)
    as select s, year, month from partitions_no;
+-----+
| summary |
+-----+
| Inserted 3 row(s) |
+-----+

-- Prove that the destination table is partitioned.
show partitions partitions_yes;
+-----+-----+-----+-----+-----+...
| year | month | #Rows | #Files | Size | ...
+-----+-----+-----+-----+-----+...
| 2016 | 1     | -1    | 1      | 13B  | ...
| 2016 | 2     | -1    | 1      | 14B  | ...
| 2016 | 3     | -1    | 1      | 11B  | ...
| Total |      | -1    | 3      | 38B  | ...
+-----+-----+-----+-----+-----+...
```

The most convenient layout for partitioned tables is with all the partition key columns at the end. The CTAS `PARTITIONED BY` syntax requires that column order in the select list, resulting in that same column order in the destination table.

```
describe partitions_no;
+-----+-----+-----+
| name | type   | comment |
+-----+-----+-----+
| year | smallint |         |
| month | tinyint |         |
| s     | string  |         |
+-----+-----+-----+

-- The CTAS operation forced us to put the partition key columns last.
-- Having those columns last works better with idioms such as SELECT *
-- for partitioned tables.
describe partitions_yes;
+-----+-----+-----+
| name | type   | comment |
+-----+-----+-----+
| s     | string |         |
| year  | smallint |         |
| month | tinyint |         |
+-----+-----+-----+
```

Attempting to use a select list with the partition key columns not at the end results in an error due to a column name mismatch:

```
-- We expect this CTAS to fail because non-key column S
-- comes after key columns YEAR and MONTH in the select list.
create table partitions_maybe partitioned by (year, month)
  as select year, month, s from partitions_no;
ERROR: AnalysisException: Partition column name mismatch: year != month
```

For example, the following statements show how you can clone all the data in a table, or a subset of the columns and/or rows, or reorder columns, rename them, or construct them out of expressions:

As part of a CTAS operation, you can convert the data to any file format that Impala can write (currently, TEXTFILE and PARQUET). You cannot specify the lower-level properties of a text table, such as the delimiter.

Sorting considerations: Although you can specify an ORDER BY clause in an INSERT ... SELECT statement, any ORDER BY clause is ignored and the results are not necessarily sorted. An INSERT ... SELECT operation potentially creates many different data files, prepared by different executor Impala daemons, and therefore the notion of the data being stored in sorted order is impractical.

CREATE TABLE LIKE PARQUET:

The variation CREATE TABLE ... LIKE PARQUET 'hdfs_path_of_parquet_file' lets you skip the column definitions of the CREATE TABLE statement. The column names and data types are automatically configured based on the organization of the specified Parquet data file, which must already reside in HDFS. You can use a data file located outside the Impala database directories, or a file from an existing Impala Parquet table; either way, Impala only uses the column definitions from the file and does not use the HDFS location for the LOCATION attribute of the new table. (Although you can also specify the enclosing directory with the LOCATION attribute, to both use the same schema as the data file and point the Impala table at the associated directory for querying.)

The following considerations apply when you use the CREATE TABLE LIKE PARQUET technique:

- Any column comments from the original table are not preserved in the new table. Each column in the new table has a comment stating the low-level Parquet field type used to deduce the appropriate SQL column type.
- If you use a data file from a partitioned Impala table, any partition key columns from the original table are left out of the new table, because they are represented in HDFS directory names rather than stored in the data file. To preserve the partition information, repeat the same PARTITION clause as in the original CREATE TABLE statement.
- The file format of the new table defaults to text, as with other kinds of CREATE TABLE statements. To make the new table also use Parquet format, include the clause STORED AS PARQUET in the CREATE TABLE LIKE PARQUET statement.
- If the Parquet data file comes from an existing Impala table, currently, any TINYINT or SMALLINT columns are turned into INT columns in the new table. Internally, Parquet stores such values as 32-bit integers.
- When the destination table uses the Parquet file format, the CREATE TABLE AS SELECT and INSERT ... SELECT statements always create at least one data file, even if the SELECT part of the statement does not match any rows. You can use such an empty Parquet data file as a template for subsequent CREATE TABLE LIKE PARQUET statements.

For more details about creating Parquet tables, and examples of the CREATE TABLE LIKE PARQUET syntax, see [Using the Parquet File Format with Impala Tables](#) on page 705.

Visibility and Metadata (TBLPROPERTIES and WITH SERDEPROPERTIES clauses):

You can associate arbitrary items of metadata with a table by specifying the TBLPROPERTIES clause. This clause takes a comma-separated list of key-value pairs and stores those items in the metastore database. You can also change the table properties later with an ALTER TABLE statement. You can observe the table properties for different delimiter and escape characters using the DESCRIBE FORMATTED command, and change those settings for an existing table with ALTER TABLE ... SET TBLPROPERTIES.

You can also associate SerDes properties with the table by specifying key-value pairs through the `WITH SERDEPROPERTIES` clause. This metadata is not used by Impala, which has its own built-in serializer and deserializer for the file formats it supports. Particular property values might be needed for Hive compatibility with certain variations of file formats, particularly Avro.

Some DDL operations that interact with other Hadoop components require specifying particular values in the `SERDEPROPERTIES` or `TBLPROPERTIES` fields, such as creating an Avro table or an HBase table. (You typically create HBase tables in Hive, because they require additional clauses not currently available in Impala.)

To see the column definitions and column comments for an existing table, for example before issuing a `CREATE TABLE ... LIKE` or a `CREATE TABLE ... AS SELECT` statement, issue the statement `DESCRIBE table_name`. To see even more detail, such as the location of data files and the values for clauses such as `ROW FORMAT` and `STORED AS`, issue the statement `DESCRIBE FORMATTED table_name`. `DESCRIBE FORMATTED` is also needed to see any overall table comment (as opposed to individual column comments).

After creating a table, your `impala-shell` session or another `impala-shell` connected to the same node can immediately query that table. There might be a brief interval (one statestore heartbeat) before the table can be queried through a different Impala node. To make the `CREATE TABLE` statement return only when the table is recognized by all Impala nodes in the cluster, enable the `SYNC_DDL` query option.

HDFS caching (CACHED IN clause):

If you specify the `CACHED IN` clause, any existing or future data files in the table directory or the partition subdirectories are designated to be loaded into memory with the HDFS caching mechanism. See [Using HDFS Caching with Impala \(Impala 2.1 or higher only\)](#) on page 646 for details about using the HDFS caching feature.

In Impala 2.2 and higher, the optional `WITH REPLICATION` clause for `CREATE TABLE` and `ALTER TABLE` lets you specify a *replication factor*, the number of hosts on which to cache the same data blocks. When Impala processes a cached data block, where the cache replication factor is greater than 1, Impala randomly selects a host that has a cached copy of that data block. This optimization avoids excessive CPU usage on a single host when the same cached data block is processed multiple times. Where practical, specify a value greater than or equal to the HDFS block replication factor.

Column order:

If you intend to use the table to hold data files produced by some external source, specify the columns in the same order as they appear in the data files.

If you intend to insert or copy data into the table through Impala, or if you have control over the way externally produced data files are arranged, use your judgment to specify columns in the most convenient order:

- If certain columns are often NULL, specify those columns last. You might produce data files that omit these trailing columns entirely. Impala automatically fills in the NULL values if so.
- If an unpartitioned table will be used as the source for an `INSERT ... SELECT` operation into a partitioned table, specify last in the unpartitioned table any columns that correspond to partition key columns in the partitioned table, and in the same order as the partition key columns are declared in the partitioned table. This technique lets you use `INSERT ... SELECT *` when copying data to the partitioned table, rather than specifying each column name individually.
- If you specify columns in an order that you later discover is suboptimal, you can sometimes work around the problem without recreating the table. You can create a view that selects columns from the original table in a permuted order, then do a `SELECT *` from the view. When inserting data into a table, you can specify a permuted order for the inserted columns to match the order in the destination table.

Hive considerations:

Impala queries can make use of metadata about the table and columns, such as the number of rows in a table or the number of different values in a column. Prior to Impala 1.2.2, to create this metadata, you issued the `ANALYZE TABLE` statement in Hive to gather this information, after creating the table and loading representative data into it. In Impala 1.2.2 and higher, the `COMPUTE STATS` statement produces these statistics within Impala, without needing to use Hive at all.

HBase considerations:

Note:

The Impala `CREATE TABLE` statement cannot create an HBase table, because it currently does not support the `STORED BY` clause needed for HBase tables. Create such tables in Hive, then query them through Impala. For information on using Impala with HBase tables, see [Using Impala to Query HBase Tables](#) on page 750.

Amazon S3 considerations:

To create a table where the data resides in the Amazon Simple Storage Service (S3), specify a `s3a://` prefix `LOCATION` attribute pointing to the data files in S3.

In Impala 2.6 and higher, you can use this special `LOCATION` syntax as part of a `CREATE TABLE AS SELECT` statement.

In Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about reading and writing S3 data with Impala.

Sorting considerations: Although you can specify an `ORDER BY` clause in an `INSERT ... SELECT` statement, any `ORDER BY` clause is ignored and the results are not necessarily sorted. An `INSERT ... SELECT` operation potentially creates many different data files, prepared by different executor Impala daemons, and therefore the notion of the data being stored in sorted order is impractical.

HDFS considerations:

The `CREATE TABLE` statement for an internal table creates a directory in HDFS. The `CREATE EXTERNAL TABLE` statement associates the table with an existing HDFS directory, and does not create any new directory in HDFS. To locate the HDFS data directory for a table, issue a `DESCRIBE FORMATTED table` statement. To examine the contents of that HDFS directory, use an OS command such as `hdfs dfs -ls hdfs://path`, either from the OS command line or through the `shell` or `!` commands in `impala-shell`.

The `CREATE TABLE AS SELECT` syntax creates data files under the table data directory to hold any data copied by the `INSERT` portion of the statement. (Even if no data is copied, Impala might create one or more empty data files.)

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have both execute and write permission for the database directory where the table is being created.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See the documentation for your Apache Hadoop distribution for details.

Cancellation: Certain multi-stage statements (`CREATE TABLE AS SELECT` and `COMPUTE STATS`) can be cancelled during some stages, when running `INSERT` or `SELECT` operations internally. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

Related information:

[Overview of Impala Tables](#) on page 206, [ALTER TABLE Statement](#) on page 215, [DROP TABLE Statement](#) on page 289, [Partitioning for Impala Tables](#) on page 685, [Internal Tables](#) on page 206, [External Tables](#) on page 207, [COMPUTE STATS Statement](#) on page 232, [SYNC_DDL Query Option](#) on page 393, [SHOW TABLES Statement](#) on page 402, [SHOW CREATE TABLE Statement](#) on page 403, [DESCRIBE Statement](#) on page 268

CREATE VIEW Statement

The `CREATE VIEW` statement lets you create a shorthand abbreviation for a more complicated query. The base query can involve joins, expressions, reordered columns, column aliases, and other SQL features that can make a query hard to understand or maintain.

Because a view is purely a logical construct (an alias for a query) with no physical data behind it, `ALTER VIEW` only involves changes to metadata in the metastore database, not any data files in HDFS.

Syntax:

```
CREATE VIEW [IF NOT EXISTS] view_name
  [(column_name [COMMENT 'column_comment'][, ...])]
  [COMMENT 'view_comment']
  [TBLPROPERTIES ('name' = 'value'[, ...])]
  AS select_statement
```

Statement type: DDL

Usage notes:

The `CREATE VIEW` statement can be useful in scenarios such as the following:

- To turn even the most lengthy and complicated SQL query into a one-liner. You can issue simple queries against the view from applications, scripts, or interactive queries in `impala-shell`. For example:

```
select * from view_name;
select * from view_name order by c1 desc limit 10;
```

The more complicated and hard-to-read the original query, the more benefit there is to simplifying the query using a view.

- To hide the underlying table and column names, to minimize maintenance problems if those names change. In that case, you re-create the view using the new names, and all queries that use the view rather than the underlying tables keep running with no changes.
- To experiment with optimization techniques and make the optimized queries available to all applications. For example, if you find a combination of `WHERE` conditions, join order, join hints, and so on that works the best for a class of queries, you can establish a view that incorporates the best-performing techniques. Applications can then make relatively simple queries against the view, without repeating the complicated and optimized logic over and over. If you later find a better way to optimize the original query, when you re-create the view, all the applications immediately take advantage of the optimized base query.
- To simplify a whole class of related queries, especially complicated queries involving joins between multiple tables, complicated expressions in the column list, and other SQL syntax that makes the query difficult to understand and debug. For example, you might create a view that joins several tables, filters using several `WHERE` conditions, and selects several columns from the result set. Applications might issue queries against this view that only vary in their `LIMIT`, `ORDER BY`, and similar simple clauses.

For queries that require repeating complicated clauses over and over again, for example in the `select` list, `ORDER BY`, and `GROUP BY` clauses, you can use the `WITH` clause as an alternative to creating a view.

You can optionally specify the table-level and the column-level comments as in the `CREATE TABLE` statement.

Complex type considerations:

For tables containing complex type columns (`ARRAY`, `STRUCT`, or `MAP`), you typically use join queries to refer to the complex values. You can use views to hide the join notation, making such tables seem like traditional denormalized tables, and making those tables queryable by business intelligence tools that do not have built-in support for those complex types. See [Accessing Complex Type Data in Flattened Form Using Views](#) on page 163 for details.

Because you cannot directly issue `SELECT col_name` against a column of complex type, you cannot use a view or a `WITH` clause to “rename” a column by selecting it with a column alias.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See the documentation for your Apache Hadoop distribution for details.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

```
-- Create a view that is exactly the same as the underlying table.
CREATE VIEW v1 AS SELECT * FROM t1;

-- Create a view that includes only certain columns from the underlying
  table.
CREATE VIEW v2 AS SELECT c1, c3, c7 FROM t1;

-- Create a view that filters the values from the underlying table.
CREATE VIEW v3 AS SELECT DISTINCT c1, c3, c7 FROM t1 WHERE c1 IS NOT NULL
  AND c5 > 0;

-- Create a view that that reorders and renames columns from the underlying
  table.
CREATE VIEW v4 AS SELECT c4 AS last_name, c6 AS address, c2 AS birth_date
  FROM t1;

-- Create a view that runs functions to convert or transform certain
  columns.
CREATE VIEW v5 AS SELECT c1, CAST(c3 AS STRING) c3, CONCAT(c4,c5) c5,
  TRIM(c6) c6, "Constant" c8 FROM t1;

-- Create a view that hides the complexity of a view query.
CREATE VIEW v6 AS SELECT t1.c1, t2.c2 FROM t1 JOIN t2 ON t1.id = t2.id;

-- Create a view with a column comment and a table comment.
CREATE VIEW v7 (c1 COMMENT 'Comment for c1', c2) COMMENT 'Comment for v7' AS
  SELECT t1.c1, t1.c2 FROM t1;

-- Create a view with tblproperties.
CREATE VIEW v7 (c1 , c2) TBLPROPERTIES ('tblp1' = '1', 'tblp2' = '2') AS
  SELECT t1.c1, t1.c2 FROM t1;
```

Related information:

[Overview of Impala Views](#) on page 209, [ALTER VIEW Statement](#) on page 230, [DROP VIEW Statement](#) on page 290

DELETE Statement (Impala 2.8 or higher only)

Deletes an arbitrary number of rows from a table. This statement only works for Kudu (from Impala 2.8) and Iceberg tables (from Impala 4.3).

Syntax:

```
DELETE [FROM] [database_name.]table_name [ WHERE where_conditions ]
```

```
DELETE table_ref FROM [joined_table_refs] [ WHERE where_conditions ]
```

The first form evaluates rows from one table against an optional WHERE clause, and deletes all the rows that match the WHERE conditions, or all rows if WHERE is omitted.

The second form evaluates one or more join clauses, and deletes all matching rows from one of the tables. The join clauses can include tables of any kind, but the table from which the rows are deleted must be a Kudu or Iceberg table. The FROM keyword is required in this case, to separate the name of the table whose rows are being deleted from the table names of the join clauses.

Usage notes:

The conditions in the WHERE clause are the same ones allowed for the SELECT statement. See [SELECT Statement](#) on page 316 for details.

The conditions in the WHERE clause can refer to any combination of primary key columns or other columns. Referring to primary key columns in the WHERE clause is more efficient than referring to non-primary key columns (in case of Kudu tables).

If the WHERE clause is omitted, all rows are removed from the table.

Because Kudu currently does not enforce strong consistency during concurrent DML operations, be aware that the results after this statement finishes might be different than you intuitively expect:

- If some rows cannot be deleted because their some primary key columns are not found, due to their being deleted by a concurrent DELETE operation, the statement succeeds but returns a warning.
- A DELETE statement might also overlap with INSERT, UPDATE, or UPSERT statements running concurrently on the same table. After the statement finishes, there might be more or fewer rows than expected in the table because it is undefined whether the DELETE applies to rows that are inserted or updated while the DELETE is in progress.

Iceberg also allows concurrent DELETE operations, in which case the concurrent DELETES might remove the same rows. This won't corrupt the table as Iceberg allows such behavior.

The number of affected rows is reported in an `impala-shell` message and in the query profile.

Statement type: DML

Important: After adding or replacing data in a table used in performance-critical queries, issue a `COMPUTE STATS` statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any `INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT` statement in Impala, or after loading data through Hive and doing a `REFRESH table_name` in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

The following examples show how to delete rows from a specified table, either all rows or rows that match a WHERE clause:

```
-- Deletes all rows. The FROM keyword is optional.
DELETE FROM table;
DELETE table;

-- Deletes 0, 1, or more rows.
-- (If c1 is a single-column primary key, the statement could only
-- delete 0 or 1 rows.)
DELETE FROM table WHERE c1 = 100;

-- Deletes all rows that match all the WHERE conditions.
DELETE FROM table WHERE
  (c1 > c2 OR c3 IN ('hello','world')) AND c4 IS NOT NULL;
DELETE FROM t1 WHERE
  (c1 IN (1,2,3) AND c2 > c3) OR c4 IS NOT NULL;
DELETE FROM time_series WHERE
  year = 2016 AND month IN (11,12) AND day > 15;
```

```
-- WHERE condition with a subquery.
DELETE FROM t1 WHERE
  c5 IN (SELECT DISTINCT other_col FROM other_table);

-- Does not delete any rows, because the WHERE condition is always false.
DELETE FROM table WHERE 1 = 0;
```

The following examples show how to delete rows that are part of the result set from a join:

```
-- Remove _all_ rows from t1 that have a matching X value in t2.
DELETE t1 FROM t1 JOIN t2 ON t1.x = t2.x;

-- Remove _some_ rows from t1 that have a matching X value in t2.
DELETE t1 FROM t1 JOIN t2 ON t1.x = t2.x
  WHERE t1.y = FALSE and t2.z > 100;

-- Delete from a table based on a join with another table.
DELETE t1 FROM table t1 JOIN other_table t2 ON t1.x = t2.x;

-- The tables can be joined in any order as long as the Kudu or Iceberg
table
-- is specified as the deletion target.
DELETE t2 FROM non_kudu_non_ice_table t1 JOIN kudu_or_ice_table t2 ON t1.x =
t2.x;
```

Related information:

[Using Impala with Iceberg Tables](#) on page 760, [Using Impala to Query Kudu Tables](#) on page 733, [INSERT Statement](#) on page 298, [UPDATE Statement \(Impala 2.8 or higher only\)](#) on page 418, [UPSERT Statement \(Impala 2.8 or higher only\)](#) on page 420

DESCRIBE Statement

The DESCRIBE statement displays metadata about a table, such as the column names and their data types. In Impala 2.3 and higher, you can specify the name of a complex type column, which takes the form of a dotted path. The path might include multiple components in the case of a nested type definition. In Impala 2.5 and higher, the DESCRIBE DATABASE form can display information about a database.

Syntax:

```
DESCRIBE [DATABASE] [FORMATTED|EXTENDED] object_name

object_name ::=
  [db_name.]table_name[.complex_col_name ...]
  | db_name
```

You can use the abbreviation DESC for the DESCRIBE statement.

The DESCRIBE FORMATTED variation displays additional information, in a format familiar to users of Apache Hive. The extra information includes low-level details such as whether the table is internal or external, when it was created, the file format, the location of the data in HDFS, whether the object is a table or a view, and (for views) the text of the query from the view definition.

Note: The Compressed field is not a reliable indicator of whether the table contains compressed data. It typically always shows No, because the compression settings only apply during the session that loads data and are not stored persistently with the table metadata.

Describing databases:

By default, the DESCRIBE output for a database includes the location and the comment, which can be set by the LOCATION and COMMENT clauses on the CREATE DATABASE statement.

The additional information displayed by the `FORMATTED` or `EXTENDED` keyword includes the HDFS user ID that is considered the owner of the database, and any optional database properties. The properties could be specified by the `WITH DBPROPERTIES` clause if the database is created using a Hive `CREATE DATABASE` statement. Impala currently does not set or do any special processing based on those properties.

The following examples show the variations in syntax and output for describing databases. This feature is available in Impala 2.5 and higher.

```
describe database default;
+-----+-----+-----+
| name   | location           | comment           |
+-----+-----+-----+
| default | /user/hive/warehouse | Default Hive database |
+-----+-----+-----+

describe database formatted default;
+-----+-----+-----+
| name   | location           | comment           |
+-----+-----+-----+
| default | /user/hive/warehouse | Default Hive database |
| Owner: | public             | ROLE              |
+-----+-----+-----+

describe database extended default;
+-----+-----+-----+
| name   | location           | comment           |
+-----+-----+-----+
| default | /user/hive/warehouse | Default Hive database |
| Owner: | public             | ROLE              |
+-----+-----+-----+
```

Describing tables:

If the `DATABASE` keyword is omitted, the default for the `DESCRIBE` statement is to refer to a table.

If you have the `SELECT` privilege on a subset of the table columns and no other relevant table/database/server-level privileges, `DESCRIBE` returns the data from the columns you have access to.

If you have the `SELECT` privilege on a subset of the table columns and no other relevant table/database/server-level privileges, `DESCRIBE FORMATTED/EXTENDED` does not return the `LOCATION` field. The `LOCATION` data is shown if you have any privilege on the table, the containing database or the server.

```
-- By default, the table is assumed to be in the current database.
describe my_table;
+-----+-----+-----+
| name | type  | comment |
+-----+-----+-----+
| x    | int   |         |
| s    | string |         |
+-----+-----+-----+

-- Use a fully qualified table name to specify a table in any database.
describe my_database.my_table;
+-----+-----+-----+
| name | type  | comment |
+-----+-----+-----+
| x    | int   |         |
| s    | string |         |
+-----+-----+-----+
```

```
-- The formatted or extended output includes additional useful information.
-- The LOCATION field is especially useful to know for DDL statements and
HDFS commands
-- during ETL jobs. (The LOCATION includes a full hdfs:// URL, omitted here
for readability.)
describe formatted my_table;
```

```
+-----+
+-----+-----+
| name      |          | type |
| comment   |          |      |
+-----+-----+
+-----+-----+
| # col_name |          | data_type |
| comment    |          |            |
| NULL       |          | NULL      |
| x          |          | int       |
| NULL       |          |           |
| s          |          | string    |
| NULL       |          |           |
| NULL       |          | NULL      |
| # Detailed Table Information | NULL |
| NULL       |          |           |
| Database:  |          | my_database |
| NULL       |          |             |
| Owner:     |          | jrusSELL    |
| NULL       |          |             |
| CreateTime: |          | Fri Mar 18 15:58:00 PDT 2016 |
| NULL       |          |             |
| LastAccessTime: |          | UNKNOWN    |
| NULL       |          |             |
| Protect Mode: |          | None       |
| NULL       |          |             |
| Retention:  |          | 0          |
| NULL       |          |             |
| Location:   |          | /user/hive/warehouse/my_database.db/ |
my_table | NULL |
| Table Type: |          | MANAGED_TABLE |
| NULL       |          |               |
| Table Parameters: |          | NULL          |
| NULL       |          |               |
| 1458341880 |          | transient_lastDdlTime |
| NULL       |          | NULL          |
| # Storage Information | NULL |
| NULL       |          |               |
| SerDe Library: |          | org. ... .LazySimpleSerDe |
| NULL       |          |               |
| InputFormat: |          | org.apache.hadoop.mapred.TextInputFormat |
| NULL       |          |               |
| OutputFormat: |          | org. ... .HiveIgnoreKeyTextOutputFormat |
| NULL       |          |               |
| Compressed:  |          | No          |
| NULL       |          |               |
| Num Buckets: |          | 0           |
| NULL       |          |               |
| Bucket Columns: |          | []          |
| NULL       |          |               |
| Sort Columns: |          | []          |
| NULL       |          |               |
```

```
+-----+
+-----+-----+
```

Complex type considerations:

Because the column definitions for complex types can become long, particularly when such types are nested, the DESCRIBE statement uses special formatting for complex type columns to make the output readable.

For the ARRAY, STRUCT, and MAP types available in Impala 2.3 and higher, the DESCRIBE output is formatted to avoid excessively long lines for multiple fields within a STRUCT, or a nested sequence of complex types.

You can pass a multi-part qualified name to DESCRIBE to specify an ARRAY, STRUCT, or MAP column and visualize its structure as if it were a table. For example, if table T1 contains an ARRAY column A1, you could issue the statement DESCRIBE t1.a1. If table T1 contained a STRUCT column S1, and a field F1 within the STRUCT was a MAP, you could issue the statement DESCRIBE t1.s1.f1. An ARRAY is shown as a two-column table, with ITEM and POS columns. A STRUCT is shown as a table with each field representing a column in the table. A MAP is shown as a two-column table, with KEY and VALUE columns.

For example, here is the DESCRIBE output for a table containing a single top-level column of each complex type:

```
create table t1 (x int, a array<int>, s struct<f1: string, f2: bigint>, m
  map<string,int>) stored as parquet;
```

```
describe t1;
```

name	type	comment
x	int	
a	array<int>	
s	struct< f1:string, f2:bigint >	
m	map<string,int>	

Here are examples showing how to “drill down” into the layouts of complex types, including using multi-part names to examine the definitions of nested types. The < > delimiters identify the columns with complex types; these are the columns where you can descend another level to see the parts that make up the complex type. This technique helps you to understand the multi-part names you use as table references in queries involving complex types, and the corresponding column names you refer to in the SELECT list. These tables are from the “nested TPC-H” schema, shown in detail in [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 165.

The REGION table contains an ARRAY of STRUCT elements:

- The first DESCRIBE specifies the table name, to display the definition of each top-level column.
- The second DESCRIBE specifies the name of a complex column, REGION.R_NATIONS, showing that when you include the name of an ARRAY column in a FROM clause, that table reference acts like a two-column table with columns ITEM and POS.
- The final DESCRIBE specifies the fully qualified name of the ITEM field, to display the layout of its underlying STRUCT type in table format, with the fields mapped to column names.

```
-- #1: The overall layout of the entire table.
```

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	

```

| r_nations | array<struct<
|           |   n_nationkey:smallint,
|           |   n_name:string,
|           |   n_comment:string
|           | >>
+-----+-----+

-- #2: The ARRAY column within the table.
describe region.r_nations;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| item | struct<
|      |   n_nationkey:smallint,
|      |   n_name:string,
|      |   n_comment:string
|      | >
| pos  | bigint
+-----+-----+-----+

-- #3: The STRUCT that makes up each ARRAY element.
--      The fields of the STRUCT act like columns of a table.
describe region.r_nations.item;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| n_nationkey | smallint |
| n_name      | string   |
| n_comment   | string   |
+-----+-----+-----+

```

The CUSTOMER table contains an ARRAY of STRUCT elements, where one field in the STRUCT is another ARRAY of STRUCT elements:

- Again, the initial DESCRIBE specifies only the table name.
- The second DESCRIBE specifies the qualified name of the complex column, CUSTOMER.C_ORDERS, showing how an ARRAY is represented as a two-column table with columns ITEM and POS.
- The third DESCRIBE specifies the qualified name of the ITEM of the ARRAY column, to see the structure of the nested ARRAY. Again, it has two parts, ITEM and POS. Because the ARRAY contains a STRUCT, the layout of the STRUCT is shown.
- The fourth and fifth DESCRIBE statements drill down into a STRUCT field that is itself a complex type, an ARRAY of STRUCT. The ITEM portion of the qualified name is only required when the ARRAY elements are anonymous. The fields of the STRUCT give names to any other complex types nested inside the STRUCT. Therefore, the DESCRIBE parameters CUSTOMER.C_ORDERS.ITEM.O_LINEITEMS and CUSTOMER.C_ORDERS.O_LINEITEMS are equivalent. (For brevity, leave out the ITEM portion of a qualified name when it is not required.)
- The final DESCRIBE shows the layout of the deeply nested STRUCT type. Because there are no more complex types nested inside this STRUCT, this is as far as you can drill down into the layout for this table.

```

-- #1: The overall layout of the entire table.
describe customer;
+-----+-----+
| name | type |
+-----+-----+
| c_custkey | bigint |
| ... more scalar columns ...
| c_orders | array<struct<
|          |   o_orderkey:bigint,
|          |   o_orderstatus:string,
|          |   o_totalprice:decimal(12,2),
+-----+-----+

```



```

o_orderdate:string,
o_orderpriority:string,
o_clerk:string,
o_shippriority:int,
o_comment:string,
o_lineitems:array<struct<
  l_partkey:bigint,
  l_suppkey:bigint,
  l_linenumber:int,
  l_quantity:decimal(12,2),
  l_extendedprice:decimal(12,2),
  l_discount:decimal(12,2),
  l_tax:decimal(12,2),
  l_returnflag:string,
  l_linestatus:string,
  l_shipdate:string,
  l_commitdate:string,
  l_receiptdate:string,
  l_shipinstruct:string,
  l_shipmode:string,
  l_comment:string
>>
>>

```

-- #2: The ARRAY column within the table.

```
describe customer.c_orders;
```

name	type
item	struct< o_orderkey:bigint, o_orderstatus:string, ... more struct fields ... o_lineitems:array<struct< l_partkey:bigint, l_suppkey:bigint, ... more nested struct fields ... l_comment:string >> >
pos	bigint

-- #3: The STRUCT that makes up each ARRAY element.

-- The fields of the STRUCT act like columns of a table.

```
describe customer.c_orders.item;
```

name	type
o_orderkey	bigint
o_orderstatus	string
o_totalprice	decimal(12,2)
o_orderdate	string
o_orderpriority	string
o_clerk	string
o_shippriority	int
o_comment	string
o_lineitems	array<struct< l_partkey:bigint, l_suppkey:bigint, ... more struct fields ... l_comment:string >>

```

+-----+-----+
-- #4: The ARRAY nested inside the STRUCT elements of the first ARRAY.
describe customer.c_orders.item.o_lineitems;
+-----+-----+
| name | type |
+-----+-----+
| item | struct<
|      |   l_partkey:bigint,
|      |   l_suppkey:bigint,
| ... more struct fields ...
|      |   l_comment:string
|      | >
| pos  | bigint
+-----+-----+

-- #5: Shorter form of the previous DESCRIBE. Omits the .ITEM portion of the
name
--      because O_LINEITEMS and other field names provide a way to refer to
things
--      inside the ARRAY element.
describe customer.c_orders.o_lineitems;
+-----+-----+
| name | type |
+-----+-----+
| item | struct<
|      |   l_partkey:bigint,
|      |   l_suppkey:bigint,
| ... more struct fields ...
|      |   l_comment:string
|      | >
| pos  | bigint
+-----+-----+

-- #6: The STRUCT representing ARRAY elements nested inside
--      another ARRAY of STRUCTs. The lack of any complex types
--      in this output means this is as far as DESCRIBE can
--      descend into the table layout.
describe customer.c_orders.o_lineitems.item;
+-----+-----+
| name          | type          |
+-----+-----+
| l_partkey     | bigint        |
| l_suppkey     | bigint        |
| ... more scalar columns ...
| l_comment     | string        |
+-----+-----+

```

Usage notes:

After the `impalad` daemons are restarted, the first query against a table can take longer than subsequent queries, because the metadata for the table is loaded before the query is processed. This one-time delay for each table can cause misleading results in benchmark tests or cause unnecessary concern. To “warm up” the Impala metadata cache, you can issue a `DESCRIBE` statement in advance for each table you intend to access later.

When you are dealing with data files stored in HDFS, sometimes it is important to know details such as the path of the data files for an Impala table, and the hostname for the namenode. You can get this information from the `DESCRIBE FORMATTED` output. You specify HDFS URIs or path specifications with statements such as `LOAD DATA` and the `LOCATION` clause of `CREATE TABLE` or `ALTER TABLE`. You might also use HDFS URIs or paths with Linux commands such as `hadoop` and `hdfs` to copy, rename, and so on, data files in HDFS.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

Each table can also have associated table statistics and column statistics. To see these categories of information, use the `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` statements. See [SHOW Statement](#) on page 395 for details.

Important: After adding or replacing data in a table used in performance-critical queries, issue a `COMPUTE STATS` statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any `INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT` statement in Impala, or after loading data through Hive and doing a `REFRESH table_name` in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

The following example shows the results of both a standard `DESCRIBE` and `DESCRIBE FORMATTED` for different kinds of schema objects:

- `DESCRIBE` for a table or a view returns the name, type, and comment for each of the columns. For a view, if the column value is computed by an expression, the column name is automatically generated as `_c0`, `_c1`, and so on depending on the ordinal number of the column.
- A table created with no special format or storage clauses is designated as a `MANAGED_TABLE` (an “internal table” in Impala terminology). Its data files are stored in an HDFS directory under the default Hive data directory. By default, it uses Text data format.
- A view is designated as `VIRTUAL_VIEW` in `DESCRIBE FORMATTED` output. Some of its properties are `NULL` or blank because they are inherited from the base table. The text of the query that defines the view is part of the `DESCRIBE FORMATTED` output.
- A table with additional clauses in the `CREATE TABLE` statement has differences in `DESCRIBE FORMATTED` output. The output for `T2` includes the `EXTERNAL_TABLE` keyword because of the `CREATE EXTERNAL TABLE` syntax, and different `InputFormat` and `OutputFormat` fields to reflect the Parquet file format.

```
[localhost:21000] > create table t1 (x int, y int, s string);
```

```
Query: create table t1 (x int, y int, s string)
```

```
[localhost:21000] > describe t1;
```

```
Query: describe t1
```

```
Query finished, fetching results ...
```

name	type	comment
x	int	
y	int	
s	string	

```
Returned 3 row(s) in 0.13s
```

```
[localhost:21000] > describe formatted t1;
```

```
Query: describe formatted t1
```

```
Query finished, fetching results ...
```

name	comment	type
# col_name		data_type
comment		
NULL		NULL
x		int
None		
y		int
None		

s	string
None	NULL
NULL	NULL
# Detailed Table Information	NULL
Database:	describe_formatted
Owner:	doc_demo
CreateTime:	Mon Jul 22 17:03:16 EDT 2013
LastAccessTime:	UNKNOWN
Protect Mode:	None
Retention:	0
Location:	hdfs://127.0.0.1:8020/user/hive/warehouse/
	describe_formatted.db/t1
Table Type:	MANAGED_TABLE
Table Parameters:	NULL
	transient_lastDdlTime
1374526996	NULL
NULL	NULL
# Storage Information	NULL
SerDe Library:	org.apache.hadoop.hive.serde2.lazy.
	LazySimpleSerDe
InputFormat:	org.apache.hadoop.mapred.TextInputFormat
OutputFormat:	org.apache.hadoop.hive.ql.io.
	HiveIgnoreKeyTextOutputFormat
Compressed:	No
Num Buckets:	0
Bucket Columns:	[]
Sort Columns:	[]
NULL	

Returned 26 row(s) in 0.03s

[localhost:21000] > create view v1 as select x, upper(s) from t1;

Query: create view v1 as select x, upper(s) from t1

[localhost:21000] > describe v1;

Query: describe v1

Query finished, fetching results ...

name	type	comment
x	int	
_c1	string	

```

Returned 2 row(s) in 0.10s
[localhost:21000] > describe formatted v1;
Query: describe formatted v1
Query finished, fetching results ...

```

+-----+		
name	type	comment
+-----+		
# col_name	data_type	comment
	NULL	NULL
x	int	None
_c1	string	None
	NULL	NULL
# Detailed Table Information	NULL	NULL
Database:	describe_formatted	NULL
Owner:	doc_demo	NULL
CreateTime:	Mon Jul 22 16:56:38 EDT 2013	NULL
LastAccessTime:	UNKNOWN	NULL
Protect Mode:	None	NULL
Retention:	0	NULL
Table Type:	VIRTUAL_VIEW	NULL
Table Parameters:	NULL	NULL
	transient_lastDdlTime	1374526598
	NULL	NULL
# Storage Information	NULL	NULL
SerDe Library:	null	NULL
InputFormat:	null	NULL
OutputFormat:	null	NULL
Compressed:	No	NULL
Num Buckets:	0	NULL
Bucket Columns:	[]	NULL
Sort Columns:	[]	NULL
	NULL	NULL
# View Information	NULL	NULL
View Original Text:	SELECT x, upper(s) FROM t1	NULL

```

| View Expanded Text: | SELECT x, upper(s) FROM t1 | NULL
+-----+
+-----+
Returned 28 row(s) in 0.03s
[localhost:21000] > create external table t2 (x int, y int, s string) stored
as parquet location '/user/doc_demo/sample_data';
[localhost:21000] > describe formatted t2;
Query: describe formatted t2
Query finished, fetching results ...
+-----+
+-----+
| name | comment | type |
+-----+
+-----+
| # col_name | comment | data_type |
| | | |
| x | NULL | int |
| y | None | int |
| s | None | string |
| | None | NULL |
| | NULL | |
| # Detailed Table Information | NULL |
| Database: | describe_formatted |
| Owner: | doc_demo |
| CreateTime: | Mon Jul 22 17:01:47 EDT 2013 |
| LastAccessTime: | UNKNOWN |
| Protect Mode: | None |
| Retention: | 0 |
| Location: | hdfs://127.0.0.1:8020/user/doc_demo/ |
sample_data | NULL |
| Table Type: | EXTERNAL_TABLE | |
| Table Parameters: | NULL |
| | EXTERNAL |
| | TRUE |
| | 1374526907 | transient_lastDdlTime |
| | NULL |
| # Storage Information | NULL |
| SerDe Library: |
org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe | NULL |
| InputFormat: |
org.apache.impala.hive.serde.ParquetInputFormat | NULL |
| OutputFormat: |
org.apache.impala.hive.serde.ParquetOutputFormat | NULL |
| Compressed: | No |
| NULL |

```

```

| Num Buckets: | 0
| | NULL |
| Bucket Columns: | []
| | NULL |
| Sort Columns: | []
| | NULL |
+-----+
+-----+
Returned 27 row(s) in 0.17s

```

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.)

Kudu considerations:

The information displayed for Kudu tables includes the additional attributes that are only applicable for Kudu tables:

- Whether or not the column is part of the primary key. Every Kudu table has a `true` value here for at least one column. There could be multiple `true` values, for tables with composite primary keys.
- Whether or not the column is nullable. Specified by the `NULL` or `NOT NULL` attributes on the `CREATE TABLE` statement. Columns that are part of the primary key are automatically non-nullable.
- The default value, if any, for the column. Specified by the `DEFAULT` attribute on the `CREATE TABLE` statement. If the default value is `NULL`, that is not indicated in this column. It is implied by nullable being true and no other default value specified.
- The encoding used for values in the column. Specified by the `ENCODING` attribute on the `CREATE TABLE` statement.
- The compression used for values in the column. Specified by the `COMPRESSION` attribute on the `CREATE TABLE` statement.
- The block size (in bytes) used for the underlying Kudu storage layer for the column. Specified by the `BLOCK_SIZE` attribute on the `CREATE TABLE` statement.

The following example shows `DESCRIBE` output for a simple Kudu table, with a single-column primary key and all column attributes left with their default values:

```

describe million_rows;
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| name | type   | comment | primary_key | nullable | default_value |
| encoding | compression | block_size |
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| id   | string |          | true        | false    |              |
| AUTO_ENCODING | DEFAULT_COMPRESSION | 0          |
| s    | string |          | false       | false    |              |
| AUTO_ENCODING | DEFAULT_COMPRESSION | 0          |
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+

```

The following example shows `DESCRIBE` output for a Kudu table with a two-column primary key, and Kudu-specific attributes applied to some columns:

```

create table kudu_describe_example
(
  c1 int, c2 int,

```

```

    c3 string, c4 string not null, c5 string default 'n/a', c6 string default
    '',
    c7 bigint not null, c8 bigint null default null, c9 bigint default -1
    encoding bit_shuffle,
    primary key(c1,c2)
)
partition by hash (c1, c2) partitions 10 stored as kudu;

```

```
describe kudu_describe_example;
```

name	type	comment	primary_key	nullable	default_value
encoding		compression		block_size	
c1	int		true	false	
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c2	int		true	false	
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c3	string		false	true	
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c4	string		false	false	
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c5	string		false	true	n/a
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c6	string		false	true	
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c7	bigint		false	false	
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c8	bigint		false	true	
AUTO_ENCODING		DEFAULT_COMPRESSION	0		
c9	bigint		false	true	-1
BIT_SHUFFLE		DEFAULT_COMPRESSION	0		

Related information:

[Overview of Impala Tables](#) on page 206, [CREATE TABLE Statement](#) on page 248, [SHOW TABLES Statement](#) on page 402, [SHOW CREATE TABLE Statement](#) on page 403

DROP DATABASE Statement

Removes a database from the system. The physical operations involve removing the metadata for the database from the metastore, and deleting the corresponding *.db directory from HDFS.

Syntax:

```
DROP (DATABASE|SCHEMA) [IF EXISTS] database_name [RESTRICT | CASCADE];
```

Statement type: DDL

Usage notes:

By default, the database must be empty before it can be dropped, to avoid losing any data.

In Impala 2.3 and higher, you can include the CASCADE clause to make Impala drop all tables and other objects in the database before dropping the database itself. The RESTRICT clause enforces the original requirement that the database be empty before being dropped. Because the RESTRICT behavior is still the default, this clause is optional.

The automatic dropping resulting from the CASCADE clause follows the same rules as the corresponding DROP TABLE, DROP VIEW, and DROP FUNCTION statements. In particular, the HDFS directories and data files for any external tables are left behind when the tables are removed.

When you do not use the `CASCADE` clause, drop or move all the objects inside the database manually before dropping the database itself:

- Use the `SHOW TABLES` statement to locate all tables and views in the database, and issue `DROP TABLE` and `DROP VIEW` statements to remove them all.
- Use the `SHOW FUNCTIONS` and `SHOW AGGREGATE FUNCTIONS` statements to locate all user-defined functions in the database, and issue `DROP FUNCTION` and `DROP AGGREGATE FUNCTION` statements to remove them all.
- To keep tables or views contained by a database while removing the database itself, use `ALTER TABLE` and `ALTER VIEW` to move the relevant objects to a different database before dropping the original database.

You cannot drop the current database, that is, the database your session connected to either through the `USE` statement or the `-d` option of `impala-shell`. Issue a `USE` statement to switch to a different database first. Because the default database is always available, issuing `USE default` is a convenient way to leave the current database before dropping it.

Hive considerations:

When you drop a database in Impala, the database can no longer be used by Hive.

Examples:

See [CREATE DATABASE Statement](#) on page 240 for examples covering `CREATE DATABASE`, `USE`, and `DROP DATABASE`.

Amazon S3 considerations:

In Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about reading and writing S3 data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for the directory associated with the database.

Examples:

```
create database first_db;
use first_db;
create table t1 (x int);

create database second_db;
use second_db;
-- Each database has its own namespace for tables.
-- You can reuse the same table names in each database.
create table t1 (s string);

create database temp;

-- You can either USE a database after creating it,
-- or qualify all references to the table name with the name of the
  database.
-- Here, tables T2 and T3 are both created in the TEMP database.

create table temp.t2 (x int, y int);
use database temp;
create table t3 (s string);

-- You cannot drop a database while it is selected by the USE statement.
```

```

drop database temp;
ERROR: AnalysisException: Cannot drop current default database: temp

-- The always-available database 'default' is a convenient one to USE
-- before dropping a database you created.
use default;

-- Before dropping a database, first drop all the tables inside it,
-- or in Impala 2.3 and higher use the CASCADE clause.
drop database temp;
ERROR: ImpalaRuntimeException: Error making 'dropDatabase' RPC to Hive
  Metastore:
CAUSED BY: InvalidOperationException: Database temp is not empty
show tables in temp;
+-----+
| name |
+-----+
| t3   |
+-----+

-- Impala 2.3 and higher:
drop database temp cascade;

-- Earlier releases:
drop table temp.t3;
drop database temp;

```

Related information:

[Overview of Impala Databases](#) on page 203, [CREATE DATABASE Statement](#) on page 240, [USE Statement](#) on page 421, [SHOW DATABASES](#) on page 401, [DROP TABLE Statement](#) on page 289

DROP FUNCTION Statement

Removes a user-defined function (UDF), so that it is not available for execution during Impala SELECT or INSERT operations.

Syntax:

To drop C++ UDFs and UDAs:

```

DROP [AGGREGATE] FUNCTION [IF EXISTS]
  [db_name.]function_name(type[, type...])

```

Note:

The preceding syntax, which includes the function signature, also applies to Java UDFs that were created using the corresponding CREATE FUNCTION syntax that includes the argument and return types. After upgrading to Impala 2.5 or higher, consider re-creating all Java UDFs with the CREATE FUNCTION syntax that does not include the function signature. Java UDFs created this way are now persisted in the metastore database and do not need to be re-created after an Impala restart.

To drop Java UDFs (created using the CREATE FUNCTION syntax with no function signature):

```

DROP FUNCTION [IF EXISTS] [db_name.]function_name

```

Statement type: DDL**Usage notes:**

Because the same function name could be overloaded with different argument signatures, you specify the argument types to identify the exact function to drop.

Restrictions:

In Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to Impala 2.5 the requirement to reload functions after a restart applied to both C++ and Java functions.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, does not need any particular HDFS permissions to perform this statement. All read and write operations are on the metastore database, not HDFS files and directories.

Examples:

The following example shows how to drop Java functions created with the signatureless `CREATE FUNCTION` syntax in Impala 2.5 and higher. Issuing `DROP FUNCTION function_name` removes all the overloaded functions under that name. (See [CREATE FUNCTION Statement](#) on page 242 for a longer example showing how to set up such functions in the first place.)

```
create function my_func location '/user/impala/udfs/udf-examples.jar'
  symbol='org.apache.impala.TestUdf';

show functions;
```

return type	signature	binary type	is persistent
BIGINT	my_func(BIGINT)	JAVA	true
BOOLEAN	my_func(BOOLEAN)	JAVA	true
BOOLEAN	my_func(BOOLEAN, BOOLEAN)	JAVA	true
...			
BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true
...			

```
drop function my_func;
show functions;
```

return type	signature	binary type	is persistent
BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true

...

Related information:

[User-Defined Functions \(UDFs\)](#) on page 588, [CREATE FUNCTION Statement](#) on page 242

DROP ROLE Statement (Impala 2.0 or higher only)

The `DROP ROLE` statement removes a role from the metastore database. Once dropped, the role is revoked for all users to whom it was previously assigned, and all privileges granted to that role are revoked. Queries that are already executing are not affected. Impala verifies the role information approximately every 60 seconds, so the effects of `DROP ROLE` might not take effect for new Impala queries for a brief period.

Syntax:

```
DROP ROLE role_name
```

Required privileges:

Only administrative users for Ranger can use this statement.

Compatibility:

Impala makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Hive, and Hive makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Impala. The Impala `GRANT` and `REVOKE` statements for privileges do not require the `ROLE` keyword to be repeated before each role name, unlike the equivalent Hive statements.

Related information:

[Impala Authorization](#) on page 83, [GRANT Statement \(Impala 2.0 or higher only\)](#) on page 294 [REVOKE Statement \(Impala 2.0 or higher only\)](#) on page 315, [CREATE ROLE Statement \(Impala 2.0 or higher only\)](#) on page 248, [SHOW Statement](#) on page 395

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

DROP STATS Statement

Removes the specified statistics from a table or partition. The statistics were originally created by the `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement.

Syntax:

```
DROP STATS [database_name.]table_name
DROP INCREMENTAL STATS [database_name.]table_name PARTITION (partition_spec)

partition_spec ::= partition_col=constant_value
```

The `PARTITION` clause is only allowed in combination with the `INCREMENTAL` clause. It is optional for `COMPUTE INCREMENTAL STATS`, and required for `DROP INCREMENTAL STATS`. Whenever you specify partitions through the `PARTITION (partition_spec)` clause in a `COMPUTE INCREMENTAL STATS` or `DROP INCREMENTAL STATS` statement, you must include all the partitioning columns in the specification, and specify constant values for all the partition key columns.

`DROP STATS` removes all statistics from the table, whether created by `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS`.

`DROP INCREMENTAL STATS` only affects incremental statistics for a single partition, specified through the `PARTITION` clause. The incremental stats are marked as outdated, so that they are recomputed by the next `COMPUTE INCREMENTAL STATS` statement.

Usage notes:

You typically use this statement when the statistics for a table or a partition have become stale due to data files being added to or removed from the associated HDFS data directories, whether by manual HDFS operations or `INSERT`, `INSERT OVERWRITE`, or `LOAD DATA` statements, or adding or dropping partitions.

When a table or partition has no associated statistics, Impala treats it as essentially zero-sized when constructing the execution plan for a query. In particular, the statistics influence the order in which tables are joined in a join query. To ensure proper query planning and good query performance and scalability, make sure to run `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` on the table or partition after removing any stale statistics.

Dropping the statistics is not required for an unpartitioned table or a partitioned table covered by the original type of statistics. A subsequent `COMPUTE STATS` statement replaces any existing statistics with new ones, for all partitions, regardless of whether the old ones were outdated. Therefore, this statement was rarely used before the introduction of incremental statistics.

Dropping the statistics is required for a partitioned table containing incremental statistics, to make a subsequent `COMPUTE INCREMENTAL STATS` statement rescan an existing partition. See [Table and Column Statistics](#) on page 625 for information about incremental statistics, a new feature available in Impala 2.1.0 and higher.

Statement type: DDL

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, does not need any particular HDFS permissions to perform this statement. All read and write operations are on the metastore database, not HDFS files and directories.

Examples:

The following example shows a partitioned table that has associated statistics produced by the `COMPUTE INCREMENTAL STATS` statement, and how the situation evolves as statistics are dropped from specific partitions, then the entire table.

Initially, all table and column statistics are filled in.

```
show table stats item_partitioned;
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	1783	1	227.97KB	NOT CACHED	PARQUET	true
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	10	2.25MB	0B		

```
show column stats item_partitioned;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
--------	------	------------------	--------	----------	----------

i_item_sk	INT	19443	-1	4	4
i_item_id	STRING	9025	-1	16	16
i_rec_start_date	TIMESTAMP	4	-1	16	16
i_rec_end_date	TIMESTAMP	3	-1	16	16
i_item_desc	STRING	13330	-1	200	
100.302803039					
i_current_price	FLOAT	2807	-1	4	4
i_wholesale_cost	FLOAT	2105	-1	4	4
i_brand_id	INT	965	-1	4	4
i_brand	STRING	725	-1	22	
16.1776008605					
i_class_id	INT	16	-1	4	4
i_class	STRING	101	-1	15	
7.76749992370					
i_category_id	INT	10	-1	4	4
i_manufact_id	INT	1857	-1	4	4
i_manufact	STRING	1028	-1	15	
11.3295001983					
i_size	STRING	8	-1	11	
4.33459997177					
i_formulation	STRING	12884	-1	20	
19.9799995422					
i_color	STRING	92	-1	10	
5.38089990615					
i_units	STRING	22	-1	7	
4.18690013885					
i_container	STRING	2	-1	7	
6.99259996414					
i_manager_id	INT	105	-1	4	4
i_product_name	STRING	19094	-1	25	
18.0233001708					
i_category	STRING	10	0	-1	-1
+-----+					
+-----+					

To remove statistics for particular partitions, use the `DROP INCREMENTAL STATS` statement. After removing statistics for two partitions, the table-level statistics reflect that change in the `#Rows` and `Incremental stats` fields. The counts, maximums, and averages of the column-level statistics are unaffected.

Note: (It is possible that the row count might be preserved in future after a `DROP INCREMENTAL STATS` statement. Check the resolution of the issue [IMPALA-1615](#).)

```
drop incremental stats item_partitioned partition (i_category='Sports');
drop incremental stats item_partitioned partition
(i_category='Electronics');
```

```
show table stats item_partitioned
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	-1	1	232.67KB	NOT CACHED	PARQUET	false
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	-1	1	227.97KB	NOT CACHED	PARQUET	false
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true

Total	17957	10	2.25MB	0B		
+-----+						
+-----+						
show column stats item_partitioned						
+-----+						
+-----+						
Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size	
+-----+						
+-----+						
i_item_sk	INT	19443	-1	4	4	
i_item_id	STRING	9025	-1	16	16	
i_rec_start_date	TIMESTAMP	4	-1	16	16	
i_rec_end_date	TIMESTAMP	3	-1	16	16	
i_item_desc	STRING	13330	-1	200		
100.302803039						
i_current_price	FLOAT	2807	-1	4	4	
i_wholesale_cost	FLOAT	2105	-1	4	4	
i_brand_id	INT	965	-1	4	4	
i_brand	STRING	725	-1	22		
16.1776008605						
i_class_id	INT	16	-1	4	4	
i_class	STRING	101	-1	15		
7.76749992370						
i_category_id	INT	10	-1	4	4	
i_manufact_id	INT	1857	-1	4	4	
i_manufact	STRING	1028	-1	15		
11.3295001983						
i_size	STRING	8	-1	11		
4.33459997177						
i_formulation	STRING	12884	-1	20		
19.9799995422						
i_color	STRING	92	-1	10		
5.38089990615						
i_units	STRING	22	-1	7		
4.18690013885						
i_container	STRING	2	-1	7		
6.99259996414						
i_manager_id	INT	105	-1	4	4	
i_product_name	STRING	19094	-1	25		
18.0233001708						
i_category	STRING	10	0	-1	-1	
+-----+						
+-----+						

To remove all statistics from the table, whether produced by `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS`, use the `DROP STATS` statement without the `INCREMENTAL` clause). Now, both table-level and column-level statistics are reset.

```
drop stats item_partitioned;
```

```
show table stats item_partitioned
```

+-----+						
+-----+						
i_category	#Rows	#Files	Size	Bytes Cached	Format	
+-----+						
+-----+						
Books	-1	1	223.74KB	NOT CACHED	PARQUET	false
Children	-1	1	230.05KB	NOT CACHED	PARQUET	false
Electronics	-1	1	232.67KB	NOT CACHED	PARQUET	false
Home	-1	1	232.56KB	NOT CACHED	PARQUET	false
Jewelry	-1	1	223.72KB	NOT CACHED	PARQUET	false

Men	-1	1	231.25KB	NOT CACHED	PARQUET	false
Music	-1	1	237.90KB	NOT CACHED	PARQUET	false
Shoes	-1	1	234.90KB	NOT CACHED	PARQUET	false
Sports	-1	1	227.97KB	NOT CACHED	PARQUET	false
Women	-1	1	226.27KB	NOT CACHED	PARQUET	false
Total	-1	10	2.25MB	0B		


```

+-----+
+-----+
show column stats item_partitioned
+-----+
+-----+
| Column          | Type          | #Distinct Values | #Nulls | Max Size | Avg
| Size |
+-----+
+-----+
| i_item_sk       | INT           | -1               | -1     | 4        | 4
| i_item_id       | STRING        | -1               | -1     | -1       | -1
| i_rec_start_date | TIMESTAMP     | -1               | -1     | 16       | 16
| i_rec_end_date   | TIMESTAMP     | -1               | -1     | 16       | 16
| i_item_desc      | STRING        | -1               | -1     | -1       | -1
| i_current_price  | FLOAT         | -1               | -1     | 4        | 4
| i_wholesale_cost | FLOAT         | -1               | -1     | 4        | 4
| i_brand_id       | INT           | -1               | -1     | 4        | 4
| i_brand          | STRING        | -1               | -1     | -1       | -1
| i_class_id       | INT           | -1               | -1     | 4        | 4
| i_class          | STRING        | -1               | -1     | -1       | -1
| i_category_id    | INT           | -1               | -1     | 4        | 4
| i_manufact_id    | INT           | -1               | -1     | 4        | 4
| i_manufact       | STRING        | -1               | -1     | -1       | -1
| i_size           | STRING        | -1               | -1     | -1       | -1
| i_formulation    | STRING        | -1               | -1     | -1       | -1
| i_color          | STRING        | -1               | -1     | -1       | -1
| i_units          | STRING        | -1               | -1     | -1       | -1
| i_container      | STRING        | -1               | -1     | -1       | -1
| i_manager_id     | INT           | -1               | -1     | 4        | 4
| i_product_name   | STRING        | -1               | -1     | -1       | -1
| i_category       | STRING        | 10               | 0      | -1       | -1
+-----+
+-----+

```

Related information:

[COMPUTE STATS Statement](#) on page 232, [SHOW TABLE STATS Statement](#) on page 406, [SHOW COLUMN STATS Statement](#) on page 408, [Table and Column Statistics](#) on page 625

DROP TABLE Statement

Removes an Impala table. Also removes the underlying HDFS data files for internal tables, although not for external tables.

Syntax:

```
DROP TABLE [IF EXISTS] [db_name.]table_name [PURGE]
```

IF EXISTS clause:

The optional `IF EXISTS` clause makes the statement succeed whether or not the table exists. If the table does exist, it is dropped; if it does not exist, the statement has no effect. This capability is useful in standardized setup scripts that remove existing schema objects and create new ones. By using some combination of `IF EXISTS` for the `DROP` statements and `IF NOT EXISTS` clauses for the `CREATE` statements, the script can run successfully the first time you run it (when the objects do not exist yet) and subsequent times (when some or all of the objects do already exist).

PURGE clause:

The optional `PURGE` keyword, available in Impala 2.3 and higher, causes Impala to remove the associated HDFS data files immediately, rather than going through the HDFS trashcan mechanism. Use this keyword when dropping a table if it is crucial to remove the data as quickly as possible to free up space, or if there is a problem with the trashcan, such as the trash cannot be configured or being in a different HDFS encryption zone than the data files.

Statement type: DDL

Usage notes:

By default, Impala removes the associated HDFS directory and data files for the table. If you issue a `DROP TABLE` and the data files are not deleted, it might be for the following reasons:

- If the table was created with the [EXTERNAL](#) clause, Impala leaves all files and directories untouched. Use external tables when the data is under the control of other Hadoop components, and Impala is only used to query the data files from their original locations.
- Impala might leave the data files behind unintentionally, if there is no HDFS location available to hold the HDFS trashcan for the `impala` user. See [User Account Requirements](#) on page 23 for the procedure to set up the required HDFS home directory.

Make sure that you are in the correct database before dropping a table, either by issuing a `USE` statement first or by using a fully qualified name `db_name.table_name`.

If you intend to issue a `DROP DATABASE` statement, first issue `DROP TABLE` statements to remove all the tables in that database.

Examples:

```
create database temporary;
use temporary;
create table unimportant (x int);
create table trivial (s string);
-- Drop a table in the current database.
drop table unimportant;
-- Switch to a different database.
use default;
-- To drop a table in a different database...
drop table trivial;
ERROR: AnalysisException: Table does not exist: default.trivial
-- ...use a fully qualified name.
drop table temporary.trivial;
```

For other tips about managing and reclaiming Impala disk space, see [Managing Disk Space for Impala Data](#) on page 73.

Amazon S3 considerations:

The `DROP TABLE` statement can remove data files from S3 if the associated S3 table is an internal table. In Impala 2.6 and higher, as part of improved support for writing to S3, Impala also removes the associated folder when dropping an internal table that resides on S3. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about working with S3 tables.

For best compatibility with the S3 write support in Impala 2.6 and higher:

- Use native Hadoop techniques to create data files in S3 for querying through Impala.
- Use the `PURGE` clause of `DROP TABLE` when dropping internal (managed) tables.

By default, when you drop an internal (managed) table, the data files are moved to the HDFS trashcan. This operation is expensive for tables that reside on the Amazon S3 object store. Therefore, for S3 tables, prefer to use `DROP TABLE table_name PURGE` rather than the default `DROP TABLE` statement. The `PURGE` clause makes Impala delete the data files immediately, skipping the HDFS trashcan. For the `PURGE` clause to work effectively, you must originally create the data files on S3 using one of the tools from the Hadoop ecosystem, such as `hadoop fs -cp`, or `INSERT` in Impala or Hive.

In Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about reading and writing S3 data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

For an internal table, the user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for all the files and directories that make up the table.

For an external table, dropping the table only involves changes to metadata in the metastore database. Because Impala does not remove any HDFS files or directories when external tables are dropped, no particular permissions are needed for the associated HDFS files or directories.

Kudu considerations:

Kudu tables can be managed or external, the same as with HDFS-based tables. For a managed table, the underlying Kudu table and its data are removed by `DROP TABLE`. For an external table, the underlying Kudu table and its data remain after a `DROP TABLE`.

Related information:

[Overview of Impala Tables](#) on page 206, [ALTER TABLE Statement](#) on page 215, [CREATE TABLE Statement](#) on page 248, [Partitioning for Impala Tables](#) on page 685, [Internal Tables](#) on page 206, [External Tables](#) on page 207

DROP VIEW Statement

Removes the specified view, which was originally created by the `CREATE VIEW` statement. Because a view is purely a logical construct (an alias for a query) with no physical data behind it, `DROP VIEW` only involves changes to metadata in the metastore database, not any data files in HDFS.

Syntax:

```
DROP VIEW [IF EXISTS] [db_name.]view_name
```

Statement type: DDL

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

The following example creates a series of views and then drops them. These examples illustrate how views are associated with a particular database, and both the view definitions and the view names for `CREATE VIEW` and `DROP VIEW` can refer to a view in the current database or a fully qualified view name.

```
-- Create and drop a view in the current database.
CREATE VIEW few_rows_from_t1 AS SELECT * FROM t1 LIMIT 10;
DROP VIEW few_rows_from_t1;

-- Create and drop a view referencing a table in a different database.
CREATE VIEW table_from_other_db AS SELECT x FROM db1.foo WHERE x IS NOT
  NULL;
DROP VIEW table_from_other_db;

USE db1;
-- Create a view in a different database.
CREATE VIEW db2.v1 AS SELECT * FROM db2.foo;
-- Switch into the other database and drop the view.
USE db2;
DROP VIEW v1;

USE db1;
-- Create a view in a different database.
CREATE VIEW db2.v1 AS SELECT * FROM db2.foo;
-- Drop a view in the other database.
DROP VIEW db2.v1;
```

Related information:

[Overview of Impala Views](#) on page 209, [CREATE VIEW Statement](#) on page 265, [ALTER VIEW Statement](#) on page 230

EXPLAIN Statement

Returns the execution plan for a statement, showing the low-level mechanisms that Impala will use to read the data, divide the work among nodes in the cluster, and transmit intermediate and final results across the network. Use `explain` followed by a complete `SELECT` query. For example:

Syntax:

```
EXPLAIN { select_query | ctas_stmt | insert_stmt }
```

The *select_query* is a `SELECT` statement, optionally prefixed by a `WITH` clause. See [SELECT Statement](#) on page 316 for details.

The *insert_stmt* is an `INSERT` statement that inserts into or overwrites an existing table. It can use either the `INSERT ... SELECT` or `INSERT ... VALUES` syntax. See [INSERT Statement](#) on page 298 for details.

The *ctas_stmt* is a `CREATE TABLE` statement using the `AS SELECT` clause, typically abbreviated as a “CTAS” operation. See [CREATE TABLE Statement](#) on page 248 for details.

Usage notes:

You can interpret the output to judge whether the query is performing efficiently, and adjust the query and/or the schema if not. For example, you might change the tests in the `WHERE` clause, add hints to make join operations more efficient, introduce subqueries, change the order of tables in a join, add or change partitioning for a table, collect column statistics and/or table statistics in Hive, or any other performance tuning steps.

The EXPLAIN output reminds you if table or column statistics are missing from any table involved in the query. These statistics are important for optimizing queries involving large tables or multi-table joins. See [COMPUTE STATS Statement](#) on page 232 for how to gather statistics, and [Table and Column Statistics](#) on page 625 for how to use this information for query tuning.

Read the EXPLAIN plan from bottom to top:

- The last part of the plan shows the low-level details such as the expected amount of data that will be read, where you can judge the effectiveness of your partitioning strategy and estimate how long it will take to scan a table based on total data size and the size of the cluster.
- As you work your way up, next you see the operations that will be parallelized and performed on each Impala node.
- At the higher levels, you see how data flows when intermediate result sets are combined and transmitted from one node to another.
- See [EXPLAIN_LEVEL Query Option](#) on page 357 for details about the EXPLAIN_LEVEL query option, which lets you customize how much detail to show in the EXPLAIN plan depending on whether you are doing high-level or low-level tuning, dealing with logical or physical aspects of the query.

If you come from a traditional database background and are not familiar with data warehousing, keep in mind that Impala is optimized for full table scans across very large tables. The structure and distribution of this data is typically not suitable for the kind of indexing and single-row lookups that are common in OLTP environments. Seeing a query scan entirely through a large table is common, not necessarily an indication of an inefficient query. Of course, if you can reduce the volume of scanned data by orders of magnitude, for example by using a query that affects only certain partitions within a partitioned table, then you might be able to optimize a query so that it executes in seconds rather than minutes.

The EXPLAIN output becomes more accurate and informative as statistics are gathered by the COMPUTE STATS statement. Initially, the information about data size and distribution, such as the number of rows or number of distinct values for each column, is marked "unavailable". The COMPUTE STATS statement performs the analysis, so a subsequent EXPLAIN statement has additional information to use in deciding how to optimize the distributed query.

For more information and examples to help you interpret EXPLAIN output, see [Using the EXPLAIN Plan for Performance Tuning](#) on page 655.

Extended EXPLAIN output:

For performance tuning of complex queries, and capacity planning (such as using the admission control and resource management features), you can enable more detailed and informative output for the EXPLAIN statement. In the `impala-shell` interpreter, issue the command `SET EXPLAIN_LEVEL=level`, where *level* is MINIMAL, STANDARD, EXTENDED, or VERBOSE.

When extended EXPLAIN output is enabled, EXPLAIN statements print information about estimated memory requirements, minimum number of virtual cores, and so on.

Starting in Impala 3.2, if the EXPLAIN_LEVEL option is set to EXTENDED level or VERBOSE, the output contains the following additional information.

- The analyzed query, in the output header.
The analyzed query may have been rewritten to include various optimizations and implicit casts. See the example below.
- The predicates in the plan output includes the same implicit casts and literals printed with a cast to show the type.

See [EXPLAIN_LEVEL Query Option](#) on page 357 for details and examples.

Examples:

This example shows how the standard EXPLAIN output moves from the lowest (physical) level to the higher (logical) levels.

1. The query begins by scanning a certain amount of data; each node performs an aggregation operation (evaluating `COUNT (*)`) on some subset of data that is local to that node.
2. The intermediate results are transmitted back to the coordinator node (labelled here as the EXCHANGE node).

3. Lastly, the intermediate results are summed to display the final result.

```
[impalad-host:21000] > EXPLAIN SELECT COUNT(*) FROM customer_address;
+-----+
| Explain String |
+-----+
| ...           |
| 03:AGGREGATE [FINALIZE] |
|   output: sum(count(*)) |
| 02:EXCHANGE [UNPARTITIONED] |
| 01:AGGREGATE |
|   output: count(*) |
| 00:SCAN HDFS [default.customer_address] |
|   partitions=1/1 size=5.25MB |
+-----+
```

The following example shows an extended EXPLAIN output. Note that the analyzed query was rewritten to include:

- The 'constant folding' optimization, which simplified the expression in the original query, '1000 / 100' to '10'.
- The implicit casts in the WHERE clause.

```
EXPLAIN SELECT * FROM functional_kudu.alltypestiny WHERE bigint_col < 1000 /
100;
+-----+
| Explain String |
+-----+
| ...           |
| Analyzed query: SELECT * FROM mytable WHERE CAST(bigint_col AS DOUBLE) <
| CAST(10 AS DOUBLE) |
| ...           |
| 00:SCAN KUDU [functional_kudu.alltypestiny] |
| predicates: CAST(bigint_col AS DOUBLE) < CAST(10 AS DOUBLE) |
| ...           |
```

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See the documentation for your Apache Hadoop distribution for details.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all applicable directories in all source tables for the query that is being explained. (A `SELECT` operation could read files from multiple different HDFS directories if the source table is partitioned.)

Kudu considerations:

The `EXPLAIN` statement displays equivalent plan information for queries against Kudu tables as for queries against HDFS-based tables.

To see which predicates Impala can “push down” to Kudu for efficient evaluation, without transmitting unnecessary rows back to Impala, look for the `kudu predicates` item in the scan phase of the query. The label `kudu predicates` indicates a condition that can be evaluated efficiently on the Kudu side. The label `predicates` in a `SCAN KUDU` node indicates a condition that is evaluated by Impala. For example, in a table with primary key column

X and non-primary key column Y, you can see that some operators in the WHERE clause are evaluated immediately by Kudu and others are evaluated later by Impala:

```
EXPLAIN SELECT x,y from kudu_table WHERE
  x = 1 AND y NOT IN (2,3) AND z = 1
  AND a IS NOT NULL AND b > 0 AND length(s) > 5;
+-----+
| Explain String
+-----+
...
| 00:SCAN KUDU [kudu_table]
|   predicates: y NOT IN (2, 3), length(s) > 5
|   kudu predicates: a IS NOT NULL, b > 0, x = 1, z = 1
```

Only binary predicates, IS NULL and IS NOT NULL (in Impala 2.9 and higher), and IN predicates containing literal values that exactly match the types in the Kudu table, and do not require any casting, can be pushed to Kudu.

Related information:

[SELECT Statement](#) on page 316, [INSERT Statement](#) on page 298, [CREATE TABLE Statement](#) on page 248, [Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles](#) on page 654

GRANT Statement (Impala 2.0 or higher only)

The GRANT statement grants a privilege on a specified object to a role, to a user, or to a group. The statement is also used to grant a role to a group.

Syntax:

The following syntax are supported in Impala through Ranger to manage authorization.

GRANT ROLE TO GROUP

For GRANT ROLE TO GROUP, only Ranger administrative users can grant roles to a group.

```
GRANT ROLE role_name TO GROUP group_name
```

GRANT privilege ON object TO PRINCIPAL

For GRANT privilege ON object TO principal (a user, a group, or a role), Ranger administrative users can use this statement. If the privilege is granted with the clause of WITH GRANT OPTION, the grantee (the user, the users belonging to the group, or the users belonging to the group granted the role) is able to grant the privilege to other principals.

```
GRANT privilege ON object_type object_name
  TO USER user_name
GRANT privilege ON object_type object_name
  TO GROUP group_name
GRANT privilege ON object_type object_name
  TO ROLE role_name

privilege ::= ALL | ALTER | CREATE | DROP | INSERT | REFRESH | SELECT |
  SELECT(column_name)
object_type ::= SERVER | URI | DATABASE | TABLE
```

Typically, the *object_name* is an identifier. For URIs, it is a string literal.

Required privileges:

Only administrative users for Ranger can use this statement.

Only Ranger administrative users can grant roles to a group.

The `WITH GRANT OPTION` clause allows members of the specified role to issue `GRANT` and `REVOKE` statements for those same privileges. Hence, if a role has the `ALL` privilege on a database and the `WITH GRANT OPTION` set, users granted that role can execute `GRANT/REVOKE` statements only for that database or child tables of the database. This means a user could revoke the privileges of the user that provided them the `GRANT OPTION`.

The ability to grant or revoke `SELECT` privilege on specific columns is available in Impala 2.3 and higher. See the documentation for Apache Sentry for details.

Usage notes:

You can only grant the `ALL` privilege to the `URI` object. Finer-grained privileges mentioned below on a `URI` are not supported.

The table below lists the minimum level of privileges and the scope required to execute SQL statements in Impala 3.0 and higher. The following notations are used:

- The **SERVER** resource type in Ranger implies all databases, all tables, all columns, all UDFs, and all URIs.
- **ANY** denotes the `SELECT`, `INSERT`, `CREATE`, `ALTER`, `DROP`, *or* `REFRESH` privilege.
- **ALL** privilege denotes the `SELECT`, `INSERT`, `CREATE`, `ALTER`, `DROP`, *and* `REFRESH` privileges.
- The owner of an object effectively has the `ALL` privilege on the object.
- The parent levels of the specified scope are implicitly supported where a scope refers to the specific level in the object hierarchy that the privilege is granted. For example, if a privilege is listed with the `TABLE` scope, the same privilege granted on `DATABASE` and `SERVER` will allow the user to execute the specified SQL statement.

SQL Statement	Privileges	Object Type / Resource Type
<code>SELECT</code>	<code>SELECT</code>	<code>TABLE</code>
<code>WITH SELECT</code>	<code>SELECT</code>	<code>TABLE</code>
<code>EXPLAIN SELECT</code>	<code>SELECT</code>	<code>TABLE</code>
<code>INSERT</code>	<code>INSERT</code>	<code>TABLE</code>
<code>EXPLAIN INSERT</code>	<code>INSERT</code>	<code>TABLE</code>
<code>TRUNCATE</code>	<code>INSERT</code>	<code>TABLE</code>
<code>LOAD</code>	<code>INSERT</code>	<code>TABLE</code>
	<code>ALL</code>	<code>URI</code>
<code>CREATE DATABASE</code>	<code>CREATE</code>	<code>SERVER</code>
<code>CREATE DATABASE LOCATION</code>	<code>CREATE</code>	<code>SERVER</code>
	<code>ALL</code>	<code>URI</code>
<code>CREATE TABLE</code>	<code>CREATE</code>	<code>DATABASE</code>
<code>CREATE TABLE LIKE</code>	<code>CREATE</code>	<code>DATABASE</code>
	<code>SELECT</code> , <code>INSERT</code> , <i>or</i> <code>REFRESH</code>	<code>TABLE</code>
<code>CREATE TABLE AS SELECT</code>	<code>CREATE</code>	<code>DATABASE</code>
	<code>INSERT</code>	<code>DATABASE</code>
	<code>SELECT</code>	<code>TABLE</code>
<code>EXPLAIN CREATE TABLE AS SELECT</code>	<code>CREATE</code>	<code>DATABASE</code>

	INSERT	DATABASE
	SELECT	TABLE
CREATE TABLE LOCATION	CREATE	TABLE
	ALL	URI
CREATE VIEW	CREATE	DATABASE
	SELECT	TABLE
ALTER DATABASE SET OWNER	ALL WITH GRANT	DATABASE
ALTER TABLE	ALTER	TABLE
ALTER TABLE SET LOCATION	ALTER	TABLE
	ALL	URI
ALTER TABLE RENAME	CREATE	DATABASE
	ALL	TABLE
ALTER TABLE SET OWNER	ALL WITH GRANT	TABLE
ALTER VIEW	ALTER	TABLE
	SELECT	TABLE
ALTER VIEW RENAME	CREATE	DATABASE
	ALL	TABLE
ALTER VIEW SET OWNER	ALL WITH GRANT	VIEW
DROP DATABASE	DROP	DATABASE
DROP TABLE	DROP	TABLE
DROP VIEW	DROP	TABLE
CREATE FUNCTION	CREATE	DATABASE
	ALL	URI
DROP FUNCTION	DROP	DATABASE
COMPUTE STATS	ALTER and SELECT	TABLE
DROP STATS	ALTER	TABLE
INVALIDATE METADATA	REFRESH	SERVER
INVALIDATE METADATA <table>	REFRESH	TABLE
REFRESH <table>	REFRESH	TABLE
REFRESH AUTHORIZATION	REFRESH	SERVER
REFRESH FUNCTIONS	REFRESH	DATABASE
COMMENT ON DATABASE	ALTER	DATABASE
COMMENT ON TABLE	ALTER	TABLE
COMMENT ON VIEW	ALTER	TABLE

COMMENT ON COLUMN	ALTER	TABLE
DESCRIBE DATABASE	SELECT, INSERT, <i>or</i> REFRESH	DATABASE
DESCRIBE <table/view>	SELECT, INSERT, <i>or</i> REFRESH	TABLE
If the user has the SELECT privilege at the COLUMN level, only the columns the user has access will show.	SELECT	COLUMN
USE	ANY	TABLE
SHOW DATABASES	ANY	TABLE
SHOW TABLES	ANY	TABLE
SHOW FUNCTIONS	SELECT, INSERT, <i>or</i> REFRESH	DATABASE
SHOW PARTITIONS	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW TABLE STATS	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW COLUMN STATS	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW FILES	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW CREATE TABLE	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW CREATE VIEW	SELECT, INSERT, <i>or</i> REFRESH	TABLE
SHOW CREATE FUNCTION	SELECT, INSERT, <i>or</i> REFRESH	DATABASE
SHOW RANGE PARTITIONS (Kudu only)	SELECT, INSERT, <i>or</i> REFRESH	TABLE
UPDATE (Kudu only)	ALL	TABLE
EXPLAIN UPDATE (Kudu only)	ALL	TABLE
UPSERT (Kudu only)	ALL	TABLE
WITH UPSERT (Kudu only)	ALL	TABLE
EXPLAIN UPSERT (Kudu only)	ALL	TABLE
DELETE (Kudu only)	ALL	TABLE
EXPLAIN DELETE (Kudu only)	ALL	TABLE

Compatibility:

- The Impala GRANT and REVOKE statements are available in Impala 2.0 and later.
- In general, Impala can make use of any roles and privileges specified by the GRANT and REVOKE statements in Hive, when your system is configured to use the Ranger service instead of the file-based policy mechanism.
- Currently, each Impala GRANT or REVOKE statement can only grant or revoke a single privilege to or from a single role.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Kudu considerations:

Access to Kudu tables must be granted to and revoked from principal with the following considerations:

- Only users with the ALL privilege on SERVER can create external Kudu tables.
- The ALL privileges on SERVER is required to specify the `kudu.master_addresses` property in the CREATE TABLE statements for managed tables as well as external tables.
- Access to Kudu tables is enforced at the table level and at the column level.
- The SELECT- and INSERT-specific permissions are supported.
- The DELETE, UPDATE, and UPSERT operations require the ALL privilege.

Related information:

[Impala Authorization](#) on page 83, [REVOKE Statement \(Impala 2.0 or higher only\)](#) on page 315, [CREATE ROLE Statement \(Impala 2.0 or higher only\)](#) on page 248, [DROP ROLE Statement \(Impala 2.0 or higher only\)](#) on page 284, [SHOW Statement](#) on page 395

INSERT Statement

Impala supports inserting into tables and partitions that you create with the Impala CREATE TABLE statement, or pre-defined tables and partitions created through Hive.

Syntax:

```
[with_clause]
INSERT [hint_clause] { INTO | OVERWRITE } [TABLE] table_name
[(column_list)]
[ PARTITION (partition_clause)]
{
    [hint_clause] select_statement
  | VALUES (value [, value ...]) [, (value [, value ...]) ...]
}

partition_clause ::= col_name [= constant] [, col_name [= constant] ...]

hint_clause ::=
    hint_with_dashes |
    hint_with_cstyle_delimiters |
    hint_with_brackets

hint_with_dashes ::= -- +SHUFFLE | -- +NOSHUFFLE -- +CLUSTERED

hint_with_cstyle_comments ::= /* +SHUFFLE */ | /* +NOSHUFFLE */ | /*
+CLUSTERED */

hint_with_brackets ::= [SHUFFLE] | [NOSHUFFLE]
    (With this hint format, the square brackets are part of the syntax.)
```

Note: The square bracket style of hint is now deprecated and might be removed in a future release. For that reason, any newly added hints are not available with the square bracket syntax.

Appending or replacing (INTO and OVERWRITE clauses):

The INSERT INTO syntax appends data to a table. The existing data files are left as-is, and the inserted data is put into one or more new data files.

The INSERT OVERWRITE syntax replaces the data in a table. Currently, the overwritten data files are deleted immediately; they do not go through the HDFS trash mechanism.

Complex type considerations:

The INSERT statement currently does not support writing data files containing complex types (ARRAY, STRUCT, and MAP). To prepare Parquet data for such tables, you generate the data files outside Impala and then use LOAD DATA or CREATE EXTERNAL TABLE to associate those data files with the table. Currently, such tables must use the Parquet file format. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about working with complex types.

Kudu considerations:

Currently, the `INSERT OVERWRITE` syntax cannot be used with Kudu tables.

Kudu tables require a unique primary key for each row. If an `INSERT` statement attempts to insert a row with the same values for the primary key columns as an existing row, that row is discarded and the insert operation continues. When rows are discarded due to duplicate primary keys, the statement finishes with a warning, not an error. (This is a change from early releases of Kudu where the default was to return in error in such cases, and the syntax `INSERT IGNORE` was required to make the statement succeed. The `IGNORE` clause is no longer part of the `INSERT` syntax.)

For situations where you prefer to replace rows with duplicate primary key values, rather than discarding the new data, you can use the `UPSERT` statement instead of `INSERT`. `UPSERT` inserts rows that are entirely new, and for rows that match an existing primary key in the table, the non-primary-key columns are updated to reflect the values in the “upserted” data.

If you really want to store new rows, not replace existing ones, but cannot do so because of the primary key uniqueness constraint, consider recreating the table with additional columns included in the primary key.

See [Using Impala to Query Kudu Tables](#) on page 733 for more details about using Impala with Kudu.

Usage notes:

Impala currently supports:

- Copy data from another table using `SELECT` query. In Impala 1.2.1 and higher, you can combine `CREATE TABLE` and `INSERT` operations into a single step with the `CREATE TABLE AS SELECT` syntax, which bypasses the actual `INSERT` keyword.
- An optional *[WITH clause](#)* before the `INSERT` keyword, to define a subquery referenced in the `SELECT` portion.
- Create one or more new rows using constant expressions through `VALUES` clause. (The `VALUES` clause was added in Impala 1.0.1.)
- By default, the first column of each newly inserted row goes into the first column of the table, the second column into the second column, and so on.

You can also specify the columns to be inserted, an arbitrarily ordered subset of the columns in the destination table, by specifying a column list immediately after the name of the destination table. This feature lets you adjust the inserted columns to match the layout of a `SELECT` statement, rather than the other way around. (This feature was added in Impala 1.1.)

The number of columns mentioned in the column list (known as the “column permutation”) must match the number of columns in the `SELECT` list or the `VALUES` tuples. The order of columns in the column permutation can be different than in the underlying table, and the columns of each input row are reordered to match. If the number of columns in the column permutation is less than in the destination table, all unmentioned columns are set to `NULL`.

- An optional hint clause immediately either before the `SELECT` keyword or after the `INSERT` keyword, to fine-tune the behavior when doing an `INSERT . . . SELECT` operation into partitioned Parquet tables. The hint clause cannot be specified in multiple places. The hint keywords are `[SHUFFLE]` and `[NOSHUFFLE]`, including the square brackets. Inserting into partitioned Parquet tables can be a resource-intensive operation because it potentially involves many files being written to HDFS simultaneously, and separate large memory buffers being allocated to buffer the data for each partition. For usage details, see [Loading Data into Parquet Tables](#) on page 706.

Note:

- Insert commands that partition or add files result in changes to Hive metadata. Because Impala uses Hive metadata, such changes may necessitate a metadata refresh. For more information, see the [REFRESH](#) function.
- Currently, Impala can only insert data into tables that use the text and Parquet formats. For other file formats, insert the data using Hive and use Impala to query it.
- As an alternative to the `INSERT` statement, if you have existing data files elsewhere in HDFS, the `LOAD DATA` statement can move those files into a table. This statement works with tables of any file format.

Statement type: DML (but still affected by [SYNC_DDL](#) query option)

Usage notes:

When you insert the results of an expression, particularly of a built-in function call, into a small numeric column such as INT, SMALLINT, TINYINT, or FLOAT, you might need to use a CAST() expression to coerce values into the appropriate type. Impala does not automatically convert from a larger type to a smaller one. For example, to insert cosine values into a FLOAT column, write CAST(COS(angle) AS FLOAT) in the INSERT statement to make the conversion explicit.

File format considerations:

Because Impala can read certain file formats that it cannot write, the INSERT statement does not work for all kinds of Impala tables. See [How Impala Works with Hadoop File Formats](#) on page 695 for details about what file formats are supported by the INSERT statement.

Any INSERT statement for a Parquet table requires enough free space in the HDFS filesystem to write one block. Because Parquet data files use a block size of 1 GB by default, an INSERT might fail (even for a very small amount of data) if your HDFS is running low on space.

If you connect to different Impala nodes within an impala-shell session for load-balancing purposes, you can enable the SYNC_DDL query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

Important: After adding or replacing data in a table used in performance-critical queries, issue a COMPUTE STATS statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any INSERT, LOAD DATA, or CREATE TABLE AS SELECT statement in Impala, or after loading data through Hive and doing a REFRESH table_name in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

The following example sets up new tables with the same definition as the TAB1 table from the [Tutorial](#) section, using different file formats, and demonstrates inserting data into the tables created with the STORED AS TEXTFILE and STORED AS PARQUET clauses:

```
CREATE DATABASE IF NOT EXISTS file_formats;
USE file_formats;

DROP TABLE IF EXISTS text_table;
CREATE TABLE text_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS TEXTFILE;

DROP TABLE IF EXISTS parquet_table;
CREATE TABLE parquet_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS PARQUET;
```

With the INSERT INTO TABLE syntax, each new set of inserted rows is appended to any existing data in the table. This is how you would record small amounts of data that arrive continuously, or ingest new batches of data alongside the existing data. For example, after running 2 INSERT INTO TABLE statements with 5 rows each, the table contains 10 rows total:

```
[localhost:21000] > insert into table text_table select * from default.tab1;
Inserted 5 rows in 0.41s

[localhost:21000] > insert into table text_table select * from default.tab1;
Inserted 5 rows in 0.46s

[localhost:21000] > select count(*) from text_table;
+-----+
| count(*) |
+-----+
| 10       |
```

```
+-----+
Returned 1 row(s) in 0.26s
```

With the `INSERT OVERWRITE TABLE` syntax, each new set of inserted rows replaces any existing data in the table. This is how you load data to query in a data warehousing scenario where you analyze just the data for a particular day, quarter, and so on, discarding the previous data each time. You might keep the entire set of data in one raw table, and transfer and transform certain rows into a more compact and efficient form to perform intensive analysis on that subset.

For example, here we insert 5 rows into a table using the `INSERT INTO` clause, then replace the data by inserting 3 rows with the `INSERT OVERWRITE` clause. Afterward, the table only contains the 3 rows from the final `INSERT` statement.

```
[localhost:21000] > insert into table parquet_table select * from
  default.tab1;
Inserted 5 rows in 0.35s

[localhost:21000] > insert overwrite table parquet_table select * from
  default.tab1 limit 3;
Inserted 3 rows in 0.43s
[localhost:21000] > select count(*) from parquet_table;
+-----+
| count(*) |
+-----+
| 3         |
+-----+
Returned 1 row(s) in 0.43s
```

The [VALUES](#) clause lets you insert one or more rows by specifying constant values for all the columns. The number, types, and order of the expressions must match the table definition.

Note: The `INSERT ... VALUES` technique is not suitable for loading large quantities of data into HDFS-based tables, because the insert operations cannot be parallelized, and each one produces a separate data file. Use it for setting up small dimension tables or tiny amounts of data for experimenting with SQL syntax, or with HBase tables. Do not use it for large ETL jobs or benchmark tests for load operations. Do not run scripts with thousands of `INSERT ... VALUES` statements that insert a single row each time. If you do run `INSERT ... VALUES` operations to load data into a staging table as one stage in an ETL pipeline, include multiple row values if possible within each `VALUES` clause, and use a separate database to make cleanup easier if the operation does produce many tiny files.

The following example shows how to insert one row or multiple rows, with expressions of different types, using literal values, expressions, and function return values:

```
create table val_test_1 (c1 int, c2 float, c3 string, c4 boolean, c5
  timestamp);
insert into val_test_1 values (100, 99.9/10, 'abc', true, now());
create table val_test_2 (id int, token string);
insert overwrite val_test_2 values (1, 'a'), (2, 'b'), (-1, 'xyzyzy');
```

These examples show the type of “not implemented” error that you see when attempting to insert data into a table with a file format that Impala currently does not write to:

```
DROP TABLE IF EXISTS sequence_table;
CREATE TABLE sequence_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS SEQUENCEFILE;

DROP TABLE IF EXISTS rc_table;
CREATE TABLE rc_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS RCFILE;
```

```
[localhost:21000] > insert into table rc_table select * from default.tab1;
Remote error
Backend 0:RC_FILE not implemented.

[localhost:21000] > insert into table sequence_table select * from
  default.tab1;
Remote error
Backend 0:SEQUENCE_FILE not implemented.
```

The following examples show how you can copy the data in all the columns from one table to another, copy the data from only some columns, or specify the columns in the select list in a different order than they actually appear in the table:

```
-- Start with 2 identical tables.
create table t1 (c1 int, c2 int);
create table t2 like t1;

-- If there is no () part after the destination table name,
-- all columns must be specified, either as * or by name.
insert into t2 select * from t1;
insert into t2 select c1, c2 from t1;

-- With the () notation following the destination table name,
-- you can omit columns (all values for that column are NULL
-- in the destination table), and/or reorder the values
-- selected from the source table. This is the "column permutation" feature.
insert into t2 (c1) select c1 from t1;
insert into t2 (c2, c1) select c1, c2 from t1;

-- The column names can be entirely different in the source and destination
-- tables.
-- You can copy any columns, not just the corresponding ones, from the
-- source table.
-- But the number and type of selected columns must match the columns
-- mentioned in the () part.
alter table t2 replace columns (x int, y int);
insert into t2 (y) select c1 from t1;
```

Sorting considerations: Although you can specify an `ORDER BY` clause in an `INSERT ... SELECT` statement, any `ORDER BY` clause is ignored and the results are not necessarily sorted. An `INSERT ... SELECT` operation potentially creates many different data files, prepared by different executor Impala daemons, and therefore the notion of the data being stored in sorted order is impractical.

Concurrency considerations: Each `INSERT` operation creates new data files with unique names, so you can run multiple `INSERT INTO` statements simultaneously without filename conflicts. While data is being inserted into an Impala table, the data is staged temporarily in a subdirectory inside the data directory; during this period, you cannot issue queries against that table in Hive. If an `INSERT` operation fails, the temporary data file and the subdirectory could be left behind in the data directory. If so, remove the relevant subdirectory and any data files it contains manually, by issuing an `hdfs dfs -rm -r` command, specifying the full path of the work subdirectory, whose name ends in `_dir`.

VALUES Clause

The `VALUES` clause is a general-purpose way to specify the columns of one or more rows, typically within an [INSERT](#) statement.

Note: The `INSERT ... VALUES` technique is not suitable for loading large quantities of data into HDFS-based tables, because the insert operations cannot be parallelized, and each one produces a separate data file. Use it for setting up small dimension tables or tiny amounts of data for experimenting with SQL syntax, or with HBase tables. Do not use it for large ETL jobs or benchmark tests for load operations. Do not run scripts with thousands of `INSERT ... VALUES` statements that insert a single row each time. If you do run `INSERT ... VALUES`

operations to load data into a staging table as one stage in an ETL pipeline, include multiple row values if possible within each VALUES clause, and use a separate database to make cleanup easier if the operation does produce many tiny files.

The following examples illustrate:

- How to insert a single row using a VALUES clause.
- How to insert multiple rows using a VALUES clause.
- How the row or rows from a VALUES clause can be appended to a table through `INSERT INTO`, or replace the contents of the table through `INSERT OVERWRITE`.
- How the entries in a VALUES clause can be literals, function results, or any other kind of expression. See [Literals](#) on page 173 for the notation to use for literal values, especially [String Literals](#) on page 175 for quoting and escaping conventions for strings. See [SQL Operators](#) on page 178 and [Impala Built-In Functions](#) on page 428 for other things you can include in expressions with the VALUES clause.

```
[localhost:21000] > describe val_example;
Query: describe val_example
Query finished, fetching results ...
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| id   | int  |          |
| col_1 | boolean |          |
| col_2 | double |          |
+-----+-----+-----+

[localhost:21000] > insert into val_example values (1,true,100.0);
Inserted 1 rows in 0.30s
[localhost:21000] > select * from val_example;
+-----+-----+-----+
| id | col_1 | col_2 |
+-----+-----+-----+
| 1  | true  | 100    |
+-----+-----+-----+

[localhost:21000] > insert overwrite val_example values (10,false,pow(2,5)),
(50,true,10/3);
Inserted 2 rows in 0.16s
[localhost:21000] > select * from val_example;
+-----+-----+-----+
| id | col_1 | col_2 |
+-----+-----+-----+
| 10 | false | 32     |
| 50 | true  | 3.333333333333333 |
+-----+-----+-----+
```

When used in an `INSERT` statement, the Impala VALUES clause can specify some or all of the columns in the destination table, and the columns can be specified in a different order than they actually appear in the table. To specify a different set or order of columns than in the table, use the syntax:

```
INSERT INTO destination
(col_x, col_y, col_z)
VALUES
(val_x, val_y, val_z);
```

Any columns in the table that are not listed in the `INSERT` statement are set to `NULL`.

HDFS considerations:

Impala physically writes all inserted files under the ownership of its default user, typically `impala`. Therefore, this user must have HDFS write permission in the corresponding table directory.

The permission requirement is independent of the authorization performed by the Ranger framework. (If the connected user is not authorized to insert into a table, Ranger blocks that operation immediately, regardless of the privileges available to the `impala` user.) Files created by Impala are not owned by and do not inherit permissions from the connected user.

The number of data files produced by an `INSERT` statement depends on the size of the cluster, the number of data blocks that are processed, the partition key columns in a partitioned table, and the mechanism Impala uses for dividing the work in parallel. Do not assume that an `INSERT` statement will produce some particular number of output files. In case of performance issues with data written by Impala, check that the output files do not suffer from issues such as many tiny files or many tiny partitions. (In the Hadoop context, even files or partitions of a few tens of megabytes are considered “tiny”.)

The `INSERT` statement has always left behind a hidden work directory inside the data directory of the table. Formerly, this hidden work directory was named `.impala_insert_staging`. In Impala 2.0.1 and later, this directory name is changed to `_impala_insert_staging`. (While HDFS tools are expected to treat names beginning either with underscore and dot as hidden, in practice names beginning with an underscore are more widely supported.) If you have any scripts, cleanup jobs, and so on that rely on the name of this work directory, adjust them to use the new name.

HBase considerations:

You can use the `INSERT` statement with HBase tables as follows:

- You can insert a single row or a small set of rows into an HBase table with the `INSERT . . . VALUES` syntax. This is a good use case for HBase tables with Impala, because HBase tables are not subject to the same kind of fragmentation from many small insert operations as HDFS tables are.
- You can insert any number of rows at once into an HBase table using the `INSERT . . . SELECT` syntax.
- If more than one inserted row has the same value for the HBase key column, only the last inserted row with that value is visible to Impala queries. You can take advantage of this fact with `INSERT . . . VALUES` statements to effectively update rows one at a time, by inserting new rows with the same key values as existing rows. Be aware that after an `INSERT . . . SELECT` operation copying from an HDFS table, the HBase table might contain fewer rows than were inserted, if the key column in the source table contained duplicate values.
- You cannot `INSERT OVERWRITE` into an HBase table. New rows are always appended.
- When you create an Impala or Hive table that maps to an HBase table, the column order you specify with the `INSERT` statement might be different than the order you declare with the `CREATE TABLE` statement. Behind the scenes, HBase arranges the columns based on how they are divided into column families. This might cause a mismatch during insert operations, especially if you use the syntax `INSERT INTO hbase_table SELECT * FROM hdfs_table`. Before inserting data, verify the column order by issuing a `DESCRIBE` statement for the table, and adjust the order of the select list in the `INSERT` statement.

See [Using Impala to Query HBase Tables](#) on page 750 for more details about using Impala with HBase.

Amazon S3 considerations:

In Impala 2.6 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in S3. The syntax of the DML statements is the same as for any other tables, because the S3 location for tables and partitions is specified by an `s3a://` prefix in the `LOCATION` attribute of `CREATE TABLE` or `ALTER TABLE` statements. If you bring data into S3 using the normal S3 transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the S3 data.

Because of differences between S3 and traditional filesystems, DML operations for S3 tables can take longer than for tables on HDFS. For example, both the `LOAD DATA` statement and the final stage of the `INSERT` and `CREATE TABLE AS SELECT` statements involve moving files from one directory to another. (In the case of `INSERT` and `CREATE TABLE AS SELECT`, the files are moved from a temporary staging directory to the final destination directory.) Because S3 does not support a “rename” operation for existing objects, in these cases Impala actually copies the data files from one location to another and then removes the original files. In Impala 2.6, the `S3_SKIP_INSERT_STAGING` query option provides a way to speed up `INSERT` statements for S3 tables and partitions, with the tradeoff that a problem during statement execution could leave data in an inconsistent state. It does

not apply to `INSERT OVERWRITE` or `LOAD DATA` statements. See [S3_SKIP_INSERT_STAGING Query Option](#) for details.

See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about reading and writing S3 data with Impala.

ADLS considerations:

In Impala 2.9 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in the Azure Data Lake Store (ADLS). ADLS Gen2 is supported in Impala 3.1 and higher.

In the `CREATE TABLE` or `ALTER TABLE` statements, specify the ADLS location for tables and partitions with the `adl://` prefix for ADLS Gen1 and `abfs://` or `abfss://` for ADLS Gen2 in the `LOCATION` attribute.

If you bring data into ADLS using the normal ADLS transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the ADLS data.

See [Using Impala with the Azure Data Lake Store \(ADLS\)](#) on page 774 for details about reading and writing ADLS data with Impala.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See the documentation for your Apache Hadoop distribution for details.

Cancellation: Can be cancelled. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permission for the files in the source directory of an `INSERT ... SELECT` operation, and write permission for all affected directories in the destination table. (An `INSERT` operation could write files to multiple different HDFS directories if the destination table is partitioned.) This user must also have write permission to create a temporary work directory in the top-level HDFS directory of the destination table. An `INSERT OVERWRITE` operation does not require write permission on the original data files in the table, only on the table directories themselves.

Restrictions:

For `INSERT` operations into `CHAR` or `VARCHAR` columns, you must cast all `STRING` literals or expressions returning `STRING` to to a `CHAR` or `VARCHAR` type with the appropriate length.

Related startup options:

By default, if an `INSERT` statement creates any new subdirectories underneath a partitioned table, those subdirectories are assigned default HDFS permissions for the `impala` user. To make each subdirectory have the same permissions as its parent directory in HDFS, specify the `##insert_inherit_permissions` startup option for the `impalad` daemon.

Inserting Into Partitioned Tables with PARTITION Clause

For a partitioned table, the optional `PARTITION` clause identifies which partition or partitions the values are inserted into.

All examples in this section will use the table declared as below:

```
CREATE TABLE t1 (w INT) PARTITIONED BY (x INT, y STRING);
```

Static Partition Inserts

In a static partition insert where a partition key column is given a constant value, such as `PARTITION (year=2012, month=2)`, the rows are inserted with the same values specified for those partition key columns.

The number of columns in the `SELECT` list must equal the number of columns in the column permutation.

The `PARTITION` clause must be used for static partitioning inserts.

Example:

The following statement will insert the `some_other_table.c1` values for the `w` column, and all the rows inserted will have the same `x` value of 10, and the same `y` value of 'a'.

```
INSERT INTO t1 PARTITION (x=10, y='a')
      SELECT c1 FROM some_other_table;
```

Dynamic Partition Inserts

In a dynamic partition insert where a partition key column is in the `INSERT` statement but not assigned a value, such as in `PARTITION (year, region)` (both columns unassigned) or `PARTITION(year, region='CA')` (`year` column unassigned), the unassigned columns are filled in with the final columns of the `SELECT` or `VALUES` clause. In this case, the number of columns in the `SELECT` list must equal the number of columns in the column permutation plus the number of partition key columns not assigned a constant value.

See [Static and Dynamic Partitioning Clauses](#) on page 687 for examples and performance characteristics of static and dynamic partitioned inserts.

The following rules apply to dynamic partition inserts.

- The columns are bound in the order they appear in the `INSERT` statement.

The table below shows the values inserted with the `INSERT` statements of different column orders.

	Column w Value	Column x Value	Column y Value
<code>INSERT INTO t1 (w, x, y) VALUES (1, 2, 'c');</code>	1	2	'c'
<code>INSERT INTO t1 (x,w) PARTITION (y) VALUES (1, 2, 'c');</code>	2	1	'c'

- When a partition clause is specified but the non-partition columns are not specified in the `INSERT` statement, as in the first example below, the non-partition columns are treated as though they had been specified before the `PARTITION` clause in the `SQL`.

Example: These three statements are equivalent, inserting 1 to `w`, 2 to `x`, and 'c' to `y` columns.

```
INSERT INTO t1 PARTITION (x,y) VALUES (1, 2, 'c');
INSERT INTO t1 (w) PARTITION (x, y) VALUES (1, 2, 'c');
INSERT INTO t1 PARTITION (x, y='c') VALUES (1, 2);
```

- The `PARTITION` clause is not required for dynamic partition, but all the partition columns must be explicitly present in the `INSERT` statement in the column list or in the `PARTITION` clause. The partition columns cannot be defaulted to `NULL`.

Example:

The following statements are valid because the partition columns, `x` and `y`, are present in the `INSERT` statements, either in the `PARTITION` clause or in the column list.

```
INSERT INTO t1 PARTITION (x,y) VALUES (1, 2, 'c');
INSERT INTO t1 (w, x) PARTITION (y) VALUES (1, 2, 'c');
```

The following statement is not valid for the partitioned table as defined above because the partition columns, `x` and `y`, are not present in the `INSERT` statement.

```
INSERT INTO t1 VALUES (1, 2, 'c');
```

- If partition columns do not exist in the source table, you can specify a specific value for that column in the `PARTITION` clause.

Example: The source table only contains the column `w` and `y`. The value, 20, specified in the `PARTITION` clause, is inserted into the `x` column.

```
INSERT INTO t1 PARTITION (x=20, y) SELECT * FROM source;
```

INVALIDATE METADATA Statement

The `INVALIDATE METADATA` statement marks the metadata for one or all tables as stale. The next time the Impala service performs a query against a table whose metadata is invalidated, Impala reloads the associated metadata before the query proceeds. As this is a very expensive operation compared to the incremental metadata update done by the `REFRESH` statement, when possible, prefer `REFRESH` rather than `INVALIDATE METADATA`.

`INVALIDATE METADATA` is required when the following changes are made outside of Impala, in Hive and other Hive client, such as SparkSQL:

- Metadata of existing tables changes.
- New tables are added, and Impala will use the tables.
- The `SERVER` or `DATABASE` level Ranger privileges are changed.
- Block metadata changes, but the files remain the same (HDFS rebalance).
- UDF jars change.
- Some tables are no longer queried, and you want to remove their metadata from the catalog and coordinator caches to reduce memory requirements.

No `INVALIDATE METADATA` is needed when the changes are made by `impalad`.

See [Overview of Impala Metadata and the Metastore](#) on page 21 for the information about the way Impala uses metadata and how it shares the same metastore database as Hive.

Once issued, the `INVALIDATE METADATA` statement cannot be cancelled.

Syntax:

```
INVALIDATE METADATA [[db_name.]table_name]
```

If there is no table specified, the cached metadata for all tables is flushed and synced with Hive Metastore (HMS). If tables were dropped from the HMS, they will be removed from the catalog, and if new tables were added, they will show up in the catalog.

If you specify a table name, only the metadata for that one table is flushed and synced with the HMS.

Usage notes:

To return accurate query results, Impala need to keep the metadata current for the databases and tables queried. Therefore, if some other entity modifies information used by Impala in the metastore, the information cached by Impala must be updated via `INVALIDATE METADATA` or `REFRESH`.

`INVALIDATE METADATA` and `REFRESH` are counterparts:

- `INVALIDATE METADATA` is an asynchronous operations that simply discards the loaded metadata from the catalog and coordinator caches. After that operation, the catalog and all the Impala coordinators only know about the existence of databases and tables and nothing more. Metadata loading for tables is triggered by any subsequent queries.

- **REFRESH** reloads the metadata synchronously. **REFRESH** is more lightweight than doing a full metadata load after a table has been invalidated. **REFRESH** cannot detect changes in block locations triggered by operations like HDFS balancer, hence causing remote reads during query execution with negative performance implications.

Use **REFRESH** after invalidating a specific table to separate the metadata load from the first query that's run against that table.

Examples:

This example illustrates creating a new database and new table in Hive, then doing an **INVALIDATE METADATA** statement in Impala using the fully qualified table name, after which both the new table and the new database are visible to Impala.

Before the **INVALIDATE METADATA** statement was issued, Impala would give a “not found” error if you tried to refer to those database or table names.

```
$ hive
hive> CREATE DATABASE new_db_from_hive;
hive> CREATE TABLE new_db_from_hive.new_table_from_hive (x INT);
hive> quit;

$ impala-shell
> REFRESH new_db_from_hive.new_table_from_hive;
ERROR: AnalysisException: Database does not exist: new_db_from_hive

> INVALIDATE METADATA new_db_from_hive.new_table_from_hive;

> SHOW DATABASES LIKE 'new*';
+-----+
| new_db_from_hive |
+-----+

> SHOW TABLES IN new_db_from_hive;
+-----+
| new_table_from_hive |
+-----+
```

Use the **REFRESH** statement for incremental metadata update.

```
> REFRESH new_table_from_hive;
```

For more examples of using **INVALIDATE METADATA** with a combination of Impala and Hive operations, see [Switching Back and Forth Between Impala and Hive](#) on page 50.

HDFS considerations:

By default, the **INVALIDATE METADATA** command checks HDFS permissions of the underlying data files and directories, caching this information so that a statement can be cancelled immediately if for example the `impala` user does not have permission to write to the data directory for the table. (This checking does not apply when the `catalogd` configuration option `--load_catalog_in_background` is set to `false`, which it is by default.) Impala reports any lack of write permissions as an **INFO** message in the log file.

If you change HDFS permissions to make data readable or writeable by the Impala user, issue another **INVALIDATE METADATA** to make Impala aware of the change.

Kudu considerations:

By default, much of the metadata for Kudu tables is handled by the underlying storage layer. Kudu tables have less reliance on the Metastore database, and require less metadata caching on the Impala side. For example, information about partitions in Kudu tables is managed by Kudu, and Impala does not cache any block locality metadata for Kudu tables. If the Kudu service is not integrated with the Hive Metastore, Impala will manage Kudu table metadata in the Hive Metastore.

The `REFRESH` and `INVALIDATE METADATA` statements are needed less frequently for Kudu tables than for HDFS-backed tables. Neither statement is needed when data is added to, removed, or updated in a Kudu table, even if the changes are made directly to Kudu through a client program using the Kudu API. Run `REFRESH table_name` or `INVALIDATE METADATA table_name` for a Kudu table only after making a change to the Kudu table schema, such as adding or dropping a column.

Related information:

[Overview of Impala Metadata and the Metastore](#) on page 21, [REFRESH Statement](#) on page 312

LOAD DATA Statement

The `LOAD DATA` statement streamlines the ETL process for an internal Impala table by moving a data file or all the data files in a directory from an HDFS location into the Impala data directory for that table.

Syntax:

```
LOAD DATA INPATH 'hdfs_file_or_directory_path' [OVERWRITE] INTO
TABLE tablename
[PARTITION (partcol1=val1, partcol2=val2 ...)]
```

When the `LOAD DATA` statement operates on a partitioned table, it always operates on one partition at a time. Specify the `PARTITION` clauses and list all the partition key columns, with a constant value specified for each.

Statement type: DML (but still affected by [SYNC_DDL](#) query option)

Usage notes:

- The loaded data files are moved, not copied, into the Impala data directory.
- You can specify the HDFS path of a single file to be moved, or the HDFS path of a directory to move all the files inside that directory. You cannot specify any sort of wildcard to take only some of the files from a directory. When loading a directory full of data files, keep all the data files at the top level, with no nested directories underneath.
- Currently, the Impala `LOAD DATA` statement only imports files from HDFS, not from the local filesystem. It does not support the `LOCAL` keyword of the Hive `LOAD DATA` statement. You must specify a path, not an `hdfs://` URI.
- In the interest of speed, only limited error checking is done. If the loaded files have the wrong file format, different columns than the destination table, or other kind of mismatch, Impala does not raise any error for the `LOAD DATA` statement. Querying the table afterward could produce a runtime error or unexpected results. Currently, the only checking the `LOAD DATA` statement does is to avoid mixing together uncompressed and LZO-compressed text files in the same table.
- When you specify an HDFS directory name as the `LOAD DATA` argument, any hidden files in that directory (files whose names start with a `.`) are not moved to the Impala data directory.
- The operation fails if the source directory contains any non-hidden directories. Prior to Impala 2.5 if the source directory contained any subdirectory, even a hidden one such as `_impala_insert_staging`, the `LOAD DATA` statement would fail. In Impala 2.5 and higher, `LOAD DATA` ignores hidden subdirectories in the source directory, and only fails if any of the subdirectories are non-hidden.
- The loaded data files retain their original names in the new location, unless a name conflicts with an existing data file, in which case the name of the new file is modified slightly to be unique. (The name-mangling is a slight difference from the Hive `LOAD DATA` statement, which replaces identically named files.)
- By providing an easy way to transport files from known locations in HDFS into the Impala data directory structure, the `LOAD DATA` statement lets you avoid memorizing the locations and layout of HDFS directory tree containing the Impala databases and tables. (For a quick way to check the location of the data files for an Impala table, issue the statement `DESCRIBE FORMATTED table_name`.)
- The `PARTITION` clause is especially convenient for ingesting new data for a partitioned table. As you receive new data for a time period, geographic region, or other division that corresponds to one or more partitioning columns, you can load that data straight into the appropriate Impala data directory, which might be nested several levels down if the table is partitioned by multiple columns. When the table is partitioned, you must specify constant values for all the partitioning columns.

Complex type considerations:

Because Impala currently cannot create Parquet data files containing complex types (ARRAY, STRUCT, and MAP), the `LOAD DATA` statement is especially important when working with tables containing complex type columns. You create the Parquet data files outside Impala, then use either `LOAD DATA`, an external table, or HDFS-level file operations followed by `REFRESH` to associate the data files with the corresponding table. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 393 for details.

Important: After adding or replacing data in a table used in performance-critical queries, issue a `COMPUTE STATS` statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any `INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT` statement in Impala, or after loading data through Hive and doing a `REFRESH table_name` in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

First, we use a trivial Python script to write different numbers of strings (one per line) into files stored in the `doc_demo` HDFS user account. (Substitute the path for your own HDFS user account when doing `hdfs dfs` operations like these.)

```
$ random_strings.py 1000 | hdfs dfs -put - /user/doc_demo/
thousand_strings.txt
$ random_strings.py 100 | hdfs dfs -put - /user/doc_demo/hundred_strings.txt
$ random_strings.py 10 | hdfs dfs -put - /user/doc_demo/ten_strings.txt
```

Next, we create a table and load an initial set of data into it. Remember, unless you specify a `STORED AS` clause, Impala tables default to `TEXTFILE` format with Ctrl-A (hex 01) as the field delimiter. This example uses a single-column table, so the delimiter is not significant. For large-scale ETL jobs, you would typically use binary format data files such as Parquet or Avro, and load them into Impala tables that use the corresponding file format.

```
[localhost:21000] > create table t1 (s string);
[localhost:21000] > load data inpath '/user/doc_demo/thousand_strings.txt'
into table t1;
Query finished, fetching results ...
+-----+
| summary |
+-----+
| Loaded 1 file(s). Total files in destination location: 1 |
+-----+
Returned 1 row(s) in 0.61s
[kilo2-202-961.cs1cloud.internal:21000] > select count(*) from t1;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 1000 |
+-----+
Returned 1 row(s) in 0.67s
[localhost:21000] > load data inpath '/user/doc_demo/thousand_strings.txt'
into table t1;
ERROR: AnalysisException: INPATH location '/user/doc_demo/
thousand_strings.txt' does not exist.
```

As indicated by the message at the end of the previous example, the data file was moved from its original location. The following example illustrates how the data file was moved into the Impala data directory for the destination table, keeping its original filename:

```
$ hdfs dfs -ls /user/hive/warehouse/load_data_testing.db/t1
```

```
Found 1 items
-rw-r--r-- 1 doc_demo doc_demo      13926 2013-06-26 15:40 /user/hive/
warehouse/load_data_testing.db/t1/thousand_strings.txt
```

The following example demonstrates the difference between the `INTO TABLE` and `OVERWRITE TABLE` clauses. The table already contains 1000 rows. After issuing the `LOAD DATA` statement with the `INTO TABLE` clause, the table contains 100 more rows, for a total of 1100. After issuing the `LOAD DATA` statement with the `OVERWRITE INTO TABLE` clause, the former contents are gone, and now the table only contains the 10 rows from the just-loaded data file.

```
[localhost:21000] > load data inpath '/user/doc_demo/hundred_strings.txt'
into table t1;
Query finished, fetching results ...
+-----+
| summary |
+-----+
| Loaded 1 file(s). Total files in destination location: 2 |
+-----+
Returned 1 row(s) in 0.24s
[localhost:21000] > select count(*) from t1;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 1100 |
+-----+
Returned 1 row(s) in 0.55s
[localhost:21000] > load data inpath '/user/doc_demo/ten_strings.txt'
overwrite into table t1;
Query finished, fetching results ...
+-----+
| summary |
+-----+
| Loaded 1 file(s). Total files in destination location: 1 |
+-----+
Returned 1 row(s) in 0.26s
[localhost:21000] > select count(*) from t1;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 10 |
+-----+
Returned 1 row(s) in 0.62s
```

Amazon S3 considerations:

In Impala 2.6 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in S3. The syntax of the DML statements is the same as for any other tables, because the S3 location for tables and partitions is specified by an `s3a://` prefix in the `LOCATION` attribute of `CREATE TABLE` or `ALTER TABLE` statements. If you bring data into S3 using the normal S3 transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the S3 data.

Because of differences between S3 and traditional filesystems, DML operations for S3 tables can take longer than for tables on HDFS. For example, both the `LOAD DATA` statement and the final stage of the `INSERT` and `CREATE TABLE AS SELECT` statements involve moving files from one directory to another. (In the case of `INSERT` and `CREATE TABLE AS SELECT`, the files are moved from a temporary staging directory to the final destination directory.) Because S3 does not support a “rename” operation for existing objects, in these cases Impala actually copies the data files from one location to another and then removes the original files. In Impala 2.6, the `S3_SKIP_INSERT_STAGING` query option provides a way to speed up `INSERT` statements for S3 tables and

partitions, with the tradeoff that a problem during statement execution could leave data in an inconsistent state. It does not apply to `INSERT OVERWRITE` or `LOAD DATA` statements. See [S3_SKIP_INSERT_STAGING Query Option](#) for details.

See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about reading and writing S3 data with Impala.

ADLS considerations:

In Impala 2.9 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in the Azure Data Lake Store (ADLS). ADLS Gen2 is supported in Impala 3.1 and higher.

In the `CREATE TABLE` or `ALTER TABLE` statements, specify the ADLS location for tables and partitions with the `adl://` prefix for ADLS Gen1 and `abfs://` or `abfss://` for ADLS Gen2 in the `LOCATION` attribute.

If you bring data into ADLS using the normal ADLS transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the ADLS data.

See [Using Impala with the Azure Data Lake Store \(ADLS\)](#) on page 774 for details about reading and writing ADLS data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and write permissions for the files in the source directory, and write permission for the destination directory.

Kudu considerations:

The `LOAD DATA` statement cannot be used with Kudu tables.

HBase considerations:

The `LOAD DATA` statement cannot be used with HBase tables.

Iceberg considerations:

See [Loading data into Iceberg tables](#) on page 765 for details about `LOAD DATA` with Iceberg.

Related information:

The `LOAD DATA` statement is an alternative to the [INSERT](#) statement. Use `LOAD DATA` when you have the data files in HDFS but outside of any Impala table.

The `LOAD DATA` statement is also an alternative to the `CREATE EXTERNAL TABLE` statement. Use `LOAD DATA` when it is appropriate to move the data files under Impala control rather than querying them from their original location. See [External Tables](#) on page 207 for information about working with external tables.

REFRESH Statement

The `REFRESH` statement reloads the metadata for the table from the metastore database and does an incremental reload of the file and block metadata from the HDFS NameNode. `REFRESH` is used to avoid inconsistencies between Impala and external metadata sources, namely Hive Metastore (HMS) and NameNodes.

The `REFRESH` statement is only required if you load data from outside of Impala. Updated metadata, as a result of running `REFRESH`, is broadcast to all Impala coordinators.

See [Overview of Impala Metadata and the Metastore](#) on page 21 for the information about the way Impala uses metadata and how it shares the same metastore database as Hive.

Once issued, the `REFRESH` statement cannot be cancelled.

Syntax:

```
REFRESH [db_name.]table_name [PARTITION (key_col1=val1
[, key_col2=val2...])]
```

Usage notes:

The table name is a required parameter, and the table must already exist and be known to Impala.

Only the metadata for the specified table is reloaded.

Use the REFRESH statement to load the latest metastore metadata for a particular table after one of the following scenarios happens outside of Impala:

- Deleting, adding, or modifying files.
For example, after loading new data files into the HDFS data directory for the table, appending to an existing HDFS file, inserting data from Hive via INSERT or LOAD DATA.
- Deleting, adding, or modifying partitions.

For example, after issuing ALTER TABLE or other table-modifying SQL statement in Hive

Note:

In Impala 2.3 and higher, the ALTER TABLE *table_name* RECOVER PARTITIONS statement is a faster alternative to REFRESH when you are only adding new partition directories through Hive or manual HDFS operations. See [ALTER TABLE Statement](#) on page 215 for details.

INVALIDATE METADATA and REFRESH are counterparts:

- INVALIDATE METADATA is an asynchronous operations that simply discards the loaded metadata from the catalog and coordinator caches. After that operation, the catalog and all the Impala coordinators only know about the existence of databases and tables and nothing more. Metadata loading for tables is triggered by any subsequent queries.
- REFRESH reloads the metadata synchronously. REFRESH is more lightweight than doing a full metadata load after a table has been invalidated. REFRESH cannot detect changes in block locations triggered by operations like HDFS balancer, hence causing remote reads during query execution with negative performance implications.

Refreshing a single partition:

In Impala 2.7 and higher, the REFRESH statement can apply to a single partition at a time, rather than the whole table. Include the optional PARTITION (*partition_spec*) clause and specify values for each of the partition key columns.

The following rules apply:

- The PARTITION clause of the REFRESH statement must include all the partition key columns.
- The order of the partition key columns does not have to match the column order in the table.
- Specifying a nonexistent partition does not cause an error.
- The partition can be one that Impala created and is already aware of, or a new partition created through Hive.

The following examples demonstrates the above rules.

```
-- Partition doesn't exist.
refresh p2 partition (y=0, z=3);
refresh p2 partition (y=0, z=-1)

-- Key columns specified in a different order than the table definition.
refresh p2 partition (z=1, y=0)

-- Incomplete partition spec causes an error.
refresh p2 partition (y=0)
ERROR: AnalysisException: Items in partition spec must exactly match the
partition columns in the table definition: default.p2 (1 vs 2)
```

For examples of using `REFRESH` and `INVALIDATE METADATA` with a combination of Impala and Hive operations, see [Switching Back and Forth Between Impala and Hive](#) on page 50.

Related impala-shell options:

Due to the expense of reloading the metadata for all tables, the `impala-shell -r` option is not recommended.

HDFS permissions:

All HDFS and Ranger permissions and privilege requirements are the same whether you refresh the entire table or a single partition.

HDFS considerations:

The `REFRESH` statement checks HDFS permissions of the underlying data files and directories, caching this information so that a statement can be cancelled immediately if for example the `impala` user does not have permission to write to the data directory for the table. Impala reports any lack of write permissions as an `INFO` message in the log file.

If you change HDFS permissions to make data readable or writeable by the Impala user, issue another `REFRESH` to make Impala aware of the change.

Kudu considerations:

By default, much of the metadata for Kudu tables is handled by the underlying storage layer. Kudu tables have less reliance on the Metastore database, and require less metadata caching on the Impala side. For example, information about partitions in Kudu tables is managed by Kudu, and Impala does not cache any block locality metadata for Kudu tables. If the Kudu service is not integrated with the Hive Metastore, Impala will manage Kudu table metadata in the Hive Metastore.

The `REFRESH` and `INVALIDATE METADATA` statements are needed less frequently for Kudu tables than for HDFS-backed tables. Neither statement is needed when data is added to, removed, or updated in a Kudu table, even if the changes are made directly to Kudu through a client program using the Kudu API. Run `REFRESH table_name` or `INVALIDATE METADATA table_name` for a Kudu table only after making a change to the Kudu table schema, such as adding or dropping a column.

Related information:

[Overview of Impala Metadata and the Metastore](#) on page 21, [INVALIDATE METADATA Statement](#) on page 307

REFRESH AUTHORIZATION Statement

The `REFRESH AUTHORIZATION` statement explicitly refreshes authorization data, including privileges and principals. When there is an external update to authorization metadata, use this statement to force Impala to refresh its authorization data without having to wait for the Ranger polling or run `INVALIDATE METADATA`.

Once issued, the `REFRESH AUTHORIZATION` statement cannot be cancelled.

See [Impala Authorization](#) for information on enabling and using authorization in Impala.

Syntax:

```
REFRESH AUTHORIZATION
```

Usage notes: If authorization is not enabled, Impala returns an error.

Added in: Impala 3.2

REFRESH FUNCTIONS Statement

In Impala 2.9 and higher, you can run the `REFRESH FUNCTIONS` statement to refresh the user-defined functions (UDFs) created outside of Impala. For example, you can add Java-based UDFs to the metastore database through the

Hive `CREATE FUNCTION` statements and make those UDFs visible to Impala at the database level by subsequently running `REFRESH FUNCTIONS`.

The `REFRESH FUNCTIONS` statement is only required if you create or modify UDFs from outside of Impala. Updated metadata, as a result of running `REFRESH FUNCTIONS`, is broadcast to all Impala coordinators.

Once issued, the `REFRESH FUNCTIONS` statement cannot be cancelled.

Syntax:

```
REFRESH FUNCTIONS db_name
```

REVOKE Statement (Impala 2.0 or higher only)

The `REVOKE` statement revokes roles or privileges on a specified object from groups, roles, or users.

Syntax:

The following syntax is supported when Impala is using Ranger to manage authorization.

```
REVOKE ROLE role_name FROM GROUP group_name

REVOKE privilege ON object_type object_name
  FROM USER user_name

REVOKE privilege ON object_type object_name
  FROM GROUP group_name

REVOKE [GRANT OPTION FOR] privilege ON object_type object_name
  FROM [ROLE] role_name

privilege ::= ALL | ALTER | CREATE | DROP | INSERT | REFRESH | SELECT |
  SELECT(column_name)

object_type ::= SERVER | URI | DATABASE | TABLE
```

Usage notes:

See [GRANT Statement \(Impala 2.0 or higher only\)](#) for the required privileges and the scope for SQL operations.

The `ALL` privilege is a distinct privilege and not a union of all other privileges. Revoking `SELECT`, `INSERT`, etc. from a role that only has the `ALL` privilege has no effect. To reduce the privileges of that role you must `REVOKE ALL` and `GRANT` the desired privileges.

You cannot revoke a privilege granted with the `WITH GRANT OPTION`. If a privilege is granted with the `WITH GRANT OPTION`, first revoke the grant option, and then revoke the privilege.

For example:

```
GRANT ALL ON SERVER TO ROLE foo_role;
...
REVOKE GRANT OPTION FOR ALL ON SERVER FROM ROLE foo_role;
REVOKE ALL ON SERVER FROM ROLE foo_role;
```

Typically, the object name is an identifier. For URIs, it is a string literal.

The ability to grant or revoke `SELECT` privilege on specific columns is available in Impala 2.3 and higher. See the documentation for Apache Sentry for details.

Required privileges:

Only administrative users for Ranger can use this statement.

Only Ranger administrative users can revoke the role from a group.

Compatibility:

- The REVOKE statements are available in Impala 2.0 and higher.
- Impala makes use of any roles and privileges specified by the GRANT and REVOKE statements in Hive, when your system is configured to use the Ranger service instead of the file-based policy mechanism.
- The Impala REVOKE statements do not require the ROLE keyword to be repeated before each role name, unlike the equivalent Hive statements.
- Currently, each Impala GRANT or REVOKE statement can only grant or revoke a single privilege to or from a single role.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Kudu considerations:

Access to Kudu tables must be granted to and revoked from principal with the following considerations:

- Only users with the ALL privilege on SERVER can create external Kudu tables.
- The ALL privileges on SERVER is required to specify the `kudu.master_addresses` property in the CREATE TABLE statements for managed tables as well as external tables.
- Access to Kudu tables is enforced at the table level and at the column level.
- The SELECT- and INSERT-specific permissions are supported.
- The DELETE, UPDATE, and UPSERT operations require the ALL privilege.

Related information:

[Impala Authorization](#) on page 83, [GRANT Statement \(Impala 2.0 or higher only\)](#) on page 294 [CREATE ROLE Statement \(Impala 2.0 or higher only\)](#) on page 248, [DROP ROLE Statement \(Impala 2.0 or higher only\)](#) on page 284, [SHOW Statement](#) on page 395

SELECT Statement

The SELECT statement performs queries, retrieving data from one or more tables and producing result sets consisting of rows and columns.

The Impala [INSERT](#) statement also typically ends with a SELECT statement, to define data to copy from one table to another.

Syntax:

```
[WITH name AS (select_expression) [, ...] ]
SELECT
  [ALL | DISTINCT]
  [STRAIGHT_JOIN]
  expression [, expression ...]
FROM table_reference [, table_reference ...]
[[FULL | [LEFT | RIGHT] INNER | [LEFT | RIGHT] OUTER | [LEFT | RIGHT] SEMI |
 [LEFT | RIGHT] ANTI | CROSS]
  JOIN table_reference
  [ON join_equality_clauses | USING (col1[, col2 ...])] ...
WHERE conditions
GROUP BY { column | expression [, ...] }
HAVING conditions
ORDER BY { column | expression [ASC | DESC] [NULLS FIRST | NULLS LAST]
  [, ...] }
LIMIT expression [OFFSET expression]
[UNION [ALL] select_statement] ...

table_reference := { table_name | (subquery) }
  [ TABLESAMPLE SYSTEM(percentage) [REPEATABLE(seed)] ]
```

Impala SELECT queries support:

- SQL scalar data types: [BOOLEAN](#), [TINYINT](#), [SMALLINT](#), [INT](#), [BIGINT](#), [DECIMAL](#), [FLOAT](#), [DOUBLE](#), [TIMESTAMP](#), [STRING](#), [VARCHAR](#), [CHAR](#).
- The complex data types ARRAY, STRUCT, and MAP, are available in Impala 2.3 and higher. Queries involving these types typically involve special qualified names using dot notation for referring to the complex column fields, and join clauses for bringing the complex columns into the result set. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details.
- An optional [WITH clause](#) before the SELECT keyword, to define a subquery whose name or column names can be referenced from later in the main query. This clause lets you abstract repeated clauses, such as aggregation functions, that are referenced multiple times in the same query.
- Subqueries in a FROM clause. In Impala 2.0 and higher, subqueries can also go in the WHERE clause, for example with the IN(), EXISTS, and NOT EXISTS operators.
- WHERE, GROUP BY, HAVING clauses.
- [ORDER BY](#). Prior to Impala 1.4.0, Impala required that queries using an ORDER BY clause also include a [LIMIT](#) clause. In Impala 1.4.0 and higher, this restriction is lifted; sort operations that would exceed the Impala memory limit automatically use a temporary disk work area to perform the sort.
- You can refer to SELECT-list items by their ordinal position. Impala supports ordinals in the GROUP BY, HAVING, and ORDER BY clauses. From Impala 3.0, ordinals can only be used at the top level. For example, the following statements are allowed:

```
SELECT int_col / 2, sum(x)
FROM t
GROUP BY 1;

SELECT int_col / 2
FROM t
ORDER BY 1;

SELECT NOT bool_col
FROM t
GROUP BY 1
HAVING 1;
```

Numbers in subexpressions are not interpreted as ordinals:

```
SELECT int_col / 2, sum(x)
FROM t
GROUP BY 1 * 2;
The above parses OK, however GROUP BY 1 * 2 has no effect.

SELECT int_col / 2
FROM t
ORDER BY 1 + 2;
The above parses OK, however ORDER BY 1 + 2 has no effect.

SELECT NOT bool_col
FROM t
GROUP BY 1
HAVING not 1;
The above raises an error at parse-time.
```

- Impala supports a wide variety of JOIN clauses. Left, right, semi, full, and outer joins are supported in all Impala versions. The CROSS JOIN operator is available in Impala 1.2.2 and higher. During performance tuning, you can override the reordering of join clauses that Impala does internally by including the keyword STRAIGHT_JOIN immediately after the SELECT and any DISTINCT or ALL keywords.

See [Joins in Impala SELECT Statements](#) on page 318 for details and examples of join queries.

- `UNION ALL`.
- `LIMIT`.
- External tables.
- Relational operators such as greater than, less than, or equal to.
- Arithmetic operators such as addition or subtraction.
- Logical/Boolean operators `AND`, `OR`, and `NOT`. Impala does not support the corresponding symbols `&&`, `| |`, and `!`.
- Common SQL built-in functions such as `COUNT`, `SUM`, `CAST`, `LIKE`, `IN`, `BETWEEN`, and `COALESCE`. Impala specifically supports built-ins described in [Impala Built-In Functions](#) on page 428.
- In Impala 2.9 and higher, an optional `TABLESAMPLE` clause immediately after a table reference, to specify that the query only processes a specified percentage of the table data. See [TABLESAMPLE Clause](#) on page 338 for details.

Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See the documentation for your Apache Hadoop distribution for details.

Amazon S3 considerations:

In Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, ORC, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Cancellation: Can be cancelled. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permissions for the files in all applicable directories in all source tables, and read and execute permissions for the relevant data directories. (A `SELECT` operation could read files from multiple different HDFS directories if the source table is partitioned.) If a query attempts to read a data file and is unable to because of an HDFS permission error, the query halts and does not return any further results.

Related information:

The `SELECT` syntax is so extensive that it forms its own category of statements: queries. The other major classifications of SQL statements are data definition language (see [DDL Statements](#) on page 213) and data manipulation language (see [DML Statements](#) on page 214).

Because the focus of Impala is on fast queries with interactive response times over huge data sets, query performance and scalability are important considerations. See [Tuning Impala for Performance](#) on page 614 and [Scalability Considerations for Impala](#) on page 657 for details.

Joins in Impala SELECT Statements

A join query is a `SELECT` statement that combines data from two or more tables, and returns a result set containing items from some or all of those tables. It is a way to cross-reference and correlate related data that is organized into multiple tables, typically using identifiers that are repeated in each of the joined tables.

Syntax:

Impala supports a wide variety of JOIN clauses. Left, right, semi, full, and outer joins are supported in all Impala versions. The CROSS JOIN operator is available in Impala 1.2.2 and higher. During performance tuning, you can override the reordering of join clauses that Impala does internally by including the keyword STRAIGHT_JOIN immediately after the SELECT and any DISTINCT or ALL keywords.

```
SELECT select_list FROM
  table_or_subquery1 [INNER] JOIN table_or_subquery2 |
  table_or_subquery1 {LEFT [OUTER] | RIGHT [OUTER] | FULL [OUTER]}
  JOIN table_or_subquery2 |
  table_or_subquery1 {LEFT | RIGHT} SEMI JOIN table_or_subquery2 |
  table_or_subquery1 {LEFT | RIGHT} ANTI JOIN table_or_subquery2 |
  [ ON col1 = col2 [AND col3 = col4 ...] |
    USING (col1 [, col2 ...]) ]
  [other_join_clause ...]
[ WHERE where_clauses ]

SELECT select_list FROM
  table_or_subquery1, table_or_subquery2 [, table_or_subquery3 ...]
  [other_join_clause ...]
WHERE
  col1 = col2 [AND col3 = col4 ...]

SELECT select_list FROM
  table_or_subquery1 CROSS JOIN table_or_subquery2
  [other_join_clause ...]
[ WHERE where_clauses ]
```

SQL-92 and SQL-89 Joins:

Queries with the explicit JOIN keywords are known as SQL-92 style joins, referring to the level of the SQL standard where they were introduced. The corresponding ON or USING clauses clearly show which columns are used as the join keys in each case:

```
SELECT t1.c1, t2.c2 FROM t1 JOIN t2
  ON t1.id = t2.id and t1.type_flag = t2.type_flag
  WHERE t1.c1 > 100;

SELECT t1.c1, t2.c2 FROM t1 JOIN t2
  USING (id, type_flag)
  WHERE t1.c1 > 100;
```

The ON clause is a general way to compare columns across the two tables, even if the column names are different. The USING clause is a shorthand notation for specifying the join columns, when the column names are the same in both tables. You can code equivalent WHERE clauses that compare the columns, instead of ON or USING clauses, but that practice is not recommended because mixing the join comparisons with other filtering clauses is typically less readable and harder to maintain.

Queries with a comma-separated list of tables and subqueries are known as SQL-89 style joins. In these queries, the equality comparisons between columns of the joined tables go in the WHERE clause alongside other kinds of comparisons. This syntax is easy to learn, but it is also easy to accidentally remove a WHERE clause needed for the join to work correctly.

```
SELECT t1.c1, t2.c2 FROM t1, t2
  WHERE
    t1.id = t2.id AND t1.type_flag = t2.type_flag
    AND t1.c1 > 100;
```

Self-joins:

Impala can do self-joins, for example to join on two different columns in the same table to represent parent-child relationships or other tree-structured data. There is no explicit syntax for this; just use the same table name for both the left-hand and right-hand table, and assign different table aliases to use when referring to the fully qualified column names:

```
-- Combine fields from both parent and child rows.
SELECT lhs.id, rhs.parent, lhs.c1, rhs.c2 FROM tree_data lhs, tree_data rhs
WHERE lhs.id = rhs.parent;
```

Inner and outer joins:

An inner join is the most common and familiar type: rows in the result set contain the requested columns from the appropriate tables, for all combinations of rows where the join columns of the tables have identical values. If a column with the same name occurs in both tables, use a fully qualified name or a column alias to refer to the column in the select list or other clauses. Impala performs inner joins by default for both SQL-89 and SQL-92 join syntax:

```
-- The following 3 forms are all equivalent.
SELECT t1.id, c1, c2 FROM t1, t2 WHERE t1.id = t2.id;
SELECT t1.id, c1, c2 FROM t1 JOIN t2 ON t1.id = t2.id;
SELECT t1.id, c1, c2 FROM t1 INNER JOIN t2 ON t1.id = t2.id;
```

An outer join retrieves all rows from the left-hand table, or the right-hand table, or both; wherever there is no matching data in the table on the other side of the join, the corresponding columns in the result set are set to NULL. To perform an outer join, include the OUTER keyword in the join operator, along with either LEFT, RIGHT, or FULL:

```
SELECT * FROM t1 LEFT OUTER JOIN t2 ON t1.id = t2.id;
SELECT * FROM t1 RIGHT OUTER JOIN t2 ON t1.id = t2.id;
SELECT * FROM t1 FULL OUTER JOIN t2 ON t1.id = t2.id;
```

For outer joins, Impala requires SQL-92 syntax; that is, the JOIN keyword instead of comma-separated table names. Impala does not support vendor extensions such as (+) or *= notation for doing outer joins with SQL-89 query syntax.

Equijoins and Non-Equijoins:

By default, Impala requires an equality comparison between the left-hand and right-hand tables, either through ON, USING, or WHERE clauses. These types of queries are classified broadly as equijoins. Inner, outer, full, and semi joins can all be equijoins based on the presence of equality tests between columns in the left-hand and right-hand tables.

In Impala 1.2.2 and higher, non-equijoin queries are also possible, with comparisons such as != or < between the join columns. These kinds of queries require care to avoid producing huge result sets that could exceed resource limits. Once you have planned a non-equijoin query that produces a result set of acceptable size, you can code the query using the CROSS JOIN operator, and add the extra comparisons in the WHERE clause:

```
SELECT * FROM t1 CROSS JOIN t2 WHERE t1.total > t2.maximum_price;
```

In Impala 2.3 and higher, additional non-equijoin queries are possible due to the addition of nested loop joins. These queries typically involve SEMI JOIN, ANTI JOIN, or FULL OUTER JOIN clauses. Impala sometimes also uses nested loop joins internally when evaluating OUTER JOIN queries involving complex type columns. Query phases involving nested loop joins do not use the spill-to-disk mechanism if they exceed the memory limit. Impala decides internally when to use each join mechanism; you cannot specify any query hint to choose between the nested loop join or the original hash join algorithm.

```
SELECT * FROM t1 LEFT OUTER JOIN t2 ON t1.int_col < t2.int_col;
```

Semi-joins:

Semi-joins are a relatively rarely used variation. With the left semi-join, only data from the left-hand table is returned, for rows where there is matching data in the right-hand table, based on comparisons between join columns in ON or

WHERE clauses. Only one instance of each row from the left-hand table is returned, regardless of how many matching rows exist in the right-hand table. A right semi-join (available in Impala 2.0 and higher) reverses the comparison and returns data from the right-hand table.

```
SELECT t1.c1, t1.c2, t1.c2 FROM t1 LEFT SEMI JOIN t2 ON t1.id = t2.id;
```

Natural joins (not supported):

Impala does not support the NATURAL JOIN operator, again to avoid inconsistent or huge result sets. Natural joins do away with the ON and USING clauses, and instead automatically join on all columns with the same names in the left-hand and right-hand tables. This kind of query is not recommended for rapidly evolving data structures such as are typically used in Hadoop. Thus, Impala does not support the NATURAL JOIN syntax, which can produce different query results as columns are added to or removed from tables.

If you do have any queries that use NATURAL JOIN, make sure to rewrite them with explicit USING clauses, because Impala could interpret the NATURAL keyword as a table alias:

```
-- 'NATURAL' is interpreted as an alias for 't1' and Impala attempts an
inner join,
-- resulting in an error because inner joins require explicit comparisons
between columns.
SELECT t1.c1, t2.c2 FROM t1 NATURAL JOIN t2;
ERROR: NotImplementedException: Join with 't2' requires at least one
conjunctive equality predicate.
To perform a Cartesian product between two tables, use a CROSS JOIN.

-- If you expect the tables to have identically named columns with matching
values,
-- list the corresponding column names in a USING clause.
SELECT t1.c1, t2.c2 FROM t1 JOIN t2 USING (id, type_flag, name, address);
```

Anti-joins (Impala 2.0 and higher only):

Impala supports the LEFT ANTI JOIN and RIGHT ANTI JOIN clauses in Impala 2.0 and higher. The LEFT or RIGHT keyword is required for this kind of join. For LEFT ANTI JOIN, this clause returns those values from the left-hand table that have no matching value in the right-hand table. RIGHT ANTI JOIN reverses the comparison and returns values from the right-hand table. You can express this negative relationship either through the ANTI JOIN clause or through a NOT EXISTS operator with a subquery.

Complex type considerations:

When referring to a column with a complex type (STRUCT, ARRAY, or MAP) in a query, you use join notation to “unpack” the scalar fields of the struct, the elements of the array, or the key-value pairs of the map. (The join notation is not required for aggregation operations, such as COUNT() or SUM() for array elements.) Because Impala recognizes which complex type elements are associated with which row of the result set, you use the same syntax as for a cross or cartesian join, without an explicit join condition. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about Impala support for complex types.

Usage notes:

You typically use join queries in situations like these:

- When related data arrives from different sources, with each data set physically residing in a separate table. For example, you might have address data from business records that you cross-check against phone listings or census data.

Note: Impala can join tables of different file formats, including Impala-managed tables and HBase tables. For example, you might keep small dimension tables in HBase, for convenience of single-row lookups and updates, and for the larger fact tables use Parquet or other binary file format optimized for scan operations. Then, you can issue a join query to cross-reference the fact tables with the dimension tables.

- When data is normalized, a technique for reducing data duplication by dividing it across multiple tables. This kind of organization is often found in data that comes from traditional relational database systems. For example, instead

of repeating some long string such as a customer name in multiple tables, each table might contain a numeric customer ID. Queries that need to display the customer name could “join” the table that specifies which customer ID corresponds to which name.

- When certain columns are rarely needed for queries, so they are moved into separate tables to reduce overhead for common queries. For example, a `biography` field might be rarely needed in queries on employee data. Putting that field in a separate table reduces the amount of I/O for common queries on employee addresses or phone numbers. Queries that do need the `biography` column can retrieve it by performing a join with that separate table.
- In Impala 2.3 or higher, when referring to complex type columns in queries. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details.

When comparing columns with the same names in `ON` or `WHERE` clauses, use the fully qualified names such as `db_name.table_name`, or assign table aliases, column aliases, or both to make the code more compact and understandable:

```
select t1.c1 as first_id, t2.c2 as second_id from
  t1 join t2 on first_id = second_id;

select fact.custno, dimension.custno from
  customer_data as fact join customer_address as dimension
  using (custno)
```

Note:

Performance for join queries is a crucial aspect for Impala, because complex join queries are resource-intensive operations. An efficient join query produces much less network traffic and CPU overhead than an inefficient one. For best results:

- Make sure that both [table and column statistics](#) are available for all the tables involved in a join query, and especially for the columns referenced in any join conditions. Impala uses the statistics to automatically deduce an efficient join order. Use `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` to check if statistics are already present. Issue the `COMPUTE STATS table_name` for a nonpartitioned table, or (in Impala 2.1.0 and higher) `COMPUTE INCREMENTAL STATS table_name` for a partitioned table, to collect the initial statistics at both the table and column levels, and to keep the statistics up to date after any substantial `INSERT` or `LOAD DATA` operations.
- If table or column statistics are not available, join the largest table first. You can check the existence of statistics with the `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` statements.
- If table or column statistics are not available, join subsequent tables according to which table has the most selective filter, based on overall size and `WHERE` clauses. Joining the table with the most selective filter results in the fewest number of rows being returned.

For more information and examples of performance for join queries, see [Performance Considerations for Join Queries](#) on page 618.

To control the result set from a join query, include the names of corresponding column names in both tables in an `ON` or `USING` clause, or by coding equality comparisons for those columns in the `WHERE` clause.

```
[localhost:21000] > select c_last_name, ca_city from customer join
  customer_address where c_customer_sk = ca_address_sk;
```

c_last_name	ca_city
Lewis	Fairfield
Moses	Fairview
Hamilton	Pleasant Valley
White	Oak Ridge
Moran	Glendale
...	
Richards	Lakewood
Day	Lebanon

Painter	Oak Hill
Bentley	Greenfield
Jones	Stringtown

Returned 50000 row(s) in 9.82s

One potential downside of joins is the possibility of excess resource usage in poorly constructed queries. Impala imposes restrictions on join queries to guard against such issues. To minimize the chance of runaway queries on large data sets, Impala requires every join query to contain at least one equality predicate between the columns of the various tables. For example, if T1 contains 1000 rows and T2 contains 1,000,000 rows, a query `SELECT columns FROM t1 JOIN t2` could return up to 1 billion rows ($1000 * 1,000,000$); Impala requires that the query include a clause such as `ON t1.c1 = t2.c2` or `WHERE t1.c1 = t2.c2`.

Because even with equality clauses, the result set can still be large, as we saw in the previous example, you might use a `LIMIT` clause to return a subset of the results:

```
[localhost:21000] > select c_last_name, ca_city from customer,
customer_address where c_customer_sk = ca_address_sk limit 10;
```

c_last_name	ca_city
Lewis	Fairfield
Moses	Fairview
Hamilton	Pleasant Valley
White	Oak Ridge
Moran	Glendale
Sharp	Lakeview
Wiles	Farmington
Shipman	Union
Gilbert	New Hope
Brunson	Martinsville

Returned 10 row(s) in 0.63s

Or you might use additional comparison operators or aggregation functions to condense a large result set into a smaller set of values:

```
[localhost:21000] > -- Find the names of customers who live in one
particular town.
[localhost:21000] > select distinct c_last_name from customer,
customer_address where
c_customer_sk = ca_address_sk
and ca_city = "Green Acres";
```

c_last_name
Hensley
Pearson
Mayer
Montgomery
Ricks
...
Barrett
Price
Hill
Hansen
Meeks

Returned 332 row(s) in 0.97s

```
[localhost:21000] > -- See how many different customers in this town have
names starting with "A".
```

```
[localhost:21000] > select count(distinct c_last_name) from customer,
customer_address where
  c_customer_sk = ca_address_sk
  and ca_city = "Green Acres"
  and substr(c_last_name,1,1) = "A";
+-----+
| count(distinct c_last_name) |
+-----+
| 12                           |
+-----+
Returned 1 row(s) in 1.00s
```

Because a join query can involve reading large amounts of data from disk, sending large amounts of data across the network, and loading large amounts of data into memory to do the comparisons and filtering, you might do benchmarking, performance analysis, and query tuning to find the most efficient join queries for your data set, hardware capacity, network configuration, and cluster workload.

The two categories of joins in Impala are known as **partitioned joins** and **broadcast joins**. If inaccurate table or column statistics, or some quirk of the data distribution, causes Impala to choose the wrong mechanism for a particular join, consider using query hints as a temporary workaround. For details, see [Optimizer Hints](#) on page 422.

Handling NULLs in Join Columns:

By default, join key columns do not match if either one contains a NULL value. To treat such columns as equal if both contain NULL, you can use an expression such as `A = B OR (A IS NULL AND B IS NULL)`. In Impala 2.5 and higher, the `<=>` operator (shorthand for `IS NOT DISTINCT FROM`) performs the same comparison in a concise and efficient form. The `<=>` operator is more efficient in for comparing join keys in a NULL-safe manner, because the operator can use a hash join while the `OR` expression cannot.

Examples:

The following examples refer to these simple tables containing small sets of integers:

```
[localhost:21000] > create table t1 (x int);
[localhost:21000] > insert into t1 values (1), (2), (3), (4), (5), (6);

[localhost:21000] > create table t2 (y int);
[localhost:21000] > insert into t2 values (2), (4), (6);

[localhost:21000] > create table t3 (z int);
[localhost:21000] > insert into t3 values (1), (3), (5);
```

The following example demonstrates an anti-join, returning the values from T1 that do not exist in T2 (in this case, the odd numbers 1, 3, and 5):

```
[localhost:21000] > select x from t1 left anti join t2 on (t1.x = t2.y);
+----+
| x  |
+----+
| 1  |
| 3  |
| 5  |
+----+
```

Related information:

See these tutorials for examples of different kinds of joins:

- [Cross Joins and Cartesian Products with the CROSS JOIN Operator](#) on page 51

ORDER BY Clause

The `ORDER BY` clause of a `SELECT` statement sorts the result set based on the values from one or more columns.

First, data is sorted locally by each `impalad` daemon, then streamed to the coordinator daemon, which merges the sorted result sets. For distributed queries, this is a relatively expensive operation and can require more memory capacity than a query without `ORDER BY`. Even if the query takes approximately the same time to finish with or without the `ORDER BY` clause, subjectively it can appear slower because no results are available until all processing is finished, rather than results coming back gradually as rows matching the `WHERE` clause are found. Therefore, if you only need the first `N` results from the sorted result set, also include the `LIMIT` clause, which reduces network overhead and the memory requirement on the coordinator node.

Syntax:

The full syntax for the `ORDER BY` clause is:

```
ORDER BY col_ref [, col_ref ...] [ASC | DESC] [NULLS FIRST | NULLS LAST]

col_ref ::= column_name | integer_literal
```

Although the most common usage is `ORDER BY column_name`, you can also specify `ORDER BY 1` to sort by the first column of the result set, `ORDER BY 2` to sort by the second column, and so on. The number must be a numeric literal, not some other kind of constant expression. (If the argument is some other expression, even a `STRING` value, the query succeeds but the order of results is undefined.)

`ORDER BY column_number` can only be used when the query explicitly lists the columns in the `SELECT` list, not with `SELECT *` queries.

Ascending and descending sorts:

The default sort order (the same as using the `ASC` keyword) puts the smallest values at the start of the result set, and the largest values at the end. Specifying the `DESC` keyword reverses that order.

Sort order for NULL values:

See [NULL](#) on page 177 for details about how `NULL` values are positioned in the sorted result set, and how to use the `NULLS FIRST` and `NULLS LAST` clauses. (The sort position for `NULL` values in `ORDER BY ... DESC` queries is changed in Impala 1.2.1 and higher to be more standards-compliant, and the `NULLS FIRST` and `NULLS LAST` keywords are new in Impala 1.2.1.)

Prior to Impala 1.4.0, Impala required any query including an `ORDER BY` clause to also use a `LIMIT` clause. In Impala 1.4.0 and higher, the `LIMIT` clause is optional for `ORDER BY` queries. In cases where sorting a huge result set requires enough memory to exceed the Impala memory limit for a particular executor Impala daemon, Impala automatically uses a temporary disk work area to perform the sort operation.

Complex type considerations:

In Impala 2.3 and higher, the complex data types `STRUCT`, `ARRAY`, and `MAP` are available. These columns cannot be referenced directly in the `ORDER BY` clause. When you query a complex type column, you use join notation to “unpack” the elements of the complex type, and within the join query you can include an `ORDER BY` clause to control the order in the result set of the scalar elements from the complex type. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about Impala support for complex types.

The following query shows how a complex type column cannot be directly used in an `ORDER BY` clause:

```
CREATE TABLE games (id BIGINT, score ARRAY <BIGINT>) STORED AS PARQUET;
...use LOAD DATA to load externally created Parquet files into the table...
SELECT id FROM games ORDER BY score DESC;
ERROR: AnalysisException: ORDER BY expression 'score' with complex type
'ARRAY<BIGINT>' is not supported.
```

Examples:

The following query retrieves the user ID and score, only for scores greater than one million, with the highest scores for each user listed first. Because the individual array elements are now represented as separate rows in the result set, they can be used in the `ORDER BY` clause, referenced using the `ITEM` pseudo-column that represents each array element.

```
SELECT id, item FROM games, games.score
WHERE item > 1000000
ORDER BY id, item desc;
```

The following queries use similar `ORDER BY` techniques with variations of the `GAMES` table, where the complex type is an `ARRAY` containing `STRUCT` or `MAP` elements to represent additional details about each game that was played. For an array of structures, the fields of the structure are referenced as `ITEM.field_name`. For an array of maps, the keys and values within each array element are referenced as `ITEM.KEY` and `ITEM.VALUE`.

```
CREATE TABLE games2 (id BIGINT, play array < struct <game_name: string,
  score: BIGINT, high_score: boolean> >) STORED AS PARQUET
...use LOAD DATA to load externally created Parquet files into the table...
SELECT id, item.game_name, item.score FROM games2, games2.play
WHERE item.score > 1000000
ORDER BY id, item.score DESC;

CREATE TABLE games3 (id BIGINT, play ARRAY < MAP <STRING, BIGINT> >) STORED
AS PARQUET;
...use LOAD DATA to load externally created Parquet files into the table...
SELECT id, info.key AS k, info.value AS v from games3, games3.play AS plays,
games3.play.item AS info
WHERE info.KEY = 'score' AND info.VALUE > 1000000
ORDER BY id, info.value desc;
```

Usage notes:

Although the `LIMIT` clause is now optional on `ORDER BY` queries, if your query only needs some number of rows that you can predict in advance, use the `LIMIT` clause to reduce unnecessary processing. For example, if the query has a clause `LIMIT 10`, each executor Impala daemon sorts its portion of the relevant result set and only returns 10 rows to the coordinator node. The coordinator node picks the 10 highest or lowest row values out of this small intermediate result set.

If an `ORDER BY` clause is applied to an early phase of query processing, such as a subquery or a view definition, Impala ignores the `ORDER BY` clause. To get ordered results from a subquery or view, apply an `ORDER BY` clause to the outermost or final `SELECT` level.

`ORDER BY` is often used in combination with `LIMIT` to perform “top-N” queries:

```
SELECT user_id AS "Top 10 Visitors", SUM(page_views) FROM web_stats
GROUP BY page_views, user_id
ORDER BY SUM(page_views) DESC LIMIT 10;
```

`ORDER BY` is sometimes used in combination with `OFFSET` and `LIMIT` to paginate query results, although it is relatively inefficient to issue multiple queries like this against the large tables typically used with Impala:

```
SELECT page_title AS "Page 1 of search results", page_url FROM
search_content
WHERE LOWER(page_title) LIKE '%game%'
ORDER BY page_title LIMIT 10 OFFSET 0;
SELECT page_title AS "Page 2 of search results", page_url FROM
search_content
WHERE LOWER(page_title) LIKE '%game%'
ORDER BY page_title LIMIT 10 OFFSET 10;
SELECT page_title AS "Page 3 of search results", page_url FROM
search_content
WHERE LOWER(page_title) LIKE '%game%';
```

```
ORDER BY page_title LIMIT 10 OFFSET 20;
```

Internal details:

Impala sorts the intermediate results of an `ORDER BY` clause in memory whenever practical. In a cluster of *N* executor Impala daemons, each daemon sorts roughly 1/*N*th of the result set, the exact proportion varying depending on how the data matching the query is distributed in HDFS.

If the size of the sorted intermediate result set on any executor Impala daemon would cause the query to exceed the Impala memory limit, Impala sorts as much as practical in memory, then writes partially sorted data to disk. (This technique is known in industry terminology as “external sorting” and “spilling to disk”.) As each 8 MB batch of data is written to disk, Impala frees the corresponding memory to sort a new 8 MB batch of data. When all the data has been processed, a final merge sort operation is performed to correctly order the in-memory and on-disk results as the result set is transmitted back to the coordinator node. When external sorting becomes necessary, Impala requires approximately 60 MB of RAM at a minimum for the buffers needed to read, write, and sort the intermediate results. If more RAM is available on the Impala daemon, Impala will use the additional RAM to minimize the amount of disk I/O for sorting.

This external sort technique is used as appropriate on each Impala daemon (possibly including the coordinator node) to sort the portion of the result set that is processed on that node. When the sorted intermediate results are sent back to the coordinator node to produce the final result set, the coordinator node uses a merge sort technique to produce a final sorted result set without using any extra resources on the coordinator node.

Configuration for disk usage:

By default, intermediate files used during large sort, join, aggregation, or analytic function operations are stored in the directory `/tmp/impala-scratch`, and these intermediate files are removed when the operation finishes. You can specify a different location by starting the `impalad` daemon with the `##scratch_dirs="path_to_directory"` configuration option.

Sorting considerations: Although you can specify an `ORDER BY` clause in an `INSERT ... SELECT` statement, any `ORDER BY` clause is ignored and the results are not necessarily sorted. An `INSERT ... SELECT` operation potentially creates many different data files, prepared by different executor Impala daemons, and therefore the notion of the data being stored in sorted order is impractical.

An `ORDER BY` clause without an additional `LIMIT` clause is ignored in any view definition. If you need to sort the entire result set from a view, use an `ORDER BY` clause in the `SELECT` statement that queries the view. You can still make a simple “top 10” report by combining the `ORDER BY` and `LIMIT` clauses in the same view definition:

```
[localhost:21000] > create table unsorted (x bigint);
[localhost:21000] > insert into unsorted values (1), (9), (3), (7), (5),
(8), (4), (6), (2);
[localhost:21000] > create view sorted_view as select x from unsorted order
by x;
[localhost:21000] > select x from sorted_view; -- ORDER BY clause in view
has no effect.
+----+
| x |
+----+
| 1 |
| 9 |
| 3 |
| 7 |
| 5 |
| 8 |
| 4 |
| 6 |
| 2 |
+----+
[localhost:21000] > select x from sorted_view order by x; -- View query
requires ORDER BY at outermost level.
+----+
```

```

| x |
+---+
| 1 |
| 2 |
| 3 |
| 4 |
| 5 |
| 6 |
| 7 |
| 8 |
| 9 |
+---+
[localhost:21000] > create view top_3_view as select x from unsorted order
by x limit 3;
[localhost:21000] > select x from top_3_view; -- ORDER BY and LIMIT together
in view definition are preserved.
+---+
| x |
+---+
| 1 |
| 2 |
| 3 |
+---+

```

With the lifting of the requirement to include a `LIMIT` clause in every `ORDER BY` query (in Impala 1.4 and higher):

- Now the use of scratch disk space raises the possibility of an “out of disk space” error on a particular Impala daemon, as opposed to the previous possibility of an “out of memory” error. Make sure to keep at least 1 GB free on the filesystem used for temporary sorting work.

In Impala 1.2.1 and higher, all `NULL` values come at the end of the result set for `ORDER BY ... ASC` queries, and at the beginning of the result set for `ORDER BY ... DESC` queries. In effect, `NULL` is considered greater than all other values for sorting purposes. The original Impala behavior always put `NULL` values at the end, even for `ORDER BY ... DESC` queries. The new behavior in Impala 1.2.1 makes Impala more compatible with other popular database systems. In Impala 1.2.1 and higher, you can override or specify the sorting behavior for `NULL` by adding the clause `NULLS FIRST` or `NULLS LAST` at the end of the `ORDER BY` clause.

```

[localhost:21000] > create table numbers (x int);
[localhost:21000] > insert into numbers values (1), (null), (2), (null),
(3);
[localhost:21000] > select x from numbers order by x nulls first;
+-----+
| x      |
+-----+
| NULL   |
| NULL   |
| 1      |
| 2      |
| 3      |
+-----+
[localhost:21000] > select x from numbers order by x desc nulls first;
+-----+
| x      |
+-----+
| NULL   |
| NULL   |
| 3      |
| 2      |
| 1      |
+-----+
[localhost:21000] > select x from numbers order by x nulls last;
+-----+
| x      |
+-----+

```



```

+-----+
| 1      |
| 2      |
| 3      |
| NULL   |
| NULL   |
+-----+
[localhost:21000] > select x from numbers order by x desc nulls last;
+-----+
| x      |
+-----+
| 3      |
| 2      |
| 1      |
| NULL   |
| NULL   |
+-----+

```

Related information:

See [SELECT Statement](#) on page 316 for further examples of queries with the ORDER BY clause.

Analytic functions use the ORDER BY clause in a different context to define the sequence in which rows are analyzed. See [Impala Analytic Functions](#) on page 569 for details.

GROUP BY Clause

Specify the GROUP BY clause in queries that use aggregation functions, such as [COUNT\(\)](#), [SUM\(\)](#), [AVG\(\)](#), [MIN\(\)](#), and [MAX\(\)](#). Specify in the [GROUP BY](#) clause the names of all the columns that do not participate in the aggregation operation.

Complex type considerations:

In Impala 2.3 and higher, the complex data types STRUCT, ARRAY, and MAP are available. These columns cannot be referenced directly in the ORDER BY clause. When you query a complex type column, you use join notation to “unpack” the elements of the complex type, and within the join query you can include an ORDER BY clause to control the order in the result set of the scalar elements from the complex type. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about Impala support for complex types.

Zero-length strings: For purposes of clauses such as DISTINCT and GROUP BY, Impala considers zero-length strings (""), NULL, and space to all be different values.

Examples:

For example, the following query finds the 5 items that sold the highest total quantity (using the SUM() function, and also counts the number of sales transactions for those items (using the COUNT() function). Because the column representing the item IDs is not used in any aggregation functions, we specify that column in the GROUP BY clause.

```

select
  ss_item_sk as Item,
  count(ss_item_sk) as Times_Purchased,
  sum(ss_quantity) as Total_Quantity_Purchased
from store_sales
  group by ss_item_sk
  order by sum(ss_quantity) desc
  limit 5;

```

item	times_purchased	total_quantity_purchased
9325	372	19072
4279	357	18501
7507	371	18475
5953	369	18451
16753	375	18446

The **HAVING** clause lets you filter the results of aggregate functions, because you cannot refer to those expressions in the **WHERE** clause. For example, to find the 5 lowest-selling items that were included in at least 100 sales transactions, we could use this query:

```
select
  ss_item_sk as Item,
  count(ss_item_sk) as Times_Purchased,
  sum(ss_quantity) as Total_Quantity_Purchased
from store_sales
group by ss_item_sk
having times_purchased >= 100
order by sum(ss_quantity)
limit 5;
```

item	times_purchased	total_quantity_purchased
13943	105	4087
2992	101	4176
4773	107	4204
14350	103	4260
11956	102	4275

When performing calculations involving scientific or financial data, remember that columns with type **FLOAT** or **DOUBLE** are stored as true floating-point numbers, which cannot precisely represent every possible fractional value. Thus, if you include a **FLOAT** or **DOUBLE** column in a **GROUP BY** clause, the results might not precisely match literal values in your query or from an original Text data file. Use rounding operations, the **BETWEEN** operator, or another arithmetic technique to match floating-point values that are “near” literal values you expect. For example, this query on the `ss_wholesale_cost` column returns cost values that are close but not identical to the original figures that were entered as decimal fractions.

```
select ss_wholesale_cost, avg(ss_quantity * ss_sales_price) as
  avg_revenue_per_sale
from sales
group by ss_wholesale_cost
order by avg_revenue_per_sale desc
limit 5;
```

ss_wholesale_cost	avg_revenue_per_sale
96.94000244140625	4454.351539300434
95.93000030517578	4423.119941283189
98.37999725341797	4332.516490316291
97.97000122070312	4330.480601655014
98.52999877929688	4291.316953108634

Notice how wholesale cost values originally entered as decimal fractions such as 96.94 and 98.38 are slightly larger or smaller in the result set, due to precision limitations in the hardware floating-point types. The imprecise representation of **FLOAT** and **DOUBLE** values is why financial data processing systems often store currency using data types that are less space-efficient but avoid these types of rounding errors.

Related information:

[SELECT Statement](#) on page 316, [Impala Aggregate Functions](#) on page 539

HAVING Clause

Performs a filter operation on a `SELECT` query, by examining the results of aggregation functions rather than testing each individual table row. Therefore, it is always used in conjunction with a function such as `COUNT()`, `SUM()`, `AVG()`, `MIN()`, or `MAX()`, and typically with the `GROUP BY` clause also.

Restrictions:

The filter expression in the `HAVING` clause cannot include a scalar subquery.

Related information:

[SELECT Statement](#) on page 316, [GROUP BY Clause](#) on page 329, [Impala Aggregate Functions](#) on page 539

LIMIT Clause

The `LIMIT` clause in a `SELECT` query sets a maximum number of rows for the result set. Pre-selecting the maximum size of the result set helps Impala to optimize memory usage while processing a distributed query.

Syntax:

```
LIMIT constant_integer_expression
```

The argument to the `LIMIT` clause must evaluate to a constant value. It can be a numeric literal, or another kind of numeric expression involving operators, casts, and function return values. You cannot refer to a column or use a subquery.

Usage notes:

This clause is useful in contexts such as:

- To return exactly N items from a top-N query, such as the 10 highest-rated items in a shopping category or the 50 hostnames that refer the most traffic to a web site.
- To demonstrate some sample values from a table or a particular query. (To display some arbitrary items, use a query with no `ORDER BY` clause. An `ORDER BY` clause causes additional memory and/or disk usage during the query.)
- To keep queries from returning huge result sets by accident if a table is larger than expected, or a `WHERE` clause matches more rows than expected.

Originally, the value for the `LIMIT` clause had to be a numeric literal. In Impala 1.2.1 and higher, it can be a numeric expression.

Prior to Impala 1.4.0, Impala required any query including an `ORDER BY` clause to also use a `LIMIT` clause. In Impala 1.4.0 and higher, the `LIMIT` clause is optional for `ORDER BY` queries. In cases where sorting a huge result set requires enough memory to exceed the Impala memory limit for a particular executor Impala daemon, Impala automatically uses a temporary disk work area to perform the sort operation.

See [ORDER BY Clause](#) on page 325 for details.

In Impala 1.2.1 and higher, you can combine a `LIMIT` clause with an `OFFSET` clause to produce a small result set that is different from a top-N query, for example, to return items 11 through 20. This technique can be used to simulate “paged” results. Because Impala queries typically involve substantial amounts of I/O, use this technique only for compatibility in cases where you cannot rewrite the application logic. For best performance and scalability, wherever practical, query as many items as you expect to need, cache them on the application side, and display small groups of results to users using application logic.

Restrictions:

Correlated subqueries used in `EXISTS` and `IN` operators cannot include a `LIMIT` clause.

Examples:

The following example shows how the `LIMIT` clause caps the size of the result set, with the limit being applied after any other clauses such as `WHERE`.

```
[localhost:21000] > create database limits;
[localhost:21000] > use limits;
[localhost:21000] > create table numbers (x int);
[localhost:21000] > insert into numbers values (1), (3), (4), (5), (2);
Inserted 5 rows in 1.34s
[localhost:21000] > select x from numbers limit 100;
+----+
| x |
+----+
| 1 |
| 3 |
| 4 |
| 5 |
| 2 |
+----+
Returned 5 row(s) in 0.26s
[localhost:21000] > select x from numbers limit 3;
+----+
| x |
+----+
| 1 |
| 3 |
| 4 |
+----+
Returned 3 row(s) in 0.27s
[localhost:21000] > select x from numbers where x > 2 limit 2;
+----+
| x |
+----+
| 3 |
| 4 |
+----+
Returned 2 row(s) in 0.27s
```

For top-N and bottom-N queries, you use the `ORDER BY` and `LIMIT` clauses together:

```
[localhost:21000] > select x as "Top 3" from numbers order by x desc limit
3;
+-----+
| top 3 |
+-----+
| 5 |
| 4 |
| 3 |
+-----+
[localhost:21000] > select x as "Bottom 3" from numbers order by x limit 3;
+-----+
| bottom 3 |
+-----+
| 1 |
| 2 |
| 3 |
+-----+
```

You can use constant values besides integer literals as the `LIMIT` argument:

```
-- Other expressions that yield constant integer values work too.
SELECT x FROM t1 LIMIT 1e6;                -- Limit is one million.
SELECT x FROM t1 LIMIT length('hello world'); -- Limit is 11.
```

```
SELECT x FROM t1 LIMIT 2+2; -- Limit is 4.
SELECT x FROM t1 LIMIT cast(truncate(9.9) AS INT); -- Limit is 9.
```

OFFSET Clause

The **OFFSET** clause in a **SELECT** query causes the result set to start some number of rows after the logical first item. The result set is numbered starting from zero, so **OFFSET 0** produces the same result as leaving out the **OFFSET** clause. Always use this clause in combination with **ORDER BY** (so that it is clear which item should be first, second, and so on) and **LIMIT** (so that the result set covers a bounded range, such as items 0-9, 100-199, and so on).

In Impala 1.2.1 and higher, you can combine a **LIMIT** clause with an **OFFSET** clause to produce a small result set that is different from a top-N query, for example, to return items 11 through 20. This technique can be used to simulate “paged” results. Because Impala queries typically involve substantial amounts of I/O, use this technique only for compatibility in cases where you cannot rewrite the application logic. For best performance and scalability, wherever practical, query as many items as you expect to need, cache them on the application side, and display small groups of results to users using application logic.

Examples:

The following example shows how you could run a “paging” query originally written for a traditional database application. Because typical Impala queries process megabytes or gigabytes of data and read large data files from disk each time, it is inefficient to run a separate query to retrieve each small group of items. Use this technique only for compatibility while porting older applications, then rewrite the application code to use a single query with a large result set, and display pages of results from the cached result set.

```
[localhost:21000] > create table numbers (x int);
[localhost:21000] > insert into numbers select x from very_long_sequence;
Inserted 1000000 rows in 1.34s
[localhost:21000] > select x from numbers order by x limit 5 offset 0;
+-----+
| x |
+-----+
| 1 |
| 2 |
| 3 |
| 4 |
| 5 |
+-----+
[localhost:21000] > select x from numbers order by x limit 5 offset 5;
+-----+
| x |
+-----+
| 6 |
| 7 |
| 8 |
| 9 |
| 10 |
+-----+
```

UNION Clause

The **UNION** clause lets you combine the result sets of multiple queries. By default, the result sets are combined as if the **DISTINCT** operator was applied.

Syntax:

```
query_1 UNION [DISTINCT | ALL] query_2
```

Usage notes:

The `UNION` keyword by itself is the same as `UNION DISTINCT`. Because eliminating duplicates can be a memory-intensive process for a large result set, prefer `UNION ALL` where practical. (That is, when you know the different queries in the union will not produce any duplicates, or where the duplicate values are acceptable.)

When an `ORDER BY` clause applies to a `UNION ALL` or `UNION` query, in Impala 1.4 and higher, the `LIMIT` clause is no longer required. To make the `ORDER BY` and `LIMIT` clauses apply to the entire result set, turn the `UNION` query into a subquery, `SELECT` from the subquery, and put the `ORDER BY` clause at the end, outside the subquery.

Examples:

First, set up some sample data, including duplicate 1 values:

```
[localhost:21000] > create table few_ints (x int);
[localhost:21000] > insert into few_ints values (1), (1), (2), (3);
[localhost:21000] > set default_order_by_limit=1000;
```

This example shows how `UNION ALL` returns all rows from both queries, without any additional filtering to eliminate duplicates. For the large result sets common with Impala queries, this is the most memory-efficient technique.

```
[localhost:21000] > select x from few_ints order by x;
+----+
| x |
+----+
| 1 |
| 1 |
| 2 |
| 3 |
+----+
Returned 4 row(s) in 0.41s
[localhost:21000] > select x from few_ints union all select x from few_ints;
+----+
| x |
+----+
| 1 |
| 1 |
| 2 |
| 3 |
| 1 |
| 1 |
| 2 |
| 3 |
+----+
Returned 8 row(s) in 0.42s
[localhost:21000] > select * from (select x from few_ints union all select x
  from few_ints) as t1 order by x;
+----+
| x |
+----+
| 1 |
| 1 |
| 1 |
| 1 |
| 2 |
| 2 |
| 3 |
| 3 |
+----+
Returned 8 row(s) in 0.53s
[localhost:21000] > select x from few_ints union all select 10;
+----+
| x |
+----+
```

```

| 10 |
| 1  |
| 1  |
| 2  |
| 3  |
+----+
Returned 5 row(s) in 0.38s

```

This example shows how the UNION clause without the ALL keyword condenses the result set to eliminate all duplicate values, making the query take more time and potentially more memory. The extra processing typically makes this technique not recommended for queries that return result sets with millions or billions of values.

```

[localhost:21000] > select x from few_ints union select x+1 from few_ints;
+----+
| x  |
+----+
| 3  |
| 4  |
| 1  |
| 2  |
+----+
Returned 4 row(s) in 0.51s
[localhost:21000] > select x from few_ints union select 10;
+-----+
| x  |
+-----+
| 2  |
| 10 |
| 1  |
| 3  |
+-----+
Returned 4 row(s) in 0.49s
[localhost:21000] > select * from (select x from few_ints union select x
from few_ints) as t1 order by x;
+----+
| x  |
+----+
| 1  |
| 2  |
| 3  |
+----+
Returned 3 row(s) in 0.53s

```

Subqueries in Impala SELECT Statements

A *subquery* is a query that is nested within another query. Subqueries let queries on one table dynamically adapt based on the contents of another table. This technique provides great flexibility and expressive power for SQL queries.

A subquery can return a result set for use in the FROM or WITH clauses, or with operators such as IN or EXISTS.

A *scalar subquery* produces a result set with a single row containing a single column, typically produced by an aggregation function such as MAX() or SUM(). This single result value can be substituted in scalar contexts such as arguments to comparison operators. If the result set is empty, the value of the scalar subquery is NULL. For example, the following query finds the maximum value of T2.Y and then substitutes that value into the WHERE clause of the outer block that queries T1:

```
SELECT x FROM t1 WHERE x > (SELECT MAX(y) FROM t2);
```

Uncorrelated subqueries do not refer to any tables from the outer block of the query. The same value or set of values produced by the subquery is used when evaluating each row from the outer query block. In this example, the subquery

returns an arbitrary number of values from T2.Y, and each value of T1.X is tested for membership in that same set of values:

```
SELECT x FROM t1 WHERE x IN (SELECT y FROM t2);
```

Correlated subqueries compare one or more values from the outer query block to values referenced in the WHERE clause of the subquery. Each row evaluated by the outer WHERE clause can be evaluated using a different set of values. These kinds of subqueries are restricted in the kinds of comparisons they can do between columns of the inner and outer tables. (See the following **Restrictions** item.)

For example, the following query finds all the employees with salaries that are higher than average for their department. The subquery potentially computes a different AVG() value for each employee.

```
SELECT employee_name, employee_id FROM employees one WHERE
  salary > (SELECT avg(salary) FROM employees two WHERE one.dept_id =
    two.dept_id);
```

Syntax:

Subquery in the FROM clause:

```
SELECT select_list FROM table_ref [, table_ref ...]

table_ref ::= table_name | (select_statement)
```

Subqueries in WHERE clause:

```
WHERE value comparison_operator (scalar_select_statement)
WHERE value [NOT] IN (select_statement)
WHERE [NOT] EXISTS (correlated_select_statement)
WHERE NOT EXISTS (correlated_select_statement)
```

comparison_operator is a numeric comparison such as =, <=, !=, and so on, or a string comparison operator such as LIKE or REGEXP.

Although you can use non-equality comparison operators such as < or >=, the subquery must include at least one equality comparison between the columns of the inner and outer query blocks.

All syntax is available for both correlated and uncorrelated queries, except that the NOT EXISTS clause cannot be used with an uncorrelated subquery.

Impala subqueries can be nested arbitrarily deep.

Standards compliance: Introduced in [SQL:1999](#).

Examples:

This example illustrates how subqueries can be used in the FROM clause to organize the table names, column names, and column values by producing intermediate result sets, especially for join queries.

```
SELECT avg(t1.x), max(t2.y) FROM
  (SELECT id, cast(a AS DECIMAL(10,5)) AS x FROM raw_data WHERE a BETWEEN 0
  AND 100) AS t1
  JOIN
  (SELECT id, length(s) AS y FROM raw_data WHERE s LIKE 'A%') AS t2;
  USING (id);
```

These examples show how a query can test for the existence of values in a separate table using the EXISTS() operator with a subquery.

The following examples show how a value can be compared against a set of values returned by a subquery.

```
SELECT count(x) FROM t1 WHERE EXISTS(SELECT 1 FROM t2 WHERE t1.x = t2.y *
10);

SELECT x FROM t1 WHERE x IN (SELECT y FROM t2 WHERE state = 'CA');
```

The following examples demonstrate scalar subqueries. When a subquery is known to return a single value, you can substitute it where you would normally put a constant value.

```
SELECT x FROM t1 WHERE y = (SELECT max(z) FROM t2);
SELECT x FROM t1 WHERE y > (SELECT count(z) FROM t2);
```

Usage notes:

If the same table is referenced in both the outer and inner query blocks, construct a table alias in the outer query block and use a fully qualified name to distinguish the inner and outer table references:

```
SELECT * FROM t1 one WHERE id IN (SELECT parent FROM t1 two WHERE t1.parent
= t2.id);
```

The `STRAIGHT_JOIN` hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or `WHERE`-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

Internal details:

Internally, subqueries involving `IN`, `NOT IN`, `EXISTS`, or `NOT EXISTS` clauses are rewritten into join queries. Depending on the syntax, the subquery might be rewritten to an outer join, semi join, cross join, or anti join.

A query is processed differently depending on whether the subquery calls any aggregation functions. There are correlated and uncorrelated forms, with and without calls to aggregation functions. Each of these four categories is rewritten differently.

Column statistics considerations:

Because queries that include correlated and uncorrelated subqueries in the `WHERE` clause are written into join queries, to achieve best performance, follow the same guidelines for running the `COMPUTE STATS` statement as you do for tables involved in regular join queries. Run the `COMPUTE STATS` statement for each associated tables after loading or substantially changing the data in that table. See [Table and Column Statistics](#) on page 625 for details.

Added in: Subqueries are substantially enhanced starting in Impala 2.0. Now, they can be used in the `WHERE` clause, in combination with clauses such as `EXISTS` and `IN`, rather than just in the `FROM` clause.

Restrictions:

The initial Impala support for nested subqueries addresses the most common use cases. Some restrictions remain:

- Although you can use subqueries in a query involving `UNION` or `UNION ALL` in Impala 2.1.0 and higher, currently you cannot construct a union of two subqueries (for example, in the argument of an `IN` or `EXISTS` operator).
- Subqueries returning scalar values cannot be used with the operators `ANY` or `ALL`. (Impala does not currently have a `SOME` operator, but if it did, the same restriction would apply.)
- For the `EXISTS` and `NOT EXISTS` clauses, any subquery comparing values from the outer query block to another table must use at least one equality comparison, not exclusively other kinds of comparisons such as less than, greater than, `BETWEEN`, or `!=`.
- Currently, a scalar subquery cannot be used as the first or second argument to the `BETWEEN` operator.
- A subquery cannot be used inside an `OR` conjunction. Expressions inside a subquery, for example in the `WHERE` clause, can use `OR` conjunctions; the restriction only applies to parts of the query “above” the subquery.

- Scalar subqueries are only supported in numeric contexts. You cannot use a scalar subquery as an argument to the LIKE, REGEXP, or RLIKE operators, or compare it to a value of a non-numeric type such as TIMESTAMP or BOOLEAN.
- You cannot use subqueries with the CASE function to generate the comparison value, the values to be compared against, or the return value.
- A subquery is not allowed in the filter condition for the HAVING clause. (Strictly speaking, a subquery cannot appear anywhere outside the WITH, FROM, and WHERE clauses.)
- You must use a fully qualified name (*table_name.column_name* or *database_name.table_name.column_name*) when referring to any column from the outer query block within a subquery.
- The TABLESAMPLE clause of the SELECT statement does not apply to a table reference derived from a view, a subquery, or anything other than a real base table. This clause only works for tables backed by HDFS or HDFS-like data files, therefore it does not apply to Kudu or HBase tables.

Complex type considerations:

For the complex types (ARRAY, STRUCT, and MAP) available in Impala 2.3 and higher, the join queries that “unpack” complex type columns often use correlated subqueries in the FROM clause. For example, if the first table in the join clause is CUSTOMER, the second join clause might have a subquery that selects from the column CUSTOMER.C_ORDERS, which is an ARRAY. The subquery re-evaluates the ARRAY elements corresponding to each row from the CUSTOMER table. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details and examples of using subqueries with complex types.

Related information:

[EXISTS Operator](#) on page 183, [IN Operator](#) on page 188

TABLESAMPLE Clause

Specify the TABLESAMPLE clause in cases where you need to explore the data distribution within the table, the table is very large, and it is impractical or unnecessary to process all the data from the table or selected partitions.

The clause makes the query process a randomized set of data files from the table, so that the total volume of data is greater than or equal to the specified percentage of data bytes within that table. (Or the data bytes within the set of partitions that remain after partition pruning is performed.)

Syntax:

```
TABLESAMPLE SYSTEM(percentage) [REPEATABLE(seed)]
```

The TABLESAMPLE clause comes immediately after a table name or table alias.

The SYSTEM keyword represents the sampling method. Currently, Impala only supports a single sampling method named SYSTEM.

The *percentage* argument is an integer literal from 0 to 100. A percentage of 0 produces an empty result set for a particular table reference, while a percentage of 100 uses the entire contents. Because the sampling works by selecting a random set of data files, the proportion of sampled data from the table may be greater than the specified percentage, based on the number and sizes of the underlying data files. See the usage notes for details.

The optional REPEATABLE keyword lets you specify an arbitrary positive integer seed value that ensures that when the query is run again, the sampling selects the same set of data files each time. REPEATABLE does not have a default value. If you omit the REPEATABLE keyword, the random seed is derived from the current time.

Added in: Impala 2.9.0

See [COMPUTE STATS Statement](#) for the TABLESAMPLE clause used in the COMPUTE STATS statement.

Usage notes:

You might use this clause with aggregation queries, such as finding the approximate average, minimum, or maximum where exact precision is not required. You can use these findings to plan the most effective strategy for constructing queries against the full table or designing a partitioning strategy for the data.

Some other database systems have a `TABLESAMPLE` clause. The Impala syntax for this clause is modeled on the syntax for popular relational databases, not the Hive `TABLESAMPLE` clause. For example, there is no `BUCKETS` keyword as in HiveQL.

The precision of the *percentage* threshold depends on the number and sizes of the underlying data files. Impala brings in additional data files, one at a time, until the number of bytes exceeds the specified percentage based on the total number of bytes for the entire set of table data. The precision of the percentage threshold is higher when the table contains many data files with consistent sizes. See the code listings later in this section for examples.

When you estimate characteristics of the data distribution based on sampling a percentage of the table data, be aware that the data might be unevenly distributed between different files. Do not assume that the percentage figure reflects the percentage of rows in the table. For example, one file might contain all blank values for a `STRING` column, while another file contains long strings in that column; therefore, one file could contain many more rows than another. Likewise, a table created with the `SORT BY` clause might contain narrow ranges of values for the sort columns, making it impractical to extrapolate the number of distinct values for those columns based on sampling only some of the data files.

Because a sample of the table data might not contain all values for a particular column, if the `TABLESAMPLE` is used in a join query, the key relationships between the tables might produce incomplete result sets compared to joins using all the table data. For example, if you join 50% of table A with 50% of table B, some values in the join columns might not match between the two tables, even though overall there is a 1:1 relationship between the tables.

The `REPEATABLE` keyword makes identical queries use a consistent set of data files when the query is repeated. You specify an arbitrary integer key that acts as a seed value when Impala randomly selects the set of data files to use in the query. This technique lets you verify correctness, examine performance, and so on for queries using the `TABLESAMPLE` clause without the sampled data being different each time. The repeatable aspect is reset (that is, the set of selected data files may change) any time the contents of the table change. The statements or operations that can make sampling results non-repeatable are:

- `INSERT`.
- `TRUNCATE TABLE`.
- `LOAD DATA`.
- `REFRESH` or `INVALIDATE METADATA` after files are added or removed by a non-Impala mechanism.
-

This clause is similar in some ways to the `LIMIT` clause, because both serve to limit the size of the intermediate data and final result set. `LIMIT 0` is more efficient than `TABLESAMPLE SYSTEM(0)` for verifying that a query can execute without producing any results. `TABLESAMPLE SYSTEM(n)` often makes query processing more efficient than using a `LIMIT` clause by itself, because all phases of query execution use less data overall. If the intent is to retrieve some representative values from the table in an efficient way, you might combine `TABLESAMPLE`, `ORDER BY`, and `LIMIT` clauses within a single query.

Partitioning:

When you query a partitioned table, any partition pruning happens before Impala selects the data files to sample. For example, in a table partitioned by year, a query with `WHERE year = 2017` and a `TABLESAMPLE SYSTEM(10)` clause would sample data files representing at least 10% of the bytes present in the 2017 partition.

Amazon S3 considerations:

This clause applies to S3 tables the same way as tables with data files stored on HDFS.

ADLS considerations:

This clause applies to ADLS tables the same way as tables with data files stored on HDFS.

Kudu considerations:

This clause does not apply to Kudu tables.

HBase considerations:

This clause does not apply to HBase tables.

Performance considerations:

From a performance perspective, the TABLESAMPLE clause is especially valuable for exploratory queries on text, Avro, or other file formats other than Parquet. Text-based or row-oriented file formats must process substantial amounts of redundant data for queries that derive aggregate results such as MAX(), MIN(), or AVG() for a single column. Therefore, you might use TABLESAMPLE early in the ETL pipeline, when data is still in raw text format and has not been converted to Parquet or moved into a partitioned table.

Restrictions:

This clause applies only to tables that use a storage layer with underlying raw data files, such as HDFS, Amazon S3, or Microsoft ADLS.

This clause does not apply to table references that represent views. A query that applies the TABLESAMPLE clause to a view or a subquery fails with a semantic error.

Because the sampling works at the level of entire data files, it is by nature coarse-grained. It is possible to specify a small sample percentage but still process a substantial portion of the table data if the table contains relatively few data files, if each data file is very large, or if the data files vary substantially in size. Be sure that you understand the data distribution and physical file layout so that you can verify if the results are suitable for extrapolation. For example, if the table contains only a single data file, the “sample” will consist of all the table data regardless of the percentage you specify. If the table contains data files of 1 GiB, 1 GiB, and 1 KiB, when you specify a sampling percentage of 50 you would either process slightly more than 50% of the table (1 GiB + 1 KiB) or almost the entire table (1 GiB + 1 GiB), depending on which data files were selected for sampling.

If data files are added by a non-Impala mechanism, and the table metadata is not updated by a REFRESH or INVALIDATE METADATA statement, the TABLESAMPLE clause does not consider those new files when computing the number of bytes in the table or selecting which files to sample.

If data files are removed by a non-Impala mechanism, and the table metadata is not updated by a REFRESH or INVALIDATE METADATA statement, the query fails if the TABLESAMPLE clause attempts to reference any of the missing files.

Examples:

The following examples demonstrate the TABLESAMPLE clause. These examples intentionally use very small data sets to illustrate how the number of files, size of each file, and overall size of data in the table interact with the percentage specified in the clause.

These examples use an unpartitioned table, containing several files of roughly the same size:

```
create table sample_demo (x int, s string);

insert into sample_demo values (1, 'one');
insert into sample_demo values (2, 'two');
insert into sample_demo values (3, 'three');
insert into sample_demo values (4, 'four');
insert into sample_demo values (5, 'five');
```

```
show files in sample_demo;
```

Path	Size	Partition
991213608_data.0.	7B	
982196806_data.0.	6B	
_2122096884_data.0.	8B	
_586325431_data.0.	6B	
1894746258_data.0.	7B	

```
show table stats sample_demo;
```

#Rows	#Files	Size	Format	Location
-1	5	34B	TEXT	/tsample.db/sample_demo

A query that samples 50% of the table must process at least 17 bytes of data. Based on the sizes of the data files, we can predict that each such query uses 3 arbitrary files. Any 1 or 2 files are not enough to reach 50% of the total data in the table (34 bytes), so the query adds more files until it passes the 50% threshold:

```
select distinct x from sample_demo tablesample system(50);
```

```
+----+
| x |
+----+
| 4 |
| 1 |
| 5 |
+----+
```

```
select distinct x from sample_demo tablesample system(50);
```

```
+----+
| x |
+----+
| 5 |
| 4 |
| 2 |
+----+
```

```
select distinct x from sample_demo tablesample system(50);
```

```
+----+
| x |
+----+
| 5 |
| 3 |
| 2 |
+----+
```

To help run reproducible experiments, the `REPEATABLE` clause causes Impala to choose the same set of files for each query. Although the data set being considered is deterministic, the order of results varies (in the absence of an `ORDER BY` clause) because of the way distributed queries are processed:

```
select distinct x from sample_demo
  tablesample system(50) repeatable (12345);
```

```
+----+
| x |
+----+
| 3 |
| 2 |
| 1 |
+----+
```

```
select distinct x from sample_demo
  tablesample system(50) repeatable (12345);
```

```
+----+
| x |
+----+
| 2 |
| 1 |
| 3 |
+----+
```

The following examples show how uneven data distribution affects which data is sampled. Adding another data file containing a long string value changes the threshold for 50% of the total data in the table:

```
insert into sample_demo values
(1000, 'Boyhood is the longest time in life for a boy. The last term of the
school-year is made of decades, not of weeks, and living through them is
like waiting for the millennium. Booth Tarkington');
```

```
show files in sample_demo;
```

Path	Size	Partition
991213608_data.0.	7B	
982196806_data.0.	6B	
_253317650_data.0.	196B	
_2122096884_data.0.	8B	
_586325431_data.0.	6B	
1894746258_data.0.	7B	

```
show table stats sample_demo;
```

#Rows	#Files	Size	Format	Location
-1	6	230B	TEXT	/tsample.db/sample_demo

Even though the queries do not refer to the S column containing the long value, all the sampling queries include the data file containing the column value X=1000, because the query cannot reach the 50% threshold (115 bytes) without including that file. The large file might be considered first, in which case it is the only file processed by the query. Or an arbitrary set of other files might be considered first.

```
select distinct x from sample_demo tablesample system(50);
```

x
1000
3
1

```
select distinct x from sample_demo tablesample system(50);
```

x
1000

```
select distinct x from sample_demo tablesample system(50);
```

x
1000
4
2
1

The following examples demonstrate how the TABLESAMPLE clause interacts with other table aspects, such as partitioning and file format:

```
create table sample_demo_partitions (x int, s string) partitioned by (n int)
stored as parquet;

insert into sample_demo_partitions partition (n = 1) select * from
sample_demo;
insert into sample_demo_partitions partition (n = 2) select * from
sample_demo;
insert into sample_demo_partitions partition (n = 3) select * from
sample_demo;

show files in sample_demo_partitions;
```

Path	Size	Partition
000000_364262785_data.0.parq	1.24KB	n=1
000001_973526736_data.0.parq	566B	n=1
0000000_1300598134_data.0.parq	1.24KB	n=2
0000001_689099063_data.0.parq	568B	n=2
0000000_1861371709_data.0.parq	1.24KB	n=3
0000001_1065507912_data.0.parq	566B	n=3

```
show table stats tablesample_demo_partitioned;
```

n	#Rows	#Files	Size	Format	Location
1	-1	2	1.79KB	PARQUET	/tsample.db/ tablesample_demo_partitioned/n=1
2	-1	2	1.80KB	PARQUET	/tsample.db/ tablesample_demo_partitioned/n=2
3	-1	2	1.79KB	PARQUET	/tsample.db/ tablesample_demo_partitioned/n=3
Total	-1	6	5.39KB		

If the query does not involve any partition pruning, the sampling applies to the data volume of the entire table:

```
-- 18 rows total.
select count(*) from sample_demo_partitions;
```

count(*)
18

```
-- The number of rows per data file is not
-- perfectly balanced, therefore the count
-- is different depending on which set of files
-- is considered.
select count(*) from sample_demo_partitions
tablesample system(75);
```

count(*)
14

```
+-----+
select count(*) from sample_demo_partitions
      tablesample system(75);
+-----+
| count(*) |
+-----+
| 16       |
+-----+
```

If the query only processes certain partitions, the query computes the sampling threshold based on the data size and set of files only from the relevant partitions:

```
select count(*) from sample_demo_partitions
      tablesample system(50) where n = 1;
+-----+
| count(*) |
+-----+
| 6        |
+-----+

select count(*) from sample_demo_partitions
      tablesample system(50) where n = 1;
+-----+
| count(*) |
+-----+
| 2        |
+-----+
```

Related information:

[SELECT Statement](#) on page 316

WITH Clause

A clause that can be added before a `SELECT` statement, to define aliases for complicated expressions that are referenced multiple times within the body of the `SELECT`. Similar to `CREATE VIEW`, except that the table and column names defined in the `WITH` clause do not persist after the query finishes, and do not conflict with names used in actual tables or views. Also known as “subquery factoring”.

You can rewrite a query using subqueries to work the same as with the `WITH` clause. The purposes of the `WITH` clause are:

- Convenience and ease of maintenance from less repetition with the body of the query. Typically used with queries involving `UNION`, joins, or aggregation functions where the similar complicated expressions are referenced multiple times.
- SQL code that is easier to read and understand by abstracting the most complex part of the query into a separate block.
- Improved compatibility with SQL from other database systems that support the same clause (primarily Oracle Database).

Note:

The Impala `WITH` clause does not support recursive queries in the `WITH`, which is supported in some other database systems.

Standards compliance: Introduced in [SQL:1999](#).

Examples:

```
-- Define 2 subqueries that can be referenced from the body of a longer
query.
```



```

with t1 as (select 1), t2 as (select 2) insert into tab select * from t1
union all select * from t2;

-- Define one subquery at the outer level, and another at the inner level as
-- part of the
-- initial stage of the UNION ALL query.
with t1 as (select 1) (with t2 as (select 2) select * from t2) union all
select * from t1;

```

DISTINCT Operator

The DISTINCT operator in a SELECT statement filters the result set to remove duplicates.

```

-- Returns the unique values from one column.
-- NULL is included in the set of values if any rows have a NULL in this
-- column.
SELECT DISTINCT c_birth_country FROM customer;

-- Returns the unique combinations of values from multiple columns.
SELECT DISTINCT c_salutation, c_last_name FROM customer;

```

You can use DISTINCT in combination with an aggregation function, typically COUNT(), to find how many different values a column contains.

```

-- Counts the unique values from one column.
-- NULL is not included as a distinct value in the count.
SELECT COUNT(DISTINCT c_birth_country) FROM customer;

-- Counts the unique combinations of values from multiple columns.
SELECT COUNT(DISTINCT c_salutation, c_last_name) FROM customer;

```

Zero-length strings: For purposes of clauses such as DISTINCT and GROUP BY, Impala considers zero-length strings (" "), NULL, and space to all be different values.

Note:

In contrast with some database systems that always return DISTINCT values in sorted order, Impala does not do any ordering of DISTINCT values. Always include an ORDER BY clause if you need the values in alphabetical or numeric sorted order.

SET Statement

The SET statement specifies values for query options that control the runtime behavior of other statements within the same session.

When issued in `impala-shell`, the SET command is interpreted as an `impala-shell` command that has differences from the SQL SET statement. See [impala-shell Command Reference](#) on page 799 for the information about the SET command in `impala-shell`.

Syntax:

```

SET
SET ALL
SET query_option=option_value
SET query_option=" "

```

SET and SET ALL with no arguments return a result set consisting of all the applicable query options and their current values.

The `query_option` and `option_value` are case-insensitive.

Unlike the `impala-shell` command version of `SET`, when used as a SQL statement, the string values for `option_value` need to be quoted, e.g. `SET option="new_value"`.

The `SET query_option = ""` statement unsets the value of the `query_option` in the current session, reverting it to the default state. In `impala-shell`, use the `UNSET` command to set a query option to its default.

Each query option has a specific allowed notation for its arguments.

Usage notes:

In Impala 2.11 and higher, the outputs of the `SET` and `SET ALL` statements were reorganized as below:

- The options are divided into groups: Regular Query Options, Advanced Query Options, Development Query Options, and Deprecated Query Options.
 - The advanced options are intended for use in specific kinds of performance tuning and debugging scenarios.
 - The development options are related to internal development of Impala or features that are not yet finalized. These options might be changed or removed without notice.
 - The deprecated options are related to features that are removed or changed so that the options no longer have any purpose. These options might be removed in future versions.
- By default, only the first two groups, regular and advanced, are displayed by the `SET` command. Use `SET ALL` to see all groups of options.
- `impala-shell` options and user-specified variables are always displayed at the end of the list of query options, after all appropriate option groups.

Added in: Impala 2.0.0

`SET` has always been available as an `impala-shell` command. Promoting it to a SQL statement lets you use this feature in client applications through the JDBC and ODBC APIs.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Query Options for the SET Statement:

You can specify the following options using the `SET` statement, and those settings affect all queries issued from that session.

Some query options are useful in day-to-day operations for improving usability, performance, or flexibility.

Other query options control special-purpose aspects of Impala operation and are intended primarily for advanced debugging or troubleshooting.

Options with Boolean parameters can be set to 1 or `true` to enable, or 0 or `false` to turn off.

Note:

In Impala 2.0 and later, you can set query options directly through the JDBC and ODBC interfaces by using the `SET` statement. Formerly, `SET` was only available as a command within the `impala-shell` interpreter.

In Impala 2.11 and later, you can set query options for an `impala-shell` session by specifying one or more command-line arguments of the form `--query_option=option=value`. See [impala-shell Configuration Options](#) on page 791 for details.

Related information:

[SET Statement](#) on page 345

ABORT_ON_ERROR Query Option

When this option is enabled, Impala cancels a query immediately when any of the nodes encounters an error, rather than continuing and possibly returning incomplete results. This option is disabled by default, to help gather maximum diagnostic information when an error occurs, for example, whether the same problem occurred on all nodes or only a single node. Currently, the errors that Impala can skip over involve data corruption, such as a column that contains a string value when expected to contain an integer value.

To control how much logging Impala does for non-fatal errors when `ABORT_ON_ERROR` is turned off, use the `MAX_ERRORS` option.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Related information:

[MAX_ERRORS Query Option](#) on page 366, [Using Impala Logging](#) on page 784

ALLOW_ERASURE_CODED_FILES Query Option

Use the `ALLOW_ERASURE_CODED_FILES` query option to enable or disable the support of erasure coded files in Impala.

When the `ALLOW_ERASURE_CODED_FILES` query option is set to `FALSE`, Impala returns an error when a query requires scanning an erasure coded file.

Type: `BOOLEAN`

Default: `TRUE`

Added in: Impala 3.1

ALLOW_UNSUPPORTED_FORMATS Query Option

Note: This query option was removed in Impala 3.1 and no longer has any effect. Do not use.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

APPX_COUNT_DISTINCT Query Option (Impala 2.0 or higher only)

When the `APPX_COUNT_DISTINCT` query option is set to `TRUE`, Impala implicitly converts `COUNT(DISTINCT)` operations to the `NDV()` function calls. The resulting count is approximate rather than precise. Enable the query option when a tolerable amount of error is acceptable in order to obtain faster query results than with a `COUNT(DISTINCT)` queries.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Related information:

[COUNT Function](#) on page 545, [DISTINCT Operator](#) on page 345, [NDV Function](#) on page 559

BATCH_SIZE Query Option

Number of rows evaluated at a time by SQL operators. Unspecified or a size of 0 uses a predefined default size. Using a large number improves responsiveness, especially for scan operations, at the cost of a higher memory footprint.

This option is primarily for testing during Impala development, or for use under the direction of the appropriate support channel.

Type: numeric

Default: 0 (meaning the predefined default of 1024)

Range: 0-65536. The value of 0 still has the special meaning of “use the default”, so the effective range is 1-65536. The maximum applies in Impala 2.11 and higher.

BROADCAST_BYTES_LIMIT Query Option

Sets the limit for the size of the broadcast input based on estimated size.

The Impala planner may in rare cases make a bad choice to broadcast a large table or intermediate result and encounter performance problems due to high memory pressure. Setting this limit will make the planner pick a partition based hash join instead of broadcast and avoid such performance problems.

Type: integer

Default:

The default value is 34359738368 (32 GB). A value of 0 causes the option to be ignored.

Examples:

```
-- Change the limit to 16GB.
set broadcast_bytes_limit=17179869184;

-- Disable the BROADCAST_BYTES_LIMIT.
set broadcast_bytes_limit=0;
```

BUFFER_POOL_LIMIT Query Option

Defines a limit on the amount of memory that a query can allocate from the internal buffer pool. The value for this limit applies to the memory on each host, not the aggregate memory across the cluster. Typically not changed by users, except during diagnosis of out-of-memory errors during queries.

Type: integer

Default:

The default setting for this option is the lower of 80% of the MEM_LIMIT setting, or the MEM_LIMIT setting minus 100 MB.

Added in: Impala 2.10.0

Usage notes:

If queries encounter out-of-memory errors, consider decreasing the BUFFER_POOL_LIMIT setting to less than 80% of the MEM_LIMIT setting.

Examples:

```
-- Set an absolute value.
set buffer_pool_limit=8GB;

-- Set a relative value based on the MEM_LIMIT setting.
set buffer_pool_limit=80%;
```

Related information:

[DEFAULT_SPILLABLE_BUFFER_SIZE Query Option](#) on page 352, [MAX_ROW_SIZE Query Option](#) on page 367, [MIN_SPILLABLE_BUFFER_SIZE Query Option](#) on page 373, [Scalability Considerations for Impala](#) on page 657

COMPRESSION_CODEC Query Option (Impala 2.0 or higher only)

When Impala writes Parquet data files using the INSERT statement, the underlying compression is controlled by the COMPRESSION_CODEC query option.

Note: Prior to Impala 2.0, this option was named PARQUET_COMPRESSION_CODEC. In Impala 2.0 and later, the PARQUET_COMPRESSION_CODEC name is not recognized. Use the more general name COMPRESSION_CODEC for new code.

Syntax:

```
SET COMPRESSION_CODEC=codec_name; // Supported for all codecs.
SET COMPRESSION_CODEC=codec_name:compression_level; // Only supported for
ZSTD.
```

The allowed values for this query option are SNAPPY (the default), GZIP, ZSTD, LZ4, and NONE.

ZSTD also supports setting a compression level. The lower the level, the faster the speed at the cost of compression ratio. Compression levels from 1 up to 22 are supported for ZSTD. The default compression level 3 is used, if one is not passed using the `compression_codec` query option.

Note: A Parquet file created with `COMPRESSION_CODEC=NONE` is still typically smaller than the original data, due to encoding schemes such as run-length encoding and dictionary encoding that are applied separately from compression.

The option value is not case-sensitive.

If the option is set to an unrecognized value, all kinds of queries will fail due to the invalid option setting, not just queries involving Parquet tables. (The value BZIP2 is also recognized, but is not compatible with Parquet tables.)

Type: STRING

Default: SNAPPY

Examples:

```
set compression_codec=lz4;
insert into parquet_table_lz4_compressed select * from t1;

set compression_codec=zstd; // Default compression level 3.
insert into parquet_table_zstd_default_compressed select * from t1;

set compression_codec=zstd:12; // Compression level 12.
insert into parquet_table_zstd_highly_compressed select * from t1;

set compression_codec=gzip;
insert into parquet_table_highly_compressed select * from t1;

set compression_codec=snappy;
insert into parquet_table_compression_plus_fast_queries select * from t1;

set compression_codec=none;
insert into parquet_table_no_compression select * from t1;

set compression_codec=foo;
select * from t1 limit 5;
ERROR: Invalid compression codec: foo
```

Related information:

For information about how compressing Parquet data files affects query performance, see [Compressions for Parquet Data Files](#) on page 709.

COMPUTE_STATS_MIN_SAMPLE_SIZE Query Option

The `COMPUTE_STATS_MIN_SAMPLE_SIZE` query option specifies the minimum number of bytes that will be scanned in `COMPUTE STATS TABLESAMPLE`, regardless of the user-supplied sampling percent. This query option prevents sampling for very small tables where accurate stats can be obtained cheaply without sampling because the minimum sample size is required to get meaningful stats.

Type: integer

Default: 1GB

Added in: Impala 2.12

Usage notes:

DEBUG_ACTION Query Option

Introduces artificial problem conditions within queries. For internal debugging and troubleshooting.

Type: STRING

Default: empty string

DECIMAL_V2 Query Option

A query option that changes behavior related to the DECIMAL data type. Set this option to FALSE for backward compatibility to Impala 2.x.

Type: Boolean

Default: TRUE

DEFAULT_FILE_FORMAT Query Option

Use the DEFAULT_FILE_FORMAT query option to set the default table file format. The following values are supported:

- TEXT (0)
- RC_FILE (1)
- SEQUENCE_FILE (2)
- AVRO (3)
- PARQUET (4)
- KUDU (5)
- ORC (6)

In impala-shell or Hue, the SET DEFAULT_FILE_FORMAT statement will not return an error when the option was set to an unsupported value. Impala validates the value and returns an error when you submitted the next query.

Type: Enum as specified above

Default: TEXT (0)

Added in: Impala 3.2

DEFAULT_HINTS_INSERT_STATEMENT Query Option

The DEFAULT_HINTS_INSERT_STATEMENT query option sets the default hints for the INSERT statements with no optimizer hint specified.

When there are hints specified in an INSERT statement, these default hints are ignored.

You can specify multiple hints separated by ': '.

For example:

```
SET DEFAULT_HINTS_INSERT_STATEMENT=CLUSTERED ;
SET DEFAULT_HINTS_INSERT_STATEMENT=SHUFFLE ;
SET DEFAULT_HINTS_INSERT_STATEMENT=NOCLUSTERED:NOSHUFFLE ;
```

The default hints apply to the HDFS and Kudu table formats and are ignored for the HBase table format.

Type: STRING

Default: none

Added in: Impala 3.3

DEFAULT_JOIN_DISTRIBUTION_MODE Query Option

This option determines the join distribution that Impala uses when any of the tables involved in a join query is missing statistics.

Impala optimizes join queries based on the presence of table statistics, which are produced by the Impala `COMPUTE STATS` statement. By default, when a table involved in the join query does not have statistics, Impala uses the “broadcast” technique that transmits the entire contents of the table to all executor nodes participating in the query. If one table involved in a join has statistics and the other does not, the table without statistics is broadcast. If both tables are missing statistics, the table that is referenced second in the join order is broadcast. This behavior is appropriate when the table involved is relatively small, but can lead to excessive network, memory, and CPU overhead if the table being broadcast is large.

Because Impala queries frequently involve very large tables, and suboptimal joins for such tables could result in spilling or out-of-memory errors, the setting `DEFAULT_JOIN_DISTRIBUTION_MODE=SHUFFLE` lets you override the default behavior. The shuffle join mechanism divides the corresponding rows of each table involved in a join query using a hashing algorithm, and transmits subsets of the rows to other nodes for processing. Typically, this kind of join is more efficient for joins between large tables of similar size.

The setting `DEFAULT_JOIN_DISTRIBUTION_MODE=SHUFFLE` is recommended when setting up and deploying new clusters, because it is less likely to result in serious consequences such as spilling or out-of-memory errors if the query plan is based on incomplete information. This setting is not the default, to avoid changing the performance characteristics of join queries for clusters that are already tuned for their existing workloads.

Type: integer

The allowed values are `BROADCAST` (equivalent to 0) or `SHUFFLE` (equivalent to 1).

Examples:

The following examples demonstrate appropriate scenarios for each setting of this query option.

```
-- Create a billion-row table.
create table big_table stored as parquet
  as select * from huge_table limit 1e9;

-- For a big table with no statistics, the
-- shuffle join mechanism is appropriate.
set default_join_distribution_mode=shuffle;

...join queries involving the big table...
```

```
-- Create a hundred-row table.
create table tiny_table stored as parquet
  as select * from huge_table limit 100;

-- For a tiny table with no statistics, the
-- broadcast join mechanism is appropriate.
set default_join_distribution_mode=broadcast;

...join queries involving the tiny table...
```

```
compute stats tiny_table;
compute stats big_table;

-- Once the stats are computed, the query option has
-- no effect on join queries involving these tables.
-- Impala can determine the absolute and relative sizes
-- of each side of the join query by examining the
```

```
-- row size, cardinality, and so on of each table.

...join queries involving both of these tables...
```

Related information:

[COMPUTE STATS Statement](#) on page 232, [Joins in Impala SELECT Statements](#) on page 318, [Performance Considerations for Join Queries](#) on page 618

DEFAULT_SPILLABLE_BUFFER_SIZE Query Option

Specifies the default size for a memory buffer used when the spill-to-disk mechanism is activated, for example for queries against a large table with no statistics, or large join operations.

Type: integer

Default:

2097152 (2 MB)

Units: A numeric argument represents a size in bytes; you can also use a suffix of m or mb for megabytes, or g or gb for gigabytes. If you specify a value with unrecognized formats, subsequent queries fail with an error.

Added in: Impala 2.10.0

Usage notes:

This query option sets an upper bound on the size of the internal buffer size that can be used during spill-to-disk operations. The actual size of the buffer is chosen by the query planner.

If overall query performance is limited by the time needed for spilling, consider increasing the `DEFAULT_SPILLABLE_BUFFER_SIZE` setting. Larger buffer sizes result in Impala issuing larger I/O requests to storage devices, which might result in higher throughput, particularly on rotational disks.

The tradeoff with a large value for this setting is increased memory usage during spill-to-disk operations. Reducing this value may reduce memory consumption.

To determine if the value for this setting is having an effect by capping the spillable buffer size, you can see the buffer size chosen by the query planner for a particular query. `EXPLAIN` the query while the setting `EXPLAIN_LEVEL=2` is in effect.

Examples:

```
set default_spillable_buffer_size=4MB;
```

Related information:

[BUFFER_POOL_LIMIT Query Option](#) on page 348, [MAX_ROW_SIZE Query Option](#) on page 367, [MIN_SPILLABLE_BUFFER_SIZE Query Option](#) on page 373, [Scalability Considerations for Impala](#) on page 657

DEFAULT_TRANSACTIONAL_TYPE Query Option

Use the `DEFAULT_TRANSACTIONAL_TYPE` query option to create insert-only transactional tables by default.

Note: The `DEFAULT_TRANSACTIONAL_TYPE` query option applies only when integrated with Hive 3.

The supported values are:

- `NONE`: The table will not be created as transactional.
- `INSERT_ONLY`: The table will be created as transactional. See [Impala Transactions](#) on page 213 for details.

If either table properties, `transactional` or `transactional_properties`, are set, this query option is ignored.

Note: The `DEFAULT_TRANSACTIONAL_TYPE` query option does not affect external, Kudu, or HBase tables as these cannot be transactional.

Type: Enum as specified above

Default: NONE

Added in: Impala 3.3

DELETE_STATS_IN_TRUNCATE Query Option

This query option `DELETE_STATS_IN_TRUNCATE` can be used to delete or retain table statistics. The default value of this option is 1 or true which means table statistics will be deleted as part of truncate operation. However the default may not be an ideal solution in case of non-transactional tables when the table and column statistics for the table are also deleted by default. This can be an expensive operation especially when many truncate table commands are running concurrently. In cases where truncate operation is used to remove the existing data and then reload new data, it is likely that you will compute stats again as soon as the new data is reloaded. This would overwrite the existing statistics and hence the additional time spent by the truncate operation to delete column and table statistics becomes obsolete. To avoid this expensive operation and to improve performance, you can set this query option to false or 0. When set to false, a truncate operation will not delete the table and column statistics for the table.

Type: BOOLEAN; recognized values are 1 and 0, or true and false;

Default: TRUE (shown as 1 in output of SET statement).

Added in: Impala 4.0

DISABLE_CODEGEN Query Option

The `DISABLE_CODEGEN` is a debug option, and it's used to work around any issues with Impala's runtime code generation. If a query fails with an “illegal instruction” or other hardware-specific message, try setting `DISABLE_CODEGEN=true` and running the query again. If the query succeeds only when the `DISABLE_CODEGEN` option is turned on, submit the problem to the appropriate support channel and include that detail in the problem report.

Most queries will run significantly slower with `DISABLE_CODEGEN=true`.

In Impala 2.10 and higher, the `DISABLE_CODEGEN_ROWS_THRESHOLD` optimisation automatically disables codegen for small queries because short-running queries may run faster without the overhead of codegen.

The following values are supported:

- TRUE or 1: Disables codegen.
- FALSE or 0: Enables codegen.

Type: Boolean

Default: false (shown as 0 in output of SET statement)

DISABLE_CODEGEN_ROWS_THRESHOLD Query Option (Impala 2.10 or higher only)

This setting controls the cutoff point (in terms of number of rows processed per Impala daemon) below which Impala disables native code generation for the whole query. Native code generation is very beneficial for queries that process many rows because it reduces the time taken to process of each row. However, generating the native code adds latency to query startup. Therefore, automatically disabling codegen for queries that process relatively small amounts of data can improve query response time.

Syntax:

```
SET DISABLE_CODEGEN_ROWS_THRESHOLD=number_of_rows
```

Type: numeric

Default: 50000

Usage notes: Typically, you increase the default value to make this optimization apply to more queries. If incorrect or corrupted table and column statistics cause Impala to apply this optimization incorrectly to queries that actually involve substantial work, you might see the queries being slower as a result of codegen being disabled. In that case, recompute statistics with the `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement. If there is a problem collecting accurate statistics, you can turn this feature off by setting the value to 0.

Internal details:

This setting applies to queries where the number of rows processed can be accurately determined, either through table and column statistics, or by the presence of a `LIMIT` clause. If Impala cannot accurately estimate the number of rows, then this setting does not apply.

If a query uses the complex data types `STRUCT`, `ARRAY`, or `MAP`, then codegen is never automatically disabled regardless of the `DISABLE_CODEGEN_ROWS_THRESHOLD` setting.

Added in: Impala 2.10.0

DISABLE_HBASE_NUM_ROWS_ESTIMATE Query Option

Use the `DISABLE_HBASE_NUM_ROWS_ESTIMATE` query option to disable key sampling of HBase tables in row count and row size estimation.

While generating a plan for an HBase query, the planner samples the underlying HBase tables to estimate their row count and row size, and the sampling can negatively impact the planning time. When the HBase table stats does not change much in short time, disable the sampling by setting the `DISABLE_HBASE_NUM_ROWS_ESTIMATE` query option to `TRUE`. And Impala planner will fall back to using Hive Metastore (HMS) table stats instead.

When `DISABLE_HBASE_NUM_ROWS_ESTIMATE` query option is set to `TRUE`, you need to update the HMS table stats by running `COMPUTE STATS`. Alternatively, you can manually set table statistics by running `ALTER TABLE`. See [Table and Column Statistics](#) on page 625 for details.

The following values are supported:

- `TRUE` or `1`: Disables the normal key sampling of HBase tables and uses HMS table stats for estimation.
- `FALSE` or `0`: Enables the normal sampling of HBase tables.

Type: `BOOLEAN`

Default: `FALSE`

DISABLE_ROW_RUNTIME_FILTERING Query Option (Impala 2.5 or higher only)

The `DISABLE_ROW_RUNTIME_FILTERING` query option reduces the scope of the runtime filtering feature. Queries still dynamically prune partitions, but do not apply the filtering logic to individual rows within partitions.

Only applies to queries against Parquet tables. For other file formats, Impala only prunes at the level of partitions, not individual rows.

Type: Boolean; recognized values are `1` and `0`, or `true` and `false`; any other value interpreted as `false`

Default: `false`

Added in: Impala 2.5.0

Usage notes:

Impala automatically evaluates whether the per-row filters are being effective at reducing the amount of intermediate data. Therefore, this option is typically only needed for the rare case where Impala cannot accurately determine how effective the per-row filtering is for a query.

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Because this setting only improves query performance in very specific circumstances, depending on the query characteristics and data distribution, only use it when you determine through benchmarking that it improves

performance of specific expensive queries. Consider setting this query option immediately before the expensive query and unsetting it immediately afterward.

File format considerations:

This query option only applies to queries against HDFS-based tables using the Parquet file format.

Kudu considerations:

When applied to a query involving a Kudu table, this option turns off all runtime filtering for the Kudu table.

Related information:

[Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641, [RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389

DISABLE_STREAMING_PREAGGREGATIONS Query Option (Impala 2.5 or higher only)

Turns off the “streaming preaggregation” optimization that is available in Impala 2.5 and higher. This optimization reduces unnecessary work performed by queries that perform aggregation operations on columns with few or no duplicate values, for example `DISTINCT id_column` or `GROUP BY unique_column`. If the optimization causes regressions in existing queries that use aggregation functions, you can turn it off as needed by setting this query option.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Note: In Impala 2.5.0, only the value 1 enables the option, and the value `true` is not recognized. This limitation is tracked by the issue [IMPALA-3334](#), which shows the releases where the problem is fixed.

Usage notes:

Typically, queries that would require enabling this option involve very large numbers of aggregated values, such as a billion or more distinct keys being processed on each worker node.

Added in: Impala 2.5.0

DISABLE_UNSAFE_SPILLS Query Option (Impala 2.0 or higher only)

Enable this option if you prefer to have queries fail when they exceed the Impala memory limit, rather than write temporary data to disk.

Queries that “spill” to disk typically complete successfully, when in earlier Impala releases they would have failed. However, queries with exorbitant memory requirements due to missing statistics or inefficient join clauses could become so slow as a result that you would rather have them cancelled automatically and reduce the memory usage through standard Impala tuning techniques.

This option prevents only “unsafe” spill operations, meaning that one or more tables are missing statistics or the query does not include a hint to set the most efficient mechanism for a join or `INSERT . . . SELECT` into a partitioned table. These are the tables most likely to result in suboptimal execution plans that could cause unnecessary spilling. Therefore, leaving this option enabled is a good way to find tables on which to run the `COMPUTE STATS` statement.

See [SQL Operations that Spill to Disk](#) on page 660 for information about the “spill to disk” feature for queries processing large result sets with joins, `ORDER BY`, `GROUP BY`, `DISTINCT`, aggregation functions, or analytic functions.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Added in: Impala 2.0.0

ENABLE_EXPR_REWRITES Query Option

The `ENABLE_EXPR_REWRITES` query option controls whether to enable or disable the query compile time optimizations. These optimizations rewrite the expression trees to a more compact and optimized form that helps avoid redundant expression evaluation at run time. Performance optimizations controlled by this query option include:

- Constant folding (added in)
- Extracting common conjuncts from disjunctions (added in)
- Simplify conditionals with constant conditions (added in)

Set the option to `false` or `0` to disable the performance optimizations.

Type: `boolean`

Default: `true` (1)

Added in: Impala 2.8

EXEC_SINGLE_NODE_ROWS_THRESHOLD Query Option (Impala 2.1 or higher only)

This setting controls the cutoff point (in terms of number of rows scanned) below which Impala treats a query as a “small” query, turning off optimizations such as parallel execution and native code generation. The overhead for these optimizations is applicable for queries involving substantial amounts of data, but it makes sense to skip them for queries involving tiny amounts of data. Reducing the overhead for small queries allows Impala to complete them more quickly, keeping admission control slots, CPU, memory, and so on available for resource-intensive queries.

Syntax:

```
SET EXEC_SINGLE_NODE_ROWS_THRESHOLD=number_of_rows
```

Type: `numeric`

Default: `100`

Usage notes: Typically, you increase the default value to make this optimization apply to more queries. If incorrect or corrupted table and column statistics cause Impala to apply this optimization incorrectly to queries that actually involve substantial work, you might see the queries being slower as a result of remote reads. In that case, recompute statistics with the `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement. If there is a problem collecting accurate statistics, you can turn this feature off by setting the value to `-1`.

Internal details:

This setting applies to queries where the number of rows processed can be accurately determined, either through table and column statistics, or by the presence of a `LIMIT` clause. If Impala cannot accurately estimate the number of rows, then this setting does not apply.

In Impala 2.3 and higher, where Impala supports the complex data types `STRUCT`, `ARRAY`, and `MAP`, if a query refers to any column of those types, the small-query optimization is turned off for that query regardless of the `EXEC_SINGLE_NODE_ROWS_THRESHOLD` setting.

For a query that is determined to be “small”, all work is performed on the coordinator node. This might result in some I/O being performed by remote reads. The savings from not distributing the query work and not generating native code are expected to outweigh any overhead from the remote reads.

Added in: Impala 2.10

Examples:

A common use case is to query just a few rows from a table to inspect typical data values. In this example, Impala does not parallelize the query or perform native code generation because the result set is guaranteed to be smaller than the threshold value from this query option:

```
SET EXEC_SINGLE_NODE_ROWS_THRESHOLD=500;
SELECT * FROM enormous_table LIMIT 300;
```

EXEC_TIME_LIMIT_S Query Option (Impala 2.12 or higher only)

The `EXEC_TIME_LIMIT_S` query option sets a time limit on query execution. If a query is still executing when time limit expires, it is automatically canceled. The option is intended to prevent runaway queries that execute for much longer than intended.

For example, an Impala administrator could set a default value of `EXEC_TIME_LIMIT_S=3600` for a resource pool to automatically kill queries that execute for longer than one hour (see [Admission Control and Query Queuing](#) on page 675 for information about default query options). Then, if a user accidentally runs a large query that executes for more than one hour, it will be automatically killed after the time limit expires to free up resources. Users can override the default value per query or per session if they do not want the default `EXEC_TIME_LIMIT_S` value to apply to a specific query or a session.

Note:

The time limit only starts once the query is executing. Time spent planning the query, scheduling the query, or in admission control is not counted towards the execution time limit. `SELECT` statements are eligible for automatic cancellation until the client has fetched all result rows. DML queries are eligible for automatic cancellation until the DML statement has finished.

Syntax:

```
SET EXEC_TIME_LIMIT_S=seconds;
```

Type: numeric

Default: 0 (no time limit)

Added in: Impala 2.12

Related information:

[Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 65

EXPLAIN_LEVEL Query Option

Controls the amount of detail provided in the output of the `EXPLAIN` statement. The basic output can help you identify high-level performance issues such as scanning a higher volume of data or more partitions than you expect. The higher levels of detail show how intermediate results flow between nodes and how different SQL operations such as `ORDER BY`, `GROUP BY`, joins, and `WHERE` clauses are implemented within a distributed query.

Type: STRING or INT

Default: 1

Arguments:

The allowed range of numeric values for this option is 0 to 3:

- 0 or `MINIMAL`: A barebones list, one line per operation. Primarily useful for checking the join order in very long queries where the regular `EXPLAIN` output is too long to read easily.
- 1 or `STANDARD`: The default level of detail, showing the logical way that work is split up for the distributed query.
- 2 or `EXTENDED`: Includes additional detail about how the query planner uses statistics in its decision-making process, to understand how a query could be tuned by gathering statistics, using query hints, adding or removing predicates, and so on. In Impala 3.2 and higher, the output also includes the analyzed query with the cast information in the output header, and the implicit cast info in the Predicate section.
- 3 or `VERBOSE`: The maximum level of detail, showing how work is split up within each node into “query fragments” that are connected in a pipeline. This extra detail is primarily useful for low-level performance testing and tuning within Impala itself, rather than for rewriting the SQL code at the user level.

Note: Prior to Impala 1.3, the allowed argument range for `EXPLAIN_LEVEL` was 0 to 1: level 0 had the mnemonic `NORMAL`, and level 1 was `VERBOSE`. In Impala 1.3 and higher, `NORMAL` is not a valid mnemonic value, and

VERBOSE still applies to the highest level of detail but now corresponds to level 3. You might need to adjust the values if you have any older `impala-shell` script files that set the `EXPLAIN_LEVEL` query option.

Changing the value of this option controls the amount of detail in the output of the `EXPLAIN` statement. The extended information from level 2 or 3 is especially useful during performance tuning, when you need to confirm whether the work for the query is distributed the way you expect, particularly for the most resource-intensive operations such as join queries against large tables, queries against tables with large numbers of partitions, and insert operations for Parquet tables. The extended information also helps to check estimated resource usage when you use the admission control or resource management features explained in [Resource Management](#) on page 675. See [EXPLAIN Statement](#) on page 291 for the syntax of the `EXPLAIN` statement, and [Using the EXPLAIN Plan for Performance Tuning](#) on page 655 for details about how to use the extended information.

Usage notes:

As always, read the `EXPLAIN` output from bottom to top. The lowest lines represent the initial work of the query (scanning data files), the lines in the middle represent calculations done on each node and how intermediate results are transmitted from one node to another, and the topmost lines represent the final results being sent back to the coordinator node.

The numbers in the left column are generated internally during the initial planning phase and do not represent the actual order of operations, so it is not significant if they appear out of order in the `EXPLAIN` output.

At all `EXPLAIN` levels, the plan contains a warning if any tables in the query are missing statistics. Use the `COMPUTE STATS` statement to gather statistics for each table and suppress this warning. See [Table and Column Statistics](#) on page 625 for details about how the statistics help query performance.

The `PROFILE` command in `impala-shell` always starts with an explain plan showing full detail, the same as with `EXPLAIN_LEVEL=3`. After the explain plan comes the executive summary, the same output as produced by the `SUMMARY` command in `impala-shell`.

Examples:

These examples use a trivial, empty table to illustrate how the essential aspects of query planning are shown in `EXPLAIN` output:

```
[localhost:21000] > create table t1 (x int, s string);
[localhost:21000] > set explain_level=1;
[localhost:21000] > explain select count(*) from t1;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=10.00MB VCores=1
| WARNING: The following tables are missing relevant table and/or column
|   statistics.
| explain_plan.t1
|
| 03:AGGREGATE [MERGE FINALIZE]
|   output: sum(count(*))
|
| 02:EXCHANGE [PARTITION=UNPARTITIONED]
|
| 01:AGGREGATE
|   output: count(*)
|
| 00:SCAN HDFS [explain_plan.t1]
|   partitions=1/1 size=0B
+-----+
[localhost:21000] > explain select * from t1;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=-9223372036854775808B VCores=0
| WARNING: The following tables are missing relevant table and/or column
```

```

    statistics.
    explain_plan.t1

01:EXCHANGE [PARTITION=UNPARTITIONED]
|
00:SCAN HDFS [explain_plan.t1]
    partitions=1/1 size=0B
+-----+
[localhost:21000] > set explain_level=2;
[localhost:21000] > explain select * from t1;
+-----+
| Explain String
+-----+
Estimated Per-Host Requirements: Memory=-9223372036854775808B VCoers=0
WARNING: The following tables are missing relevant table and/or column
statistics.
explain_plan.t1

01:EXCHANGE [PARTITION=UNPARTITIONED]
|
|   hosts=0 per-host-mem=unavailable
|   tuple-ids=0 row-size=19B cardinality=unavailable
|
00:SCAN HDFS [explain_plan.t1, PARTITION=RANDOM]
    partitions=1/1 size=0B
    table stats: unavailable
    column stats: unavailable
    hosts=0 per-host-mem=0B
    tuple-ids=0 row-size=19B cardinality=unavailable
+-----+
[localhost:21000] > set explain_level=3;
[localhost:21000] > explain select * from t1;
+-----+
| Explain String
+-----+
Estimated Per-Host Requirements: Memory=-9223372036854775808B VCoers=0
WARNING: The following tables are missing relevant table and/or column
statistics.
explain_plan.t1

F01:PLAN FRAGMENT [PARTITION=UNPARTITIONED]
    01:EXCHANGE [PARTITION=UNPARTITIONED]
        hosts=0 per-host-mem=unavailable
        tuple-ids=0 row-size=19B cardinality=unavailable

F00:PLAN FRAGMENT [PARTITION=RANDOM]
    DATASTREAM SINK [FRAGMENT=F01, EXCHANGE=01, PARTITION=UNPARTITIONED]
    00:SCAN HDFS [explain_plan.t1, PARTITION=RANDOM]
        partitions=1/1 size=0B
        table stats: unavailable
        column stats: unavailable
        hosts=0 per-host-mem=0B
        tuple-ids=0 row-size=19B cardinality=unavailable
+-----+

```

As the warning message demonstrates, most of the information needed for Impala to do efficient query planning, and for you to understand the performance characteristics of the query, requires running the `COMPUTE STATS` statement for the table:

```

[localhost:21000] > compute stats t1;
+-----+
| summary
+-----+
| Updated 1 partition(s) and 2 column(s).
+-----+

```

```

+-----+
[localhost:21000] > explain select * from t1;
+-----+
| Explain String |
+-----+
Estimated Per-Host Requirements: Memory=-9223372036854775808B VCores=0

F01:PLAN FRAGMENT [PARTITION=UNPARTITIONED]
  01:EXCHANGE [PARTITION=UNPARTITIONED]
      hosts=0 per-host-mem=unavailable
      tuple-ids=0 row-size=20B cardinality=0

F00:PLAN FRAGMENT [PARTITION=RANDOM]
  DATASTREAM SINK [FRAGMENT=F01, EXCHANGE=01, PARTITION=UNPARTITIONED]
  00:SCAN HDFS [explain_plan.t1, PARTITION=RANDOM]
      partitions=1/1 size=0B
      table stats: 0 rows total
      column stats: all
      hosts=0 per-host-mem=0B
      tuple-ids=0 row-size=20B cardinality=0
+-----+

```

Joins and other complicated, multi-part queries are the ones where you most commonly need to examine the EXPLAIN output and customize the amount of detail in the output. This example shows the default EXPLAIN output for a three-way join query, then the equivalent output with a [SHUFFLE] hint to change the join mechanism between the first two tables from a broadcast join to a shuffle join.

```

[localhost:21000] > set explain_level=1;
[localhost:21000] > explain select one.*, two.*, three.* from t1 one, t1
two, t1 three where one.x = two.x and two.x = three.x;
+-----+
| Explain String |
+-----+
Estimated Per-Host Requirements: Memory=4.00GB VCores=3

07:EXCHANGE [PARTITION=UNPARTITIONED]
|
04:HASH JOIN [INNER JOIN, BROADCAST]
    hash predicates: two.x = three.x
|
--06:EXCHANGE [BROADCAST]
    |
    02:SCAN HDFS [explain_plan.t1 three]
        partitions=1/1 size=0B
|
03:HASH JOIN [INNER JOIN, BROADCAST]
    hash predicates: one.x = two.x
|
--05:EXCHANGE [BROADCAST]
    |
    01:SCAN HDFS [explain_plan.t1 two]
        partitions=1/1 size=0B
|
    00:SCAN HDFS [explain_plan.t1 one]
        partitions=1/1 size=0B
+-----+
[localhost:21000] > explain select one.*, two.*, three.*
> from t1 one join [shuffle] t1 two join t1 three
> where one.x = two.x and two.x = three.x;
+-----+
| Explain String |
+-----+
Estimated Per-Host Requirements: Memory=4.00GB VCores=3

```



```

08:EXCHANGE [PARTITION=UNPARTITIONED]
|
04:HASH JOIN [INNER JOIN, BROADCAST]
|   hash predicates: two.x = three.x
|
|--07:EXCHANGE [BROADCAST]
|   |
|   02:SCAN HDFS [explain_plan.t1 three]
|       partitions=1/1 size=0B
|
03:HASH JOIN [INNER JOIN, PARTITIONED]
|   hash predicates: one.x = two.x
|
|--06:EXCHANGE [PARTITION=HASH(two.x)]
|   |
|   01:SCAN HDFS [explain_plan.t1 two]
|       partitions=1/1 size=0B
|
05:EXCHANGE [PARTITION=HASH(one.x)]
|
00:SCAN HDFS [explain_plan.t1 one]
|   partitions=1/1 size=0B
+-----+

```

For a join involving many different tables, the default EXPLAIN output might stretch over several pages, and the only details you care about might be the join order and the mechanism (broadcast or shuffle) for joining each pair of tables. In that case, you might set `EXPLAIN_LEVEL` to its lowest value of 0, to focus on just the join order and join mechanism for each stage. The following example shows how the rows from the first and second joined tables are hashed and divided among the nodes of the cluster for further filtering; then the entire contents of the third table are broadcast to all nodes for the final stage of join processing.

```

[localhost:21000] > set explain_level=0;
[localhost:21000] > explain select one.*, two.*, three.*
                    > from t1 one join [shuffle] t1 two join t1 three
                    > where one.x = two.x and two.x = three.x;

```

```

+-----+
| Explain String                                     |
+-----+
| Estimated Per-Host Requirements: Memory=4.00GB VCores=3 |
|
| 08:EXCHANGE [PARTITION=UNPARTITIONED]
| 04:HASH JOIN [INNER JOIN, BROADCAST]
| |--07:EXCHANGE [BROADCAST]
|   | 02:SCAN HDFS [explain_plan.t1 three]
| 03:HASH JOIN [INNER JOIN, PARTITIONED]
| |--06:EXCHANGE [PARTITION=HASH(two.x)]
|   | 01:SCAN HDFS [explain_plan.t1 two]
| 05:EXCHANGE [PARTITION=HASH(one.x)]
| 00:SCAN HDFS [explain_plan.t1 one]
+-----+

```

MAX_NUM_RUNTIME_FILTERS Query Option (Impala 2.5 or higher only)

The `MAX_NUM_RUNTIME_FILTERS` query option sets an upper limit on the number of runtime filters that can be produced for each query.

Type: integer

Default: 10

Added in: Impala 2.5.0

Usage notes:

Each runtime filter imposes some memory overhead on the query. Depending on the setting of the `RUNTIME_BLOOM_FILTER_SIZE` query option, each filter might consume between 1 and 16 megabytes per plan fragment. There are typically 5 or fewer filters per plan fragment.

Impala evaluates the effectiveness of each filter, and keeps the ones that eliminate the largest number of partitions or rows. Therefore, this setting can protect against potential problems due to excessive memory overhead for filter production, while still allowing a high level of optimization for suitable queries.

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Kudu considerations:

This query option affects only Bloom filters, not the min/max filters that are applied to Kudu tables. Therefore, it does not affect the performance of queries against Kudu tables.

Related information:

[Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641,
[RUNTIME_BLOOM_FILTER_SIZE Query Option \(Impala 2.5 or higher only\)](#) on page 387,
[RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389

FETCH_ROWS_TIMEOUT_MS Query Option

Use the `FETCH_ROWS_TIMEOUT_MS` query option to control how long Impala waits for query results when clients fetch rows.

When this query option is set to 0, fetch requests wait indefinitely.

The timeout applies both when query result spooling is enabled and disabled:

- When result spooling is disabled (`SPOOL_QUERY_RESULTS = FALSE`), the timeout controls how long a client waits for a single row batch to be produced by the coordinator.
- When result spooling is enabled (`SPOOL_QUERY_RESULTS = TRUE`), a client can fetch multiple row batches at a time, so this timeout controls the total time a client waits for row batches to be produced.

The timeout also applies to fetch requests issued against queries in the 'RUNNING' state. A 'RUNNING' query has no rows available, so any fetch request will wait until the query transitions to the 'FINISHED' state and for it to fetch all requested rows. A query in the 'FINISHED' state means that the rows are available to be fetched.

Type: INT

Default: 10000 (10 seconds)

Added in: Impala 3.4

Related information: [MAX_RESULT_SPOOLING_MEM Query Option](#) on page 366,
[MAX_SPILLED_RESULT_SPOOLING_MEM Query Option](#) on page 370, [SPOOL_QUERY_RESULTS Query Option](#) on page 392

JOIN_ROWS_PRODUCED_LIMIT Query Option

The `JOIN_ROWS_PRODUCED_LIMIT` query option limits the number of join rows produced by a join node and is used to prevent runaway join queries. A query is canceled when any one of the joins in the query produces more rows (totaled across all instances of that join) than the specified limit set by the `JOIN_ROWS_PRODUCED_LIMIT` option.

This limit is checked periodically, so it is possible that the actual number of rows produced may be slightly higher than the limit.

The default value of 0 specifies that there is no limit on the number of join rows produced.

Type: BIGINT

Allowed values: 0 or positive numbers

Default: 0

Added in: Impala 4.0

HBASE_CACHE_BLOCKS Query Option

Setting this option is equivalent to calling the `setCacheBlocks` method of the class [org.apache.hadoop.hbase.client.Scan](#), in an HBase Java application. Helps to control the memory pressure on the HBase RegionServer, in conjunction with the `HBASE_CACHING` query option.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Related information:

[Using Impala to Query HBase Tables](#) on page 750, [HBASE_CACHING Query Option](#) on page 363

HBASE_CACHING Query Option

Setting this option is equivalent to calling the `setCaching` method of the class [org.apache.hadoop.hbase.client.Scan](#), in an HBase Java application. Helps to control the memory pressure on the HBase RegionServer, in conjunction with the `HBASE_CACHE_BLOCKS` query option.

Type: BOOLEAN

Default: 0

Related information:

[Using Impala to Query HBase Tables](#) on page 750, [HBASE_CACHE_BLOCKS Query Option](#) on page 363

IDLE_SESSION_TIMEOUT Query Option (Impala 2.12 or higher only)

The `IDLE_SESSION_TIMEOUT` query option sets the time in seconds after which an idle session is cancelled. A session is idle when no activity is occurring for any of the queries in that session, and the session has not started any new queries. Once a session is expired, you cannot issue any new query requests to it. The session remains open, but the only operation you can perform is to close it.

The `IDLE_SESSION_TIMEOUT` query option overrides the `##idle_session_timeout` startup option. See [Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 65 for the `##idle_session_timeout` startup option.

The `IDLE_SESSION_TIMEOUT` query option allows JDBC/ODBC connections to set the session timeout as a query option with the `SET` statement.

Syntax:

```
SET IDLE_SESSION_TIMEOUT=seconds;
```

Type: numeric

Default: 0

- If `##idle_session_timeout` is not set, the session never expires.
- If `##idle_session_timeout` is set, use that timeout value.

Added in: Impala 2.12

Related information:

[Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 65

KUDU_READ_MODE Query Option (Impala 3.1 or higher only)

The `KUDU_READ_MODE` query option allows you to set a desired consistency level for scans of Kudu tables.

Type: String

Default: "DEFAULT"

Added in: Impala 3.1

Usage notes:

The following values are supported for the query option:

- "DEFAULT": The value of the startup flag, `##kudu_read_mode`, is used.
- "READ_LATEST": Commonly known as the Read Committed isolation mode, in this mode, Kudu provides no consistency guarantees for this mode, except that all returned rows were committed at some point.
- "READ_AT_SNAPSHOT": Kudu will take a snapshot of the current state of the data and perform the scan over the snapshot, possibly after briefly waiting for ongoing writes to complete. This provides "Read Your Writes" consistency within a single Impala session, except in the case of a Kudu leader change. See the Kudu documentation for more details.

LIVE_PROGRESS Query Option (Impala 2.3 or higher only)

In Impala 3.4.0 and higher when you start the Impala shell in interactive mode, the `LIVE_PROGRESS` query option is set to `TRUE` by default. When you run a query, the live progress bar appears in the output of a query. The bar shows roughly the percentage of completed processing. When the query finishes, the live progress bar disappears from the console output.

Starting in Impala 3.1, the summary output also includes the queuing status consisting of whether the query was queued and what was the latest queuing reason.

Type: Boolean

Default: `TRUE (0)`

Command-line equivalent:

You can turn off `LIVE_PROGRESS` within the shell using the `SET` command. You can also turn off `LIVE_PROGRESS` by starting the shell with the `--disable_live_progress` command-line option.

Usage notes:

The output from this query option is printed to standard error. The output is displayed only in interactive mode, not when the `-q` or `-f` options are used.

For tracking the progress of an interactive query through all phases of processing, see [LIVE_SUMMARY Query Option \(Impala 2.3 or higher only\)](#) on page 365.

Restrictions:

Because the percentage complete figure is calculated using the number of issued and completed “scan ranges”, which occur while reading the table data, the progress bar might reach 100% before the query is entirely finished. For example, the query might do work to perform aggregations after all the table data has been read. If many of your queries fall into this category, consider using the `LIVE_SUMMARY` option for more granular progress reporting.

The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options currently do not produce any output during `COMPUTE STATS` operations.

Because the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options are available only within the `impala-shell` interpreter:

- You cannot change these query options through the SQL `SET` statement using the JDBC or ODBC interfaces. The `SET` command in `impala-shell` recognizes these names as shell-only options.
- Be careful when using `impala-shell` on a pre-Impala 2.3 system to connect to a system running Impala 2.3 or higher. The older `impala-shell` does not recognize these query option names. Upgrade `impala-shell` on the systems where you intend to use these query options.
- Likewise, the `impala-shell` command relies on some information only available in Impala 2.3 and higher to prepare live progress reports and query summaries. The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options have no effect when `impala-shell` connects to a cluster running an older version of Impala.

Added in: Impala 2.3.0

Examples:

```
[localhost:21000] > select count(*) from customer;
+-----+
| count(*) |
+-----+
| 150000    |
+-----+
[localhost:21000] > select count(*) from customer t1 cross join customer t2;
[#####] 50%
[#####]
100%
```

To see how the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options work in real time, see [this animated demo](#).

LIVE_SUMMARY Query Option (Impala 2.3 or higher only)

When the `LIVE_SUMMARY` query option is set to `TRUE`, Impala displays the same output as the `SUMMARY` command for queries submitted through the `impala-shell` command, with the measurements updated in real time as the query progresses. When the query finishes, the final `SUMMARY` output remains visible in the `impala-shell` console output.

Starting in Impala 3.1, the summary output also includes the queuing status consisting of whether the query was queued and what was the latest queuing reason.

Type: Boolean

Default: FALSE (0)

Command-line equivalent:

You can enable this query option within `impala-shell` by starting the shell with the `--live_summary` command-line option. You can still turn this setting off and on again within the shell through the `SET` command.

Usage notes:

The live summary output can be useful for evaluating long-running queries, to evaluate which phase of execution takes up the most time, or if some hosts take much longer than others for certain operations, dragging overall performance down. By making the information available in real time, this feature lets you decide what action to take even before you cancel a query that is taking much longer than normal.

For example, you might see the HDFS scan phase taking a long time, and therefore revisit performance-related aspects of your schema design such as constructing a partitioned table, switching to the Parquet file format, running the `COMPUTE STATS` statement for the table, and so on. Or you might see a wide variation between the average and maximum times for all hosts to perform some phase of the query, and therefore investigate if one particular host needed more memory or was experiencing a network problem.

The output from this query option is printed to standard error. The output is displayed only in interactive mode, not when the `-q` or `-f` options are used.

For a simple and concise way of tracking the progress of an interactive query, see [LIVE_PROGRESS Query Option \(Impala 2.3 or higher only\)](#) on page 364.

Restrictions:

The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options currently do not produce any output during `COMPUTE STATS` operations.

Because the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options are available only within the `impala-shell` interpreter:

- You cannot change these query options through the SQL `SET` statement using the JDBC or ODBC interfaces. The `SET` command in `impala-shell` recognizes these names as shell-only options.

- Be careful when using `impala-shell` on a pre-Impala 2.3 system to connect to a system running Impala 2.3 or higher. The older `impala-shell` does not recognize these query option names. Upgrade `impala-shell` on the systems where you intend to use these query options.
- Likewise, the `impala-shell` command relies on some information only available in Impala 2.3 and higher to prepare live progress reports and query summaries. The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options have no effect when `impala-shell` connects to a cluster running an older version of Impala.

Added in: Impala 2.3.0

To see how the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options work in real time, see [this animated demo](#).

MAX_ERRORS Query Option

Maximum number of non-fatal errors for any particular query that are recorded in the Impala log file. For example, if a billion-row table had a non-fatal data error in every row, you could diagnose the problem without all billion errors being logged. Unspecified or 0 indicates the built-in default value of 1000.

This option only controls how many errors are reported. To specify whether Impala continues or halts when it encounters such errors, use the `ABORT_ON_ERROR` option.

Type: numeric

Default: 0 (meaning 1000 errors)

Related information:

[ABORT_ON_ERROR Query Option](#) on page 346, [Using Impala Logging](#) on page 784

MAX_MEM_ESTIMATE_FOR_ADMISSION Query Option

Use the `MAX_MEM_ESTIMATE_FOR_ADMISSION` query option to set an upper limit on the memory estimates of a query as a workaround for over-estimates precluding a query from being admitted.

The query option takes effect when all of the below conditions are met:

- Memory-based admission control is enabled for the pool.
- The `MEM_LIMIT` query option is not set at the query, session, resource pool, or global level.

When the above conditions are met, `MIN(MAX_MEM_ESTIMATE_FOR_ADMISSION, mem_estimate)` is used for admission control.

Setting the `MEM_LIMIT` query option is usually a better option. Use the `MAX_MEM_ESTIMATE_FOR_ADMISSION` query option when it is not feasible to set `MEM_LIMIT` for each individual query.

Type: integer

Default:

Added in: Impala 3.1

Usage notes:

Related information:

MAX_RESULT_SPOOLING_MEM Query Option

Use the `MAX_RESULT_SPOOLING_MEM` query option to set the maximum amount of memory used when spooling query results.

If the amount of memory exceeds this value when spooling query results, all memory will most likely be spilled to disk.

The `MAX_RESULT_SPOOLING_MEM` query option is applicable only when query result spooling is enabled with the `SPOOL_QUERY_RESULTS` query option set to `TRUE`.

Setting the option to 0 or -1 means the memory is unbounded.

You cannot set this query option to values below -1.

Type: INT

Default: 100 * 1024 * 1024 (100 MB)

Added in: Impala 3.4

Related information: [FETCH_ROWS_TIMEOUT_MS Query Option](#) on page 362, [MAX_SPILLED_RESULT_SPOOLING_MEM Query Option](#) on page 370, [SPOOL_QUERY_RESULTS Query Option](#) on page 392

MAX_ROW_SIZE Query Option

Ensures that Impala can process rows of at least the specified size. (Larger rows might be successfully processed, but that is not guaranteed.) Applies when constructing intermediate or final rows in the result set. This setting prevents out-of-control memory use when accessing columns containing huge strings.

Type: integer

Default:

524288 (512 KB)

Units: A numeric argument represents a size in bytes; you can also use a suffix of `m` or `mb` for megabytes, or `g` or `gb` for gigabytes. If you specify a value with unrecognized formats, subsequent queries fail with an error.

Added in: Impala 2.10.0

Usage notes:

If a query fails because it involves rows with long strings and/or many columns, causing the total row size to exceed `MAX_ROW_SIZE` bytes, increase the `MAX_ROW_SIZE` setting to accommodate the total bytes stored in the largest row. Examine the error messages for any failed queries to see the size of the row that caused the problem.

Impala attempts to handle rows that exceed the `MAX_ROW_SIZE` value where practical, so in many cases, queries succeed despite having rows that are larger than this setting.

Specifying a value that is substantially higher than actually needed can cause Impala to reserve more memory than is necessary to execute the query.

In a Hadoop cluster with highly concurrent workloads and queries that process high volumes of data, traditional SQL tuning advice about minimizing wasted memory is worth remembering. For example, if a table has `STRING` columns where a single value might be multiple megabytes, make sure that the `SELECT` lists in queries only refer to columns that are actually needed in the result set, instead of using the `SELECT *` shorthand.

Examples:

The following examples show the kinds of situations where it is necessary to adjust the `MAX_ROW_SIZE` setting. First, we create a table containing some very long values in `STRING` columns:

```
create table big_strings (s1 string, s2 string, s3 string) stored as
parquet;

-- Turn off compression to more easily reason about data volume by doing
SHOW TABLE STATS.
-- Does not actually affect query success or failure, because MAX_ROW_SIZE
applies when
-- column values are materialized in memory.
set compression_codec=none;
set;
...
  MAX_ROW_SIZE: [524288]
...

-- A very small row.
insert into big_strings values ('one', 'two', 'three');
```

```
-- A row right around the default MAX_ROW_SIZE limit: a 500 KiB string and a
30 KiB string.
insert into big_strings values (repeat('12345',100000), 'short',
repeat('123',10000));
-- A row that is too big if the query has to materialize both S1 and S3.
insert into big_strings values (repeat('12345',100000), 'short',
repeat('12345',100000));
```

With the default MAX_ROW_SIZE setting, different queries succeed or fail based on which column values have to be materialized during query processing:

```
-- All the S1 values can be materialized within the 512 KB MAX_ROW_SIZE
buffer.
select count(distinct s1) from big_strings;
+-----+
| count(distinct s1) |
+-----+
| 2                  |
+-----+

-- A row where even the S1 value is too large to materialize within
MAX_ROW_SIZE.
insert into big_strings values (repeat('12345',1000000), 'short',
repeat('12345',1000000));

-- The 5 MiB string is too large to materialize. The message explains the
size of the result
-- set row the query is attempting to materialize.
select count(distinct(s1)) from big_strings;
WARNINGS: Row of size 4.77 MB could not be materialized in plan node with id
1.
Increase the max_row_size query option (currently 512.00 KB) to process
larger rows.

-- If more columns are involved, the result set row being materialized is
bigger.
select count(distinct s1, s2, s3) from big_strings;
WARNINGS: Row of size 9.54 MB could not be materialized in plan node with id
1.
Increase the max_row_size query option (currently 512.00 KB) to process
larger rows.

-- Column S2, containing only short strings, can still be examined.
select count(distinct(s2)) from big_strings;
+-----+
| count(distinct (s2)) |
+-----+
| 2                  |
+-----+

-- Queries that do not materialize the big column values are OK.
select count(*) from big_strings;
+-----+
| count(*) |
+-----+
| 4        |
+-----+
```


The following examples show how adjusting MAX_ROW_SIZE upward allows queries involving the long string columns to succeed:

```
-- Boosting MAX_ROW_SIZE moderately allows all S1 values to be materialized.
set max_row_size=7mb;

select count(distinct s1) from big_strings;
+-----+
| count(distinct s1) |
+-----+
| 3                  |
+-----+

-- But the combination of S1 + S3 strings is still too large.
select count(distinct s1, s2, s3) from big_strings;
WARNINGS: Row of size 9.54 MB could not be materialized in plan node with id
1. Increase the max_row_size query option (currently 7.00 MB) to process
larger rows.

-- Boosting MAX_ROW_SIZE to larger than the largest row in the table allows
-- all queries to complete successfully.
set max_row_size=12mb;

select count(distinct s1, s2, s3) from big_strings;
+-----+
| count(distinct s1, s2, s3) |
+-----+
| 4                          |
+-----+
```

The following examples show how to reason about appropriate values for MAX_ROW_SIZE, based on the characteristics of the columns containing the long values:

```
-- With a large MAX_ROW_SIZE in place, we can examine the columns to
-- understand the practical lower limit for MAX_ROW_SIZE based on the
-- table structure and column values.
select max(length(s1) + length(s2) + length(s3)) / 1e6 as megabytes from
big_strings;
+-----+
| megabytes |
+-----+
| 10.000005 |
+-----+

-- We can also examine the 'Max Size' for each column after computing stats.
compute stats big_strings;
show column stats big_strings;
+-----+-----+-----+-----+-----+-----+
| Column | Type   | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| s1     | STRING | 2                | -1     | 5000000  | 2500002.5 |
| s2     | STRING | 2                | -1     | 10       | 7.5       |
| s3     | STRING | 2                | -1     | 5000000  | 2500005   |
+-----+-----+-----+-----+-----+-----+
```

Related information:

[BUFFER_POOL_LIMIT Query Option](#) on page 348, [DEFAULT_SPILLABLE_BUFFER_SIZE Query Option](#) on page 352, [MIN_SPILLABLE_BUFFER_SIZE Query Option](#) on page 373, [Scalability Considerations for Impala](#) on page 657

MAX_SCAN_RANGE_LENGTH Query Option

Maximum length of the scan range. Interacts with the number of HDFS blocks in the table to determine how many CPU cores across the cluster are involved with the processing for a query. (Each core processes one scan range.)

Lowering the value can sometimes increase parallelism if you have unused CPU capacity, but a too-small value can limit query performance because each scan range involves extra overhead.

Only applicable to HDFS tables. Has no effect on Parquet tables. Unspecified or 0 indicates backend default, which is the same as the HDFS block size for each table.

Although the scan range can be arbitrarily long, Impala internally uses an 8 MB read buffer so that it can query tables with huge block sizes without allocating equivalent blocks of memory.

Type: numeric

In Impala 2.7 and higher, the argument value can include unit specifiers, such as 100m or 100mb. In previous versions, Impala interpreted such formatted values as 0, leading to query failures.

Default: 0

MAX_SPILLED_RESULT_SPOOLING_MEM Query Option

Use the MAX_SPILLED_RESULT_SPOOLING_MEM query option to set the maximum amount of memory that can be spilled when spooling query results.

If the amount of memory exceeds this value when spooling query results, the coordinator fragment will block until the client has consumed enough rows to free up more memory.

The MAX_SPILLED_RESULT_SPOOLING_MEM query option is applicable only when query result spooling is enabled with the SPOOL_QUERY_RESULTS query option set to TRUE.

The value must be greater than or equal to the value of MAX_RESULT_SPOOLING_MEM.

Setting the option to 0 or -1 means the memory is unbounded.

Values below -1 are not allowed for this query option.

Type: INT

Default: 1024 * 1024 * 1024 (1 GB)

Added in: Impala 3.4

Related information: [FETCH_ROWS_TIMEOUT_MS Query Option](#) on page 362, [MAX_SPILLED_RESULT_SPOOLING_MEM Query Option](#) on page 370, [SPOOL_QUERY_RESULTS Query Option](#) on page 392

MEM_LIMIT Query Option

The MEM_LIMIT query option defines the maximum amount of memory a query can allocate on each node. The total memory that can be used by a query is the MEM_LIMIT times the number of nodes.

There are two levels of memory limit for Impala. The `##mem_limit` startup option sets an overall limit for the `impalad` process (which handles multiple queries concurrently). That process memory limit can be expressed either as a percentage of RAM available to the process such as `##mem_limit=70%` or as a fixed amount of memory, such as 100gb. The memory available to the process is based on the host's physical memory and, since Impala 3.2, memory limits from Linux Control Groups. E.g. if an `impalad` process is running in a Docker container on a host with 100GB of memory, the memory available is 100GB or the Docker container's memory limit, whichever is less.

The MEM_LIMIT query option, which you set through `impala-shell` or the SET statement in a JDBC or ODBC application, applies to each individual query. The MEM_LIMIT query option is usually expressed as a fixed size such as 10gb, and must always be less than the `impalad` memory limit.

If query processing approaches the specified memory limit on any node, either the per-query limit or the impalad limit, then the SQL operations will start to reduce their memory consumption, for example by writing the temporary data to disk (known as spilling to disk). The result is a query that completes successfully, rather than failing with an out-of-memory error. The tradeoff is decreased performance due to the extra disk I/O to write the temporary data and read it back in. The slowdown could potentially be significant. Thus, while this feature improves reliability, you should optimize your queries, system parameters, and hardware configuration to make this spilling a rare occurrence.

Type: numeric

Units: A numeric argument represents memory size in bytes; you can also use a suffix of `m` or `mb` for megabytes, or more commonly `g` or `gb` for gigabytes. If you specify a value with unrecognized formats, subsequent queries fail with an error.

Default: 0 (unlimited)

Usage notes:

The `MEM_LIMIT` setting is primarily useful for production workloads. Impala's Admission Controller can be configured to automatically assign memory limits to queries and limit memory consumption of resource pools. See [Concurrent Queries and Admission Control](#) on page 675 and [Memory Limits and Admission Control](#) on page 677 for more information on configuring the resource usage through admission control.

Use the output of the `SUMMARY` command in `impala-shell` to get a report of memory used for each phase of your most heavyweight queries on each node, and then set a `MEM_LIMIT` somewhat higher than that. See [Using the SUMMARY Report for Performance Tuning](#) on page 655 for usage information about the `SUMMARY` command.

Examples:

The following examples show how to set the `MEM_LIMIT` query option using a fixed number of bytes, or suffixes representing gigabytes or megabytes.

```
[localhost:21000] > set mem_limit=3000000000;
MEM_LIMIT set to 3000000000
[localhost:21000] > select 5;
Query: select 5
+----+
| 5 |
+----+
| 5 |
+----+

[localhost:21000] > set mem_limit=3g;
MEM_LIMIT set to 3g
[localhost:21000] > select 5;
Query: select 5
+----+
| 5 |
+----+
| 5 |
+----+

[localhost:21000] > set mem_limit=3gb;
MEM_LIMIT set to 3gb
[localhost:21000] > select 5;
+----+
| 5 |
+----+
| 5 |
+----+

[localhost:21000] > set mem_limit=3m;
MEM_LIMIT set to 3m
[localhost:21000] > select 5;
```

```

+----+
| 5 |
+----+
| 5 |
+----+
[localhost:21000] > set mem_limit=3mb;
MEM_LIMIT set to 3mb
[localhost:21000] > select 5;
+----+
| 5 |
+----+

```

The following examples show how unrecognized MEM_LIMIT values lead to errors for subsequent queries.

```

[localhost:21000] > set mem_limit=3pb;
MEM_LIMIT set to 3pb
[localhost:21000] > select 5;
ERROR: Failed to parse query memory limit from '3pb'.

[localhost:21000] > set mem_limit=xyz;
MEM_LIMIT set to xyz
[localhost:21000] > select 5;
Query: select 5
ERROR: Failed to parse query memory limit from 'xyz'.

```

The following examples shows the automatic query cancellation when the MEM_LIMIT value is exceeded on any host involved in the Impala query. First it runs a successful query and checks the largest amount of memory used on any node for any stage of the query. Then it sets an artificially low MEM_LIMIT setting so that the same query cannot run.

```

[localhost:21000] > select count(*) from customer;
Query: select count(*) from customer
+-----+
| count(*) |
+-----+
| 150000 |
+-----+

[localhost:21000] > select count(distinct c_name) from customer;
Query: select count(distinct c_name) from customer
+-----+
| count(distinct c_name) |
+-----+
| 150000 |
+-----+

[localhost:21000] > summary;
+-----+-----+-----+-----+-----+-----+
| Operator | #Hosts | #Inst | Avg Time | Max Time | #Rows | Est. |
| #Rows | Peak Mem | Est. Peak Mem | Detail | | | |
+-----+-----+-----+-----+-----+-----+
| 06:AGGREGATE | 1 | 1 | 230.00ms | 230.00ms | 1 | 1 |
| 16.00 KB | -1 B | FINALIZE | | | | |
| 05:EXCHANGE | 1 | 1 | 43.44us | 43.44us | 1 | 1 |
| 0 B | -1 B | UNPARTITIONED | | | | |
| 02:AGGREGATE | 1 | 1 | 227.14ms | 227.14ms | 1 | 1 |
| 12.00 KB | 10.00 MB | | | | | |

```

04:AGGREGATE	1	1		126.27ms	126.27ms	150.00K	150.00K
15.17 MB	10.00 MB						
03:EXCHANGE	1	1		44.07ms	44.07ms	150.00K	150.00K
0 B	0 B			HASH(c_name)			
01:AGGREGATE	1	1		361.94ms	361.94ms	150.00K	150.00K
23.04 MB	10.00 MB						
00:SCAN HDFS	1	1		43.64ms	43.64ms	150.00K	150.00K
24.19 MB	64.00 MB			tpch.customer			
+-----+-----+-----+-----+-----+-----+-----+-----							
+-----+-----+-----+-----+-----+-----+-----+-----							

```
[localhost:21000] > set mem_limit=15mb;
MEM_LIMIT set to 15mb
[localhost:21000] > select count(distinct c_name) from customer;
Query: select count(distinct c_name) from customer
ERROR:
Rejected query from pool default-pool: minimum memory reservation is greater
than memory available to the query
for buffer reservations. Memory reservation needed given the current plan:
38.00 MB. Adjust either the mem_limit
or the pool config (max-query-mem-limit, min-query-mem-limit) for the query
to allow the query memory limit to be
at least 70.00 MB. Note that changing the mem_limit may also change the
plan. See the query profile for more
information about the per-node memory requirements.
```

MEM_LIMIT_EXECUTORS Query Option

Note: This is an advanced query option. Setting this query option is not recommended unless specifically advised.

The existing MEM_LIMIT query option applies to all impala coordinators and executors. This means that the same amount of memory gets reserved but coordinators typically just do the job of coordinating the query and thus do not necessarily need all the estimated memory. Blocking the estimated memory on coordinators blocks the memory to be used for other queries.

The new MEM_LIMIT_EXECUTORS query option functions similarly to the MEM_LIMIT option but sets the query memory limit only on executors. This new option addresses the issue related to MEM_LIMIT and is recommended in scenarios where the query needs much higher memory on executors compared with coordinators.

Note that the MEM_LIMIT_EXECUTORS option does not work with MEM_LIMIT. If you set both, only MEM_LIMIT applies.

MEM_LIMIT_COORDINATORS Query Option

Note: This is an advanced query option. Setting this query option is not recommended unless specifically advised.

The existing MEM_LIMIT query option applies to all impala coordinators and executors. This means that the same amount of memory gets reserved but coordinators typically just do the job of coordinating the query and thus do not necessarily need all the estimated memory. Blocking the estimated memory on coordinators blocks the memory to be used for other queries.

The new MEM_LIMIT_COORDINATORS query option functions similarly to the MEM_LIMIT option but sets the query memory limit only on coordinators. This new option addresses the issue related to MEM_LIMIT and is recommended in scenarios where the query needs higher or lower memory on coordinators compared to the planner estimates.

Note that the MEM_LIMIT_COORDINATORS option does not work with MEM_LIMIT. If you set both, only MEM_LIMIT applies.

MIN_SPILLABLE_BUFFER_SIZE Query Option

Specifies the minimum size for a memory buffer used when the spill-to-disk mechanism is activated, for example for queries against a large table with no statistics, or large join operations.

Type: integer

Default:

65536 (64 KB)

Units: A numeric argument represents a size in bytes; you can also use a suffix of `m` or `mb` for megabytes, or `g` or `gb` for gigabytes. If you specify a value with unrecognized formats, subsequent queries fail with an error.

Added in: Impala 2.10.0

Usage notes:

This query option sets a lower bound on the size of the internal buffer size that can be used during spill-to-disk operations. The actual size of the buffer is chosen by the query planner.

If overall query performance is limited by the time needed for spilling, consider increasing the `MIN_SPILLABLE_BUFFER_SIZE` setting. Larger buffer sizes result in Impala issuing larger I/O requests to storage devices, which might result in higher throughput, particularly on rotational disks.

The tradeoff with a large value for this setting is increased memory usage during spill-to-disk operations. Reducing this value may reduce memory consumption.

To determine if the value for this setting is having an effect by capping the spillable buffer size, you can see the buffer size chosen by the query planner for a particular query. `EXPLAIN` the query while the setting `EXPLAIN_LEVEL=2` is in effect.

Examples:

```
set min_spillable_buffer_size=128KB;
```

Related information:

[BUFFER_POOL_LIMIT Query Option](#) on page 348, [DEFAULT_SPILLABLE_BUFFER_SIZE Query Option](#) on page 352, [MAX_ROW_SIZE Query Option](#) on page 367, [Scalability Considerations for Impala](#) on page 657

MT_DOP Query Option

Sets the degree of intra-node parallelism used for certain operations that can benefit from multithreaded execution. You can specify values higher than zero to find the ideal balance of response time, memory usage, and CPU usage during statement processing.

Note:

The Impala execution engine is being revamped incrementally to add additional parallelism within a single host for certain statements and kinds of operations. The setting `MT_DOP=0` uses the “old” code path with limited intra-node parallelism.

Currently, `MT_DOP` support varies by statement type:

- `COMPUTE [INCREMENTAL] STATS`. Impala automatically sets `MT_DOP=4` for `COMPUTE STATS` and `COMPUTE INCREMENTAL STATS` statements on Parquet tables.
- `SELECT` statements. `MT_DOP` is 0 by default for `SELECT` statements but can be set to a value greater than 0 to control intra-node parallelism. This may be useful to tune query performance and in particular to reduce execution time of long-running, CPU-intensive queries.
- DML statements. `MT_DOP` values greater than zero are not currently supported for DML statements. DML statements will produce an error if `MT_DOP` is set to a non-zero value.
- In Impala 3.4 and earlier, not all `SELECT` statements support setting `MT_DOP`. Specifically, only scan and aggregation operators, and local joins that do not need data exchanges (such as for nested types) are supported. Other `SELECT` statements produce an error if `MT_DOP` is set to a non-zero value.

Type: integer

Default: 0

Because `COMPUTE STATS` and `COMPUTE INCREMENTAL STATS` statements for Parquet tables benefit substantially from extra intra-node parallelism, Impala automatically sets `MT_DOP=4` when computing stats for Parquet tables.

Range: 0 to 64

Examples:

Note:

Any timing figures in the following examples are on a small, lightly loaded development cluster. Your mileage may vary. Speedups depend on many factors, including the number of rows, columns, and partitions within each table.

The following example shows how to run a `COMPUTE STATS` statement against a Parquet table with or without an explicit `MT_DOP` setting:

```
-- Explicitly setting MT_DOP to 0 selects the old code path.
set mt_dop = 0;
MT_DOP set to 0

-- The analysis for the billion rows is distributed among hosts,
-- but uses only a single core on each host.
compute stats billion_rows_parquet;
+-----+
| summary                                     |
+-----+
| Updated 1 partition(s) and 2 column(s). |
+-----+

drop stats billion_rows_parquet;

-- Using 4 logical processors per host is faster.
set mt_dop = 4;
MT_DOP set to 4

compute stats billion_rows_parquet;
+-----+
| summary                                     |
+-----+
| Updated 1 partition(s) and 2 column(s). |
+-----+

drop stats billion_rows_parquet;

-- Unsetting the option reverts back to its default.
-- Which for COMPUTE STATS and a Parquet table is 4,
-- so again it uses the fast path.
unset MT_DOP;
Unsetting option MT_DOP

compute stats billion_rows_parquet;
+-----+
| summary                                     |
+-----+
| Updated 1 partition(s) and 2 column(s). |
+-----+
```

The following example shows the effects of setting `MT_DOP` for a query on a Parquet table:

```
set mt_dop = 0;
MT_DOP set to 0
```

```
-- COUNT(DISTINCT) for a unique column is CPU-intensive.
select count(distinct id) from billion_rows_parquet;
+-----+
| count(distinct id) |
+-----+
| 1000000000         |
+-----+
Fetched 1 row(s) in 67.20s

set mt_dop = 16;
MT_DOP set to 16

-- Introducing more intra-node parallelism for the aggregation
-- speeds things up, and potentially reduces memory overhead by
-- reducing the number of scanner threads.
select count(distinct id) from billion_rows_parquet;
+-----+
| count(distinct id) |
+-----+
| 1000000000         |
+-----+
Fetched 1 row(s) in 17.19s
```

The following example shows how queries that are not compatible with non-zero MT_DOP settings produce an error when MT_DOP is set:

```
set mt_dop=1;
MT_DOP set to 1

insert into a1
select * from a2;
ERROR: NotImplementedException: MT_DOP not supported for DML statements.
```

Related information:

[COMPUTE STATS Statement](#) on page 232, [Impala Aggregate Functions](#) on page 539

NUM_NODES Query Option

Limit the number of nodes that process a query, typically during debugging.

Type: numeric

Allowed values: Only accepts the values 0 (meaning all nodes) or 1 (meaning all work is done on the coordinator node).

Default: 0

Usage notes:

Setting NUM_NODES to 1 disables multithreading, i.e. if MT_DOP is greater than 1, it is effectively reduced to 1.

If you are diagnosing a problem that you suspect is due to a timing issue due to distributed query processing, you can set NUM_NODES=1 to verify if the problem still occurs when all the work is done on a single node.

You might set the NUM_NODES option to 1 briefly, during INSERT or CREATE TABLE AS SELECT statements. Normally, those statements produce one or more data files per data node. If the write operation involves small amounts of data, a Parquet table, and/or a partitioned table, the default behavior could produce many small files when intuitively you might expect only a single output file. SET NUM_NODES=1 turns off the “distributed” aspect of the write operation, making it more likely to produce only one or a few data files.

**Warning:**

Because this option results in increased resource utilization on a single host, it could cause problems due to contention with other Impala statements or high resource usage. Symptoms could include queries running slowly, exceeding the memory limit, or appearing to hang. Use it only in a single-user development/test environment; **do not** use it in a production environment or in a cluster with a high-concurrency or high-volume or performance-critical workload.

NUM_ROWS_PRODUCED_LIMIT Query Option

The `NUM_ROWS_PRODUCED_LIMIT` query option limits the number of rows produced by a query. A query is canceled when its execution produces more rows than the specified limit set by the `NUM_ROWS_PRODUCED_LIMIT` option.

This limit only applies when the results are returned to a client, for example, to a `SELECT` query, but not to an `INSERT` query.

The default value of 0 specifies that there is no limit on the number of rows produced.

Type: `INT`

Allowed values: 0 or positive numbers

Default: 0

NUM_SCANNER_THREADS Query Option

Maximum number of scanner threads (on each node) used for each query. By default, Impala uses as many cores as are available (one thread per core). You might lower this value if queries are using excessive resources on a busy cluster. Impala imposes a maximum value automatically, so a high value has no practical effect.

Has no effect if multi-threaded query execution is enabled, i.e. `MT_DOP` is greater than 0.

Type: numeric

Default: 0

OPTIMIZE_PARTITION_KEY_SCANS Query Option (Impala 2.5 or higher only)

Enables a fast code path for queries that apply simple aggregate functions to partition key columns: `MIN(key_column)`, `MAX(key_column)`, or `COUNT(DISTINCT key_column)`.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Note: In Impala 2.5.0, only the value 1 enables the option, and the value `true` is not recognized. This limitation is tracked by the issue [IMPALA-3334](#), which shows the releases where the problem is fixed.

Added in: Impala 2.5.0

Usage notes:

This optimization speeds up common “introspection” operations over partition key columns, for example determining the distinct values of partition keys.

This optimization does not apply to `SELECT` statements that reference columns that are not partition keys. It also only applies when all the partition key columns in the `SELECT` statement are referenced in one of the following contexts:

- Within a `MAX()` or `MAX()` aggregate function or as the argument of any aggregate function with the `DISTINCT` keyword applied.
- Within a `WHERE`, `GROUP BY` or `HAVING` clause.

This optimization is enabled by a query option because it skips some consistency checks and therefore can return slightly different partition values if partitions are in the process of being added, dropped, or loaded outside of Impala. Queries might exhibit different behavior depending on the setting of this option in the following cases:

- If files are removed from a partition using HDFS or other non-Impala operations, there is a period until the next REFRESH of the table where regular queries fail at run time because they detect the missing files. With this optimization enabled, queries that evaluate only the partition key column values (not the contents of the partition itself) succeed, and treat the partition as if it still exists.
- If a partition contains any data files, but the data files do not contain any rows, a regular query considers that the partition does not exist. With this optimization enabled, the partition is treated as if it exists.

If the partition includes no files at all, this optimization does not change the query behavior: the partition is considered to not exist whether or not this optimization is enabled.

Examples:

The following example shows initial schema setup and the default behavior of queries that return just the partition key column for a table:

```
-- Make a partitioned table with 3 partitions.
create table t1 (s string) partitioned by (year int);
insert into t1 partition (year=2015) values ('last year');
insert into t1 partition (year=2016) values ('this year');
insert into t1 partition (year=2017) values ('next year');

-- Regardless of the option setting, this query must read the
-- data files to know how many rows to return for each year value.
explain select year from t1;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=0B VCores=0 |
| F00:PLAN FRAGMENT [UNPARTITIONED] |
|   00:SCAN HDFS [key_cols.t1] |
|     partitions=3/3 files=4 size=40B |
|     table stats: 3 rows total |
|     column stats: all |
|     hosts=3 per-host-mem=unavailable |
|     tuple-ids=0 row-size=4B cardinality=3 |
+-----+

-- The aggregation operation means the query does not need to read
-- the data within each partition: the result set contains exactly 1 row
-- per partition, derived from the partition key column value.
-- By default, Impala still includes a 'scan' operation in the query.
explain select distinct year from t1;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=0B VCores=0 |
| | |
| 01:AGGREGATE [FINALIZE] |
| | group by: year |
| | |
| 00:SCAN HDFS [key_cols.t1] |
+-----+
```

```
| partitions=0/0 files=0 size=0B
|
+-----+
+
```

The following examples show how the plan is made more efficient when the OPTIMIZE_PARTITION_KEY_SCANS option is enabled:

```
set optimize_partition_key_scans=1;
OPTIMIZE_PARTITION_KEY_SCANS set to 1

-- The aggregation operation is turned into a UNION internally,
-- with constant values known in advance based on the metadata
-- for the partitioned table.
explain select distinct year from t1;
+-----+
| Explain String                                     |
+-----+
| Estimated Per-Host Requirements: Memory=0B VCores=0 |
| F00:PLAN FRAGMENT [UNPARTITIONED]                 |
|   01:AGGREGATE [FINALIZE]                           |
|     | group by: year                                |
|     | hosts=1 per-host-mem=unavailable                |
|     | tuple-ids=1 row-size=4B cardinality=3           |
|   00:UNION                                           |
|     | constant-operands=3                            |
|     | hosts=1 per-host-mem=unavailable                |
|     | tuple-ids=0 row-size=4B cardinality=3           |
+-----+

-- The same optimization applies to other aggregation queries
-- that only return values based on partition key columns:
-- MIN, MAX, COUNT(DISTINCT), and so on.
explain select min(year) from t1;
+-----+
| Explain String                                     |
+-----+
| Estimated Per-Host Requirements: Memory=0B VCores=0 |
| F00:PLAN FRAGMENT [UNPARTITIONED]                 |
|   01:AGGREGATE [FINALIZE]                           |
|     | output: min(year)                             |
|     | hosts=1 per-host-mem=unavailable                |
|     | tuple-ids=1 row-size=4B cardinality=1           |
|   00:UNION                                           |
|     | constant-operands=3                            |
|     | hosts=1 per-host-mem=unavailable                |
|     | tuple-ids=0 row-size=4B cardinality=3           |
+-----+
```

PARQUET_COMPRESSION_CODEC Query Option

Deprecated. Use COMPRESSION_CODEC in Impala 2.0 and later. See [COMPRESSION_CODEC Query Option \(Impala 2.0 or higher only\)](#) on page 348 for details.

PARQUET_ANNOTATE_STRINGS_UTF8 Query Option (Impala 2.6 or higher only)

Causes Impala INSERT and CREATE TABLE AS SELECT statements to write Parquet files that use the UTF-8 annotation for STRING columns.

Usage notes:

By default, Impala represents a `STRING` column in Parquet as an unannotated binary field.

Impala always uses the UTF-8 annotation when writing `CHAR` and `VARCHAR` columns to Parquet files. An alternative to using the query option is to cast `STRING` values to `VARCHAR`.

This option is to help make Impala-written data more interoperable with other data processing engines. Impala itself currently does not support all operations on UTF-8 data. Although data processed by Impala is typically represented in ASCII, it is valid to designate the data as UTF-8 when storing on disk, because ASCII is a subset of UTF-8.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Added in: Impala 2.6.0

Related information:

[Using the Parquet File Format with Impala Tables](#) on page 705

PARQUET_ARRAY_RESOLUTION Query Option (Impala 2.9 or higher only)

The `PARQUET_ARRAY_RESOLUTION` query option controls the behavior of the indexed-based resolution for nested arrays in Parquet.

In Parquet, you can represent an array using a 2-level or 3-level representation. The modern, standard representation is 3-level. The legacy 2-level scheme is supported for compatibility with older Parquet files. However, there is no reliable metadata within Parquet files to indicate which encoding was used. It is even possible to have mixed encodings within the same file if there are multiple arrays. The `PARQUET_ARRAY_RESOLUTION` option controls the process of resolution that is to match every column/field reference from a query to a column in the Parquet file.

The supported values for the query option are:

- `THREE_LEVEL`: Assumes arrays are encoded with the 3-level representation, and does not attempt the 2-level resolution.
- `TWO_LEVEL`: Assumes arrays are encoded with the 2-level representation, and does not attempt the 3-level resolution.
- `TWO_LEVEL_THEN_THREE_LEVEL`: First tries to resolve assuming a 2-level representation, and if unsuccessful, tries a 3-level representation.

All of the above options resolve arrays encoded with a single level.

A failure to resolve a column/field reference in a query with a given array resolution policy does not necessarily result in a warning or error returned by the query. A mismatch might be treated like a missing column (returns `NULL` values), and it is not possible to reliably distinguish the 'bad resolution' and 'legitimately missing column' cases.

The name-based policy generally does not have the problem of ambiguous array representations. You specify to use the name-based policy by setting the `PARQUET_FALLBACK_SCHEMA_RESOLUTION` query option to `NAME`.

Type: Enum of `TWO_LEVEL`, `TWO_LEVEL_THEN_THREE_LEVEL`, and `THREE_LEVEL`

Default: `THREE_LEVEL`

Added in: Impala 2.9.0

Examples:

EXAMPLE A: The following Parquet schema of a file can be interpreted as a 2-level or 3-level:

```
ParquetSchemaExampleA {
  optional group single_element_groups (LIST) {
    repeated group single_element_group {
      required int64 count;
    }
  }
}
```

```
}
```

The following table schema corresponds to a 2-level interpretation:

```
CREATE TABLE t (coll array<struct<f1: bigint>>) STORED AS PARQUET;
```

Successful query with a 2-level interpretation:

```
SET PARQUET_ARRAY_RESOLUTION=TWO_LEVEL;
SELECT ITEM.f1 FROM t.coll;
```

The following table schema corresponds to a 3-level interpretation:

```
CREATE TABLE t (coll array<bigint>) STORED AS PARQUET;
```

Successful query with a 3-level interpretation:

```
SET PARQUET_ARRAY_RESOLUTION=THREE_LEVEL;
SELECT ITEM FROM t.coll
```

EXAMPLE B: The following Parquet schema of a file can be only be successfully interpreted as a 2-level:

```
ParquetSchemaExampleB {
  required group list_of_ints (LIST) {
    repeated int32 list_of_ints_tuple;
  }
}
```

The following table schema corresponds to a 2-level interpretation:

```
CREATE TABLE t (coll array<int>) STORED AS PARQUET;
```

Successful query with a 2-level interpretation:

```
SET PARQUET_ARRAY_RESOLUTION=TWO_LEVEL;
SELECT ITEM FROM t.coll
```

Unsuccessful query with a 3-level interpretation. The query returns NULLs as if the column was missing in the file:

```
SET PARQUET_ARRAY_RESOLUTION=THREE_LEVEL;
SELECT ITEM FROM t.coll
```

PARQUET_DICTIONARY_FILTERING Query Option (Impala 2.9 or higher only)

The `PARQUET_DICTIONARY_FILTERING` query option controls whether Impala uses dictionary filtering for Parquet files.

To efficiently process a highly selective scan query, when this option is enabled, Impala checks the values in the Parquet dictionary page and determines if the whole row group can be thrown out.

A column chunk is purely dictionary encoded and can be used by dictionary filtering if any of the following conditions are met:

1. If the `encoding_stats` is in the Parquet file, dictionary filtering uses it to determine if there are only dictionary encoded pages (i.e. there are no data pages with an encoding other than `RLE_DICTIONARY` or `PLAIN_DICTIONARY`).
2. If the encoding stats are not present, dictionary filtering looks at the encodings. The column is purely dictionary encoded if both of the conditions satisfy:
 - `PLAIN_DICTIONARY` or `RLE_DICTIONARY` is present.
 - Only `PLAIN_DICTIONARY`, `RLE_DICTIONARY`, `RLE`, or `BIT_PACKED` encodings are listed.
3. Dictionary filtering works for the Parquet dictionaries with less than 40000 values if the file was written by or lower.

In the query runtime profile output for each Impalad instance, the `NumDictFilteredRowGroups` field in the SCAN node section shows the number of row groups that were skipped based on dictionary filtering.

Note that row groups can be filtered out by Parquet statistics, and in such cases, dictionary filtering will not be considered.

The supported values for the query option are:

- `true` (1): Use dictionary filtering.
- `false` (0): Do not use dictionary filtering
- Any other values are treated as `false`.

Type: Boolean

Default: `true` (1)

Added in: Impala 2.9.0

PARQUET_FALLBACK_SCHEMA_RESOLUTION Query Option (Impala 2.6 or higher only)

The `PARQUET_FALLBACK_SCHEMA_RESOLUTION` query option allows Impala to look up columns within Parquet files by column name, rather than column order, when necessary. The allowed values are:

- `POSITION` (0)
- `NAME` (1)

Usage notes:

By default, Impala looks up columns within a Parquet file based on the order of columns in the table.

The name setting for this option enables behavior for Impala queries similar to the Hive setting `parquet.column.index.access=false`. It also allows Impala to query Parquet files created by Hive with the `parquet.column.index.access=false` setting in effect.

Type: integer or string

Added in: Impala 2.6.0

Related information:

[Schema Evolution for Parquet Tables](#) on page 716

PARQUET_FILE_SIZE Query Option

Specifies the maximum size of each Parquet data file produced by Impala `INSERT` statements.

Syntax:

Specify the size in bytes, or with a trailing `m` or `g` character to indicate megabytes or gigabytes. For example:

```
-- 128 megabytes.
set PARQUET_FILE_SIZE=134217728
INSERT OVERWRITE parquet_table SELECT * FROM text_table;

-- 512 megabytes.
set PARQUET_FILE_SIZE=512m;
```

```
INSERT OVERWRITE parquet_table SELECT * FROM text_table;

-- 1 gigabyte.
set PARQUET_FILE_SIZE=1g;
INSERT OVERWRITE parquet_table SELECT * FROM text_table;
```

Usage notes:

With tables that are small or finely partitioned, the default Parquet block size (formerly 1 GB, now 256 MB in Impala 2.0 and later) could be much larger than needed for each data file. For INSERT operations into such tables, you can increase parallelism by specifying a smaller PARQUET_FILE_SIZE value, resulting in more HDFS blocks that can be processed by different nodes.

Type: numeric, with optional unit specifier

Important:

Currently, the maximum value for this setting is 1 gigabyte (1g). Setting a value higher than 1 gigabyte could result in errors during an INSERT operation.

Default: 0 (produces files with a target size of 256 MB; files might be larger for very wide tables)

Because ADLS does not expose the block sizes of data files the way HDFS does, any Impala INSERT or CREATE TABLE AS SELECT statements use the PARQUET_FILE_SIZE query option setting to define the size of Parquet data files. (Using a large block size is more important for Parquet tables than for tables that use other file formats.)

Isilon considerations:

Because the EMC Isilon storage devices use a global value for the block size rather than a configurable value for each file, the PARQUET_FILE_SIZE query option has no effect when Impala inserts data into a table or partition residing on Isilon storage. Use the `isi` command to set the default block size globally on the Isilon device. For example, to set the Isilon default block size to 256 MB, the recommended size for Parquet data files for Impala, issue the following command:

```
isi hdfs settings modify --default-block-size=256MB
```

Ozone considerations:

Because Apache Ozone storage buckets use a global value for the block size rather than a configurable value for each file, the PARQUET_FILE_SIZE query option has no effect when Impala inserts data into a table or partition residing on Ozone storage.

Related information:

For information about the Parquet file format, and how the number and size of data files affects query performance, see [Using the Parquet File Format with Impala Tables](#) on page 705.

PARQUET_OBJECT_STORE_SPLIT_SIZE Query Option

Use the PARQUET_OBJECT_STORE_SPLIT_SIZE query option to control the Parquet format specific split sizes on non-block based stores, e.g. S3, ADLS, etc.

The value must be greater than or equal to 1 MB.

Type: INT

Default: 256 MB

Added in: Impala 3.4

PARQUET_PAGE_ROW_COUNT_LIMIT Query Option

Use the PARQUET_PAGE_ROW_COUNT_LIMIT query option to set the maximum number of rows that can be written on a single Parquet data page. By default there is no row count limit.

Type: INT

Allowed values: Positive integers

Added in: Impala 3.3

PARQUET_READ_STATISTICS Query Option (Impala 2.9 or higher only)

The `PARQUET_READ_STATISTICS` query option controls whether to read statistics from Parquet files and use them during query processing.

Parquet stores min/max stats which can be used to skip reading row groups if they don't qualify a certain predicate. When this query option is set to `true`, Impala reads the Parquet statistics and skips reading row groups that do not match the conditions in the `WHERE` clause.

Impala supports filtering based on Parquet statistics:

- Of the numerical types for the old version of the statistics: Boolean, Integer, Float
- Of the types for the new version of the statistics (starting in IMPALA 2.8): Boolean, Integer, Float, Decimal, String, Timestamp
- For simple predicates of the forms: `<slot> <op> <constant>` or `<constant> <op> <slot>`, where `<op>` is LT, LE, GE, GT, and EQ

The `PARQUET_READ_STATISTICS` option provides a workaround when dealing with files that have corrupt Parquet statistics and unknown errors.

In the query runtime profile output for each Impalad instance, the `NumStatsFilteredRowGroups` field in the `SCAN` node section shows the number of row groups that were skipped based on Parquet statistics.

The supported values for the query option are:

- `true` (1): Read statistics from Parquet files and use them in query processing.
- `false` (0): Do not use Parquet read statistics.
- Any other values are treated as `false`.

Type: Boolean

Default: `true`

Added in: Impala 2.9.0

PARQUET_READ_PAGE_INDEX Query Option

Use the `PARQUET_READ_PAGE_INDEX` query option to disable or enable using the Parquet page index during scans. The page index contains min/max statistics at the page-level granularity. It can be used to skip pages and rows that do not match the conditions in the `WHERE` clause.

This option enables the same optimization as the `PARQUET_READ_STATISTICS` at the finer grained page level.

Impala supports filtering based on Parquet statistics:

- Of the types: Boolean, Integer, Decimal, String, Timestamp
- For simple predicates of the forms: `<slot> <op> <constant>` or `<constant> <op> <slot>`, where `<op>` is LT, LE, GE, GT, and EQ

The supported values for the query option are:

- `true` (1): Read the page-level statistics from the Parquet page index during query processing and filter out pages based on the statistics.
- `false` (0): Do not use the Parquet page index.
- Any other values are treated as `false`.

Type: Boolean

Default: `TRUE`

PARQUET_WRITE_PAGE_INDEX Query Option

The `PARQUET_WRITE_PAGE_INDEX` query option to disable or enable the Parquet page index writing.

Impala writes page-level statistics into the Parquet page index of the types: Boolean, Integer, Decimal, String, Timestamp

The supported values for the query option are:

- `true` (1): Write the Parquet page index when creating Parquet files.
- `false` (0): Do not write the Parquet page index when creating Parquet files.
- Any other values are treated as `false`.

Type: Boolean

Default: `TRUE`

Added in: Impala 3.3

PREFETCH_MODE Query Option (Impala 2.6 or higher only)

Determines whether the prefetching optimization is applied during join query processing.

Type: numeric (0, 1) or corresponding mnemonic strings (`NONE`, `HT_BUCKET`).

Default: 1 (equivalent to `HT_BUCKET`)

Added in: Impala 2.6.0

Usage notes:

The default mode is 1, which means that hash table buckets are prefetched during join query processing.

Related information:

[Joins in Impala SELECT Statements](#) on page 318, [Performance Considerations for Join Queries](#) on page 618.

QUERY_TIMEOUT_S Query Option (Impala 2.0 or higher only)

Sets the idle query timeout value for the session, in seconds. Queries that sit idle for longer than the timeout value are automatically cancelled. If the system administrator specified the `--idle_query_timeout` startup option, `QUERY_TIMEOUT_S` must be smaller than or equal to the `--idle_query_timeout` value.

Note:

The timeout clock for queries and sessions only starts ticking when the query or session is idle.

For queries, this means the query has results ready but is waiting for a client to fetch the data. A query can run for an arbitrary time without triggering a timeout, because the query is computing results rather than sitting idle waiting for the results to be fetched. The timeout period is intended to prevent unclosed queries from consuming resources and taking up slots in the admission count of running queries, potentially preventing other queries from starting.

For sessions, this means that no query has been submitted for some period of time.

Syntax:

```
SET QUERY_TIMEOUT_S=seconds;
```

Type: numeric

Default: 0 (no timeout if `--idle_query_timeout` not in effect; otherwise, use `--idle_query_timeout` value)

Added in: Impala 2.0.0

Related information:

[Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 65

REFRESH_UPDATED_HMS_PARTITIONS Query Option

As the name implies the query option `REFRESH_UPDATED_HMS_PARTITIONS` is used to refresh any updated HMS partitions.

This option is disabled by default so that the performance is not compromised when refreshing a table. However, for certain corner case scenarios refresh table command does not detect changed partitions. In case of the default refresh, catalogd detects, adds any new partitions and removes any partitions which are not present in HMS anymore. However, it does not update any partitions that changed (eg. change of location). When this query option is enabled, the refresh table command will detect certain changes to the partitions and update them accordingly. Currently, catalogd will update the partitions if any of the following StorageDescriptor properties have been modified. 1. Partition Location 2. Partition Fileformat. 3 SerdeInfo. 4. Partition schema changes. 5. Partition bucketInfo.

Type: BOOLEAN; recognized values are 1 and 0, or true and false; any other value will be interpreted as false.

Default: FALSE (shown as 0 in output of SET statement).

Added in: Impala 4.0

REPLICA_PREFERENCE Query Option (Impala 2.7 or higher only)

The `REPLICA_PREFERENCE` query option lets you distribute the work more evenly if hotspots and bottlenecks persist. It causes the access cost of all replicas of a data block to be considered equal to or worse than the configured value. This allows Impala to schedule reads to suboptimal replicas (e.g. local in the presence of cached ones) in order to distribute the work across more executor nodes.

Allowed values are: `CACHE_LOCAL` (0), `DISK_LOCAL` (2), `REMOTE` (4)

Type: Enum

Default: `CACHE_LOCAL` (0)

Added in: Impala 2.7.0

Usage Notes:

By default Impala selects the best replica it can find in terms of access cost. The preferred order is cached, local, and remote. With `REPLICA_PREFERENCE`, the preference of all replicas are capped at the selected value. For example, when `REPLICA_PREFERENCE` is set to `DISK_LOCAL`, cached and local replicas are treated with the equal preference. When set to `REMOTE`, all three types of replicas, cached, local, remote, are treated with equal preference.

Related information:

[Using HDFS Caching with Impala \(Impala 2.1 or higher only\)](#) on page 646, [SCHEDULE_RANDOM_REPLICA Query Option \(Impala 2.5 or higher only\)](#) on page 391

REQUEST_POOL Query Option

The pool or queue name that queries should be submitted to. Only applies when you enable the Impala admission control feature. Specifies the name of the pool used by requests from Impala to the resource manager.

Type: STRING

Default: empty (use the user-to-pool mapping defined by an `impalad` startup option in the Impala configuration file)

Related information:

[Admission Control and Query Queuing](#) on page 675

RESOURCE_TRACE_RATIO Query Option (Impala 3.2 or higher only)

The `RESOURCE_TRACE_RATIO` query option specifies the ratio of queries where the CPU usage info will be included in the profiles. Collecting CPU usage and sending it around adds a slight overhead during query execution. This query option lets you control whether to collect additional information to diagnose the resource usage.

For example, setting `RESOURCE_TRACE_RATIO=1` adds a trace of the CPU usage to the profile of each query.

Setting `RESOURCE_TRACE_RATIO=0.5` means that randomly selected half of all queries will have that information collected by the coordinator and included in the profiles.

Setting `RESOURCE_TRACE_RATIO=0` means that CPU usage will not be tracked and included in the profiles.

Values from 0 to 1 are allowed.

Type: Number

Default: 0

Added in: Impala 3.2

RETRY_FAILED_QUERIES Query Option

Use the `RETRY_FAILED_QUERIES` query option to control whether or not queries are transparently retried on cluster membership changes.

Cluster membership changes typically occur when an impalad crashes, or if the node is blacklisted by the Impala Coordinator. If a `SELECT` query fails due to a cluster membership change, the Coordinator will cancel and unregister the running query and then launch a retry of the query. For example, if one of the executor nodes fails during query execution, the query fails but is transparently re-executed, either with the executor node immediately replaced, or with a temporarily reduced number of executor nodes. This feature supports retrying the entire query and NOT the individual query fragments. `INSERT` and `DDL` queries will NOT be retried.

Note that query retry will be skipped if the query has returned any results to the client. To avoid this, enable `Result Spooling` and set the `spool_all_results_for_retries` query option.

Type: BOOLEAN

Default: TRUE

Added in: Impala 4.0

Related information: [Impala Transparent Query Retries](#) on page 806

RUNTIME_BLOOM_FILTER_SIZE Query Option (Impala 2.5 or higher only)

Size (in bytes) of Bloom filter data structure used by the runtime filtering feature.

Important:

In Impala 2.6 and higher, this query option only applies as a fallback, when statistics are not available. By default, Impala estimates the optimal size of the Bloom filter structure regardless of the setting for this option. (This is a change from the original behavior in Impala 2.5.)

In Impala 2.6 and higher, when the value of this query option is used for query planning, it is constrained by the minimum and maximum sizes specified by the `RUNTIME_FILTER_MIN_SIZE` and `RUNTIME_FILTER_MAX_SIZE` query options. The filter size is adjusted upward or downward if necessary to fit within the minimum/maximum range.

Type: integer

Default: 1048576 (1 MB)

Maximum: 16 MB

Added in: Impala 2.5.0

Usage notes:

This setting affects optimizations for large and complex queries, such as dynamic partition pruning for partitioned tables, and join optimization for queries that join large tables. Larger filters are more effective at handling higher cardinality input sets, but consume more memory per filter.

If your query filters on high-cardinality columns (for example, millions of different values) and you do not get the expected speedup from the runtime filtering mechanism, consider doing some benchmarks with a higher value for `RUNTIME_BLOOM_FILTER_SIZE`. The extra memory devoted to the Bloom filter data structures can help make the filtering more accurate.

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Because the effectiveness of this setting depends so much on query characteristics and data distribution, you typically only use it for specific queries that need some extra tuning, and the ideal value depends on the query. Consider setting this query option immediately before the expensive query and unsetting it immediately afterward.

Kudu considerations:

This query option affects only Bloom filters, not the min/max filters that are applied to Kudu tables. Therefore, it does not affect the performance of queries against Kudu tables.

Related information:

[Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641, [RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389, [RUNTIME_FILTER_MIN_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388, [RUNTIME_FILTER_MAX_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388

RUNTIME_FILTER_MAX_SIZE Query Option (Impala 2.6 or higher only)

The `RUNTIME_FILTER_MAX_SIZE` query option adjusts the settings for the runtime filtering feature. This option defines the maximum size for a filter, no matter what the estimates produced by the planner are. This value also overrides any lower number specified for the `RUNTIME_BLOOM_FILTER_SIZE` query option. Filter sizes are rounded up to the nearest power of two.

Type: integer

Default: 0 (meaning use the value from the corresponding `impalad` startup option)

Added in: Impala 2.6.0

Usage notes:

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Kudu considerations:

This query option affects only Bloom filters, not the min/max filters that are applied to Kudu tables. Therefore, it does not affect the performance of queries against Kudu tables.

Related information:

[Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641, [RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389, [RUNTIME_FILTER_MIN_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388, [RUNTIME_BLOOM_FILTER_SIZE Query Option \(Impala 2.5 or higher only\)](#) on page 387

RUNTIME_FILTER_MIN_SIZE Query Option (Impala 2.6 or higher only)

The `RUNTIME_FILTER_MIN_SIZE` query option adjusts the settings for the runtime filtering feature. This option defines the minimum size for a filter, no matter what the estimates produced by the planner are. This value also overrides any lower number specified for the `RUNTIME_BLOOM_FILTER_SIZE` query option. Filter sizes are rounded up to the nearest power of two.

Type: integer

Default: 0 (meaning use the value from the corresponding `impalad` startup option)

Added in: Impala 2.6.0

Usage notes:

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Kudu considerations:

This query option affects only Bloom filters, not the min/max filters that are applied to Kudu tables. Therefore, it does not affect the performance of queries against Kudu tables.

Related information:

[Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641, [RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389, [RUNTIME_FILTER_MAX_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388, [RUNTIME_BLOOM_FILTER_SIZE Query Option \(Impala 2.5 or higher only\)](#) on page 387

RUNTIME_FILTER_MODE Query Option (Impala 2.5 or higher only)

The `RUNTIME_FILTER_MODE` query option adjusts the settings for the runtime filtering feature. It turns this feature on and off, and controls how extensively the filters are transmitted between hosts.

Type: numeric (0, 1, 2) or corresponding mnemonic strings (OFF, LOCAL, GLOBAL).

Default: 2 (equivalent to GLOBAL); formerly was 1 / LOCAL, in Impala 2.5

Added in: Impala 2.5.0

Usage notes:

In Impala 2.6 and higher, the default is GLOBAL. This setting is recommended for a wide variety of workloads, to provide best performance with “out of the box” settings.

The lowest setting of LOCAL does a similar level of optimization (such as partition pruning) as in earlier Impala releases. This setting was the default in Impala 2.5, to allow for a period of post-upgrade testing for existing workloads. This setting is suitable for workloads with non-performance-critical queries, or if the coordinator node is under heavy CPU or memory pressure.

You might change the setting to OFF if your workload contains many queries involving partitioned tables or joins that do not experience a performance increase from the runtime filters feature. If the overhead of producing the runtime filters outweighs the performance benefit for queries, you can turn the feature off entirely.

Related information:

[Partitioning for Impala Tables](#) on page 685 for details about runtime filtering.
[DISABLE_ROW_RUNTIME_FILTERING Query Option \(Impala 2.5 or higher only\)](#) on page 354,
[RUNTIME_BLOOM_FILTER_SIZE Query Option \(Impala 2.5 or higher only\)](#) on page 387,
[RUNTIME_FILTER_WAIT_TIME_MS Query Option \(Impala 2.5 or higher only\)](#) on page 389, and
[MAX_NUM_RUNTIME_FILTERS Query Option \(Impala 2.5 or higher only\)](#) on page 361 for tuning options for runtime filtering.

RUNTIME_FILTER_WAIT_TIME_MS Query Option (Impala 2.5 or higher only)

The `RUNTIME_FILTER_WAIT_TIME_MS` query option adjusts the settings for the runtime filtering feature. It specifies a time in milliseconds that each scan node waits for runtime filters to be produced by other plan fragments.

Type: integer

Default: 0 (meaning use the value from the corresponding `impalad` startup option)

Added in: Impala 2.5.0

Usage notes:

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Related information:

[Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641, [RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389

S3_SKIP_INSERT_STAGING Query Option (Impala 2.6 or higher only)

Speeds up INSERT operations on tables or partitions residing on the Amazon S3 filesystem. The tradeoff is the possibility of inconsistent data left behind if an error occurs partway through the operation.

By default, Impala write operations to S3 tables and partitions involve a two-stage process. Impala writes intermediate files to S3, then (because S3 does not provide a “rename” operation) those intermediate files are copied to their final location, making the process more expensive as on a filesystem that supports renaming or moving files. This query option makes Impala skip the intermediate files, and instead write the new data directly to the final destination.

Usage notes:

Important:

If a host that is participating in the INSERT operation fails partway through the query, you might be left with a table or partition that contains some but not all of the expected data files. Therefore, this option is most appropriate for a development or test environment where you have the ability to reconstruct the table if a problem during INSERT leaves the data in an inconsistent state.

The timing of file deletion during an INSERT OVERWRITE operation makes it impractical to write new files to S3 and delete the old files in a single operation. Therefore, this query option only affects regular INSERT statements that add to the existing data in a table, not INSERT OVERWRITE statements. Use TRUNCATE TABLE if you need to remove all contents from an S3 table before performing a fast INSERT with this option enabled.

Performance improvements with this option enabled can be substantial. The speed increase might be more noticeable for non-partitioned tables than for partitioned tables.

Type: Boolean; recognized values are 1 and 0, or true and false; any other value interpreted as false

Default: true (shown as 1 in output of SET statement)

Added in: Impala 2.6.0

Related information:

[Using Impala with Amazon S3 Object Store](#) on page 769

SCAN_BYTES_LIMIT Query Option (Impala 3.1 or higher only)

The SCAN_BYTES_LIMIT query option sets a limit on the bytes scanned by HDFS and HBase SCAN operations. If a query is still executing when the query’s coordinator detects that it has exceeded the limit, the query is terminated with an error. The option is intended to prevent runaway queries that scan more data than is intended.

For example, an Impala administrator could set a default value of SCAN_BYTES_LIMIT=100GB for a resource pool to automatically kill queries that scan more than 100 GB of data (see [Impala Admission Control and Query Queuing](#) for information about default query options). If a user accidentally omits a partition filter in a WHERE clause and runs a large query that scans a lot of data, the query will be automatically terminated after it scans more data than the SCAN_BYTES_LIMIT.

You can override the default value per-query or per-session, in the same way as other query options, if you do not want the default SCAN_BYTES_LIMIT value to apply to a specific query or session.

Note:

- Only data actually read from the underlying storage layer is counted towards the limit. E.g. Impala's Parquet scanner employs several techniques to skip over data in a file that is not relevant to a specific query, so often only a fraction of the file size is counted towards `SCAN_BYTES_LIMIT`.
- As of Impala 3.1, bytes scanned by Kudu tablet servers are not counted towards the limit.

Because the checks are done periodically, the query may scan over the limit at times.

Syntax: `SET SCAN_BYTES_LIMIT=bytes;`

Type: numeric

Units:

- A numeric argument represents memory size in bytes.
- Specify a suffix of `m` or `mb` for megabytes.
- Specify a suffix of `g` or `gb` for gigabytes.
- If you specify a suffix with unrecognized formats, subsequent queries fail with an error.

Default: 0 (no limit)

Added in: Impala 3.1

SCHEDULE_RANDOM_REPLICA Query Option (Impala 2.5 or higher only)

The `SCHEDULE_RANDOM_REPLICA` query option fine-tunes the scheduling algorithm for deciding which host processes each HDFS data block or Kudu tablet to reduce the chance of CPU hotspots.

By default, Impala estimates how much work each host has done for the query, and selects the host that has the lowest workload. This algorithm is intended to reduce CPU hotspots arising when the same host is selected to process multiple data blocks / tablets. Use the `SCHEDULE_RANDOM_REPLICA` query option if hotspots still arise for some combinations of queries and data layout.

The `SCHEDULE_RANDOM_REPLICA` query option only applies to tables and partitions that are not enabled for the HDFS caching.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false`

Added in: Impala 2.5.0

Related information:

[Using HDFS Caching with Impala \(Impala 2.1 or higher only\)](#) on page 646, [Avoiding CPU Hotspots for HDFS Cached Data](#) on page 664, [REPLICA_PREFERENCE Query Option \(Impala 2.7 or higher only\)](#) on page 386

SCRATCH_LIMIT Query Option

Specifies the maximum amount of disk storage, in bytes, that any Impala query can consume on any host using the “spill to disk” mechanism that handles queries that exceed the memory limit.

Syntax:

Specify the size in bytes, or with a trailing `m` or `g` character to indicate megabytes or gigabytes. For example:

```
-- 128 megabytes.
set SCRATCH_LIMIT=134217728

-- 512 megabytes.
set SCRATCH_LIMIT=512m;

-- 1 gigabyte.
set SCRATCH_LIMIT=1g;
```

Usage notes:

A value of zero turns off the spill to disk feature for queries in the current session, causing them to fail immediately if they exceed the memory limit.

The amount of memory used per host for a query is limited by the `MEM_LIMIT` query option.

The more Impala daemon hosts in the cluster, the less memory is used on each host, and therefore also less scratch space is required for queries that exceed the memory limit.

Type: numeric, with optional unit specifier

Default: -1 (amount of spill space is unlimited)

Related information:

[SQL Operations that Spill to Disk](#) on page 660, [MEM_LIMIT Query Option](#) on page 370

SHUFFLE_DISTINCT_EXPRS Query Option

The `SHUFFLE_DISTINCT_EXPRS` query option controls the shuffling behavior when a query has both grouping and distinct expressions. Impala can optionally include the distinct expressions in the hash exchange to spread the data among more nodes. However, this plan requires one more hash exchange phase.

It is recommended that you turn off this option if the NDVs of the grouping expressions are high.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false`

SPOOL_QUERY_RESULTS Query Option

Use the `SPOOL_QUERY_RESULTS` query option to enable query result spooling, which is disabled by default.

Query result spooling controls how rows are returned to the client.

- When query result spooling is disabled (`SPOOL_QUERY_RESULTS = FALSE`), Impala relies on clients to fetch results to trigger the generation of more result row batches until all the result rows have been produced. If a client issues a query without fetching all the results, the query fragments will continue to consume the resources until the query is cancelled and unregistered, potentially tying up resources and cause other queries to wait for extended period of time in admission control.
- When query result spooling is enabled (`SPOOL_QUERY_RESULTS = TRUE`), the result sets of queries are eagerly fetched and spooled, either in memory or on disk.

Once all result rows have been fetched and stored in the spooling location, the resources are freed up. Incoming client fetches can get the data from the spooled results.

Type: BOOLEAN

Default: FALSE

Added in: Impala 3.4

Related information: [DEFAULT_SPILLABLE_BUFFER_SIZE Query Option](#) on page 352, [MAX_SPILLED_RESULT_SPOOLING_MEM Query Option](#) on page 370, [MAX_RESULT_SPOOLING_MEM Query Option](#) on page 366

SUPPORT_START_OVER Query Option

Leave this setting at its default value. It is a read-only setting, tested by some client applications such as Hue.

If you accidentally change it through `impala-shell`, subsequent queries encounter errors until you undo the change by issuing `UNSET support_start_over`.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false`

SYNC_DDL Query Option

When enabled, causes any DDL operation such as `CREATE TABLE` or `ALTER TABLE` to return only when the changes have been propagated to all other Impala nodes in the cluster by the Impala catalog service. That way, if you issue a subsequent `CONNECT` statement in `impala-shell` to connect to a different node in the cluster, you can be sure that other node will already recognize any added or changed tables. (The catalog service automatically broadcasts the DDL changes to all nodes automatically, but without this option there could be a period of inconsistency if you quickly switched to another node, such as by issuing a subsequent query through a load-balancing proxy.)

Although `INSERT` is classified as a DML statement, when the `SYNC_DDL` option is enabled, `INSERT` statements also delay their completion until all the underlying data and metadata changes are propagated to all Impala nodes and this option applies to all filesystem-based tables. Internally, Impala inserts have similarities with DDL statements in traditional database systems, because they create metadata needed to track HDFS block locations for new files and they potentially add new partitions to partitioned tables.

Note: Because this option can introduce a delay after each write operation, if you are running a sequence of `CREATE DATABASE`, `CREATE TABLE`, `ALTER TABLE`, `INSERT`, and similar statements within a setup script, to minimize the overall delay you can enable the `SYNC_DDL` query option only near the end, before the final DDL statement.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Related information:

[DDL Statements](#) on page 213

THREAD_RESERVATION_AGGREGATE_LIMIT Query Option (Impala 3.1 or higher only)

The `THREAD_RESERVATION_AGGREGATE_LIMIT` query option limits the number of reserved threads for a query across all nodes on which it is executing. The option is intended to prevent execution of complex queries that can consume excessive CPU or operating system resources on a cluster. Queries that have more threads than this threshold are rejected by Impala's admission controller before they start executing.

For example, an Impala administrator could set a default value of `THREAD_RESERVATION_AGGREGATE_LIMIT=2000` for a resource pool on a 100 node where they expect only relatively simple queries with less than 20 threads per node to run. This will reject queries that require more than 2000 reserved threads across all nodes, for example a query with 21 fragments running on all 100 nodes of the cluster.

You can override the default value per-query or per-session, in the same way as other query options, if you do not want the default `THREAD_RESERVATION_AGGREGATE_LIMIT` value to apply to a specific query or session.

Syntax: `SET THREAD_RESERVATION_AGGREGATE_LIMIT=number;`

Type: numeric

Default: 0 (no limit)

Added in: Impala 3.1

THREAD_RESERVATION_LIMIT Query Option (Impala 3.1 or higher only)

The `THREAD_RESERVATION_LIMIT` query option limits the number of reserved threads for a query on each node. The option is intended to prevent execution of complex queries that can consume excessive CPU or operating system resources on a single node. Queries that have more threads per node than this threshold are rejected by Impala's admission controller before they start executing. You can see the number of reserved threads for a query in its [explain plan](#) in the "Per-Host Resource Reservation" line.

For example, an Impala administrator could set a default value of `THREAD_RESERVATION_LIMIT=100` for a resource pool where they expect only relatively simple queries to run. This will reject queries that require more than 100 reserved threads on a node, for example, queries with more than 100 fragments.

You can override the default value per-query or per-session, in the same way as other query options, if you do not want the default `THREAD_RESERVATION_LIMIT` value to apply to a specific query or session.

Note: The number of reserved threads on a node may be lower than the maximum value in the explain plan if not all fragments of that query are scheduled on every node.

Syntax: `SET THREAD_RESERVATION_LIMIT=number;`

Type: numeric

Default: 3000

Added in: Impala 3.1

TIMEZONE Query Option (Impala 3.1 or higher only)

The `TIMEZONE` query option defines the timezone used for conversions between UTC and the local time. If not set, Impala uses the system time zone where the Coordinator Impalad runs. As query options are not sent to the Coordinator immediately, the timezones are validated only when the query runs.

Impala takes the timezone into a consideration in the following cases:

- When calling the `NOW()` function
- When converting between Unix time and timestamp if the `use_local_tz_for_unix_timestamp_conversions` flag is `TRUE`
- When reading Parquet timestamps written by Hive if the `convert_legacy_hive_parquet_utc_timestamps` flag is `TRUE`

Syntax:

```
SET TIMEZONE=time zone
```

time zone can be a canonical code or a time zone name defined in [IANA Time Zone Database](#). The value is case-sensitive.

Leading/trailing quotes (') and double quotes (") are stripped.

If *time zone* is an empty string, the time zone for the query is set to the default time zone of the Impalad Coordinator.

If *time zone* is `NULL` or a space character, Impala returns an error when the query is executed.

Type: String

Default: The system time zone where the Coordinator Impalad runs

Examples:

```
SET TIMEZONE=UTC;
SET TIMEZONE="Europe/Budapest";
```

Added in: Impala 3.1

TOPN_BYTES_LIMIT Query Option (Impala 3.1 or higher only)

The `TOPN_BYTES_LIMIT` query option places a limit on the amount of estimated memory that Impala can process for *top-N* queries.

Top-N queries are the queries that include both `ORDER BY` and `LIMIT` clauses. *Top-N* queries don't spill to disk so they have to keep all rows they process in memory, and those queries can cause out-of-memory issues when running with a large limit and an offset. If the Impala planner estimates that a *top-N* operator will process more bytes than the `TOPN_BYTES_LIMIT` value, it will replace the *top-N* operator with the *sort* operator. Switching to the *sort* operator allows Impala to spill to disk, thus requiring less memory than *top-N*, but potentially with performance penalties.

The option has no effect when set to 0 or -1.

Syntax:

```
SET TOPN_BYTES_LIMIT=limit
```

Type: Number

Default: 536870912 (512 MB)

Added in: Impala 3.1

UTF8_MODE Query Option

UTF-8 support allows string functions to recognize the UTF-8 characters, thus processing strings in a compatible way as other engines.

You can use the new query option, UTF8_MODE, to turn on/off the UTF-8 aware behavior. The query option can be set globally, or at per session level. Only queries with UTF8_MODE=true will have UTF-8 aware behaviors. If the query option UTF8_MODE is turned on globally, existing queries that depend on the original binary behavior need to be explicitly set to UTF8_MODE=false.

Type: BOOLEAN

Default: FALSE

Added in: Impala 4.1

Related information:

[STRING Data Type](#) on page 125, [UTF-8 Support](#) on page 613

EXPAND_COMPLEX_TYPES Query Option

Older versions of Impala did not support complex types in the select list, and therefore a SELECT * statement only expanded to primitive types even when the table contained complex-typed columns. Support for complex types in the select list has since been added, but for backward compatibility the behaviour that “*” expressions skip complex types has been kept as the default. If the EXPAND_COMPLEX_TYPES query option is set to true, “*” expressions will include complex types as well.

Note: even if EXPAND_COMPLEX_TYPES is false, complex-typed columns that are listed explicitly in the select list (i.e. not as a “*” expression) will be included in the result.

Type: BOOLEAN

Default: FALSE

Added in: Impala 4.2

Related information:

[Complex Types \(Impala 2.3 or higher only\)](#) on page 142,

SHOW Statement

The SHOW statement is a flexible way to get information about different types of Impala objects.

Syntax:

```
SHOW DATABASES [[LIKE] 'pattern']
SHOW SCHEMAS [[LIKE] 'pattern'] - an alias for SHOW DATABASES
SHOW TABLES [IN database_name] [[LIKE] 'pattern']
SHOW [AGGREGATE | ANALYTIC] FUNCTIONS [IN database_name] [[LIKE] 'pattern']
SHOW CREATE TABLE [database_name].table_name
SHOW CREATE VIEW [database_name].view_name
SHOW TABLE STATS [database_name.]table_name
SHOW COLUMN STATS [database_name.]table_name
SHOW PARTITIONS [database_name.]table_name
SHOW [RANGE] PARTITIONS [database_name.]table_name
SHOW FILES IN [database_name.]table_name [PARTITION (key_col_expression
    [, key_col_expression]]
SHOW ROLES
```

```
SHOW CURRENT ROLES
SHOW ROLE GRANT GROUP group_name

SHOW GRANT USER user_name
SHOW GRANT USER user_name ON SERVER
SHOW GRANT USER user_name ON DATABASE database_name
SHOW GRANT USER user_name ON TABLE database_name.table_name
SHOW GRANT USER user_name ON URI uri
SHOW GRANT USER user_name ON COLUMN database_name.table_name.column_name
```

```
SHOW GRANT ROLE role_name
SHOW GRANT ROLE role_name ON SERVER
SHOW GRANT ROLE role_name ON DATABASE database_name
SHOW GRANT ROLE role_name ON TABLE database_name.table_name
SHOW GRANT ROLE role_name ON URI uri
SHOW GRANT ROLE role_name ON COLUMN database_name.table_name.column_name
```

```
SHOW GRANT GROUP group_name ON SERVER
SHOW GRANT GROUP group_name ON DATABASE database_name
SHOW GRANT GROUP group_name ON TABLE database_name.table_name
SHOW GRANT GROUP group_name ON URI uri
SHOW GRANT GROUP group_name ON COLUMN database_name.table_name.column_name
```

Issue a `SHOW object_type` statement to see the appropriate objects in the current database, or `SHOW object_type IN database_name` to see objects in a specific database.

The optional *pattern* argument is a quoted string literal, using Unix-style * wildcards and allowing | for alternation. The preceding LIKE keyword is also optional. All object names are stored in lowercase, so use all lowercase letters in the pattern string. For example:

```
SHOW DATABASES 'a*';
SHOW DATABASES LIKE 'a*';
SHOW TABLES IN some_db LIKE '*fact*';
USE some_db;
SHOW TABLES '*dim*|*fact*';
```

Cancellation: Cannot be cancelled.

SHOW FILES Statement

The `SHOW FILES` statement displays the files that constitute a specified table, or a partition within a partitioned table. This syntax is available in Impala 2.2 and higher only. The output includes the names of the files, the size of each file, and the applicable partition for a partitioned table. The size includes a suffix of B for bytes, MB for megabytes, and GB for gigabytes.

In Impala 2.8 and higher, you can use general expressions with operators such as <, IN, LIKE, and BETWEEN in the PARTITION clause, instead of only equality operators. For example:

```
show files in sample_table partition (j < 5);
show files in sample_table partition (k = 3, l between 1 and 10);
show files in sample_table partition (month like 'J%');
```

Note: This statement applies to tables and partitions stored on HDFS, or in the Amazon Simple Storage System (S3). It does not apply to views. It does not apply to tables mapped onto HBase or Kudu, because those data management systems do not use the same file-based storage layout.

Usage notes:

You can use this statement to verify the results of your ETL process: that is, that the expected files are present, with the expected sizes. You can examine the file information to detect conditions such as empty files, missing files, or inefficient layouts due to a large number of small files. When you use `INSERT` statements to copy from one table to another, you can see how the file layout changes due to file format conversions, compaction of small input files into large data blocks, and multiple output files from parallel queries and partitioned inserts.

The output from this statement does not include files that Impala considers to be hidden or invisible, such as those whose names start with a dot or an underscore, or that end with the suffixes `.copying` or `.tmp`.

The information for partitioned tables complements the output of the `SHOW PARTITIONS` statement, which summarizes information about each partition. `SHOW PARTITIONS` produces some output for each partition, while `SHOW FILES` does not produce any output for empty partitions because they do not include any data files.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permission for all the table files, read and execute permission for all the directories that make up the table, and execute permission for the database directory and all its parent directories.

Examples:

The following example shows a `SHOW FILES` statement for an unpartitioned table using text format:

```
[localhost:21000] > create table unpart_text (x bigint, s string);
[localhost:21000] > insert into unpart_text (x, s) select id, name
> from oreilly.sample_data limit 20e6;
[localhost:21000] > show files in unpart_text;
```

Path	Size	Partition	EC Policy
hdfs://impala_data_dir/show_files.db/unpart_text/35665776ef85cfaf_1012432410_data.0.	448.31MB		NONE

```
[localhost:21000] > insert into unpart_text (x, s) select id, name from oreilly.sample_data limit 100e6;
[localhost:21000] > show files in unpart_text;
```

Path	Size	Partition	EC Policy
hdfs://impala_data_dir/show_files.db/unpart_text/35665776ef85cfaf_1012432410_data.0.	448.31MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_text/ac3dba252a8952b8_1663177415_data.0.	2.19GB		NONE

This example illustrates how, after issuing some `INSERT ... VALUES` statements, the table now contains some tiny files of just a few bytes. Such small files could cause inefficient processing of parallel queries that are expecting multi-megabyte input files. The example shows how you might compact the small files by doing an `INSERT ... SELECT` into a different table, possibly converting the data to Parquet in the process:

```
[localhost:21000] > insert into unpart_text values (10, 'hello'), (20, 'world');
[localhost:21000] > insert into unpart_text values (-1, 'foo'), (-1000, 'bar');
[localhost:21000] > show files in unpart_text;
```

Path	Size	Partition	EC Policy
hdfs://impala_data_dir/show_files.db/unpart_text/4f11b8bdf8b6aa92_238145083_data.0.	18B		NONE
hdfs://impala_data_dir/show_files.db/unpart_text/35665776ef85cfaf_1012432410_data.0.	448.31MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_text/ac3dba252a8952b8_1663177415_data.0.	2.19GB		NONE
hdfs://impala_data_dir/show_files.db/unpart_text/cfb8252452445682_1868457216_data.0.	17B		NONE

```
[localhost:21000] > create table unpart_parq stored as parquet as select * from unpart_text;
+-----+
| summary |
+-----+
| Inserted 120000002 row(s) |
+-----+
[localhost:21000] > show files in unpart_parq;
```

Path	Size	Partition	EC Policy
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630184_549959007_data.0.parq	255.36MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630184_549959007_data.1.parq	178.52MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630185_549959007_data.0.parq	255.37MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630185_549959007_data.1.parq	57.71MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630186_2141167244_data.0.parq	255.40MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630186_2141167244_data.1.parq	175.52MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630187_1006832086_data.0.parq	255.40MB		NONE
hdfs://impala_data_dir/show_files.db/unpart_parq/60798d96ba630187_1006832086_data.1.parq	214.61MB		NONE

The following example shows a `SHOW FILES` statement for a partitioned text table with data in two different partitions, and two empty partitions. The partitions with no data are not represented in the `SHOW FILES` output.

```
[localhost:21000] > create table part_text (x bigint, y int, s string)
> partitioned by (year bigint, month bigint, day bigint);
[localhost:21000] > insert overwrite part_text (x, y, s) partition (year=2014, month=1, day=1)
```

```

> select id, val, name from oreilly.normalized_parquet
where id between 1 and 1000000;
[localhost:21000] > insert overwrite part_text (x, y, s) partition (year=2014,month=1,day=2)
> select id, val, name from oreilly.normalized_parquet
> where id between 1000001 and 2000000;
[localhost:21000] > alter table part_text add partition (year=2014,month=1,day=3);
[localhost:21000] > alter table part_text add partition (year=2014,month=1,day=4);
[localhost:21000] > show partitions part_text;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| year | month | day | #Rows | #Files | Size | Bytes Cached | Cache Replication | Format | Incremental stats | Location |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| 2014 | 1 | 1 | -1 | 4 | 25.16MB | NOT CACHED | NOT CACHED | TEXT | false | hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=1 | NONE |
| 2014 | 1 | 2 | -1 | 4 | 26.22MB | NOT CACHED | NOT CACHED | TEXT | false | hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=2 | NONE |
| 2014 | 1 | 3 | -1 | 0 | 0B | NOT CACHED | NOT CACHED | TEXT | false | hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=3 | NONE |
| 2014 | 1 | 4 | -1 | 0 | 0B | NOT CACHED | NOT CACHED | TEXT | false | hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=4 | NONE |
| Total | | | -1 | 8 | 51.38MB | 0B | | | | | |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

[localhost:21000] > show files in part_text;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Path | Partition | EC Policy | Size |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=1/80732d9dc80689f_1418645991_data.0. | year=2014/month=1/day=1 | NONE | 5.77MB |
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=1/80732d9dc8068a0_1418645991_data.0. | year=2014/month=1/day=1 | NONE | 6.25MB |
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=1/80732d9dc8068a1_147082319_data.0. | year=2014/month=1/day=1 | NONE | 7.16MB |
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=1/80732d9dc8068a2_2111411753_data.0. | year=2014/month=1/day=1 | NONE | 5.98MB |
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbb_501271652_data.0. | year=2014/month=1/day=2 | NONE | 6.42MB |
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbc_501271652_data.0. | year=2014/month=1/day=2 | NONE | 6.62MB |
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbd_1393490200_data.0. | year=2014/month=1/day=2 | NONE | 6.98MB |
| hdfs://impala_data_dir/show_files.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbe_1393490200_data.0. | year=2014/month=1/day=2 | NONE | 6.20MB |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

```

The following example shows a `SHOW FILES` statement for a partitioned Parquet table. The number and sizes of files are different from the equivalent partitioned text table used in the previous example, because `INSERT` operations for Parquet tables are parallelized differently than for text tables. (Also, the amount of data is so small that it can be written to Parquet without involving all the hosts in this 4-node cluster.)

```

[localhost:21000] > create table part_parq (x bigint, y int, s string) partitioned by (year bigint, month bigint, day bigint)
stored as parquet;
[localhost:21000] > insert into part_parq partition (year,month,day) select x, y, s, year, month, day from partitioned_text;
[localhost:21000] > show partitions part_parq;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| year | month | day | #Rows | #Files | Size | Bytes Cached | Cache Replication | Format | Incremental stats | Location |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| 2014 | 1 | 1 | -1 | 3 | 17.89MB | NOT CACHED | NOT CACHED | PARQUET | false | hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=1 | NONE |
| 2014 | 1 | 2 | -1 | 3 | 17.89MB | NOT CACHED | NOT CACHED | PARQUET | false | hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=2 | NONE |
| Total | | | -1 | 6 | 35.79MB | 0B | | | | | |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

[localhost:21000] > show files in part_parq;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Path | EC Policy | Size | Partition |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=1/1134113650_data.0.parq | NONE | 4.49MB | year=2014/month=1/day=1 |
| hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=1/617567880_data.0.parq | NONE | 5.14MB | year=2014/month=1/day=1 |
| hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=1/2099499416_data.0.parq | NONE | 8.27MB | year=2014/month=1/day=1 |
| hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=2/945567189_data.0.parq | NONE | 8.80MB | year=2014/month=1/day=2 |
| hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=2/2145850112_data.0.parq | NONE | 4.80MB | year=2014/month=1/day=2 |
| hdfs://impala_data_dir/show_files.db/part_parq/year=2014/month=1/day=2/665613448_data.0.parq | NONE | 4.29MB | year=2014/month=1/day=2 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

```

The following example shows output from the `SHOW FILES` statement for a table where the data files are stored in Amazon S3:

```
[localhost:21000] > show files in s3_testing.sample_data_s3;
```

Path	Size
s3a://impala-demo/sample_data/e065453cba1988a6_1733868553_data.0.parq	24.84MB

SHOW ROLES Statement

The `SHOW ROLES` statement displays roles. This syntax is available in Impala 2.0 and later only, when you are using the Ranger authorization framework along with the Ranger service, as described in [Managing Privileges](#) on page 86.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

Examples:

Depending on the roles set up within your organization by the `CREATE ROLE` statement, the output might look something like this:

```
show roles;
```

role_name
analyst
role1
sales
superuser
test_role

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Impala Authorization](#) on page 83

SHOW CURRENT ROLES

The `SHOW CURRENT ROLES` statement displays roles assigned to the current user. This syntax is available in Impala 2.0 and later only, when you are using the Ranger authorization framework along with the Ranger service, as described in [Managing Privileges](#) on page 86.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

Examples:

Depending on the roles set up within your organization by the `CREATE ROLE` statement, the output might look something like this:

```
show current roles;
```

|--|

```

| role_name |
+-----+
| role1    |
| superuser|
+-----+

```

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Impala Authorization](#) on page 83

SHOW ROLE GRANT GROUP Statement

The `SHOW ROLE GRANT GROUP` statement lists all the roles assigned to the specified group. This statement is only allowed for Ranger administrative users and others users that are part of the specified group. This syntax is available in Impala 2.0 and later only, when you are using the Ranger authorization framework along with the Ranger service, as described in [Managing Privileges](#) on page 86.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Impala Authorization](#) on page 83

SHOW GRANT ROLE Statement

The `SHOW GRANT ROLE` statement list all the grants for the given role name. This statement is only allowed for Ranger administrative users and other users that have been granted the specified role. This syntax is available in Impala 2.0 and later only, when you are using the Ranger authorization framework along with the Ranger service, as described in [Managing Privileges](#) on page 86.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Impala Authorization](#) on page 83

SHOW GRANT USER Statement

The `SHOW GRANT USER` statement shows the list of privileges for a given user. This statement is only allowed for Ranger administrative users. However, the current user can run `SHOW GRANT USER` for themselves.

This syntax is available in Impala 3.1 and later only, when you are using the Ranger authorization framework along with the Ranger service, as described in [Managing Privileges](#) on page 86.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Impala Authorization](#) on page 83

SHOW DATABASES

The `SHOW DATABASES` statement is often the first one you issue when connecting to an instance for the first time. You typically issue `SHOW DATABASES` to see the names you can specify in a `USE db_name` statement, then after switching to a database you issue `SHOW TABLES` to see the names you can specify in `SELECT` and `INSERT` statements.

In Impala 2.5 and higher, the output includes a second column showing any associated comment for each database.

The output of `SHOW DATABASES` includes the special `_impala_builtins` database, which lets you view definitions of built-in functions, as described under `SHOW FUNCTIONS`.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

Examples:

This example shows how you might locate a particular table on an unfamiliar system. The `DEFAULT` database is the one you initially connect to; a database with that name is present on every system. You can issue `SHOW TABLES IN db_name` without going into a database, or `SHOW TABLES` once you are inside a particular database.

```
[localhost:21000] > show databases;
```

name	comment
_impala_builtins	System database for Impala builtin functions
default	Default Hive database
file_formats	

```
Returned 3 row(s) in 0.02s
[localhost:21000] > show tables in file_formats;
```

name
parquet_table
rcfile_table
sequencefile_table
textfile_table

```
Returned 4 row(s) in 0.01s
[localhost:21000] > use file_formats;
[localhost:21000] > show tables like '*parq*';
```

name
parquet_table

```
Returned 1 row(s) in 0.01s
```

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Overview of Impala Databases](#) on page 203, [CREATE DATABASE Statement](#) on page 240, [DROP DATABASE Statement](#) on page 280, [USE Statement](#) on page 421 [SHOW TABLES Statement](#) on page 402, [SHOW FUNCTIONS Statement](#) on page 414

SHOW TABLES Statement

Displays the names of tables. By default, lists tables in the current database, or with the `IN` clause, in a specified database. By default, lists all tables, or with the `LIKE` clause, only those whose name match a pattern with `*` wildcards.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.)

Examples:

The following examples demonstrate the `SHOW TABLES` statement. If the database contains no tables, the result set is empty. If the database does contain tables, `SHOW TABLES IN db_name` lists all the table names. `SHOW TABLES` with no qualifiers lists all the table names in the current database.

```
create database empty_db;
show tables in empty_db;
Fetched 0 row(s) in 0.11s

create database full_db;
create table full_db.t1 (x int);
create table full_db.t2 like full_db.t1;

show tables in full_db;
+-----+
| name |
+-----+
| t1   |
| t2   |
+-----+

use full_db;
show tables;
+-----+
| name |
+-----+
| t1   |
| t2   |
+-----+
```

This example demonstrates how `SHOW TABLES LIKE 'wildcard_pattern'` lists table names that match a pattern, or multiple alternative patterns. The ability to do wildcard matches for table names makes it helpful to establish naming conventions for tables to conveniently locate a group of related tables.

```
create table fact_tbl (x int);
```

```

create table dim_tbl_1 (s string);
create table dim_tbl_2 (s string);

/* Asterisk is the wildcard character. Only 2 out of the 3 just-created
   tables are returned. */
show tables like 'dim*';
+-----+
| name   |
+-----+
| dim_tbl_1 |
| dim_tbl_2 |
+-----+

/* We are already in the FULL_DB database, but just to be sure we can
   specify the database name also. */
show tables in full_db like 'dim*';
+-----+
| name   |
+-----+
| dim_tbl_1 |
| dim_tbl_2 |
+-----+

/* The pipe character separates multiple wildcard patterns. */
show tables like '*dim*|t*';
+-----+
| name   |
+-----+
| dim_tbl_1 |
| dim_tbl_2 |
| t1      |
| t2      |
+-----+

```

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Overview of Impala Tables](#) on page 206, [CREATE TABLE Statement](#) on page 248, [ALTER TABLE Statement](#) on page 215, [DROP TABLE Statement](#) on page 289, [DESCRIBE Statement](#) on page 268, [SHOW CREATE TABLE Statement](#) on page 403, [SHOW TABLE STATS Statement](#) on page 406, [SHOW DATABASES](#) on page 401, [SHOW FUNCTIONS Statement](#) on page 414

SHOW CREATE TABLE Statement

As a schema changes over time, you might run a CREATE TABLE statement followed by several ALTER TABLE statements. To capture the cumulative effect of all those statements, SHOW CREATE TABLE displays a CREATE TABLE statement that would reproduce the current structure of a table. You can use this output in scripts that set up or clone a group of tables, rather than trying to reproduce the original sequence of CREATE TABLE and ALTER TABLE statements. When creating variations on the original table, or cloning the original table on a different system, you might need to edit the SHOW CREATE TABLE output to change things such as the database name, LOCATION field, and so on that might be different on the destination system.

If you specify a view name in the SHOW CREATE TABLE, it returns a CREATE VIEW statement with column names and the original SQL statement to reproduce the view. You need the VIEW_METADATA privilege on the view and SELECT privilege on all underlying views and tables to successfully run the SHOW CREATE VIEW statement for a view. The SHOW CREATE VIEW is available as an alias for SHOW CREATE TABLE.

Security considerations:

When authorization is enabled, the output of the SHOW statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the SHOW output, check with the system

administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

For Kudu tables:

- The column specifications include attributes such as NULL, NOT NULL, ENCODING, and COMPRESSION. If you do not specify those attributes in the original CREATE TABLE statement, the SHOW CREATE TABLE output displays the defaults that were used.
- The specifications of any RANGE clauses are not displayed in full. To see the definition of the range clauses for a Kudu table, use the SHOW RANGE PARTITIONS statement.
- The TBLPROPERTIES output reflects the Kudu master address and the internal Kudu name associated with the Impala table.

```
show CREATE TABLE numeric_grades_default_letter;
+-----+
+
| result
|
+-----+
+
| CREATE TABLE user.numeric_grades_default_letter (
|   score TINYINT NOT NULL ENCODING AUTO_ENCODING COMPRESSION
|   DEFAULT_COMPRESSION,
|   letter_grade STRING NULL ENCODING AUTO_ENCODING COMPRESSION
|   DEFAULT_COMPRESSION DEFAULT '-',
|   student STRING NULL ENCODING AUTO_ENCODING COMPRESSION
|   DEFAULT_COMPRESSION,
|   PRIMARY KEY (score)
| )
|
| PARTITION BY RANGE (score) (...) .
|
| STORED AS KUDU
|
| TBLPROPERTIES ('kudu.master_addresses'='vd0342.example.com:7051')
+-----+
+

show range partitions numeric_grades_default_letter;
+-----+
| RANGE (score)
+-----+
| 0 <= VALUES < 50
| 50 <= VALUES < 65
| 65 <= VALUES < 80
| 80 <= VALUES < 100
+-----+
```

Examples:

The following example shows how various clauses from the CREATE TABLE statement are represented in the output of SHOW CREATE TABLE.

```
create table show_create_table_demo (id int comment "Unique ID", y double, s
string)
partitioned by (year smallint)
```

```

    stored as parquet;

show create table show_create_table_demo;
+-----+
+ | result |
+-----+
+ | CREATE TABLE scratch.show_create_table_demo (
+ |   id INT COMMENT 'Unique ID',
+ |   y DOUBLE,
+ |   s STRING
+ | )
+ | PARTITIONED BY (
+ |   year SMALLINT
+ | )
+ | STORED AS PARQUET
+ | LOCATION 'hdfs://127.0.0.1:8020/user/hive/warehouse/scratch.db/
show_create_table_demo' |
+ | TBLPROPERTIES ('transient_lastDdlTime'='1418152582')
+-----+
+

```

The following example shows how, after a sequence of ALTER TABLE statements, the output from SHOW CREATE TABLE represents the current state of the table. This output could be used to create a matching table rather than executing the original CREATE TABLE and sequence of ALTER TABLE statements.

```

alter table show_create_table_demo drop column s;
alter table show_create_table_demo set fileformat textfile;

show create table show_create_table_demo;
+-----+
+ | result |
+-----+
+ | CREATE TABLE scratch.show_create_table_demo (
+ |   id INT COMMENT 'Unique ID',
+ |   y DOUBLE
+ | )
+ | PARTITIONED BY (
+ |   year SMALLINT
+ | )
+

```

```

| STORED AS TEXTFILE
|
| LOCATION 'hdfs://127.0.0.1:8020/user/hive/warehouse/demo.db/'
show_create_table_demo'
| TBLPROPERTIES ('transient_lastDdlTime'='1418152638')
|
+-----+
+

```

Related information:

[CREATE TABLE Statement](#) on page 248, [DESCRIBE Statement](#) on page 268, [SHOW TABLES Statement](#) on page 402

SHOW CREATE VIEW Statement

The `SHOW CREATE VIEW`, it returns a `CREATE VIEW` statement with column names and the original SQL statement to reproduce the view. You need the `VIEW_METADATA` privilege on the view and `SELECT` privilege on all underlying views and tables to successfully run the `SHOW CREATE VIEW` statement for a view.

The `SHOW CREATE VIEW` is an alias for `SHOW CREATE TABLE`.

SHOW TABLE STATS Statement

The `SHOW TABLE STATS` and `SHOW COLUMN STATS` variants are important for tuning performance and diagnosing performance issues, especially with the largest tables and the most complex join queries.

Any values that are not available (because the `COMPUTE STATS` statement has not been run yet) are displayed as `-1`.

`SHOW TABLE STATS` provides some general information about the table, such as the number of files, overall size of the data, whether some or all of the data is in the HDFS cache, and the file format, that is useful whether or not you have run the `COMPUTE STATS` statement. A `-1` in the `#Rows` output column indicates that the `COMPUTE STATS` statement has never been run for this table. If the table is partitioned, `SHOW TABLE STATS` provides this information for each partition. (It produces the same output as the `SHOW PARTITIONS` statement in this case.)

The output of `SHOW COLUMN STATS` is primarily only useful after the `COMPUTE STATS` statement has been run on the table. A `-1` in the `#Distinct Values` output column indicates that the `COMPUTE STATS` statement has never been run for this table. Currently, Impala always leaves the `#Nulls` column as `-1`, even after `COMPUTE STATS` has been run.

These `SHOW` statements work on actual tables only, not on views.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

Kudu considerations:

Because Kudu tables do not have characteristics derived from HDFS, such as number of files and HDFS cache status, the output of `SHOW TABLE STATS` reflects different characteristics that apply to Kudu tables.

```

show table stats kudu_table;
+-----+-----+-----+-----+-----+
| #Rows | #Partitions | Size   | Format | Location                               |
+-----+-----+-----+-----+-----+
| 100   | 7           | 56.16MB | KUDU   | kudu-master.example.com:7051         |
+-----+-----+-----+-----+-----+

```

Examples:

The following examples show how the `SHOW TABLE STATS` statement displays physical information about a table and the associated data files:

```
show table stats store_sales;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
| Location          | EC Policy |
+-----+-----+-----+-----+-----+
| -1      | 1      | 370.45MB | NOT CACHED   | TEXT  | false             |
| hdfs://impala_data_dir/store_sales | NONE      |
+-----+-----+-----+-----+-----+

show table stats customer;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
| Location          | EC Policy |
+-----+-----+-----+-----+-----+
| -1      | 1      | 12.60MB  | NOT CACHED   | TEXT  | false             |
| hdfs://impala_data_dir/customer | NONE      |
+-----+-----+-----+-----+-----+
```

The following example shows how, after a `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement, the `#Rows` field is now filled in. Because the `STORE_SALES` table in this example is not partitioned, the `COMPUTE INCREMENTAL STATS` statement produces regular stats rather than incremental stats, therefore the `Incremental stats` field remains false.

```
compute stats customer;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 18 column(s). |
+-----+

show table stats customer;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
| Location          | EC Policy |
+-----+-----+-----+-----+-----+
| 100000 | 1      | 12.60MB  | NOT CACHED   | TEXT  | false             |
| hdfs://impala_data_dir/customer | NONE      |
+-----+-----+-----+-----+-----+

compute incremental stats store_sales;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 23 column(s). |
+-----+

show table stats store_sales;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
| Location          | EC Policy |
+-----+-----+-----+-----+-----+-----+
| 100000 | 1      | 370.45MB | NOT CACHED   | TEXT  | false             |
| hdfs://impala_data_dir/store_sales | NONE      |
+-----+-----+-----+-----+-----+-----+
```

#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Location			EC Policy		
2880404	1	370.45MB	NOT CACHED	TEXT	false
hdfs://impala_data_dir/store_sales			NONE		

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.) The Impala user must also have execute permission for the database directory, and any parent directories of the database directory in HDFS.

Related information:

[COMPUTE STATS Statement](#) on page 232, [SHOW COLUMN STATS Statement](#) on page 408

See [Table and Column Statistics](#) on page 625 for usage information and examples.

SHOW COLUMN STATS Statement

The `SHOW TABLE STATS` and `SHOW COLUMN STATS` variants are important for tuning performance and diagnosing performance issues, especially with the largest tables and the most complex join queries.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

The output for `SHOW COLUMN STATS` includes the relevant information for Kudu tables. The information for column statistics that originates in the underlying Kudu storage layer is also represented in the metastore database that Impala uses.

Examples:

The following examples show the output of the `SHOW COLUMN STATS` statement for some tables, before the `COMPUTE STATS` statement is run. Impala deduces some information, such as maximum and average size for fixed-length columns, and leaves and unknown values as `-1`.

```
show column stats customer;
+-----+-----+-----+-----+-----+
+-----+
| Column              | Type   | #Distinct Values | #Nulls | Max Size |
| Avg Size |
+-----+-----+-----+-----+-----+
| c_customer_sk       | INT    | -1               | -1     | 4        | 4
| c_customer_id       | STRING | -1               | -1     | -1       |
| c_current_cdemo_sk  | INT    | -1               | -1     | 4        | 4
| c_current_hdemo_sk  | INT    | -1               | -1     | 4        | 4
| c_current_addr_sk   | INT    | -1               | -1     | 4        | 4
| c_first_shipto_date_sk | INT    | -1               | -1     | 4        | 4
```



```

| c_first_sales_date_sk | INT      | -1      | -1      | 4      | 4
| c_salutation          | STRING   | -1      | -1      | -1     |
| c_first_name          | STRING   | -1      | -1      | -1     |
| c_last_name           | STRING   | -1      | -1      | -1     |
| c_preferred_cust_flag | STRING   | -1      | -1      | -1     |
| c_birth_day           | INT      | -1      | -1      | 4      | 4
| c_birth_month         | INT      | -1      | -1      | 4      | 4
| c_birth_year          | INT      | -1      | -1      | 4      | 4
| c_birth_country       | STRING   | -1      | -1      | -1     |
| c_login               | STRING   | -1      | -1      | -1     |
| c_email_address       | STRING   | -1      | -1      | -1     |
| c_last_review_date    | STRING   | -1      | -1      | -1     |
+-----+-----+-----+-----+-----+
+-----+

show column stats store_sales;
+-----+-----+-----+-----+-----+
+-----+
| Column              | Type    | #Distinct Values | #Nulls | Max Size | Avg
Size |
+-----+-----+-----+-----+-----+
+-----+
| ss_sold_date_sk     | INT     | -1              | -1     | 4        | 4
| ss_sold_time_sk     | INT     | -1              | -1     | 4        | 4
| ss_item_sk          | INT     | -1              | -1     | 4        | 4
| ss_customer_sk      | INT     | -1              | -1     | 4        | 4
| ss_cdemo_sk         | INT     | -1              | -1     | 4        | 4
| ss_hdemo_sk        | INT     | -1              | -1     | 4        | 4
| ss_addr_sk          | INT     | -1              | -1     | 4        | 4
| ss_store_sk         | INT     | -1              | -1     | 4        | 4
| ss_promo_sk         | INT     | -1              | -1     | 4        | 4
| ss_ticket_number    | INT     | -1              | -1     | 4        | 4
| ss_quantity         | INT     | -1              | -1     | 4        | 4
| ss_wholesale_cost    | FLOAT   | -1              | -1     | 4        | 4
| ss_list_price       | FLOAT   | -1              | -1     | 4        | 4
| ss_sales_price      | FLOAT   | -1              | -1     | 4        | 4
| ss_ext_discount_amt | FLOAT   | -1              | -1     | 4        | 4

```

ss_ext_sales_price	FLOAT	-1	-1	4	4
ss_ext_wholesale_cost	FLOAT	-1	-1	4	4
ss_ext_list_price	FLOAT	-1	-1	4	4
ss_ext_tax	FLOAT	-1	-1	4	4
ss_coupon_amt	FLOAT	-1	-1	4	4
ss_net_paid	FLOAT	-1	-1	4	4
ss_net_paid_inc_tax	FLOAT	-1	-1	4	4
ss_net_profit	FLOAT	-1	-1	4	4
+-----+-----+-----+-----+-----+					
+-----+					

The following examples show the output of the `SHOW COLUMN STATS` statement for some tables, after the `COMPUTE STATS` statement is run. Now most of the -1 values are changed to reflect the actual table data. The #Nulls column remains -1 because Impala does not use the number of NULL values to influence query planning.

```
compute stats customer;
```

```
+-----+
| summary                                     |
+-----+
| Updated 1 partition(s) and 18 column(s). |
+-----+
```

```
compute stats store_sales;
```

```
+-----+
| summary                                     |
+-----+
| Updated 1 partition(s) and 23 column(s). |
+-----+
```

```
show column stats customer;
```

```
+-----+-----+-----+-----+-----+
| Column          | Type   | #Distinct Values | #Nulls | Max Size |
| Avg Size       |
+-----+-----+-----+-----+-----+
| c_customer_sk   | INT    | 139017           | -1     | 4         | 4
| c_customer_id   | STRING | 111904           | -1     | 16        |
| c_current_cdemo_sk | INT    | 95837            | -1     | 4         | 4
| c_current_hdemo_sk | INT    | 8097             | -1     | 4         | 4
| c_current_addr_sk | INT    | 57334            | -1     | 4         | 4
| c_first_shipto_date_sk | INT    | 4374             | -1     | 4         | 4
| c_first_sales_date_sk | INT    | 4409             | -1     | 4         | 4
| c_salutation    | STRING | 7                | -1     | 4         |
| c_first_name     | STRING | 3887             | -1     | 11        |
| c_last_name      | STRING | 3887             | -1     | 11        |
```

```

| c_last_name          | STRING | 4739          | -1      | 13          |
5.9106 |
| c_preferred_cust_flag | STRING | 3              | -1      | 1           |
0.9656 |
| c_birth_day          | INT    | 31             | -1      | 4           | 4
|
| c_birth_month        | INT    | 12             | -1      | 4           | 4
|
| c_birth_year         | INT    | 71             | -1      | 4           | 4
|
| c_birth_country      | STRING | 205            | -1      | 20          |
8.4001 |
| c_login              | STRING | 1              | -1      | 0           | 0
|
| c_email_address      | STRING | 94492          | -1      | 46          |
26.485 |
| c_last_review_date   | STRING | 349            | -1      | 7           |
6.7561 |
+-----+-----+-----+-----+-----+
+-----+

show column stats store_sales;
+-----+-----+-----+-----+-----+
+-----+
| Column              | Type   | #Distinct Values | #Nulls | Max Size | Avg
Size |
+-----+-----+-----+-----+-----+
+-----+
| ss_sold_date_sk     | INT    | 4395            | -1      | 4         | 4
|
| ss_sold_time_sk     | INT    | 63617           | -1      | 4         | 4
|
| ss_item_sk          | INT    | 19463           | -1      | 4         | 4
|
| ss_customer_sk      | INT    | 122720          | -1      | 4         | 4
|
| ss_cdemo_sk         | INT    | 242982          | -1      | 4         | 4
|
| ss_hdemo_sk         | INT    | 8097            | -1      | 4         | 4
|
| ss_addr_sk          | INT    | 70770           | -1      | 4         | 4
|
| ss_store_sk         | INT    | 6               | -1      | 4         | 4
|
| ss_promo_sk         | INT    | 355             | -1      | 4         | 4
|
| ss_ticket_number     | INT    | 304098          | -1      | 4         | 4
|
| ss_quantity         | INT    | 105             | -1      | 4         | 4
|
| ss_wholesale_cost    | FLOAT  | 9600            | -1      | 4         | 4
|
| ss_list_price        | FLOAT  | 22191           | -1      | 4         | 4
|
| ss_sales_price       | FLOAT  | 20693           | -1      | 4         | 4
|
| ss_ext_discount_amt  | FLOAT  | 228141          | -1      | 4         | 4
|
| ss_ext_sales_price   | FLOAT  | 433550          | -1      | 4         | 4
|
| ss_ext_wholesale_cost | FLOAT  | 406291          | -1      | 4         | 4
|
| ss_ext_list_price    | FLOAT  | 574871          | -1      | 4         | 4
|

```

ss_ext_tax	FLOAT	91806	-1	4	4
ss_coupon_amt	FLOAT	228141	-1	4	4
ss_net_paid	FLOAT	493107	-1	4	4
ss_net_paid_inc_tax	FLOAT	653523	-1	4	4
ss_net_profit	FLOAT	611934	-1	4	4
+-----+-----+-----+-----+-----+					
+-----+					

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.) The Impala user must also have execute permission for the database directory, and any parent directories of the database directory in HDFS.

Related information:

[COMPUTE STATS Statement](#) on page 232, [SHOW TABLE STATS Statement](#) on page 406

See [Table and Column Statistics](#) on page 625 for usage information and examples.

SHOW PARTITIONS Statement

`SHOW PARTITIONS` displays information about each partition for a partitioned table. (The output is the same as the `SHOW TABLE STATS` statement, but `SHOW PARTITIONS` only works on a partitioned table.) Because it displays table statistics for all partitions, the output is more informative if you have run the `COMPUTE STATS` statement after creating all the partitions. See [COMPUTE STATS Statement](#) on page 232 for details. For example, on a `CENSUS` table partitioned on the `YEAR` column:

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

Kudu considerations:

The optional `RANGE` clause only applies to Kudu tables. It displays only the partitions defined by the `RANGE` clause of `CREATE TABLE` or `ALTER TABLE`.

Although you can specify `<` or `<=` comparison operators when defining range partitions for Kudu tables, Kudu rewrites them if necessary to represent each range as `low_bound <= VALUES < high_bound`. This rewriting might involve incrementing one of the boundary values or appending a `\0` for string values, so that the partition covers the same range as originally specified.

Examples:

The following example shows the output for a Parquet, text, or other HDFS-backed table partitioned on the `YEAR` column:

```
[localhost:21000] > show partitions census;
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| year  | #Rows | #Files | Size | Format | Incremental stats | Location
|      |      |      |      |      |      | EC Policy |
+-----+-----+-----+-----+-----+-----+
+-----+
```

2000	-1	0	0B	TEXT	false	
hdfs://impala_data_dir/census/year=2000	NONE					
2004	-1	0	0B	TEXT	false	
hdfs://impala_data_dir/census/year=2000	NONE					
2008	-1	0	0B	TEXT	false	
hdfs://impala_data_dir/census/year=2000	NONE					
2010	-1	0	0B	TEXT	false	
hdfs://impala_data_dir/census/year=2000	NONE					
2011	4	1	22B	TEXT	false	
hdfs://impala_data_dir/census/year=2000	NONE					
2012	4	1	22B	TEXT	false	
hdfs://impala_data_dir/census/year=2000	NONE					
2013	1	1	231B	PARQUET	false	
hdfs://impala_data_dir/census/year=2000	NONE					
Total	9	3	275B			
+-----+-----+-----+-----+-----+-----+-----						
+-----+-----+-----+-----+-----+-----+-----						

The following example shows the output for a Kudu table using the hash partitioning mechanism. The number of rows in the result set corresponds to the values used in the `PARTITIONS N` clause of `CREATE TABLE`. If the Kudu table is created with the clause `PARTITIONS 20`, then the result set of `SHOW PARTITIONS` consists of 20 rows, each representing one of the numbered partitions. For example:

```
show partitions million_rows_hash;
```

# Rows	Start Key	Stop Key	Leader Replica	# Replicas
-1		00000001	n236.example.com:7050	3
-1	00000001	00000002	n236.example.com:7050	3
-1	00000002	00000003	n336.example.com:7050	3
-1	00000003	00000004	n238.example.com:7050	3
-1	00000004	00000005	n338.example.com:7050	3
...				
-1	0000002E	0000002F	n240.example.com:7050	3
-1	0000002F	00000030	n336.example.com:7050	3
-1	00000030	00000031	n240.example.com:7050	3
-1	00000031		n334.example.com:7050	3

Fetches 50 row(s) in 0.05s

Impala only computes the number of rows for the whole Kudu table, partition level row counts are not available.

The following example shows the output for a Kudu table using the range partitioning mechanism:

```
show range partitions million_rows_range;
```

RANGE (id)
VALUES < "A"
"A" <= VALUES < "["
"a" <= VALUES < "{"
"{" <= VALUES < "~\0"

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.) The Impala user must also have execute permission for the database directory, and any parent directories of the database directory in HDFS.

Related information:

See [Table and Column Statistics](#) on page 625 for usage information and examples.

[SHOW TABLE STATS Statement](#) on page 406, [Partitioning for Impala Tables](#) on page 685

SHOW FUNCTIONS Statement

By default, `SHOW FUNCTIONS` displays user-defined functions (UDFs) and `SHOW AGGREGATE FUNCTIONS` displays user-defined aggregate functions (UDAFs) associated with a particular database. The output from `SHOW FUNCTIONS` includes the argument signature of each function. You specify this argument signature as part of the `DROP FUNCTION` statement. You might have several UDFs with the same name, each accepting different argument data types.

Usage notes:

In Impala 2.5 and higher, the `SHOW FUNCTIONS` output includes a new column, labelled `is persistent`. This property is `true` for Impala built-in functions, C++ UDFs, and Java UDFs created using the new `CREATE FUNCTION` syntax with no signature. It is `false` for Java UDFs created using the old `CREATE FUNCTION` syntax that includes the types for the arguments and return value. Any functions with `false` shown for this property must be created again by the `CREATE FUNCTION` statement each time the Impala catalog server is restarted. See `CREATE FUNCTION` for information on switching to the new syntax, so that Java UDFs are preserved across restarts. Java UDFs that are persisted this way are also easier to share across Impala and Hive.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement only shows those objects for which you have the privilege to view. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Impala Authorization](#) on page 83 for how to set up authorization and add privileges for specific objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

To display Impala built-in functions, specify the special database name `_impala_builtins`:

```
show functions in _impala_builtins;
+-----+-----+-----+-----+
+-----+-----+-----+-----+
| return type | signature | is persistent | binary |
+-----+-----+-----+-----+
+-----+-----+-----+-----+
| BIGINT      | abs(BIGINT) | true          | BUILTIN |
| true       |            |              |         |
| DECIMAL(*,*) | abs(DECIMAL(*,*)) | true          | BUILTIN |
| true       |            |              |         |
| DOUBLE      | abs(DOUBLE) | true          | BUILTIN |
| true       |            |              |         |
| FLOAT       | abs(FLOAT)  | true          | BUILTIN |
| true       |            |              |         |
+-----+-----+-----+-----+
+-----+-----+-----+-----+

show functions in _impala_builtins like '*week*';
+-----+-----+-----+-----+
+-----+-----+-----+-----+
```

return type	signature	binary type	is persistent
INT	dayofweek(TIMESTAMP)	BUILTIN	true
INT	weekofyear(TIMESTAMP)	BUILTIN	true
TIMESTAMP	weeks_add(TIMESTAMP, BIGINT)	BUILTIN	true
TIMESTAMP	weeks_add(TIMESTAMP, INT)	BUILTIN	true
TIMESTAMP	weeks_sub(TIMESTAMP, BIGINT)	BUILTIN	true
TIMESTAMP	weeks_sub(TIMESTAMP, INT)	BUILTIN	true

Related information:

[Overview of Impala Functions](#) on page 204, [Impala Built-In Functions](#) on page 428, [User-Defined Functions \(UDFs\)](#) on page 588, [SHOW DATABASES](#) on page 401, [SHOW TABLES Statement](#) on page 402

SHUTDOWN Statement

The SHUTDOWN statement performs a graceful shutdown of Impala Daemon. The Impala daemon will notify other Impala daemons that it is shutting down, wait for a grace period, then shut itself down once no more queries or fragments are executing on that daemon. The `--shutdown_grace_period_s` flag determines the duration of the grace period in seconds.

Syntax:

```
:SHUTDOWN( )
:SHUTDOWN([host_name[:port_number] ] )
:SHUTDOWN(deadline)
:SHUTDOWN([host_name[:port_number] , deadline)
```

Usage notes:

All arguments are optional for SHUTDOWN.

Argument	Type	Default	Description
<i>host_name</i>	STRING	The current impalad host to whom the SHUTDOWN statement is submitted.	Address of the impalad to be shut down.
<i>port_number</i>	INT	<ul style="list-style-type: none"> In Impala 3.1, the current impalad's port used for the thrift based communication with other impalads (by default, 22000). In Impala 3.2 and higher, the current impalad's port used for the KRPC based communication with other impalads (by default, 27000). 	<p>Specifies the port by which the impalad can be contacted.</p> <ul style="list-style-type: none"> In Impala 3.1, use the same impalad port used for the thrift based inter-Impala communication. In Impala 3.2 and higher, use the same impalad port used for the KRPC based inter-Impala communication.
<i>deadline</i>	INT	The value of the <code>##shutdown_deadline</code> flag, which defaults to 1 hour.	<p><i>deadline</i> must be a non-negative number, specified in seconds.</p> <p>The value, 0, for <i>deadline</i> specifies an immediate shutdown.</p>

Take the following points into consideration when running the SHUTDOWN statement:

- A client can shut down the *coordinator* impalad that it is connected to via :SHUTDOWN().
- A client can remotely shut down any impalad via :SHUTDOWN('hostname').
- The shutdown time limit can be overridden to force a quicker or slower shutdown by specifying a deadline. The default deadline is determined by the --shutdown_deadline_s flag, which defaults to 1 hour.
- *Executors* can be shut down without disrupting running queries. Short-running queries will finish, and long-running queries will continue until the *deadline* is reached.
- If queries are submitted to a coordinator after shutdown of that coordinator has started, they will fail.
- Long running queries or other issues, such as stuck fragments, will slow down but not prevent eventual shutdown.

Security considerations:

The ALL privilege is required on the server.

Cancellation: Cannot be cancelled.

Examples:

```
:SHUTDOWN(); -- Shut down the current impalad with the default deadline.
:SHUTDOWN('hostname'); -- Shut down impalad running on hostname with the
  default deadline.
:SHUTDOWN("\hostname:1234\"); -- Shut down impalad running on host at port
  1234 with the default deadline.
:SHUTDOWN(10); -- Shut down the current impalad after 10 seconds.
:SHUTDOWN('hostname', 10); -- Shut down impalad running on hostname when all
  queries running on hostname finish, or after 10 seconds.
:SHUTDOWN('hostname:11', 10 * 60); -- Shut down impalad running on hostname
  at port 11 when all queries running on hostname finish, or after 600
  seconds.
:SHUTDOWN(0); -- Perform an immediate shutdown of the current impalad.
```

Added in: Impala 3.1

TRUNCATE TABLE Statement (Impala 2.3 or higher only)

Removes the data from an Impala table while leaving the table itself.

Syntax:

```
TRUNCATE [TABLE] [IF EXISTS] [db_name.]table_name
```

Statement type: DDL

Usage notes:

Often used to empty tables that are used during ETL cycles, after the data has been copied to another table for the next stage of processing. This statement is a low-overhead alternative to dropping and recreating the table, or using INSERT OVERWRITE to replace the data during the next ETL cycle.

This statement removes all the data and associated data files in the table. It can remove data files from internal tables, external tables, partitioned tables, and tables mapped to HBase or the Amazon Simple Storage Service (S3). The data removal applies to the entire table, including all partitions of a partitioned table.

Any statistics produced by the COMPUTE STATS statement are reset when the data is removed.

Make sure that you are in the correct database before truncating a table, either by issuing a USE statement first or by using a fully qualified name *db_name.table_name*.

The optional TABLE keyword does not affect the behavior of the statement.

The optional IF EXISTS clause makes the statement succeed whether or not the table exists. If the table does exist, it is truncated; if it does not exist, the statement has no effect. This capability is useful in standardized setup scripts that might be run both before and after some of the tables exist. This clause is available in Impala 2.5 and higher.

For other tips about managing and reclaiming Impala disk space, see [Managing Disk Space for Impala Data](#) on page 73.

Amazon S3 considerations:

Although Impala cannot write new data to a table stored in the Amazon S3 filesystem, the `TRUNCATE TABLE` statement can remove data files from S3. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about working with S3 tables.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for all the files and directories that make up the table.

Kudu considerations:

Currently, the `TRUNCATE TABLE` statement cannot be used with Kudu tables.

Examples:

The following example shows a table containing some data and with table and column statistics. After the `TRUNCATE TABLE` statement, the data is removed and the statistics are reset.

```
CREATE TABLE truncate_demo (x INT);
INSERT INTO truncate_demo VALUES (1), (2), (4), (8);
SELECT COUNT(*) FROM truncate_demo;
+-----+
| count(*) |
+-----+
| 4         |
+-----+

COMPUTE STATS truncate_demo;
+-----+
| summary                                     |
+-----+
| Updated 1 partition(s) and 1 column(s). |
+-----+

SHOW TABLE STATS truncate_demo;
+-----+
| #Rows | #Files | Size | Bytes Cached | Cache Replication | Format |
+-----+
| 4      | 1      | 8B   | NOT CACHED   | NOT CACHED        | TEXT  |
+-----+

SHOW COLUMN STATS truncate_demo;
+-----+
| Column | Type | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+
| x      | INT  | 4                | -1     | 4        | 4        |
+-----+

-- After this statement, the data and the table/column stats will be gone.
TRUNCATE TABLE truncate_demo;

SELECT COUNT(*) FROM truncate_demo;
+-----+
| count(*) |
+-----+
| 0         |
+-----+
```

```

+-----+
SHOW TABLE STATS truncate_demo;
+-----+-----+-----+-----+-----+-----+
+-----+
| #Rows | #Files | Size | Bytes Cached | Cache Replication | Format |
Incremental stats |
+-----+-----+-----+-----+-----+-----+
| -1    | 0      | 0B   | NOT CACHED   | NOT CACHED        | TEXT   | false
+-----+-----+-----+-----+-----+-----+
+-----+
SHOW COLUMN STATS truncate_demo;
+-----+-----+-----+-----+-----+-----+
| Column | Type | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| x      | INT  | -1              | -1     | 4        | 4        |
+-----+-----+-----+-----+-----+-----+

```

The following example shows how the `IF EXISTS` clause allows the `TRUNCATE TABLE` statement to be run without error whether or not the table exists:

```

CREATE TABLE staging_table1 (x INT, s STRING);
Fetched 0 row(s) in 0.33s

SHOW TABLES LIKE 'staging*';
+-----+
| name          |
+-----+
| staging_table1 |
+-----+
Fetched 1 row(s) in 0.25s

-- Our ETL process involves removing all data from several staging tables
-- even though some might be already dropped, or not created yet.

TRUNCATE TABLE IF EXISTS staging_table1;
Fetched 0 row(s) in 5.04s

TRUNCATE TABLE IF EXISTS staging_table2;
Fetched 0 row(s) in 0.25s

TRUNCATE TABLE IF EXISTS staging_table3;
Fetched 0 row(s) in 0.25s

```

Related information:

[Overview of Impala Tables](#) on page 206, [ALTER TABLE Statement](#) on page 215, [CREATE TABLE Statement](#) on page 248, [Partitioning for Impala Tables](#) on page 685, [Internal Tables](#) on page 206, [External Tables](#) on page 207

UPDATE Statement (Impala 2.8 or higher only)

This statement only works for Kudu and Iceberg tables. Updates an arbitrary number of rows in a target table.

Syntax:

```

UPDATE [database_name.]table_name SET col = val [, col = val ... ]
[ FROM joined_table_refs ]
[ WHERE where_conditions ]

```

Usage notes:

None of the columns that make up the primary key can be updated by the SET clause.

The conditions in the WHERE clause are the same ones allowed for the SELECT statement. See [SELECT Statement](#) on page 316 for details.

If the WHERE clause is omitted, all rows in the table are updated.

The number of affected rows is reported in an `impala-shell` message and in the query profile.

The optional FROM clause lets you restrict the updates to only the rows in the specified table that are part of the result set for a join query. The join clauses can include tables with any format, but the table from which the rows are deleted must be a Kudu or Iceberg table.

Kudu considerations

The conditions in the WHERE clause can refer to any combination of primary key columns or other columns.

Referring to primary key columns in the WHERE clause is more efficient than referring to non-primary key columns.

Because Kudu currently does not enforce strong consistency during concurrent DML operations, be aware that the results after this statement finishes might be different than you intuitively expect:

- If some rows cannot be updated because their some primary key columns are not found, due to their being deleted by a concurrent DELETE operation, the statement succeeds but returns a warning.
- An UPDATE statement might also overlap with INSERT, UPDATE, or UPSERT statements running concurrently on the same table. After the statement finishes, there might be more or fewer matching rows than expected in the table because it is undefined whether the UPDATE applies to rows that are inserted or updated while the UPDATE is in progress.

Statement type: DML

Important: After adding or replacing data in a table used in performance-critical queries, issue a `COMPUTE STATS` statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any `INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT` statement in Impala, or after loading data through Hive and doing a `REFRESH table_name` in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

The following examples show how to perform a simple update on a table, with or without a WHERE clause:

```
-- Set all rows to the same value for column c3.
-- In this case, c1 and c2 are primary key columns
-- and so cannot be updated.
UPDATE target_table SET c3 = 'not applicable';

-- Update only the rows that match the condition.
UPDATE target_table SET c3 = NULL WHERE c1 > 100 AND c3 IS NULL;

-- Does not update any rows, because the WHERE condition is always false.
UPDATE target_table SET c3 = 'impossible' WHERE 1 = 0;

-- Change the values of multiple columns in a single UPDATE statement.
UPDATE target_table SET c3 = upper(c3), c4 = FALSE, c5 = 0 WHERE c6 = TRUE;
```

The following examples show how to perform an update using the FROM keyword with a join clause:

```
-- Uppercase a column value, only for rows that have
-- an ID that matches the value from another table.
UPDATE target_table SET c3 = upper(c3)
FROM target_table JOIN other_table
ON target_table.id = other_table.id;
```

```
-- Same effect as previous statement.
-- Assign table aliases in FROM clause, then refer to
-- short names elsewhere in the statement.
UPDATE t1 SET c3 = upper(c3)
  FROM target_table t1 JOIN other_table t2
    ON t1.id = t2.id;

-- Same effect as previous statements, but more efficient.
-- Use WHERE clause to skip updating values that are
-- already uppercase.
UPDATE t1 SET c3 = upper(c3)
  FROM target_table t1 JOIN other_table t2
    ON t1.id = t2.id
 WHERE c3 != upper(c3);
```

Related information:

[Using Impala to Query Kudu Tables](#) on page 733, [INSERT Statement](#) on page 298, [DELETE Statement \(Impala 2.8 or higher only\)](#) on page 266, [UPSERT Statement \(Impala 2.8 or higher only\)](#) on page 420

UPSERT Statement (Impala 2.8 or higher only)

Acts as a combination of the INSERT and UPDATE statements. For each row processed by the UPSERT statement:

- If another row already exists with the same set of primary key values, the other columns are updated to match the values from the row being “UPSERTed”.
- If there is not any row with the same set of primary key values, the row is created, the same as if the INSERT statement was used.

This statement only works for Impala tables that use the Kudu storage engine.

Syntax:

```
UPSERT [hint_clause] INTO [TABLE] [db_name.]table_name
  [(column_list)]
{
  [hint_clause] select_statement
  | VALUES (value [, value ...]) [, (value [, value ...]) ...]
}

hint_clause ::= [SHUFFLE] | [NOSHUFFLE]
  (Note: the square brackets are part of the syntax.)
```

The *select_statement* clause can use the full syntax, such as WHERE and join clauses, as [SELECT Statement](#) on page 316.

Statement type: DML**Usage notes:**

If you specify a column list, any omitted columns in the inserted or updated rows are set to their default value (if the column has one) or NULL (if the column does not have a default value). Therefore, if a column is not nullable and has no default value, it must be included in the column list for any UPSERT statement. Because all primary key columns meet these conditions, all the primary key columns must be specified in every UPSERT statement.

Because Kudu tables can efficiently handle small incremental changes, the VALUES clause is more practical to use with Kudu tables than with HDFS-based tables.

Important: After adding or replacing data in a table used in performance-critical queries, issue a COMPUTE STATS statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any INSERT, LOAD DATA, or CREATE TABLE AS SELECT statement in Impala, or after loading data through Hive and doing a

REFRESH *table_name* in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

```
UPSERT INTO kudu_table (pk, c1, c2, c3) VALUES (0, 'hello', 50, true), (1,
'world', -1, false);
UPSERT INTO production_table SELECT * FROM staging_table;
UPSERT INTO production_table SELECT * FROM staging_table WHERE c1 IS NOT
NULL AND c2 > 0;
```

Related information:

[Using Impala to Query Kudu Tables](#) on page 733, [INSERT Statement](#) on page 298, [UPDATE Statement \(Impala 2.8 or higher only\)](#) on page 418

USE Statement

Switches the current session to a specified database. The *current database* is where any CREATE TABLE, INSERT, SELECT, or other statements act when you specify a table or other object name, without prefixing it with a database name. The new current database applies for the duration of the session or until another USE statement is executed.

Syntax:

```
USE db_name
```

By default, when you connect to an Impala instance, you begin in a database named `default`.

Usage notes:

Switching the default database is convenient in the following situations:

- To avoid qualifying each reference to a table with the database name. For example, `SELECT * FROM t1 JOIN t2` rather than `SELECT * FROM db.t1 JOIN db.t2`.
- To do a sequence of operations all within the same database, such as creating a table, inserting data, and querying the table.

To start the `impala-shell` interpreter and automatically issue a USE statement for a particular database, specify the option `-d db_name` for the `impala-shell` command. The `-d` option is useful to run SQL scripts, such as setup or test scripts, against multiple databases without hardcoding a USE statement into the SQL source.

Examples:

See [CREATE DATABASE Statement](#) on page 240 for examples covering CREATE DATABASE, USE, and DROP DATABASE.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[CREATE DATABASE Statement](#) on page 240, [DROP DATABASE Statement](#) on page 280, [SHOW DATABASES](#) on page 401

VALUES Statement

In addition to being part of the INSERT statement, the VALUES clause can be used as stand-alone statement or with the SELECT statement to construct a data set without creating a table. For example, the following statement returns a data set of 2 rows and 3 columns.

```
VALUES ('r1_c1', 'r1_c2', 'r1_c3')
      , ('r2_c1', 'r2_c2', 'r2_c3');
```

Syntax:

```
VALUES (row)[, (row), ...];

SELECT select_list FROM (VALUES (row)[, (row), ...]) AS alias;

row ::= column [[AS alias], column [AS alias], ...]
```

- The VALUES keyword is followed by a comma separated list of one or more *rows*.
- *row* is a comma-separated list of one or more *columns*.
- Each *row* must have the same number of *columns*.
- *column* can be a constant, a variable, or an expression.
- The corresponding *columns* must have compatible data types in all *rows*. See the third query in the Examples section below.
- By default, the first row is used to name columns. But using the AS keyword, you can optionally give the column an *alias*.
- If used in the SELECT statement, the AS keyword with an *alias* is required.
- *select_list* is the columns to be selected for the result set.

Examples:

```
> SELECT * FROM (VALUES(4,5,6),(7,8,9)) AS t;
+---+---+---+
| 4 | 5 | 6 |
+---+---+---+
| 4 | 5 | 6 |
| 7 | 8 | 9 |
+---+---+---+

> SELECT * FROM (VALUES(1 AS c1, true AS c2, 'abc' AS c3),(100,false,'xyz'))
AS t;
+-----+-----+-----+
| c1 | c2 | c3 |
+-----+-----+-----+
| 1 | true | abc |
| 100 | false | xyz |
+-----+-----+-----+

> VALUES (CAST('2019-01-01' AS TIMESTAMP)), ('2019-02-02');
+-----+
| cast('2019-01-01' as timestamp) |
+-----+
| 2019-01-01 00:00:00 |
| 2019-02-02 00:00:00 |
+-----+
```

Related information:

[SELECT Statement](#) on page 316

Optimizer Hints

The Impala SQL supports query hints, for fine-tuning the inner workings of queries. Specify hints as a temporary workaround for expensive queries, where missing statistics or other factors cause inefficient performance.

Hints are most often used for the resource-intensive Impala queries, such as:

- Join queries involving large tables, where intermediate result sets are transmitted across the network to evaluate the join conditions.
- Inserting into partitioned Parquet tables, where many memory buffers could be allocated on each host to hold intermediate results for each partition.

Syntax:

In Impala 2.0 and higher, you can specify the hints inside comments that use either the `/* */` or `--` notation. Specify a `+` symbol immediately before the hint name. Recently added hints are only available using the `/* */` and `--` notation. For clarity, the `/* */` and `--` styles are used in the syntax and examples throughout this section. With the `/* */` or `--` notation for hints, specify a `+` symbol immediately before the first hint name. Multiple hints can be specified separated by commas, for example `/* +clustered,shuffle */`

```
SELECT STRAIGHT_JOIN select_list FROM
join_left_hand_table
  JOIN /* +BROADCAST|SHUFFLE */
join_right_hand_table
remainder_of_query;

SELECT select_list FROM
join_left_hand_table
  JOIN -- +BROADCAST|SHUFFLE
join_right_hand_table
remainder_of_query;

INSERT insert_clauses
/* +SHUFFLE|NOSHUFFLE */
  SELECT remainder_of_query;

INSERT insert_clauses
-- +SHUFFLE|NOSHUFFLE
  SELECT remainder_of_query;

INSERT /* +SHUFFLE|NOSHUFFLE */
  insert_clauses
  SELECT remainder_of_query;

INSERT -- +SHUFFLE|NOSHUFFLE
  insert_clauses
  SELECT remainder_of_query;

UPSERT /* +SHUFFLE|NOSHUFFLE */
  upsert_clauses
  SELECT remainder_of_query;

UPSERT -- +SHUFFLE|NOSHUFFLE
  upsert_clauses
  SELECT remainder_of_query;

SELECT select_list
FROM
table_ref
  /* +{SCHEDULE_CACHE_LOCAL | SCHEDULE_DISK_LOCAL | SCHEDULE_REMOTE}
  [,RANDOM_REPLICA] */
remainder_of_query;

INSERT insert_clauses
-- +CLUSTERED
  SELECT remainder_of_query;
```

```

INSERT insert_clauses
/* +CLUSTERED */
SELECT remainder_of_query;

INSERT -- +CLUSTERED
insert_clauses
SELECT remainder_of_query;

INSERT /* +CLUSTERED */
insert_clauses
SELECT remainder_of_query;

UPSERT -- +CLUSTERED
upsert_clauses
SELECT remainder_of_query;

UPSERT /* +CLUSTERED */
upsert_clauses
SELECT remainder_of_query;

CREATE /* +SHUFFLE|NOSHUFFLE */
table_clauses
AS SELECT remainder_of_query;

CREATE -- +SHUFFLE|NOSHUFFLE
table_clauses
AS SELECT remainder_of_query;

CREATE /* +CLUSTERED|NOCLUSTERED */
table_clauses
AS SELECT remainder_of_query;

CREATE -- +CLUSTERED|NOCLUSTERED
table_clauses
AS SELECT remainder_of_query;

```

The square bracket style hints are supported for backward compatibility, but the syntax is deprecated and will be removed in a future release. For that reason, any newly added hints are not available with the square bracket syntax.

```

SELECT STRAIGHT_JOIN select_list FROM
join_left_hand_table
JOIN [{ /* +BROADCAST */ | /* +SHUFFLE */ }]
join_right_hand_table
remainder_of_query;

INSERT insert_clauses
[{ /* +SHUFFLE */ | /* +NOSHUFFLE */ }]
[/* +CLUSTERED */]
SELECT remainder_of_query;

UPSERT [{ /* +SHUFFLE */ | /* +NOSHUFFLE */ }]
[/* +CLUSTERED */]
upsert_clauses
SELECT remainder_of_query;

```

Usage notes:

With both forms of hint syntax, include the STRAIGHT_JOIN keyword immediately after the SELECT and any DISTINCT or ALL keywords to prevent Impala from reordering the tables in a way that makes the join-related hints ineffective.

The `STRAIGHT_JOIN` hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or `WHERE`-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

To reduce the need to use hints, run the `COMPUTE STATS` statement against all tables involved in joins, or used as the source tables for `INSERT ... SELECT` operations where the destination is a partitioned Parquet table. Do this operation after loading data or making substantial changes to the data within each table. Having up-to-date statistics helps Impala choose more efficient query plans without the need for hinting. See [Table and Column Statistics](#) on page 625 for details and examples.

To see which join strategy is used for a particular query, examine the `EXPLAIN` output for that query. See [Using the EXPLAIN Plan for Performance Tuning](#) on page 655 for details and examples.

Hints for join queries:

The `/* +BROADCAST */` and `/* +SHUFFLE */` hints control the execution strategy for join queries. Specify one of the following constructs immediately after the `JOIN` keyword in a query:

- `/* +SHUFFLE */` makes that join operation use the “partitioned” technique, which divides up corresponding rows from both tables using a hashing algorithm, sending subsets of the rows to other nodes for processing. (The keyword `SHUFFLE` is used to indicate a “partitioned join”, because that type of join is not related to “partitioned tables”.) Since the alternative “broadcast” join mechanism is the default when table and index statistics are unavailable, you might use this hint for queries where broadcast joins are unsuitable; typically, partitioned joins are more efficient for joins between large tables of similar size.
- `/* +BROADCAST */` makes that join operation use the “broadcast” technique that sends the entire contents of the right-hand table to all nodes involved in processing the join. This is the default mode of operation when table and index statistics are unavailable, so you would typically only need it if stale metadata caused Impala to mistakenly choose a partitioned join operation. Typically, broadcast joins are more efficient in cases where one table is much smaller than the other. (Put the smaller table on the right side of the `JOIN` operator.)

Hints for `INSERT ... SELECT` and `CREATE TABLE AS SELECT (CTAS)`:

When inserting into partitioned tables, such as using the Parquet file format, you can include a hint in the `INSERT` or `CREATE TABLE AS SELECT (CTAS)` statements to fine-tune the overall performance of the operation and its resource usage.

You would only use hints if an `INSERT` or `CTAS` into a partitioned table was failing due to capacity limits, or if such an operation was succeeding but with less-than-optimal performance.

- `/* +SHUFFLE */` and `/* +NOSHUFFLE */` Hints
 - `/* +SHUFFLE */` adds an exchange node, before writing the data, which re-partitions the result of the `SELECT` based on the partitioning columns of the target table. With this hint, only one node writes to a partition at a time, minimizing the global number of simultaneous writes and the number of memory buffers holding data for individual partitions. This also reduces fragmentation, resulting in fewer files. Thus it reduces overall resource usage of the `INSERT` or `CTAS` operation and allows some operations to succeed that otherwise would fail. It does involve some data transfer between the nodes so that the data files for a particular partition are all written on the same node.

Use `/* +SHUFFLE */` in cases where an `INSERT` or `CTAS` statement fails or runs inefficiently due to all nodes attempting to write data for all partitions.

If the table is unpartitioned or every partitioning expression is constant, then `/* +SHUFFLE */` will cause every write to happen on the coordinator node.

- `/* +NOSHUFFLE */` does not add exchange node before inserting to partitioned tables and disables re-partitioning. So the selected execution plan might be faster overall, but might also produce a larger number of small data files or exceed capacity limits, causing the `INSERT` or `CTAS` operation to fail.

Impala automatically uses the `/* +SHUFFLE */` method if any partition key column in the source table, mentioned in the `SELECT` clause, does not have column statistics. In this case, use the `/* +NOSHUFFLE */` hint if you want to override this default behavior.

- If column statistics are available for all partition key columns in the source table mentioned in the INSERT ... SELECT or CTAS query, Impala chooses whether to use the /* +SHUFFLE */ or /* +NOSHUFFLE */ technique based on the estimated number of distinct values in those columns and the number of nodes involved in the operation. In this case, you might need the /* +SHUFFLE */ or the /* +NOSHUFFLE */ hint to override the execution plan selected by Impala.
- /* +CLUSTERED */ and /* +NOCLUSTERED */ Hints
 - /* +CLUSTERED */ sorts data by the partition columns before inserting to ensure that only one partition is written at a time per node. Use this hint to reduce the number of files kept open and the number of buffers kept in memory simultaneously. This technique is primarily useful for inserts into Parquet tables, where the large block size requires substantial memory to buffer data for multiple output files at once. This hint is available in Impala 2.8 or higher.

Starting in Impala 3.0, /* +CLUSTERED */ is the default behavior for HDFS tables.

- /* +NOCLUSTERED */ does not sort by primary key before insert. This hint is available in Impala 2.8 or higher.

Use this hint when inserting to Kudu tables.

In the versions lower than Impala 3.0, /* +NOCLUSTERED */ is the default in HDFS tables.

Kudu consideration:

Starting from Impala 2.9, the INSERT or UPSERT operations into Kudu tables automatically add an exchange and a sort node to the plan that partitions and sorts the rows according to the partitioning/primary key scheme of the target table (unless the number of rows to be inserted is small enough to trigger single node execution). Since Kudu partitions and sorts rows on write, pre-partitioning and sorting takes some of the load off of Kudu and helps large INSERT operations to complete without timing out. However, this default behavior may slow down the end-to-end performance of the INSERT or UPSERT operations. Starting from Impala 2.10, you can use the /* +NOCLUSTERED */ and /* +NOSHUFFLE */ hints together to disable partitioning and sorting before the rows are sent to Kudu. Additionally, since sorting may consume a large amount of memory, consider setting the MEM_LIMIT query option for those queries.

Hints for scheduling of scan ranges (HDFS data blocks or Kudu tablets)

The hints /* +SCHEDULE_CACHE_LOCAL */, /* +SCHEDULE_DISK_LOCAL */, and /* +SCHEDULE_REMOTE */ have the same effect as specifying the REPLICA_PREFERENCE query option with the respective option settings of CACHE_LOCAL, DISK_LOCAL, or REMOTE.

Specifying the replica preference as a query hint always overrides the query option setting.

The hint /* +RANDOM_REPLICA */ is the same as enabling the SCHEDULE_RANDOM_REPLICA query option.

You can use these hints in combination by separating them with commas, for example, /* +SCHEDULE_CACHE_LOCAL, RANDOM_REPLICA */. See [REPLICA_PREFERENCE Query Option \(Impala 2.7 or higher only\)](#) on page 386 and [SCHEDULE_RANDOM_REPLICA Query Option \(Impala 2.5 or higher only\)](#) on page 391 for information about how these settings influence the way Impala processes HDFS data blocks or Kudu tablets.

Specifying either the SCHEDULE_RANDOM_REPLICA query option or the corresponding RANDOM_REPLICA query hint enables the random tie-breaking behavior when processing data blocks during the query.

Suggestions versus directives:

In early Impala releases, hints were always obeyed and so acted more like directives. Once Impala gained join order optimizations, sometimes join queries were automatically reordered in a way that made a hint irrelevant. Therefore, the hints act more like suggestions in Impala 1.2.2 and higher.

To force Impala to follow the hinted execution mechanism for a join query, include the STRAIGHT_JOIN keyword in the SELECT statement. See [Overriding Join Reordering with STRAIGHT_JOIN](#) on page 619 for details. When you use this technique, Impala does not reorder the joined tables at all, so you must be careful to arrange the join order to put the largest table (or subquery result set) first, then the smallest, second smallest, third smallest, and so on. This ordering lets Impala do the most I/O-intensive parts of the query using local reads on the DataNodes, and then

reduce the size of the intermediate result set as much as possible as each subsequent table or subquery result set is joined.

Restrictions:

Queries that include subqueries in the `WHERE` clause can be rewritten internally as join queries. Currently, you cannot apply hints to the joins produced by these types of queries.

Because hints can prevent queries from taking advantage of new metadata or improvements in query planning, use them only when required to work around performance issues, and be prepared to remove them when they are no longer required, such as after a new Impala release or bug fix.

In particular, the `/* +BROADCAST */` and `/* +SHUFFLE */` hints are expected to be needed much less frequently in Impala 1.2.2 and higher, because the join order optimization feature in combination with the `COMPUTE STATS` statement now automatically choose join order and join mechanism without the need to rewrite the query and add hints. See [Performance Considerations for Join Queries](#) on page 618 for details.

Compatibility:

The hints embedded within `--` comments are compatible with Hive queries. The hints embedded within `/* */` comments or `[]` square brackets are not recognized by or not compatible with Hive. For example, Hive raises an error for Impala hints within `/* */` comments because it does not recognize the Impala hint names.

Considerations for views:

If you use a hint in the query that defines a view, the hint is preserved when you query the view. Impala internally rewrites all hints in views to use the `--` comment notation, so that Hive can query such views without errors due to unrecognized hint names.

Examples:

For example, this query joins a large customer table with a small lookup table of less than 100 rows. The right-hand table can be broadcast efficiently to all nodes involved in the join. Thus, you would use the `/* +broadcast */` hint to force a broadcast join strategy:

```
select straight_join customer.address, state_lookup.state_name
  from customer join /* +broadcast */ state_lookup
    on customer.state_id = state_lookup.state_id;
```

This query joins two large tables of unpredictable size. You might benchmark the query with both kinds of hints and find that it is more efficient to transmit portions of each table to other nodes for processing. Thus, you would use the `/* +shuffle */` hint to force a partitioned join strategy:

```
select straight_join weather.wind_velocity, geospatial.altitude
  from weather join /* +shuffle */ geospatial
    on weather.lat = geospatial.lat and weather.long = geospatial.long;
```

For joins involving three or more tables, the hint applies to the tables on either side of that specific `JOIN` keyword. The `STRAIGHT_JOIN` keyword ensures that joins are processed in a predictable order from left to right. For example, this query joins `t1` and `t2` using a partitioned join, then joins that result set to `t3` using a broadcast join:

```
select straight_join t1.name, t2.id, t3.price
  from t1 join /* +shuffle */ t2 join /* +broadcast */ t3
    on t1.id = t2.id and t2.id = t3.id;
```

Related information:

For more background information about join queries, see [Joins in Impala SELECT Statements](#) on page 318. For performance considerations, see [Performance Considerations for Join Queries](#) on page 618.

Impala Built-In Functions

Impala supports several categories of built-in functions. These functions let you perform mathematical calculations, string manipulation, date calculations, and other kinds of data transformations directly in SQL statements.

The categories of functions supported by Impala are:

- [*Impala Mathematical Functions*](#) on page 434
- [*Impala Type Conversion Functions*](#) on page 467
- [*Impala Date and Time Functions*](#) on page 478
- [*Impala Conditional Functions*](#) on page 502
- [*Impala String Functions*](#) on page 509
- [*Impala Aggregate Functions*](#) on page 539
- [*Impala Analytic Functions*](#) on page 569
- [*Impala Bit Functions*](#) on page 455
- [*Impala Miscellaneous Functions*](#) on page 535

The following is a list of built-in functions supported in Impala:

[*ABS*](#)
[*ACOS*](#)
[*ADD_MONTHS*](#)
[*ADDDATE*](#)
[*APPX_MEDIAN*](#)
[*ASCII*](#)
[*ASIN*](#)
[*ATAN*](#)
[*ATAN2*](#)
[*AVG*](#)
[*AVG - Analytic Function*](#)
[*BASE64DECODE*](#)
[*BASE64ENCODE*](#)
[*BITAND*](#)
[*BIN*](#)
[*BITNOT*](#)
[*BITOR*](#)
[*BITXOR*](#)
[*BTRIM*](#)
[*CASE*](#)
[*CASE WHEN*](#)
[*CAST*](#)
[*CEIL, CEILING, DCEIL*](#)
[*CHAR_LENGTH*](#)
[*CHR*](#)

COALESCE

CONCAT

CONCAT_WS

CONV

COS

COSH

COT

COUNT

COUNT - Analytic Function

COUNTSET

CUME_DIST

CURRENT_DATABASE

CURRENT_TIMESTAMP

DATE_ADD

DATE_PART

DATE_SUB

DATE_TRUNC

DATEDIFF

DAY

DAYNAME

DAYOFWEEK

DAYOFYEAR

DAYS_ADD

DAYS_SUB

DECODE

DEGREES

DENSE_RANK

E

EFFECTIVE_USER

EXP

EXTRACT

FACTORIAL

FIND_IN_SET

FIRST_VALUE

FLOOR, DFLOOR

FMOD

FNV_HASH

FROM_UNIXTIME

FROM_TIMESTAMP

FROM_UTC_TIMESTAMP

GET_JSON_OBJECT

GETBIT

GREATEST

GROUP_CONCAT

GROUP_CONCAT - *Analytic Function*

HEX

HOUR

HOURS_ADD

HOURS_SUB

IF

IFNULL

INITCAP

INSTR

INT_MONTHS_BETWEEN

IS_INF

IS_NAN

ISFALSE

ISNOTFALSE

ISNOTTRUE

ISNULL

ISTRUE

JARO_DISTANCE, JARO_DIST

JARO_SIMILARITY, JARO_SIM

JARO_WINKER_DISTANCE, JW_DST

JARO_WINKER_SIMILARITY, JW_SIM

LAG

LAST_VALUE

LEAD

LEAST

LEFT

LENGTH

LN

LOCATE

LOG

LOG10

LOG2

LOWER, LCASE

LPAD

LTRIM

MAX

MAX - Analytic Function

MAX_INT, MAX_TINYINT, MAX_SMALLINT, MAX_BIGINT

MICROSECONDS_ADD

MICROSECONDS_SUB

MILLISECOND

MILLISECONDS_ADD

MILLISECONDS_SUB

MIN

MIN - Analytic Function

MIN_INT, MIN_TINYINT, MIN_SMALLINT, MIN_BIGINT

MINUTE

MINUTES_ADD

MINUTES_SUB

MOD

MONTH

MONTHNAME

MONTHS_ADD

MONTHS_BETWEEN

MONTHS_SUB

MURMUR_HASH

NANOSECONDS_ADD

NANOSECONDS_SUB

NDV

NEGATIVE

NEXT_DAY

NONNULLVALUE

NOW

NTILE

NULLIF

NULLIFZERO

NULLVALUE

NVL

NVL2

OVER Clause

PARSE_URL

PERCENT_RANK

PI

PID

PMOD

POSITIVE

POW, POWER, DPOW, FPOW

PRECISION

PRETTYPRINT_BYTES

QUARTER

QUOTIENT

RADIANS

RAND, RANDOM

RANK

REGEXP_ESCAPE

REGEXP_EXTRACT

REGEXP_LIKE

REGEXP_REPLACE

REPEAT

REPLACE

REVERSE

RIGHT

ROTATELEFT

ROTATERIGHT

ROUND, DROUND

ROW_NUMBER

RPAD

RTRIM

SCALE

SECOND

SECONDS_ADD

SECONDS_SUB

SETBIT

SHIFTLEFT

SHIFTRIGHT

SIGN

SIN

SINH

SLEEP

SPACE

SPLIT_PART

SQRT

STDDEV, STDDEV_SAMP, STDDEV_POP

STRLEFT

STRRIGHT

SUBDATE

SUBSTR, SUBSTRING

SUM

SUM - Analytic Function

TAN

TANH

TIMEOFDAY

TIMESTAMP_CMP

TO_DATE

TO_TIMESTAMP

TO_UTC_TIMESTAMP

TRANSLATE

TRIM

TRUNC

TRUNCATE, DTRUNC, TRUNC

TYPEOF

UNHEX

UNIX_TIMESTAMP

UPPER, UCASE

USER

UTC_TIMESTAMP

UUID

VARIANCE, VARIANCE_SAMP, VARIANCE_POP, VAR_SAMP, VAR_POP

VERSION

WEEKOFYEAR

WEEKS_ADD

[*WEEKS_SUB*](#)[*WIDTH_BUCKET*](#)[*YEAR*](#)[*YEARS_ADD*](#)[*YEARS_SUB*](#)[*ZEROIFNULL*](#)

Impala Mathematical Functions

Mathematical functions, or arithmetic functions, perform numeric calculations that are typically more complex than basic addition, subtraction, multiplication, and division. For example, these functions include trigonometric, logarithmic, and base conversion operations.

Note: In Impala, exponentiation uses the `pow()` function rather than an exponentiation operator such as `**`.

Related information:

The mathematical functions operate mainly on these data types: [INT Data Type](#) on page 118, [BIGINT Data Type](#) on page 106, [SMALLINT Data Type](#) on page 124, [TINYINT Data Type](#) on page 139, [DOUBLE Data Type](#) on page 116, [FLOAT Data Type](#) on page 117, and [DECIMAL Data Type \(Impala 3.0 or higher only\)](#) on page 111. For the operators that perform the standard operations such as addition, subtraction, multiplication, and division, see [Arithmetic Operators](#) on page 178.

Functions that perform bitwise operations are explained in [Impala Bit Functions](#) on page 455.

Function reference:

Impala supports the following mathematical functions:

- [*ABS*](#)
- [*ACOS*](#)
- [*ASIN*](#)
- [*ATAN*](#)
- [*ATAN2*](#)
- [*BIN*](#)
- [*CEIL, CEILING, DCEIL*](#)
- [*CONV*](#)
- [*COS*](#)
- [*COSH*](#)
- [*COT*](#)
- [*DEGREES*](#)
- [*E*](#)
- [*EXP*](#)
- [*FACTORIAL*](#)
- [*FLOOR, DFLOOR*](#)
- [*FMOD*](#)
- [*FNV_HASH*](#)
- [*GREATEST*](#)
- [*HEX*](#)
- [*IS_INF*](#)
- [*IS_NAN*](#)
- [*LEAST*](#)
- [*LN*](#)
- [*LOG*](#)

- *LOG10*
- *LOG2*
- *MAX_INT, MAX_TINYINT, MAX_SMALLINT, MAX_BIGINT*
- *MIN_INT, MIN_TINYINT, MIN_SMALLINT, MIN_BIGINT*
- *MOD*
- *MURMUR_HASH*
- *NEGATIVE*
- *PI*
- *PMOD*
- *POSITIVE*
- *POW, POWER, DPOW, FPOW*
- *PRECISION*
- *QUOTIENT*
- *RADIANS*
- *RAND, RANDOM*
- *ROUND, DROUND*
- *SCALE*
- *SIGN*
- *SIN*
- *SINH*
- *SQRT*
- *TAN*
- *TANH*
- *TRUNCATE, DTRUNC, TRUNC*
- *UNHEX*
- *WIDTH_BUCKET*

ABS(numeric_type a)

Purpose: Returns the absolute value of the argument.

Return type: Same as the input value

Usage notes: Use this function to ensure all return values are positive. This is different than the `POSITIVE()` function, which returns its argument unchanged (even if the argument was negative).

ACOS(DOUBLE a)

Purpose: Returns the arccosine of the argument.

Return type: DOUBLE

ASIN(DOUBLE a)

Purpose: Returns the arcsine of the argument.

Return type: DOUBLE

ATAN(DOUBLE a)

Purpose: Returns the arctangent of the argument.

Return type: DOUBLE

ATAN2(DOUBLE a, DOUBLE b)

Purpose: Returns the arctangent of the two arguments, with the signs of the arguments used to determine the quadrant of the result.

Return type: DOUBLE

BIN(BIGINT a)

Purpose: Returns the binary representation of an integer value, that is, a string of 0 and 1 digits.

**CEIL(DOUBLE a), CEIL(DECIMAL(p,s) a),
CEILING(DOUBLE a), CEILING(DECIMAL(p,s)
a), DCEIL(DOUBLE a), DCEIL(DECIMAL(p,s) a)**

**CONV(BIGINT n, INT from_base, INT to_base),
CONV(STRING s, INT from_base, INT to_base)**

Return type: STRING

Purpose: Returns the smallest integer that is greater than or equal to the argument.

Return type: Same as the input value

Purpose: Returns a string representation of the first argument converted from `from_base` to `to_base`. The first argument can be specified as a number or a string. For example, `CONV(100, 2, 10)` and `CONV('100', 2, 10)` both return '4'.

Return type: STRING

Usage notes:

If `to_base` is negative, the first argument is treated as signed, and otherwise, it is treated as unsigned. For example:

- `conv(-17, 10, -2)` returns '-10001', -17 in base 2.
- `conv(-17, 10, 10)` returns '18446744073709551599'. -17 is interpreted as an unsigned, $2^{64}-17$, and then the value is returned in base 10.

The function returns NULL when the following illegal arguments are specified:

- Any argument is NULL.
- `from_base` or `to_base` is below -36 or above 36.
- `from_base` or `to_base` is -1, 0, or 1.
- The first argument represents a positive number and `from_base` is a negative number.

If the first argument represents a negative number and `from_base` is a negative number, the function returns 0.

If the first argument represents a number larger than the maximum `bigint`, the function returns:

- The string representation of -1 in `to_base` if `to_base` is negative.
- The string representation of 18446744073709551615' ($2^{64} - 1$) in `to_base` if `to_base` is positive.

If the first argument does not represent a valid number in `from_base`, e.g. 3 in base 2 or '1a23' in base 10, the digits in the first argument are evaluated from left-to-right and used if a valid digit in `from_base`. The invalid digit and the digits to the right are ignored.

For example:

- `conv(445, 5, 10)` is converted to `conv(44, 5, 10)` and returns '24'.

COS(DOUBLE a)

COSH(DOUBLE a)

COT(DOUBLE a)

DEGREES(DOUBLE a)

E()

EXP(DOUBLE a), DEXP(DOUBLE a)

FACTORIAL(integer_type a)

- `conv('1a23', 10, 16)` is converted to `conv('1', 10, 16)` and returns '1'.

Purpose: Returns the cosine of the argument.

Return type: DOUBLE

Purpose: Returns the hyperbolic cosine of the argument.

Return type: DOUBLE

Purpose: Returns the cotangent of the argument.

Return type: DOUBLE

Added in: Impala 2.3.0

Purpose: Converts argument value from radians to degrees.

Return type: DOUBLE

Purpose: Returns the *mathematical constant e*.

Return type: DOUBLE

Purpose: Returns the *mathematical constant e* raised to the power of the argument.

Return type: DOUBLE

Purpose: Computes the *factorial* of an integer value. It works with any integer type.

Added in: Impala 2.3.0

Usage notes: You can use either the `factorial()` function or the `!` operator. The factorial of 0 is 1. Likewise, the `factorial()` function returns 1 for any negative value. The maximum positive value for the input argument is 20; a value of 21 or greater overflows the range for a BIGINT and causes an error.

Return type: BIGINT

Added in: Impala 2.3.0

```
select factorial(5);
+-----+
| factorial(5) |
+-----+
| 120          |
+-----+

select 5!;
+-----+
| 5!      |
+-----+
| 120     |
+-----+

select factorial(0);
+-----+
| factorial(0) |
+-----+
| 1           |
+-----+
```

```

+-----+
select factorial(-100);
+-----+
| factorial(-100) |
+-----+
| 1               |
+-----+

```

**FLOOR(DOUBLE a), FLOOR(DECIMAL(p,s) a),
DFLOOR(DOUBLE a), DFLOOR(DECIMAL(p,s) a)**

Purpose: Returns the largest integer that is less than or equal to the argument.

Return type: Same as the input type

**FMOD(DOUBLE a, DOUBLE b), FMOD(FLOAT a,
FLOAT b)**

Purpose: Returns the modulus of a floating-point number.

Return type: FLOAT or DOUBLE, depending on type of arguments

Added in: Impala 1.1.1

Usage notes:

Because this function operates on DOUBLE or FLOAT values, it is subject to potential rounding errors for values that cannot be represented precisely. Prefer to use whole numbers, or values that you know can be represented precisely by the DOUBLE or FLOAT types.

Examples:

The following examples show equivalent operations with the `fmod()` function and the `%` arithmetic operator, for values not subject to any rounding error.

```

select fmod(10,3);
+-----+
| fmod(10, 3) |
+-----+
| 1           |
+-----+

select fmod(5.5,2);
+-----+
| fmod(5.5, 2) |
+-----+
| 1.5          |
+-----+

select 10 % 3;
+-----+
| 10 % 3 |
+-----+
| 1      |
+-----+

select 5.5 % 2;
+-----+
| 5.5 % 2 |
+-----+
| 1.5     |
+-----+

```

The following examples show operations with the `fmod()` function for values that cannot be represented precisely by the `DOUBLE` or `FLOAT` types, and thus are subject to rounding error. `fmod(9.9, 3.0)` returns a value slightly different than the expected 0.9 because of rounding. `fmod(9.9, 3.3)` returns a value quite different from the expected value of 0 because of rounding error during intermediate calculations.

```
select fmod(9.9,3.0);
+-----+
| fmod(9.9, 3.0) |
+-----+
| 0.89999996185302734 |
+-----+

select fmod(9.9,3.3);
+-----+
| fmod(9.9, 3.3) |
+-----+
| 3.2999999713897705 |
+-----+
```

FNV_HASH(type v),

Purpose: Returns a consistent 64-bit value derived from the input argument, for convenience of implementing hashing logic in an application.

Return type: `BIGINT`

Usage notes:

You might use the return value in an application where you perform load balancing, bucketing, or some other technique to divide processing or storage.

Because the result can be any 64-bit value, to restrict the value to a particular range, you can use an expression that includes the `ABS()` function and the `%` (modulo) operator. For example, to produce a hash value in the range 0-9, you could use the expression `ABS(FNV_HASH(x)) % 10`.

This function implements the same algorithm that Impala uses internally for hashing, on systems where the CRC32 instructions are not available.

This function implements the [Fowler–Noll–Vo hash function](#), in particular the FNV-1a variation. This is not a perfect hash function: some combinations of values could produce the same result value. It is not suitable for cryptographic use.

Similar input values of different types could produce different hash values, for example the same numeric value represented as `SMALLINT` or `BIGINT`, `FLOAT` or `DOUBLE`, or `DECIMAL(5, 2)` or `DECIMAL(20, 5)`.

Examples:

```
[localhost:21000] > create table h
(x int, s string);
```

```
[localhost:21000] > insert into h
values (0, 'hello'), (1, 'world'),
(1234567890, 'antidisestablishmentarianism');
[localhost:21000] > select x,
fnv_hash(x) from h;
```

x	fnv_hash(x)
0	-2611523532599129963
1	4307505193096137732
1234567890	3614724209955230832

```
[localhost:21000] > select s,
fnv_hash(s) from h;
```

s	fnv_hash(s)
hello	6414202926103426347
world	6535280128821139475
antidisestablishmentarianism	-209330013948433970

```
[localhost:21000] > select s,
abs(fnv_hash(s)) % 10 from h;
```

s	abs(fnv_hash(s)) % 10.0
hello	8
world	6
antidisestablishmentarianism	4

For short argument values, the high-order bits of the result have relatively low entropy:

```
[localhost:21000] > create table b
(x boolean);
[localhost:21000] > insert into b
values (true), (true), (false),
(false);
[localhost:21000] > select x,
fnv_hash(x) from b;
```


x	fnv_hash(x)
true	2062020650953872396
true	2062020650953872396
false	2062021750465500607
false	2062021750465500607

Added in: Impala 1.2.2

GREATEST(BIGINT a[, BIGINT b ...]),
GREATEST(DOUBLE a[, DOUBLE b ...]),
GREATEST(DECIMAL(p,s) a[, DECIMAL(p,s)
b ...]), **GREATEST**(STRING a[, STRING b ...]),
GREATEST(TIMESTAMP a[, TIMESTAMP b ...])

Purpose: Returns the largest value from a list of expressions.

Return type: same as the initial argument value, except that integer values are promoted to BIGINT and floating-point values are promoted to DOUBLE; use CAST () when inserting into a smaller numeric column

HEX(BIGINT a), **HEX**(STRING a)

Purpose: Returns the hexadecimal representation of an integer value, or of the characters in a string.

Return type: STRING

IS_INF(DOUBLE a)

Purpose: Tests whether a value is equal to the special value “inf”, signifying infinity.

Return type: BOOLEAN

Usage notes:

Infinity and NaN can be specified in text data files as `inf` and `nan` respectively, and Impala interprets them as these special values. They can also be produced by certain arithmetic expressions; for example, `1/0` returns `Infinity` and `pow(-1, 0.5)` returns `NaN`. Or you can cast the literal values, such as `CAST('nan' AS DOUBLE)` or `CAST('inf' AS DOUBLE)`.

IS_NAN(DOUBLE a)

Purpose: Tests whether a value is equal to the special value “NaN”, signifying “not a number”.

Return type: BOOLEAN

Usage notes:

Infinity and NaN can be specified in text data files as `inf` and `nan` respectively, and Impala interprets them as these special values. They can also be produced by certain arithmetic expressions; for example, `1/0` returns `Infinity` and `pow(-1, 0.5)` returns `NaN`. Or you can cast the literal values, such as `CAST('nan' AS DOUBLE)` or `CAST('inf' AS DOUBLE)`.

LEAST(BIGINT a[, BIGINT b ...]),
LEAST(DOUBLE a[, DOUBLE b ...]),
LEAST(DECIMAL(p,s) a[, DECIMAL(p,s)
b ...]), **LEAST**(STRING a[, STRING b ...]),
LEAST(TIMESTAMP a[, TIMESTAMP b ...])

Purpose: Returns the smallest value from a list of expressions.

Return type: same as the initial argument value, except that integer values are promoted to BIGINT and floating-point values are promoted to DOUBLE; use CAST () when inserting into a smaller numeric column

LN(DOUBLE a), **DLOG1**(DOUBLE a)

Purpose: Returns the *natural logarithm* of the argument.

LOG(DOUBLE base, DOUBLE a)

Return type: DOUBLE

Purpose: Returns the logarithm of the second argument to the specified base.

Return type: DOUBLE

LOG10(DOUBLE a), DLOG10(DOUBLE a)

Purpose: Returns the logarithm of the argument to the base 10.

Return type: DOUBLE

LOG2(DOUBLE a)

Purpose: Returns the logarithm of the argument to the base 2.

Return type: DOUBLE

**MAX_INT(), MAX_TINYINT(),
MAX_SMALLINT(), MAX_BIGINT()**

Purpose: Returns the largest value of the associated integral type.

Return type: The same as the integral type being checked.

Usage notes: Use the corresponding `min_` and `max_` functions to check if all values in a column are within the allowed range, before copying data or altering column definitions. If not, switch to the next higher integral type or to a `DECIMAL` with sufficient precision.

**MIN_INT(), MIN_TINYINT(), MIN_SMALLINT(),
MIN_BIGINT()**

Purpose: Returns the smallest value of the associated integral type (a negative number).

Return type: The same as the integral type being checked.

Usage notes: Use the corresponding `min_` and `max_` functions to check if all values in a column are within the allowed range, before copying data or altering column definitions. If not, switch to the next higher integral type or to a `DECIMAL` with sufficient precision.

MOD(numeric_type a, same_type b)

Purpose: Returns the modulus of a number. Equivalent to the `%` arithmetic operator. Works with any size integer type, any size floating-point type, and `DECIMAL` with any precision and scale.

Return type: Same as the input value

Added in: Impala 2.2.0

Usage notes:

Because this function works with `DECIMAL` values, prefer it over `fmod()` when working with fractional values. It is not subject to the rounding errors that make `fmod()` problematic with floating-point numbers.

Query plans shows the `MOD()` function as the `%` operator.

Examples:

The following examples show how the `mod()` function works for whole numbers and fractional values, and how the `%` operator works the same way. In the case

of `mod(9.9, 3)`, the type conversion for the second argument results in the first argument being interpreted as `DOUBLE`, so to produce an accurate `DECIMAL` result requires casting the second argument or writing it as a `DECIMAL` literal, `3.0`.

```
select mod(10,3);
```

```
+-----+
| mod(10, 3) |
+-----+
| 1          |
+-----+
```

```
select mod(5.5,2);
```

```
+-----+
| mod(5.5, 2) |
+-----+
| 1.5         |
+-----+
```

```
select 10 % 3;
```

```
+-----+
| 10 % 3      |
+-----+
| 1           |
+-----+
```

```
select 5.5 % 2;
```

```
+-----+
| 5.5 % 2     |
+-----+
| 1.5         |
+-----+
```

```
select mod(9.9,3.3);
```

```
+-----+
| mod(9.9, 3.3) |
+-----+
| 0.0           |
+-----+
```

```
select mod(9.9,3);
```

```
+-----+
| mod(9.9, 3)   |
+-----+
| 0.8999996185302734 |
+-----+
```

```
select mod(9.9, cast(3 as
  decimal(2,1)));
```

```
+-----+
+
| mod(9.9, cast(3 as decimal(2,1))) |
+-----+
+
| 0.9 |
+-----+
+
```

```
select mod(9.9,3.0);
```

```
+-----+
```

```

| mod(9.9, 3.0) |
+-----+
| 0.9           |
+-----+

```

MURMUR_HASH(type v)

Purpose: Returns a consistent 64-bit value derived from the input argument, for convenience of implementing *MurmurHash2* non-cryptographic hash function.

Return type: BIGINT

Usage notes:

You might use the return value in an application where you perform load balancing, bucketing, or some other technique to divide processing or storage. This function provides a good performance for all kinds of keys such as number, ascii string and UTF-8. It can be recommended as general-purpose hashing function.

Regarding comparison of murmur_hash with fnv_hash, murmur_hash is based on Murmur2 hash algorithm and fnv_hash function is based on FNV-1a hash algorithm. Murmur2 and FNV-1a can show very good randomness and performance compared with well known other hash algorithms, but Murmur2 slightly show better randomness and performance than FNV-1a. See [\[1\]\[2\]\[3\]](#) for details.

Similar input values of different types could produce different hash values, for example the same numeric value represented as SMALLINT or BIGINT, FLOAT or DOUBLE, or DECIMAL(5, 2) or DECIMAL(20, 5).

Examples:

```

[localhost:21000] > create table h
(x int, s string);
[localhost:21000] > insert into h
values (0, 'hello'), (1, 'world'),
(1234567890, 'antidisestablishmentarianism');
[localhost:21000] > select x,
murmur_hash(x) from h;
+-----+-----+
| x          | murmur_hash(x) |
+-----+-----+
| 0          | 6960269033020761575 |
| 1          | -780611581681153783 |
| 1234567890 | -5754914572385924334 |
+-----+-----+
[localhost:21000] > select s,
murmur_hash(s) from h;
+-----+

```

s	murmur_hash(s)
hello	2191231550387646743
world	5568329560871645431
antidisestablishmentarianism	-2261804666958489663

For short argument values, the high-order bits of the result have relatively higher entropy than fnv_hash:

```
[localhost:21000] > create table b
(x boolean);
[localhost:21000] > insert into b
values (true), (true), (false),
(false);
[localhost:21000] > select x,
murmur_hash(x) from b;
```

x	murmur_hash(x)
true	-5720937396023583481
true	-5720937396023583481
false	6351753276682545529
false	6351753276682545529

Added in: Impala 2.12.0

NEGATIVE(numeric_type a)

Purpose: Returns the argument with the sign reversed; returns a positive value if the argument was already negative.

Return type: Same as the input value

Usage notes: Use `-ABS (a)` instead if you need to ensure all return values are negative.

PI()

Purpose: Returns the constant pi.

Return type: DOUBLE

PMOD(BIGINT a, BIGINT b), PMOD(DOUBLE a, DOUBLE b)

Purpose: Returns the positive modulus of a number. Primarily for [HiveQL compatibility](#).

Return type: INT or DOUBLE, depending on type of arguments

Examples:

The following examples show how the `FMOD ()` function sometimes returns a negative value depending on the sign of its arguments, and the `PMOD ()` function returns the same value as `FMOD ()`, but sometimes with the sign flipped.

```
select fmod(-5,2);
+-----+
```

```

| fmod(-5, 2) |
+-----+
| -1          |
+-----+

select pmod(-5,2);
+-----+
| pmod(-5, 2) |
+-----+
| 1           |
+-----+

select fmod(-5,-2);
+-----+
| fmod(-5, -2) |
+-----+
| -1           |
+-----+

select pmod(-5,-2);
+-----+
| pmod(-5, -2) |
+-----+
| -1           |
+-----+

select fmod(5,-2);
+-----+
| fmod(5, -2)  |
+-----+
| 1            |
+-----+

select pmod(5,-2);
+-----+
| pmod(5, -2)  |
+-----+
| -1           |
+-----+

```

POSITIVE(numeric_type a)

Purpose: Returns the original argument unchanged (even if the argument is negative).

Return type: Same as the input value

Usage notes: Use `ABS()` instead if you need to ensure all return values are positive.

POW(DOUBLE a, DOUBLE p), POWER(DOUBLE a, DOUBLE p), DPOW(DOUBLE a, DOUBLE p), FPOW(DOUBLE a, DOUBLE p)

Purpose: Returns the first argument raised to the power of the second argument.

Return type: DOUBLE

PRECISION(numeric_expression)

Purpose: Computes the precision (number of decimal digits) needed to represent the type of the argument expression as a DECIMAL value.

Usage notes:

Typically used in combination with the `SCALE()` function, to determine the appropriate `DECIMAL(precision, scale)` type to declare in a `CREATE TABLE` statement or `CAST()` function.

Return type: INT

Examples:

The following examples demonstrate how to check the precision and scale of numeric literals or other numeric expressions. Impala represents numeric literals in the smallest appropriate type. 5 is a TINYINT value, which ranges from -128 to 127, therefore 3 decimal digits are needed to represent the entire range, and because it is an integer value there are no fractional digits. 1.333 is interpreted as a DECIMAL value, with 4 digits total and 3 digits after the decimal point.

```
[localhost:21000] > select
precision(5), scale(5);
+-----+-----+
| precision(5) | scale(5) |
+-----+-----+
| 3           | 0        |
+-----+-----+
[localhost:21000] > select
precision(1.333), scale(1.333);
+-----+-----+
| precision(1.333) | scale(1.333) |
+-----+-----+
| 4               | 3            |
+-----+-----+
[localhost:21000] > with t1 as
( select cast(12.34 as
decimal(20,2)) x union select
cast(1 as decimal(8,6)) x )
select precision(x), scale(x) from
t1 limit 1;
+-----+-----+
| precision(x) | scale(x) |
+-----+-----+
| 24          | 6        |
+-----+-----+
```

QUOTIENT(BIGINT numerator, BIGINT denominator), QUOTIENT(DOUBLE numerator, DOUBLE denominator)

Purpose: Returns the first argument divided by the second argument, discarding any fractional part. Avoids promoting integer arguments to DOUBLE as happens with the / SQL operator. Also includes an overload that accepts DOUBLE arguments, discards the fractional part of each argument value before dividing, and again returns BIGINT. With integer arguments, this function works the same as the DIV operator.

Return type: BIGINT

RADIANS(DOUBLE a)

Purpose: Converts argument value from degrees to radians.

Return type: DOUBLE

RAND(), RAND(BIGINT seed), RANDOM(), RANDOM(BIGINT seed)

Purpose: Returns a random value between 0 and 1. After RAND() is called with a seed argument, it produces a consistent random sequence based on the seed value.

Return type: DOUBLE

Usage notes: Currently, the random sequence is reset after each query, and multiple calls to `RAND()` within the same query return the same value each time. For different number sequences that are different for each query, pass a unique seed value to each call to `RAND()`. For example, `SELECT RAND(UNIX_TIMESTAMP())` FROM ...

Examples:

The following examples show how `rand()` can produce sequences of varying predictability, so that you can reproduce query results involving random values or generate unique sequences of random values for each query. When `rand()` is called with no argument, it generates the same sequence of values each time, regardless of the ordering of the result set. When `rand()` is called with a constant integer, it generates a different sequence of values, but still always the same sequence for the same seed value. If you pass in a seed value that changes, such as the return value of the expression `unix_timestamp(now())`, each query will use a different sequence of random values, potentially more useful in probability calculations although more difficult to reproduce at a later time. Therefore, the final two examples with an unpredictable seed value also include the seed in the result set, to make it possible to reproduce the same random sequence later.

```
select x, rand() from three_rows;
```

x	rand()
1	0.0004714746030380365
2	0.5895895192351144
3	0.4431900859080209

```
select x, rand() from three_rows
order by x desc;
```

x	rand()
3	0.0004714746030380365
2	0.5895895192351144
1	0.4431900859080209

```
select x, rand(1234) from three_rows
order by x;
```

x	rand(1234)
1	0.7377511392057646
2	0.009428468537250751
3	0.208117277924026

```
select x, rand(1234) from three_rows
order by x desc;
```

x	rand(1234)
3	0.7377511392057646
2	0.009428468537250751
1	0.208117277924026


```

| x | rand(1234) |
+---+-----+
| 3 | 0.7377511392057646 |
| 2 | 0.009428468537250751 |
| 1 | 0.208117277924026 |
+---+-----+

select x, unix_timestamp(now()),
       rand(unix_timestamp(now()))
from three_rows order by x;
+---+-----+
| x | unix_timestamp(now()) |
   rand(unix_timestamp(now())) |
+---+-----+
| 1 | 1440777752           |
   0.002051228658320023 |
| 2 | 1440777752           |
   0.5098743483004506 |
| 3 | 1440777752           |
   0.9517714925817081 |
+---+-----+

select x, unix_timestamp(now()),
       rand(unix_timestamp(now()))
from three_rows order by x desc;
+---+-----+
| x | unix_timestamp(now()) |
   rand(unix_timestamp(now())) |
+---+-----+
| 3 | 1440777761           |
   0.9985985015512437 |
| 2 | 1440777761           |
   0.3251255333074953 |
| 1 | 1440777761           |
   0.02422675025846192 |
+---+-----+

```

ROUND(DOUBLE a), ROUND(DOUBLE a, INT d), ROUND(DECIMAL a, int_type d), DROUND(DOUBLE a), DROUND(DOUBLE a, INT d), DROUND(DECIMAL(p,s) a, int_type d)

Purpose: Rounds a floating-point value. By default (with a single argument), rounds to the nearest integer. Values ending in .5 are rounded up for positive numbers, down for negative numbers (that is, away from zero). The optional second argument specifies how many digits to leave after the decimal point; values greater than zero produce a floating-point return value rounded to the requested number of digits to the right of the decimal point.

Return type: Same as the input type

SCALE(numeric_expression)

Purpose: Computes the scale (number of decimal digits to the right of the decimal point) needed to represent the type of the argument expression as a DECIMAL value.

Usage notes:

Typically used in combination with the `PRECISION()` function, to determine the appropriate `DECIMAL(precision,scale)` type to declare in a `CREATE TABLE` statement or `CAST()` function.

Return type: INT

Examples:

The following examples demonstrate how to check the precision and scale of numeric literals or other numeric expressions. Impala represents numeric literals in the smallest appropriate type. 5 is a TINYINT value, which ranges from -128 to 127, therefore 3 decimal digits are needed to represent the entire range, and because it is an integer value there are no fractional digits. 1.333 is interpreted as a DECIMAL value, with 4 digits total and 3 digits after the decimal point.

```
[localhost:21000] > select
precision(5), scale(5);
+-----+-----+
| precision(5) | scale(5) |
+-----+-----+
| 3           | 0        |
+-----+-----+
[localhost:21000] > select
precision(1.333), scale(1.333);
+-----+-----+
| precision(1.333) | scale(1.333) |
+-----+-----+
| 4               | 3            |
+-----+-----+
[localhost:21000] > with t1 as
( select cast(12.34 as
decimal(20,2)) x union select
cast(1 as decimal(8,6)) x )
select precision(x), scale(x) from
t1 limit 1;
+-----+-----+
| precision(x) | scale(x) |
+-----+-----+
| 24          | 6        |
+-----+-----+
```

SIGN(DOUBLE a)

Purpose: Returns -1, 0, or 1 to indicate the signedness of the argument value.

Return type: INT

SIN(DOUBLE a)

Purpose: Returns the sine of the argument.

Return type: DOUBLE

SINH(DOUBLE a)

Purpose: Returns the hyperbolic sine of the argument.

Return type: DOUBLE

SQRT(DOUBLE a), DSQRT(DOUBLE a)

Purpose: Returns the square root of the argument.

Return type: DOUBLE

TAN(DOUBLE a)

Purpose: Returns the tangent of the argument.

TANH(DOUBLE a)

**TRUNCATE(DOUBLE_or_DECIMAL
a[, digits_to_leave]),
DTRUNC(DOUBLE_or_DECIMAL a[,
digits_to_leave]), TRUNC(DOUBLE_or_DECIMAL
a[, digits_to_leave])**

Return type: DOUBLE

Purpose: Returns the hyperbolic tangent of the argument.

Return type: DOUBLE

Purpose: Removes some or all fractional digits from a numeric value.

Arguments: With a single floating-point argument, removes all fractional digits, leaving an integer value. The optional second argument specifies the number of fractional digits to include in the return value, and only applies when the argument type is DECIMAL. A second argument of 0 truncates to a whole integer value. A second argument of negative N sets N digits to 0 on the left side of the decimal

Scale argument: The scale argument applies only when truncating DECIMAL values. It is an integer specifying how many significant digits to leave to the right of the decimal point. A scale argument of 0 truncates to a whole integer value. A scale argument of negative N sets N digits to 0 on the left side of the decimal point.

TRUNCATE (), DTRUNC (), and TRUNC () are aliases for the same function.

Return type: Same as the input type

Added in: The TRUNC () alias was added in Impala 2.10.

Usage notes:

You can also pass a DOUBLE argument, or DECIMAL argument with optional scale, to the DTRUNC () or TRUNCATE functions. Using the TRUNC () function for numeric values is common with other industry-standard database systems, so you might find such TRUNC () calls in code that you are porting to Impala.

The TRUNC () function also has a signature that applies to TIMESTAMP values. See [Impala Date and Time Functions](#) on page 478 for details.

Examples:

The following examples demonstrate the TRUNCATE () and DTRUNC () signatures for this function:

```
select truncate(3.45);
+-----+
| truncate(3.45) |
+-----+
| 3              |
+-----+

select truncate(-3.45);
+-----+
| truncate(-3.45) |
+-----+
```

```

| -3 |
+-----+

select truncate(3.456,1);
+-----+
| truncate(3.456, 1) |
+-----+
| 3.4 |
+-----+

select dtrunc(3.456,1);
+-----+
| dtrunc(3.456, 1) |
+-----+
| 3.4 |
+-----+

select truncate(3.456,2);
+-----+
| truncate(3.456, 2) |
+-----+
| 3.45 |
+-----+

select truncate(3.456,7);
+-----+
| truncate(3.456, 7) |
+-----+
| 3.4560000 |
+-----+

```

The following examples demonstrate using `trunc()` with `DECIMAL` or `DOUBLE` values, and with an optional scale argument for `DECIMAL` values. (The behavior is the same for the `truncate()` and `dtrunc()` aliases also.)

```

create table t1 (d decimal(20,7));

-- By default, no digits to the
  right of the decimal point.
insert into t1 values (1.1), (2.22),
  (3.333), (4.4444), (5.55555);
select trunc(d) from t1 order by d;
+-----+
| trunc(d) |
+-----+
| 1 |
| 2 |
| 3 |
| 4 |
| 5 |
+-----+

-- 1 digit to the right of the
  decimal point.
select trunc(d,1) from t1 order by
  d;
+-----+
| trunc(d, 1) |
+-----+
| 1.1 |

```

```

| 2.2 |
| 3.3 |
| 4.4 |
| 5.5 |
+-----+

-- 2 digits to the right of the
-- decimal point,
-- including trailing zeroes if
-- needed.
select trunc(d,2) from t1 order by
d;
+-----+
| trunc(d, 2) |
+-----+
| 1.10 |
| 2.22 |
| 3.33 |
| 4.44 |
| 5.55 |
+-----+

insert into t1 values (9999.9999),
(8888.8888);

-- Negative scale truncates digits
-- to the left
-- of the decimal point.
select trunc(d,-2) from t1 where d >
100 order by d;
+-----+
| trunc(d, -2) |
+-----+
| 8800 |
| 9900 |
+-----+

-- The scale of the result is
-- adjusted to match the
-- scale argument.
select trunc(d,2),
precision(trunc(d,2)) as p,
scale(trunc(d,2)) as s
from t1 order by d;
+-----+-----+-----+
| trunc(d, 2) | p | s |
+-----+-----+-----+
| 1.10 | 15 | 2 |
| 2.22 | 15 | 2 |
| 3.33 | 15 | 2 |
| 4.44 | 15 | 2 |
| 5.55 | 15 | 2 |
| 8888.88 | 15 | 2 |
| 9999.99 | 15 | 2 |
+-----+-----+-----+

```

```

create table dbl (d double);

insert into dbl values
(1.1), (2.22), (3.333), (4.4444),
(5.55555),
(8888.8888), (9999.9999);

```

```
-- With double values, there is no
  optional scale argument.
select trunc(d) from dbl order by d;
```

```
+-----+
| trunc(d) |
+-----+
| 1         |
| 2         |
| 3         |
| 4         |
| 5         |
| 8888      |
| 9999      |
+-----+
```

UNHEX(String a)

WIDTH_BUCKET(DECIMAL expr, DECIMAL min_value, DECIMAL max_value, INT num_buckets)

Purpose: Returns a string of characters with ASCII values corresponding to pairs of hexadecimal digits in the argument.

Return type: STRING

Purpose: Returns the bucket number in which the expr value would fall in the histogram where its range between min_value and max_value is divided into num_buckets buckets of identical sizes.

The function returns:

- NULL if any argument is NULL.
- 0 if expr < min_value.
- num_buckets + 1 if expr >= max_val.
- If none of the above, the bucket number where expr falls.

Arguments: The following rules apply to the arguments.

- min_val is the minimum value of the histogram range.
- max_val is the maximum value of the histogram range.
- num_buckets must be greater than 0.
- min_value must be less than max_value.

Usage notes:

Each bucket contains values equal to or greater than the base value of that bucket and less than the base value of the next bucket. For example, with width_bucket(8, 1, 10, 3), the bucket ranges are actually the 0th "underflow bucket" with the range (-infinity to 0.999...), (1 to 3.999...), (4, to 6.999...), (7 to 9.999...), and the "overflow bucket" with the range (10 to infinity).

Return type: BIGINT

Added in: Impala 3.1.

Examples:

The below function creates 3 buckets between the range of 1 and 20 with the bucket width of 6.333, and returns 2 for the bucket #2 where the value 8 falls in:

```
width_bucket(8, 1, 20, 3)
```

The below statement returns a list of accounts with the energy spending and the spending bracket each account falls in, between 0 and 11. Bucket 0 (underflow bucket) will be assigned to the accounts whose energy spendings are less than \$50. Bucket 11 (overflow bucket) will be assigned to the accounts whose energy spendings are more than or equal to \$1000.

```
SELECT account, invoice_amount,
       WIDTH_BUCKET(invoice_amount, 50, 1000, 10)
FROM   invoices_june2018
ORDER BY 3;
```

Impala Bit Functions

Bit manipulation functions perform bitwise operations involved in scientific processing or computer science algorithms. For example, these functions include setting, clearing, or testing bits within an integer value, or changing the positions of bits with or without wraparound.

If a function takes two integer arguments that are required to be of the same type, the smaller argument is promoted to the type of the larger one if required. For example, `BITAND(1, 4096)` treats both arguments as `SMALLINT`, because 1 can be represented as a `TINYINT` but 4096 requires a `SMALLINT`.

Remember that all Impala integer values are signed. Therefore, when dealing with binary values where the most significant bit is 1, the specified or returned values might be negative when represented in base 10.

Whenever any argument is `NULL`, either the input value, bit position, or number of shift or rotate positions, the return value from any of these functions is also `NULL`.

Related information:

The bit functions operate on all the integral data types: [INT Data Type](#) on page 118, [BIGINT Data Type](#) on page 106, [SMALLINT Data Type](#) on page 124, and [TINYINT Data Type](#) on page 139.

Function reference:

Impala supports the following bit functions:

- [BITAND](#)
- [BITNOT](#)
- [BITOR](#)
- [BITXOR](#)
- [COUNTSET](#)
- [GETBIT](#)
- [ROTATELEFT](#)
- [ROTATERIGHT](#)
- [SETBIT](#)
- [SHIFTL](#)
- [SHIFTR](#)

BITAND(integer_type a, same_type b)

Purpose: Returns an integer value representing the bits that are set to 1 in both of the arguments. If the

arguments are of different sizes, the smaller is promoted to the type of the larger.

Usage notes: The `BITAND()` function is equivalent to the `&` binary operator.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

The following examples show the results of ANDing integer values. 255 contains all 1 bits in its lowermost 7 bits. 32767 contains all 1 bits in its lowermost 15 bits. You can use the `BIN()` function to check the binary representation of any integer value, although the result is always represented as a 64-bit value. If necessary, the smaller argument is promoted to the type of the larger one.

```
select bitand(255, 32767); /*
0000000011111111 & 0111111111111111
*/
+-----+
| bitand(255, 32767) |
+-----+
| 255                |
+-----+

select bitand(32767, 1); /*
0111111111111111 & 0000000000000001
*/
+-----+
| bitand(32767, 1) |
+-----+
| 1                 |
+-----+

select bitand(32, 16); /* 00010000 &
00001000 */
+-----+
| bitand(32, 16) |
+-----+
| 0               |
+-----+

select bitand(12,5); /* 00001100 &
00000101 */
+-----+
| bitand(12, 5) |
+-----+
| 4              |
+-----+

select bitand(-1,15); /* 11111111 &
00001111 */
+-----+
| bitand(-1, 15) |
+-----+
| 15             |
+-----+
```


BITNOT(integer_type a)

Purpose: Inverts all the bits of the input argument.

Usage notes: The BITNOT() function is equivalent to the ~ unary operator.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

These examples illustrate what happens when you flip all the bits of an integer value. The sign always changes. The decimal representation is one different between the positive and negative values.

```
select bitnot(127); /* 01111111 ->
10000000 */
+-----+
| bitnot(127) |
+-----+
| -128        |
+-----+

select bitnot(16); /* 00010000 ->
11101111 */
+-----+
| bitnot(16)  |
+-----+
| -17         |
+-----+

select bitnot(0); /* 00000000 ->
11111111 */
+-----+
| bitnot(0)   |
+-----+
| -1          |
+-----+

select bitnot(-128); /* 10000000 ->
01111111 */
+-----+
| bitnot(-128)|
+-----+
| 127         |
+-----+
```

BITOR(integer_type a, same_type b)

Purpose: Returns an integer value representing the bits that are set to 1 in either of the arguments. If the arguments are of different sizes, the smaller is promoted to the type of the larger.

Usage notes: The BITOR() function is equivalent to the | binary operator.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

The following examples show the results of ORing integer values.

```
select bitor(1,4); /* 00000001 |
00000100 */
+-----+
| bitor(1, 4) |
+-----+
| 5            |
+-----+

select bitor(16,48); /* 00001000 |
00011000 */
+-----+
| bitor(16, 48) |
+-----+
| 48            |
+-----+

select bitor(0,7); /* 00000000 |
00000111 */
+-----+
| bitor(0, 7) |
+-----+
| 7           |
+-----+
```

BITXOR(integer_type a, same_type b)

Purpose: Returns an integer value representing the bits that are set to 1 in one but not both of the arguments. If the arguments are of different sizes, the smaller is promoted to the type of the larger.

Usage notes: The BITXOR() function is equivalent to the ^ binary operator.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

The following examples show the results of XORing integer values. XORing a non-zero value with zero returns the non-zero value. XORing two identical values returns zero, because all the 1 bits from the first argument are also 1 bits in the second argument. XORing different non-zero values turns off some bits and leaves others turned on, based on whether the same bit is set in both arguments.

```
select bitxor(0,15); /* 00000000 ^
00001111 */
+-----+
| bitxor(0, 15) |
+-----+
| 15            |
+-----+

select bitxor(7,7); /* 00000111 ^
00000111 */
+-----+
| bitxor(7, 7) |
+-----+
```

```

| 0 |
+---+

select bitxor(8,4); /* 00001000 ^
00000100 */
+---+
| bitxor(8, 4) |
+---+
| 12 |
+---+

select bitxor(3,7); /* 00000011 ^
00000111 */
+---+
| bitxor(3, 7) |
+---+
| 4 |
+---+

```

COUNTSET(integer_type a [, INT zero_or_one])

Purpose: By default, returns the number of 1 bits in the specified integer value. If the optional second argument is set to zero, it returns the number of 0 bits instead.

Usage notes:

In discussions of information theory, this operation is referred to as the “*population count*” or “popcount”.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

The following examples show how to count the number of 1 bits in an integer value.

```

select countset(1); /* 00000001 */
+---+
| countset(1) |
+---+
| 1 |
+---+

select countset(3); /* 00000011 */
+---+
| countset(3) |
+---+
| 2 |
+---+

select countset(16); /* 00010000 */
+---+
| countset(16) |
+---+
| 1 |
+---+

select countset(17); /* 00010001 */
+---+
| countset(17) |
+---+
| 2 |
+---+

```

```

select countset(7,1); /* 00000111
= 3 1 bits; the function counts 1
bits by default */
+-----+
| countset(7, 1) |
+-----+
| 3              |
+-----+

select countset(7,0); /* 00000111 =
5 0 bits; third argument can only
be 0 or 1 */
+-----+
| countset(7, 0) |
+-----+
| 5              |
+-----+

```

GETBIT(integer_type a, INT position)

Purpose: Returns a 0 or 1 representing the bit at a specified position. The positions are numbered right to left, starting at zero. The position argument cannot be negative.

Usage notes:

When you use a literal input value, it is treated as an 8-bit, 16-bit, and so on value, the smallest type that is appropriate. The type of the input value limits the range of the positions. Cast the input value to the appropriate type if you need to ensure it is treated as a 64-bit, 32-bit, and so on value.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

The following examples show how to test a specific bit within an integer value.

```

select getbit(1,0); /* 00000001 */
+-----+
| getbit(1, 0) |
+-----+
| 1            |
+-----+

select getbit(16,1) /* 00010000 */
+-----+
| getbit(16, 1) |
+-----+
| 0            |
+-----+

select getbit(16,4) /* 00010000 */
+-----+
| getbit(16, 4) |
+-----+
| 1            |
+-----+

```

```

select getbit(16,5) /* 00010000 */
+-----+
| getbit(16, 5) |
+-----+
| 0              |
+-----+

select getbit(-1,3); /* 11111111 */
+-----+
| getbit(-1, 3) |
+-----+
| 1              |
+-----+

select getbit(-1,25); /* 11111111 */
ERROR: Invalid bit position: 25

select getbit(cast(-1 as int),25); /
* 11111111111111111111111111111111
*/
+-----+
| getbit(cast(-1 as int), 25) |
+-----+
| 1                              |
+-----+

```

ROTATELEFT(integer_type a, INT positions)

Purpose: Rotates an integer value left by a specified number of bits. As the most significant bit is taken out of the original value, if it is a 1 bit, it is “rotated” back to the least significant bit. Therefore, the final value has the same number of 1 bits as the original value, just in different positions. In computer science terms, this operation is a “*circular shift*”.

Usage notes:

Specifying a second argument of zero leaves the original value unchanged. Rotating a -1 value by any number of positions still returns -1, because the original value has all 1 bits and all the 1 bits are preserved during rotation. Similarly, rotating a 0 value by any number of positions still returns 0. Rotating a value by the same number of bits as in the value returns the same value. Because this is a circular operation, the number of positions is not limited to the number of bits in the input value. For example, rotating an 8-bit value by 1, 9, 17, and so on positions returns an identical result in each case.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

```

select rotateleft(1,4); /* 00000001
-> 00010000 */
+-----+
| rotateleft(1, 4) |
+-----+
| 16                |
+-----+

```

```

select rotateleft(-1,155); /*
11111111 -> 11111111 */
+-----+
| rotateleft(-1, 155) |
+-----+
| -1                  |
+-----+

select rotateleft(-128,1); /*
10000000 -> 00000001 */
+-----+
| rotateleft(-128, 1) |
+-----+
| 1                    |
+-----+

select rotateleft(-127,3); /*
10000001 -> 00001100 */
+-----+
| rotateleft(-127, 3) |
+-----+
| 12                   |
+-----+

```

ROTATERIGHT(integer_type a, INT positions)

Purpose: Rotates an integer value right by a specified number of bits. As the least significant bit is taken out of the original value, if it is a 1 bit, it is “rotated” back to the most significant bit. Therefore, the final value has the same number of 1 bits as the original value, just in different positions. In computer science terms, this operation is a “*circular shift*”.

Usage notes:

Specifying a second argument of zero leaves the original value unchanged. Rotating a -1 value by any number of positions still returns -1, because the original value has all 1 bits and all the 1 bits are preserved during rotation. Similarly, rotating a 0 value by any number of positions still returns 0. Rotating a value by the same number of bits as in the value returns the same value. Because this is a circular operation, the number of positions is not limited to the number of bits in the input value. For example, rotating an 8-bit value by 1, 9, 17, and so on positions returns an identical result in each case.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

```

select rotateright(16,4); /*
00010000 -> 00000001 */
+-----+
| rotateright(16, 4) |
+-----+
| 1                    |
+-----+

```

SETBIT(integer_type a, INT position [, INT zero_or_one])

```
select rotateright(-1,155); /*
11111111 -> 11111111 */
+-----+
| rotateright(-1, 155) |
+-----+
| -1                    |
+-----+

select rotateright(-128,1); /*
10000000 -> 01000000 */
+-----+
| rotateright(-128, 1) |
+-----+
| 64                    |
+-----+

select rotateright(-127,3); /*
10000001 -> 00110000 */
+-----+
| rotateright(-127, 3) |
+-----+
| 48                    |
+-----+
```

Purpose: By default, changes a bit at a specified position to a 1, if it is not already. If the optional third argument is set to zero, the specified bit is set to 0 instead.

Usage notes:

If the bit at the specified position was already 1 (by default) or 0 (with a third argument of zero), the return value is the same as the first argument. The positions are numbered right to left, starting at zero. (Therefore, the return value could be different from the first argument even if the position argument is zero.) The position argument cannot be negative.

When you use a literal input value, it is treated as an 8-bit, 16-bit, and so on value, the smallest type that is appropriate. The type of the input value limits the range of the positions. Cast the input value to the appropriate type if you need to ensure it is treated as a 64-bit, 32-bit, and so on value.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

```
select setbit(0,0); /* 00000000 ->
00000001 */
+-----+
| setbit(0, 0) |
+-----+
| 1            |
+-----+

select setbit(0,3); /* 00000000 ->
00001000 */
+-----+
| setbit(0, 3) |
```

```

+-----+
| 8      |
+-----+

select setbit(7,3); /* 00000111 ->
00001111 */
+-----+
| setbit(7, 3) |
+-----+
| 15           |
+-----+

select setbit(15,3); /* 00001111 ->
00001111 */
+-----+
| setbit(15, 3) |
+-----+
| 15           |
+-----+

select setbit(0,32); /* By default,
0 is a TINYINT with only 8 bits. */
ERROR: Invalid bit position: 32

select setbit(cast(0 as
bigint),32); /* For BIGINT, the
position can be 0..63. */
+-----+
| setbit(cast(0 as bigint), 32) |
+-----+
| 4294967296                    |
+-----+

select setbit(7,3,1); /* 00000111
-> 00001111; setting to 1 is the
default */
+-----+
| setbit(7, 3, 1) |
+-----+
| 15             |
+-----+

select setbit(7,2,0); /* 00000111
-> 00000011; third argument of 0
clears instead of sets */
+-----+
| setbit(7, 2, 0) |
+-----+
| 3               |
+-----+

```

SHIFTLEFT(integer_type a, INT positions)

Purpose: Shifts an integer value left by a specified number of bits. As the most significant bit is taken out of the original value, it is discarded and the least significant bit becomes 0. In computer science terms, this operation is a “*logical shift*”.

Usage notes:

The final value has either the same number of 1 bits as the original value, or fewer. Shifting an 8-bit value by 8 positions, a 16-bit value by 16 positions, and so on produces a result of zero.

Specifying a second argument of zero leaves the original value unchanged. Shifting any value by 0 returns the original value. Shifting any value by 1 is the same as multiplying it by 2, as long as the value is small enough; larger values eventually become negative when shifted, as the sign bit is set. Starting with the value 1 and shifting it left by N positions gives the same result as 2 to the Nth power, or $\text{POW}(2, N)$.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

```
select shiftleft(1,0); /* 00000001 -
> 00000001 */
+-----+
| shiftleft(1, 0) |
+-----+
| 1               |
+-----+

select shiftleft(1,3); /* 00000001 -
> 00001000 */
+-----+
| shiftleft(1, 3) |
+-----+
| 8               |
+-----+

select shiftleft(8,2); /* 00001000 -
> 00100000 */
+-----+
| shiftleft(8, 2) |
+-----+
| 32              |
+-----+

select shiftleft(127,1); /* 01111111
-> 11111110 */
+-----+
| shiftleft(127, 1) |
+-----+
| -2               |
+-----+

select shiftleft(127,5); /* 01111111
-> 11100000 */
+-----+
| shiftleft(127, 5) |
+-----+
| -32              |
+-----+

select shiftleft(-1,4); /* 11111111
-> 11110000 */
+-----+
| shiftleft(-1, 4) |
+-----+
| -16              |
+-----+
```

SHIFTRIGHT(integer_type a, INT positions)

Purpose: Shifts an integer value right by a specified number of bits. As the least significant bit is taken out of the original value, it is discarded and the most significant bit becomes 0. In computer science terms, this operation is a “*logical shift*”.

Usage notes:

Therefore, the final value has either the same number of 1 bits as the original value, or fewer. Shifting an 8-bit value by 8 positions, a 16-bit value by 16 positions, and so on produces a result of zero.

Specifying a second argument of zero leaves the original value unchanged. Shifting any value by 0 returns the original value. Shifting any positive value right by 1 is the same as dividing it by 2. Negative values become positive when shifted right.

Return type: Same as the input value

Added in: Impala 2.3.0

Examples:

```
select shiftright(16,0); /* 00010000
-> 00010000 */
+-----+
| shiftright(16, 0) |
+-----+
| 16                |
+-----+

select shiftright(16,4); /* 00010000
-> 00000001 */
+-----+
| shiftright(16, 4) |
+-----+
| 1                  |
+-----+

select shiftright(16,5); /* 00010000
-> 00000000 */
+-----+
| shiftright(16, 5) |
+-----+
| 0                  |
+-----+

select shiftright(-1,1); /* 11111111
-> 01111111 */
+-----+
| shiftright(-1, 1) |
+-----+
| 127                |
+-----+

select shiftright(-1,5); /* 11111111
-> 00000111 */
+-----+
| shiftright(-1, 5) |
+-----+
| 7                  |
+-----+
```

+-----+

Impala Type Conversion Functions

Conversion functions are typically used in combination with other functions to explicitly pass the expected data types. Impala has strict rules regarding data types for function parameters. For example, Impala does not automatically convert a `DOUBLE` value to `FLOAT`, a `BIGINT` value to `INT`, or other conversion where precision could be lost or overflow could occur. Also, for reporting or dealing with loosely defined schemas in big data contexts, you might need to convert values to or from the `STRING` type.

Function reference:

Impala supports the following type conversion functions:

- [CAST](#)
- [TYPEOF](#)

CAST(expression AS type)

Purpose: Returns *expression* converted to the *type* data type.

If the *expression* value is of a type that cannot be converted to the target *type*:

- Of `DECIMAL`, `DATE`, and `BOOLEAN`, the function returns an error.
- Of all other types, the function returns `NULL`.

Usage notes:

Use `CAST` when passing a column value or literal to a function that expects a parameter with a different type. Frequently used in SQL operations such as `CREATE TABLE AS SELECT` and `INSERT ... VALUES` to ensure that values from various sources are of the appropriate type for the destination columns.

Where practical, do a one-time `CAST ()` operation during the ingestion process to make each column into the appropriate type, rather than using many `CAST ()` operations in each query; doing type conversions for each row during each query can be expensive for tables with millions or billions of rows.

The way this function deals with time zones when converting to or from `TIMESTAMP` values is affected by the `##use_local_tz_for_unix_timestamp_conversions` startup flag for the `impalad` daemon. See [TIMESTAMP Data Type](#) on page 133 for details about how Impala handles time zone considerations for the `TIMESTAMP` data type.

Related information:

For details of casts from each kind of data type, see the description of the appropriate type: [TINYINT Data Type](#) on page 139, [SMALLINT Data Type](#) on page 124, [INT Data Type](#) on page 118, [BIGINT Data Type](#) on page 106, [FLOAT Data Type](#) on page 117, [DOUBLE Data Type](#) on page 116, [DECIMAL Data Type](#), [STRING Data Type](#) on page 125, [CHAR Data](#)

[Type](#), [VARCHAR Data Type](#), [TIMESTAMP Data Type](#) on page 133, [BOOLEAN Data Type](#) on page 107

CAST(expression AS type FORMAT pattern)

Purpose: Returns *expression* converted to the *type* data type based on the *pattern* format string. This signature of CAST () with the FORMAT clause is supported only for casts between STRING / CHAR / VARCHAR types and TIMESTAMP / DATE types.

Note: The patterns allowed in the FORMAT clause support ISO SQL:2016 standard patterns. Those patterns are not the same format patterns used with the other Impala conversion functions, e.g. TO_TIMESTAMP () and FROM_TIMESTAMP ().

The following rules apply to *pattern*. Any exceptions to these rules are noted in the Details column of the table below.

- *pattern* is a case-insensitive STRING unless noted otherwise in the table below.
- If *pattern* is NULL, an empty string, or a number, an error returns.
- A fewer digits in *expression* than specified in the *pattern* is accepted if a separator is correctly specified in the *pattern*. For example, CAST (' 5-01-2017 ' AS DATE FORMAT 'MM-dd-yyyy') returns DATE ' 2017-05-01 '.
- If fewer number of digits are in *expression* than specified in the *pattern*, the current date is used to complete the year pattern. For example, CAST (' 19/05 ' AS DATE FORMAT 'YYYY/MM') will return DATE ' 2019-05-01 ' when executed on August 8, 2019.

The following format patterns are supported in the FORMAT clause.

Pattern	Description	Details
YYYY	4-digit year.	
YYY	Last 3 digits of a year.	
YY	Last 2 digits of a year.	
Y	Last digit of a year	

Pattern	Description	Details
RRRR	4-digit round year	<p>If 1,3 or 4-digit year values are provided in <i>expression</i>, treated as YYYY.</p> <p>If 2-digit years are provided in <i>expression</i>, treated as RR.</p> <p>For date/time to string conversions, treated as YYYY.</p> <p>If YYYY, YYYY, YY, Y, or RR is given in the same <i>pattern</i> for a string to date/time conversion, an error returns.</p>

Pattern	Description	Details
RR	2-digit round year.	<p>For date/time to string conversions, same as YY.</p> <p>For string to date/time conversions, the first 2 digits of the year in the return value depends on the specified two-digit year and the last two digits of the current year as follows:</p> <ul style="list-style-type: none"> • If the specified 2-digit year is 00 to 49: <ul style="list-style-type: none"> • If the last 2 digits of the current year are 00 to 49, the returned year has the same first 2 digits as the current year. • If the last 2 digits of the current year are 50 to 99, the first 2 digits of the returned year are 1 greater than the first 2 digits of the current year. • If the specified 2-digit year is 50 to 99: <ul style="list-style-type: none"> • If the last 2 digits of the current year are 00 to 49, the first 2 digits of the returned year are 1 less than the first 2 digits of the current year. • If the last 2 digits of the current year are 50 to 99, the returned year has the same first 2 digits as the current year. <p>If YYYY, YYYY, YY, Y, or RR is given in the same <i>pattern</i> for a string to date/time conversion, an error returns.</p> <p>If 1-digit year values are provided in <i>expression</i>, it is treated as YYYY.</p>
Q	Quarter of year (1-4)	Not supported in string to date/time conversions.
MM	Month number	In date/time to string conversions, 1-digit months are prefixed with a zero.

Pattern	Description	Details
MONTH Month month	Full month name	<p>In string to date/time conversions:</p> <ul style="list-style-type: none"> Converts a textual month name to a 2-digit month number. The input strings are expected without trailing spaces, e.g. "June", "August". If the FX modifier is active for the token, a 9-character-long full month name with trailing spaces is expected for the input string. <p>In date/time to string conversions:</p> <ul style="list-style-type: none"> Converts to a 9-character-long full month name with trailing spaces. If the FM modifier is active for this token, converts to a month name without trailing spaces. <p>This pattern token is case sensitive. MONTH, Month, month would require different casing of the input in string to date/time conversions and would produce cased outputs in date/time to string conversions. For example, MONTH, Month, month would convert respectively JULY, July, and july.</p>
MON Mon mon	Abbreviated 3-character month name	<p>This pattern token is case sensitive. MON, Mon, mon would require different casing of the input in string to date/time conversions and would produce cased outputs in date/time to string conversions. For example, MON, Mon, mon would convert respectively JUL, Jul, and jul.</p>
WW	Week of year (1-53)	<p>Not supported in string to date/time conversions.</p> <p>The 1st week begins on January 1st and ends on January 7th.</p>
W	Week of month (1-5)	<p>Not supported in string to date/time conversions.</p> <p>1st week begins on the 1st of the month and ends on the 7th.</p>

Pattern	Description	Details
D	Day of week (1-7)	Not supported in string to date/time conversions. In date/time to string conversions, converts to a day number, for example, 1 for Sunday, 2 for Monday.
DD	Day of month (1-31)	In date/time to string conversions, 1-digit days are prefixed with a zero.
DDD	Day of year (1-366)	In string to date/time conversions, providing MM and DD along with DDD results an error, e.g. YYYY-MM-DDD.
DAY Day day	Day name	Not supported in string to date/time conversions. In date/time to string conversions: <ul style="list-style-type: none"> Converts to a 9-character-long full day name with trailing spaces. If the FM modifier is active for this token, converts to a day name without trailing spaces. <p>This pattern token is case sensitive. DAY, Day, day would produce cased outputs in date/time to string conversions, For example, DAY, Day, day would convert respectively MONDAY, Monday, and monday.</p>
DY Dy dy	Abbreviated 3-character day name	Not supported in string to date/time conversions. This pattern token is case sensitive. DY, Dy, dy would produce cased outputs in date/time to string conversions, For example, DY, Dy, dy would convert respectively MON, Mon, and mon.
HH HH12	Hour of day (1-12)	In date/time to string conversions, 1-digit hours are prefixed with a zero. If provided hour in <i>expression</i> is not between 1 and 12, returns an error. If no AM/PM is provided in <i>expression</i> , the default is AM.
HH24	Hour of day (0-23)	In string to date/time conversions, if HH12, AM, PM are given in the same <i>pattern</i> , an error returns.

Pattern	Description	Details
MI	Minute of hour (0-59)	In date/time to string conversions, 1-digit minutes are prefixed with a zero.
SS	Second of minute (0-59)	In date/time to string conversions, 1-digit seconds are prefixed with a zero.
SSSS	Second of Day (0-86399)	In string to timestamp conversions, if SS, HH, HH12, HH24, MI, AM/PM are given in the same <i>pattern</i> , an error returns.
FF FF1, FF9	Fractional second ..., FF9	A number, 1 to 9, can be used to indicate the number of digits. FF specifies a 9 digits fractional second.
AM PM A.M. P.M.	Meridiem indicator	For date/time to string conversions, AM and PM are treated as synonyms. For example, casting '2019-01-01 11:00 am' to <code>TIMESTAMP</code> with the 'YYYY-MM-DD HH12:MI PM' pattern returns 01-JAN-19 11.00.00.000000 AM. For string to date/time conversion, HH24 in the same <i>pattern</i> returns an error.
TZH	Timezone offset hour	An optional sign, + or -, and 2 digits for the value of signed numbers are allowed for the source <i>expression</i> , e.g. +10, -05, 04. The allowed values are from -15 to +5.
TZM	Timezone offset minute	Unsigned numbers are allowed for the source <i>expression</i> . The allowed values are from 0 to 59.

Pattern	Description	Details
- . / ' ' ; : <space>	Separator	<p>For string to date/time conversions, any separator character in the <i>pattern</i> string would match any separator character in the input <i>expression</i>.</p> <p>For example, <code>CAST("20191010" AS DATE FORMAT "YYYY-MM-DD")</code> returns an error, but <code>CAST("2019- . ; 10 10" AS DATE FORMAT "YYYY-MM-DD")</code> succeeds.</p>
T	Separates the date from the time.	<p>This pattern is used for accepting ISO 8601 date/time formats.</p> <p>Example: <code>YYYY-MM-DDTHH24:MI:SS.FF9Z</code></p>
Z	Indicates the zero hour offset from UTC.	<p>This pattern is used for accepting ISO 8601 date/time formats.</p>
FX	Forces an exact match between the format pattern, <i>pattern</i> , and the input argument, <i>expression</i> .	<p>Must be specified at the beginning of the format <i>pattern</i> and is valid for the whole <i>pattern</i>.</p> <p>In string to date/time conversions:</p> <ul style="list-style-type: none"> Forces strict separator matching, including the separator character. Expects all the tokens to have the maximum possible length. <p>In date/time to string conversions, the outputs are padded as follows:</p> <ul style="list-style-type: none"> Numeric outputs are left padded with zeros. Text outputs are right padded with spaces.

Pattern	Description	Details
FM	Overrides FX.	<p>In a date/time to string conversions, FM suppresses blank padding for the element immediately following the FM in the <i>pattern</i> string, e.g. "2010-1-9".</p> <p>In string to date/time conversions, FM is used to override the effect of FX for certain tokens as follows:</p> <ul style="list-style-type: none"> The length of the token in the input argument can be shorter than the max length of that token type if followed by a separator, e.g. 1-digit month, less than 4-digit year. FM modifier skips the separators and affects the next non-separator token. For example, <code>CAST('1999-10-2' AS TIMESTAMP FORMAT 'FXYYYY-MMFM-DD')</code> returns 1999-10-02 00:00:00 as FM is applied to DD and not to the separator(-).

Pattern	Description	Details
Free text	Nested string	<p>You can specify a free text with surrounding double quotes (") in <i>pattern</i> where the same text is expected in the input argument without surrounding double quotes.</p> <p>In date/time to string conversions, the string is included in the output with the characters' case preserved.</p> <p>In string to date/time conversions, the nested string is not included in the resulting date/time object. However, the nested string has to match the related part of the input string, including the case.</p> <p>The following rules apply:</p> <ul style="list-style-type: none"> If the <i>pattern</i> is surrounded by double quotes, double quotes surrounding the free text token must be escaped with a single backslash (\ "). <p>For example:</p> <pre>CAST(' "Date: "2019-11-10 AS DATE FORMAT " \"Date: \"YYYY-MM-DD")</pre> <ul style="list-style-type: none"> If the <i>pattern</i> is surrounded by double quotes, and there is an escaped double quotes inside a text token that is itself surrounded by escaped double quotes, escape the double quotes in the free text token with a triple backslash: (\ \ \ "). <p>For example: <code>CAST("1985 some \"text 11-28" AS DATE ' ' ' FORMAT "YYYY\"some \\\"text \"MM-DD")</code></p> <ul style="list-style-type: none"> If the <i>pattern</i> is surrounded by single quotes, the free text token can be surrounded by (non-escaped) double quotes. To include double quotes within the free text token, those double quotes must be escaped by a single backslash. <p>For example:</p> <pre>CAST(' "Date: "2019-11-10 AS DATE FORMAT ' \"Date: \" "YYYY-MM-DD')</pre> <ul style="list-style-type: none"> Literal single quotes/apostrophes (') in the nested string must be escaped with a single backslash if the whole pattern string is delimited by single quotes.

Examples:

Input	Output
<code>CAST("02-11-2014" AS DATE FORMAT 'dd-mm-yyyy')</code>	2014-11-02
<code>CAST("365 2014" AS DATE FORMAT 'DDD-YYYY')</code>	2014-12-31
<code>CAST("5-01-26" AS DATE FORMAT 'YY-MM-DD')</code>	Executed at 2019-01-01 11:11:11: 2015-01-26
<code>CAST('2018-11-10T15:11:04Z' AS TIMESTAMP FORMAT 'YYYY-MM-DDTHH24:MI:SSZ')</code>	2018-11-10 15:11:04 15:11:04Z
<code>CAST("95-01-28" AS DATE FORMAT 'YYY- MM-DD')</code>	Executed at 2019-01-01 11:11:11: 2095-01-28
<code>CAST("49-01-15" AS DATE FORMAT 'RR- MM-DD')</code>	Round year when last 2 digits of current year is greater than 49. Executed at 2099-01-01 11:11:11: 2149-01-15
<code>CAST('2019.10.10 13:30:40.123456 +01:30' AS TIMESTAMP FORMAT 'YYYY-MM-DD HH24:MI:SS.FF9 TZH:TZM')</code>	2019-10-10 13:30:40.123456000
<code>CAST('2001-03-01 03:10:15.123456 -01:30' AS TIMESTAMP FORMAT 'FXYYYY-MM-DD HH12:MI:SS.FF6 TZH:TZM')</code>	2001-03-01 03:10:15.123456000
<code>CAST('2001-03-02 03:10:15' AS TIMESTAMP FORMAT 'FXYYYY MM-DD HH12:MI:SS')</code>	NULL because the separator between the year and month do not match.

TYPEOF(expression)

Purpose: Returns the name of the data type corresponding to *expression*. For types with extra attributes, such as length for CHAR and VARCHAR, or precision and scale for DECIMAL, includes the full specification of the type.

Return type: STRING

Usage notes: Typically used in interactive exploration of a schema, or in application code that programmatically generates schema definitions such as CREATE TABLE statements, for example, to get the type of an expression such as col1 / col2 or CONCAT(col1, col2, col3). This function is especially useful for arithmetic expressions involving DECIMAL types because the precision and scale of the result is can be different than that of the operands.

Examples:

TYPEOF(2) returns TINYINT.

TYPEOF(NOW()) returns TIMESTAMP.

Impala Date and Time Functions

The underlying Impala data types for date and time data are TIMESTAMP and DATE.

Some of the date/time functions are affected by the setting of the

##use_local_tz_for_unix_timestamp_conversions startup flag for the impalad daemon:

- The setting is off by default, meaning that functions such as FROM_UNIXTIME() and UNIX_TIMESTAMP() consider the input values to always represent the UTC time zone.
- The setting also applies when you CAST() a BIGINT value to TIMESTAMP, or a TIMESTAMP value to BIGINT. When this setting is enabled, these functions and operations convert to and from values representing the local time zone. See [TIMESTAMP Data Type](#) on page 133 for details about how Impala handles time zone considerations for the TIMESTAMP data type.

Function reference:

Impala supports the following date and time functions:

- [ADD_MONTHS](#)
- [ADDDATE](#)
- [CURRENT_DATE](#)
- [CURRENT_TIMESTAMP](#)
- [DATE_ADD](#)
- [DATE_PART](#)
- [DATE_SUB](#)
- [DATE_TRUNC](#)
- [DATEDIFF](#)
- [DAY](#)
- [DAYNAME](#)
- [DAYOFWEEK](#)
- [DAYOFYEAR](#)
- [DAYS_ADD](#)
- [DAYS_SUB](#)
- [EXTRACT](#)

- *FROM_TIMESTAMP*
- *FROM_UNIXTIME*
- *FROM_UTC_TIMESTAMP*
- *HOUR*
- *HOURS_ADD*
- *HOURS_SUB*
- *INT_MONTHS_BETWEEN*
- *MICROSECONDS_ADD*
- *MICROSECONDS_SUB*
- *MILLISECOND*
- *MILLISECONDS_ADD*
- *MILLISECONDS_SUB*
- *MINUTE*
- *MINUTES_ADD*
- *MINUTES_SUB*
- *MONTH*
- *MONTHNAME*
- *MONTHS_ADD*
- *MONTHS_BETWEEN*
- *MONTHS_SUB*
- *NANOSECONDS_ADD*
- *NANOSECONDS_SUB*
- *NEXT_DAY*
- *NOW*
- *QUARTER*
- *SECOND*
- *SECONDS_ADD*
- *SECONDS_SUB*
- *SUBDATE*
- *TIMEOFDAY*
- *TIMESTAMP_CMP*
- *TO_DATE*
- *TO_TIMESTAMP*
- *TO_UTC_TIMESTAMP*
- *TRUNC*
- *UNIX_TIMESTAMP*
- *UTC_TIMESTAMP*
- *WEEKOFYEAR*
- *WEEKS_ADD*
- *WEEKS_SUB*
- *YEAR*
- *YEARS_ADD*
- *YEARS_SUB*

ADD_MONTHS(TIMESTAMP / DATE date, INT months), ADD_MONTHS(TIMESTAMP / DATE date, BIGINT months)

Purpose: Adds *months* to *date* and returns the new date value.

Return type:

- If *date* is `TIMESTAMP`, returns `TIMESTAMP`.
- If *date* is `DATE`, returns `DATE`.

ADDDATE(TIMESTAMP / DATE date, INT / BIGINT days)

CURRENT_DATE()

CURRENT_TIMESTAMP()

DATE_ADD(TIMESTAMP / DATE date, INT / BIGINT days), DATE_ADD(TIMESTAMP / DATE date, interval_expression)

Usage notes:

Same as [MONTHS_ADD\(\)](#). Available in Impala 1.4 and higher. For compatibility when porting code with vendor extensions.

Purpose: Adds *days* to *date* and returns the new date value.

The *days* value can be negative, which gives the same result as the `SUBDATE()` function.

Return type:

- If *date* is `TIMESTAMP`, returns `TIMESTAMP`.
- If *date* is `DATE`, returns `DATE`.

Purpose: Returns the current date.

Any references to the `CURRENT_DATE()` function are evaluated at the start of a query. All calls to `CURRENT_DATE()` within the same query return the same value, and the value does not depend on how long the query takes.

Return type: `DATE`

Purpose: Alias for the `NOW()` function.

Return type: `TIMESTAMP`

Purpose: Adds a specified number of days to the *date* argument.

With an `INTERVAL` expression as the second argument, you can calculate a delta value using other units such as weeks, years, hours, seconds, and so on; see [TIMESTAMP Data Type](#) on page 133 for details.

Return type:

- If *date* is `TIMESTAMP`, returns `TIMESTAMP`.
- If *date* is `DATE`, returns `DATE`.

The following examples show the shorthand notation of an `INTERVAL` expression, instead of specifying the precise number of days. The `INTERVAL` notation also lets you work with units smaller than a single day.

```
select now() as right_now,
       date_add(now(), interval 3 weeks)
       as in_3_weeks;
+-----+
+-----+
| right_now |
| in_3_weeks |
+-----+
+-----+
| 2016-05-20 11:05:39.173331000 |
| 2016-06-10 11:05:39.173331000 |
+-----+
+-----+
```



```

select now() as right_now,
       date_add(now(), interval 6 hours)
       as in_6_hours;
+-----+
+-----+
| right_now                |
| in_6_hours                |
+-----+
+-----+
| 2016-05-20 11:13:51.492536000 |
| 2016-05-20 17:13:51.492536000 |
+-----+
+-----+

```

Like all date/time functions that deal with months, `date_add()` handles nonexistent dates past the end of a month by setting the date to the last day of the month. The following example shows how the nonexistent date April 31st is normalized to April 30th:

```

select date_add(cast('2016-01-31' as
timestamp), interval 3 months) as
'april_31st';
+-----+
| april_31st                |
+-----+
| 2016-04-30 00:00:00      |
+-----+

```

DATE_CMP(DATE *date1*, DATE *date2*)

Purpose: Compares *date1* and *date2* and returns:

- 0 if the dates are identical.
- 1 if *date1* > *date2*.
- -1 if *date1* < *date2*.
- NULL if *date1* or *date2* is NULL.

Return type: INT

DATE_PART(STRING *part*, TIMESTAMP / DATE *date*)

Purpose: Similar to [EXTRACT\(\)](#), with the argument order reversed. Supports the same date and time units as `EXTRACT()`. For compatibility with SQL code containing vendor extensions.

Return type: BIGINT

DATE_SUB(TIMESTAMP *startdate*, INT *days*), **DATE_SUB**(TIMESTAMP *startdate*, *interval_expression*)

Purpose: Subtracts a specified number of days from a TIMESTAMP value. With an INTERVAL expression as the second argument, you can calculate a delta value using other units such as weeks, years, hours, seconds, and so on; see [TIMESTAMP Data Type](#) on page 133 for details.

Return type:

- If *date* is TIMESTAMP, returns TIMESTAMP.
- If *date* is DATE, returns DATE.

Examples:

The following example shows the simplest usage, of subtracting a specified number of days from a `TIMESTAMP` value:

```
select now() as right_now,
       date_sub(now(), 7) as last_week;
+-----+
+-----+
| right_now                |
| last_week                |
+-----+
+-----+
| 2016-05-20 11:21:30.491011000 |
| 2016-05-13 11:21:30.491011000 |
+-----+
+-----+
```

The following examples show the shorthand notation of an `INTERVAL` expression, instead of specifying the precise number of days. The `INTERVAL` notation also lets you work with units smaller than a single day.

```
select now() as right_now,
       date_sub(now(), interval 3 weeks)
       as 3_weeks_ago;
+-----+
+-----+
| right_now                |
| 3_weeks_ago              |
+-----+
+-----+
| 2016-05-20 11:23:05.176953000 |
| 2016-04-29 11:23:05.176953000 |
+-----+
+-----+

select now() as right_now,
       date_sub(now(), interval 6 hours)
       as 6_hours_ago;
+-----+
+-----+
| right_now                |
| 6_hours_ago              |
+-----+
+-----+
| 2016-05-20 11:23:35.439631000 |
| 2016-05-20 05:23:35.439631000 |
+-----+
+-----+
```

Like all date/time functions that deal with months, `date_add()` handles nonexistent dates past the end of a month by setting the date to the last day of the month. The following example shows how the nonexistent date April 31st is normalized to April 30th:

```
select date_sub(cast('2016-05-31' as
timestamp), interval 1 months) as
'april_31st';
+-----+
| april_31st |
+-----+
| 2016-04-30 00:00:00 |
+-----+
```

DATE_TRUNC(STRING *unit*, **TIMESTAMP** /
DATE *ts*)

Purpose: Returns the *ts* value truncated to the specified *unit*.

Argument: The *unit* argument is not case-sensitive. This argument string can be one of:

Unit	Supported for TIMESTAMP	Supported for DATE
'MICROSECOND'	Yes	No
'MILLISECOND'	Yes	No
'SECOND'	Yes	No
'MINUTE'	Yes	No
'HOUR'	Yes	No
'DAY'	Yes	Yes
'WEEK'	Yes	Yes
'MONTH'	Yes	Yes
'YEAR'	Yes	Yes
'DECADE'	Yes	Yes
'CENTURY'	Yes	Yes
'MILLENNIUM'	Yes	Yes

Added in: Impala 2.11.0

Usage notes:

Although this function is similar to calling `TRUNC()` with a **TIMESTAMP** or **DATE** argument, the order of arguments and the recognized units are different between `TRUNC()` and `DATE_TRUNC()`. Therefore, these functions are not interchangeable.

This function is typically used in `GROUP BY` queries to aggregate results from the same hour, day, week, month, quarter, and so on. You can also use this function in an `INSERT ... SELECT` into a partitioned table to divide **TIMESTAMP** or **DATE** values into the correct partition.

Return type:

- **TIMESTAMP** if the second argument, *ts*, is **TIMESTAMP**.
- **DATE** if the second argument, *ts*, is **DATE**.

**DATEDIFF(TIMESTAMP / DATE *enddate*,
TIMESTAMP / DATE *startdate*)**

Examples:

`DATE_TRUNC('HOUR' , NOW())` returns
2017-12-05 13:00:00.

`DATE_TRUNC('MILLENNIUM' ,
DATE '2019-08-02')` returns 2001-01-01.

Purpose: Returns the number of days from *startdate* to *enddate*.

If *enddate* > *startdate*, the return value is positive.

If *enddate* < *startdate*, the return value is negative.

If *enddate* = *startdate*, the return value is zero.

Return type: INT

Usage notes:

The time portions of the *enddate* and *startdate* values are ignored. For example, 11:59 PM on one day and 12:01 AM on the next day represent a `DATEDIFF()` of -1 because the date/time values represent different days, even though the `TIMESTAMP` values differ by only 2 minutes.

**DAY(TIMESTAMP / DATE *date*),
DAYOFMONTH(TIMESTAMP / DATE *date*)**

Purpose: Returns the day value from the *date* argument. The value represents the day of the month, therefore is in the range 1-31, or less for months without 31 days.

Returns NULL for nonexistent dates, e.g. Feb 30, or misformatted date strings, e.g. '1999-02-013'.

Return type: INT

DAYNAME(TIMESTAMP / DATE *date*)

Purpose: Returns the day name of the *date* argument. The range of return values is 'Sunday' to 'Saturday'. Used in report-generating queries, as an alternative to calling `DAYOFWEEK()` and turning that numeric return value into a string using a `CASE` expression.

Return type: STRING

DAYOFWEEK(TIMESTAMP / DATE *date*)

Purpose: Returns the day field of the *date* argument, corresponding to the day of the week. The range of return values is 1 (Sunday) to 7 (Saturday).

Return type: INT

DAYOFYEAR(TIMESTAMP / DATE *date*)

Purpose: Returns the day field from the *date* argument, corresponding to the day of the year. The range of return values is 1 (January 1) to 366 (December 31 of a leap year).

Return type: INT

**DAYS_ADD(TIMESTAMP / DATE *date*, INT /
BIGINT *days*)**

Purpose: Returns the value with the number of *days* added to *date*.

Return type:

- If *date* is `TIMESTAMP`, returns `TIMESTAMP`.

DAYS_SUB(TIMESTAMP / DATE *date*, INT / BIGINT *days*)

- If *date* is DATE, returns DATE.

Purpose: Returns the value with the number of *days* subtracted from *date*.

Return type:

- If *date* is TIMESTAMP, returns TIMESTAMP.
- If *date* is DATE, returns DATE.

**EXTRACT(TIMESTAMP / DATE *ts*, STRING *unit*),
EXTRACT(*unit* FROM TIMESTAMP / DATE *ts*)**

Purpose: Returns one of the numeric date or time fields, specified by *unit*, from *ts*.

Argument: The *unit* argument value is not case-sensitive. The *unit* string can be one of:

Unit	Supported for TIMESTAMP ts	Supported for DATE ts
'EPOCH'	Yes	No
'MILLISECOND'	Yes	No
'SECOND'	Yes	No
'MINUTE'	Yes	No
'HOUR'	Yes	No
'DAY'	Yes	Yes
'MONTH'	Yes	Yes
'QUARTER'	Yes	Yes
'YEAR'	Yes	Yes

Usage notes:

Typically used in GROUP BY queries to arrange results by hour, day, month, and so on. You can also use this function in an INSERT ... SELECT statement to insert into a partitioned table to split up TIMESTAMP values into individual parts, if the partitioned table has separate partition key columns representing year, month, day, and so on. If you need to divide by more complex units of time, such as by week or by quarter, use the TRUNC () function instead.

Return type: BIGINT

Examples:

EXTRACT(DAY FROM DATE '2019-08-17')
returns 17.

If you specify 'MILLISECOND' for the *unit* argument, the function returns the seconds component and the milliseconds component.

EXTRACT(CAST('2006-05-12
18:27:28.123456789' AS TIMESTAMP),
'MILLISECOND') returns 28123.

FROM_TIMESTAMP(TIMESTAMP datetime, STRING pattern), FROM_TIMESTAMP(STRING datetime, STRING pattern)

Purpose: Converts a `TIMESTAMP` value into a string representing the same value.

Return type: `STRING`

Usage notes:

The `FROM_TIMESTAMP ()` function provides a flexible way to convert `TIMESTAMP` values into arbitrary string formats for reporting purposes.

Because Impala implicitly converts string values into `TIMESTAMP`, you can pass date/time values represented as strings (in the standard `yyyy-MM-dd HH:mm:ss.SSS` format) to this function. The result is a string using different separator characters, order of fields, spelled-out month names, or other variation of the date/time string representation.

The allowed tokens for the pattern string are the same as for the `FROM_UNIXTIME ()` function.

FROM_UNIXTIME(BIGINT unixtime [, STRING pattern])

Purpose: Converts the number of seconds from the Unix epoch to the specified time into a string in the local time zone.

Return type: `STRING`

The *pattern* string supports the following subset of Java `SimpleDateFormat`.

Pattern	Description
Y	Year
M	Month
d	Day
H	Hour
m	Minute
s	Second
S	Fractional second

The following rules apply to the *pattern* string:

- The *pattern* string is case-sensitive.
- All fields are variable length, and thus must use separators to specify the boundaries of the fields, with the exception of the time zone values.
- Time zone offsets will be disregarded. The `FROM_UNIXTIME()` function accepts a bigint number as input (seconds from Unix epoch) but will not hold the timezone related information and will be excluded in the output.
- Formatting character groups can appear in any order along with any separators. For example:
 - `yyyy/MM/dd`
 - `dd-MMM-yy`

- (dd)(MM)(yyyy) HH:mm:ss
- yyyy-MM-dd HH:mm:ss

In Impala 1.3 and later, you can switch the order of elements, use alternative separator characters, and use a different number of placeholders for each unit. Adding more instances of y, d, H, and so on produces output strings zero-padded to the requested number of characters. The exception is M for months, where M produces a non-padded value such as 3, MM produces a zero-padded value such as 03, MMM produces an abbreviated month name such as Mar, and sequences of 4 or more M are not allowed.

A date string including all fields could be 'yyyy-MM-dd HH:mm:ss.SSSSSS', 'dd/MM/yyyy HH:mm:ss.SSSSSS', 'MMM dd, yyyy HH.mm.ss (SSSSSS)' or other combinations of placeholders and separator characters.

In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the “[Year 2038 problem](#)” or “[Y2K38 problem](#)”). This change affects the `FROM_UNIXTIME()` and `UNIX_TIMESTAMP()` functions. You might need to change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST()` calls to SQL statements that call these functions.

Usage notes:

The way this function deals with time zones when converting to or from `TIMESTAMP` values is affected by the `##use_local_tz_for_unix_timestamp_conversions` startup flag for the `impalad` daemon. See [TIMESTAMP Data Type](#) on page 133 for details about how Impala handles time zone considerations for the `TIMESTAMP` data type.

FROM_UTC_TIMESTAMP(TIMESTAMP ts, STRING timezone)

Purpose: Converts a specified UTC timestamp value into the appropriate value for a specified time zone.

Return type: `TIMESTAMP`

Usage notes: Often used to translate UTC time zone data stored in a table back to the local date and time for reporting. The opposite of the `TO_UTC_TIMESTAMP()` function.

To determine the time zone of the server you are connected to, in Impala 2.3 and higher you can call the `timeofday()` function, which includes the time zone specifier in its return value. Remember that with cloud computing, the server you interact with might be in a different time zone than you are, or different sessions

HOUR(TIMESTAMP ts)

might connect to servers in different time zones, or a cluster might include servers in more than one time zone.

See discussion of time zones in [TIMESTAMP Data Type](#) on page 133 for information about using this function for conversions between the local time zone and UTC.

Purpose: Returns the hour field from a `TIMESTAMP` field.

Return type: `INT`

**HOURS_ADD(TIMESTAMP date, INT hours),
HOURS_ADD(TIMESTAMP date, BIGINT hours)**

Purpose: Returns the specified date and time plus some number of hours.

Return type: `TIMESTAMP`

**HOURS_SUB(TIMESTAMP date, INT hours),
HOURS_SUB(TIMESTAMP date, BIGINT hours)**

Purpose: Returns the specified date and time minus some number of hours.

Return type: `TIMESTAMP`

**INT_MONTHS_BETWEEN(TIMESTAMP / DATE
enddate, TIMESTAMP / DATE startdate)**

Purpose: Returns the number of months from *startdate* to *enddate*, representing only the full months that passed.

Return type: `INT`

Added in: Impala 2.3.0

Usage notes:

Typically used in business contexts, for example to determine whether a specified number of months have passed or whether some end-of-month deadline was reached.

The method of determining the number of elapsed months includes some special handling of months with different numbers of days that creates edge cases for dates between the 28th and 31st days of certain months. See `MONTHS_BETWEEN()` for details. The `INT_MONTHS_BETWEEN()` result is essentially the `FLOOR()` of the `MONTHS_BETWEEN()` result.

If either value is `NULL`, which could happen for example when converting a nonexistent date string such as `'2015-02-29'` to a `TIMESTAMP`, the result is also `NULL`.

If the first argument represents an earlier time than the second argument, the result is negative.

LAST_DAY(TIMESTAMP / DATE ts)

Purpose: Returns the beginning of the last calendar day in the same month of *ts*.

Return type:

- Returns `TIMESTAMP` if *ts* is of the `TIMESTAMP` type.
- Returns `DATE` if *ts* is of the `DATE` type.

Added in: Impala 2.9.0

Usage notes:

MICROSECONDS_ADD(TIMESTAMP date, INT microseconds),
MICROSECONDS_ADD(TIMESTAMP date, BIGINT microseconds)

MICROSECONDS_SUB(TIMESTAMP date, INT microseconds),
MICROSECONDS_SUB(TIMESTAMP date, BIGINT microseconds)

MILLISECOND(TIMESTAMP ts)

MILLISECONDS_ADD(TIMESTAMP date, INT milliseconds),
MILLISECONDS_ADD(TIMESTAMP date, BIGINT milliseconds)

MILLISECONDS_SUB(TIMESTAMP date, INT milliseconds),
MILLISECONDS_SUB(TIMESTAMP date, BIGINT milliseconds)

MINUTE(TIMESTAMP date)

MINUTES_ADD(TIMESTAMP date, INT minutes),
MINUTES_ADD(TIMESTAMP date, BIGINT minutes)

MINUTES_SUB(TIMESTAMP date, INT minutes),
MINUTES_SUB(TIMESTAMP date, BIGINT minutes)

MONTH(TIMESTAMP / DATE date)

MONTHNAME(TIMESTAMP / DATE date)

If the input argument does not represent a valid Impala **TIMESTAMP** including both date and time portions, the function returns **NULL**. For example, if the input argument is a string that cannot be implicitly cast to **TIMESTAMP**, does not include a date portion, or is out of the allowed range for Impala **TIMESTAMP** values, the function returns **NULL**.

Purpose: Returns the specified date and time plus some number of microseconds.

Return type: **TIMESTAMP**

Purpose: Returns the specified date and time minus some number of microseconds.

Return type: **TIMESTAMP**

Purpose: Returns the millisecond portion of a **TIMESTAMP** value.

Return type: **INT**

Added in: Impala 2.5.0

Usage notes:

The millisecond value is truncated, not rounded, if the **TIMESTAMP** value contains more than 3 significant digits to the right of the decimal point.

Purpose: Returns the specified date and time plus some number of milliseconds.

Return type: **TIMESTAMP**

Purpose: Returns the specified date and time minus some number of milliseconds.

Return type: **TIMESTAMP**

Purpose: Returns the minute field from a **TIMESTAMP** value.

Return type: **INT**

Purpose: Returns the specified date and time plus some number of minutes.

Return type: **TIMESTAMP**

Purpose: Returns the specified date and time minus some number of minutes.

Return type: **TIMESTAMP**

Purpose: Returns the month field, represented as an integer, from the *date* argument.

Return type: **INT**

Purpose: Returns the month name of the *date* argument.

Return type: **STRING**

MONTHS_ADD(TIMESTAMP / DATE *date*, INT / BIGINT *months*)

Purpose: Returns the value with the number of *months* added to *date*.

Return type:

- If *date* is `TIMESTAMP`, returns `TIMESTAMP`.
- If *date* is `DATE`, returns `DATE`.

Usage notes:

If *date* is the last day of a month, the return date will fall on the last day of the target month, e.g. `MONTHS_ADD(DATE '2019-01-31' , 1)` returns `DATE '2019-02-28'`.

MONTHS_BETWEEN(TIMESTAMP / DATE *enddate*, TIMESTAMP / DATE *startdate*)

Purpose: Returns the number of months from *startdate* to *enddate*.

This result can include a fractional part representing extra days in addition to the full months between the dates. The fractional component is computed by dividing the difference in days by 31 (regardless of the month).

Return type: `DOUBLE`

Added in: Impala 2.3.0

Usage notes:

Typically used in business contexts, for example to determine whether a specified number of months have passed or whether some end-of-month deadline was reached.

If the only consideration is the number of full months and any fractional value is not significant, use `INT_MONTHS_BETWEEN()` instead.

The method of determining the number of elapsed months includes some special handling of months with different numbers of days that creates edge cases for dates between the 28th and 31st days of certain months.

If either value is `NULL`, which could happen for example when converting a nonexistent date string such as `'2015-02-29'` to a `TIMESTAMP`, the result is also `NULL`.

If the first argument represents an earlier time than the second argument, the result is negative.

The time portion of the input arguments are ignored.

MONTHS_SUB(TIMESTAMP / DATE *date*, INT / BIGINT *months*)

Purpose: Returns the value with the number of *months* subtracted from *date*.

Return type:

- If *date* is `TIMESTAMP`, returns `TIMESTAMP`.
- If *date* is `DATE`, returns `DATE`.

Usage notes:

If *date* is the last day of a month, the return date will fall on the last day of the target month, e.g.

	MONTHS_SUB(DATE ' 2019-02-28 ' , 1) returns DATE ' 2019-01-31 '.
NANOSECONDS_ADD(TIMESTAMP date, INT nanoseconds), NANOSECONDS_ADD(TIMESTAMP date, BIGINT nanoseconds)	<p>Purpose: Returns the specified date and time plus some number of nanoseconds.</p> <p>Return type: TIMESTAMP</p> <p>Kudu considerations:</p> <p>The nanosecond portion of an Impala TIMESTAMP value is rounded to the nearest microsecond when that value is stored in a Kudu table.</p>
NANOSECONDS_SUB(TIMESTAMP date, INT nanoseconds), NANOSECONDS_SUB(TIMESTAMP date, BIGINT nanoseconds)	<p>Purpose: Returns the specified date and time minus some number of nanoseconds.</p> <p>Return type: TIMESTAMP</p> <p>Kudu considerations:</p> <p>The nanosecond portion of an Impala TIMESTAMP value is rounded to the nearest microsecond when that value is stored in a Kudu table.</p>
NEXT_DAY(TIMESTAMP / DATE date, STRING weekday)	<p>Purpose: Returns the date of the <i>weekday</i> that follows the specified <i>date</i>.</p> <p>Argument: The <i>weekday</i> is not case-sensitive.</p> <p>The following values are accepted for <i>weekday</i>: "Sunday"/"Sun", "Monday"/"Mon", "Tuesday"/"Tue", "Wednesday"/"Wed", "Thursday"/"Thu", "Friday"/"Fri", "Saturday"/"Sat"</p> <p>Return type:</p> <ul style="list-style-type: none"> • Returns TIMESTAMP if <i>date</i> is of the TIMESTAMP type. • Returns DATE if <i>date</i> is of the DATE type. <p>Examples:</p> <p>NEXT_DAY(' 2013-12-25 ' , ' Saturday ') returns ' 2013-12-28 00:00:00 ' which is the first Saturday after December 25, 2013.</p>
NOW()	<p>Purpose: Returns the current date and time (in the local time zone) as a TIMESTAMP value.</p> <p>Return type: TIMESTAMP</p> <p>Usage notes:</p> <p>To find a date/time value in the future or the past relative to the current date and time, add or subtract an INTERVAL expression to the return value of NOW(). See TIMESTAMP Data Type on page 133 for examples.</p> <p>To produce a TIMESTAMP representing the current date and time that can be shared or stored without interoperability problems due to time zone differences, use the TO_UTC_TIMESTAMP() function and specify</p>

the time zone of the server. When `TIMESTAMP` data is stored in UTC form, any application that queries those values can convert them to the appropriate local time zone by calling the inverse function, `FROM_UTC_TIMESTAMP ()`.

To determine the time zone of the server you are connected to, in Impala 2.3 and higher you can call the `timeofday ()` function, which includes the time zone specifier in its return value. Remember that with cloud computing, the server you interact with might be in a different time zone than you are, or different sessions might connect to servers in different time zones, or a cluster might include servers in more than one time zone.

Any references to the `NOW ()` function are evaluated at the start of a query. All calls to `NOW ()` within the same query return the same value, and the value does not depend on how long the query takes.

QUARTER(TIMESTAMP / DATE date)

Purpose: Returns the quarter in the input *date* argument as an integer value, 1, 2, 3, or 4, where 1 represents January 1 through March 31.

Return type: `INT`

SECOND(TIMESTAMP date)

Purpose: Returns the second field from a `TIMESTAMP` value.

Return type: `INT`

SECONDS_ADD(TIMESTAMP date, INT seconds), SECONDS_ADD(TIMESTAMP date, BIGINT seconds)

Purpose: Returns the specified date and time plus some number of seconds.

Return type: `TIMESTAMP`

SECONDS_SUB(TIMESTAMP date, INT seconds), SECONDS_SUB(TIMESTAMP date, BIGINT seconds)

Purpose: Returns the specified date and time minus some number of seconds.

Return type: `TIMESTAMP`

SUBDATE(TIMESTAMP / DATE date, INT / BIGINT days)

Purpose: Subtracts *days* from *date* and returns the new date value.

The *days* value can be negative, which gives the same result as the `ADDDATE ()` function.

Return type:

- If *date* is `TIMESTAMP`, returns `TIMESTAMP`.
- If *date* is `DATE`, returns `DATE`.

TIMEOFDAY()

Purpose: Returns a string representation of the current date and time, according to the time of the local system, including any time zone designation.

Return type: `STRING`

Added in: Impala 2.3.0

Usage notes: The result value represents similar information as the `now ()` function, only as a `STRING` type and with somewhat different formatting. For

**TIMESTAMP_CMP(TIMESTAMP t1,
TIMESTAMP t2)**

example, the day of the week and the time zone identifier are included. This function is intended primarily for compatibility with SQL code from other systems that also have a `timeofday()` function. Prefer to use `now()` if practical for any new Impala code.

Purpose: Tests if one `TIMESTAMP` value is newer than, older than, or identical to another `TIMESTAMP`

- If the first argument represents a later point in time than the second argument, the result is 1.
- If the first argument represents an earlier point in time than the second argument, the result is -1.
- If the first and second arguments represent identical points in time, the result is 0.
- If either argument is `NULL`, the result is `NULL`.

Return type: `INT` (either -1, 0, 1, or `NULL`)

Added in: Impala 2.3.0

Usage notes:

Usage notes: A comparison function for `TIMESTAMP` values that only tests whether the date and time increases, decreases, or stays the same. Similar to the `SIGN()` function for numeric values.

TO_DATE(TIMESTAMP ts)

Purpose: Returns a string representation of the date field from the *ts* argument.

Return type: `STRING`

**TO_TIMESTAMP(BIGINT unixtime),
TO_TIMESTAMP(STRING date, STRING pattern)**

Purpose: Converts an integer or string representing a date/time value into the corresponding `TIMESTAMP` value.

Return type: `TIMESTAMP`

Added in: Impala 2.3.0

Usage notes:

An integer argument represents the number of seconds past the epoch (midnight on January 1, 1970). It is the converse of the `UNIX_TIMESTAMP()` function, which produces a `BIGINT` representing the number of seconds past the epoch.

A string argument, plus another string argument representing the pattern, turns an arbitrary string representation of a date and time into a true `TIMESTAMP` value. The ability to parse many kinds of date and time formats allows you to deal with temporal data from diverse sources, and if desired to convert to efficient `TIMESTAMP` values during your ETL process. Using `TIMESTAMP` directly in queries and expressions lets you perform date and time calculations without the overhead of extra function calls and conversions each time you reference the applicable columns.

Examples:

The following examples demonstrate how to convert an arbitrary string representation to `TIMESTAMP` based on a pattern string:

```
select to_timestamp('Sep 25, 1984',
  'MMM dd, yyyy');
+-----+
+
+ | to_timestamp('sep 25, 1984', 'mmm
+   dd, yyyy') |
+-----+
+
+ | 1984-09-25 00:00:00
+   |
+-----+
+
select to_timestamp('1984/09/25',
  'yyyy/MM/dd');
+-----+
+
+ | to_timestamp('1984/09/25', 'yyyy/
+   mm/dd') |
+-----+
+
+ | 1984-09-25 00:00:00
+   |
+-----+
+
```

The following examples show how to convert a `BIGINT` representing seconds past epoch into a `TIMESTAMP` value:

```
-- One day past the epoch.
select to_timestamp(24 * 60 * 60);
+-----+
+ | to_timestamp(24 * 60 * 60) |
+-----+
+ | 1970-01-02 00:00:00      |
+-----+

-- 60 seconds in the past.
select now() as 'current date/time',
  unix_timestamp(now()) 'now in
  seconds',
  to_timestamp(unix_timestamp(now())
  - 60) as '60 seconds ago';
+-----+
+-----+
+-----+
+ | current date/time      |
+ | now in seconds | 60 seconds ago |
+ |                       |
+-----+
+-----+
+ | 2017-10-01 22:03:46.885624000
+ | 1506895426          | 2017-10-01
+ | 22:02:46           |
+-----+
```

TO_UTC_TIMESTAMP(TIMESTAMP ts, STRING timezone)

Purpose: Converts a specified timestamp value in a specified time zone into the corresponding value for the UTC time zone.

Return type: TIMESTAMP

Usage notes:

Often used in combination with the `now()` function, to translate local date and time values to the UTC time zone for consistent representation on disk. The opposite of the `FROM_UTC_TIMESTAMP()` function.

See discussion of time zones in [TIMESTAMP Data Type](#) on page 133 for information about using this function for conversions between the local time zone and UTC.

Examples:

The simplest use of this function is to turn a local date/time value to one with the standardized UTC time zone. Because the time zone specifier is not saved as part of the Impala `TIMESTAMP` value, all applications that refer to such data must agree in advance which time zone the values represent. If different parts of the ETL cycle, or different instances of the application, occur in different time zones, the ideal reference point is to convert all `TIMESTAMP` values to UTC for storage.

```
select now() as 'Current time in
California USA',
  to_utc_timestamp(now(), 'PDT') as
'Current time in Greenwich UK';
+-----+
+-----+
| current time in california usa |
| current time in greenwich uk   |
+-----+
+-----+
| 2016-06-01 15:52:08.980072000 |
| 2016-06-01 22:52:08.980072000 |
+-----+
+-----+
```

Once a value is converted to the UTC time zone by `TO_UTC_TIMESTAMP()`, it can be converted back to the local time zone with `FROM_UTC_TIMESTAMP()`. You can combine these functions using different time zone identifiers to convert a `TIMESTAMP` between any two time zones. This example starts with a `TIMESTAMP` value representing Pacific Daylight Time, converts it to UTC, and converts it to the equivalent value in Eastern Daylight Time.

```

select now() as 'Current time in
California USA',
  from_utc_timestamp
  (
    to_utc_timestamp(now(), 'PDT'),
    'EDT'
  ) as 'Current time in New York,
USA';
+-----+
+-----+
| current time in california usa |
| current time in new york, usa |
+-----+
+-----+
| 2016-06-01 18:14:12.743658000 |
| 2016-06-01 21:14:12.743658000 |
+-----+
+-----+

```

TRUNC(TIMESTAMP / DATE *ts*, STRING *unit*)

Purpose: Returns the *ts* truncated to the *unit* specified.

Argument: The *unit* argument is not case-sensitive. This argument string can be one of:

Unit	Supported for TIMESTAMP <i>ts</i>	Supported for DATE	Description
'SYYYY' 'YYYY' 'YEAR' 'SYEAR' 'YYY' 'YY' 'Y'	Yes	Yes	Year
'Q'	Yes	Yes	Quarter
'MONTH' 'MON' 'MM' 'RM'	Yes	Yes	Month
'WW'	Yes	Yes	The most recent date that is the same day of the week as the first day of the year

Unit	Supported for TIMESTAM ts	Supported for DATE	Description
'W'	Yes	Yes	The most recent date that is the same day of the week as the first day of the month
'DDD' 'DD' 'J'	Yes	Yes	Day
'DAY' 'DY' 'D'	Yes	Yes	Starting day of the week (Monday)
'HH' 'HH12' 'HH24'	Yes	No	Hour. A <code>TIMESTAMP</code> value truncated to the hour is always represented in 24-hour notation, even for the <code>HH12</code> argument string.
'MI'	Yes	No	Minute

Added in: The ability to truncate numeric values is new starting in Impala 2.10.

Usage notes:

The `TIMESTAMP` form is typically used in `GROUP BY` queries to aggregate results from the same hour, day, week, month, quarter, and so on. You can also use this function in an `INSERT . . . SELECT` into a partitioned table to divide `TIMESTAMP` values into the correct partition.

Return type:

- `TIMESTAMP` if the first argument, *ts*, is `TIMESTAMP`.
- `DATE` if the first argument, *ts*, is `DATE`.

Example:

UNIX_TIMESTAMP(),
UNIX_TIMESTAMP(String datetime),
UNIX_TIMESTAMP(String datetime, String
pattern), UNIX_TIMESTAMP(TIMESTAMP
datetime)

`TRUNC (DATE '2019-05-08' , 'YEAR')` returns
 2019-01-01.

`TRUNC (DATE '2019-05-08' , 'QUARTER')`
 returns 2019-04-01.

Purpose: Returns a Unix time, which is a number of seconds elapsed since '1970-01-01 00:00:00' UTC. If called with no argument, the current date and time is converted to its Unix time. If called with arguments, the first argument represented as the `TIMESTAMP` or `STRING` is converted to its Unix time.

Return type: `BIGINT`

Usage notes:

See `FROM_UNIXTIME ()` for details about the patterns you can use in the *pattern* string to represent the position of year, month, day, and so on in the `date` string. In Impala 1.3 and higher, you have more flexibility to switch the positions of elements and use different separator characters.

In Impala 2.2.3 and higher, you can include a trailing uppercase Z qualifier to indicate “Zulu” time, a synonym for UTC.

In Impala 2.3 and higher, you can include a timezone offset specified as minutes and hours, provided you also specify the details in the *pattern* string argument. The offset is specified in the *pattern* string as a plus or minus sign followed by `hh:mm`, `hhmm`, or `hh`. The `hh` must be lowercase, to distinguish it from the `HH` represent hours in the actual time value. Currently, only numeric timezone offsets are allowed, not symbolic names.

In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the “[Year 2038 problem](#)” or “[Y2K38 problem](#)”). This change affects the `FROM_UNIXTIME ()` and `UNIX_TIMESTAMP ()` functions. You might need to change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST ()` calls to SQL statements that call these functions.

`UNIX_TIMESTAMP ()` and `FROM_UNIXTIME ()` are often used in combination to convert a `TIMESTAMP` value into a particular string format. For example:

```
SELECT
  FROM_UNIXTIME (UNIX_TIMESTAMP (NOW ( )
    + interval 3 days),
    'yyyy/MM/dd HH:mm' ) AS
    yyyy_mm_dd_hh_mm;
+-----+
| yyyy_mm_dd_hh_mm |
```

```
+-----+
| 2016/06/03 11:38 |
+-----+
```

The way this function deals with time zones when converting to or from `TIMESTAMP` values is affected by the `##use_local_tz_for_unix_timestamp_conversions` startup flag for the `impalad` daemon. See [TIMESTAMP Data Type](#) on page 133 for details about how Impala handles time zone considerations for the `TIMESTAMP` data type.

Examples:

The following examples show different ways of turning the same date and time into an integer value. A *pattern* string that Impala recognizes by default is interpreted as a UTC date and time. The trailing `Z` is a confirmation that the timezone is UTC. If the date and time string is formatted differently, a second argument specifies the position and units for each of the date and time values.

The final two examples show how to specify a timezone offset of Pacific Daylight Saving Time, which is 7 hours earlier than UTC. You can use the numeric offset `-07:00` and the equivalent suffix of `-hh:mm` in the pattern string, or specify the mnemonic name for the time zone in a call to `TO_UTC_TIMESTAMP()`. This particular date and time expressed in PDT translates to a different number than the same date and time expressed in UTC.

```
-- 3 ways of expressing the same
date/time in UTC and converting to
an integer.
```

```
select unix_timestamp('2015-05-15
12:00:00');
```

```
+-----+
+
| unix_timestamp('2015-05-15
12:00:00') |
+-----+
+
| 1431691200
|
+-----+
+
```

```
select unix_timestamp('2015-05-15
12:00:00Z');
```

```
+-----+
+
| unix_timestamp('2015-05-15
12:00:00Z') |
+-----+
+
| 1431691200
|
+-----+
```

```

+-----+
+
select unix_timestamp
(
  'May 15, 2015 12:00:00',
  'MMM dd, yyyy HH:mm:ss'
) as may_15_month_day_year;
+-----+
| may_15_month_day_year |
+-----+
| 1431691200             |
+-----+

-- 2 ways of expressing the same
date and time but in a different
timezone.
-- The resulting integer is
different from the previous
examples.

select unix_timestamp
(
  '2015-05-15 12:00:00-07:00',
  'yyyy-MM-dd HH:mm:ss-hh:mm'
) as may_15_year_month_day;
+-----+
| may_15_year_month_day |
+-----+
| 1431716400             |
+-----+

select unix_timestamp
(
  to_utc_timestamp(
    '2015-05-15 12:00:00',
    'PDT'
  )
) as may_15_pdt;
+-----+
| may_15_pdt            |
+-----+
| 1431716400            |
+-----+

```

UTC_TIMESTAMP()

Purpose: Returns a **TIMESTAMP** corresponding to the current date and time in the UTC time zone.

Return type: **TIMESTAMP**

Added in: Impala 2.10

Usage notes:

Similar to the **NOW()** or **CURRENT_TIMESTAMP()** functions, but does not use the local time zone as those functions do. Use **UTC_TIMESTAMP()** to record **TIMESTAMP** values that are interoperable with servers around the world, in arbitrary time zones, without the need for additional conversion functions to standardize the time zone of each value representing a date/time.

For working with date/time values represented as integer values, you can convert back and forth between **TIMESTAMP** and **BIGINT** with the

UNIX_MICROS_TO_UTC_TIMESTAMP() and UTC_TO_UNIX_MICROS() functions. The integer values represent the number of microseconds since the Unix epoch (midnight on January 1, 1970).

Examples:

The following example shows how NOW() and CURRENT_TIMESTAMP() represent the current date/time in the local time zone (in this case, UTC-7), while utc_timestamp() represents the same date/time in the standardized UTC time zone:

```
select now(), utc_timestamp();
+-----+
| now()                |
| utc_timestamp()      |
+-----+
| 2017-10-01 23:33:58.919688000 |
| 2017-10-02 06:33:58.919688000 |
+-----+

select current_timestamp(),
       utc_timestamp();
+-----+
| current_timestamp()   |
| utc_timestamp()      |
+-----+
| 2017-10-01 23:34:07.400642000 |
| 2017-10-02 06:34:07.400642000 |
+-----+
```

WEEK(TIMESTAMP / DATE date),
WEEKOFYEAR(TIMESTAMP / DATE date)

Purpose: Returns the corresponding week (1-53) from the *date* argument.

Return type: INT

WEEKS_ADD(TIMESTAMP / DATE date, INT /
BIGINT weeks)

Purpose: Returns the value with the number of *weeks* added to *date*.

Return type:

- If *date* is TIMESTAMP, returns TIMESTAMP.
- If *date* is DATE, returns DATE.

WEEKS_SUB(TIMESTAMP / DATE date, INT /
BIGINT weeks)

Purpose: Returns the value with the number of *weeks* subtracted from *date*.

Return type:

- If *date* is TIMESTAMP, returns TIMESTAMP.
- If *date* is DATE, returns DATE.

YEAR(TIMESTAMP / DATE date)

Purpose: Returns the year field from the *date* argument.

Return type: INT

YEARS_ADD(TIMESTAMP / DATE *date*, INT / BIGINT *years*)

Purpose: Returns the value with the number of *years* added to *date*.

Return type:

- If *date* is TIMESTAMP, returns TIMESTAMP.
- If *date* is DATE, returns DATE.

Usage notes:

If the equivalent date does not exist in the year of the result due to a leap year, the date is changed to the last day of the appropriate month.

YEARS_SUB(TIMESTAMP / DATE *date*, INT / BIGINT *years*)

Purpose: Returns the value with the number of *years* subtracted from *date*.

Return type:

- If *date* is TIMESTAMP, returns TIMESTAMP.
- If *date* is DATE, returns DATE.

Usage notes:

If the equivalent date does not exist in the year of the result due to a leap year, the date is changed to the last day of the appropriate month.

Impala Conditional Functions

Impala supports the following conditional functions for testing equality, comparison operators, and nullity:

- *CASE*
- *CASE2*
- *COALESCE*
- *DECODE*
- *IF*
- *IFNULL*
- *ISFALSE*
- *ISNOTFALSE*
- *ISNOTTRUE*
- *ISNULL*
- *ISTRUE*
- *NONNULLVALUE*
- *NULLIF*
- *NULLIFZERO*
- *NULLVALUE*
- *NVL*
- *NVL2*
- *ZEROIFNULL*

CASE *a* **WHEN** *b* **THEN** *c* [**WHEN** *d* **THEN** *e*]...
[**ELSE** *f*] **END**

Purpose: Compares an expression to one or more possible values, and returns a corresponding result when a match is found.

Return type: same as the initial argument value, except that integer values are promoted to BIGINT

and floating-point values are promoted to `DOUBLE`; use `CAST ()` when inserting into a smaller numeric column

Usage notes:

In this form of the `CASE` expression, the initial value `A` being evaluated for each row is typically a column reference, or an expression involving a column. This form can only compare against a set of specified values, not ranges, multi-value comparisons such as `BETWEEN` or `IN`, regular expressions, or `NULL`.

Examples:

Although this example is split across multiple lines, you can put any or all parts of a `CASE` expression on a single line, with no punctuation or other separators between the `WHEN`, `ELSE`, and `END` clauses.

```
select case x
  when 1 then 'one'
  when 2 then 'two'
  when 0 then 'zero'
  else 'out of range'
end
from t1;
```

**CASE WHEN a THEN b [WHEN c THEN d]...
[ELSE e] END**

Purpose: Tests whether any of a sequence of expressions is `TRUE`, and returns a corresponding result for the first true expression.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST ()` when inserting into a smaller numeric column

Usage notes:

`CASE` expressions without an initial test value have more flexibility. For example, they can test different columns in different `WHEN` clauses, or use comparison operators such as `BETWEEN`, `IN` and `IS NULL` rather than comparing against discrete values.

`CASE` expressions are often the foundation of long queries that summarize and format results for easy-to-read reports. For example, you might use a `CASE` function call to turn values from a numeric column into category strings corresponding to integer values, or labels such as “Small”, “Medium” and “Large” based on ranges. Then subsequent parts of the query might aggregate based on the transformed values, such as how many values are classified as small, medium, or large. You can also use `CASE` to signal problems with out-of-bounds values, `NULL` values, and so on.

By using operators such as `OR`, `IN`, `REGEXP`, and so on in `CASE` expressions, you can build extensive tests and transformations into a single query. Therefore, applications that construct SQL statements often rely heavily on `CASE` calls in the generated SQL code.

Because this flexible form of the CASE expressions allows you to perform many comparisons and call multiple functions when evaluating each row, be careful applying elaborate CASE expressions to queries that process large amounts of data. For example, when practical, evaluate and transform values through CASE after applying operations such as aggregations that reduce the size of the result set; transform numbers to strings after performing joins with the original numeric values.

Examples:

Although this example is split across multiple lines, you can put any or all parts of a CASE expression on a single line, with no punctuation or other separators between the WHEN, ELSE, and END clauses.

```
select case
  when dayname(now()) in
    ('Saturday','Sunday') then 'result
    undefined on weekends'
  when x > y then 'x greater than
  y'
  when x = y then 'x and y are
  equal'
  when x is null or y is null then
    'one of the columns is null'
  else null
end
from t1;
```

COALESCE(type v1, type v2, ...)

Purpose: Returns the first specified argument that is not NULL, or NULL if all arguments are NULL.

Return type: same as the initial argument value, except that integer values are promoted to BIGINT and floating-point values are promoted to DOUBLE; use CAST () when inserting into a smaller numeric column

DECODE(type expression, type search1, type result1
[, type search2, type result2 ...] [, type default])

Purpose: Compares the first argument, expression, to the search expressions using the IS NOT DISTINCT operator, and returns:

- The corresponding result when a match is found.
- The first corresponding result if there are more than one matching search expressions.
- The default expression if none of the search expressions matches the first argument expression.
- NULL if the final default expression is omitted and none of the search expressions matches the first argument.

Return type: Same as the first argument with the following exceptions:

- Integer values are promoted to BIGINT.
- Floating-point values are promoted to DOUBLE.

- Use `CAST ()` when inserting into a smaller numeric column.

Usage notes:

- Can be used as shorthand for a `CASE` expression.
- The first argument, `expression`, and the search expressions must be of the same type or convertible types.
- The result expression can be a different type, but all result expressions must be of the same type.
- Returns a successful match if the first argument is `NULL` and a search expression is also `NULL`.
- `NULL` can be used as a search expression.

Examples:

The following example translates numeric day values into weekday names, such as 1 to Monday, 2 to Tuesday, etc.

```
SELECT event, DECODE(day_of_week,
  1, "Monday", 2, "Tuesday", 3,
  "Wednesday",
  4, "Thursday", 5, "Friday", 6,
  "Saturday", 7, "Sunday", "Unknown
day")
FROM calendar;
```

IF(BOOLEAN condition, type ifTrue, type ifFalseOrNull)

Purpose: Tests an expression and returns a corresponding result depending on whether the result is `TRUE`, `FALSE`, or `NULL`.

Return type: Same as the `ifTrue` argument value

IFNULL(type a, type ifNull)

Purpose: Alias for the `ISNULL ()` function, with the same behavior. To simplify porting SQL with vendor extensions to Impala.

Added in: Impala 1.3.0

ISFALSE(BOOLEAN expression)

Purpose: Returns `TRUE` if the expression is `FALSE`. Returns `FALSE` if the expression is `TRUE` or `NULL`.

Same as the `IS FALSE` operator.

Similar to `ISNOTTRUE ()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Added in: Impala 2.2.0

Usage notes:

In Impala 2.11 and higher, you can use the operators `IS [NOT] TRUE` and `IS [NOT] FALSE` as equivalents for the built-in functions `ISTRUE ()`, `ISNOTTRUE ()`, `ISFALSE ()`, and `ISNOTFALSE ()`.

ISNOTFALSE(BOOLEAN expression)

Purpose: Tests if a Boolean expression is not `FALSE` (that is, either `TRUE` or `NULL`). Returns `TRUE` if so. If the argument is `NULL`, returns `TRUE`.

ISNOTTRUE(BOOLEAN expression)

Same as the `IS NOT FALSE` operator.

Similar to `ISTRUE ()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: Impala 2.2.0

Usage notes:

In Impala 2.11 and higher, you can use the operators `IS [NOT] TRUE` and `IS [NOT] FALSE` as equivalents for the built-in functions `ISTRUE ()`, `ISNOTTRUE ()`, `ISFALSE ()`, and `ISNOTFALSE ()`.

Purpose: Tests if a Boolean expression is not `TRUE` (that is, either `FALSE` or `NULL`). Returns `TRUE` if so. If the argument is `NULL`, returns `TRUE`.

Same as the `IS NOT TRUE` operator.

Similar to `ISFALSE ()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Added in: Impala 2.2.0

Usage notes:

In Impala 2.11 and higher, you can use the operators `IS [NOT] TRUE` and `IS [NOT] FALSE` as equivalents for the built-in functions `ISTRUE ()`, `ISNOTTRUE ()`, `ISFALSE ()`, and `ISNOTFALSE ()`.

ISNULL(type a, type ifNull)

Purpose: Tests if an expression is `NULL`, and returns the expression result value if not. If the first argument is `NULL`, returns the second argument.

Compatibility notes: Equivalent to the `NVL ()` function from Oracle Database or `IFNULL ()` from MySQL. The `NVL ()` and `IFNULL ()` functions are also available in Impala.

Return type: Same as the first argument value

ISTRUE(BOOLEAN expression)

Purpose: Returns `TRUE` if the expression is `TRUE`. Returns `FALSE` if the expression is `FALSE` or `NULL`.

Same as the `IS TRUE` operator.

Similar to `ISNOTFALSE ()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: Impala 2.2.0

Usage notes:

NONNULLVALUE(type expression)

In Impala 2.11 and higher, you can use the operators `IS [NOT] TRUE` and `IS [NOT] FALSE` as equivalents for the built-in functions `ISTRUE()`, `ISNOTTRUE()`, `ISFALSE()`, and `ISNOTFALSE()`.

Purpose: Returns `TRUE` if the expression is non-null and returns `FALSE` if the expression is `NULL`.

Same as the `IS NOT NULL` operator.

The converse of `NULLVALUE()`.

Return type: `BOOLEAN`

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: Impala 2.2.0

NULLIF(type expr1, type expr2)

Purpose: Returns `NULL` if the two specified arguments are equal. If the specified arguments are not equal, returns the value of *expr1*. The data types of the expressions must be compatible, according to the conversion rules from [Data Types](#) on page 102. You cannot use an expression that evaluates to `NULL` for *expr1*; that way, you can distinguish a return value of `NULL` from an argument value of `NULL`, which would never match *expr2*.

Usage notes: This function is effectively shorthand for a `CASE` expression of the form:

```
CASE
  WHEN expr1 = expr2 THEN NULL
  ELSE expr1
END
```

It is commonly used in division expressions, to produce a `NULL` result instead of a divide-by-zero error when the divisor is equal to zero:

```
select 1.0 / nullif(c1,0) as
  reciprocal from t1;
```

You might also use it for compatibility with other database systems that support the same `NULLIF()` function.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

Added in: Impala 1.3.0

NULLIFZERO(type numeric_expr)

Purpose: Returns `NULL` if the numeric expression evaluates to 0, otherwise returns the result of the expression.

Usage notes: Used to avoid error conditions such as divide-by-zero in numeric calculations. Serves as

NULLVALUE(type expression)

shorthand for a more elaborate CASE expression, to simplify porting SQL with vendor extensions to Impala.

Return type: Same type as the input argument

Added in: Impala 1.3.0

Purpose: Returns TRUE if the expression is NULL, and returns FALSE otherwise.

Same as the IS NULL operator.

The converse of NONNULLVALUE ().

Return type: BOOLEAN

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: Impala 2.2.0

NVL(type a, type ifNull)

Purpose: Alias for the ISNULL () function. Returns the first argument if the first argument is not NULL. Returns the second argument if the first argument is NULL.

Equivalent to the NVL () function in Oracle Database or IFNULL () in MySQL.

Return type: Same as the first argument value

Added in: Impala 1.1

NVL2(type a, type ifNotNull, type ifNull)

Purpose: Returns the second argument, ifNotNull, if the first argument is not NULL. Returns the third argument, ifNull, if the first argument is NULL.

Equivalent to the NVL2 () function in Oracle Database.

Return type: Same as the first argument value

Added in: Impala 2.9.0

Examples:

```
SELECT NVL2(NULL, 999, 0); --
Returns 0
SELECT NVL2('ABC', 'Is Not Null',
'Is Null'); -- Returns 'Is Not
Null'
```

ZEROIFNULL(type numeric_expr)

Purpose: Returns 0 if the numeric expression evaluates to NULL, otherwise returns the result of the expression.

Usage notes: Used to avoid unexpected results due to unexpected propagation of NULL values in numeric calculations. Serves as shorthand for a more elaborate CASE expression, to simplify porting SQL with vendor extensions to Impala.

Return type: Same type as the input argument

Added in: Impala 1.3.0

Impala String Functions

String functions are classified as those primarily accepting or returning `STRING`, `VARCHAR`, or `CHAR` data types, for example to measure the length of a string or concatenate two strings together.

- All the functions that accept `STRING` arguments also accept the `VARCHAR` and `CHAR` types introduced in Impala 2.0.
- Whenever `VARCHAR` or `CHAR` values are passed to a function that returns a string value, the return type is normalized to `STRING`. For example, a call to `CONCAT ()` with a mix of `STRING`, `VARCHAR`, and `CHAR` arguments produces a `STRING` result.

Related information:

The string functions operate mainly on these data types: [STRING Data Type](#) on page 125, [VARCHAR Data Type \(Impala 2.0 or higher only\)](#) on page 140, and [CHAR Data Type \(Impala 2.0 or higher only\)](#) on page 108.

Function reference:

Impala supports the following string functions:

- [ASCII](#)
- [BASE64DECODE](#)
- [BASE64ENCODE](#)
- [BTRIM](#)
- [BYTES](#)
- [CHAR_LENGTH](#)
- [CHR](#)
- [CONCAT](#)
- [CONCAT_WS](#)
- [FIND_IN_SET](#)
- [GROUP_CONCAT](#)
- [INITCAP](#)
- [INSTR](#)
- [JARO_DISTANCE](#), [JARO_DIST](#)
- [JARO_SIMILARITY](#), [JARO_SIM](#)
- [JARO_WINKER_DISTANCE](#), [JW_DST](#)
- [JARO_WINKER_SIMILARITY](#), [JW_SIM](#)
- [LEFT](#)
- [LENGTH](#)
- [LEVENSHTEIN](#), [LE_DST](#)
- [LOCATE](#)
- [LOWER](#), [LCASE](#)
- [LPAD](#)
- [LTRIM](#)
- [PARSE_URL](#)
- [PRETTYPRINT_BYTES](#)
- [REGEXP_ESCAPE](#)
- [REGEXP_EXTRACT](#)
- [REGEXP_LIKE](#)
- [REGEXP_REPLACE](#)
- [REPEAT](#)
- [REPLACE](#)
- [REVERSE](#)
- [RIGHT](#)
- [RPAD](#)

- [*RTRIM*](#)
- [*SPACE*](#)
- [*SPLIT_PART*](#)
- [*STRLEFT*](#)
- [*STRRIGHT*](#)
- [*SUBSTR, SUBSTRING*](#)
- [*TRANSLATE*](#)
- [*TRIM*](#)
- [*UPPER, UCASE*](#)

ASCII(STRING str)

Purpose: Returns the numeric ASCII code of the first character of the argument.

Return type: INT

BASE64DECODE(STRING str)

Purpose:

Return type: STRING

Usage notes:

For general information about Base64 encoding, see [Base64 article on Wikipedia](#).

The functions `BASE64ENCODE ()` and `BASE64DECODE ()` are typically used in combination, to store in an Impala table string data that is problematic to store or transmit. For example, you could use these functions to store string data that uses an encoding other than UTF-8, or to transform the values in contexts that require ASCII values, such as for partition key columns. Keep in mind that base64-encoded values produce different results for string functions such as `LENGTH ()`, `MAX ()`, and `MIN ()` than when those functions are called with the unencoded string values.

The set of characters that can be generated as output from `BASE64ENCODE ()`, or specified in the argument string to `BASE64DECODE ()`, are the ASCII uppercase and lowercase letters (A-Z, a-z), digits (0-9), and the punctuation characters `+`, `/`, and `=`.

All return values produced by `BASE64ENCODE ()` are a multiple of 4 bytes in length. All argument values supplied to `BASE64DECODE ()` must also be a multiple of 4 bytes in length. If a base64-encoded value would otherwise have a different length, it can be padded with trailing `=` characters to reach a length that is a multiple of 4 bytes.

If the argument string to `BASE64DECODE ()` does not represent a valid base64-encoded value, subject to the constraints of the Impala implementation such as the allowed character set, the function returns NULL.

Examples:

The following examples show how to use `BASE64ENCODE()` and `BASE64DECODE()` together to store and retrieve string values:

```
-- An arbitrary string can be
-- encoded in base 64.
-- The length of the output is a
-- multiple of 4 bytes,
-- padded with trailing = characters
-- if necessary.
select base64encode('hello world')
as encoded,
length(base64encode('hello
world')) as length;
+-----+-----+
| encoded          | length |
+-----+-----+
| aGVsbG8gd29ybGQ= | 16     |
+-----+-----+

-- Passing an encoded value to
-- base64decode() produces
-- the original value.
select
base64decode('aGVsbG8gd29ybGQ=') as
decoded;
+-----+
| decoded |
+-----+
| hello world |
+-----+
```

These examples demonstrate incorrect encoded values that produce `NULL` return values when decoded:

```
-- The input value to base64decode()
-- must be a multiple of 4 bytes.
-- In this case, leaving off the
-- trailing = padding character
-- produces a NULL return value.
select
base64decode('aGVsbG8gd29ybGQ') as
decoded;
+-----+
| decoded |
+-----+
| NULL    |
+-----+
WARNINGS: UDF WARNING: Invalid
base64 string; input length is 15,
which is not a multiple of 4.

-- The input to base64decode() can
-- only contain certain characters.
-- The $ character in this case
-- causes a NULL return value.
select base64decode('abc$');
+-----+
| base64decode('abc$') |
+-----+
```

```
| NULL |
+-----+
WARNINGS: UDF WARNING: Could not
base64 decode input in space 4;
actual output length 0
```

These examples demonstrate “round-tripping” of an original string to an encoded string, and back again. This technique is applicable if the original source is in an unknown encoding, or if some intermediate processing stage might cause national characters to be misrepresented:

```

select 'circumflex accents: â, ê, î,
ô, û' as original,
base64encode('circumflex accents:
â, ê, î, ô, û') as encoded;
+-----+
+-----+
+
| original
| encoded
|
+-----+
+-----+
+
| circumflex accents:
| â, ê, î, ô, û |
| Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiwgw6osIMOuLCDDtCw
|
+-----+
+-----+
+
select base64encode('circumflex
accents: â, ê, î, ô, û') as
encoded,

base64decode(base64encode('circumflex
accents: â, ê, î, ô, û')) as
decoded;
+-----+
+-----+
+
| encoded
|
| decoded
|
+-----+
+-----+
+
| Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiwgw6osIMOuLCDDtCw
| circumflex accents: â, ê, î, ô, û
|
+-----+
+-----+
+

```

BASE64ENCODE(String str)

Purpose:

Return type: STRING

Usage notes:

For general information about Base64 encoding, see [Base64 article on Wikipedia](#).

The functions `BASE64ENCODE()` and `BASE64DECODE()` are typically used in combination, to store in an Impala table string data that is problematic to store or transmit. For example, you could use these functions to store string data that uses an encoding other than UTF-8, or to transform the values in contexts that require ASCII values, such as for partition key columns. Keep in mind that base64-encoded values produce different results for string functions such as `LENGTH()`, `MAX()`, and `MIN()` than when those functions are called with the unencoded string values.

The set of characters that can be generated as output from `BASE64ENCODE()`, or specified in the argument string to `BASE64DECODE()`, are the ASCII uppercase and lowercase letters (A-Z, a-z), digits (0-9), and the punctuation characters `+`, `/`, and `=`.

All return values produced by `BASE64ENCODE()` are a multiple of 4 bytes in length. All argument values supplied to `BASE64DECODE()` must also be a multiple of 4 bytes in length. If a base64-encoded value would otherwise have a different length, it can be padded with trailing `=` characters to reach a length that is a multiple of 4 bytes.

Examples:

The following examples show how to use `BASE64ENCODE()` and `BASE64DECODE()` together to store and retrieve string values:

```
-- An arbitrary string can be
-- encoded in base 64.
-- The length of the output is a
-- multiple of 4 bytes,
-- padded with trailing = characters
-- if necessary.
select base64encode('hello world')
  as encoded,
       length(base64encode('hello
world')) as length;
+-----+-----+
| encoded                | length |
+-----+-----+
| aGVsbG8gd29ybGQ=      | 16     |
+-----+-----+
```

```
-- Passing an encoded value to
-- base64decode() produces
-- the original value.
select
  base64decode('aGVsbG8gd29ybGQ=') as
  decoded;
+-----+
| decoded                |
+-----+
```

```
+-----+
| hello world |
+-----+
```

These examples demonstrate incorrect encoded values that produce NULL return values when decoded:

```
-- The input value to base64decode()
-- must be a multiple of 4 bytes.
-- In this case, leaving off the
-- trailing = padding character
-- produces a NULL return value.
select
  base64decode('aGVsbG8gd29ybGQ') as
  decoded;
+-----+
| decoded |
+-----+
| NULL    |
+-----+
WARNINGS: UDF WARNING: Invalid
base64 string; input length is 15,
which is not a multiple of 4.

-- The input to base64decode() can
-- only contain certain characters.
-- The $ character in this case
-- causes a NULL return value.
select base64decode('abc$');
+-----+
| base64decode('abc$') |
+-----+
| NULL                  |
+-----+
WARNINGS: UDF WARNING: Could not
base64 decode input in space 4;
actual output length 0
```

These examples demonstrate “round-tripping” of an original string to an encoded string, and back again. This technique is applicable if the original source is in an unknown encoding, or if some intermediate processing stage might cause national characters to be misrepresented:

```
select 'circumflex accents: â, ê, î,
      ô, û' as original,
       base64encode('circumflex accents:
      â, ê, î, ô, û') as encoded;
+-----+
+-----+
+
| original
| encoded
|
+-----+
+-----+
+
| circumflex accents:
| â, ê, î, ô, û |
```

```

Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiw6osIMOuLCDDtCv
|
+-----+
+-----+
+
select base64encode('circumflex
accents: â, ê, î, ô, û') as
encoded,

base64decode(base64encode('circumflex
accents: â, ê, î, ô, û')) as
decoded;
+-----+
+-----+
+
| encoded                                | decoded
|                                         |
+-----+-----+
+-----+
+
|                                         |
| Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiw6osIMOuLCDDtCv |
| circumflex accents: â, ê, î, ô, û           |
|                                         |
+-----+-----+
+-----+
+

```

BTRIM(*STRING a*), BTRIM(*STRING a*, *STRING chars_to_trim*)

Purpose: Removes all instances of one or more characters from the start and end of a *STRING* value. By default, removes only spaces. If a non-NULL optional second argument is specified, the function removes all occurrences of characters in that second argument from the beginning and end of the string.

Return type: *STRING*

Added in: Impala 2.3.0

Examples:

The following examples show the default `BTRIM()` behavior, and what changes when you specify the optional second argument. All the examples bracket the output value with `[]` so that you can see any leading or trailing spaces in the `BTRIM()` result. By default, the function removes a number of both leading and trailing spaces. When the second argument is specified, any number of occurrences of any character in the second argument are removed from the start and end of the input string; in this case, spaces are not removed (unless they are part of the second argument) and any instances of the characters are not removed if they do not come right at the beginning or end of the string.

```

-- Remove multiple spaces before and
-- one space after.
select concat('[',btrim('    hello
'),']');
```

```

+-----+
+
+ concat(['', btrim('    hello '),
+       '']) |
+-----+
+
+ [hello]
+
+-----+
+
-- Remove any instances of x or y or
-- z at beginning or end. Leave spaces
-- alone.
select concat(['',btrim('xy    hello
zyzzxx','xyz'),'']);
+-----+
+
+ concat(['', btrim('xy    hello
zyzzxx', 'xyz'), '']) |
+-----+
+
+ [    hello ]
+
+-----+
+
-- Remove any instances of x or y or
-- z at beginning or end.
-- Leave x, y, z alone in the middle
-- of the string.
select
  concat(['',btrim('xyhelxyzlozyzzxx','xyz'),''])
+-----+
+
+ concat(['',
+       btrim('xyhelxyzlozyzzxx', 'xyz'),
+       '']) |
+-----+
+
+ [helxyzlo]
+
+-----+
+

```

BYTES

Purpose: Returns the number of bytes contained in the specified byte string.

Syntax: BYTES (*byte_expression*)

Where:

byte_expression is the byte string for which the number of bytes is to be returned.

Usage notes:

The BYTES function is similar to the LENGTH() function except that it always returns the number of bytes regardless of the status of UTF-8 mode whether it is turned ON or OFF.

The following is the list of supported string data types to be used in *byte_expression*:

- STRING
- VARCHAR
- CHAR

Note: The BYTES (*byte_expression*) function counts the trailing zeros because trailing zero bytes are considered bytes. In the case of a fixed *length* column, the length of the value is always equal to the length defined for the column whereas the length of the value in a *variable* length column is always equal to the number of bytes, including any trailing zero bytes, contained in that value.

Examples:

The following example obtains the number of bytes from “cloudera” by applying the BYTES function to the column “cloudera”, which is type VARCHAR.

```
SELECT bytes(cast('cloudera' as
varchar(20))) FROM xyz;

+-----+
+               | bytes(cast('cloudera'
as varchar(20))) |
+-----+
+               | 8               |
+-----+
+               |                 |
+-----+
```

Note: Use the TRIM function on the *byte_expression* to exclude the trailing blanks included in the byte count for a data value.

**CHAR_LENGTH(STRING a),
CHARACTER_LENGTH(STRING a)**

Purpose: Returns the length in characters of the argument string, including any trailing spaces that pad a CHAR value.

Return type: INT

Usage notes:

When applied to a STRING value, it returns the same result as the length() function. When applied to a CHAR value, it might return a larger value than length() does, to account for trailing spaces in the CHAR.

Examples:

The following example demonstrates how length() and char_length() sometimes produce the same result, and sometimes produce different results depending on the type of the argument and the presence of trailing spaces for CHAR values. The S and C values

are displayed with enclosing quotation marks to show any trailing spaces.

```
create table length_demo (s string,
c char(5));
insert into length_demo values
('a',cast('a' as char(5))),
('abc',cast('abc' as char(5))),
('hello',cast('hello' as
char(5)));

select concat('"'||s,'"') as s,
concat('"'||c,'"') as c,
length(s), length(c),
char_length(s), char_length(c)
from length_demo;
```

s	c	length(s)	length(c)	char_length(s)	char_length(c)
"a"	"a"	1	5	1	1
"abc"	"abc"	3	5	3	3
"hello"	"hello"	5	5	5	5

CHR(INT character_code)

Purpose: Returns a character specified by a decimal code point value. The interpretation and display of the resulting character depends on your system locale. Because consistent processing of Impala string values is only guaranteed for values within the ASCII range, only use this function for values corresponding to ASCII characters. In particular, parameter values greater than 255 return an empty string.

Return type: STRING

Usage notes: Can be used as the inverse of the `ascii()` function, which converts a character to its numeric ASCII code.

Added in: Impala 2.3.0

Examples:

```
SELECT chr(65);
```

chr(65)
A

```
+-----+
SELECT chr(97);
+-----+
| chr(97) |
+-----+
| a       |
+-----+
```

CONCAT(String a, String b...)

Purpose: Returns a single string representing all the argument values joined together. If any argument is NULL, it returns NULL.

Return type: STRING

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

CONCAT_WS(String sep, String a, String b...)

Purpose: Returns a single string representing the second and following argument values joined together, delimited by a specified separator.

Return type: STRING

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

FIND_IN_SET(String str, String strList)

Purpose: Returns the position (starting from 1) of the first occurrence of a specified string within a comma-separated string. Returns NULL if either argument is NULL, 0 if the search string is not found, or 0 if the search string contains a comma.

Return type: INT

GROUP_CONCAT(String s [, String sep])

Purpose: Returns a single string representing the argument value concatenated together for each row of the result set. If the optional separator string is specified, the separator is added between each pair of concatenated values.

Return type: STRING

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

By default, returns a single string covering the whole result set. To include other columns or values in the result set, or to produce multiple concatenated strings for subsets of rows, include a `GROUP BY` clause in the query.

INITCAP(String str)

Strictly speaking, `GROUP_CONCAT()` is an aggregate function, not a scalar function like the others in this list. For additional details and examples, see [GROUP_CONCAT Function](#) on page 549.

Purpose: Returns the input string with the first letter of each word capitalized and all other letters in lowercase.

Return type: STRING

Example:

```
INITCAP("i gOt mY ChiCkeNs in tHe
yard.") returns " I Got My Chickens In The
Yard."
```

INSTR(String str, String substr [, BIGINT position [, BIGINT occurrence]])

Purpose: Returns the position (starting from 1) of the first occurrence of a *substr* within a longer string.

Return type: INT

Usage notes:

If the *substr* is not present in *str*, the function returns 0.

The optional third and fourth arguments let you find instances of the *substr* other than the first instance starting from the left.

- The third argument, *position*, lets you specify a starting point within the *str* other than 1.

```
-- Restricting the search to
-- positions 7..end,
-- the first occurrence of 'b' is
-- at position 9.
select instr('foo bar bleetch',
'b', 7);
+-----+
+ | instr('foo bar bleetch', 'b', 7) |
+-----+
+ | 9 |
+-----+
+
```

- If there are no more occurrences after the specified position, the result is 0.
- If *position* is negative, the search works right-to-left starting that many characters from the right. The return value still represents the position starting from the left side of *str*.

```
-- Scanning right to left, the
-- first occurrence of 'o'
-- is at position 8. (8th
-- character from the left.)
select instr('hello
world', 'o', -1);
```



```

+-----+
| instr('hello world', 'o', -1) |
+-----+
|      8                        |
+-----+

```

- The fourth argument, *occurrence*, lets you specify an occurrence other than the first.

```

-- 2nd occurrence of 'b' is at
-- position 9.
select instr('foo bar bleetch',
            'b', 1, 2);
+-----+
| instr('foo bar bleetch', 'b', 1, 2) |
+-----+
|      9                             |
+-----+

```

- If *occurrence* is greater than the number of matching occurrences, the function returns 0.
- *occurrence* cannot be negative or zero. A non-positive value for this argument causes an error.
- If either of the optional arguments, *position* or *occurrence*, is NULL, the function also returns NULL.

JARO_DISTANCE(STRING str1, STRING str2),
JARO_DST(STRING str1, STRING str2)

Purpose: Returns the *Jaro distance* between two input strings. The Jaro distance is a measure of similarity between two strings and is the complementary of JARO_SIMILARITY(), i.e. (1 - JARO_SIMILARITY()).

Return type: DOUBLE

Usage notes:

If the two input strings are identical, the function returns 0.0.

If there is no matching character between the input strings, the function returns 1.0.

If either input strings is NULL, the function returns NULL.

If the length of either input string is bigger than 255 characters, the function returns an error.

JARO_SIMILARITY(STRING str1, STRING str2),
JARO_SIM(STRING str1, STRING str2)

Purpose: Returns the *Jaro similarity* of two strings. The higher the Jaro similarity for two strings is, the more similar the strings are.

Return type: DOUBLE

Usage notes:

JARO_WINKLER_DISTANCE(STRING str1, STRING str2[, DOUBLE scaling_factor, DOUBLE boost_threshold]), **JW_DST**(STRING str1, STRING str2[, DOUBLE scaling_factor, DOUBLE boost_threshold])

If the two input strings are identical, the function returns 1.0.

If there is no matching character between the input strings, the function returns 0.0.

If either input strings is NULL, the function returns NULL.

If the length of either input string is bigger than 255 characters, the function returns an error.

Purpose: Returns the *Jaro-Winkler distance* of two input strings. It is the complementary of **JARO_WINKLER_SIMILARITY**(), i.e. $1 - \text{JARO_WINKLER_SIMILARITY}()$.

Return type: DOUBLE

Usage notes:

If the two input strings are identical, the function returns 0.0.

If there is no matching character between the input strings, the function returns 1.0.

The function returns an error in the following cases:

- The length of either input string is bigger than 255 characters.
- *scaling_factor* < 0.0 or *scaling_factor* > 0.25
- *boost_threshold* < 0.0 or *boost_threshold* > 1.0

If either input strings is NULL, the function returns NULL.

The default *scaling factor* is 0.1.

The prefix weight will only be applied if the Jaro-distance exceeds the optional *boost_threshold*. By default, the *boost_threshold* value is 0.7.

JARO_WINKLER_SIMILARITY(STRING str1, STRING str2[, DOUBLE scaling_factor, DOUBLE boost_threshold]), **JARO_SIM**(STRING str1, STRING str2[, DOUBLE scaling_factor, DOUBLE boost_threshold])

Purpose: Returns the *Jaro-Winkler Similarity* between two input strings. The Jaro-Winkler similarity uses a prefix weight, specified by *scaling factor*, which gives more favorable ratings to strings that match from the beginning for a set prefix length, up to a maximum of four characters.

Use Jaro or Jaro-Winkler functions to perform fuzzy matches on relatively short strings, e.g. to scrub user inputs of names against the records in the database.

Return type: DOUBLE

Usage notes:

If the two input strings are identical, the function returns 1.0.

If there is no matching character between the input strings, the function returns 0.0.

The function returns an error in the following cases:

- The length of either input string is bigger than 255 characters.
- *scaling_factor* < 0.0 or *scaling_factor* > 0.25
- *boost_threshold* < 0.0 or *boost_threshold* > 1.0

If either input strings is NULL, the function returns NULL.

The default *scaling factor* is 0.1.

The prefix weight will only be applied if the Jaro-similarity exceeds the optional *boost_threshold*. By default, the *boost_threshold* value is 0.7.

LEFT(STRING a, INT num_chars)

LENGTH(STRING a)

See the STRLEFT() function.

Purpose: Returns the length in characters of the argument string, ignoring any trailing spaces in CHAR values.

Return type: INT

Usage notes:

When applied to a STRING value, it returns the same result as the CHAR_LENGTH() function. When applied to a CHAR value, it might return a smaller value than CHAR_LENGTH() does, because LENGTH() ignores any trailing spaces in the CHAR.

Note: Because the behavior of LENGTH() with CHAR values containing trailing spaces is not standardized across the industry, when porting code from other database systems, evaluate the behavior of LENGTH() on the source system and switch to CHAR_LENGTH() for Impala if necessary.

Examples:

The following example demonstrates how length() and char_length() sometimes produce the same result, and sometimes produce different results depending on the type of the argument and the presence of trailing spaces for CHAR values. The S and C values are displayed with enclosing quotation marks to show any trailing spaces.

```
create table length_demo (s string,
  c char(5));
insert into length_demo values
  ('a',cast('a' as char(5))),
  ('abc',cast('abc' as char(5))),
  ('hello',cast('hello' as
  char(5)));

select concat('"' ,s,'"') as s,
  concat('"' ,c,'"') as c,
  length(s), length(c),
  char_length(s), char_length(c)
from length_demo;
+-----+-----+-----+
+-----+-----+
+-----+
```

s	c	length(s)
length(c)	char_length(s)	
char_length(c)		
+-----+-----+-----		
+-----+-----+-----		
+-----+-----+-----		
"a"	"a"	1
1	5	1
+-----+-----+-----		
"abc"	"abc"	3
3	5	3
+-----+-----+-----		
"hello"	"hello"	5
5	5	5
+-----+-----+-----		
+-----+-----+-----		
+-----+-----+-----		

LEVENSHTEIN(STRING str1, STRING str2),
LE_DST(STRING str1, STRING str2)

Purpose: Returns the Levenshtein distance between two input strings. The Levenshtein distance between two strings is the minimum number of single-character edits required to transform one string to other. The function indicates how different the input strings are.

Return type: INT

Usage notes:

If input strings are equal, the function returns 0.

If either input exceeds 255 characters, the function returns an error.

If either input string is NULL, the function returns NULL.

If the length of one input string is zero, the function returns the length of the other string.

Example:

LEVENSHTEIN ('welcome', 'We come')
returns 2, first change to replace 'w' to 'W', and then to replace 'l' to a space character.

LOCATE(STRING substr, STRING str[, INT pos])

Purpose: Returns the position (starting from 1) of the first occurrence of a substring within a longer string, optionally after a particular position.

Return type: INT

LOWER(STRING a), **LCASE**(STRING a)

Purpose: Returns the argument string converted to all-lowercase.

Return type: STRING

Usage notes:

In Impala 2.5 and higher, you can simplify queries that use many UPPER () and LOWER () calls to do case-insensitive comparisons, by using the ILIKE or IREGEXP operators instead. See [ILIKE Operator](#) on

LPAD(STRING str, INT len, STRING pad)

page 187 and [IREGEXP Operator](#) on page 190 for details.

Purpose: Returns a string of a specified length, based on the first argument string. If the specified string is too short, it is padded on the left with a repeating sequence of the characters from the pad string. If the specified string is too long, it is truncated on the right.

Return type: STRING

LTRIM(STRING a [, STRING chars_to_trim])

Purpose: Returns the argument string with all occurrences of characters specified by the second argument removed from the left side. Removes spaces if the second argument is not specified.

Return type: STRING

PARSE_URL(STRING urlString, STRING partToExtract [, STRING keyToExtract])

Purpose: Returns the portion of a URL corresponding to a specified part. The part argument can be 'PROTOCOL', 'HOST', 'PATH', 'REF', 'AUTHORITY', 'FILE', 'USERINFO', or 'QUERY'. Uppercase is required for these literal values. When requesting the QUERY portion of the URL, you can optionally specify a key to retrieve just the associated value from the key-value pairs in the query string.

Return type: STRING

Usage notes: This function is important for the traditional Hadoop use case of interpreting web logs. For example, if the web traffic data features raw URLs not divided into separate table columns, you can count visitors to a particular page by extracting the 'PATH' or 'FILE' field, or analyze search terms by extracting the corresponding key from the 'QUERY' field.

PRETTYPRINT_BYTES(TINYINT / SMALLINT / INT / BIGINT bytes)


Purpose: Formats numeric bytes in a human readable manner.

Return type: STRING

Examples:

```
select prettyprint_bytes(1),
       prettyprint_bytes(12345678),
       prettyprint_bytes(1234567890),
       prettyprint_bytes(1234567890123);

+-----+
+-----+
+-----+
+-----+
| prettyprint_bytes(1) |
| prettyprint_bytes(12345678) |
| prettyprint_bytes(1234567890) |
| prettyprint_bytes(1234567890123) |
+-----+
+-----+
+-----+
+-----+
```



REGEXP_ESCAPE(String source)

Purpose: The `REGEXP_ESCAPE()` function returns a string escaped for the special character in RE2 library so that the special characters are interpreted literally rather than as special characters. The following special characters are escaped by the function:

```
. \ + * ? [ ^ ] $ ( ) { } = ! < > | : -
```

Return type: STRING

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `. * ?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0](#) on page 873 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\d` which you would have to escape as `\\d`.

Examples:

This example shows escaping one of special characters in RE2.

```

+-----+
+
| regexp_escape('Hello.world')
|
+-----+
+
| Hello\world
|
+-----+
+

```

This example shows escaping all the special characters in RE2.

```
+-----+
+
|  regexp_escape('a.b\\c+d*e?f[g]h
|i(j)k{l}m=n!o<p>q|r:s-t')  |
+-----+
+
|  a\\.b\\.c\\.d\\.e\\.f\\[g\\]h\\$i\\(j\\)k\\{l
\\}m\\=n\\!o\\<p\\>q\\|r\\:s\\-t  |
+-----+
+
```

REGEXP_EXTRACT(STRING subject, STRING pattern, INT index)

Purpose: Returns the specified () group from a string based on a regular expression pattern. Group 0 refers to the entire extracted string, while group 1, 2, and so on refers to the first, second, and so on (. . .) portion.

Return type: STRING

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including . * ? for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0](#) on page 873 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\d` which you would have to escape as `\\d`.

Examples:

This example shows how group 0 matches the full pattern string, including the portion outside any () group:

```
[localhost:21000] > select
  regexp_extract('abcdef123ghi456jkl', '.*?
(\\d+)', 0);
+-----+
+
|
|  regexp_extract('abcdef123ghi456jkl',
'.*?(\\d+)', 0) |
```

```

+-----+
+
| abcdef123ghi456
|
+-----+
+
Returned 1 row(s) in 0.11s

```

This example shows how group 1 matches just the contents inside the first () group in the pattern string:

```

[localhost:21000] > select
  regexp_extract('abcdef123ghi456jkl', '.*?
  (\\d+)', 1);
+-----+
+
|
|
+-----+
+
| 456
|
+-----+
+
Returned 1 row(s) in 0.11s

```

Unlike in earlier Impala releases, the regular expression library used in Impala 2.0 and later supports the `.*?` idiom for non-greedy matches. This example shows how a pattern string starting with `.*?` matches the shortest possible portion of the source string, returning the rightmost set of lowercase letters. A pattern string both starting and ending with `.*?` finds two potential matches of equal length, and returns the first one found (the leftmost set of lowercase letters).

```

[localhost:21000] > select
  regexp_extract('AbcdBCdefGHI', '.*?
  ([[:lower:]]+)', 1);
+-----+
+
| regexp_extract('abdbcdefghi',
| '.*?([[:lower:]]+)', 1) |
+-----+
+
| def
|
+-----+
+
[localhost:21000] > select
  regexp_extract('AbcdBCdefGHI', '.*?
  ([[:lower:]]+).*?', 1);
+-----+
+
| regexp_extract('abdbcdefghi',
| '.*?([[:lower:]]+).*?', 1) |
+-----+
+
| bcd
|
+-----+

```


REGEXP_LIKE(STRING source, STRING pattern[, STRING options])

```
+-----+
+
```

Purpose: Returns `true` or `false` to indicate whether the source string contains anywhere inside it the regular expression given by the pattern. The optional third argument consists of letter flags that change how the match is performed, such as `i` for case-insensitive matching.

Syntax:

The flags that you can include in the optional third argument are:

- `c`: Case-sensitive matching (the default).
- `i`: Case-insensitive matching. If multiple instances of `c` and `i` are included in the third argument, the last such option takes precedence.
- `m`: Multi-line matching. The `^` and `$` operators match the start or end of any line within the source string, not the start and end of the entire string.
- `n`: Newline matching. The `.` operator can match the newline character. A repetition operator such as `.*` can match a portion of the source string that spans multiple lines.

Return type: `BOOLEAN`

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `.*?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0](#) on page 873 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\\d` which you would have to escape as `\\d`.

Examples:

This example shows how `regexp_like()` can test for the existence of various kinds of regular expression patterns within a source string:

```
-- Matches because the 'f' appears
   somewhere in 'foo'.
```

```

select regexp_like('foo','f');
+-----+
| regexp_like('foo','f') |
+-----+
| true                    |
+-----+

-- Does not match because the
-- comparison is case-sensitive by
-- default.
select regexp_like('foo','F');
+-----+
| regexp_like('foo','f') |
+-----+
| false                  |
+-----+

-- The 3rd argument can change the
-- matching logic, such as 'i' meaning
-- case-insensitive.
select regexp_like('foo','F','i');
+-----+
| regexp_like('foo','f','i') |
+-----+
| true                        |
+-----+

-- The familiar regular expression
-- notations work, such as ^ and $
-- anchors...
select regexp_like('foo','f$');
+-----+
| regexp_like('foo','f$') |
+-----+
| false                    |
+-----+

select regexp_like('foo','o$');
+-----+
| regexp_like('foo','o$') |
+-----+
| true                    |
+-----+

-- ...and repetition operators such
-- as * and +
select regexp_like('foooooobar','fo
+b');
+-----+
| regexp_like('foooooobar','fo+b') |
+-----+
| true                               |
+-----+
+

select
  regexp_like('foooooobar','fx*y*o*b');
+-----+
+

```

REGEXP_REPLACE(STRING initial, STRING pattern, STRING replacement)

```
| regexp_like('fooooooobar',  
| 'fx*y*o*b') |
```

```
+-----+  
+  
| true  
|
```

```
+-----+  
+
```

Purpose: Returns the initial argument with the regular expression pattern replaced by the final argument string.

Return type: STRING

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `. * ?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0](#) on page 873 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\d` which you would have to escape as `\\d`.

Examples:

These examples show how you can replace parts of a string matching a pattern with replacement text, which can include backreferences to any `()` groups in the pattern string. The backreference numbers start at 1, and any `\` characters must be escaped as `\\`.

Replace a character pattern with new text:

```
[localhost:21000] > select  
  regexp_replace('aaabbbbaaa', 'b  
+', 'xyz') ;  
+-----+  
+  
| regexp_replace('aaabbbbaaa', 'b+',  
| 'xyz') |
```

```
+-----+  
+  
| aaaxyzaaa  
|
```

```
+-----+  
+
```

```
Returned 1 row(s) in 0.11s
```

Replace a character pattern with substitution text that includes the original matching text:

```
[localhost:21000] > select
  regexp_replace('aaabbbbaaa', '(b
+)', '<\\1>');
+-----+
+
+ | regexp_replace('aaabbbbaaa', '(b
+)', '<\\1>') |
+-----+
+
+ | aaa<bbb>aaa
+ |
+-----+
+
Returned 1 row(s) in 0.11s
```

Remove all characters that are not digits:

```
[localhost:21000] > select
  regexp_replace('123-456-789', '^[^:digit:]', '');
+-----+
+
+ | regexp_replace('123-456-789',
+ | '^[^:digit:]', '') |
+-----+
+
+ | 123456789
+ |
+-----+
+
Returned 1 row(s) in 0.12s
```

REPEAT(STRING str, INT n)

REPLACE(STRING initial, STRING target, STRING replacement)

Purpose: Returns the argument string repeated a specified number of times.

Return type: STRING

Purpose: Returns the initial argument with all occurrences of the target string replaced by the replacement string.

Return type: STRING

Usage notes:

Because this function does not use any regular expression patterns, it is typically faster than `regexp_replace()` for simple string substitutions.

If any argument is NULL, the return value is NULL.

Matching is case-sensitive.

If the replacement string contains another instance of the target string, the expansion is only performed once, instead of applying again to the newly constructed string.

Added in: Impala 2.9.0

Examples:

```

-- Replace one string with another.
select replace('hello
world','world','earth');
+-----+
+
| replace('hello world', 'world',
'earth') |
+-----+
+
| hello earth
|
+-----+
+

-- All occurrences of the target
string are replaced.
select replace('hello
world','o','0');
+-----+
+
| replace('hello world', 'o', '0') |
+-----+
+
| hell0 w0rld
|
+-----+

-- If no match is found, the
original string is returned
unchanged.
select replace('hello
world','xyz','abc');
+-----+
+
| replace('hello world', 'xyz',
'abc') |
+-----+
+
| hello world
|
+-----+
+

```

REVERSE(STRING a)**Purpose:** Returns the argument string with characters in reversed order.**Return type:** STRING**RIGHT**(STRING a, INT num_chars)

See the STRRIGHT() function.

RPAD(STRING str, INT len, STRING pad)**Purpose:** Returns a string of a specified length, based on the first argument string. If the specified string is too short, it is padded on the right with a repeating sequence of the characters from the pad string. If the specified string is too long, it is truncated on the right.**Return type:** STRING**RTRIM**(STRING a [, STRING chars_to_trim])**Purpose:** Returns the argument string with all occurrences of characters specified by the second argument removed from the right side. Removes spaces if the second argument is not specified.

SPACE(INT *n*)

SPLIT_PART(STRING *source*, STRING *delimiter*, BIGINT *index*)

STRLEFT(STRING *a*, INT *num_chars*)

STRRIGHT(STRING *a*, INT *num_chars*)

SUBSTR(STRING *a*, INT *start* [, INT *len*]),
SUBSTRING(STRING *a*, INT *start* [, INT *len*])

TRANSLATE(STRING *input*, STRING *from*,
STRING *to*)

Return type: STRING

Purpose: Returns a concatenated string of the specified number of spaces. Shorthand for `REPEAT(' ', n)`.

Return type: STRING

Purpose: Returns the requested *index*th part of the input *source* string split by the *delimiter*.

- If *index* is a positive number, returns the *index*th part from the left within the *source* string.
- If *index* is a negative number, returns the *index*th part from the right within the *source* string.
- If *index* is 0, returns an error.

The *delimiter* can consist of multiple characters, not just a single character.

All matching of the delimiter is done exactly, not using any regular expression patterns.

Return type: STRING

Examples:

`SPLIT_PART('x,y,z',' ',2)` returns 'y'.

`SPLIT_PART('one***two***three','***',2)` returns 'two'.

`SPLIT_PART('abc@@def@@ghi','@@',3)` returns 'ghi'.

`SPLIT_PART('abc@@def@@ghi','@@',-3)` returns 'abc'.

Purpose: Returns the leftmost characters of the string. Shorthand for a call to `SUBSTR()` with 2 arguments.

Return type: STRING

Purpose: Returns the rightmost characters of the string. Shorthand for a call to `SUBSTR()` with 2 arguments.

Return type: STRING

Purpose: Returns the portion of the string starting at a specified point, optionally with a specified maximum length. The characters in the string are indexed starting at 1.

Return type: STRING

Purpose: Returns the input string with each character in the *from* argument replaced with the corresponding character in the *to* argument. The characters are matched in the order they appear in *from* and *to*.

For example: `translate('hello world','world','earth')` returns 'hetta earth'.

Return type: STRING

Usage notes:

If `from` contains more characters than `to`, the `from` characters that are beyond the length of `to` are removed in the result.

For example:

```
translate('abcdedg', 'bcd', 'l') returns
'aleg'.
```

```
translate('Unit Number#2', '# ', '_')
returns 'UnitNumber_2'.
```

If `from` is `NULL`, the function returns `NULL`.

If `to` contains more characters than `from`, the extra characters in `to` are ignored.

If `from` contains duplicate characters, the duplicate character is replaced with the first matching character in `to`.

For example: `translate ('hello', 'll', '67')` returns `'he66o'`.

TRIM(STRING a)

Purpose: Returns the input string with both leading and trailing spaces removed. The same as passing the string through both `LTRIM()` and `RTRIM()`.

Usage notes: Often used during data cleansing operations during the ETL cycle, if input values might still have surrounding spaces. For a more general-purpose function that can remove other leading and trailing characters besides spaces, see `BTRIM()`.

Return type: `STRING`

UPPER(STRING a), UCASE(STRING a)

Purpose: Returns the argument string converted to all-uppercase.

Return type: `STRING`

Usage notes:

In Impala 2.5 and higher, you can simplify queries that use many `UPPER()` and `LOWER()` calls to do case-insensitive comparisons, by using the `ILIKE` or `IREGEXP` operators instead. See [ILIKE Operator](#) on page 187 and [IREGEXP Operator](#) on page 190 for details.

Impala Miscellaneous Functions

Impala supports the following utility functions that do not operate on a particular column or data type:

- [CURRENT_DATABASE](#)
- [EFFECTIVE_USER](#)
- [GET_JSON_OBJECT](#)
- [LOGGED_IN_USER](#)
- [PID](#)
- [SLEEP](#)
- [USER](#)

- [UUID](#)
- [VERSION](#)
- [COORDINATOR](#)

CURRENT_DATABASE()

Purpose: Returns the database that the session is currently using, either `default` if no database has been selected, or whatever database the session switched to through a `USE` statement or the `impalad -d` option.

Return type: `STRING`

EFFECTIVE_USER()

Purpose: Typically returns the same value as `USER()`. If delegation is enabled, it returns the ID of the delegated user.

Return type: `STRING`

Added in: Impala 2.2.5

GET_JSON_OBJECT(`STRING json_str`, `STRING selector`)

Purpose: Extracts JSON object from the *json_str* based on the *selector* JSON path and returns the string of the extracted JSON object.

The function returns `NULL` if the input *json_str* is invalid or if nothing is selected based on the *selector* JSON path.

The following characters are supported in the *selector* JSON path:

- `$` : Denotes the root object
- `.` : Denotes the child operator
- `[]` : Denotes the subscript operator for array
- `*` : Denotes the wildcard for `[]` or `.`

Return type: `STRING`

Examples:

```
---- QUERY
SELECT GET_JSON_OBJECT ('{"a":true,
  "b":false, "c":true}', '$.*');
---- RESULTS
[true,false,true]
```

```
---- QUERY
SELECT GET_JSON_OBJECT(t.json,
  '$.a.b.c') FROM (VALUES (
  ('{"a": {"b": {"c": 1}}}' AS json),
  ('{"a": {"b": {"c": 2}}}' ),
  ('{"a": {"b": {"c": 3}}}' )
)) t
---- RESULTS
'1'
'2'
'3'
```

```
---- QUERY
SELECT GET_JSON_OBJECT(t.json,
  '$.a'),
  GET_JSON_OBJECT(t.json, '$.b'),
  GET_JSON_OBJECT(t.json, '$.c')
FROM (VALUES (
```



```
( ('{"a":1, "b":2, "c":3}' AS json),
  ('{"b":2, "c":3}'),
  ('{"c":3}')
)) t
---- RESULTS
'1','2','3'
'NULL','2','3'
'NULL','NULL','3'
```

```
---- QUERY
SELECT GET_JSON_OBJECT(t.json,
  '$[1]'),
  GET_JSON_OBJECT(t.json, '$[*]')
FROM (VALUES (
  ('["a", "b", "c"]' AS json),
  ('["a", "b"]'),
  ('["a"]')
)) t
---- RESULTS
'b', '["a", "b", "c"]'
'b', '["a", "b"]'
'NULL', 'a'
```

Added in: Impala 3.1

LOGGED_IN_USER()

Purpose: Typically returns the same value as `USER()`. If delegation is enabled, it returns the ID of the delegated user.

`LOGGED_IN_USER()` is an alias of `EFFECTIVE_USER()`.

Return type: STRING

Added in: Impala 3.1

PID()

Purpose: Returns the process ID of the `impalad` daemon that the session is connected to. You can use it during low-level debugging, to issue Linux commands that trace, show the arguments, and so on the `impalad` process.

Return type: INT

SLEEP(INT ms)

Purpose: Pauses the query for a specified number of milliseconds. For slowing down queries with small result sets enough to monitor runtime execution, memory usage, or other factors that otherwise would be difficult to capture during the brief interval of query execution. When used in the `SELECT` list, it is called once for each row in the result set; adjust the number of milliseconds accordingly. For example, a query `SELECT *, SLEEP(5) FROM table_with_1000_rows` would take at least 5 seconds to complete (5 milliseconds * 1000 rows in result set). To avoid an excessive number of concurrent queries, use this function for troubleshooting on test and development systems, not for production queries.

Return type: N/A

USER()

Purpose: Returns the username of the Linux user who is connected to the `impalad` daemon. Typically called a single time, in a query without any `FROM` clause, to understand how authorization settings apply in a security context; once you know the logged-in username, you can check which groups that user belongs to, and from the list of groups you can check which roles are available to those groups through the authorization policy file.

In Impala 2.0 and later, `user()` returns the full Kerberos principal string, such as `user@example.com`, in a Kerberized environment.

When delegation is enabled, consider calling the `EFFECTIVE_USER()` function instead.

Return type: `STRING`

UUID()

Purpose: Returns a *universal unique identifier*, a 128-bit value encoded as a string with groups of hexadecimal digits separated by dashes.

Each call to `UUID()` produces a new arbitrary value.

If you get a `UUID` for each row of a result set, you can use it as a unique identifier within a table, or even a unique ID across tables.

Return type: `STRING`

Added in: Impala 2.5.0

Usage notes:

Ascending numeric sequences of type `BIGINT` are often used as identifiers within a table, and as join keys across multiple tables. The `UUID()` value is a convenient alternative that does not require storing or querying the highest sequence number. For example, you can use it to quickly construct new unique identifiers during a data import job, or to combine data from different tables without the likelihood of ID collisions.

VERSION()

Purpose: Returns information such as the precise version number and build date for the `impalad` daemon that you are currently connected to. Typically used to confirm that you are connected to the expected level of Impala to use a particular feature, or to connect to several nodes and confirm they are all running the same level of `impalad`.

Return type: `STRING` (with one or more embedded newlines)

COORDINATOR()

Purpose: Returns the name of the host which is running the `impalad` daemon that is acting as the coordinator for the current query.

Return type: `STRING`

Added in: Impala 3.1

Impala Aggregate Functions

Aggregate functions are a special category with different rules. These functions calculate a return value across all the items in a result set, so they require a `FROM` clause in the query:

```
select count(product_id) from product_catalog;
select max(height), avg(height) from census_data where age > 20;
```

Aggregate functions also ignore `NULL` values rather than returning a `NULL` result. For example, if some rows have `NULL` for a particular column, those rows are ignored when computing the `AVG()` for that column. Likewise, specifying `COUNT(col_name)` in a query counts only those rows where `col_name` contains a non-`NULL` value.

APPX_MEDIAN Function

An aggregate function that returns a value that is approximately the median (midpoint) of values in the set of input values.

Syntax:

```
APPX_MEDIAN([DISTINCT | ALL] expression)
```

This function works with any input type, because the only requirement is that the type supports less-than and greater-than comparison operators.

Usage notes:

Because the return value represents the estimated midpoint, it might not reflect the precise midpoint value, especially if the cardinality of the input values is very high. If the cardinality is low (up to approximately 20,000), the result is more accurate because the sampling considers all or almost all of the different values.

Return type: Same as the input value, except for `CHAR` and `VARCHAR` arguments which produce a `STRING` result

The return value is always the same as one of the input values, not an “in-between” value produced by averaging.

Restrictions:

This function cannot be used in an analytic context. That is, the `OVER()` clause is not allowed at all with this function.

The `APPX_MEDIAN` function returns only the first 10 characters for string values (`string`, `varchar`, `char`). Additional characters are truncated.

Examples:

The following example uses a table of a million random floating-point numbers ranging up to approximately 50,000. The average is approximately 25,000. Because of the random distribution, we would expect the median to be close to this same number. Computing the precise median is a more intensive operation than computing the average, because it requires keeping track of every distinct value and how many times each occurs. The `APPX_MEDIAN()` function uses a sampling algorithm to return an approximate result, which in this case is close to the expected value. To make sure that the value is not substantially out of range due to a skewed distribution, subsequent queries confirm that there are approximately 500,000 values higher than the `APPX_MEDIAN()` value, and approximately 500,000 values lower than the `APPX_MEDIAN()` value.

```
[localhost:21000] > select min(x), max(x), avg(x) from million_numbers;
+-----+-----+-----+
| min(x) | max(x) | avg(x) |
+-----+-----+-----+
| 4.725693727250069 | 49994.56852674231 | 24945.38563793553 |
+-----+-----+-----+
[localhost:21000] > select appx_median(x) from million_numbers;
+-----+
| appx_median(x) |
+-----+
```

```

| 24721.6 |
+-----+
[localhost:21000] > select count(x) as higher from million_numbers where x >
(select appx_median(x) from million_numbers);
+-----+
| higher |
+-----+
| 502013 |
+-----+
[localhost:21000] > select count(x) as lower from million_numbers where x <
(select appx_median(x) from million_numbers);
+-----+
| lower  |
+-----+
| 497987 |
+-----+

```

The following example computes the approximate median using a subset of the values from the table, and then confirms that the result is a reasonable estimate for the midpoint.

```

[localhost:21000] > select appx_median(x) from million_numbers where x
between 1000 and 5000;
+-----+
| appx_median(x) |
+-----+
| 3013.107787358159 |
+-----+
[localhost:21000] > select count(x) as higher from million_numbers where x
between 1000 and 5000 and x > 3013.107787358159;
+-----+
| higher |
+-----+
| 37692  |
+-----+
[localhost:21000] > select count(x) as lower from million_numbers where x
between 1000 and 5000 and x < 3013.107787358159;
+-----+
| lower  |
+-----+
| 37089  |
+-----+

```

AVG Function

An aggregate function that returns the average value from a set of numbers or `TIMESTAMP` values. Its single argument can be numeric column, or the numeric result of a function or expression applied to the column value. Rows with a `NULL` value for the specified column are ignored. If the table is empty, or all the values supplied to `AVG` are `NULL`, `AVG` returns `NULL`.

Syntax:

```
AVG([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

When the query contains a `GROUP BY` clause, returns one value for each combination of grouping values.

Return type: `DOUBLE` for numeric values; `TIMESTAMP` for `TIMESTAMP` values

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an ARRAY of STRUCT items). The array is unpacked inside the query using join notation. The array elements are referenced using the ITEM pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as SUM() and AVG() are computed using the numeric R_NATIONKEY field, and the general-purpose MAX() and MIN() values are computed from the string N_NAME field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
```

```

    region, region.r_nations as r_nations
group by r_name
order by r_name;
+-----+-----+-----+-----+-----+-----+
+-----+
| r_name      | count | sum | avg  | minimum | maximum |
| distinct_vals |
+-----+-----+-----+-----+-----+-----+
+-----+
| AFRICA      | 5     | 50  | 10   | ALGERIA  | MOZAMBIQUE | 5
| |
| AMERICA     | 5     | 47  | 9.4  | ARGENTINA | UNITED STATES | 5
| |
| ASIA        | 5     | 68  | 13.6 | CHINA    | VIETNAM    | 5
| |
| EUROPE      | 5     | 77  | 15.4 | FRANCE   | UNITED KINGDOM | 5
| |
| MIDDLE EAST | 5     | 58  | 11.6 | EGYPT    | SAUDI ARABIA | 5
| |
+-----+-----+-----+-----+-----+-----+
+-----+

```

Examples:

```

-- Average all the non-NULL values in a column.
insert overwrite avg_t values (2),(4),(6),(null),(null);
-- The average of the above values is 4: (2+4+6) / 3. The 2 NULL values are
   ignored.
select avg(x) from avg_t;
-- Average only certain values from the column.
select avg(x) from t1 where month = 'January' and year = '2013';
-- Apply a calculation to the value of the column before averaging.
select avg(x/3) from t1;
-- Apply a function to the value of the column before averaging.
-- Here we are substituting a value of 0 for all NULLs in the column,
-- so that those rows do factor into the return value.
select avg(isnull(x,0)) from t1;
-- Apply some number-returning function to a string column and average the
   results.
-- If column s contains any NULLs, length(s) also returns NULL and those
   rows are ignored.
select avg(length(s)) from t1;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, avg(page_visits) from web_stats group by month, year;
-- Filter the input to eliminate duplicates before performing the
   calculation.
select avg(distinct x) from t1;
-- Filter the output after performing the calculation.
select avg(x) from t1 group by y having avg(x) between 1 and 20;

```

The following examples show how to use `AVG()` in an analytic context. They use a table containing integers from 1 to 10. Notice how the `AVG()` is reported for each input value, as opposed to the `GROUP BY` clause which condenses the result set.

```

select x, property, avg(x) over (partition by property) as avg from int_t
where property in ('odd','even');
+---+-----+-----+
| x | property | avg |
+---+-----+-----+
| 2 | even    | 6   |
| 4 | even    | 6   |

```

6	even	6
8	even	6
10	even	6
1	odd	5
3	odd	5
5	odd	5
7	odd	5
9	odd	5

Adding an `ORDER BY` clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use `AVG()` in an analytic context (that is, with an `OVER()` clause) to produce a running average of all the even values, then a running average of all the odd values. The basic `ORDER BY x` clause implicitly activates a window clause of `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, which is effectively the same as `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, therefore all of these examples produce the same results:

```
select x, property,
       avg(x) over (partition by property order by x) as 'cumulative average'
from int_t where property in ('odd','even');
```

x	property	cumulative average
2	even	2
4	even	3
6	even	4
8	even	5
10	even	6
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

```
select x, property,
       avg(x) over
       (
         partition by property
         order by x
         range between unbounded preceding and current row
       ) as 'cumulative average'
from int_t where property in ('odd','even');
```

x	property	cumulative average
2	even	2
4	even	3
6	even	4
8	even	5
10	even	6
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

```
select x, property,
       avg(x) over
       (
         partition by property
```

```

    order by x
  rows between unbounded preceding and current row
) as 'cumulative average'
from int_t where property in ('odd','even');

```

x	property	cumulative average
2	even	2
4	even	3
6	even	4
8	even	5
10	even	6
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

The following examples show how to construct a moving window, with a running average taking into account 1 row before and 1 row after the current row, within the same partition (all the even values or all the odd values). Because of a restriction in the Impala RANGE syntax, this type of moving window is possible with the **ROWS BETWEEN** clause but not the **RANGE BETWEEN** clause:

```

select x, property,
  avg(x) over
  (
    partition by property
    order by x
    rows between 1 preceding and 1 following
  ) as 'moving average'
from int_t where property in ('odd','even');

```

x	property	moving average
2	even	3
4	even	4
6	even	6
8	even	8
10	even	9
1	odd	2
3	odd	3
5	odd	5
7	odd	7
9	odd	8

```
-- Doesn't work because of syntax restriction on RANGE clause.
```

```

select x, property,
  avg(x) over
  (
    partition by property
    order by x
    range between 1 preceding and 1 following
  ) as 'moving average'
from int_t where property in ('odd','even');
ERROR: AnalysisException: RANGE is only supported with both the lower and
upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.

```

Restrictions:

Due to the way arithmetic on **FLOAT** and **DOUBLE** columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for

aggregate function calls such as `SUM()` and `AVG()` for `FLOAT` and `DOUBLE` columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the `DECIMAL` data type for such operations instead of `FLOAT` or `DOUBLE`.

Related information:

[Impala Analytic Functions](#) on page 569, [MAX Function](#) on page 551, [MIN Function](#) on page 555

COUNT Function

An aggregate function that returns the number of rows, or the number of non-NULL rows.

Syntax:

```
COUNT([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

Depending on the argument, `COUNT()` considers rows that meet certain conditions:

- The notation `COUNT(*)` includes NULL values in the total.
- The notation `COUNT(column_name)` only considers rows where the column contains a non-NULL value.
- You can also combine `COUNT` with the `DISTINCT` operator to eliminate duplicates before counting, and to count the combinations of values across multiple columns.

When the query contains a `GROUP BY` clause, returns one value for each combination of grouping values.

Return type: BIGINT

Usage notes:

If you frequently run aggregate functions such as `MIN()`, `MAX()`, and `COUNT(DISTINCT)` on partition key columns, consider enabling the `OPTIMIZE_PARTITION_KEY_SCANS` query option, which optimizes such queries. This feature is available in Impala 2.5 and higher. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(Impala 2.5 or higher only\)](#) on page 377 for the kinds of queries that this option applies to, and slight differences in how partitions are evaluated when this query option is enabled.

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an `ARRAY` of `STRUCT` items). The array is unpacked inside the query using join notation. The array elements are referenced using the `ITEM` pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as `SUM()` and `AVG()` are computed using the numeric `R_NATIONKEY` field, and the general-purpose `MAX()` and `MIN()` values are computed from the string `N_NAME` field.

```
describe region;
+-----+-----+-----+
| name      | type      | comment |
+-----+-----+-----+
| r_regionkey | smallint  |         |
| r_name     | string    |         |
| r_comment  | string    |         |
| r_nations  | array<struct<
|             |   n_nationkey:smallint,
|             |   n_name:string,
|             |   n_comment:string
|             | >>       |         |
+-----+-----+-----+

select r_name, r_nations.item.n_nationkey
```

```
from region, region.r_nations as r_nations
order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

```
-- How many rows total are in the table, regardless of NULL values?
select count(*) from t1;
-- How many rows are in the table with non-NULL values for a column?
select count(c1) from t1;
-- Count the rows that meet certain conditions.
-- Again, * includes NULLs, so COUNT(*) might be greater than COUNT(col).
select count(*) from t1 where x > 10;
select count(c1) from t1 where x > 10;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Combine COUNT and DISTINCT to find the number of unique values.
-- Must use column names rather than * with COUNT(DISTINCT ...) syntax.
-- Rows with NULL values are not counted.
select count(distinct c1) from t1;
-- Rows with a NULL value in _either_ column are not counted.
select count(distinct c1, c2) from t1;
-- Return more than one result.
select month, year, count(distinct visitor_id) from web_stats group by
    month, year;
```

The following examples show how to use COUNT() in an analytic context. They use a table containing integers from 1 to 10. Notice how the COUNT() is reported for each input value, as opposed to the GROUP BY clause which condenses the result set.

```
select x, property, count(x) over (partition by property) as count from
    int_t where property in ('odd','even');
```

x	property	count
2	even	5
4	even	5
6	even	5
8	even	5
10	even	5
1	odd	5
3	odd	5
5	odd	5
7	odd	5
9	odd	5

Adding an ORDER BY clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use COUNT() in an analytic context (that is, with an OVER() clause) to produce a running count of all the even values, then a running count of all the odd values. The basic ORDER BY x clause implicitly activates a window clause of RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW, which is effectively the same as ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW, therefore all of these examples produce the same results:

```
select x, property,
    count(x) over (partition by property order by x) as 'cumulative count'
from int_t where property in ('odd','even');
```

x	property	cumulative count
2	even	1
4	even	2
6	even	3
8	even	4
10	even	5
1	odd	1
3	odd	2

5	odd	3
7	odd	4
9	odd	5

```
select x, property,
       count(x) over
       (
         partition by property
         order by x
         range between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative count
2	even	1
4	even	2
6	even	3
8	even	4
10	even	5
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

```
select x, property,
       count(x) over
       (
         partition by property
         order by x
         rows between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative count
2	even	1
4	even	2
6	even	3
8	even	4
10	even	5
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

The following examples show how to construct a moving window, with a running count taking into account 1 row before and 1 row after the current row, within the same partition (all the even values or all the odd values). Therefore, the count is consistently 3 for rows in the middle of the window, and 2 for rows near the ends of the window, where there is no preceding or no following row in the partition. Because of a restriction in the Impala RANGE syntax, this type of moving window is possible with the ROWS BETWEEN clause but not the RANGE BETWEEN clause:

```
select x, property,
       count(x) over
       (
         partition by property
         order by x
         rows between 1 preceding and 1 following
```

```
) as 'moving total'
from int_t where property in ('odd','even');
```

x	property	moving total
2	even	2
4	even	3
6	even	3
8	even	3
10	even	2
1	odd	2
3	odd	3
5	odd	3
7	odd	3
9	odd	2

```
-- Doesn't work because of syntax restriction on RANGE clause.
```

```
select x, property,
       count(x) over
```

```
  (
    partition by property
    order by x
    range between 1 preceding and 1 following
  ) as 'moving total'
```

```
from int_t where property in ('odd','even');
```

```
ERROR: AnalysisException: RANGE is only supported with both the lower and
upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.
```

Related information:

[Impala Analytic Functions](#) on page 569

GROUP_CONCAT Function

An aggregate function that returns a single string representing the argument value concatenated together for each row of the result set. If the optional separator string is specified, the separator is added between each pair of concatenated values. The default separator is a comma followed by a space.

Syntax:

```
GROUP_CONCAT([ALL | DISTINCT] expression [, separator])
```

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

By default, returns a single string covering the whole result set. To include other columns or values in the result set, or to produce multiple concatenated strings for subsets of rows, include a `GROUP BY` clause in the query.

Return type: `STRING`

This function cannot be used in an analytic context. That is, the `OVER()` clause is not allowed at all with this function.

Currently, Impala returns an error if the result value grows larger than 1 GiB.

Examples:

The following examples illustrate various aspects of the `GROUP_CONCAT()` function.

You can call the function directly on a `STRING` column. To use it with a numeric column, cast the value to `STRING`.

```
[localhost:21000] > create table t1 (x int, s string);
[localhost:21000] > insert into t1 values (1, "one"), (3, "three"), (2,
"two"), (1, "one");
```

```
[localhost:21000] > select group_concat(s) from t1;
+-----+
| group_concat(s) |
+-----+
| one, three, two, one |
+-----+
[localhost:21000] > select group_concat(cast(x as string)) from t1;
+-----+
| group_concat(cast(x as string)) |
+-----+
| 1, 3, 2, 1 |
+-----+
```

Specify the **DISTINCT** keyword to eliminate duplicate values from the concatenated result:

```
[localhost:21000] > select group_concat(distinct s) from t1;
+-----+
| group_concat(distinct s) |
+-----+
| three, two, one |
+-----+
```

The optional separator lets you format the result in flexible ways. The separator can be an arbitrary string expression, not just a single character.

```
[localhost:21000] > select group_concat(s,"|") from t1;
+-----+
| group_concat(s, '|') |
+-----+
| one|three|two|one |
+-----+
[localhost:21000] > select group_concat(s,'---') from t1;
+-----+
| group_concat(s, '---') |
+-----+
| one---three---two---one |
+-----+
```

The default separator is a comma followed by a space. To get a comma-delimited result without extra spaces, specify a delimiter character that is only a comma.

```
[localhost:21000] > select group_concat(s,',') from t1;
+-----+
| group_concat(s, ',') |
+-----+
| one,three,two,one |
+-----+
```

Including a **GROUP BY** clause lets you produce a different concatenated result for each group in the result set. In this example, the only **X** value that occurs more than once is 1, so that is the only row in the result set where **GROUP_CONCAT()** returns a delimited value. For groups containing a single value, **GROUP_CONCAT()** returns the original value of its **STRING** argument.

```
[localhost:21000] > select x, group_concat(s) from t1 group by x;
+---+-----+
| x | group_concat(s) |
+---+-----+
| 2 | two |
| 3 | three |
| 1 | one, one |
+---+-----+
```

```
+---+-----+
```

MAX Function

An aggregate function that returns the maximum value from a set of numbers. Opposite of the MIN function. Its single argument can be numeric column, or the numeric result of a function or expression applied to the column value. Rows with a NULL value for the specified column are ignored. If the table is empty, or all the values supplied to MAX are NULL, MAX returns NULL.

Syntax:

```
MAX([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

When the query contains a GROUP BY clause, returns one value for each combination of grouping values.

Restrictions: In Impala 2.0 and higher, this function can be used as an analytic function, but with restrictions on any window clause. For MAX() and MIN(), the window clause is only allowed if the start bound is UNBOUNDED PRECEDING.

Return type: Same as the input value, except for CHAR and VARCHAR arguments which produce a STRING result

Usage notes:

If you frequently run aggregate functions such as MIN(), MAX(), and COUNT(DISTINCT) on partition key columns, consider enabling the OPTIMIZE_PARTITION_KEY_SCANS query option, which optimizes such queries. This feature is available in Impala 2.5 and higher. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(Impala 2.5 or higher only\)](#) on page 377 for the kinds of queries that this option applies to, and slight differences in how partitions are evaluated when this query option is enabled.

Complex type considerations:

To access a column with a complex type (ARRAY, STRUCT, or MAP) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an ARRAY of STRUCT items). The array is unpacked inside the query using join notation. The array elements are referenced using the ITEM pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as SUM() and AVG() are computed using the numeric R_NATIONKEY field, and the general-purpose MAX() and MIN() values are computed from the string N_NAME field.

```
describe region;
+-----+-----+-----+
| name      | type                                | comment |
+-----+-----+-----+
| r_regionkey | smallint                           |         |
| r_name      | string                             |         |
| r_comment   | string                             |         |
| r_nations   | array<struct<                      |         |
|              |   n_nationkey:smallint,            |         |
|              |   n_name:string,                  |         |
|              |   n_comment:string                |         |
|              | >>                                |         |
+-----+-----+-----+

select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
+-----+-----+
| r_name      | item.n_nationkey |
+-----+-----+
```

AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```

select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;

```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

```

-- Find the largest value for this column in the table.
select max(c1) from t1;
-- Find the largest value for this column from a subset of the table.

```



```

select max(c1) from t1 where month = 'January' and year = '2013';
-- Find the largest value from a set of numeric function results.
select max(length(s)) from t1;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, max(purchase_price) from store_stats group by month,
year;
-- Filter the input to eliminate duplicates before performing the
calculation.
select max(distinct x) from t1;

```

The following examples show how to use MAX() in an analytic context. They use a table containing integers from 1 to 10. Notice how the MAX() is reported for each input value, as opposed to the GROUP BY clause which condenses the result set.

```

select x, property, max(x) over (partition by property) as max from int_t
where property in ('odd','even');

```

x	property	max
2	even	10
4	even	10
6	even	10
8	even	10
10	even	10
1	odd	9
3	odd	9
5	odd	9
7	odd	9
9	odd	9

Adding an ORDER BY clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use MAX() in an analytic context (that is, with an OVER() clause) to display the smallest value of X encountered up to each row in the result set. The examples use two columns in the ORDER BY clause to produce a sequence of values that rises and falls, to illustrate how the MAX() result only increases or stays the same throughout each partition within the result set. The basic ORDER BY x clause implicitly activates a window clause of RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW, which is effectively the same as ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW, therefore all of these examples produce the same results:

```

select x, property,
max(x) over (order by property, x desc) as 'maximum to this point'
from int_t where property in ('prime','square');

```

x	property	maximum to this point
7	prime	7
5	prime	7
3	prime	7
2	prime	7
9	square	9
4	square	9
1	square	9

```

select x, property,
max(x) over
(
order by property, x desc
rows between unbounded preceding and current row
) as 'maximum to this point'

```

```
from int_t where property in ('prime','square');
```

x	property	maximum to this point
7	prime	7
5	prime	7
3	prime	7
2	prime	7
9	square	9
4	square	9
1	square	9

```
select x, property,
       max(x) over
       (
         order by property, x desc
         range between unbounded preceding and current row
       ) as 'maximum to this point'
from int_t where property in ('prime','square');
```

x	property	maximum to this point
7	prime	7
5	prime	7
3	prime	7
2	prime	7
9	square	9
4	square	9
1	square	9

The following examples show how to construct a moving window, with a running maximum taking into account all rows before and 1 row after the current row. Because of a restriction in the Impala RANGE syntax, this type of moving window is possible with the ROWS BETWEEN clause but not the RANGE BETWEEN clause. Because of an extra Impala restriction on the MAX() and MIN() functions in an analytic context, the lower bound must be UNBOUNDED PRECEDING.

```
select x, property,
       max(x) over
       (
         order by property, x
         rows between unbounded preceding and 1 following
       ) as 'local maximum'
from int_t where property in ('prime','square');
```

x	property	local maximum
2	prime	3
3	prime	5
5	prime	7
7	prime	7
1	square	7
4	square	9
9	square	9

```
-- Doesn't work because of syntax restriction on RANGE clause.
```

```
select x, property,
       max(x) over
       (
         order by property, x
         range between unbounded preceding and 1 following
```



```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

```
+-----+-----+-----+-----+-----+
+-----+
```

Examples:

```
-- Find the smallest value for this column in the table.
select min(c1) from t1;
-- Find the smallest value for this column from a subset of the table.
select min(c1) from t1 where month = 'January' and year = '2013';
-- Find the smallest value from a set of numeric function results.
select min(length(s)) from t1;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, min(purchase_price) from store_stats group by month,
year;
-- Filter the input to eliminate duplicates before performing the
  calculation.
select min(distinct x) from t1;
```

The following examples show how to use MIN() in an analytic context. They use a table containing integers from 1 to 10. Notice how the MIN() is reported for each input value, as opposed to the GROUP BY clause which condenses the result set.

```
select x, property, min(x) over (partition by property) as min from int_t
where property in ('odd','even');
```

x	property	min
2	even	2
4	even	2
6	even	2
8	even	2
10	even	2
1	odd	1
3	odd	1
5	odd	1
7	odd	1
9	odd	1

Adding an ORDER BY clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use MIN() in an analytic context (that is, with an OVER() clause) to display the smallest value of X encountered up to each row in the result set. The examples use two columns in the ORDER BY clause to produce a sequence of values that rises and falls, to illustrate how the MIN() result only decreases or stays the same throughout each partition within the result set. The basic ORDER BY x clause implicitly activates a window clause of RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW, which is effectively the same as ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW, therefore all of these examples produce the same results:

```
select x, property, min(x) over (order by property, x desc) as 'minimum to
  this point'
  from int_t where property in ('prime','square');
```

x	property	minimum to this point
7	prime	7
5	prime	5
3	prime	3
2	prime	2
9	square	2
4	square	2

```

| 1 | square | 1 |
+---+-----+---+

select x, property,
       min(x) over
       (
         order by property, x desc
         range between unbounded preceding and current row
       ) as 'minimum to this point'
from int_t where property in ('prime','square');

```

x	property	minimum to this point
7	prime	7
5	prime	5
3	prime	3
2	prime	2
9	square	2
4	square	2
1	square	1

```

select x, property,
       min(x) over
       (
         order by property, x desc
         rows between unbounded preceding and current row
       ) as 'minimum to this point'
from int_t where property in ('prime','square');

```

x	property	minimum to this point
7	prime	7
5	prime	5
3	prime	3
2	prime	2
9	square	2
4	square	2
1	square	1

The following examples show how to construct a moving window, with a running minimum taking into account all rows before and 1 row after the current row. Because of a restriction in the Impala RANGE syntax, this type of moving window is possible with the ROWS BETWEEN clause but not the RANGE BETWEEN clause. Because of an extra Impala restriction on the MAX() and MIN() functions in an analytic context, the lower bound must be UNBOUNDED PRECEDING.

```

select x, property,
       min(x) over
       (
         order by property, x desc
         rows between unbounded preceding and 1 following
       ) as 'local minimum'
from int_t where property in ('prime','square');

```

x	property	local minimum
7	prime	5
5	prime	3
3	prime	2
2	prime	2
9	square	2
4	square	1

```

| 1 | square | 1 |
+---+-----+---+

-- Doesn't work because of syntax restriction on RANGE clause.
select x, property,
       min(x) over
       (
         order by property, x desc
         range between unbounded preceding and 1 following
       ) as 'local minimum'
from int_t where property in ('prime','square');
ERROR: AnalysisException: RANGE is only supported with both the lower and
upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.

```

Related information:

[Impala Analytic Functions](#) on page 569, [MAX Function](#) on page 551, [AVG Function](#) on page 540

NDV Function

An aggregate function that returns an approximate value similar to the result of `COUNT(DISTINCT col)`, the “number of distinct values”. It is much faster than the combination of `COUNT` and `DISTINCT`, and uses a constant amount of memory and thus is less memory-intensive for columns with high cardinality.

Syntax:

```
NDV([DISTINCT | ALL] expression [,scale])
```

Note: The optional argument `scale` must be an integer and can be in the range from 1 to 10 and maps to a precision used by the HyperLogLog (HLL) algorithm with the following mapping formula:

```
precision = scale + 8
```

Therefore a scale of 1 is mapped to a precision of 9 and a scale of 10 is mapped to a precision of 18.

Without the optional argument, the precision which determines the total number of different estimators in the HLL algorithm will be still 10.

A large precision value generally produces a better estimation with less error than a small precision value. This is due to the extra number of estimators involved. The expense is at the need of extra memory. For a given precision `p`, the amount of memory used by the HLL algorithm is in the order of 2^p bytes.

When provided a scale of 10 against a total of 22 distinct data sets loaded into external Impala tables, the error will be computed as $\text{abs}(\langle \text{true_unique_value} \rangle - \langle \text{estimated_unique_value} \rangle) / \langle \text{true_unique_value} \rangle$

The scale of 10, mapped to the precision of 18, yielded the worst estimation error at 0.42% (for one set of 10 million integers), and average error no more than 0.17%. This was at the cost of 256Kb of memory for the internal data structure per evaluation of the HLL algorithm.

Usage notes:

This is the mechanism used internally by the `COMPUTE STATS` statement for computing the number of distinct values in a column.

Because this number is an estimate, it might not reflect the precise number of different values in the column, especially if the cardinality is very low or very high. If the estimated number is higher than the number of rows in the table, Impala adjusts the value internally during query planning.

Return type: `DOUBLE` in Impala 2.0 and higher; `STRING` in earlier releases

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or

value at the bottom of any nested type hierarchy in the column. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an ARRAY of STRUCT items). The array is unpacked inside the query using join notation. The array elements are referenced using the ITEM pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as SUM() and AVG() are computed using the numeric R_NATIONKEY field, and the general-purpose MAX() and MIN() values are computed from the string N_NAME field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
```



```

    max(r_nations.item.n_name) as maximum,
    ndv(r_nations.item.n_nationkey) as distinct_vals
from
    region, region.r_nations as r_nations
group by r_name
order by r_name;
+-----+-----+-----+-----+-----+-----+
+-----+
| r_name      | count | sum | avg  | minimum | maximum      |
| distinct_vals |
+-----+-----+-----+-----+-----+-----+
| AFRICA      | 5     | 50  | 10   | ALGERIA  | MOZAMBIQUE    | 5
| |
| AMERICA     | 5     | 47  | 9.4  | ARGENTINA | UNITED STATES | 5
| |
| ASIA        | 5     | 68  | 13.6 | CHINA    | VIETNAM       | 5
| |
| EUROPE      | 5     | 77  | 15.4 | FRANCE   | UNITED KINGDOM | 5
| |
| MIDDLE EAST | 5     | 58  | 11.6 | EGYPT    | SAUDI ARABIA  | 5
| |
+-----+-----+-----+-----+-----+-----+
+-----+

```

Restrictions:

This function cannot be used in an analytic context. That is, the `OVER ()` clause is not allowed at all with this function.

Examples:

The following example queries a billion-row table to illustrate the relative performance of `COUNT(DISTINCT)` and `NDV ()`. It shows how `COUNT(DISTINCT)` gives a precise answer, but is inefficient for large-scale data where an approximate result is sufficient. The `NDV ()` function gives an approximate result but is much faster.

```

select count(distinct coll) from sample_data;
+-----+
| count(distinct coll)|
+-----+
| 100000                |
+-----+
Fetched 1 row(s) in 20.13s

select cast(ndv(coll) as bigint) as coll from sample_data;
+-----+
| coll      |
+-----+
| 139017    |
+-----+
Fetched 1 row(s) in 8.91s

```

The following example shows how you can code multiple `NDV ()` calls in a single query, to easily learn which columns have substantially more or fewer distinct values. This technique is faster than running a sequence of queries with `COUNT(DISTINCT)` calls.

```

select cast(ndv(coll) as bigint) as coll, cast(ndv(col2) as bigint) as col2,
       cast(ndv(col3) as bigint) as col3, cast(ndv(col4) as bigint) as col4
from sample_data;
+-----+-----+-----+-----+
| coll      | col2      | col3      | col4      |
+-----+-----+-----+-----+
| 139017    | 282       | 46        | 145636240 |

```

```

+-----+-----+-----+-----+
Fetched 1 row(s) in 34.97s

select count(distinct col1) from sample_data;
+-----+
| count(distinct col1) |
+-----+
| 100000                |
+-----+
Fetched 1 row(s) in 20.13s

select count(distinct col2) from sample_data;
+-----+
| count(distinct col2) |
+-----+
| 278                  |
+-----+
Fetched 1 row(s) in 20.09s

select count(distinct col3) from sample_data;
+-----+
| count(distinct col3) |
+-----+
| 46                   |
+-----+
Fetched 1 row(s) in 19.12s

select count(distinct col4) from sample_data;
+-----+
| count(distinct col4) |
+-----+
| 147135880            |
+-----+
Fetched 1 row(s) in 266.95s

```

STDDEV, STDDEV_SAMP, STDDEV_POP Functions

An aggregate function that *standard deviation* of a set of numbers.

Syntax:

```
{ STDDEV | STDDEV_SAMP | STDDEV_POP } ([DISTINCT | ALL] expression)
```

This function works with any numeric data type.

Return type: DOUBLE in Impala 2.0 and higher; STRING in earlier releases

This function is typically used in mathematical formulas related to probability distributions.

The STDDEV_POP() and STDDEV_SAMP() functions compute the population standard deviation and sample standard deviation, respectively, of the input values. (STDDEV() is an alias for STDDEV_SAMP().) Both functions evaluate all input rows matched by the query. The difference is that STDDEV_SAMP() is scaled by $1/(N-1)$ while STDDEV_POP() is scaled by $1/N$.

If no input rows match the query, the result of any of these functions is NULL. If a single input row matches the query, the result of any of these functions is "0.0".

Examples:

This example demonstrates how STDDEV() and STDDEV_SAMP() return the same result, while STDDEV_POP() uses a slightly different calculation to reflect that the input data is considered part of a larger “population”.

```

[localhost:21000] > select stddev(score) from test_scores;
+-----+

```

```

| stddev(score) |
+-----+
| 28.5          |
+-----+
[localhost:21000] > select stddev_samp(score) from test_scores;
+-----+
| stddev_samp(score) |
+-----+
| 28.5              |
+-----+
[localhost:21000] > select stddev_pop(score) from test_scores;
+-----+
| stddev_pop(score) |
+-----+
| 28.4858           |
+-----+

```

This example demonstrates that, because the return value of these aggregate functions is a STRING, you must currently convert the result with CAST.

```

[localhost:21000] > create table score_stats as select cast(stddev(score) as
  decimal(7,4)) `standard_deviation`, cast(variance(score) as decimal(7,4))
  `variance` from test_scores;
+-----+
| summary          |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc score_stats;
+-----+-----+-----+
| name              | type              | comment |
+-----+-----+-----+
| standard_deviation | decimal(7,4)      |         |
| variance          | decimal(7,4)      |         |
+-----+-----+-----+

```

Restrictions:

This function cannot be used in an analytic context. That is, the OVER () clause is not allowed at all with this function.

Related information:

The STDDEV (), STDDEV_POP (), and STDDEV_SAMP () functions compute the standard deviation (square root of the variance) based on the results of VARIANCE (), VARIANCE_POP (), and VARIANCE_SAMP () respectively. See [VARIANCE, VARIANCE_SAMP, VARIANCE_POP, VAR_SAMP, VAR_POP Functions](#) on page 568 for details about the variance property.

SUM Function

An aggregate function that returns the sum of a set of numbers. Its single argument can be numeric column, or the numeric result of a function or expression applied to the column value. Rows with a NULL value for the specified column are ignored. If the table is empty, or all the values supplied to MIN are NULL, SUM returns NULL.

Syntax:

```
SUM([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

When the query contains a GROUP BY clause, returns one value for each combination of grouping values.

Return type: BIGINT for integer arguments, DOUBLE for floating-point arguments

Complex type considerations:

To access a column with a complex type (ARRAY, STRUCT, or MAP) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an ARRAY of STRUCT items). The array is unpacked inside the query using join notation. The array elements are referenced using the ITEM pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as SUM() and AVG() are computed using the numeric R_NATIONKEY field, and the general-purpose MAX() and MIN() values are computed from the string N_NAME field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
```

```

    avg(r_nations.item.n_nationkey) as avg,
    min(r_nations.item.n_name) as minimum,
    max(r_nations.item.n_name) as maximum,
    ndv(r_nations.item.n_nationkey) as distinct_vals
from
    region, region.r_nations as r_nations
group by r_name
order by r_name;

```

r_name	count	sum	avg	minimum	maximum	
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

The following example shows how to use SUM() to compute the total for all the values in the table, a subset of values, or the sum for each combination of values in the GROUP BY clause:

```

-- Total all the values for this column in the table.
select sum(c1) from t1;
-- Find the total for this column from a subset of the table.
select sum(c1) from t1 where month = 'January' and year = '2013';
-- Find the total from a set of numeric function results.
select sum(length(s)) from t1;
-- Often used with functions that return predefined values to compute a
  score.
select sum(case when grade = 'A' then 1.0 when grade = 'B' then 0.75 else 0)
  as class_honors from test_scores;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, sum(purchase_price) from store_stats group by month,
  year;
-- Filter the input to eliminate duplicates before performing the
  calculation.
select sum(distinct x) from t1;

```

The following examples show how to use SUM() in an analytic context. They use a table containing integers from 1 to 10. Notice how the SUM() is reported for each input value, as opposed to the GROUP BY clause which condenses the result set.

```

select x, property, sum(x) over (partition by property) as sum from int_t
  where property in ('odd','even');

```

x	property	sum
2	even	30
4	even	30
6	even	30
8	even	30

10	even	30
1	odd	25
3	odd	25
5	odd	25
7	odd	25
9	odd	25

Adding an `ORDER BY` clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use `SUM()` in an analytic context (that is, with an `OVER()` clause) to produce a running total of all the even values, then a running total of all the odd values. The basic `ORDER BY x` clause implicitly activates a window clause of `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, which is effectively the same as `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, therefore all of these examples produce the same results:

```
select x, property,
       sum(x) over (partition by property order by x) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
2	even	2
4	even	6
6	even	12
8	even	20
10	even	30
1	odd	1
3	odd	4
5	odd	9
7	odd	16
9	odd	25

```
select x, property,
       sum(x) over
       (
         partition by property
         order by x
         range between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
2	even	2
4	even	6
6	even	12
8	even	20
10	even	30
1	odd	1
3	odd	4
5	odd	9
7	odd	16
9	odd	25

```
select x, property,
       sum(x) over
       (
         partition by property
         order by x
         rows between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

```
) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
2	even	2
4	even	6
6	even	12
8	even	20
10	even	30
1	odd	1
3	odd	4
5	odd	9
7	odd	16
9	odd	25

Changing the direction of the ORDER BY clause causes the intermediate results of the cumulative total to be calculated in a different order:

```
select sum(x) over (partition by property order by x desc) as 'cumulative
total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
10	even	10
8	even	18
6	even	24
4	even	28
2	even	30
9	odd	9
7	odd	16
5	odd	21
3	odd	24
1	odd	25

The following examples show how to construct a moving window, with a running total taking into account 1 row before and 1 row after the current row, within the same partition (all the even values or all the odd values). Because of a restriction in the Impala RANGE syntax, this type of moving window is possible with the ROWS BETWEEN clause but not the RANGE BETWEEN clause:

```
select x, property,
sum(x) over
(
partition by property
order by x
rows between 1 preceding and 1 following
) as 'moving total'
from int_t where property in ('odd','even');
```

x	property	moving total
2	even	6
4	even	12
6	even	18
8	even	24
10	even	18
1	odd	4
3	odd	9
5	odd	15

7	odd	21
9	odd	16

+-----+

```
-- Doesn't work because of syntax restriction on RANGE clause.
select x, property,
       sum(x) over
       (
         partition by property
         order by x
         range between 1 preceding and 1 following
       ) as 'moving total'
from int_t where property in ('odd','even');
ERROR: AnalysisException: RANGE is only supported with both the lower and
upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.
```

Restrictions:

Due to the way arithmetic on `FLOAT` and `DOUBLE` columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for aggregate function calls such as `SUM()` and `AVG()` for `FLOAT` and `DOUBLE` columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the `DECIMAL` data type for such operations instead of `FLOAT` or `DOUBLE`.

Related information:

[Impala Analytic Functions](#) on page 569

VARIANCE, VARIANCE_SAMP, VARIANCE_POP, VAR_SAMP, VAR_POP Functions

An aggregate function that returns the *variance* of a set of numbers. This is a mathematical property that signifies how far the values spread apart from the mean. The return value can be zero (if the input is a single value, or a set of identical values), or a positive number otherwise.

Syntax:

```
{ VARIANCE | VAR[ IANCE ]_SAMP | VAR[ IANCE ]_POP } ([DISTINCT |
ALL] expression)
```

This function works with any numeric data type.

Return type: `DOUBLE` in Impala 2.0 and higher; `STRING` in earlier releases

This function is typically used in mathematical formulas related to probability distributions.

The `VARIANCE_SAMP()` and `VARIANCE_POP()` functions compute the sample variance and population variance, respectively, of the input values. (`VARIANCE()` is an alias for `VARIANCE_SAMP()`.) Both functions evaluate all input rows matched by the query. The difference is that `STDDEV_SAMP()` is scaled by $1/(N-1)$ while `STDDEV_POP()` is scaled by $1/N$.

The functions `VAR_SAMP()` and `VAR_POP()` are the same as `VARIANCE_SAMP()` and `VARIANCE_POP()`, respectively. These aliases are available in Impala 2.0 and later.

If no input rows match the query, the result of any of these functions is `NULL`. If a single input row matches the query, the result of any of these functions is "0.0".

Examples:

This example demonstrates how `VARIANCE()` and `VARIANCE_SAMP()` return the same result, while `VARIANCE_POP()` uses a slightly different calculation to reflect that the input data is considered part of a larger "population".

```
[localhost:21000] > select variance(score) from test_scores;
+-----+
| variance(score) |
```



```

+-----+
| 812.25 |
+-----+
[localhost:21000] > select variance_samp(score) from test_scores;
+-----+
| variance_samp(score) |
+-----+
| 812.25               |
+-----+
[localhost:21000] > select variance_pop(score) from test_scores;
+-----+
| variance_pop(score)  |
+-----+
| 811.438              |
+-----+

```

This example demonstrates that, because the return value of these aggregate functions is a `STRING`, you convert the result with `CAST` if you need to do further calculations as a numeric value.

```

[localhost:21000] > create table score_stats as select cast(stddev(score) as
  decimal(7,4)) `standard_deviation`, cast(variance(score) as decimal(7,4))
  `variance` from test_scores;
+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc score_stats;
+-----+-----+-----+
| name          | type          | comment |
+-----+-----+-----+
| standard_deviation | decimal(7,4) |         |
| variance      | decimal(7,4) |         |
+-----+-----+-----+

```

Restrictions:

This function cannot be used in an analytic context. That is, the `OVER ()` clause is not allowed at all with this function.

Related information:

The `STDDEV ()`, `STDDEV_POP ()`, and `STDDEV_SAMP ()` functions compute the standard deviation (square root of the variance) based on the results of `VARIANCE ()`, `VARIANCE_POP ()`, and `VARIANCE_SAMP ()` respectively. See [STDDEV, STDDEV_SAMP, STDDEV_POP Functions](#) on page 562 for details about the standard deviation property.

Impala Analytic Functions

Analytic functions (also known as window functions) are a special category of built-in functions. Like aggregate functions, they examine the contents of multiple input rows to compute each output value. However, rather than being limited to one result value per `GROUP BY` group, they operate on *windows* where the input rows are ordered and grouped using flexible conditions expressed through an `OVER ()` clause.

Added in: Impala 2.0.0

Some functions, such as `LAG ()` and `RANK ()`, can only be used in this analytic context. Some aggregate functions do double duty: when you call the aggregation functions such as `MAX ()`, `SUM ()`, `AVG ()`, and so on with an `OVER ()` clause, they produce an output value for each row, based on computations across other rows in the window.

Although analytic functions often compute the same value you would see from an aggregate function in a `GROUP BY` query, the analytic functions produce a value for each row in the result set rather than a single value for each group.

This flexibility lets you include additional columns in the `SELECT` list, offering more opportunities for organizing and filtering the result set.

Analytic function calls are only allowed in the `SELECT` list and in the outermost `ORDER BY` clause of the query. During query processing, analytic functions are evaluated after other query stages such as `joins`, `WHERE`, and `GROUP BY`.

The rows that are part of each partition are analyzed by computations across an ordered or unordered set of rows. For example, `COUNT()` and `SUM()` might be applied to all the rows in the partition, in which case the order of analysis does not matter. The `ORDER BY` clause might be used inside the `OVER()` clause to defines the ordering that applies to functions such as `LAG()` and `FIRST_VALUE()`.

Analytic functions are frequently used in fields such as finance and science to provide trend, outlier, and bucketed analysis for large data sets. You might also see the term “window functions” in database literature, referring to the sequence of rows (the “window”) that the function call applies to, particularly when the `OVER` clause includes a `ROWS` or `RANGE` keyword.

The following sections describe the analytic query clauses and the pure analytic functions provided by Impala. For usage information about aggregate functions in an analytic context, see [Impala Aggregate Functions](#) on page 539.

OVER Clause

The `OVER` clause is required for calls to pure analytic functions such as `LEAD()`, `RANK()`, and `FIRST_VALUE()`. When you include an `OVER` clause with calls to aggregate functions such as `MAX()`, `COUNT()`, or `SUM()`, they operate as analytic functions.

Syntax:

```
function(args) OVER([partition_by_clause] [order_by_clause] [window_clause])

partition_by_clause ::= PARTITION BY expr [, expr ...]
order_by_clause ::= ORDER BY expr [ASC | DESC] [NULLS FIRST | NULLS LAST]
[, expr [ASC | DESC] [NULLS FIRST | NULLS LAST] ...]
window_clause: See Window Clause
```

PARTITION BY clause:

The `PARTITION BY` clause acts much like the `GROUP BY` clause in the outermost block of a query. It divides the rows into groups containing identical values in one or more columns. These logical groups are known as *partitions*. Throughout the discussion of analytic functions, “partitions” refers to the groups produced by the `PARTITION BY` clause, not to partitioned tables. However, note the following limitation that applies specifically to analytic function calls involving partitioned tables.

In queries involving both analytic functions and partitioned tables, partition pruning only occurs for columns named in the `PARTITION BY` clause of the analytic function call. For example, if an analytic function query has a clause such as `WHERE year=2016`, the way to make the query prune all other `YEAR` partitions is to include `PARTITION BY year` in the analytic function call; for example, `OVER (PARTITION BY year, other_columns other_analytic_clauses)`.

The sequence of results from an analytic function “resets” for each new partition in the result set. That is, the set of preceding or following rows considered by the analytic function always come from a single partition. Any `MAX()`, `SUM()`, `ROW_NUMBER()`, and so on apply to each partition independently. Omit the `PARTITION BY` clause to apply the analytic operation to all the rows in the table.

ORDER BY clause:

The `ORDER BY` clause works much like the `ORDER BY` clause in the outermost block of a query. It defines the order in which rows are evaluated for the entire input set, or for each group produced by a `PARTITION BY` clause. You can order by one or multiple expressions, and for each expression optionally choose ascending or descending order and whether nulls come first or last in the sort order. Because this `ORDER BY` clause only defines the order in which rows are evaluated, if you want the results to be output in a specific order, also include an `ORDER BY` clause in the outer block of the query.

When the `ORDER BY` clause is omitted, the analytic function applies to all items in the group produced by the `PARTITION BY` clause. When the `ORDER BY` clause is included, the analysis can apply to all or a subset of the items in the group, depending on the optional window clause.

The order in which the rows are analyzed is only defined for those columns specified in `ORDER BY` clauses.

One difference between the analytic and outer uses of the `ORDER BY` clause: inside the `OVER` clause, `ORDER BY 1` or other integer value is interpreted as a constant sort value (effectively a no-op) rather than referring to column 1.

Window clause:

The window clause is only allowed in combination with an `ORDER BY` clause. If the `ORDER BY` clause is specified but the window clause is not, the default window is `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`. See [Window Clause](#) on page 572 for full details.

HBase considerations:

Because HBase tables are optimized for single-row lookups rather than full scans, analytic functions using the `OVER ()` clause are not recommended for HBase tables. Although such queries work, their performance is lower than on comparable tables using HDFS data files.

Parquet considerations:

Analytic functions are very efficient for Parquet tables. The data that is examined during evaluation of the `OVER ()` clause comes from a specified set of columns, and the values for each column are arranged sequentially within each data file.

Text table considerations:

Analytic functions are convenient to use with text tables for exploratory business intelligence. When the volume of data is substantial, prefer to use Parquet tables for performance-critical analytic queries.

Added in: Impala 2.0.0

Examples:

The following example shows how to synthesize a numeric sequence corresponding to all the rows in a table. The new table has the same columns as the old one, plus an additional column `ID` containing the integers 1, 2, 3, and so on, corresponding to the order of a `TIMESTAMP` column in the original table.

```
CREATE TABLE events_with_id AS
SELECT
    row_number() OVER (ORDER BY date_and_time) AS id,
    c1, c2, c3, c4
FROM events;
```

The following example shows how to determine the number of rows containing each value for a column. Unlike a corresponding `GROUP BY` query, this one can analyze a single column and still return all values (not just the distinct ones) from the other columns.

```
SELECT x, y, z,
    count() OVER (PARTITION BY x) AS how_many_x
FROM t1;
```

Restrictions:

You cannot directly combine the `DISTINCT` operator with analytic function calls. You can put the analytic function call in a `WITH` clause or an inline view, and apply the `DISTINCT` operator to its result set.

```
WITH t1 AS (SELECT x, sum(x) OVER (PARTITION BY x) AS total FROM t1)
SELECT DISTINCT x, total FROM t1;
```

Window Clause

Certain analytic functions accept an optional *window clause*, which makes the function analyze only certain rows “around” the current row rather than all rows in the partition. For example, you can get a moving average by specifying some number of preceding and following rows, or a running count or running total by specifying all rows up to the current position. This clause can result in different analytic results for rows within the same partition.

The window clause is supported with the `AVG()`, `COUNT()`, `FIRST_VALUE()`, `LAST_VALUE()`, and `SUM()` functions. For `MAX()` and `MIN()`, the window clause only allowed if the start bound is `UNBOUNDED PRECEDING`.

Syntax:

```
ROWS BETWEEN [ { m | UNBOUNDED } PRECEDING | CURRENT ROW ] [ AND [ CURRENT ROW
| { UNBOUNDED | n } FOLLOWING ] ]
RANGE BETWEEN [ { m | UNBOUNDED } PRECEDING | CURRENT ROW ] [ AND [ CURRENT ROW
| { UNBOUNDED | n } FOLLOWING ] ]
```

`ROWS BETWEEN` defines the size of the window in terms of the indexes of the rows in the result set. The size of the window is predictable based on the clauses the position within the result set.

`RANGE BETWEEN` does not currently support numeric arguments to define a variable-size sliding window.

Currently, Impala supports only some combinations of arguments to the `RANGE` clause:

- `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW` (the default when `ORDER BY` is specified and the window clause is omitted)
- `RANGE BETWEEN CURRENT ROW AND UNBOUNDED FOLLOWING`
- `RANGE BETWEEN UNBOUNDED PRECEDING AND UNBOUNDED FOLLOWING`

When `RANGE` is used, `CURRENT ROW` includes not just the current row but all rows that are tied with the current row based on the `ORDER BY` expressions.

Added in: Impala 2.0.0

Examples:

The following examples show financial data for a fictional stock symbol JDR. The closing price moves up and down each day.

```
create table stock_ticker (stock_symbol string, closing_price decimal(8,2),
  closing_date timestamp);
...load some data...
select * from stock_ticker order by stock_symbol, closing_date
```

stock_symbol	closing_price	closing_date
JDR	12.86	2014-10-02 00:00:00
JDR	12.89	2014-10-03 00:00:00
JDR	12.94	2014-10-04 00:00:00
JDR	12.55	2014-10-05 00:00:00
JDR	14.03	2014-10-06 00:00:00
JDR	14.75	2014-10-07 00:00:00
JDR	13.98	2014-10-08 00:00:00

The queries use analytic functions with window clauses to compute moving averages of the closing price. For example, `ROWS BETWEEN 1 PRECEDING AND 1 FOLLOWING` produces an average of the value from a 3-day span, producing a different value for each row. The first row, which has no preceding row, only gets averaged with the row following it. If the table contained more than one stock symbol, the `PARTITION BY` clause would limit the window for the moving average to only consider the prices for a single stock.

```
select stock_symbol, closing_date, closing_price,
  avg(closing_price) over (partition by stock_symbol order by closing_date
```

```
rows between 1 preceding and 1 following) as moving_average
from stock_ticker;
```

stock_symbol	closing_date	closing_price	moving_average
JDR	2014-10-02 00:00:00	12.86	12.87
JDR	2014-10-03 00:00:00	12.89	12.89
JDR	2014-10-04 00:00:00	12.94	12.79
JDR	2014-10-05 00:00:00	12.55	13.17
JDR	2014-10-06 00:00:00	14.03	13.77
JDR	2014-10-07 00:00:00	14.75	14.25
JDR	2014-10-08 00:00:00	13.98	14.36

The clause `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW` produces a cumulative moving average, from the earliest data up to the value for each day.

```
select stock_symbol, closing_date, closing_price,
       avg(closing_price) over (partition by stock_symbol order by closing_date
                               rows between unbounded preceding and current row) as moving_average
from stock_ticker;
```

stock_symbol	closing_date	closing_price	moving_average
JDR	2014-10-02 00:00:00	12.86	12.86
JDR	2014-10-03 00:00:00	12.89	12.87
JDR	2014-10-04 00:00:00	12.94	12.89
JDR	2014-10-05 00:00:00	12.55	12.81
JDR	2014-10-06 00:00:00	14.03	13.05
JDR	2014-10-07 00:00:00	14.75	13.33
JDR	2014-10-08 00:00:00	13.98	13.42

AVG Function - Analytic Context

You can include an `OVER` clause with a call to this function to use it as an analytic function. See [AVG Function](#) on page 540 for details and examples.

COUNT Function - Analytic Context

You can include an `OVER` clause with a call to this function to use it as an analytic function. See [COUNT Function](#) on page 545 for details and examples.

CUME_DIST Function (Impala 2.3 or higher only)

Returns the cumulative distribution of a value. The value for each row in the result set is greater than 0 and less than or equal to 1.

Syntax:

```
CUME_DIST (expr)
OVER ([partition_by_clause] order_by_clause)
```

The `ORDER BY` clause is required. The `PARTITION BY` clause is optional. The window clause is not allowed.

Usage notes:

Within each partition of the result set, the `CUME_DIST()` value represents an ascending sequence that ends at 1. Each value represents the proportion of rows in the partition whose values are less than or equal to the value in the current row.

If the sequence of input values contains ties, the `CUME_DIST()` results are identical for the tied values.

Impala only supports the `CUME_DIST()` function in an analytic context, not as a regular aggregate function.

Examples:

This example uses a table with 9 rows. The `CUME_DIST()` function evaluates the entire table because there is no `PARTITION BY` clause, with the rows ordered by the weight of the animal. the sequence of values shows that 1/9 of the values are less than or equal to the lightest animal (mouse), 2/9 of the values are less than or equal to the second-lightest animal, and so on up to the heaviest animal (elephant), where 9/9 of the rows are less than or equal to its weight.

```
create table animals (name string, kind string, kilos decimal(9,3));
insert into animals values
  ('Elephant', 'Mammal', 4000), ('Giraffe', 'Mammal', 1200), ('Mouse',
'Mammal', 0.020),
  ('Condor', 'Bird', 15), ('Horse', 'Mammal', 500), ('Owl', 'Bird', 2.5),
  ('Ostrich', 'Bird', 145), ('Polar bear', 'Mammal', 700), ('Housecat',
'Mammal', 5);
```

```
select name, cume_dist() over (order by kilos) from animals;
```

name	cume_dist() OVER(...)
Elephant	1
Giraffe	0.8888888888888888
Polar bear	0.7777777777777778
Horse	0.6666666666666666
Ostrich	0.5555555555555556
Condor	0.4444444444444444
Housecat	0.3333333333333333
Owl	0.2222222222222222
Mouse	0.1111111111111111

Using a `PARTITION BY` clause produces a separate sequence for each partition group, in this case one for mammals and one for birds. Because there are 3 birds and 6 mammals, the sequence illustrates how 1/3 of the “Bird” rows have a `kilos` value that is less than or equal to the lightest bird, 1/6 of the “Mammal” rows have a `kilos` value that is less than or equal to the lightest mammal, and so on until both the heaviest bird and heaviest mammal have a `CUME_DIST()` value of 1.

```
select name, kind, cume_dist() over (partition by kind order by kilos) from
animals
```

name	kind	cume_dist() OVER(...)
Ostrich	Bird	1
Condor	Bird	0.6666666666666666
Owl	Bird	0.3333333333333333
Elephant	Mammal	1
Giraffe	Mammal	0.8333333333333334
Polar bear	Mammal	0.6666666666666666
Horse	Mammal	0.5
Housecat	Mammal	0.3333333333333333
Mouse	Mammal	0.1666666666666667

We can reverse the ordering within each partition group by using an `ORDER BY ... DESC` clause within the `OVER()` clause. Now the lightest (smallest value of `kilos`) animal of each kind has a `CUME_DIST()` value of 1.

```
select name, kind, cume_dist() over (partition by kind order by kilos desc)
from animals
```

name	kind	cume_dist() OVER(...)
Owl	Bird	1

Condor	Bird	0.6666666666666666
Ostrich	Bird	0.3333333333333333
Mouse	Mammal	1
Housecat	Mammal	0.8333333333333334
Horse	Mammal	0.6666666666666666
Polar bear	Mammal	0.5
Giraffe	Mammal	0.3333333333333333
Elephant	Mammal	0.1666666666666667

The following example manufactures some rows with identical values in the `kilos` column, to demonstrate how the results look in case of tie values. For simplicity, it only shows the `CUME_DIST()` sequence for the “Bird” rows. Now with 3 rows all with a value of 15, all of those rows have the same `CUME_DIST()` value. 4/5 of the rows have a value for `kilos` that is less than or equal to 15.

```
insert into animals values ('California Condor', 'Bird', 15), ('Andean Condor', 'Bird', 15)
```

```
select name, kind, cume_dist() over (order by kilos) from animals where kind = 'Bird';
```

name	kind	cume_dist() OVER(...)
Ostrich	Bird	1
Condor	Bird	0.8
California Condor	Bird	0.8
Andean Condor	Bird	0.8
Owl	Bird	0.2

The following example shows how to use an `ORDER BY` clause in the outer block to order the result set in case of ties. Here, all the “Bird” rows are together, then in descending order by the result of the `CUME_DIST()` function, and all tied `CUME_DIST()` values are ordered by the animal name.

```
select name, kind, cume_dist() over (partition by kind order by kilos) as
  ordering
  from animals
 where
  kind = 'Bird'
 order by kind, ordering desc, name;
```

name	kind	ordering
Ostrich	Bird	1
Andean Condor	Bird	0.8
California Condor	Bird	0.8
Condor	Bird	0.8
Owl	Bird	0.2

DENSE_RANK Function

Returns an ascending sequence of integers, starting with 1. The output sequence produces duplicate integers for duplicate values of the `ORDER BY` expressions. After generating duplicate output values for the “tied” input values, the function continues the sequence with the next higher integer. Therefore, the sequence contains duplicates but no gaps when the input contains duplicates. Starts the sequence over for each group produced by the `PARTITIONED BY` clause.

Syntax:

```
DENSE_RANK() OVER([partition_by_clause] order_by_clause)
```

The `PARTITION BY` clause is optional. The `ORDER BY` clause is required. The window clause is not allowed.

Usage notes:

Often used for top-N and bottom-N queries. For example, it could produce a “top 10” report including all the items with the 10 highest values, even if several items tied for 1st place.

Similar to `ROW_NUMBER` and `RANK`. These functions differ in how they treat duplicate combinations of values.

Added in: Impala 2.0.0

Examples:

The following example demonstrates how the `DENSE_RANK()` function identifies where each value “places” in the result set, producing the same result for duplicate values, but with a strict sequence from 1 to the number of groups. For example, when results are ordered by the `x` column, both 1 values are tied for first; both 2 values are tied for second; and so on.

```
select x, dense_rank() over(order by x) as rank, property from int_t;
```

x	rank	property
1	1	square
1	1	odd
2	2	even
2	2	prime
3	3	prime
3	3	odd
4	4	even
4	4	square
5	5	odd
5	5	prime
6	6	even
6	6	perfect
7	7	lucky
7	7	lucky
7	7	lucky
7	7	odd
7	7	prime
8	8	even
9	9	square
9	9	odd
10	10	round
10	10	even

The following examples show how the `DENSE_RANK()` function is affected by the `PARTITION` property within the `ORDER BY` clause.

Partitioning by the `PROPERTY` column groups all the even, odd, and so on values together, and `DENSE_RANK()` returns the place of each value within the group, producing several ascending sequences.

```
select x, dense_rank() over(partition by property order by x) as rank,
property from int_t;
```

x	rank	property
2	1	even
4	2	even
6	3	even
8	4	even
10	5	even
7	1	lucky
7	1	lucky

7	1	lucky
1	1	odd
3	2	odd
5	3	odd
7	4	odd
9	5	odd
6	1	perfect
2	1	prime
3	2	prime
5	3	prime
7	4	prime
10	1	round
1	1	square
4	2	square
9	3	square

Partitioning by the X column groups all the duplicate numbers together and returns the place each value within the group; because each value occurs only 1 or 2 times, DENSE_RANK () designates each X value as either first or second within its group.

```
select x, dense_rank() over(partition by x order by property) as rank,
       property from int_t;
```

x	rank	property
1	1	odd
1	2	square
2	1	even
2	2	prime
3	1	odd
3	2	prime
4	1	even
4	2	square
5	1	odd
5	2	prime
6	1	even
6	2	perfect
7	1	lucky
7	1	lucky
7	1	lucky
7	2	odd
7	3	prime
8	1	even
9	1	odd
9	2	square
10	1	even
10	2	round

The following example shows how DENSE_RANK () produces a continuous sequence while still allowing for ties. In this case, Croesus and Midas both have the second largest fortune, while Crassus has the third largest. (In [RANK Function](#) on page 585, you see a similar query with the RANK () function that shows that while Crassus has the third largest fortune, he is the fourth richest person.)

```
select dense_rank() over (order by net_worth desc) as placement, name,
       net_worth from wealth order by placement, name;
```

placement	name	net_worth
1	Solomon	20000000000.00
2	Croesus	10000000000.00

2	Midas	1000000000.00
3	Crassus	500000000.00
4	Scrooge	80000000.00

Related information:

[RANK Function](#) on page 585, [ROW_NUMBER Function](#) on page 587

FIRST_VALUE Function

Returns the expression value from the first row in the window. The return value is NULL if the input expression is NULL.

Syntax:

```
FIRST_VALUE(expr) OVER([partition_by_clause] order_by_clause
[window_clause])
```

The PARTITION BY clause is optional. The ORDER BY clause is required. The window clause is optional.

Usage notes:

If any duplicate values occur in the tuples evaluated by the ORDER BY clause, the result of this function is not deterministic. Consider adding additional ORDER BY columns to ensure consistent ordering.

Added in: Impala 2.0.0

Examples:

The following example shows a table with a wide variety of country-appropriate greetings. For consistency, we want to standardize on a single greeting for each country. The FIRST_VALUE () function helps to produce a mail merge report where every person from the same country is addressed with the same greeting.

```
select name, country, greeting from mail_merge
```

name	country	greeting
Pete	USA	Hello
John	USA	Hi
Boris	Germany	Guten tag
Michael	Germany	Guten morgen
Bjorn	Sweden	Hej
Mats	Sweden	Tja

```
select country, name,
       first_value(greeting)
         over (partition by country order by name, greeting) as greeting
  from mail_merge;
```

country	name	greeting
Germany	Boris	Guten tag
Germany	Michael	Guten tag
Sweden	Bjorn	Hej
Sweden	Mats	Hej
USA	John	Hi
USA	Pete	Hi

Changing the order in which the names are evaluated changes which greeting is applied to each group.

```
select country, name,
```

```
first_value(greeting)
  over (partition by country order by name desc, greeting) as greeting
from mail_merge;
```

country	name	greeting
Germany	Michael	Guten morgen
Germany	Boris	Guten morgen
Sweden	Mats	Tja
Sweden	Bjorn	Tja
USA	Pete	Hello
USA	John	Hello

Related information:

[LAST_VALUE Function](#) on page 580

LAG Function

This function returns the value of an expression using column values from a preceding row. You specify an integer offset, which designates a row position some number of rows previous to the current row. Any column references in the expression argument refer to column values from that prior row. Typically, the table contains a time sequence or numeric sequence column that clearly distinguishes the ordering of the rows.

Syntax:

```
LAG (expr [, offset] [, default])
  OVER ([partition_by_clause] order_by_clause)
```

The ORDER BY clause is required. The PARTITION BY clause is optional. The window clause is not allowed.

Usage notes:

Sometimes used as an alternative to doing a self-join.

Added in: Impala 2.0.0

Examples:

The following example uses the same stock data created in [Window Clause](#) on page 572. For each day, the query prints the closing price alongside the previous day's closing price. The first row for each stock symbol has no previous row, so that LAG() value is NULL.

```
select stock_symbol, closing_date, closing_price,
       lag(closing_price,1) over (partition by stock_symbol order by
       closing_date) as "yesterday closing"
from stock_ticker
order by closing_date;
```

stock_symbol	closing_date	closing_price	yesterday closing
JDR	2014-09-13 00:00:00	12.86	NULL
JDR	2014-09-14 00:00:00	12.89	12.86
JDR	2014-09-15 00:00:00	12.94	12.89
JDR	2014-09-16 00:00:00	12.55	12.94
JDR	2014-09-17 00:00:00	14.03	12.55
JDR	2014-09-18 00:00:00	14.75	14.03
JDR	2014-09-19 00:00:00	13.98	14.75

The following example does an arithmetic operation between the current row and a value from the previous row, to produce a delta value for each day. This example also demonstrates how ORDER BY works independently in the different parts of the query. The ORDER BY closing_date in the OVER clause makes the query analyze the rows

in chronological order. Then the outer query block uses `ORDER BY closing_date DESC` to present the results with the most recent date first.

```
select stock_symbol, closing_date, closing_price,
       cast(
         closing_price - lag(closing_price,1) over
           (partition by stock_symbol order by closing_date)
         as decimal(8,2)
       )
       as "change from yesterday"
from stock_ticker
order by closing_date desc;
```

stock_symbol	closing_date	closing_price	change from yesterday
JDR	2014-09-19 00:00:00	13.98	-0.76
JDR	2014-09-18 00:00:00	14.75	0.72
JDR	2014-09-17 00:00:00	14.03	1.47
JDR	2014-09-16 00:00:00	12.55	-0.38
JDR	2014-09-15 00:00:00	12.94	0.04
JDR	2014-09-14 00:00:00	12.89	0.03
JDR	2014-09-13 00:00:00	12.86	NULL

Related information:

This function is the converse of [LEAD Function](#) on page 581.

LAST_VALUE Function

Returns the expression value from the last row in the window. This same value is repeated for all result rows for the group. The return value is NULL if the input expression is NULL.

Syntax:

```
LAST_VALUE(expr) OVER([partition_by_clause] order_by_clause [window_clause])
```

The `PARTITION BY` clause is optional. The `ORDER BY` clause is required. The window clause is optional.

Usage notes:

If any duplicate values occur in the tuples evaluated by the `ORDER BY` clause, the result of this function is not deterministic. Consider adding additional `ORDER BY` columns to ensure consistent ordering.

Added in: Impala 2.0.0

Examples:

The following example uses the same `MAIL_MERGE` table as in the example for [FIRST_VALUE Function](#) on page 578. Because the default window when `ORDER BY` is used is `BETWEEN UNBOUNDED PRECEDING AND`

CURRENT ROW, the query requires the UNBOUNDED FOLLOWING to look ahead to subsequent rows and find the last value for each country.

```
select country, name,
       last_value(greeting) over (
         partition by country order by name, greeting
         rows between unbounded preceding and unbounded following
       ) as greeting
from mail_merge
```

country	name	greeting
Germany	Boris	Guten morgen
Germany	Michael	Guten morgen
Sweden	Bjorn	Tja
Sweden	Mats	Tja
USA	John	Hello
USA	Pete	Hello

Related information:

[FIRST_VALUE Function](#) on page 578

LEAD Function

This function returns the value of an expression using column values from a following row. You specify an integer offset, which designates a row position some number of rows after to the current row. Any column references in the expression argument refer to column values from that later row. Typically, the table contains a time sequence or numeric sequence column that clearly distinguishes the ordering of the rows.

Syntax:

```
LEAD (expr [, offset] [, default])
OVER ([partition_by_clause] order_by_clause)
```

The ORDER BY clause is required. The PARTITION BY clause is optional. The window clause is not allowed.

Usage notes:

Sometimes used as an alternative to doing a self-join.

Added in: Impala 2.0.0

Examples:

The following example uses the same stock data created in [Window Clause](#) on page 572. The query analyzes the closing price for a stock symbol, and for each day evaluates if the closing price for the following day is higher or lower.

```
select stock_symbol, closing_date, closing_price,
       case
         (lead(closing_price,1)
          over (partition by stock_symbol order by closing_date)
          - closing_price) > 0
         when true then "higher"
         when false then "flat or lower"
       end as "trending"
from stock_ticker
order by closing_date;
```

stock_symbol	closing_date	closing_price	trending
JDR	2014-09-13 00:00:00	12.86	higher

JDR	2014-09-14 00:00:00	12.89	higher
JDR	2014-09-15 00:00:00	12.94	flat or lower
JDR	2014-09-16 00:00:00	12.55	higher
JDR	2014-09-17 00:00:00	14.03	higher
JDR	2014-09-18 00:00:00	14.75	flat or lower
JDR	2014-09-19 00:00:00	13.98	NULL

Related information:

This function is the converse of [LAG Function](#) on page 579.

MAX Function - Analytic Context

You can include an OVER clause with a call to this function to use it as an analytic function. See [MAX Function](#) on page 551 for details and examples.

MIN Function - Analytic Context

You can include an OVER clause with a call to this function to use it as an analytic function. See [MIN Function](#) on page 555 for details and examples.

NTILE Function (Impala 2.3 or higher only)

Returns the “bucket number” associated with each row, between 1 and the value of an expression. For example, creating 100 buckets puts the lowest 1% of values in the first bucket, while creating 10 buckets puts the lowest 10% of values in the first bucket. Each partition can have a different number of buckets.

Syntax:

```
NTILE (expr [, offset ...]
      OVER ([partition_by_clause] order_by_clause)
```

The ORDER BY clause is required. The PARTITION BY clause is optional. The window clause is not allowed.

Usage notes:

The “ntile” name is derived from the practice of dividing result sets into fourths (quartile), tenths (decile), and so on. The NTILE () function divides the result set based on an arbitrary percentile value.

The number of buckets must be a positive integer.

The number of items in each bucket is identical or almost so, varying by at most 1. If the number of items does not divide evenly between the buckets, the remaining N items are divided evenly among the first N buckets.

If the number of buckets N is greater than the number of input rows in the partition, then the first N buckets each contain one item, and the remaining buckets are empty.

Examples:

The following example shows divides groups of animals into 4 buckets based on their weight. The ORDER BY ... DESC clause in the OVER () clause means that the heaviest 25% are in the first group, and the lightest 25% are in the fourth group. (The ORDER BY in the outermost part of the query shows how you can order the final result set independently from the order in which the rows are evaluated by the OVER () clause.) Because there are 9 rows in the group, divided into 4 buckets, the first bucket receives the extra item.

```
create table animals (name string, kind string, kilos decimal(9,3));

insert into animals values
  ('Elephant', 'Mammal', 4000), ('Giraffe', 'Mammal', 1200), ('Mouse',
'Mammal', 0.020),
  ('Condor', 'Bird', 15), ('Horse', 'Mammal', 500), ('Owl', 'Bird', 2.5),
  ('Ostrich', 'Bird', 145), ('Polar bear', 'Mammal', 700), ('Housecat',
'Mammal', 5);
```

```
select name, ntile(4) over (order by kilos desc) as quarter
from animals
order by quarter desc;
```

name	quarter
Owl	4
Mouse	4
Condor	3
Housecat	3
Horse	2
Ostrich	2
Elephant	1
Giraffe	1
Polar bear	1

The following examples show how the PARTITION clause works for the NTILE () function. Here, we divide each kind of animal (mammal or bird) into 2 buckets, the heavier half and the lighter half.

```
select name, kind, ntile(2) over (partition by kind order by kilos desc) as
half
from animals
order by kind;
```

name	kind	half
Ostrich	Bird	1
Condor	Bird	1
Owl	Bird	2
Elephant	Mammal	1
Giraffe	Mammal	1
Polar bear	Mammal	1
Horse	Mammal	2
Housecat	Mammal	2
Mouse	Mammal	2

Again, the result set can be ordered independently from the analytic evaluation. This next example lists all the animals heaviest to lightest, showing that elephant and giraffe are in the “top half” of mammals by weight, while housecat and mouse are in the “bottom half”.

```
select name, kind, ntile(2) over (partition by kind order by kilos desc) as
half
from animals
order by kilos desc;
```

name	kind	half
Elephant	Mammal	1
Giraffe	Mammal	1
Polar bear	Mammal	1
Horse	Mammal	2
Ostrich	Bird	1
Condor	Bird	1
Housecat	Mammal	2
Owl	Bird	2
Mouse	Mammal	2

PERCENT_RANK Function (Impala 2.3 or higher only)**Syntax:**

```
PERCENT_RANK (expr)
  OVER ([partition_by_clause] order_by_clause)
```

Calculates the rank, expressed as a percentage, of each row within a group of rows. If rank is the value for that same row from the RANK () function (from 1 to the total number of rows in the partition group), then the PERCENT_RANK () value is calculated as $(rank - 1) / (rows_in_group - 1)$. If there is only a single item in the partition group, its PERCENT_RANK () value is 0.

The ORDER BY clause is required. The PARTITION BY clause is optional. The window clause is not allowed.

Usage notes:

This function is similar to the RANK and CUME_DIST () functions: it returns an ascending sequence representing the position of each row within the rows of the same partition group. The actual numeric sequence is calculated differently, and the handling of duplicate (tied) values is different.

The return values range from 0 to 1 inclusive. The first row in each partition group always has the value 0. A NULL value is considered the lowest possible value. In the case of duplicate input values, all the corresponding rows in the result set have an identical value: the lowest PERCENT_RANK () value of those tied rows. (In contrast to CUME_DIST (), where all tied rows have the highest CUME_DIST () value.)

Examples:

The following example uses the same ANIMALS table as the examples for CUME_DIST () and NTILE (), with a few additional rows to illustrate the results where some values are NULL or there is only a single row in a partition group.

```
insert into animals values ('Komodo dragon', 'Reptile', 70);
insert into animals values ('Unicorn', 'Mythical', NULL);
insert into animals values ('Fire-breathing dragon', 'Mythical', NULL);
```

As with CUME_DIST (), there is an ascending sequence for each kind of animal. For example, the “Birds” and “Mammals” rows each have a PERCENT_RANK () sequence that ranges from 0 to 1. The “Reptile” row has a PERCENT_RANK () of 0 because that partition group contains only a single item. Both “Mythical” animals have a PERCENT_RANK () of 0 because a NULL is considered the lowest value within its partition group.

```
select name, kind, percent_rank() over (partition by kind order by kilos)
from animals;
```

name	kind	percent_rank() OVER(...)
Mouse	Mammal	0
Housecat	Mammal	0.2
Horse	Mammal	0.4
Polar bear	Mammal	0.6
Giraffe	Mammal	0.8
Elephant	Mammal	1
Komodo dragon	Reptile	0
Owl	Bird	0
California Condor	Bird	0.25
Andean Condor	Bird	0.25
Condor	Bird	0.25
Ostrich	Bird	1
Fire-breathing dragon	Mythical	0
Unicorn	Mythical	0

RANK Function

Returns an ascending sequence of integers, starting with 1. The output sequence produces duplicate integers for duplicate values of the `ORDER BY` expressions. After generating duplicate output values for the “tied” input values, the function increments the sequence by the number of tied values. Therefore, the sequence contains both duplicates and gaps when the input contains duplicates. Starts the sequence over for each group produced by the `PARTITIONED BY` clause.

Syntax:

```
RANK() OVER([partition_by_clause] order_by_clause)
```

The `PARTITION BY` clause is optional. The `ORDER BY` clause is required. The window clause is not allowed.

Usage notes:

Often used for top-N and bottom-N queries. For example, it could produce a “top 10” report including several items that were tied for 10th place.

Similar to `ROW_NUMBER` and `DENSE_RANK`. These functions differ in how they treat duplicate combinations of values.

Added in: Impala 2.0.0

Examples:

The following example demonstrates how the `RANK()` function identifies where each value “places” in the result set, producing the same result for duplicate values, and skipping values in the sequence to account for the number of duplicates. For example, when results are ordered by the `X` column, both 1 values are tied for first; both 2 values are tied for third; and so on.

```
select x, rank() over(order by x) as rank, property from int_t;
```

x	rank	property
1	1	square
1	1	odd
2	3	even
2	3	prime
3	5	prime
3	5	odd
4	7	even
4	7	square
5	9	odd
5	9	prime
6	11	even
6	11	perfect
7	13	lucky
7	13	lucky
7	13	lucky
7	13	odd
7	13	prime
8	18	even
9	19	square
9	19	odd
10	21	round
10	21	even

The following examples show how the `RANK()` function is affected by the `PARTITION` property within the `ORDER BY` clause.

Partitioning by the `PROPERTY` column groups all the even, odd, and so on values together, and `RANK ()` returns the place of each value within the group, producing several ascending sequences.

```
select x, rank() over(partition by property order by x) as rank, property
from int_t;
```

x	rank	property
2	1	even
4	2	even
6	3	even
8	4	even
10	5	even
7	1	lucky
7	1	lucky
7	1	lucky
1	1	odd
3	2	odd
5	3	odd
7	4	odd
9	5	odd
6	1	perfect
2	1	prime
3	2	prime
5	3	prime
7	4	prime
10	1	round
1	1	square
4	2	square
9	3	square

Partitioning by the `X` column groups all the duplicate numbers together and returns the place each value within the group; because each value occurs only 1 or 2 times, `RANK ()` designates each `X` value as either first or second within its group.

```
select x, rank() over(partition by x order by property) as rank, property
from int_t;
```

x	rank	property
1	1	odd
1	2	square
2	1	even
2	2	prime
3	1	odd
3	2	prime
4	1	even
4	2	square
5	1	odd
5	2	prime
6	1	even
6	2	perfect
7	1	lucky
7	1	lucky
7	1	lucky
7	4	odd
7	5	prime
8	1	even
9	1	odd
9	2	square
10	1	even

10	2	round
----	---	-------

The following example shows how a magazine might prepare a list of history's wealthiest people. Croesus and Midas are tied for second, then Crassus is fourth.

```
select rank() over (order by net_worth desc) as rank, name, net_worth from
wealth order by rank, name;
```

rank	name	net_worth
1	Solomon	20000000000.00
2	Croesus	10000000000.00
2	Midas	10000000000.00
4	Crassus	5000000000.00
5	Scrooge	800000000.00

Related information:

[DENSE_RANK Function](#) on page 575, [ROW_NUMBER Function](#) on page 587

ROW_NUMBER Function

Returns an ascending sequence of integers, starting with 1. Starts the sequence over for each group produced by the `PARTITIONED BY` clause. The output sequence includes different values for duplicate input values. Therefore, the sequence never contains any duplicates or gaps, regardless of duplicate input values.

Syntax:

```
ROW_NUMBER() OVER([partition_by_clause] order_by_clause)
```

The `ORDER BY` clause is required. The `PARTITION BY` clause is optional. The window clause is not allowed.

Usage notes:

Often used for top-N and bottom-N queries where the input values are known to be unique, or precisely N rows are needed regardless of duplicate values.

Because its result value is different for each row in the result set (when used without a `PARTITION BY` clause), `ROW_NUMBER()` can be used to synthesize unique numeric ID values, for example for result sets involving unique values or tuples.

Similar to `RANK` and `DENSE_RANK`. These functions differ in how they treat duplicate combinations of values.

Added in: Impala 2.0.0

Examples:

The following example demonstrates how `ROW_NUMBER()` produces a continuous numeric sequence, even though some values of X are repeated.

```
select x, row_number() over(order by x, property) as row_number, property
from int_t;
```

x	row_number	property
1	1	odd
1	2	square
2	3	even
2	4	prime
3	5	odd
3	6	prime
4	7	even

4	8	square
5	9	odd
5	10	prime
6	11	even
6	12	perfect
7	13	lucky
7	14	lucky
7	15	lucky
7	16	odd
7	17	prime
8	18	even
9	19	odd
9	20	square
10	21	even
10	22	round

The following example shows how a financial institution might assign customer IDs to some of history's wealthiest figures. Although two of the people have identical net worth figures, unique IDs are required for this purpose. `ROW_NUMBER()` produces a sequence of five different values for the five input rows.

```
select row_number() over (order by net_worth desc) as account_id, name,
       net_worth
from wealth order by account_id, name;
```

account_id	name	net_worth
1	Solomon	2000000000.00
2	Croesus	1000000000.00
3	Midas	1000000000.00
4	Crassus	500000000.00
5	Scrooge	80000000.00

Related information:

[RANK Function](#) on page 585, [DENSE_RANK Function](#) on page 575

SUM Function - Analytic Context

You can include an `OVER` clause with a call to this function to use it as an analytic function. See [SUM Function](#) on page 563 for details and examples.

User-Defined Functions (UDFs)

User-defined functions (frequently abbreviated as UDFs) let you code your own application logic for processing column values during an Impala query. For example, a UDF could perform calculations using an external math library, combine several column values into one, do geospatial calculations, or other kinds of tests and transformations that are outside the scope of the built-in SQL operators and functions.

You can use UDFs to simplify query logic when producing reports, or to transform data in flexible ways when copying from one table to another with the `INSERT ... SELECT` syntax.

You might be familiar with this feature from other database products, under names such as stored functions or stored routines.

Impala support for UDFs is available in Impala 1.2 and higher:

- In Impala 1.1, using UDFs in a query required using the Hive shell. (Because Impala and Hive share the same metastore database, you could switch to Hive to run just those queries requiring UDFs, then switch back to Impala.)

- Starting in Impala 1.2, Impala can run both high-performance native code UDFs written in C++, and Java-based Hive UDFs that you might already have written.
- Impala can run scalar UDFs that return a single value for each row of the result set, and user-defined aggregate functions (UDAFs) that return a value based on a set of rows. Currently, Impala does not support user-defined table functions (UDTFs) or window functions.

UDF Concepts

Depending on your use case, you might write all-new functions, reuse Java UDFs that you have already written for Hive, or port Hive Java UDF code to higher-performance native Impala UDFs in C++. You can code either scalar functions for producing results one row at a time, or more complex aggregate functions for doing analysis across. The following sections discuss these different aspects of working with UDFs.

UDFs and UDAFs

Depending on your use case, the user-defined functions (UDFs) you write might accept or produce different numbers of input and output values:

- The most general kind of user-defined function (the one typically referred to by the abbreviation UDF) takes a single input value and produces a single output value. When used in a query, it is called once for each row in the result set. For example:

```
select customer_name, is_frequent_customer(customer_id) from customers;
select obfuscate(sensitive_column) from sensitive_data;
```

- A user-defined aggregate function (UDAF) accepts a group of values and returns a single value. You use UDAFs to summarize and condense sets of rows, in the same style as the built-in COUNT, MAX(), SUM(), and AVG() functions. When called in a query that uses the GROUP BY clause, the function is called once for each combination of GROUP BY values. For example:

```
-- Evaluates multiple rows but returns a single value.
select closest_restaurant(latitude, longitude) from places;

-- Evaluates batches of rows and returns a separate value for each batch.
select most_profitable_location(store_id, sales, expenses, tax_rate,
    depreciation) from franchise_data group by year;
```

- Currently, Impala does not support other categories of user-defined functions, such as user-defined table functions (UDTFs) or window functions.

Native Impala UDFs

Impala supports UDFs written in C++, in addition to supporting existing Hive UDFs written in Java. Where practical, use C++ UDFs because the compiled native code can yield higher performance, with UDF execution time often 10x faster for a C++ UDF than the equivalent Java UDF.

Using Hive UDFs with Impala

Impala can run Java-based user-defined functions (UDFs), originally written for Hive, with no changes, subject to the following conditions:

- The parameters and return value must all use scalar data types supported by Impala. For example, complex or nested types are not supported.
- Hive/Java UDFs must extend `org.apache.hadoop.hive.ql.exec.UDF` class.
- Currently, Hive UDFs that accept or return the `TIMESTAMP` type are not supported.
- Prior to Impala 2.5 the return type must be a “Writable” type such as `Text` or `IntWritable`, rather than a Java primitive type such as `String` or `int`. Otherwise, the UDF returns `NULL`. In Impala 2.5 and higher, this restriction is lifted, and both UDF arguments and return values can be Java primitive types.
- Hive UDAFs and UDTFs are not supported.

- Typically, a Java UDF will execute several times slower in Impala than the equivalent native UDF written in C++.
- In Impala 2.5 and higher, you can transparently call Hive Java UDFs through Impala, or call Impala Java UDFs through Hive. This feature does not apply to built-in Hive functions. Any Impala Java UDFs created with older versions must be re-created using new `CREATE FUNCTION` syntax, without any signature for arguments or the return value.

To take full advantage of the Impala architecture and performance features, you can also write Impala-specific UDFs in C++.

For background about Java-based Hive UDFs, see the [Hive documentation for UDFs](#). For examples or tutorials for writing such UDFs, search the web for related blog posts.

The ideal way to understand how to reuse Java-based UDFs (originally written for Hive) with Impala is to take some of the Hive built-in functions (implemented as Java UDFs) and take the applicable JAR files through the UDF deployment process for Impala, creating new UDFs with different names:

1. Take a copy of the Hive JAR file containing the Hive built-in functions. For example, the path might be like `/usr/lib/hive/lib/hive-exec-0.10.0.jar`, with different version numbers corresponding to your specific level of .
2. Use `jar tf jar_file` to see a list of the classes inside the JAR. You will see names like `org/apache/hadoop/hive/ql/udf/UDFLower.class` and `org/apache/hadoop/hive/ql/udf/UDFOPNegative.class`. Make a note of the names of the functions you want to experiment with. When you specify the entry points for the Impala `CREATE FUNCTION` statement, change the slash characters to dots and strip off the `.class` suffix, for example `org.apache.hadoop.hive.ql.udf.UDFLower` and `org.apache.hadoop.hive.ql.udf.UDFOPNegative`.
3. Copy that file to an HDFS location that Impala can read. (In the examples here, we renamed the file to `hive-builtins.jar` in HDFS for simplicity.)
4. For each Java-based UDF that you want to call through Impala, issue a `CREATE FUNCTION` statement, with a `LOCATION` clause containing the full HDFS path of the JAR file, and a `SYMBOL` clause with the fully qualified name of the class, using dots as separators and without the `.class` extension. Remember that user-defined functions are associated with a particular database, so issue a `USE` statement for the appropriate database first, or specify the SQL function name as `db_name.function_name`. Use completely new names for the SQL functions, because Impala UDFs cannot have the same name as Impala built-in functions.
5. Call the function from your queries, passing arguments of the correct type to match the function signature. These arguments could be references to columns, arithmetic or other kinds of expressions, the results of `CAST` functions to ensure correct data types, and so on.

Note:

In Impala 2.9 and higher, you can refresh the user-defined functions (UDFs) that Impala recognizes, at the database level, by running the `REFRESH FUNCTIONS` statement with the database name as an argument. Java-based UDFs can be added to the metastore database through Hive `CREATE FUNCTION` statements, and made visible to Impala by subsequently running `REFRESH FUNCTIONS`. For example:

```
CREATE DATABASE shared_udfs;
USE shared_udfs;
...use CREATE FUNCTION statements in Hive to create some Java-based UDFs
   that Impala is not initially aware of...
REFRESH FUNCTIONS shared_udfs;
SELECT udf_created_by_hive(c1) FROM ...
```

Java UDF Example: Reusing lower() Function

For example, the following `impala-shell` session creates an Impala UDF `my_lower()` that reuses the Java code for the Hive `lower()`: built-in function. We cannot call it `lower()` because Impala does not allow UDFs to have the same name as built-in functions. From SQL, we call the

function in a basic way (in a query with no WHERE clause), directly on a column, and on the results of a string expression:

```
[localhost:21000] > create database udfs;
[localhost:21000] > use udfs;
[localhost:21000] > create function lower(string)
  returns string location '/user/hive/udfs/hive.jar'
  symbol='org.apache.hadoop.hive.ql.udf.UDFLower';
ERROR: AnalysisException: Function cannot have the same name as
a builtin: lower
[localhost:21000] > create function my_lower(string)
  returns string location '/user/hive/udfs/hive.jar'
  symbol='org.apache.hadoop.hive.ql.udf.UDFLower';
[localhost:21000] > select my_lower('Some String NOT ALREADY
LOWERCASE');
```

udfs.my_lower('some string not already lowercase')
some string not already lowercase

```
Returned 1 row(s) in 0.11s
[localhost:21000] > create table t2 (s string);
[localhost:21000] > insert into t2 values ('lower'),('UPPER'),
('Init cap'),('CamelCase');
Inserted 4 rows in 2.28s
[localhost:21000] > select * from t2;
```

s
lower
UPPER
Init cap
CamelCase

```
Returned 4 row(s) in 0.47s
[localhost:21000] > select my_lower(s) from t2;
```

udfs.my_lower(s)
lower
upper
init cap
camelcase

```
Returned 4 row(s) in 0.54s
[localhost:21000] > select my_lower(concat('ABC ',s,' XYZ'))
from t2;
```

udfs.my_lower(concat('abc ', s, ' xyz'))
abc lower xyz
abc upper xyz
abc init cap xyz
abc camelcase xyz

```
Returned 4 row(s) in 0.22s
```

Java UDF Example: Reusing negative() Function

Here is an example that reuses the Hive Java code for the `negative()` built-in function. This example demonstrates how the data types of the arguments must match precisely with the function

signature. At first, we create an Impala SQL function that can only accept an integer argument. Impala cannot find a matching function when the query passes a floating-point argument, although we can call the integer version of the function by casting the argument. Then we overload the same function name to also accept a floating-point argument.

```
[localhost:21000] > create table t (x int);
[localhost:21000] > insert into t values (1), (2), (4), (100);
Inserted 4 rows in 1.43s
[localhost:21000] > create function my_neg(bigint)
  returns bigint location '/user/hive/udfs/hive.jar'
  symbol='org.apache.hadoop.hive.ql.udf.UDFOPNegative';
[localhost:21000] > select my_neg(4);
+-----+
| udfs.my_neg(4) |
+-----+
| -4             |
+-----+
[localhost:21000] > select my_neg(x) from t;
+-----+
| udfs.my_neg(x) |
+-----+
| -2             |
| -4             |
| -100           |
+-----+
Returned 3 row(s) in 0.60s
[localhost:21000] > select my_neg(4.0);
ERROR: AnalysisException: No matching function with signature:
  udfs.my_neg(FLOAT).
[localhost:21000] > select my_neg(cast(4.0 as int));
+-----+
| udfs.my_neg(cast(4.0 as int)) |
+-----+
| -4                             |
+-----+
Returned 1 row(s) in 0.11s
[localhost:21000] > create function my_neg(double)
  returns double location '/user/hive/udfs/hive.jar'
  symbol='org.apache.hadoop.hive.ql.udf.UDFOPNegative';
[localhost:21000] > select my_neg(4.0);
+-----+
| udfs.my_neg(4.0) |
+-----+
| -4               |
+-----+
Returned 1 row(s) in 0.11s
```

Runtime Environment for UDFs

By default, Impala copies UDFs into /tmp, and you can configure this location through the `--local_library_dir` startup flag for the `impalad` daemon.

Installing the UDF Development Package

To develop UDFs for Impala, download and install the `impala-udf-devel` package (RHEL-based distributions) or `impala-udf-dev` (Ubuntu and Debian). This package contains header files, sample source, and build configuration files.

1. Locate the appropriate `.repo` or `list` file for your operating system version.

2. Use the familiar `yum`, `zypper`, or `apt-get` commands depending on your operating system. For the package name, specify `impala-udf-devel` (RHEL-based distributions) or `impala-udf-dev` (Ubuntu and Debian).

Note: The UDF development code does not rely on Impala being installed on the same machine. You can write and compile UDFs on a minimal development system, then deploy them on a different one for use with Impala.

When you are ready to start writing your own UDFs, download the sample code and build scripts from the Impala sample UDF github. Then see [Writing User-Defined Functions \(UDFs\)](#) on page 593 for how to code UDFs, and [Examples of Creating and Using UDFs](#) on page 598 for how to build and run UDFs.

Writing User-Defined Functions (UDFs)

Before starting UDF development, make sure to install the development package and download the UDF code samples, as described in [Installing the UDF Development Package](#) on page 592.

When writing UDFs:

- Keep in mind the data type differences as you transfer values from the high-level SQL to your lower-level UDF code. For example, in the UDF code you might be much more aware of how many bytes different kinds of integers require.
- Use best practices for function-oriented programming: choose arguments carefully, avoid side effects, make each function do a single thing, and so on.

Getting Started with UDF Coding

To understand the layout and member variables and functions of the predefined UDF data types, examine the header file `/usr/include/impala_udf/udf.h`:

```
// This is the only Impala header required to develop UDFs and UDAs. This
// header
// contains the types that need to be used and the FunctionContext object.
// The context
// object serves as the interface object between the UDF/UDA and the impala
// process.
```

For the basic declarations needed to write a scalar UDF, see the header file `udf-sample.h` within the sample build environment, which defines a simple function named `AddUdf()`:

```
#ifndef IMPALA_UDF_SAMPLE_UDF_H
#define IMPALA_UDF_SAMPLE_UDF_H

#include <impala_udf/udf.h>

using namespace impala_udf;

IntVal AddUdf(FunctionContext* context, const IntVal& arg1, const IntVal&
arg2);

#endif
```

For sample C++ code for a simple function named `AddUdf()`, see the source file `udf-sample.cc` within the sample build environment:

```
#include "udf-sample.h"

// In this sample we are declaring a UDF that adds two ints and returns an
// int.
IntVal AddUdf(FunctionContext* context, const IntVal& arg1, const IntVal&
arg2) {
    if (arg1.is_null || arg2.is_null) return IntVal::null();
    return IntVal(arg1.val + arg2.val);
}
```

```
}
// Multiple UDFs can be defined in the same file
```

Data Types for Function Arguments and Return Values

Each value that a user-defined function can accept as an argument or return as a result value must map to a SQL data type that you could specify for a table column.

Currently, Impala UDFs cannot accept arguments or return values of the Impala complex types (STRUCT, ARRAY, or MAP).

Each data type has a corresponding structure defined in the C++ and Java header files, with two member fields and some predefined comparison operators and constructors:

- `is_null` indicates whether the value is NULL or not. `val` holds the actual argument or return value when it is non-NULL.
- Each struct also defines a `null()` member function that constructs an instance of the struct with the `is_null` flag set.
- The built-in SQL comparison operators and clauses such as `<`, `>=`, `BETWEEN`, and `ORDER BY` all work automatically based on the SQL return type of each UDF. For example, Impala knows how to evaluate `BETWEEN 1 AND udf_returning_int(col1)` or `ORDER BY udf_returning_string(col2)` without you declaring any comparison operators within the UDF itself.

For convenience within your UDF code, each struct defines `==` and `!=` operators for comparisons with other structs of the same type. These are for typical C++ comparisons within your own code, not necessarily reproducing SQL semantics. For example, if the `is_null` flag is set in both structs, they compare as equal. That behavior of `null` comparisons is different from SQL (where `NULL == NULL` is `NULL` rather than `true`), but more in line with typical C++ behavior.

- Each kind of struct has one or more constructors that define a filled-in instance of the struct, optionally with default values.
- Impala cannot process UDFs that accept composite or nested types as arguments or return them as result values. This limitation applies both to Impala UDFs written in C++ and Java-based Hive UDFs.
- You can overload functions by creating multiple functions with the same SQL name but different argument types. For overloaded functions, you must use different C++ or Java entry point names in the underlying functions.

The data types defined on the C++ side (in `/usr/include/impala_udf/udf.h`) are:

- `IntVal` represents an `INT` column.
- `BigIntVal` represents a `BIGINT` column. Even if you do not need the full range of a `BIGINT` value, it can be useful to code your function arguments as `BigIntVal` to make it convenient to call the function with different kinds of integer columns and expressions as arguments. Impala automatically casts smaller integer types to larger ones when appropriate, but does not implicitly cast large integer types to smaller ones.
- `SmallIntVal` represents a `SMALLINT` column.
- `TinyIntVal` represents a `TINYINT` column.
- `StringVal` represents a `STRING` column. It has a `len` field representing the length of the string, and a `ptr` field pointing to the string data. It has constructors that create a new `StringVal` struct based on a null-terminated C-style string, or a pointer plus a length; these new structs still refer to the original string data rather than allocating a new buffer for the data. It also has a constructor that takes a pointer to a `FunctionContext` struct and a length, that does allocate space for a new copy of the string data, for use in UDFs that return string values.
- `BooleanVal` represents a `BOOLEAN` column.
- `FloatVal` represents a `FLOAT` column.
- `DoubleVal` represents a `DOUBLE` column.
- `TimestampVal` represents a `TIMESTAMP` column. It has a `date` field, a 32-bit integer representing the Gregorian date, that is, the days past the epoch date. It also has a `time_of_day` field, a 64-bit integer representing the current time of day in nanoseconds.

Variable-Length Argument Lists

UDFs typically take a fixed number of arguments, with each one named explicitly in the signature of your C++ function. Your function can also accept additional optional arguments, all of the same type. For example, you can concatenate two strings, three strings, four strings, and so on. Or you can compare two numbers, three numbers, four numbers, and so on.

To accept a variable-length argument list, code the signature of your function like this:

```
StringVal Concat(FunctionContext* context, const StringVal& separator,
    int num_var_args, const StringVal* args);
```

In the `CREATE FUNCTION` statement, after the type of the first optional argument, include `...` to indicate it could be followed by more arguments of the same type. For example, the following function accepts a `STRING` argument, followed by one or more additional `STRING` arguments:

```
[localhost:21000] > create function my_concat(string, string ...) returns
    string location '/user/test_user/udfs/sample.so' symbol='Concat';
```

The call from the SQL query must pass at least one argument to the variable-length portion of the argument list.

When Impala calls the function, it fills in the initial set of required arguments, then passes the number of extra arguments and a pointer to the first of those optional arguments.

Handling NULL Values

For correctness, performance, and reliability, it is important for each UDF to handle all situations where any `NULL` values are passed to your function. For example, when passed a `NULL`, UDFs typically also return `NULL`. In an aggregate function, which could be passed a combination of real and `NULL` values, you might make the final value into a `NULL` (as in `CONCAT()`), ignore the `NULL` value (as in `AVG()`), or treat it the same as a numeric zero or empty string.

Each parameter type, such as `IntVal` or `StringVal`, has an `is_null` Boolean member. Test this flag immediately for each argument to your function, and if it is set, do not refer to the `val` field of the argument structure. The `val` field is undefined when the argument is `NULL`, so your function could go into an infinite loop or produce incorrect results if you skip the special handling for `NULL`.

If your function returns `NULL` when passed a `NULL` value, or in other cases such as when a search string is not found, you can construct a null instance of the return type by using its `null()` member function.

Memory Allocation for UDFs

By default, memory allocated within a UDF is deallocated when the function exits, which could be before the query is finished. The input arguments remain allocated for the lifetime of the function, so you can refer to them in the expressions for your return values. If you use temporary variables to construct all-new string values, use the `StringVal()` constructor that takes an initial `FunctionContext*` argument followed by a length, and copy the data into the newly allocated memory buffer.

Thread-Safe Work Area for UDFs

One way to improve performance of UDFs is to specify the optional `PREPARE_FN` and `CLOSE_FN` clauses on the `CREATE FUNCTION` statement. The “prepare” function sets up a thread-safe data structure in memory that you can use as a work area. The “close” function deallocates that memory. Each subsequent call to the UDF within the same thread can access that same memory area. There might be several such memory areas allocated on the same host, as UDFs are parallelized using multiple threads.

Within this work area, you can set up predefined lookup tables, or record the results of complex operations on data types such as `STRING` or `TIMESTAMP`. Saving the results of previous computations rather than repeating the computation each time is an optimization known as <http://en.wikipedia.org/wiki/Memoization>. For example, if your UDF performs a regular expression match or date manipulation on a column that repeats the same value over and over, you could store the last-computed value or a hash table of already-computed values, and do a fast lookup to find the result for subsequent iterations of the UDF.

Each such function must have the signature:

```
void function_name(impala_udf::FunctionContext*,
    impala_udf::FunctionContext::FunctionScope)
```

Currently, only `THREAD_SCOPE` is implemented, not `FRAGMENT_SCOPE`. See `udf.h` for details about the scope values.

Error Handling for UDFs

To handle errors in UDFs, you call functions that are members of the initial `FunctionContext*` argument passed to your function.

A UDF can record one or more warnings, for conditions that indicate minor, recoverable problems that do not cause the query to stop. The signature for this function is:

```
bool AddWarning(const char* warning_msg);
```

For a serious problem that requires cancelling the query, a UDF can set an error flag that prevents the query from returning any results. The signature for this function is:

```
void SetError(const char* error_msg);
```

Writing User-Defined Aggregate Functions (UDAFs)

User-defined aggregate functions (UDAFs or UDAs) are a powerful and flexible category of user-defined functions. If a query processes *N* rows, calling a UDAF during the query condenses the result set, anywhere from a single value (such as with the `SUM` or `MAX` functions), or some number less than or equal to *N* (as in queries using the `GROUP BY` or `HAVING` clause).

The Underlying Functions for a UDA

A UDAF must maintain a state value across subsequent calls, so that it can accumulate a result across a set of calls, rather than derive it purely from one set of arguments. For that reason, a UDAF is represented by multiple underlying functions:

- An initialization function that sets any counters to zero, creates empty buffers, and does any other one-time setup for a query.
- An update function that processes the arguments for each row in the query result set and accumulates an intermediate result for each node. For example, this function might increment a counter, append to a string buffer, or set flags.
- A merge function that combines the intermediate results from two different nodes.
- A serialize function that flattens any intermediate values containing pointers, and frees any memory allocated during the init, update, and merge phases.
- A finalize function that either passes through the combined result unchanged, or does one final transformation.

Intermediate values returned by the init, update and merge functions that referred to allocations must be allocated using `FunctionContext::Allocate()` and freed using `FunctionContext::Free()`. Both serialize and finalize functions are responsible for cleaning up the intermediate value and freeing such allocations. `StringVals` returned to Impala directly by `Serialize()`, `Finalize()` or `GetValue()` functions should be backed by temporary results memory allocated using the `StringVal(FunctionContext*, int)` constructor, `StringVal::CopyFrom(FunctionContext*, const uint8_t*, size_t)`, or `StringVal::Resize()`.

In the SQL syntax, you create a UDAF by using the statement `CREATE AGGREGATE FUNCTION`. You specify the entry points of the underlying C++ functions using the clauses `INIT_FN`, `UPDATE_FN`, `MERGE_FN`, `SERIALIZE_FN`, and `FINALIZE_FN`.

For convenience, you can use a naming convention for the underlying functions and Impala automatically recognizes those entry points. Specify the `UPDATE_FN` clause, using an entry point name containing the string `update` or `Update`. When you omit the other `_FN` clauses from the SQL statement, Impala looks for entry points with names formed by substituting the `update` or `Update` portion of the specified name.

`uda-sample.h`:

`uda-sample.cc`:

Intermediate Results for UDAs

A user-defined aggregate function might produce and combine intermediate results during some phases of processing, using a different data type than the final return value. For example, if you implement a function similar to the built-in `AVG()` function, it must keep track of two values, the number of values counted and the sum of those values. Or, you might accumulate a string value over the course of a UDA, then in the end return a numeric or Boolean result.

In such a case, specify the data type of the intermediate results using the optional `INTERMEDIATE type_name` clause of the `CREATE AGGREGATE FUNCTION` statement. If the intermediate data is a typeless byte array (for example, to represent a C++ struct or array), specify the type name as `CHAR(n)`, with *n* representing the number of bytes in the intermediate result buffer.

For an example of this technique, see the `trunc_sum()` aggregate function, which accumulates intermediate results of type `DOUBLE` and returns `BIGINT` at the end. View [the `CREATE FUNCTION` statement](#) and [the implementation of the underlying `TruncSum*\(\)` functions](#) on Github.

Building and Deploying UDFs

This section explains the steps to compile Impala UDFs from C++ source code, and deploy the resulting libraries for use in Impala queries.

Impala ships with a sample build environment for UDFs, that you can study, experiment with, and adapt for your own use. This sample build environment starts with the `cmake` configuration command, which reads the file `CMakeLists.txt` and generates a `Makefile` customized for your particular directory paths. Then the `make` command runs the actual build steps based on the rules in the `Makefile`.

Impala loads the shared library from an HDFS location. After building a shared library containing one or more UDFs, use `hdfs dfs` or `hadoop fs` commands to copy the binary file to an HDFS location readable by Impala.

The final step in deployment is to issue a `CREATE FUNCTION` statement in the `impala-shell` interpreter to make Impala aware of the new function. See [CREATE FUNCTION Statement](#) on page 242 for syntax details. Because each function is associated with a particular database, always issue a `USE` statement to the appropriate database before creating a function, or specify a fully qualified name, that is, `CREATE FUNCTION db_name.function_name`.

As you update the UDF code and redeploy updated versions of a shared library, use `DROP FUNCTION` and `CREATE FUNCTION` to let Impala pick up the latest version of the code.

Note:

In Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to Impala 2.5 the requirement to reload functions after a restart applied to both C++ and Java functions.

See [CREATE FUNCTION Statement](#) on page 242 and [DROP FUNCTION Statement](#) on page 282 for the new syntax for the persistent Java UDFs.

Prerequisites for the build environment are:

```
# Use the appropriate package installation command for your Linux
distribution.
sudo yum install gcc-c++ cmake boost-devel
sudo yum install impala-udf-devel
# The package name on Ubuntu and Debian is impala-udf-dev.
```

Then, unpack the sample code in `udf_samples.tar.gz` and use that as a template to set up your build environment.

To build the original samples:

```
# Process CMakeLists.txt and set up appropriate Makefiles.
cmake .
# Generate shared libraries from UDF and UDAF sample code,
# udf_samples/libudfsample.so and udf_samples/libudasample.so
make
```

The sample code to examine, experiment with, and adapt is in these files:

- `udf-sample.h`: Header file that declares the signature for a scalar UDF (`AddUDF`).
- `udf-sample.cc`: Sample source for a simple UDF that adds two integers. Because Impala can reference multiple function entry points from the same shared library, you could add other UDF functions in this file and add their signatures to the corresponding header file.
- `udf-sample-test.cc`: Basic unit tests for the sample UDF.
- `uda-sample.h`: Header file that declares the signature for sample aggregate functions. The SQL functions will be called `COUNT`, `AVG`, and `STRINGCONCAT`. Because aggregate functions require more elaborate coding to handle the processing for multiple phases, there are several underlying C++ functions such as `CountInit`, `AvgUpdate`, and `StringConcatFinalize`.
- `uda-sample.cc`: Sample source for simple UDAFs that demonstrate how to manage the state transitions as the underlying functions are called during the different phases of query processing.
 - The UDAF that imitates the `COUNT` function keeps track of a single incrementing number; the merge functions combine the intermediate count values from each Impala node, and the combined number is returned verbatim by the finalize function.
 - The UDAF that imitates the `AVG` function keeps track of two numbers, a count of rows processed and the sum of values for a column. These numbers are updated and merged as with `COUNT`, then the finalize function divides them to produce and return the final average value.
 - The UDAF that concatenates string values into a comma-separated list demonstrates how to manage storage for a string that increases in length as the function is called for multiple rows.
- `uda-sample-test.cc`: basic unit tests for the sample UDAFs.

Performance Considerations for UDFs

Because a UDF typically processes each row of a table, potentially being called billions of times, the performance of each UDF is a critical factor in the speed of the overall ETL or ELT pipeline. Tiny optimizations you can make within the function body can pay off in a big way when the function is called over and over when processing a huge result set.

Examples of Creating and Using UDFs

This section demonstrates how to create and use all kinds of user-defined functions (UDFs).

Sample C++ UDFs: HasVowels, CountVowels, StripVowels

This example shows 3 separate UDFs that operate on strings and return different data types. In the C++ code, the functions are `HasVowels()` (checks if a string contains any vowels),

`CountVowels()` (returns the number of vowels in a string), and `StripVowels()` (returns a new string with vowels removed).

First, we add the signatures for these functions to `udf-sample.h` in the demo build environment:

```
BooleanVal HasVowels(FunctionContext* context, const StringVal&
    input);
IntVal CountVowels(FunctionContext* context, const StringVal&
    arg1);
StringVal StripVowels(FunctionContext* context, const StringVal&
    arg1);
```

Then, we add the bodies of these functions to `udf-sample.cc`:

```
BooleanVal HasVowels(FunctionContext* context, const StringVal&
    input)
{
    if (input.is_null) return BooleanVal::null();

    int index;
    uint8_t *ptr;

    for (ptr = input.ptr, index = 0; index <= input.len;
        index++, ptr++)
    {
        uint8_t c = tolower(*ptr);
        if (c == 'a' || c == 'e' || c == 'i' || c == 'o'
            || c == 'u')
        {
            return BooleanVal(true);
        }
    }
    return BooleanVal(false);
}

IntVal CountVowels(FunctionContext* context, const StringVal&
    arg1)
{
    if (arg1.is_null) return IntVal::null();

    int count;
    int index;
    uint8_t *ptr;

    for (ptr = arg1.ptr, count = 0, index = 0; index <=
        arg1.len; index++, ptr++)
    {
        uint8_t c = tolower(*ptr);
        if (c == 'a' || c == 'e' || c == 'i' || c == 'o'
            || c == 'u')
        {
            count++;
        }
    }
    return IntVal(count);
}

StringVal StripVowels(FunctionContext* context, const StringVal&
    arg1)
{
    if (arg1.is_null) return StringVal::null();

    int index;
```

```

std::string original((const char *)arg1.ptr,arg1.len);
std::string shorter("");

for (index = 0; index < original.length(); index++)
{
    uint8_t c = original[index];
    uint8_t l = tolower(c);

    if (l == 'a' || l == 'e' || l == 'i' || l == 'o'
|| l == 'u')
    {
        ;
    }
    else
    {
        shorter.append(1, (char)c);
    }
}
// The modified string is stored in 'shorter', which is
// destroyed when this function ends. We need to make a string val
// and copy the contents.
StringVal result(context, shorter.size()); // Only the
version of the ctor that takes a context object allocates new
memory
memcpy(result.ptr, shorter.c_str(), shorter.size());
return result;
}

```

We build a shared library, `libudfsample.so`, and put the library file into HDFS where Impala can read it:

```

$ make
[ 0%] Generating udf_samples/uda-sample.ll
[ 16%] Built target uda-sample-ir
[ 33%] Built target udasample
[ 50%] Built target uda-sample-test
[ 50%] Generating udf_samples/udf-sample.ll
[ 66%] Built target udf-sample-ir
Scanning dependencies of target udfs-sample
[ 83%] Building CXX object CMakeFiles/udfsample.dir/udf-sample.o
Linking CXX shared library udf_samples/libudfsample.so
[ 83%] Built target udfs-sample
Linking CXX executable udf_samples/udf-sample-test
[100%] Built target udf-sample-test
$ hdfs dfs -put ./udf_samples/libudfsample.so /user/hive/udfs/
libudfsample.so

```

Finally, we go into the `impala-shell` interpreter where we set up some sample data, issue `CREATE FUNCTION` statements to set up the SQL function names, and call the functions in some queries:

```

[localhost:21000] > create database udf_testing;
[localhost:21000] > use udf_testing;

[localhost:21000] > create function has_vowels (string)
returns boolean location '/user/hive/udfs/libudfsample.so'
symbol='HasVowels';
[localhost:21000] > select has_vowels('abc');
+-----+
| udfs.has_vowels('abc') |
+-----+
| true                   |

```



```

+-----+
Returned 1 row(s) in 0.13s
[localhost:21000] > select has_vowels('zxcvbnm');
+-----+
| udfs.has_vowels('zxcvbnm') |
+-----+
| false                       |
+-----+

Returned 1 row(s) in 0.12s
[localhost:21000] > select has_vowels(null);
+-----+
| udfs.has_vowels(null) |
+-----+
| NULL                  |
+-----+

Returned 1 row(s) in 0.11s
[localhost:21000] > select s, has_vowels(s) from t2;
+-----+-----+
| s          | udfs.has_vowels(s) |
+-----+-----+
| lower      | true               |
| UPPER      | true               |
| Init cap   | true               |
| CamelCase  | true               |
+-----+-----+

Returned 4 row(s) in 0.24s

[localhost:21000] > create function count_vowels (string)
  returns int location '/user/hive/udfs/libudfsample.so'
  symbol='CountVowels';
[localhost:21000] > select count_vowels('cat in the hat');
+-----+
| udfs.count_vowels('cat in the hat') |
+-----+
| 4                                     |
+-----+

Returned 1 row(s) in 0.12s
[localhost:21000] > select s, count_vowels(s) from t2;
+-----+-----+
| s          | udfs.count_vowels(s) |
+-----+-----+
| lower      | 2                     |
| UPPER      | 2                     |
| Init cap   | 3                     |
| CamelCase  | 4                     |
+-----+-----+

Returned 4 row(s) in 0.23s
[localhost:21000] > select count_vowels(null);
+-----+
| udfs.count_vowels(null) |
+-----+
| NULL                    |
+-----+

Returned 1 row(s) in 0.12s

[localhost:21000] > create function strip_vowels (string)
  returns string location '/user/hive/udfs/libudfsample.so'
  symbol='StripVowels';
[localhost:21000] > select strip_vowels('abcdefg');
+-----+
| udfs.strip_vowels('abcdefg') |
+-----+
| bcdfg                        |
+-----+

```

```

Returned 1 row(s) in 0.11s
[localhost:21000] > select strip_vowels('ABCDEFGF');
+-----+
| udfs.strip_vowels('abcdefg') |
+-----+
| BCDFG                          |
+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select strip_vowels(null);
+-----+
| udfs.strip_vowels(null) |
+-----+
| NULL                     |
+-----+
Returned 1 row(s) in 0.16s
[localhost:21000] > select s, strip_vowels(s) from t2;
+-----+-----+
| s          | udfs.strip_vowels(s) |
+-----+-----+
| lower      | lwr                  |
| UPPER      | PPR                  |
| Init cap   | nt cp                |
| CamelCase  | CmlCs                |
+-----+-----+
Returned 4 row(s) in 0.24s

```

Sample C++ UDA: SumOfSquares

This example demonstrates a user-defined aggregate function (UDA) that produces the sum of the squares of its input values.

The coding for a UDA is a little more involved than a scalar UDF, because the processing is split into several phases, each implemented by a different function. Each phase is relatively straightforward: the “update” and “merge” phases, where most of the work is done, read an input value and combine it with some accumulated intermediate value.

As in our sample UDF from the previous example, we add function signatures to a header file (in this case, `uda-sample.h`). Because this is a math-oriented UDA, we make two versions of each function, one accepting an integer value and the other accepting a floating-point value.

```

void SumOfSquaresInit(FunctionContext* context, BigIntVal* val);
void SumOfSquaresInit(FunctionContext* context, DoubleVal* val);

void SumOfSquaresUpdate(FunctionContext* context, const
    BigIntVal& input, BigIntVal* val);
void SumOfSquaresUpdate(FunctionContext* context, const
    DoubleVal& input, DoubleVal* val);

void SumOfSquaresMerge(FunctionContext* context, const
    BigIntVal& src, BigIntVal* dst);
void SumOfSquaresMerge(FunctionContext* context, const
    DoubleVal& src, DoubleVal* dst);

BigIntVal SumOfSquaresFinalize(FunctionContext* context, const
    BigIntVal& val);
DoubleVal SumOfSquaresFinalize(FunctionContext* context, const
    DoubleVal& val);

```

We add the function bodies to a C++ source file (in this case, `uda-sample.cc`):

```
void SumOfSquaresInit(FunctionContext* context, BigIntVal* val)
{
    val->is_null = false;
    val->val = 0;
}
void SumOfSquaresInit(FunctionContext* context, DoubleVal* val)
{
    val->is_null = false;
    val->val = 0.0;
}

void SumOfSquaresUpdate(FunctionContext* context, const
    BigIntVal& input, BigIntVal* val) {
    if (input.is_null) return;
    val->val += input.val * input.val;
}
void SumOfSquaresUpdate(FunctionContext* context, const
    DoubleVal& input, DoubleVal* val) {
    if (input.is_null) return;
    val->val += input.val * input.val;
}

void SumOfSquaresMerge(FunctionContext* context, const
    BigIntVal& src, BigIntVal* dst) {
    dst->val += src.val;
}
void SumOfSquaresMerge(FunctionContext* context, const
    DoubleVal& src, DoubleVal* dst) {
    dst->val += src.val;
}

BigIntVal SumOfSquaresFinalize(FunctionContext* context, const
    BigIntVal& val) {
    return val;
}
DoubleVal SumOfSquaresFinalize(FunctionContext* context, const
    DoubleVal& val) {
    return val;
}
```

As with the sample UDF, we build a shared library and put it into HDFS:

```
$ make
[ 0%] Generating udf_samples/uda-sample.ll
[ 16%] Built target uda-sample-ir
Scanning dependencies of target udasample
[ 33%] Building CXX object CMakeFiles/udasample.dir/uda-sample.o
Linking CXX shared library udf_samples/libudasample.so
[ 33%] Built target udasample
Scanning dependencies of target uda-sample-test
[ 50%] Building CXX object CMakeFiles/uda-sample-test.dir/uda-
sample-test.o
Linking CXX executable udf_samples/uda-sample-test
[ 50%] Built target uda-sample-test
[ 50%] Generating udf_samples/udf-sample.ll
[ 66%] Built target udf-sample-ir
[ 83%] Built target udfsample
[100%] Built target udf-sample-test
$ hdfs dfs -put ./udf_samples/libudasample.so /user/hive/udfs/
libudasample.so
```

To create the SQL function, we issue a `CREATE AGGREGATE FUNCTION` statement and specify the underlying C++ function names for the different phases:

```
[localhost:21000] > use udf_testing;

[localhost:21000] > create table sos (x bigint, y double);
[localhost:21000] > insert into sos values (1, 1.1), (2, 2.2),
(3, 3.3), (4, 4.4);
Inserted 4 rows in 1.10s

[localhost:21000] > create aggregate function
sum_of_squares(bigint) returns bigint
> location '/user/hive/udfs/libudasample.so'
> init_fn='SumOfSquaresInit'
> update_fn='SumOfSquaresUpdate'
> merge_fn='SumOfSquaresMerge'
> finalize_fn='SumOfSquaresFinalize';

[localhost:21000] > -- Compute the same value using literals or
the UDA;
[localhost:21000] > select 1*1 + 2*2 + 3*3 + 4*4;
+-----+
| 1 * 1 + 2 * 2 + 3 * 3 + 4 * 4 |
+-----+
| 30                             |
+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select sum_of_squares(x) from sos;
+-----+
| udfs.sum_of_squares(x) |
+-----+
| 30                     |
+-----+
Returned 1 row(s) in 0.35s
```

Until we create the overloaded version of the UDA, it can only handle a single data type. To allow it to handle `DOUBLE` as well as `BIGINT`, we issue another `CREATE AGGREGATE FUNCTION` statement:

```
[localhost:21000] > select sum_of_squares(y) from sos;
ERROR: AnalysisException: No matching function with signature:
udfs.sum_of_squares(DOUBLE).

[localhost:21000] > create aggregate function
sum_of_squares(double) returns double
> location '/user/hive/udfs/libudasample.so'
> init_fn='SumOfSquaresInit'
> update_fn='SumOfSquaresUpdate'
> merge_fn='SumOfSquaresMerge'
> finalize_fn='SumOfSquaresFinalize';

[localhost:21000] > -- Compute the same value using literals or
the UDA;
[localhost:21000] > select 1.1*1.1 + 2.2*2.2 + 3.3*3.3 +
4.4*4.4;
+-----+
| 1.1 * 1.1 + 2.2 * 2.2 + 3.3 * 3.3 + 4.4 * 4.4 |
+-----+
| 36.3                                           |
+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select sum_of_squares(y) from sos;
```

```
+-----+
| udfs.sum_of_squares(y) |
+-----+
| 36.3                    |
+-----+
Returned 1 row(s) in 0.35s
```

Typically, you use a UDA in queries with `GROUP BY` clauses, to produce a result set with a separate aggregate value for each combination of values from the `GROUP BY` clause. Let's change our sample table to use 0 to indicate rows containing even values, and 1 to flag rows containing odd values. Then the `GROUP BY` query can return two values, the sum of the squares for the even values, and the sum of the squares for the odd values:

```
[localhost:21000] > insert overwrite sos values (1, 1), (2, 0),
(3, 1), (4, 0);
Inserted 4 rows in 1.24s

[localhost:21000] > -- Compute 1 squared + 3 squared, and 2
squared + 4 squared;
[localhost:21000] > select y, sum_of_squares(x) from sos group
by y;
+-----+-----+
| y | udfs.sum_of_squares(x) |
+-----+-----+
| 1 | 10                     |
| 0 | 20                     |
+-----+-----+
Returned 2 row(s) in 0.43s
```

Security Considerations for User-Defined Functions

When the Impala authorization feature is enabled:

- To call a UDF in a query, you must have the required read privilege for any databases and tables used in the query.
- The `CREATE FUNCTION` statement requires:
 - The `CREATE` privilege on the database.
 - The `ALL` privilege on URI where URI is the value you specified for the `LOCATION` in the `CREATE FUNCTION` statement.

See [Impala Authorization](#) on page 83 for details about authorization in Impala.

Limitations and Restrictions for Impala UDFs

The following limitations and restrictions apply to Impala UDFs in the current release:

- Impala does not support Hive UDFs that accept or return composite or nested types, or other types not available in Impala tables.
- The Hive `current_user()` function cannot be called from a Java UDF through Impala.
- All Impala UDFs must be deterministic, that is, produce the same output each time when passed the same argument values. For example, an Impala UDF must not call functions such as `rand()` to produce different values for each invocation. It must not retrieve data from external sources, such as from disk or over the network.
- An Impala UDF must not spawn other threads or processes.
- Prior to Impala 2.5 when the `catalogd` process is restarted, all UDFs become undefined and must be reloaded. In Impala 2.5 and higher, this limitation only applies to older Java UDFs. Re-create those UDFs using the new `CREATE FUNCTION` syntax for Java UDFs, which excludes the function signature, to remove the limitation entirely.
- Impala currently does not support user-defined table functions (UDTFs).

- The CHAR and VARCHAR types cannot be used as input arguments or return values for UDFs.

SQL Differences Between Impala and Hive

Impala's SQL syntax follows the SQL-92 standard, and includes many industry extensions in areas such as built-in functions. See [Porting SQL from Other Database Systems to Impala](#) on page 608 for a general discussion of adapting SQL code from a variety of database systems to Impala.

Because Impala and Hive share the same metastore database and their tables are often used interchangeably, the following section covers differences between Impala and Hive in detail.

HiveQL Features not Available in Impala

The current release of Impala does not support the following SQL features that you might be familiar with from HiveQL:

- Extensibility mechanisms such as TRANSFORM, custom file formats, or custom SerDes.
- The DATE data type.
- XML functions.
- Certain aggregate functions from HiveQL: covar_pop, covar_samp, corr, percentile, percentile_approx, histogram_numeric, collect_set; Impala supports the set of aggregate functions listed in [Impala Aggregate Functions](#) on page 539 and analytic functions listed in [Impala Analytic Functions](#) on page 569.
- Sampling.
- Lateral views. In Impala 2.3 and higher, Impala supports queries on complex types (STRUCT, ARRAY, or MAP), using join notation rather than the EXPLODE () keyword. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details about Impala support for complex types.

User-defined functions (UDFs) are supported starting in Impala 1.2. See [User-Defined Functions \(UDFs\)](#) on page 588 for full details on Impala UDFs.

- Impala supports high-performance UDFs written in C++, as well as reusing some Java-based Hive UDFs.
- Impala supports scalar UDFs and user-defined aggregate functions (UDAFs). Impala does not currently support user-defined table generating functions (UDTFs).
- Only Impala-supported column types are supported in Java-based UDFs.
- The Hive `current_user()` function cannot be called from a Java UDF through Impala.

Impala does not currently support these HiveQL statements:

- ANALYZE TABLE (the Impala equivalent is COMPUTE STATS)
- DESCRIBE COLUMN
- DESCRIBE DATABASE
- EXPORT TABLE
- IMPORT TABLE
- SHOW TABLE EXTENDED
- SHOW TBLPROPERTIES
- SHOW INDEXES
- SHOW COLUMNS
- INSERT OVERWRITE DIRECTORY; use INSERT OVERWRITE *table_name* or CREATE TABLE AS SELECT to materialize query results into the HDFS directory associated with an Impala table.

Impala respects the `serialization.null.format` table property only for TEXT tables and ignores the property for Parquet and other formats. Hive respects the `serialization.null.format` property for Parquet and other formats and converts matching values to NULL during the scan. See [Using Text Data Files with Impala Tables](#) on page 697 for using the table property in Impala.

Semantic Differences Between Impala and HiveQL Features

This section covers instances where Impala and Hive have similar functionality, sometimes including the same syntax, but there are differences in the runtime semantics of those features.

Security:

Impala utilizes the [Apache Ranger](#) authorization framework, which provides fine-grained role-based access control to protect data against unauthorized access or tampering.

The Hive component now includes Ranger-enabled GRANT, REVOKE, and CREATE/DROP ROLE statements. Earlier Hive releases had a privilege system with GRANT and REVOKE statements that were primarily intended to prevent accidental deletion of data, rather than a security mechanism to protect against malicious users.

Impala can make use of privileges set up through Hive GRANT and REVOKE statements. Impala has its own GRANT and REVOKE statements in Impala 2.0 and higher. See [Impala Authorization](#) on page 83 for the details of authorization in Impala.

SQL statements and clauses:

The semantics of Impala SQL statements varies from HiveQL in some cases where they use similar SQL statement and clause names:

- Impala uses different syntax and names for query hints, [SHUFFLE] and [NOSHUFFLE] rather than MapJoin or StreamJoin. See [Joins in Impala SELECT Statements](#) on page 318 for the Impala details.
- Impala does not expose MapReduce specific features of SORT BY, DISTRIBUTE BY, or CLUSTER BY.
- Impala does not require queries to include a FROM clause.

Data types:

- Impala supports a limited set of implicit casts. This can help avoid undesired results from unexpected casting behavior.
 - Impala does not implicitly cast between string and numeric or Boolean types. Always use CAST () for these conversions.
 - Impala does perform implicit casts among the numeric types, when going from a smaller or less precise type to a larger or more precise one. For example, Impala will implicitly convert a SMALLINT to a BIGINT or FLOAT, but to convert from DOUBLE to FLOAT or INT to TINYINT requires a call to CAST () in the query.
 - Impala does perform implicit casts from string to timestamp. Impala has a restricted set of literal formats for the TIMESTAMP data type and the from_unixtime () format string; see [TIMESTAMP Data Type](#) on page 133 for details.

See the topics under [Data Types](#) on page 102 for full details on implicit and explicit casting for each data type, and [Impala Type Conversion Functions](#) on page 467 for details about the CAST () function.

- Impala does not store or interpret timestamps using the local timezone, to avoid undesired results from unexpected time zone issues. Timestamps are stored and interpreted relative to UTC. This difference can produce different results for some calls to similarly named date/time functions between Impala and Hive. See [Impala Date and Time Functions](#) on page 478 for details about the Impala functions. See [TIMESTAMP Data Type](#) on page 133 for a discussion of how Impala handles time zones, and configuration options you can use to make Impala match the Hive behavior more closely when dealing with Parquet-encoded TIMESTAMP data or when converting between the local time zone and UTC.
- The Impala TIMESTAMP type can represent dates ranging from 1400-01-01 to 9999-12-31. This is different from the Hive date range, which is 0000-01-01 to 9999-12-31.
- Impala does not return column overflows as NULL, so that customers can distinguish between NULL data and overflow conditions similar to how they do so with traditional database systems. Impala returns the largest or smallest value in the range for the type. For example, valid values for a tinyint range from -128 to 127. In Impala, a tinyint with a value of -200 returns -128 rather than NULL. A tinyint with a value of 200 returns 127.

Miscellaneous features:

- Impala does not provide virtual columns.

- Impala does not expose locking.
- Impala does not expose some configuration properties.

Porting SQL from Other Database Systems to Impala

Although Impala uses standard SQL for queries, you might need to modify SQL source when bringing applications to Impala, due to variations in data types, built-in functions, vendor language extensions, and Hadoop-specific syntax. Even when SQL is working correctly, you might make further minor modifications for best performance.

Porting DDL and DML Statements

When adapting SQL code from a traditional database system to Impala, expect to find a number of differences in the DDL statements that you use to set up the schema. Clauses related to physical layout of files, tablespaces, and indexes have no equivalent in Impala. You might restructure your schema considerably to account for the Impala partitioning scheme and Hadoop file formats.

Expect SQL queries to have a much higher degree of compatibility. With modest rewriting to address vendor extensions and features not yet supported in Impala, you might be able to run identical or almost-identical query text on both systems.

Therefore, consider separating out the DDL into a separate Impala-specific setup script. Focus your reuse and ongoing tuning efforts on the code for SQL queries.

Porting Data Types from Other Database Systems

- Change any VARCHAR, VARCHAR2, and CHAR columns to STRING. Remove any length constraints from the column declarations; for example, change VARCHAR(32) or CHAR(1) to STRING. Impala is very flexible about the length of string values; it does not impose any length constraints or do any special processing (such as blank-padding) for STRING columns. (In Impala 2.0 and higher, there are data types VARCHAR and CHAR, with length constraints for both types and blank-padding for CHAR. However, for performance reasons, it is still preferable to use STRING columns where practical.)
- For national language character types such as NCHAR, NVARCHAR, or NCLOB, be aware that while Impala can store and query UTF-8 character data, currently some string manipulation operations only work correctly with ASCII data. See [STRING Data Type](#) on page 125 for details.
- Change any DATE, DATETIME, or TIME columns to TIMESTAMP. Remove any precision constraints. Remove any timezone clauses, and make sure your application logic or ETL process accounts for the fact that Impala expects all TIMESTAMP values to be in [Coordinated Universal Time \(UTC\)](#). See [TIMESTAMP Data Type](#) on page 133 for information about the TIMESTAMP data type, and [Impala Date and Time Functions](#) on page 478 for conversion functions for different date and time formats.

You might also need to adapt date- and time-related literal values and format strings to use the supported Impala date and time formats. If you have date and time literals with different separators or different numbers of YY, MM, and so on placeholders than Impala expects, consider using calls to `regexp_replace()` to transform those values to the Impala-compatible format. See [TIMESTAMP Data Type](#) on page 133 for information about the allowed formats for date and time literals, and [Impala String Functions](#) on page 509 for string conversion functions such as `regexp_replace()`.

Instead of SYSDATE, call the function `NOW()`.

Instead of adding or subtracting directly from a date value to produce a value *N* days in the past or future, use an INTERVAL expression, for example `NOW() + INTERVAL 30 DAYS`.

- Although Impala supports INTERVAL expressions for datetime arithmetic, as shown in [TIMESTAMP Data Type](#) on page 133, INTERVAL is not available as a column data type in Impala. For any INTERVAL values stored in tables, convert them to numeric values that you can add or subtract using the functions in [Impala Date and Time](#)

[Functions](#) on page 478. For example, if you had a table `DEADLINES` with an `INT` column `TIME_PERIOD`, you could construct dates `N` days in the future like so:

```
SELECT NOW() + INTERVAL time_period DAYS from deadlines;
```

- For `YEAR` columns, change to the smallest Impala integer type that has sufficient range. See [Data Types](#) on page 102 for details about ranges, casting, and so on for the various numeric data types.
- Change any `DECIMAL` and `NUMBER` types. If fixed-point precision is not required, you can use `FLOAT` or `DOUBLE` on the Impala side depending on the range of values. For applications that require precise decimal values, such as financial data, you might need to make more extensive changes to table structure and application logic, such as using separate integer columns for dollars and cents, or encoding numbers as string values and writing UDFs to manipulate them. See [Data Types](#) on page 102 for details about ranges, casting, and so on for the various numeric data types.
- `FLOAT`, `DOUBLE`, and `REAL` types are supported in Impala. Remove any precision and scale specifications. (In Impala, `REAL` is just an alias for `DOUBLE`; columns declared as `REAL` are turned into `DOUBLE` behind the scenes.) See [Data Types](#) on page 102 for details about ranges, casting, and so on for the various numeric data types.
- Most integer types from other systems have equivalents in Impala, perhaps under different names such as `BIGINT` instead of `INT8`. For any that are unavailable, for example `MEDIUMINT`, switch to the smallest Impala integer type that has sufficient range. Remove any precision specifications. See [Data Types](#) on page 102 for details about ranges, casting, and so on for the various numeric data types.
- Remove any `UNSIGNED` constraints. All Impala numeric types are signed. See [Data Types](#) on page 102 for details about ranges, casting, and so on for the various numeric data types.
- For any types holding bitwise values, use an integer type with enough range to hold all the relevant bits within a positive integer. See [Data Types](#) on page 102 for details about ranges, casting, and so on for the various numeric data types.

For example, `TINYINT` has a maximum positive value of 127, not 256, so to manipulate 8-bit bitfields as positive numbers switch to the next largest type `SMALLINT`.

```
[localhost:21000] > select cast(127*2 as tinyint);
+-----+
| cast(127 * 2 as tinyint) |
+-----+
| -2                        |
+-----+
[localhost:21000] > select cast(128 as tinyint);
+-----+
| cast(128 as tinyint) |
+-----+
| -128                 |
+-----+
[localhost:21000] > select cast(127*2 as smallint);
+-----+
| cast(127 * 2 as smallint) |
+-----+
| 254                    |
+-----+
```

Impala does not support notation such as `b'0101'` for bit literals.

- For `BLOB` values, use `STRING` to represent `CLOB` or `TEXT` types (character based large objects) up to 32 KB in size. Binary large objects such as `BLOB`, `RAW BINARY`, and `VARBINARY` do not currently have an equivalent in Impala.
- For Boolean-like types such as `BOOL`, use the Impala `BOOLEAN` type.
- Because Impala currently does not support composite or nested types, any spatial data types in other database systems do not have direct equivalents in Impala. You could represent spatial values in string format and write UDFs to process them. See [User-Defined Functions \(UDFs\)](#) on page 588 for details. Where practical, separate spatial types into separate tables so that Impala can still work with the non-spatial data.

- Take out any `DEFAULT` clauses. Impala can use data files produced from many different sources, such as Pig, Hive, or MapReduce jobs. The fast import mechanisms of `LOAD DATA` and external tables mean that Impala is flexible about the format of data files, and Impala does not necessarily validate or cleanse data before querying it. When copying data through Impala `INSERT` statements, you can use conditional functions such as `CASE` or `NVL` to substitute some other value for `NULL` fields; see [Impala Conditional Functions](#) on page 502 for details.
- Take out any constraints from your `CREATE TABLE` and `ALTER TABLE` statements, for example `PRIMARY KEY`, `FOREIGN KEY`, `UNIQUE`, `NOT NULL`, `UNSIGNED`, or `CHECK` constraints. Impala can use data files produced from many different sources, such as Pig, Hive, or MapReduce jobs. Therefore, Impala expects initial data validation to happen earlier during the ETL or ELT cycle. After data is loaded into Impala tables, you can perform queries to test for `NULL` values. When copying data through Impala `INSERT` statements, you can use conditional functions such as `CASE` or `NVL` to substitute some other value for `NULL` fields; see [Impala Conditional Functions](#) on page 502 for details.

Do as much verification as practical before loading data into Impala. After data is loaded into Impala, you can do further verification using SQL queries to check if values have expected ranges, if values are `NULL` or not, and so on. If there is a problem with the data, you will need to re-run earlier stages of the ETL process, or do an `INSERT ... SELECT` statement in Impala to copy the faulty data to a new table and transform or filter out the bad values.

- Take out any `CREATE INDEX`, `DROP INDEX`, and `ALTER INDEX` statements, and equivalent `ALTER TABLE` statements. Remove any `INDEX`, `KEY`, or `PRIMARY KEY` clauses from `CREATE TABLE` and `ALTER TABLE` statements. Impala is optimized for bulk read operations for data warehouse-style queries, and therefore does not support indexes for its tables.
- Calls to built-in functions with out-of-range or otherwise incorrect arguments, return `NULL` in Impala as opposed to raising exceptions. (This rule applies even when the `ABORT_ON_ERROR=true` query option is in effect.) Run small-scale queries using representative data to doublecheck that calls to built-in functions are returning expected values rather than `NULL`. For example, unsupported `CAST` operations do not raise an error in Impala:

```
select cast('foo' as int);
+-----+
| cast('foo' as int) |
+-----+
| NULL               |
+-----+
```

- For any other type not supported in Impala, you could represent their values in string format and write UDFs to process them. See [User-Defined Functions \(UDFs\)](#) on page 588 for details.
- To detect the presence of unsupported or unconvertible data types in data files, do initial testing with the `ABORT_ON_ERROR=true` query option in effect. This option causes queries to fail immediately if they encounter disallowed type conversions. See [ABORT_ON_ERROR Query Option](#) on page 346 for details. For example:

```
set abort_on_error=true;
select count(*) from (select * from t1);
-- The above query will fail if the data files for T1 contain any
-- values that can't be converted to the expected Impala data types.
-- For example, if T1.C1 is defined as INT but the column contains
-- floating-point values like 1.1, the query will return an error.
```

SQL Statements to Remove or Adapt

The following SQL statements or clauses are not currently supported or supported with limitations in Impala:

- Impala supports the `DELETE` statement only for Kudu tables.

Impala is intended for data warehouse-style operations where you do bulk moves and transforms of large quantities of data. When not using Kudu tables, instead of `DELETE`, use `INSERT OVERWRITE` to entirely replace the contents of a table or partition, or use `INSERT ... SELECT` to copy a subset of data (everything but the rows you intended to delete) from one table to another. See [DML Statements](#) on page 214 for an overview of Impala DML statements.

- Impala supports the `UPDATE` statement only for Kudu tables.

When not using Kudu tables, instead of `UPDATE`, do all necessary transformations early in the ETL process, such as in the job that generates the original data, or when copying from one table to another to convert to a particular file format or partitioning scheme. See [DML Statements](#) on page 214 for an overview of Impala DML statements.

- Impala has no transactional statements, such as `COMMIT` or `ROLLBACK`.

Impala effectively works like the `AUTOCOMMIT` mode in some database systems, where changes take effect as soon as they are made.

- If your database, table, column, or other names conflict with Impala reserved words, use different names or quote the names with backticks.

See [Impala Reserved Words](#) on page 821 for the current list of Impala reserved words.

Conversely, if you use a keyword that Impala does not recognize, it might be interpreted as a table or column alias.

For example, in `SELECT * FROM t1 NATURAL JOIN t2`, Impala does not recognize the `NATURAL` keyword and interprets it as an alias for the table `t1`. If you experience any unexpected behavior with queries, check the list of reserved words to make sure all keywords in `join` and `WHERE` clauses are supported keywords in Impala.

- Impala has some restrictions on subquery support. See [Subqueries in Impala SELECT Statements](#) for the current details.
- Impala supports `UNION` and `UNION ALL` set operators, but not `INTERSECT`.

Prefer `UNION ALL` over `UNION` when you know the data sets are disjoint or duplicate values are not a problem; `UNION ALL` is more efficient because it avoids materializing and sorting the entire result set to eliminate duplicate values.

- Impala requires query aliases for the subqueries used as inline views in the `FROM` clause.

For example, without the alias `contents_of_t1` at the end, the following query gives a syntax error:

```
SELECT COUNT(*) FROM (SELECT * FROM t1) contents_of_t1;
```

Aliases are not required for the subqueries used in other parts of queries. For example:

```
SELECT * FROM functional.alltypes WHERE id = (SELECT MIN(id) FROM
functional.alltypes);
```

- When an alias is declared for an expression in a query, that alias cannot be referenced again within the same `SELECT` list.

For example, the `average` alias cannot be referenced twice in the `SELECT` list as below. You will receive an error:

```
SELECT AVG(x) AS average, average+1 FROM t1 GROUP BY x;
```

An alias can be referenced again in the same query if not in the `SELECT` list. For example, the `average` alias can be referenced twice as shown below:

```
SELECT AVG(x) AS average FROM t1 GROUP BY x HAVING average > 3;
```

- Impala does not support `NATURAL JOIN`, and it does not support the `USING` clause in joins. See [Joins in Impala SELECT Statements](#) on page 318 for details on the syntax for Impala join clauses.
- Impala supports a limited choice of partitioning types.

Partitions are defined based on each distinct combination of values for one or more partition key columns. Impala does not redistribute or check data to create evenly distributed partitions. You must choose partition key columns based on your knowledge of the data volume and distribution. Adapt any tables that use range, list, hash, or key partitioning to use the Impala partition syntax for `CREATE TABLE` and `ALTER TABLE` statements.

Impala partitioning is similar to range partitioning where every range has exactly one value, or key partitioning where the hash function produces a separate bucket for every combination of key values. See [Partitioning for Impala Tables](#) on page 685 for usage details, and [CREATE TABLE Statement](#) on page 248 and [ALTER TABLE Statement](#) on page 215 for syntax.

Note: Because the number of separate partitions is potentially higher than in other database systems, keep a close eye on the number of partitions and the volume of data in each one; scale back the number of partition key columns if you end up with too many partitions with a small volume of data in each one.

To distribute work for a query across a cluster, you need at least one HDFS block per node. HDFS blocks are typically multiple megabytes, especially for Parquet files. Therefore, if each partition holds only a few megabytes of data, you are unlikely to see much parallelism in the query because such a small amount of data is typically processed by a single node.

- For the “top-N” queries, Impala uses the `LIMIT` clause rather than comparing against a pseudo column named `ROWNUM` or `ROW_NUM`.

See [LIMIT Clause](#) on page 331 for details.

SQL Constructs to Double-check

Some SQL constructs that are supported have behavior or defaults more oriented towards convenience than optimal performance. Also, sometimes machine-generated SQL, perhaps issued through JDBC or ODBC applications, might have inefficiencies or exceed internal Impala limits. As you port SQL code, examine and possibly update the following where appropriate:

- A `CREATE TABLE` statement with no `STORED AS` clause creates data files in plain text format, which is convenient for data interchange but not a good choice for high-volume data with high-performance queries. See [How Impala Works with Hadoop File Formats](#) on page 695 for why and how to use specific file formats for compact data and high-performance queries. Especially see [Using the Parquet File Format with Impala Tables](#) on page 705, for details about the file format most heavily optimized for large-scale data warehouse queries.
- Adapting tables that were already partitioned in a different database system could produce an Impala table with a high number of partitions and not enough data in each one, leading to underutilization of Impala's parallel query features.

See [Partitioning for Impala Tables](#) on page 685 for details about setting up partitioning and tuning the performance of queries on partitioned tables.

- The `INSERT . . . VALUES` syntax is suitable for setting up toy tables with a few rows for functional testing when used with HDFS. Each such statement creates a separate tiny file in HDFS, and it is not a scalable technique for loading megabytes or gigabytes (let alone petabytes) of data.

Consider revising your data load process to produce raw data files outside of Impala, then setting up Impala external tables or using the `LOAD DATA` statement to use those data files instantly in Impala tables, with no conversion or indexing stage. See [External Tables](#) on page 207 and [LOAD DATA Statement](#) on page 309 for details about the Impala techniques for working with data files produced outside of Impala; see [Data Loading and Querying Examples](#) on page 45 for examples of ETL workflow for Impala.

`INSERT` works fine for Kudu tables even though not particularly fast.

- If your ETL process is not optimized for Hadoop, you might end up with highly fragmented small data files, or a single giant data file that cannot take advantage of distributed parallel queries or partitioning. In this case, use an `INSERT . . . SELECT` statement to copy the data into a new table and reorganize into a more efficient layout in the same operation. See [INSERT Statement](#) on page 298 for details about the `INSERT` statement.

You can do `INSERT . . . SELECT` into a table with a more efficient file format (see [How Impala Works with Hadoop File Formats](#) on page 695) or from an unpartitioned table into a partitioned one. See [Partitioning for Impala Tables](#) on page 685.

- Complex queries may have high codegen time. As a workaround, set the query option `DISABLE_CODEGEN=true` if queries fail for this reason. See [DISABLE_CODEGEN Query Option](#) on page 353 for details.

- If practical, rewrite `UNION` queries to use the `UNION ALL` operator instead. Prefer `UNION ALL` over `UNION` when you know the data sets are disjoint or duplicate values are not a problem; `UNION ALL` is more efficient because it avoids materializing and sorting the entire result set to eliminate duplicate values.

Next Porting Steps after Verifying Syntax and Semantics

Some of the decisions you make during the porting process can have an impact on performance. After your SQL code is ported and working correctly, examine the performance-related aspects of your schema design, physical layout, and queries to make sure that the ported application is taking full advantage of Impala's parallelism, performance-related SQL features, and integration with Hadoop components. The following are a few of the areas you should examine:

- For the optimal performance, we recommend that you run `COMPUTE STATS` on all tables.
- Use the most efficient file format for your data volumes, table structure, and query characteristics.
- Partition on columns that are often used for filtering in `WHERE` clauses.
- Your ETL process should produce a relatively small number of multi-megabyte data files rather than a huge number of small files.

See [Tuning Impala for Performance](#) on page 614 for details about the performance tuning process.

UTF-8 Support

Impala has traditionally offered a single-byte binary character set for `STRING` data type and the character data is encoded in ASCII character set. Prior to this release, Impala was incompatible with Hive in some functions applying on non-ASCII strings. E.g. `length()` in Impala used to return the length of bytes of the string, while `length()` in Hive returns the length of UTF-8 characters of the string. UTF-8 characters (code points) are assembled in variant-length bytes (1~4 bytes), so the results differ when there are non-ASCII characters in the string. This release provides a UTF-8 aware behavior for Impala `STRING` type to get consistent behavior with Hive on UTF-8 strings using a query option.

UTF-8 support allows you to read and write UTF-8 from standard formats like Parquet and ORC, thus improving interoperability with other engines that also support those standard formats.

Turning ON the UTF-8 behavior

You can use the new query option, `UTF8_MODE`, to turn on/off the UTF-8 aware behavior. The query option can be set globally, or at per session level. Only queries with `UTF8_MODE=true` will have UTF-8 aware behaviors.

Note:

- If the query option `UTF8_MODE` is turned on globally, existing queries that depend on the original binary behavior need to explicitly set `UTF8_MODE=false`.
- Impala Daemons should be deployed on nodes using the same Glibc version since different Glibc version supports different Unicode standard version and also ensure that the `en_US.UTF-8` locale is installed in the nodes. Not using the same Glibc version might result in inconsistent UTF-8 behavior when `UTF8_MODE` is set to true.

List of `STRING` Functions

The new query option introduced will turn on the UTF-8 aware behavior of the following string functions:

- `LENGTH(STRING a)`
 - returns the number of UTF-8 characters instead of bytes
- `SUBSTR(STRING a, INT start [, INT len])`
- `SUBSTRING(STRING a, INT start [, INT len])()`
 - the substring start position and length is counted by UTF-8 characters instead of bytes
- `REVERSE(STRING a)`
 - the unit of the operation is a UTF-8 character, ie. it won't reverse bytes inside a UTF-8 character.

Note: The results of `reverse('###SQL##')` used to be `####LQS####` and now `##LQS###`.

- `INSTR(String str, String substr[, BIGINT position[, BIGINT occurrence]])`
- `LOCATE(String substr, String str[, INT pos])`
 - These functions have an optional position argument. The return values are also positions in the string. In UTF-8 mode, these positions are counted by UTF-8 characters instead of bytes.
- mask functions
 - The unit of the operation is a UTF-8 character, ie. they won't mask the string byte-to-byte.
- upper/lower/initcap
 - These functions will recognize non-ascii characters and transform them based on the current locale used by the Impala process.

Limitations

- Use the `UTF8_MODE` option only when needed since the performance of UTF_8 is not optimized yet. It is only an experimental feature.
- UTF-8 support for `CHAR` and `VARCHAR` types is not implemented yet. So `VARCHAR(N)` will still return N bytes instead of N UTF-8 characters.

Tuning Impala for Performance

The following sections explain the factors affecting the performance of Impala features, and procedures for tuning, monitoring, and benchmarking Impala queries and other SQL operations.

This section also describes techniques for maximizing Impala scalability. Scalability is tied to performance: it means that performance remains high as the system workload increases. For example, reducing the disk I/O performed by a query can speed up an individual query, and at the same time improve scalability by making it practical to run more queries simultaneously. Sometimes, an optimization technique improves scalability more than performance. For example, reducing memory usage for a query might not change the query performance much, but might improve scalability by allowing more Impala queries or other kinds of jobs to run at the same time without running out of memory.

Note:

Before starting any performance tuning or benchmarking, make sure your system is configured with all the recommended minimum hardware requirements from [Hardware Requirements](#) on page 23 and software settings from [Post-Installation Configuration for Impala](#) on page 27.

- [Partitioning for Impala Tables](#) on page 685. This technique physically divides the data based on the different values in frequently queried columns, allowing queries to skip reading a large percentage of the data in a table.
- [Performance Considerations for Join Queries](#) on page 618. Joins are the main class of queries that you can tune at the SQL level, as opposed to changing physical factors such as the file format or the hardware configuration. The related topics [Overview of Column Statistics](#) on page 626 and [Overview of Table Statistics](#) on page 625 are also important primarily for join performance.
- [Overview of Table Statistics](#) on page 625 and [Overview of Column Statistics](#) on page 626. Gathering table and column statistics, using the `COMPUTE STATS` statement, helps Impala automatically optimize the performance for join queries, without requiring changes to SQL query statements. (This process is greatly simplified in Impala 1.2.2 and higher, because the `COMPUTE STATS` statement gathers both kinds of statistics in one operation, and does not require any setup and configuration as was previously necessary for the `ANALYZE TABLE` statement in Hive.)
- [Testing Impala Performance](#) on page 653. Do some post-setup testing to ensure Impala is using optimal settings for performance, before conducting any benchmark tests.
- [Benchmarking Impala Queries](#) on page 641. The configuration and sample data that you use for initial experiments with Impala is often not appropriate for doing performance tests.

- [Controlling Impala Resource Usage](#) on page 641. The more memory Impala can utilize, the better query performance you can expect. In a cluster running other kinds of workloads as well, you must make tradeoffs to make sure all Hadoop components have enough memory to perform well, so you might cap the memory that Impala can use.
- [Using Impala with Amazon S3 Object Store](#) on page 769. Queries against data stored in the Amazon Simple Storage Service (S3) have different performance characteristics than when the data is stored in HDFS.

A good source of tips related to scalability and performance tuning is the [Impala Cookbook](#) presentation. These slides are updated periodically as new features come out and new benchmarks are performed.

Impala Performance Guidelines and Best Practices

Here are performance guidelines and best practices that you can use during planning, experimentation, and performance tuning for an Impala-enabled cluster. All of this information is also available in more detail elsewhere in the Impala documentation; it is gathered together here to serve as a cookbook and emphasize which performance techniques typically provide the highest return on investment

Choose the appropriate file format for the data

Typically, for large volumes of data (multiple gigabytes per table or partition), the Parquet file format performs best because of its combination of columnar storage layout, large I/O request size, and compression and encoding. See [How Impala Works with Hadoop File Formats](#) on page 695 for comparisons of all file formats supported by Impala, and [Using the Parquet File Format with Impala Tables](#) on page 705 for details about the Parquet file format.

Note: For smaller volumes of data, a few gigabytes or less for each table or partition, you might not see significant performance differences between file formats. At small data volumes, reduced I/O from an efficient compressed file format can be counterbalanced by reduced opportunity for parallel execution. When planning for a production deployment or conducting benchmarks, always use realistic data volumes to get a true picture of performance and scalability.

Avoid data ingestion processes that produce many small files

When producing data files outside of Impala, prefer either text format or Avro, where you can build up the files row by row. Once the data is in Impala, you can convert it to the more efficient Parquet format and split into multiple data files using a single `INSERT ... SELECT` statement. Or, if you have the infrastructure to produce multi-megabyte Parquet files as part of your data preparation process, do that and skip the conversion step inside Impala.

Always use `INSERT ... SELECT` to copy significant volumes of data from table to table within Impala. Avoid `INSERT ... VALUES` for any substantial volume of data or performance-critical tables, because each such statement produces a separate tiny data file. See [INSERT Statement](#) on page 298 for examples of the `INSERT ... SELECT` syntax.

For example, if you have thousands of partitions in a Parquet table, each with less than 256 MB of data, consider partitioning in a less granular way, such as by year / month rather than year / month / day. If an inefficient data ingestion process produces thousands of data files in the same table or partition, consider compacting the data by performing an `INSERT ... SELECT` to copy all the data to a different table; the data will be reorganized into a smaller number of larger files by this process.

Choose partitioning granularity based on actual data volume

Partitioning is a technique that physically divides the data based on values of one or more columns, such as by year, month, day, region, city, section of a web site, and so on. When you issue queries that request a specific value or range of values for the partition key columns, Impala can avoid reading the irrelevant data, potentially yielding a huge savings in disk I/O.

When deciding which column(s) to use for partitioning, choose the right level of granularity. For example, should you partition by year, month, and day, or only by year and month? Choose a partitioning strategy that puts at least 256 MB of data in each partition, to take advantage of HDFS bulk I/O and Impala distributed queries.

Over-partitioning can also cause query planning to take longer than necessary, as Impala prunes the unnecessary partitions. Ideally, keep the number of partitions in the table under 30 thousand.

When preparing data files to go in a partition directory, create several large files rather than many small ones. If you receive data in the form of many small files and have no control over the input format, consider using the `INSERT . . . SELECT` syntax to copy data from one table or partition to another, which compacts the files into a relatively small number (based on the number of nodes in the cluster).

If you need to reduce the overall number of partitions and increase the amount of data in each partition, first look for partition key columns that are rarely referenced or are referenced in non-critical queries (not subject to an SLA). For example, your web site log data might be partitioned by year, month, day, and hour, but if most queries roll up the results by day, perhaps you only need to partition by year, month, and day.

If you need to reduce the granularity even more, consider creating “buckets”, computed values corresponding to different sets of partition key values. For example, you can use the `TRUNC ()` function with a `TIMESTAMP` column to group date and time values based on intervals such as week or quarter. See [Impala Date and Time Functions](#) on page 478 for details.

See [Partitioning for Impala Tables](#) on page 685 for full details and performance considerations for partitioning.

Use smallest appropriate integer types for partition key columns

Although it is tempting to use strings for partition key columns, since those values are turned into HDFS directory names anyway, you can minimize memory usage by using numeric values for common partition key fields such as `YEAR`, `MONTH`, and `DAY`. Use the smallest integer type that holds the appropriate range of values, typically `TINYINT` for `MONTH` and `DAY`, and `SMALLINT` for `YEAR`. Use the `EXTRACT ()` function to pull out individual date and time fields from a `TIMESTAMP` value, and `CAST ()` the return value to the appropriate integer type.

Choose an appropriate Parquet block size

By default, the Impala `INSERT . . . SELECT` statement creates Parquet files with a 256 MB block size. (This default was changed in Impala 2.0. Formerly, the limit was 1 GB, but Impala made conservative estimates about compression, resulting in files that were smaller than 1 GB.)

Each Parquet file written by Impala is a single block, allowing the whole file to be processed as a unit by a single host. As you copy Parquet files into HDFS or between HDFS filesystems, use `hdfs dfs -pb` to preserve the original block size.

If there is only one or a few data block in your Parquet table, or in a partition that is the only one accessed by a query, then you might experience a slowdown for a different reason: not enough data to take advantage of Impala's parallel distributed queries. Each data block is processed by a single core on one of the DataNodes. In a 100-node cluster of 16-core machines, you could potentially process thousands of data files simultaneously. You want to find a sweet spot between “many tiny files” and “single giant file” that balances bulk I/O and parallel processing. You can set the `PARQUET_FILE_SIZE` query option before doing an `INSERT . . . SELECT` statement to reduce the size of each generated Parquet file. (Specify the file size as an absolute number of bytes, or in Impala 2.0 and later, in units ending with `m` for megabytes or `g` for gigabytes.) Run benchmarks with different file sizes to find the right balance point for your particular data volume.

Gather statistics for all tables used in performance-critical or high-volume join queries

Gather the statistics with the `COMPUTE STATS` statement. See [Performance Considerations for Join Queries](#) on page 618 for details.

Minimize the overhead of transmitting results back to the client

Use techniques such as:

- Aggregation. If you need to know how many rows match a condition, the total values of matching values from some column, the lowest or highest matching value, and so on, call aggregate functions such as `COUNT()`, `SUM()`, and `MAX()` in the query rather than sending the result set to an application and doing those computations there. Remember that the size of an unaggregated result set could be huge, requiring substantial time to transmit across the network.
- Filtering. Use all applicable tests in the `WHERE` clause of a query to eliminate rows that are not relevant, rather than producing a big result set and filtering it using application logic.
- `LIMIT` clause. If you only need to see a few sample values from a result set, or the top or bottom values from a query using `ORDER BY`, include the `LIMIT` clause to reduce the size of the result set rather than asking for the full result set and then throwing most of the rows away.
- Avoid overhead from pretty-printing the result set and displaying it on the screen. When you retrieve the results through `impala-shell`, use `impala-shell` options such as `-B` and `--output_delimiter` to produce results without special formatting, and redirect output to a file rather than printing to the screen. Consider using `INSERT ... SELECT` to write the results directly to new files in HDFS. See [impala-shell Configuration Options](#) on page 791 for details about the `impala-shell` command-line options.

Verify that your queries are planned in an efficient logical manner

Examine the `EXPLAIN` plan for a query before actually running it. See [EXPLAIN Statement](#) on page 291 and [Using the EXPLAIN Plan for Performance Tuning](#) on page 655 for details.

Verify performance characteristics of queries

Verify that the low-level aspects of I/O, memory usage, network bandwidth, CPU utilization, and so on are within expected ranges by examining the query profile for a query after running it. See [Using the Query Profile for Performance Tuning](#) on page 656 for details.

Use appropriate operating system settings

See the documentation for your Apache Hadoop distribution for recommendations about operating system settings that you can change to influence Impala performance. In particular, you might find that changing the `vm.swappiness` Linux kernel setting to a non-zero value improves overall performance.

Hotspot analysis

In the context of Impala, a hotspot is defined as “an Impala daemon that for a single query or a workload is spending a far greater amount of time processing data relative to its neighbours”.

Before discussing the options to tackle this issue some background is first required to understand how this problem can occur.

By default, the scheduling of scan based plan fragments is deterministic. This means that for multiple queries needing to read the same block of data, the same node will be picked to host the scan. The default scheduling logic does not take into account node workload from prior queries. The complexity of materializing a tuple depends on a few factors, namely: decoding and decompression. If the tuples are densely packed into data pages due to good encoding/compression ratios, there will be more work required when reconstructing the data. Each compression codec offers different performance tradeoffs and should be considered before writing the data. Due to the deterministic nature of the scheduler, single nodes can become bottlenecks for highly concurrent queries that use the same tables.

If, for example, a Parquet based dataset is tiny, e.g. a small dimension table, such that it fits into a single HDFS block (Impala by default will create 256 MB blocks when Parquet is used, each containing a single row group) then there are a number of options that can be considered to resolve the potential scheduling hotspots when querying this data:

- In Impala 2.5 and higher, the scheduler’s deterministic behaviour can be changed using the following query options: `REPLICA_PREFERENCE` and `RANDOM_REPLICA`. For a detailed description of each of these modes see `IMPALA-2696`.
- HDFS caching can be used to cache block replicas. This will cause the Impala scheduler to randomly pick (from Impala 2.2 and higher) a node that is hosting a cached block replica for the scan. Note, although HDFS caching has benefits, it serves only to help with the reading of raw block data and not cached tuple data, but with the right

number of cached replicas (by default, HDFS only caches one replica), even load distribution can be achieved for smaller datasets.

- Do not compress the table data. The uncompressed table data spans more nodes and eliminates skew caused by compression.
- Reduce the Parquet file size via the `PARQUET_FILE_SIZE` query option when writing the table data. Using this approach the data will span more nodes. However it's not recommended to drop the size below 32 MB.

Performance Considerations for Join Queries

Queries involving join operations often require more tuning than queries that refer to only one table. The maximum size of the result set from a join query is the product of the number of rows in all the joined tables. When joining several tables with millions or billions of rows, any missed opportunity to filter the result set, or other inefficiency in the query, could lead to an operation that does not finish in a practical time and has to be cancelled.

The simplest technique for tuning an Impala join query is to collect statistics on each table involved in the join using the `COMPUTE STATS` statement, and then let Impala automatically optimize the query based on the size of each table, number of distinct values of each column, and so on. The `COMPUTE STATS` statement and the join optimization are new features introduced in Impala 1.2.2. For accurate statistics about each table, issue the `COMPUTE STATS` statement after loading the data into that table, and again if the amount of data changes substantially due to an `INSERT`, `LOAD DATA`, adding a partition, and so on.

If statistics are not available for all the tables in the join query, or if Impala chooses a join order that is not the most efficient, you can override the automatic join order optimization by specifying the `STRAIGHT_JOIN` keyword immediately after the `SELECT` and any `DISTINCT` or `ALL` keywords. In this case, Impala uses the order the tables appear in the query to guide how the joins are processed.

When you use the `STRAIGHT_JOIN` technique, you must order the tables in the join query manually instead of relying on the Impala optimizer. The optimizer uses sophisticated techniques to estimate the size of the result set at each stage of the join. For manual ordering, use this heuristic approach to start with, and then experiment to fine-tune the order:

- Specify the largest table first. This table is read from disk by each Impala node and so its size is not significant in terms of memory usage during the query.
- Next, specify the smallest table. The contents of the second, third, and so on tables are all transmitted across the network. You want to minimize the size of the result set from each subsequent stage of the join query. The most likely approach involves joining a small table first, so that the result set remains small even as subsequent larger tables are processed.
- Join the next smallest table, then the next smallest, and so on.

For example, if you had tables `BIG`, `MEDIUM`, `SMALL`, and `TINY`, the logical join order to try would be `BIG`, `TINY`, `SMALL`, `MEDIUM`.

The terms “largest” and “smallest” refers to the size of the intermediate result set based on the number of rows and columns from each table that are part of the result set. For example, if you join one table `sales` with another table `customers`, a query might find results from 100 different customers who made a total of 5000 purchases. In that case, you would specify `SELECT ... FROM sales JOIN customers ...`, putting `customers` on the right side because it is smaller in the context of this query.

The Impala query planner chooses between different techniques for performing join queries, depending on the absolute and relative sizes of the tables. **Broadcast joins** are the default, where the right-hand table is considered to be smaller than the left-hand table, and its contents are sent to all the other nodes involved in the query. The alternative technique is known as a **partitioned join** (not related to a partitioned table), which is more suitable for large tables of roughly equal size. With this technique, portions of each table are sent to appropriate other nodes where those subsets of rows can be processed in parallel. The choice of broadcast or partitioned join also depends on statistics being available for all tables in the join, gathered by the `COMPUTE STATS` statement.

To see which join strategy is used for a particular query, issue an `EXPLAIN` statement for the query. If you find that a query uses a broadcast join when you know through benchmarking that a partitioned join would be more efficient, or

vice versa, add a hint to the query to specify the precise join mechanism to use. See [Optimizer Hints](#) on page 422 for details.

How Joins Are Processed when Statistics Are Unavailable

If table or column statistics are not available for some tables in a join, Impala still reorders the tables using the information that is available. Tables with statistics are placed on the left side of the join order, in descending order of cost based on overall size and cardinality. Tables without statistics are treated as zero-size, that is, they are always placed on the right side of the join order.

Overriding Join Reordering with STRAIGHT_JOIN

If an Impala join query is inefficient because of outdated statistics or unexpected data distribution, you can keep Impala from reordering the joined tables by using the `STRAIGHT_JOIN` keyword immediately after the `SELECT` and any `DISTINCT` or `ALL` keywords. The `STRAIGHT_JOIN` keyword turns off the reordering of join clauses that Impala does internally, and produces a plan that relies on the join clauses being ordered optimally in the query text.

Note:

The `STRAIGHT_JOIN` hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or `WHERE`-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

In this example, the subselect from the `BIG` table produces a very small result set, but the table might still be treated as if it were the biggest and placed first in the join order. Using `STRAIGHT_JOIN` for the last join clause prevents the final table from being reordered, keeping it as the rightmost table in the join order.

```
select straight_join x from medium join small join (select * from big where
  c1 < 10) as big
  where medium.id = small.id and small.id = big.id;

-- If the query contains [DISTINCT | ALL], the hint goes after those
  keywords.
select distinct straight_join x from medium join small join (select * from
  big where c1 < 10) as big
  where medium.id = small.id and small.id = big.id;
```

Examples of Join Order Optimization

Here are examples showing joins between tables with 1 billion, 200 million, and 1 million rows. (In this case, the tables are unpartitioned and using Parquet format.) The smaller tables contain subsets of data from the largest one, for convenience of joining on the unique `ID` column. The smallest table only contains a subset of columns from the others.

```
[localhost:21000] > create table big stored as parquet as select * from
  raw_data;
```

summary		
Inserted 1000000000 row(s)		

```
Returned 1 row(s) in 671.56s
[localhost:21000] > desc big;
```

name	type	comment
id	int	
val	int	
zfill	string	
name	string	

```

| assertion | boolean |
+-----+
Returned 5 row(s) in 0.01s
[localhost:21000] > create table medium stored as parquet as select * from
  big limit 200 * floor(1e6);
+-----+
| summary |
+-----+
| Inserted 200000000 row(s) |
+-----+
Returned 1 row(s) in 138.31s
[localhost:21000] > create table small stored as parquet as select
  id,val,name from big where assertion = true limit 1 * floor(1e6);
+-----+
| summary |
+-----+
| Inserted 1000000 row(s) |
+-----+
Returned 1 row(s) in 6.32s

```

For any kind of performance experimentation, use the EXPLAIN statement to see how any expensive query will be performed without actually running it, and enable verbose EXPLAIN plans containing more performance-oriented detail: The most interesting plan lines are highlighted in bold, showing that without statistics for the joined tables, Impala cannot make a good estimate of the number of rows involved at each stage of processing, and is likely to stick with the BROADCAST join mechanism that sends a complete copy of one of the tables to each node.

```

[localhost:21000] > set explain_level=verbose;
EXPLAIN_LEVEL set to verbose
[localhost:21000] > explain select count(*) from big join medium where
  big.id = medium.id;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=2.10GB VCores=2 |
+-----+
| PLAN FRAGMENT 0 |
| PARTITION: UNPARTITIONED |
| 6:AGGREGATE (merge finalize) |
|   output: SUM(COUNT(*)) |
|   cardinality: 1 |
|   per-host memory: unavailable |
|   tuple ids: 2 |
| 5:EXCHANGE |
|   cardinality: 1 |
|   per-host memory: unavailable |
|   tuple ids: 2 |
| PLAN FRAGMENT 1 |
| PARTITION: RANDOM |
| STREAM DATA SINK |
|   EXCHANGE ID: 5 |
|   UNPARTITIONED |
| 3:AGGREGATE |
|   output: COUNT(*) |
|   cardinality: 1 |
|   per-host memory: 10.00MB |
|   tuple ids: 2 |
| 2:HASH JOIN |

```

```

join op: INNER JOIN (BROADCAST)
hash predicates:
  big.id = medium.id
cardinality: unavailable
per-host memory: 2.00GB
tuple ids: 0 1

----4:EXCHANGE
  cardinality: unavailable
  per-host memory: 0B
  tuple ids: 1

0:SCAN HDFS
  table=join_order.big #partitions=1/1 size=23.12GB
  table stats: unavailable
  column stats: unavailable
  cardinality: unavailable
  per-host memory: 88.00MB
  tuple ids: 0

PLAN FRAGMENT 2
PARTITION: RANDOM

STREAM DATA SINK
  EXCHANGE ID: 4
  UNPARTITIONED

1:SCAN HDFS
  table=join_order.medium #partitions=1/1 size=4.62GB
  table stats: unavailable
  column stats: unavailable
  cardinality: unavailable
  per-host memory: 88.00MB
  tuple ids: 1
+-----+
Returned 64 row(s) in 0.04s

```

Gathering statistics for all the tables is straightforward, one `COMPUTE STATS` statement per table:

```

[localhost:21000] > compute stats small;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 3 column(s). |
+-----+
Returned 1 row(s) in 4.26s
[localhost:21000] > compute stats medium;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 5 column(s). |
+-----+
Returned 1 row(s) in 42.11s
[localhost:21000] > compute stats big;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 5 column(s). |
+-----+
Returned 1 row(s) in 165.44s

```

With statistics in place, Impala can choose a more effective join order rather than following the left-to-right sequence of tables in the query, and can choose BROADCAST or PARTITIONED join strategies based on the overall sizes and number of rows in the table:

```
[localhost:21000] > explain select count(*) from medium join big where
big.id = medium.id;
Query: explain select count(*) from medium join big where big.id = medium.id
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=937.23MB VCores=2 |
+-----+
| PLAN FRAGMENT 0 |
|   PARTITION: UNPARTITIONED |
| |
| 6:AGGREGATE (merge finalize) |
|   output: SUM(COUNT(*)) |
|   cardinality: 1 |
|   per-host memory: unavailable |
|   tuple ids: 2 |
| |
| 5:EXCHANGE |
|   cardinality: 1 |
|   per-host memory: unavailable |
|   tuple ids: 2 |
| |
| PLAN FRAGMENT 1 |
|   PARTITION: RANDOM |
| |
| STREAM DATA SINK |
|   EXCHANGE ID: 5 |
|   UNPARTITIONED |
| |
| 3:AGGREGATE |
|   output: COUNT(*) |
|   cardinality: 1 |
|   per-host memory: 10.00MB |
|   tuple ids: 2 |
| |
| 2:HASH JOIN |
|   join op: INNER JOIN (BROADCAST) |
|   hash predicates: |
|     big.id = medium.id |
|   cardinality: 1443004441 |
|   per-host memory: 839.23MB |
|   tuple ids: 1 0 |
| |
| ----4:EXCHANGE |
|       cardinality: 200000000 |
|       per-host memory: 0B |
|       tuple ids: 0 |
| |
| 1:SCAN HDFS |
|   table=join_order.big #partitions=1/1 size=23.12GB |
|   table stats: 1000000000 rows total |
|   column stats: all |
|   cardinality: 1000000000 |
|   per-host memory: 88.00MB |
|   tuple ids: 1 |
| |
| PLAN FRAGMENT 2 |
|   PARTITION: RANDOM |
```

```

STREAM DATA SINK
  EXCHANGE ID: 4
  UNPARTITIONED

0:SCAN HDFS
  table=join_order.medium #partitions=1/1 size=4.62GB
  table stats: 200000000 rows total
  column stats: all
  cardinality: 200000000
  per-host memory: 88.00MB
  tuple ids: 0

```

Returned 64 row(s) in 0.04s

```
[localhost:21000] > explain select count(*) from small join big where big.id = small.id;
```

Query: explain select count(*) from small join big where big.id = small.id

```

-----
| Explain String

```

```

-----
| Estimated Per-Host Requirements: Memory=101.15MB VCores=2

```

```

PLAN FRAGMENT 0
  PARTITION: UNPARTITIONED

6:AGGREGATE (merge finalize)
  | output: SUM(COUNT(*))
  | cardinality: 1
  | per-host memory: unavailable
  | tuple ids: 2

5:EXCHANGE
  cardinality: 1
  per-host memory: unavailable
  tuple ids: 2

```

```

PLAN FRAGMENT 1
  PARTITION: RANDOM

```

```

STREAM DATA SINK
  EXCHANGE ID: 5
  UNPARTITIONED

```

```

3:AGGREGATE
  | output: COUNT(*)
  | cardinality: 1
  | per-host memory: 10.00MB
  | tuple ids: 2

```

```

2:HASH JOIN
  | join op: INNER JOIN (BROADCAST)
  | hash predicates:
  |   big.id = small.id
  | cardinality: 1000000000
  | per-host memory: 3.15MB
  | tuple ids: 1 0

```

```

----4:EXCHANGE
  | cardinality: 1000000
  | per-host memory: 0B
  | tuple ids: 0

```

```

1:SCAN HDFS
  table=join_order.big #partitions=1/1 size=23.12GB

```

```

    table stats: 1000000000 rows total
    column stats: all
    cardinality: 1000000000
    per-host memory: 88.00MB
    tuple ids: 1

PLAN FRAGMENT 2
  PARTITION: RANDOM

  STREAM DATA SINK
    EXCHANGE ID: 4
    UNPARTITIONED

    0:SCAN HDFS
      table=join_order.small #partitions=1/1 size=17.93MB
      table stats: 1000000 rows total
      column stats: all
      cardinality: 1000000
      per-host memory: 32.00MB
      tuple ids: 0
+-----+
Returned 64 row(s) in 0.03s

```

When queries like these are actually run, the execution times are relatively consistent regardless of the table order in the query text. Here are examples using both the unique ID column and the VAL column containing duplicate values:

```

[localhost:21000] > select count(*) from big join small on (big.id =
  small.id);
Query: select count(*) from big join small on (big.id = small.id)
+-----+
| count(*) |
+-----+
| 1000000  |
+-----+
Returned 1 row(s) in 21.68s
[localhost:21000] > select count(*) from small join big on (big.id =
  small.id);
Query: select count(*) from small join big on (big.id = small.id)
+-----+
| count(*) |
+-----+
| 1000000  |
+-----+
Returned 1 row(s) in 20.45s

[localhost:21000] > select count(*) from big join small on (big.val =
  small.val);
+-----+
| count(*) |
+-----+
| 2000948962 |
+-----+
Returned 1 row(s) in 108.85s
[localhost:21000] > select count(*) from small join big on (big.val =
  small.val);
+-----+
| count(*) |
+-----+
| 2000948962 |
+-----+
Returned 1 row(s) in 100.76s

```


Note: When examining the performance of join queries and the effectiveness of the join order optimization, make sure the query involves enough data and cluster resources to see a difference depending on the query plan. For example, a single data file of just a few megabytes will reside in a single HDFS block and be processed on a single node. Likewise, if you use a single-node or two-node cluster, there might not be much difference in efficiency for the broadcast or partitioned join strategies.

Table and Column Statistics

Impala can do better optimization for complex or multi-table queries when it has access to statistics about the volume of data and how the values are distributed. Impala uses this information to help parallelize and distribute the work for a query. For example, optimizing join queries requires a way of determining if one table is “bigger” than another, which is a function of the number of rows and the average row size for each table. The following sections describe the categories of statistics Impala can work with, and how to produce them and keep them up to date.

Overview of Table Statistics

The Impala query planner can make use of statistics about entire tables and partitions. This information includes physical characteristics such as the number of rows, number of data files, the total size of the data files, and the file format. For partitioned tables, the numbers are calculated per partition, and as totals for the whole table. This metadata is stored in the metastore database, and can be updated by either Impala or Hive. If a number is not available, the value -1 is used as a placeholder. Some numbers, such as number and total sizes of data files, are always kept up to date because they can be calculated cheaply, as part of gathering HDFS block metadata.

The following example shows table stats for an unpartitioned Parquet table. The values for the number and sizes of files are always available. Initially, the number of rows is not known, because it requires a potentially expensive scan through the entire table, and so that value is displayed as -1. The `COMPUTE STATS` statement fills in any unknown table stats values.

```
show table stats parquet_snappy;
```

#Rows	#Files	Size	Bytes Cached	Cache Replication	Format
-1	96	23.35GB	NOT CACHED	NOT CACHED	PARQUET

```
compute stats parquet_snappy;
```

summary
Updated 1 partition(s) and 6 column(s).

```
show table stats parquet_snappy;
```

#Rows	#Files	Size	Bytes Cached	Cache Replication	Format
1000000000	96	23.35GB	NOT CACHED	NOT CACHED	PARQUET

Impala performs some optimizations using this metadata on its own, and other optimizations by using a combination of table and column statistics.

To check that table statistics are available for a table, and see the details of those statistics, use the statement `SHOW TABLE STATS table_name`. See [SHOW Statement](#) on page 395 for details.

If you use the Hive-based methods of gathering statistics, see [the Hive wiki](#) for information about the required configuration on the Hive side. Where practical, use the Impala `COMPUTE STATS` statement to avoid potential configuration and scalability issues with the statistics-gathering process.

If you run the Hive statement `ANALYZE TABLE COMPUTE STATISTICS FOR COLUMNS`, Impala can only use the resulting column statistics if the table is unpartitioned. Impala cannot use Hive-generated column statistics for a partitioned table.

Overview of Column Statistics

The Impala query planner can make use of statistics about individual columns when that metadata is available in the metastore database. This technique is most valuable for columns compared across tables in [join queries](#), to help estimate how many rows the query will retrieve from each table. These statistics are also important for correlated subqueries using the `EXISTS()` or `IN()` operators, which are processed internally the same way as join queries.

The following example shows column stats for an unpartitioned Parquet table. The values for the maximum and average sizes of some types are always available, because those figures are constant for numeric and other fixed-size types. Initially, the number of distinct values is not known, because it requires a potentially expensive scan through the entire table, and so that value is displayed as -1. The same applies to maximum and average sizes of variable-sized types, such as `STRING`. The `COMPUTE STATS` statement fills in most unknown column stats values. (It does not record the number of `NULL` values, because currently Impala does not use that figure for query optimization.)

```
show column stats parquet_snappy;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
id	BIGINT	-1	-1	8	8
val	INT	-1	-1	4	4
zerofill	STRING	-1	-1	-1	-1
name	STRING	-1	-1	-1	-1
assertion	BOOLEAN	-1	-1	1	1
location_id	SMALLINT	-1	-1	2	2

```
compute stats parquet_snappy;
```

```
| summary |
+-----+
| Updated 1 partition(s) and 6 column(s). |
+-----+
```

```
show column stats parquet_snappy;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
id	BIGINT	183861280	-1	8	8
val	INT	139017	-1	4	4

zerofill	STRING	101761	-1	6	6
name	STRING	145636240	-1	22	
13.00020027160645					
assertion	BOOLEAN	2	-1	1	1
location_id	SMALLINT	339	-1	2	2
+-----+-----+-----+-----+-----+					
+-----+					

Note:

For column statistics to be effective in Impala, you also need to have table statistics for the applicable tables, as described in [Overview of Table Statistics](#) on page 625. When you use the Impala `COMPUTE STATS` statement, both table and column statistics are automatically gathered at the same time, for all columns in the table.

Note: Prior to Impala 1.4.0, `COMPUTE STATS` counted the number of NULL values in each column and recorded that figure in the metastore database. Because Impala does not currently use the NULL count during query planning, Impala 1.4.0 and higher speeds up the `COMPUTE STATS` statement by skipping this NULL counting.

To check whether column statistics are available for a particular set of columns, use the `SHOW COLUMN STATS table_name` statement, or check the extended `EXPLAIN` output for a query against that table that refers to those columns. See [SHOW Statement](#) on page 395 and [EXPLAIN Statement](#) on page 291 for details.

If you run the Hive statement `ANALYZE TABLE COMPUTE STATISTICS FOR COLUMNS`, Impala can only use the resulting column statistics if the table is unpartitioned. Impala cannot use Hive-generated column statistics for a partitioned table.

How Table and Column Statistics Work for Partitioned Tables

When you use Impala for “big data”, you are highly likely to use partitioning for your biggest tables, the ones representing data that can be logically divided based on dates, geographic regions, or similar criteria. The table and column statistics are especially useful for optimizing queries on such tables. For example, a query involving one year might involve substantially more or less data than a query involving a different year, or a range of several years. Each query might be optimized differently as a result.

The following examples show how table and column stats work with a partitioned table. The table for this example is partitioned by year, month, and day. For simplicity, the sample data consists of 5 partitions, all from the same year and month. Table stats are collected independently for each partition. (In fact, the `SHOW PARTITIONS` statement displays exactly the same information as `SHOW TABLE STATS` for a partitioned table.) Column stats apply to the entire table, not to individual partitions. Because the partition key column values are represented as HDFS directories, their characteristics are typically known in advance, even when the values for non-key columns are shown as -1.

```
show partitions year_month_day;
+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+
| year | month | day | #Rows | #Files | Size | Bytes Cached | Cache
Replication | Format | Incremental stats | Location
+-----+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+-----+
| 2013 | 12 | 1 | -1 | 1 | 2.51MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| 2013 | 12 | 2 | -1 | 1 | 2.53MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
```

```

| 2013 | 12 | 3 | -1 | 1 | 2.52MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| 2013 | 12 | 4 | -1 | 1 | 2.51MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| 2013 | 12 | 5 | -1 | 1 | 2.52MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| Total | | | -1 | 5 | 12.58MB | 0B | |

```

```

+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+

```

```
show table stats year_month_day;
```

```

+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
| year | month | day | #Rows | #Files | Size | Bytes Cached | Cache
Replication | Format | Incremental stats | Location
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
| 2013 | 12 | 1 | -1 | 1 | 2.51MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| 2013 | 12 | 2 | -1 | 1 | 2.53MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| 2013 | 12 | 3 | -1 | 1 | 2.52MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| 2013 | 12 | 4 | -1 | 1 | 2.51MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| 2013 | 12 | 5 | -1 | 1 | 2.52MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | | |
parquet_snappy |
| Total | | | -1 | 5 | 12.58MB | 0B | |

```

```

+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+

```

```
show column stats year_month_day;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
id	INT	-1	-1	4	4
val	INT	-1	-1	4	4
zfill	STRING	-1	-1	-1	-1
name	STRING	-1	-1	-1	-1
assertion	BOOLEAN	-1	-1	1	1
year	INT	1	0	4	4
month	INT	1	0	4	4
day	INT	5	0	4	4

```
compute stats year_month_day;
```

```
+-----+-----+-----+-----+-----+-----+-----+
```

```

| summary |
+-----+
| Updated 5 partition(s) and 5 column(s). |
+-----+

show table stats year_month_day;
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| year | month | day | #Rows | #Files | Size | Bytes Cached | Cache
Replication | Format | Incremental stats | Location
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| 2013 | 12 | 1 | 93606 | 1 | 2.51MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | |
parquet_snappy |
| 2013 | 12 | 2 | 94158 | 1 | 2.53MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | |
parquet_snappy |
| 2013 | 12 | 3 | 94122 | 1 | 2.52MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | |
parquet_snappy |
| 2013 | 12 | 4 | 93559 | 1 | 2.51MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | |
parquet_snappy |
| 2013 | 12 | 5 | 93845 | 1 | 2.52MB | NOT CACHED | NOT
CACHED | PARQUET | false | | | | | |
parquet_snappy |
| Total | | | 469290 | 5 | 12.58MB | 0B | |
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+

show column stats year_month_day;
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| Column | Type | #Distinct Values | #Nulls | Max Size | Avg Size
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+
| id | INT | 511129 | -1 | 4 | 4
| val | INT | 364853 | -1 | 4 | 4
| zfill | STRING | 311430 | -1 | 6 | 6
| name | STRING | 471975 | -1 | 22 |
13.00160026550293 |
| assertion | BOOLEAN | 2 | -1 | 1 | 1
| year | INT | 1 | 0 | 4 | 4
| month | INT | 1 | 0 | 4 | 4
| day | INT | 5 | 0 | 4 | 4
+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+

```

If you run the Hive statement `ANALYZE TABLE COMPUTE STATISTICS FOR COLUMNS`, Impala can only use the resulting column statistics if the table is unpartitioned. Impala cannot use Hive-generated column statistics for a partitioned table.

Generating Table and Column Statistics

Use the `COMPUTE STATS` family of commands to collect table and column statistics. The `COMPUTE STATS` variants offer different tradeoffs between computation cost, staleness, and maintenance workflows which are explained below.

Important:

For a particular table, use either `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS`, but never combine the two or alternate between them. If you switch from `COMPUTE STATS` to `COMPUTE INCREMENTAL STATS` during the lifetime of a table, or vice versa, drop all statistics by running `DROP STATS` before making the switch.

COMPUTE STATS

The `COMPUTE STATS` command collects and sets the table-level and partition-level row counts as well as all column statistics for a given table. The collection process is CPU-intensive and can take a long time to complete for very large tables.

To speed up `COMPUTE STATS` consider the following options which can be combined.

- Limit the number of columns for which statistics are collected to increase the efficiency of `COMPUTE STATS`. Queries benefit from statistics for those columns involved in filters, join conditions, group by or partition by clauses. Other columns are good candidates to exclude from `COMPUTE STATS`. This feature is available since Impala 2.12.
- Set the `MT_DOP` query option to use more threads within each participating impalad to compute the statistics faster - but not more efficiently. Note that computing stats on a large table with a high `MT_DOP` value can negatively affect other queries running at the same time if the `COMPUTE STATS` claims most CPU cycles. This feature is available since Impala 2.8.
- Consider the experimental extrapolation and sampling features (see below) to further increase the efficiency of computing stats.

`COMPUTE STATS` is intended to be run periodically, e.g. weekly, or on-demand when the contents of a table have changed significantly. Due to the high resource utilization and long response time of `COMPUTE STATS`, it is most practical to run it in a scheduled maintenance window where the Impala cluster is idle enough to accommodate the expensive operation. The degree of change that qualifies as “significant” depends on the query workload, but typically, if 30% of the rows have changed then it is recommended to recompute statistics.

If you reload a complete new set of data for a table, but the number of rows and number of distinct values for each column is relatively unchanged from before, you do not need to recompute stats for the table.

Experimental: Extrapolation and Sampling

Impala 2.12 and higher includes two experimental features to alleviate common issues for computing and maintaining statistics on very large tables. The following shortcomings are improved upon:

- Newly added partitions do not have row count statistics. Table scans that only access those new partitions are treated as not having stats. Similarly, table scans that access both new and old partitions estimate the scan cardinality based on those old partitions that have stats, and the new partitions without stats are treated as having 0 rows.
- The row counts of existing partitions become stale when data is added or dropped.
- Computing stats for tables with a 100,000 or more partitions might fail or be very slow due to the high cost of updating the partition metadata in the Hive Metastore.
- With transient compute resources it is important to minimize the time from starting a new cluster to successfully running queries. Since the cluster might be relatively short-lived, users might prefer to quickly collect stats that are “good enough” as opposed to spending a lot of time and resources on computing full-fidelity stats.

For very large tables, it is often wasteful or impractical to run a full `COMPUTE STATS` to address the scenarios above on a frequent basis.

The sampling feature makes `COMPUTE STATS` more efficient by processing a fraction of the table data, and the extrapolation feature aims to reduce the frequency at which `COMPUTE STATS` needs to be re-run by estimating the row count of new and modified partitions.

The sampling and extrapolation features are disabled by default. They can be enabled globally or for specific tables, as follows. Set the `impalad` start-up configuration `--enable_stats_extrapolation` to enable the features globally. To enable them only for a specific table, set the `"impala.enable.stats.extrapolation"` table property to `"true"` for the desired table. The table-level property overrides the global setting, so it is also possible to enable sampling and extrapolation globally, but disable it for specific tables by setting the table property to `"false"`. Example: `ALTER TABLE mytable test_table SET TBLPROPERTIES("impala.enable.stats.extrapolation"="true")`

Note: Why are these features experimental? Due to their probabilistic nature it is possible that these features perform pathologically poorly on tables with extreme data/file/size distributions. Since it is not feasible for us to test all possible scenarios we only cautiously advertise these new capabilities. That said, the features have been thoroughly tested and are considered functionally stable. If you decide to give these features a try, please tell us about your experience at user@impala.apache.org! We rely on user feedback to guide future improvements in statistics collection.

Stats Extrapolation

The main idea of stats extrapolation is to estimate the row count of new and modified partitions based on the result of the last `COMPUTE STATS`. Enabling stats extrapolation changes the behavior of `COMPUTE STATS`, as well as the cardinality estimation of table scans. `COMPUTE STATS` no longer computes and stores per-partition row counts, and instead, only computes a table-level row count together with the total number of file bytes in the table at that time. No partition metadata is modified. The input cardinality of a table scan is estimated by converting the data volume of relevant partitions to a row count, based on the table-level row count and file bytes statistics. It is assumed that within the same table, different sets of files with the same data volume correspond to the similar number of rows on average. With extrapolation enabled, the scan cardinality estimation ignores per-partition row counts. It only relies on the table-level statistics and the scanned data volume.

The `SHOW TABLE STATS` and `EXPLAIN` commands distinguish between row counts stored in the Hive Metastore, and the row counts extrapolated based on the above process. Consult the `SHOW TABLE STATS` and `EXPLAIN` documentation for more details.

Sampling

A `TABLESAMPLE` clause may be added to `COMPUTE STATS` to limit the percentage of data to be processed. The final statistics are obtained by extrapolating the statistics from the data sample over the entire table. The extrapolated statistics are stored in the Hive Metastore, just as if no sampling was used. The following example runs `COMPUTE STATS` over a 10 percent data sample: `COMPUTE STATS test_table TABLESAMPLE SYSTEM(10)`

We have found that a 10 percent sampling rate typically offers a good tradeoff between statistics accuracy and execution cost. A sampling rate well below 10 percent has shown poor results and is not recommended.

Important: Sampling-based techniques sacrifice result accuracy for execution efficiency, so your mileage may vary for different tables and columns depending on their data distribution. The extrapolation procedure Impala uses for estimating the number of distinct values per column is inherently non-deterministic, so your results may even vary between runs of `COMPUTE STATS TABLESAMPLE`, even if no data has changed.

COMPUTE INCREMENTAL STATS

In Impala 2.1.0 and higher, you can use the `COMPUTE INCREMENTAL STATS` and `DROP INCREMENTAL STATS` commands. The `INCREMENTAL` clauses work with incremental statistics, a specialized feature for partitioned tables.

When you compute incremental statistics for a partitioned table, by default Impala only processes those partitions that do not yet have incremental statistics. By processing only newly added partitions, you can keep statistics up to date without incurring the overhead of reprocessing the entire table each time.

You can also compute or drop statistics for a specified subset of partitions by including a `PARTITION` clause in the `COMPUTE INCREMENTAL STATS` or `DROP INCREMENTAL STATS` statement.

Important:

In Impala 3.0 and lower, approximately 400 bytes of metadata per column per partition are needed for caching. Tables with a big number of partitions and many columns can add up to a significant memory overhead as the metadata must be cached on the `catalogd` host and on every `impalad` host that is eligible to be a coordinator. If this metadata for all tables exceeds 2 GB, you might experience service downtime. In Impala 3.1 and higher, the issue was alleviated with an improved handling of incremental stats.

When you run `COMPUTE INCREMENTAL STATS` on a table for the first time, the statistics are computed again from scratch regardless of whether the table already has statistics. Therefore, expect a one-time resource-intensive operation for scanning the entire table when running `COMPUTE INCREMENTAL STATS` for the first time on a given table.

The metadata for incremental statistics is handled differently from the original style of statistics:

- Issuing a `COMPUTE INCREMENTAL STATS` without a partition clause causes Impala to compute incremental stats for all partitions that do not already have incremental stats. This might be the entire table when running the command for the first time, but subsequent runs should only update new partitions. You can force updating a partition that already has incremental stats by issuing a `DROP INCREMENTAL STATS` before running `COMPUTE INCREMENTAL STATS`.
- The `SHOW TABLE STATS` and `SHOW PARTITIONS` statements now include an additional column showing whether incremental statistics are available for each column. A partition could already be covered by the original type of statistics based on a prior `COMPUTE STATS` statement, as indicated by a value other than `-1` under the `#Rows` column. Impala query planning uses either kind of statistics when available.
- `COMPUTE INCREMENTAL STATS` takes more time than `COMPUTE STATS` for the same volume of data. Therefore it is most suitable for tables with large data volume where new partitions are added frequently, making it impractical to run a full `COMPUTE STATS` operation for each new partition. For unpartitioned tables, or partitioned tables that are loaded once and not updated with new partitions, use the original `COMPUTE STATS` syntax.
- `COMPUTE INCREMENTAL STATS` uses some memory in the `catalogd` process, proportional to the number of partitions and number of columns in the applicable table. The memory overhead is approximately 400 bytes for each column in each partition. This memory is reserved in the `catalogd` daemon, the `statestored` daemon, and in each instance of the `impalad` daemon.
- In cases where new files are added to an existing partition, issue a `REFRESH` statement for the table, followed by a `DROP INCREMENTAL STATS` and `COMPUTE INCREMENTAL STATS` sequence for the changed partition.
- The `DROP INCREMENTAL STATS` statement operates only on a single partition at a time. To remove statistics (whether incremental or not) from all partitions of a table, issue a `DROP STATS` statement with no `INCREMENTAL` or `PARTITION` clauses.

The following considerations apply to incremental statistics when the structure of an existing table is changed (known as *schema evolution*):

- If you use an `ALTER TABLE` statement to drop a column, the existing statistics remain valid and `COMPUTE INCREMENTAL STATS` does not rescan any partitions.
- If you use an `ALTER TABLE` statement to add a column, Impala rescans all partitions and fills in the appropriate column-level values the next time you run `COMPUTE INCREMENTAL STATS`.
- If you use an `ALTER TABLE` statement to change the data type of a column, Impala rescans all partitions and fills in the appropriate column-level values the next time you run `COMPUTE INCREMENTAL STATS`.
- If you use an `ALTER TABLE` statement to change the file format of a table, the existing statistics remain valid and a subsequent `COMPUTE INCREMENTAL STATS` does not rescan any partitions.

See [COMPUTE STATS Statement](#) on page 232 and [DROP STATS Statement](#) on page 284 for syntax details.

Maximum Serialized Stats Size

In Impala 3.0 and lower, when executing `COMPUTE INCREMENTAL STATS` on very large tables, use the configuration setting `--inc_stats_size_limit_bytes` to prevent Impala from running out of memory while updating table metadata. If this limit is reached, Impala will stop loading the table and return an error. The error serves as an indication that `COMPUTE INCREMENTAL STATS` should not be used on the particular table. Consider spitting the table and using regular `COMPUTE STATS` if possible.

The `--inc_stats_size_limit_bytes` limit is set as a safety check, to prevent Impala from hitting the maximum limit for the table metadata. Note that this limit is only one part of the entire table's metadata all of which together must be below 2 GB.

The default value for `--inc_stats_size_limit_bytes` is 209715200, 200 MB.

To change the `--inc_stats_size_limit_bytes` value, restart `impalad` and `catalogd` with the new value specified in bytes, for example, 1048576000 for 1 GB. See [Modifying Impala Startup Options](#) on page 32 for the steps to change the option and restart Impala daemons.



Attention: The `--inc_stats_size_limit_bytes` setting should be increased with care. A big value for the setting, such as 1 GB or more, can result in a spike in heap usage as well as a crash of Impala.

In Impala 3.1 and higher, Impala improved how metadata is updated when executing `COMPUTE INCREMENTAL STATS`, significantly reducing the need for `--inc_stats_size_limit_bytes`.

Detecting Missing Statistics

You can check whether a specific table has statistics using the `SHOW TABLE STATS` statement (for any table) or the `SHOW PARTITIONS` statement (for a partitioned table). Both statements display the same information. If a table or a partition does not have any statistics, the `#Rows` field contains `-1`. Once you compute statistics for the table or partition, the `#Rows` field changes to an accurate value.

The following example shows a table that initially does not have any statistics. The `SHOW TABLE STATS` statement displays different values for `#Rows` before and after the `COMPUTE STATS` operation.

```
[localhost:21000] > create table no_stats (x int);
[localhost:21000] > show table stats no_stats;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| -1    | 0      | 0B   | NOT CACHED   | TEXT  | false             |
+-----+-----+-----+-----+-----+-----+
[localhost:21000] > compute stats no_stats;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 1 column(s). |
+-----+
[localhost:21000] > show table stats no_stats;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| 0     | 0      | 0B   | NOT CACHED   | TEXT  | false             |
+-----+-----+-----+-----+-----+-----+
```

The following example shows a similar progression with a partitioned table. Initially, `#Rows` is `-1`. After a `COMPUTE STATS` operation, `#Rows` changes to an accurate value. Any newly added partition starts with no statistics, meaning that you must collect statistics after adding a new partition.

```
[localhost:21000] > create table no_stats_partitioned (x int) partitioned by
  (year smallint);
[localhost:21000] > show table stats no_stats_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+
| year  | #Rows | #Files | Size | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+-----+
+
| Total | -1    | 0      | 0B   | 0B           |       |                   |
+-----+-----+-----+-----+-----+-----+-----+
```

```

+-----+-----+-----+-----+-----+-----+-----+
+
[localhost:21000] > show partitions no_stats_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+
| year  | #Rows | #Files | Size | Bytes Cached | Format | Incremental stats
|
+-----+-----+-----+-----+-----+-----+-----+
+
| Total | -1    | 0      | 0B   | 0B           |       |
|
+-----+-----+-----+-----+-----+-----+-----+
+
[localhost:21000] > alter table no_stats_partitioned add partition
  (year=2013);
[localhost:21000] > compute stats no_stats_partitioned;
+-----+-----+
| summary                                     |
+-----+-----+
| Updated 1 partition(s) and 1 column(s). |
+-----+-----+
[localhost:21000] > alter table no_stats_partitioned add partition
  (year=2014);
[localhost:21000] > show partitions no_stats_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+
| year  | #Rows | #Files | Size | Bytes Cached | Format | Incremental stats
|
+-----+-----+-----+-----+-----+-----+-----+
+
| 2013  | 0     | 0      | 0B   | NOT CACHED   | TEXT  | false
|
| 2014  | -1    | 0      | 0B   | NOT CACHED   | TEXT  | false
|
| Total | 0     | 0      | 0B   | 0B           |       |
|
+-----+-----+-----+-----+-----+-----+-----+
+

```

Note: Because the default `COMPUTE STATS` statement creates and updates statistics for all partitions in a table, if you expect to frequently add new partitions, use the `COMPUTE INCREMENTAL STATS` syntax instead, which lets you compute stats for a single specified partition, or only for those partitions that do not already have incremental stats.

If checking each individual table is impractical, due to a large number of tables or views that hide the underlying base tables, you can also check for missing statistics for a particular query. Use the `EXPLAIN` statement to preview query efficiency before actually running the query. Use the query profile output available through the `PROFILE` command in `impala-shell` or the web UI to verify query execution and timing after running the query. Both the `EXPLAIN` plan and the `PROFILE` output display a warning if any tables or partitions involved in the query do not have statistics.

```

[localhost:21000] > create table no_stats (x int);
[localhost:21000] > explain select count(*) from no_stats;
+-----+
+
| Explain String
|
+-----+
+
| Estimated Per-Host Requirements: Memory=10.00MB VCores=1
|

```

```

| WARNING: The following tables are missing relevant table and/or column
| statistics. |
| incremental_stats.no_stats
|
|
| 03:AGGREGATE [FINALIZE]
| | output: count:merge(*)
| |
| 02:EXCHANGE [UNPARTITIONED]
| |
| 01:AGGREGATE
| | output: count(*)
| |
| 00:SCAN HDFS [incremental_stats.no_stats]
| partitions=1/1 files=0 size=0B
|
+-----+
+

```

Because Impala uses the *partition pruning* technique when possible to only evaluate certain partitions, if you have a partitioned table with statistics for some partitions and not others, whether or not the EXPLAIN statement shows the warning depends on the actual partitions used by the query. For example, you might see warnings or not for different queries against the same table:

```

-- No warning because all the partitions for the year 2012 have stats.
EXPLAIN SELECT ... FROM t1 WHERE year = 2012;

-- Missing stats warning because one or more partitions in this range
-- do not have stats.
EXPLAIN SELECT ... FROM t1 WHERE year BETWEEN 2006 AND 2009;

```

To confirm if any partitions at all in the table are missing statistics, you might explain a query that scans the entire table, such as `SELECT COUNT(*) FROM table_name`.

Manually Setting Table and Column Statistics with ALTER TABLE

Setting Table Statistics

The most crucial piece of data in all the statistics is the number of rows in the table (for an unpartitioned or partitioned table) and for each partition (for a partitioned table). The `COMPUTE STATS` statement always gathers statistics about all columns, as well as overall table statistics. If it is not practical to do a full `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` operation after adding a partition or inserting data, or if you can see that Impala would produce a more efficient plan if the number of rows was different, you can manually set the number of rows through an `ALTER TABLE` statement:

```

-- Set total number of rows. Applies to both unpartitioned and partitioned
-- tables.
alter table table_name set tblproperties('numRows'='new_value',
    'STATS_GENERATED_VIA_STATS_TASK'='true');

```

```
-- Set total number of rows for a specific partition. Applies to partitioned
-- tables only.
-- You must specify all the partition key columns in the PARTITION clause.
alter table table_name partition (keycol1=val1,keycol2=val2...) set
tblproperties('numRows'='new_value',
'STATS_GENERATED_VIA_STATS_TASK'='true');
```

This statement avoids re-scanning any data files. (The requirement to include the `STATS_GENERATED_VIA_STATS_TASK` property is relatively new, as a result of the issue [HIVE-8648](#) for the Hive metastore.)

```
create table analysis_data stored as parquet as select * from raw_data;
Inserted 1000000000 rows in 181.98s
compute stats analysis_data;
insert into analysis_data select * from smaller_table_we_forgot_before;
Inserted 1000000 rows in 15.32s
-- Now there are 1001000000 rows. We can update this single data point in
-- the stats.
alter table analysis_data set tblproperties('numRows'='1001000000',
'STATS_GENERATED_VIA_STATS_TASK'='true');
```

For a partitioned table, update both the per-partition number of rows and the number of rows for the whole table:

```
-- If the table originally contained 1 million rows, and we add another
-- partition with 30 thousand rows,
-- change the numRows property for the partition and the overall table.
alter table partitioned_data partition(year=2009, month=4) set tblproperties
('numRows'='30000', 'STATS_GENERATED_VIA_STATS_TASK'='true');
alter table partitioned_data set tblproperties ('numRows'='1030000',
'STATS_GENERATED_VIA_STATS_TASK'='true');
```

In practice, the `COMPUTE STATS` statement, or `COMPUTE INCREMENTAL STATS` for a partitioned table, should be fast and convenient enough that this technique is only useful for the very largest partitioned tables. Because the column statistics might be left in a stale state, do not use this technique as a replacement for `COMPUTE STATS`. Only use this technique if all other means of collecting statistics are impractical, or as a low-overhead operation that you run in between periodic `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` operations.

Setting Column Statistics

In Impala 2.6 and higher, you can also use the `SET COLUMN STATS` clause of `ALTER TABLE` to manually set or change column statistics. Only use this technique in cases where it is impractical to run `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` frequently enough to keep up with data changes for a huge table.

You specify a case-insensitive symbolic name for the kind of statistics: `numDVs`, `numNulls`, `avgSize`, `maxSize`. The key names and values are both quoted. This operation applies to an entire table, not a specific partition. For example:

```
create table t1 (x int, s string);
insert into t1 values (1, 'one'), (2, 'two'), (2, 'deux');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
x	INT	-1	-1	4	4
s	STRING	-1	-1	-1	-1

```
alter table t1 set column stats x ('numDVs'='2','numNulls'='0');
alter table t1 set column stats s ('numdvs'='3','maxsize'='4');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
--------	------	------------------	--------	----------	----------

x	INT	2	0	4	4
s	STRING	3	-1	4	-1

Examples of Using Table and Column Statistics with Impala

The following examples walk through a sequence of `SHOW TABLE STATS`, `SHOW COLUMN STATS`, `ALTER TABLE`, and `SELECT` and `INSERT` statements to illustrate various aspects of how Impala uses statistics to help optimize queries.

This example shows table and column statistics for the `STORE` column used in the [TPC-DS benchmarks for decision support](#) systems. It is a tiny table holding data for 12 stores. Initially, before any statistics are gathered by a `COMPUTE STATS` statement, most of the numeric fields show placeholder values of -1, indicating that the figures are unknown. The figures that are filled in are values that are easily countable or deducible at the physical level, such as the number of files, total data size of the files, and the maximum and average sizes for data types that have a constant size such as `INT`, `FLOAT`, and `TIMESTAMP`.

```
[localhost:21000] > show table stats store;
```

#Rows	#Files	Size	Format
-1	1	3.08KB	TEXT

Returned 1 row(s) in 0.03s

```
[localhost:21000] > show column stats store;
```

Column Avg Size	Type	#Distinct Values	#Nulls	Max Size
s_store_sk	INT	-1	-1	4
s_store_id	STRING	-1	-1	-1
s_rec_start_date	TIMESTAMP	-1	-1	16
s_rec_end_date	TIMESTAMP	-1	-1	16
s_closed_date_sk	INT	-1	-1	4
s_store_name	STRING	-1	-1	-1
s_number_employees	INT	-1	-1	4
s_floor_space	INT	-1	-1	4
s_hours	STRING	-1	-1	-1
s_manager	STRING	-1	-1	-1
s_market_id	INT	-1	-1	4
s_geography_class	STRING	-1	-1	-1
s_market_desc	STRING	-1	-1	-1
s_market_manager	STRING	-1	-1	-1
s_division_id	INT	-1	-1	4

s_division_name	STRING	-1	-1	-1	-1
s_company_id	INT	-1	-1	4	4
s_company_name	STRING	-1	-1	-1	-1
s_street_number	STRING	-1	-1	-1	-1
s_street_name	STRING	-1	-1	-1	-1
s_street_type	STRING	-1	-1	-1	-1
s_suite_number	STRING	-1	-1	-1	-1
s_city	STRING	-1	-1	-1	-1
s_county	STRING	-1	-1	-1	-1
s_state	STRING	-1	-1	-1	-1
s_zip	STRING	-1	-1	-1	-1
s_country	STRING	-1	-1	-1	-1
s_gmt_offset	FLOAT	-1	-1	4	4
s_tax_percentage	FLOAT	-1	-1	4	4

```

+-----+-----+-----+-----+-----+
+-----+
Returned 29 row(s) in 0.04s

```

With the Hive `ANALYZE TABLE` statement for column statistics, you had to specify each column for which to gather statistics. The Impala `COMPUTE STATS` statement automatically gathers statistics for all columns, because it reads through the entire table relatively quickly and can efficiently compute the values for all the columns. This example shows how after running the `COMPUTE STATS` statement, statistics are filled in for both the table and all its columns:

```

[localhost:21000] > compute stats store;
+-----+-----+
| summary |
+-----+-----+
| Updated 1 partition(s) and 29 column(s). |
+-----+-----+
Returned 1 row(s) in 1.88s
[localhost:21000] > show table stats store;
+-----+-----+-----+-----+
| #Rows | #Files | Size   | Format |
+-----+-----+-----+-----+
| 12    | 1      | 3.08KB | TEXT   |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.02s
[localhost:21000] > show column stats store;
+-----+-----+-----+-----+-----+-----+
| Column           | Type      | #Distinct Values | #Nulls | Max Size |
| Avg Size        |           |                  |        |          |
+-----+-----+-----+-----+-----+-----+
+-----+
| s_store_sk       | INT       | 12               | -1     | 4        | 4
+-----+
| s_store_id       | STRING    | 6                | -1     | 16       | 16
+-----+

```

s_rec_start_date		TIMESTAMP		4		-1		16		16
s_rec_end_date		TIMESTAMP		3		-1		16		16
s_closed_date_sk		INT		3		-1		4		4
s_store_name		STRING		8		-1		5		
4.25										
s_number_employees		INT		9		-1		4		4
s_floor_space		INT		10		-1		4		4
s_hours		STRING		2		-1		8		
7.083300113677979										
s_manager		STRING		7		-1		15		12
s_market_id		INT		7		-1		4		4
s_geography_class		STRING		1		-1		7		7
s_market_desc		STRING		10		-1		94		
55.5										
s_market_manager		STRING		7		-1		16		14
s_division_id		INT		1		-1		4		4
s_division_name		STRING		1		-1		7		7
s_company_id		INT		1		-1		4		4
s_company_name		STRING		1		-1		7		7
s_street_number		STRING		9		-1		3		
2.833300113677979										
s_street_name		STRING		12		-1		11		
6.583300113677979										
s_street_type		STRING		8		-1		9		
4.833300113677979										
s_suite_number		STRING		11		-1		9		
8.25										
s_city		STRING		2		-1		8		
6.5										
s_county		STRING		1		-1		17		17
s_state		STRING		1		-1		2		2
s_zip		STRING		2		-1		5		5
s_country		STRING		1		-1		13		13
s_gmt_offset		FLOAT		1		-1		4		4
s_tax_percentage		FLOAT		5		-1		4		4
+-----+-----+-----+-----+-----+										
+-----+										
Returned 29 row(s) in 0.04s										

The following example shows how statistics are represented for a partitioned table. In this case, we have set up a table to hold the world's most trivial census data, a single STRING field, partitioned by a YEAR column. The table statistics include a separate entry for each partition, plus final totals for the numeric fields. The column statistics include some

easily deducible facts for the partitioning column, such as the number of distinct values (the number of partition subdirectories).

```
localhost:21000] > describe census;
+-----+-----+
| name | type | comment |
+-----+-----+
| name | string |
| year | smallint |
+-----+-----+
Returned 2 row(s) in 0.02s
```

```
[localhost:21000] > show table stats census;
```

year	#Rows	#Files	Size	Format
2000	-1	0	0B	TEXT
2004	-1	0	0B	TEXT
2008	-1	0	0B	TEXT
2010	-1	0	0B	TEXT
2011	0	1	22B	TEXT
2012	-1	1	22B	TEXT
2013	-1	1	231B	PARQUET
Total	0	3	275B	

```
Returned 8 row(s) in 0.02s
```

```
[localhost:21000] > show column stats census;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
name	STRING	-1	-1	-1	-1
year	SMALLINT	7	-1	2	2

```
Returned 2 row(s) in 0.02s
```

The following example shows how the statistics are filled in by a `COMPUTE STATS` statement in Impala.

```
[localhost:21000] > compute stats census;
```

```
+-----+
| summary |
+-----+
| Updated 3 partition(s) and 1 column(s). |
+-----+
```

```
Returned 1 row(s) in 2.16s
```

```
[localhost:21000] > show table stats census;
```

year	#Rows	#Files	Size	Format
2000	-1	0	0B	TEXT
2004	-1	0	0B	TEXT
2008	-1	0	0B	TEXT
2010	-1	0	0B	TEXT
2011	4	1	22B	TEXT
2012	4	1	22B	TEXT
2013	1	1	231B	PARQUET
Total	9	3	275B	

```
Returned 8 row(s) in 0.02s
```

```
[localhost:21000] > show column stats census;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
name	STRING	4	-1	5	4.5
year	SMALLINT	7	-1	2	2


```
+-----+-----+-----+-----+-----+
Returned 2 row(s) in 0.02s
```

For examples showing how some queries work differently when statistics are available, see [Examples of Join Order Optimization](#) on page 619. You can see how Impala executes a query differently in each case by observing the EXPLAIN output before and after collecting statistics. Measure the before and after query times, and examine the throughput numbers in before and after SUMMARY or PROFILE output, to verify how much the improved plan speeds up performance.

Benchmarking Impala Queries

Because Impala, like other Hadoop components, is designed to handle large data volumes in a distributed environment, conduct any performance tests using realistic data and cluster configurations. Use a multi-node cluster rather than a single node; run queries against tables containing terabytes of data rather than tens of gigabytes. The parallel processing techniques used by Impala are most appropriate for workloads that are beyond the capacity of a single server.

When you run queries returning large numbers of rows, the CPU time to pretty-print the output can be substantial, giving an inaccurate measurement of the actual query time. Consider using the `-B` option on the `impala-shell` command to turn off the pretty-printing, and optionally the `-o` option to store query results in a file rather than printing to the screen. See [impala-shell Configuration Options](#) on page 791 for details.

Controlling Impala Resource Usage

Sometimes, balancing raw query performance against scalability requires limiting the amount of resources, such as memory or CPU, used by a single query or group of queries. Impala can use several mechanisms that help to smooth out the load during heavy concurrent usage, resulting in faster overall query times and sharing of resources across Impala queries, MapReduce jobs, and other kinds of workloads across a cluster:

- The Impala admission control feature uses a fast, distributed mechanism to hold back queries that exceed limits on the number of concurrent queries or the amount of memory used. The queries are queued, and executed as other queries finish and resources become available. You can control the concurrency limits, and specify different limits for different groups of users to divide cluster resources according to the priorities of different classes of users. This feature is new in Impala 1.3. See [Admission Control and Query Queuing](#) on page 675 for details.
- You can restrict the amount of memory Impala reserves during query execution by specifying the `-mem_limit` option for the `impalad` daemon. See [Modifying Impala Startup Options](#) on page 32 for details. This limit applies only to the memory that is directly consumed by queries; Impala reserves additional memory at startup, for example to hold cached metadata.
- For production deployments, implement resource isolation using your cluster management tool.

Runtime Filtering for Impala Queries (Impala 2.5 or higher only)

Runtime filtering is a wide-ranging optimization feature available in Impala 2.5 and higher. When only a fraction of the data in a table is needed for a query against a partitioned table or to evaluate a join condition, Impala determines the appropriate conditions while the query is running, and broadcasts that information to all the `impalad` nodes that are reading the table so that they can avoid unnecessary I/O to read partition data, and avoid unnecessary network transmission by sending only the subset of rows that match the join keys across the network.

This feature is primarily used to optimize queries against large partitioned tables (under the name *dynamic partition pruning*) and joins of large tables. The information in this section includes concepts, internals, and troubleshooting information for the entire runtime filtering feature. For specific tuning steps for partitioned tables, see [Dynamic Partition Pruning](#) on page 689.

Important:

When this feature made its debut in Impala 2.5, the default setting was `RUNTIME_FILTER_MODE=LOCAL`. Now the default is `RUNTIME_FILTER_MODE=GLOBAL` in Impala 2.6 and higher, which enables more wide-ranging and ambitious query optimization without requiring you to explicitly set any query options.

Background Information for Runtime Filtering

To understand how runtime filtering works at a detailed level, you must be familiar with some terminology from the field of distributed database technology:

- What a *plan fragment* is. Impala decomposes each query into smaller units of work that are distributed across the cluster. Wherever possible, a data block is read, filtered, and aggregated by plan fragments executing on the same host. For some operations, such as joins and combining intermediate results into a final result set, data is transmitted across the network from one Impala daemon to another.
- What `SCAN` and `HASH JOIN` plan nodes are, and their role in computing query results:

In the Impala query plan, a *scan node* performs the I/O to read from the underlying data files. Although this is an expensive operation from the traditional database perspective, Hadoop clusters and Impala are optimized to do this kind of I/O in a highly parallel fashion. The major potential cost savings come from using the columnar Parquet format (where Impala can avoid reading data for unneeded columns) and partitioned tables (where Impala can avoid reading data for unneeded partitions).

Most Impala joins use the *hash join* mechanism. (It is only fairly recently that Impala started using the nested-loop join technique, for certain kinds of non-equi-join queries.) In a hash join, when evaluating join conditions from two tables, Impala constructs a hash table in memory with all the different column values from the table on one side of the join. Then, for each row from the table on the other side of the join, Impala tests whether the relevant column values are in this hash table or not.

A *hash join node* constructs such an in-memory hash table, then performs the comparisons to identify which rows match the relevant join conditions and should be included in the result set (or at least sent on to the subsequent intermediate stage of query processing). Because some of the input for a hash join might be transmitted across the network from another host, it is especially important from a performance perspective to prune out ahead of time any data that is known to be irrelevant.

The more distinct values are in the columns used as join keys, the larger the in-memory hash table and thus the more memory required to process the query.

- The difference between a *broadcast join* and a *shuffle join*. (The Hadoop notion of a shuffle join is sometimes referred to in Impala as a *partitioned join*.) In a broadcast join, the table from one side of the join (typically the smaller table) is sent in its entirety to all the hosts involved in the query. Then each host can compare its portion of the data from the other (larger) table against the full set of possible join keys. In a shuffle join, there is no obvious “smaller” table, and so the contents of both tables are divided up, and corresponding portions of the data are transmitted to each host involved in the query. See *Optimizer Hints* on page 422 for information about how these different kinds of joins are processed.
- The notion of the build phase and probe phase when Impala processes a join query. The *build phase* is where the rows containing the join key columns, typically for the smaller table, are transmitted across the network and built into an in-memory hash table data structure on one or more destination nodes. The *probe phase* is where data is read locally (typically from the larger table) and the join key columns are compared to the values in the in-memory hash table. The corresponding input sources (tables, subqueries, and so on) for these phases are referred to as the *build side* and the *probe side*.
- How to set Impala query options: interactively within an `impala-shell` session through the `SET` command, for a JDBC or ODBC application through the `SET` statement, or globally for all `impalad` daemons through the `default_query_options` configuration setting.

Runtime Filtering Internals

The *filter* that is transmitted between plan fragments is essentially a list of values for join key columns. When this list of values is transmitted in time to a scan node, Impala can filter out non-matching values immediately after reading them, rather than transmitting the raw data to another host to compare against the in-memory hash table on that host.

For HDFS-based tables, this data structure is implemented as a *Bloom filter*, which uses a probability-based algorithm to determine all possible matching values. (The probability-based aspects means that the filter might include some non-matching values, but if so, that does not cause any inaccuracy in the final results.)

Another kind of filter is the “min-max” filter. It currently only applies to Kudu tables. The filter is a data structure representing a minimum and maximum value. These filters are passed to Kudu to reduce the number of rows returned to Impala when scanning the probe side of the join.

There are different kinds of filters to match the different kinds of joins (partitioned and broadcast). A broadcast filter reflects the complete list of relevant values and can be immediately evaluated by a scan node. A partitioned filter reflects only the values processed by one host in the cluster; all the partitioned filters must be combined into one (by the coordinator node) before the scan nodes can use the results to accurately filter the data as it is read from storage.

Broadcast filters are also classified as local or global. With a local broadcast filter, the information in the filter is used by a subsequent query fragment that is running on the same host that produced the filter. A non-local broadcast filter must be transmitted across the network to a query fragment that is running on a different host. Impala designates 3 hosts to each produce non-local broadcast filters, to guard against the possibility of a single slow host taking too long. Depending on the setting of the `RUNTIME_FILTER_MODE` query option (LOCAL or GLOBAL), Impala either uses a conservative optimization strategy where filters are only consumed on the same host that produced them, or a more aggressive strategy where filters are eligible to be transmitted across the network.

Note: In Impala 2.6 and higher, the default for runtime filtering is the GLOBAL setting.

File Format Considerations for Runtime Filtering

Parquet tables get the most benefit from the runtime filtering optimizations. Runtime filtering can speed up join queries against partitioned or unpartitioned Parquet tables, and single-table queries against partitioned Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 705 for information about using Parquet tables with Impala.

For other file formats (text, Avro, RCFile, and SequenceFile), runtime filtering speeds up queries against partitioned tables only. Because partitioned tables can use a mixture of formats, Impala produces the filters in all cases, even if they are not ultimately used to optimize the query.

Wait Intervals for Runtime Filters

Because it takes time to produce runtime filters, especially for partitioned filters that must be combined by the coordinator node, there is a time interval above which it is more efficient for the scan nodes to go ahead and construct their intermediate result sets, even if that intermediate data is larger than optimal. If it only takes a few seconds to produce the filters, it is worth the extra time if pruning the unnecessary data can save minutes in the overall query time. You can specify the maximum wait time in milliseconds using the `RUNTIME_FILTER_WAIT_TIME_MS` query option.

By default, each scan node waits for up to 1 second (1000 milliseconds) for filters to arrive. If all filters have not arrived within the specified interval, the scan node proceeds, using whatever filters did arrive to help avoid reading unnecessary data. If a filter arrives after the scan node begins reading data, the scan node applies that filter to the data that is read after the filter arrives, but not to the data that was already read.

If the cluster is relatively busy and your workload contains many resource-intensive or long-running queries, consider increasing the wait time so that complicated queries do not miss opportunities for optimization. If the cluster is lightly loaded and your workload contains many small queries taking only a few seconds, consider decreasing the wait time to avoid the 1 second delay for each query.

Query Options for Runtime Filtering

See the following sections for information about the query options that control runtime filtering:

- The first query option adjusts the “sensitivity” of this feature. By default, it is set to the highest level (GLOBAL). (This default applies to Impala 2.6 and higher. In previous releases, the default was LOCAL.)
 - [RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389

- The other query options are tuning knobs that you typically only adjust after doing performance testing, and that you might want to change only for the duration of a single expensive query:
 - [MAX_NUM_RUNTIME_FILTERS Query Option \(Impala 2.5 or higher only\)](#) on page 361
 - [DISABLE_ROW_RUNTIME_FILTERING Query Option \(Impala 2.5 or higher only\)](#) on page 354
 - [RUNTIME_FILTER_MAX_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388
 - [RUNTIME_FILTER_MIN_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388
 - [RUNTIME_BLOOM_FILTER_SIZE Query Option \(Impala 2.5 or higher only\)](#) on page 387; in Impala 2.6 and higher, this setting acts as a fallback when statistics are not available, rather than as a directive.

Runtime Filtering and Query Plans

In the same way the query plan displayed by the EXPLAIN statement includes information about predicates used by each plan fragment, it also includes annotations showing whether a plan fragment produces or consumes a runtime filter. A plan fragment that produces a filter includes an annotation such as `runtime filters: filter_id <- table.column`, while a plan fragment that consumes a filter includes an annotation such as `runtime filters: filter_id -> table.column`. Setting the query option `EXPLAIN_LEVEL=2` adds additional annotations showing the type of the filter, either `filter_id[bloom]` (for HDFS-based tables) or `filter_id[min_max]` (for Kudu tables).

The following example shows a query that uses a single runtime filter, labeled RF000, to prune the partitions based on evaluating the result set of a subquery at runtime:

```
CREATE TABLE yy (s STRING) PARTITIONED BY (year INT);
INSERT INTO yy PARTITION (year) VALUES ('1999', 1999), ('2000', 2000),
  ('2001', 2001), ('2010', 2010), ('2018', 2018);
COMPUTE STATS yy;

CREATE TABLE yy2 (s STRING, year INT);
INSERT INTO yy2 VALUES ('1999', 1999), ('2000', 2000), ('2001', 2001);
COMPUTE STATS yy2;

-- The following query reads an unknown number of partitions, whose key
-- values
-- are only known at run time. The runtime filters line shows the
-- information used in query fragment 02 to decide which partitions to skip.

EXPLAIN SELECT s FROM yy WHERE year IN (SELECT year FROM yy2);
+-----+
| PLAN-ROOT SINK |
| 04:EXCHANGE [UNPARTITIONED] |
| 02:HASH JOIN [LEFT SEMI JOIN, BROADCAST] |
|   hash predicates: year = year |
|   runtime filters: RF000 <- year |
| --03:EXCHANGE [BROADCAST] |
|   |
|   01:SCAN HDFS [default.yy2] |
|     partitions=1/1 files=1 size=620B |
| 00:SCAN HDFS [default.yy] |
|   partitions=5/5 files=5 size=1.71KB |
|   runtime filters: RF000 -> year |
+-----+

SELECT s FROM yy WHERE year IN (SELECT year FROM yy2); -- Returns 3 rows
from yy
PROFILE;
```

The query profile (displayed by the `PROFILE` command in `impala-shell`) contains both the `EXPLAIN` plan and more detailed information about the internal workings of the query. The profile output includes the `Filter routing table` section with information about each filter based on its ID.

Examples of Queries that Benefit from Runtime Filtering

In this example, Impala would normally do extra work to interpret the columns `C1`, `C2`, `C3`, and `ID` for each row in `HUGE_T1`, before checking the `ID` value against the in-memory hash table constructed from all the `TINY_T2.ID` values. By producing a filter containing all the `TINY_T2.ID` values even before the query starts scanning the `HUGE_T1` table, Impala can skip the unnecessary work to parse the column info as soon as it determines that an `ID` value does not match any of the values from the other table.

The example shows `COMPUTE STATS` statements for both the tables (even though that is a one-time operation after loading data into those tables) because Impala relies on up-to-date statistics to determine which one has more distinct `ID` values than the other. That information lets Impala make effective decisions about which table to use to construct the in-memory hash table, and which table to read from disk and compare against the entries in the hash table.

```
COMPUTE STATS huge_t1;
COMPUTE STATS tiny_t2;
SELECT c1, c2, c3 FROM huge_t1 JOIN tiny_t2 WHERE huge_t1.id = tiny_t2.id;
```

In this example, `T1` is a table partitioned by year. The subquery on `T2` produces multiple values, and transmits those values as a filter to the plan fragments that are reading from `T1`. Any non-matching partitions in `T1` are skipped.

```
select c1 from t1 where year in (select distinct year from t2);
```

Now the `WHERE` clause contains an additional test that does not apply to the partition key column. A filter on a column that is not a partition key is called a per-row filter. Because per-row filters only apply for Parquet, `T1` must be a Parquet table.

The subqueries result in two filters being transmitted to the scan nodes that read from `T1`. The filter on `YEAR` helps the query eliminate entire partitions based on non-matching years. The filter on `C2` lets Impala discard rows with non-matching `C2` values immediately after reading them. Without runtime filtering, Impala would have to keep the non-matching values in memory, assemble `C1`, `C2`, and `C3` into rows in the intermediate result set, and transmit all the intermediate rows back to the coordinator node, where they would be eliminated only at the very end of the query.

```
select c1, c2, c3 from t1
  where year in (select distinct year from t2)
     and c2 in (select other_column from t3);
```

This example involves a broadcast join. The fact that the `ON` clause would return a small number of matching rows (because there are not very many rows in `TINY_T2`) means that the corresponding filter is very selective. Therefore, runtime filtering will probably be effective in optimizing this query.

```
select c1 from huge_t1 join [broadcast] tiny_t2
  on huge_t1.id = tiny_t2.id
 where huge_t1.year in (select distinct year from tiny_t2)
     and c2 in (select other_column from t3);
```

This example involves a shuffle or partitioned join. Assume that most rows in `HUGE_T1` have a corresponding row in `HUGE_T2`. The fact that the `ON` clause could return a large number of matching rows means that the corresponding filter would not be very selective. Therefore, runtime filtering might be less effective in optimizing this query.

```
select c1 from huge_t1 join [shuffle] huge_t2
```

```
on huge_t1.id = huge_t2.id
where huge_t1.year in (select distinct year from huge_t2)
and c2 in (select other_column from t3);
```

Tuning and Troubleshooting Queries that Use Runtime Filtering

These tuning and troubleshooting procedures apply to queries that are resource-intensive enough, long-running enough, and frequent enough that you can devote special attention to optimizing them individually.

Use the `EXPLAIN` statement and examine the `runtime_filters:` lines to determine whether runtime filters are being applied to the `WHERE` predicates and join clauses that you expect. For example, runtime filtering does not apply to queries that use the nested loop join mechanism due to non-equijoin operators.

Make sure statistics are up-to-date for all tables involved in the queries. Use the `COMPUTE STATS` statement after loading data into non-partitioned tables, and `COMPUTE INCREMENTAL STATS` after adding new partitions to partitioned tables.

If join queries involving large tables use unique columns as the join keys, for example joining a primary key column with a foreign key column, the overhead of producing and transmitting the filter might outweigh the performance benefit because not much data could be pruned during the early stages of the query. For such queries, consider setting the query option `RUNTIME_FILTER_MODE=OFF`.

Limitations and Restrictions for Runtime Filtering

The runtime filtering feature is most effective for the Parquet file formats. For other file formats, filtering only applies for partitioned tables. See [File Format Considerations for Runtime Filtering](#) on page 643. For the ways in which runtime filtering works for Kudu tables, see [Impala Query Performance for Kudu Tables](#) on page 749.

When the spill-to-disk mechanism is activated on a particular host during a query, that host does not produce any filters while processing that query. This limitation does not affect the correctness of results; it only reduces the amount of optimization that can be applied to the query.

Using HDFS Caching with Impala (Impala 2.1 or higher only)

HDFS caching provides performance and scalability benefits in production environments where Impala queries and other Hadoop jobs operate on quantities of data much larger than the physical RAM on the DataNodes, making it impractical to rely on the Linux OS cache, which only keeps the most recently used data in memory. Data read from the HDFS cache avoids the overhead of checksumming and memory-to-memory copying involved when using data from the Linux OS cache.

Note:

On a small or lightly loaded cluster, HDFS caching might not produce any speedup. It might even lead to slower queries, if I/O read operations that were performed in parallel across the entire cluster are replaced by in-memory operations operating on a smaller number of hosts. The hosts where the HDFS blocks are cached can become bottlenecks because they experience high CPU load while processing the cached data blocks, while other hosts remain idle. Therefore, always compare performance with and without this feature enabled, using a realistic workload.

In Impala 2.2 and higher, you can spread the CPU load more evenly by specifying the `WITH REPLICATION` clause of the `CREATE TABLE` and `ALTER TABLE` statements. This clause lets you control the replication factor for HDFS caching for a specific table or partition. By default, each cached block is only present on a single host, which can lead to CPU contention if the same host processes each cached block. Increasing the replication factor lets Impala choose different hosts to process different cached blocks, to better distribute the CPU load. Always use a `WITH REPLICATION` setting of at least 3, and adjust upward if necessary to match the replication factor for the underlying HDFS data files.

In Impala 2.5 and higher, Impala automatically randomizes which host processes a cached HDFS block, to avoid CPU hotspots. For tables where HDFS caching is not applied, Impala designates which host to process a data block using an algorithm that estimates the load on each host. If CPU hotspots still arise during queries,

you can enable additional randomization for the scheduling algorithm for non-HDFS cached data by setting the `SCHEDULE_RANDOM_REPLICA` query option.

For background information about how to set up and manage HDFS caching for a cluster, see the documentation for your Apache Hadoop distribution.

Overview of HDFS Caching for Impala

In Impala 1.4 and higher, Impala can use the HDFS caching feature to make more effective use of RAM, so that repeated queries can take advantage of data “pinned” in memory regardless of how much data is processed overall. The HDFS caching feature lets you designate a subset of frequently accessed data to be pinned permanently in memory, remaining in the cache across multiple queries and never being evicted. This technique is suitable for tables or partitions that are frequently accessed and are small enough to fit entirely within the HDFS memory cache. For example, you might designate several dimension tables to be pinned in the cache, to speed up many different join queries that reference them. Or in a partitioned table, you might pin a partition holding data from the most recent time period because that data will be queried intensively; then when the next set of data arrives, you could unpin the previous partition and pin the partition holding the new data.

Because this Impala performance feature relies on HDFS infrastructure, it only applies to Impala tables that use HDFS data files. HDFS caching for Impala does not apply to HBase tables, S3 tables, Kudu tables, or Isilon tables.

Setting Up HDFS Caching for Impala

To use HDFS caching with Impala, first set up that feature for your cluster:

- Decide how much memory to devote to the HDFS cache on each host. Remember that the total memory available for cached data is the sum of the cache sizes on all the hosts. By default, any data block is only cached on one host, although you can cache a block across multiple hosts by increasing the replication factor.
- Issue `hdfs cacheadmin` commands to set up one or more cache pools, owned by the same user as the `impalad` daemon (typically `impala`). For example:

```
hdfs cacheadmin -addPool four_gig_pool -owner impala -limit 4000000000
```

For details about the `hdfs cacheadmin` command, see the documentation for your Apache Hadoop distribution.

Once HDFS caching is enabled and one or more pools are available, see [Enabling HDFS Caching for Impala Tables and Partitions](#) on page 647 for how to choose which Impala data to load into the HDFS cache. On the Impala side, you specify the cache pool name defined by the `hdfs cacheadmin` command in the Impala DDL statements that enable HDFS caching for a table or partition, such as `CREATE TABLE ... CACHED IN pool` or `ALTER TABLE ... SET CACHED IN pool`.

Enabling HDFS Caching for Impala Tables and Partitions

Begin by choosing which tables or partitions to cache. For example, these might be lookup tables that are accessed by many different join queries, or partitions corresponding to the most recent time period that are analyzed by different reports or ad hoc queries.

In your SQL statements, you specify logical divisions such as tables and partitions to be cached. Impala translates these requests into HDFS-level directives that apply to particular directories and files. For example, given a partitioned table `CENSUS` with a partition key column `YEAR`, you could choose to cache all or part of the data as follows:

In Impala 2.2 and higher, the optional `WITH REPLICATION` clause for `CREATE TABLE` and `ALTER TABLE` lets you specify a *replication factor*, the number of hosts on which to cache the same data blocks. When Impala processes a cached data block, where the cache replication factor is greater than 1, Impala randomly selects a host that has a cached copy of that data block. This optimization avoids excessive CPU usage on a single host when the same cached

data block is processed multiple times. Where practical, specify a value greater than or equal to the HDFS block replication factor.

```
-- Cache the entire table (all partitions).
alter table census set cached in 'pool_name';

-- Remove the entire table from the cache.
alter table census set uncached;

-- Cache a portion of the table (a single partition).
-- If the table is partitioned by multiple columns (such as year, month,
  day),
-- the ALTER TABLE command must specify values for all those columns.
alter table census partition (year=1960) set cached in 'pool_name';

-- Cache the data from one partition on up to 4 hosts, to minimize CPU load
  on any
  single host when the same data block is processed multiple times.
alter table census partition (year=1970)
  set cached in 'pool_name' with replication = 4;

-- At each stage, check the volume of cached data.
-- For large tables or partitions, the background loading might take some
  time,
-- so you might have to wait and reissue the statement until all the data
-- has finished being loaded into the cache.
show table stats census;
```

year	#Rows	#Files	Size	Bytes Cached	Format
1900	-1	1	11B	NOT CACHED	TEXT
1940	-1	1	11B	NOT CACHED	TEXT
1960	-1	1	11B	11B	TEXT
1970	-1	1	11B	NOT CACHED	TEXT
Total	-1	4	44B	11B	

CREATE TABLE considerations:

The HDFS caching feature affects the Impala CREATE TABLE statement as follows:

- You can put a `CACHED IN 'pool_name'` clause and optionally a `WITH REPLICATION = number_of_hosts` clause at the end of a CREATE TABLE statement to automatically cache the entire contents of the table, including any partitions added later. The *pool_name* is a pool that you previously set up with the `hdfs cacheadmin` command.
- Once a table is designated for HDFS caching through the CREATE TABLE statement, if new partitions are added later through ALTER TABLE ... ADD PARTITION statements, the data in those new partitions is automatically cached in the same pool.
- If you want to perform repetitive queries on a subset of data from a large table, and it is not practical to designate the entire table or specific partitions for HDFS caching, you can create a new cached table with just a subset of the data by using CREATE TABLE ... CACHED IN 'pool_name' AS SELECT ... WHERE When you are finished with generating reports from this subset of data, drop the table and both the data files and the data cached in RAM are automatically deleted.

See [CREATE TABLE Statement](#) on page 248 for the full syntax.

Other memory considerations:

Certain DDL operations, such as ALTER TABLE ... SET LOCATION, are blocked while the underlying HDFS directories contain cached files. You must uncache the files first, before changing the location, dropping the table, and so on.

When data is requested to be pinned in memory, that process happens in the background without blocking access to the data while the caching is in progress. Loading the data from disk could take some time. Impala reads each HDFS data block from memory if it has been pinned already, or from disk if it has not been pinned yet.

The amount of data that you can pin on each node through the HDFS caching mechanism is subject to a quota that is enforced by the underlying HDFS service. Before requesting to pin an Impala table or partition in memory, check that its size does not exceed this quota.

Note: Because the HDFS cache consists of combined memory from all the DataNodes in the cluster, cached tables or partitions can be bigger than the amount of HDFS cache memory on any single host.

Loading and Removing Data with HDFS Caching Enabled

When HDFS caching is enabled, extra processing happens in the background when you add or remove data through statements such as `INSERT` and `DROP TABLE`.

Inserting or loading data:

- When Impala performs an `INSERT` or `LOAD DATA` statement for a table or partition that is cached, the new data files are automatically cached and Impala recognizes that fact automatically.
- If you perform an `INSERT` or `LOAD DATA` through Hive, as always, Impala only recognizes the new data files after a `REFRESH table_name` statement in Impala.
- If the cache pool is entirely full, or becomes full before all the requested data can be cached, the Impala DDL statement returns an error. This is to avoid situations where only some of the requested data could be cached.
- When HDFS caching is enabled for a table or partition, new data files are cached automatically when they are added to the appropriate directory in HDFS, without the need for a `REFRESH` statement in Impala. Impala automatically performs a `REFRESH` once the new data is loaded into the HDFS cache.

Dropping tables, partitions, or cache pools:

The HDFS caching feature interacts with the Impala `DROP TABLE` and `ALTER TABLE ... DROP PARTITION` statements as follows:

- When you issue a `DROP TABLE` for a table that is entirely cached, or has some partitions cached, the `DROP TABLE` succeeds and all the cache directives Impala submitted for that table are removed from the HDFS cache system.
- The same applies to `ALTER TABLE ... DROP PARTITION`. The operation succeeds and any cache directives are removed.
- As always, the underlying data files are removed if the dropped table is an internal table, or the dropped partition is in its default location underneath an internal table. The data files are left alone if the dropped table is an external table, or if the dropped partition is in a non-default location.
- If you designated the data files as cached through the `hdfs cacheadmin` command, and the data files are left behind as described in the previous item, the data files remain cached. Impala only removes the cache directives submitted by Impala through the `CREATE TABLE` or `ALTER TABLE` statements. It is OK to have multiple redundant cache directives pertaining to the same files; the directives all have unique IDs and owners so that the system can tell them apart.
- If you drop an HDFS cache pool through the `hdfs cacheadmin` command, all the Impala data files are preserved, just no longer cached. After a subsequent `REFRESH`, `SHOW TABLE STATS` reports 0 bytes cached for each associated Impala table or partition.

Relocating a table or partition:

The HDFS caching feature interacts with the Impala `ALTER TABLE ... SET LOCATION` statement as follows:

- If you have designated a table or partition as cached through the `CREATE TABLE` or `ALTER TABLE` statements, subsequent attempts to relocate the table or partition through an `ALTER TABLE ... SET LOCATION` statement will fail. You must issue an `ALTER TABLE ... SET UNCACHED` statement for the table or partition first. Otherwise, Impala would lose track of some cached data files and have no way to uncache them later.

Administration for HDFS Caching with Impala

Here are the guidelines and steps to check or change the status of HDFS caching for Impala data:

hdfs cacheadmin command:

- If you drop a cache pool with the `hdfs cacheadmin` command, Impala queries against the associated data files will still work, by falling back to reading the files from disk. After performing a `REFRESH` on the table, Impala reports the number of bytes cached as 0 for all associated tables and partitions.
- You might use `hdfs cacheadmin` to get a list of existing cache pools, or detailed information about the pools, as follows:

```
hdfs cacheadmin -listDirectives          # Basic info
Found 122 entries
  ID POOL      REPL EXPIRY  PATH
  123 testPool  1  never  /user/hive/warehouse/tpcds.store_sales
  124 testPool  1  never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-01-15
  125 testPool  1  never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-02-01
  ...

hdfs cacheadmin -listDirectives -stats # More details
Found 122 entries
  ID POOL      REPL EXPIRY  PATH                                BYTES_NEEDED  BYTES_CACHED
  FILES_NEEDED  FILES_CACHED
  123 testPool  1  never  /user/hive/warehouse/tpcds.store_sales      0              0
  0
  124 testPool  1  never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-01-15  143169         143169
  1
  125 testPool  1  never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-02-01  112447         112447
  1
  ...
```

Impala SHOW statement:

- For each table or partition, the `SHOW TABLE STATS` or `SHOW PARTITIONS` statement displays the number of bytes currently cached by the HDFS caching feature. If there are no cache directives in place for that table or partition, the result set displays `NOT CACHED`. A value of 0, or a smaller number than the overall size of the table or partition, indicates that the cache request has been submitted but the data has not been entirely loaded into memory yet. See [SHOW Statement](#) on page 395 for details.

Impala memory limits:

The Impala HDFS caching feature interacts with the Impala memory limits as follows:

- The maximum size of each HDFS cache pool is specified externally to Impala, through the `hdfs cacheadmin` command.
- All the memory used for HDFS caching is separate from the `impalad` daemon address space and does not count towards the limits of the `--mem_limit` startup option, `MEM_LIMIT` query option, or further limits imposed through YARN resource management or the Linux `cgroups` mechanism.
- Because accessing HDFS cached data avoids a memory-to-memory copy operation, queries involving cached data require less memory on the Impala side than the equivalent queries on uncached data. In addition to any performance benefits in a single-user environment, the reduced memory helps to improve scalability under high-concurrency workloads.

Performance Considerations for HDFS Caching with Impala

In Impala 1.4.0 and higher, Impala supports efficient reads from data that is pinned in memory through HDFS caching. Impala takes advantage of the HDFS API and reads the data from memory rather than from disk whether the data files are pinned using Impala DDL statements, or using the command-line mechanism where you specify HDFS paths.

When you examine the output of the `impala-shell SUMMARY` command, or look in the metrics report for the `impalad` daemon, you see how many bytes are read from the HDFS cache. For example, this excerpt from a query profile illustrates that all the data read during a particular phase of the query came from the HDFS cache, because the `BytesRead` and `BytesReadDataNodeCache` values are identical.

```
HDFS_SCAN_NODE (id=0):(Total: 11s114ms, non-child: 11s114ms, % non-child:
100.00%)
  - AverageHdfsReadThreadConcurrency: 0.00
```

```
- AverageScannerThreadConcurrency: 32.75
- BytesRead: 10.47 GB (11240756479)
- BytesReadDataNodeCache: 10.47 GB (11240756479)
- BytesReadLocal: 10.47 GB (11240756479)
- BytesReadShortCircuit: 10.47 GB (11240756479)
- DecompressionTime: 27s572ms
```

For queries involving smaller amounts of data, or in single-user workloads, you might not notice a significant difference in query response time with or without HDFS caching. Even with HDFS caching turned off, the data for the query might still be in the Linux OS buffer cache. The benefits become clearer as data volume increases, and especially as the system processes more concurrent queries. HDFS caching improves the scalability of the overall system. That is, it prevents query performance from declining when the workload outstrips the capacity of the Linux OS cache.

Due to a limitation of HDFS, zero-copy reads are not supported with encryption. Where practical, avoid HDFS caching for Impala data files in encryption zones. The queries fall back to the normal read path during query execution, which might cause some performance overhead.

SELECT considerations:

The Impala HDFS caching feature interacts with the [SELECT](#) statement and query performance as follows:

- Impala automatically reads from memory any data that has been designated as cached and actually loaded into the HDFS cache. (It could take some time after the initial request to fully populate the cache for a table with large size or many partitions.) The speedup comes from two aspects: reading from RAM instead of disk, and accessing the data straight from the cache area instead of copying from one RAM area to another. This second aspect yields further performance improvement over the standard OS caching mechanism, which still results in memory-to-memory copying of cached data.
- For small amounts of data, the query speedup might not be noticeable in terms of wall clock time. The performance might be roughly the same with HDFS caching turned on or off, due to recently used data being held in the Linux OS cache. The difference is more pronounced with:
 - Data volumes (for all queries running concurrently) that exceed the size of the Linux OS cache.
 - A busy cluster running many concurrent queries, where the reduction in memory-to-memory copying and overall memory usage during queries results in greater scalability and throughput.
 - Thus, to really exercise and benchmark this feature in a development environment, you might need to simulate realistic workloads and concurrent queries that match your production environment.
 - One way to simulate a heavy workload on a lightly loaded system is to flush the OS buffer cache (on each DataNode) between iterations of queries against the same tables or partitions:

```
$ sync
$ echo 1 > /proc/sys/vm/drop_caches
```

- Impala queries take advantage of HDFS cached data regardless of whether the cache directive was issued by Impala or externally through the `hdfs cacheadmin` command, for example for an external table where the cached data files might be accessed by several different Hadoop components.
- If your query returns a large result set, the time reported for the query could be dominated by the time needed to print the results on the screen. To measure the time for the underlying query processing, query the `COUNT()` of the big result set, which does all the same processing but only prints a single line to the screen.

Detecting and Correcting HDFS Block Skew Conditions

For best performance of Impala parallel queries, the work is divided equally across hosts in the cluster, and all hosts take approximately equal time to finish their work. If one host takes substantially longer than others, the extra time needed for the slow host can become the dominant factor in query performance. Therefore, one of the first steps in performance tuning for Impala is to detect and correct such conditions.

The main cause of uneven performance that you can correct within Impala is *skew* in the number of HDFS data blocks processed by each host, where some hosts process substantially more data blocks than others. This condition

can occur because of uneven distribution of the data values themselves, for example causing certain data files or partitions to be large while others are very small. (Although it is possible to have unevenly distributed data without any problems with the distribution of HDFS blocks.) Block skew could also be due to the underlying block allocation policies within HDFS, the replication factor of the data files, and the way that Impala chooses the host to process each data block.

The most convenient way to detect block skew, or slow-host issues in general, is to examine the “executive summary” information from the query profile after running a query:

- In `impala-shell`, issue the `SUMMARY` command immediately after the query is complete, to see just the summary information. If you detect issues involving skew, you might switch to issuing the `PROFILE` command, which displays the summary information followed by a detailed performance analysis.
- In the Impala debug web UI, click on the **Profile** link associated with the query after it is complete. The executive summary information is displayed early in the profile output.

For each phase of the query, you see an **Avg Time** and a **Max Time** value, along with **#Hosts** indicating how many hosts are involved in that query phase. For all the phases with **#Hosts** greater than one, look for cases where the maximum time is substantially greater than the average time. Focus on the phases that took the longest, for example, those taking multiple seconds rather than milliseconds or microseconds.

If you detect that some hosts take longer than others, first rule out non-Impala causes. One reason that some hosts could be slower than others is if those hosts have less capacity than the others, or if they are substantially busier due to unevenly distributed non-Impala workloads:

- For clusters running Impala, keep the relative capacities of all hosts roughly equal. Any cost savings from including some underpowered hosts in the cluster will likely be outweighed by poor or uneven performance, and the time spent diagnosing performance issues.
- If non-Impala workloads cause slowdowns on some hosts but not others, use the appropriate load-balancing techniques for the non-Impala components to smooth out the load across the cluster.

If the hosts on your cluster are evenly powered and evenly loaded, examine the detailed profile output to determine which host is taking longer than others for the query phase in question. Examine how many bytes are processed during that phase on that host, how much memory is used, and how many bytes are transmitted across the network.

The most common symptom is a higher number of bytes read on one host than others, due to one host being requested to process a higher number of HDFS data blocks. This condition is more likely to occur when the number of blocks accessed by the query is relatively small. For example, if you have a 10-node cluster and the query processes 10 HDFS blocks, each node might not process exactly one block. If one node sits idle while another node processes two blocks, the query could take twice as long as if the data was perfectly distributed.

Possible solutions in this case include:

- If the query is artificially small, perhaps for benchmarking purposes, scale it up to process a larger data set. For example, if some nodes read 10 HDFS data blocks while others read 11, the overall effect of the uneven distribution is much lower than when some nodes did twice as much work as others. As a guideline, aim for a “sweet spot” where each node reads 2 GB or more from HDFS per query. Queries that process lower volumes than that could experience inconsistent performance that smooths out as queries become more data-intensive.
- If the query processes only a few large blocks, so that many nodes sit idle and cannot help to parallelize the query, consider reducing the overall block size. For example, you might adjust the `PARQUET_FILE_SIZE` query option before copying or converting data into a Parquet table. Or you might adjust the granularity of data files produced earlier in the ETL pipeline by non-Impala components. In Impala 2.0 and later, the default Parquet block size is 256 MB, reduced from 1 GB, to improve parallelism for common cluster sizes and data volumes.
- Reduce the amount of compression applied to the data. For text data files, the highest degree of compression (gzip) produces unsplittable files that are more difficult for Impala to process in parallel, and require extra memory during processing to hold the compressed and uncompressed data simultaneously. For binary formats such as Parquet and Avro, compression can result in fewer data blocks overall, but remember that when queries process relatively few blocks, there is less opportunity for parallel execution and many nodes in the cluster might sit idle. Note that when Impala writes Parquet data with the query option `COMPRESSION_CODEC=NONE` enabled, the data is still typically compact due to the encoding schemes used by Parquet, independent of the final compression step.

Data Cache for Remote Reads

When Impala compute nodes and its storage are not co-located, the network bandwidth requirement goes up as the network traffic includes the data fetch as well as the shuffling exchange traffic of intermediate results.

To mitigate the pressure on the network, you can enable the compute nodes to cache the working set read from remote filesystems, such as, remote HDFS data node, S3, ABFS, ADLS.

To enable remote data cache, set the `--data_cache` Impala Daemon start-up flag as below:

```
--data_cache=dir1,dir2,dir3,...:quota
```

The flag is set to a list of directories, separated by `,`, followed by a `:`, and a capacity *quota* per directory.

If set to an empty string, data caching is disabled.

Cached data is stored in the specified directories.

The specified directories must exist in the local filesystem of each Impala Daemon, or Impala will fail to start.

In addition, the filesystem which the directory resides in must support hole punching.

The cache can consume up to the *quota* bytes for each of the directories specified.

The default setting for `--data_cache` is an empty string.

For example, with the following setting, the data cache may use up to 1 TB, with 500 GB max in `/data/0` and `/data/1` respectively.

```
--data_cache=/data/0,/data/1:500GB
```

In Impala 3.4 and higher, you can configure one of the following cache eviction policies for the data cache:

- LRU (Least Recently Used--the default)
- LIRS (Inter-reference Recency Set)

LIRS is a scan-resistant, low performance-overhead policy. You configure a cache eviction policy using the `--data_cache_eviction_policy` Impala Daemon start-up flag:

```
--data_cache_eviction_policy=policy
```

Note: The cache item will not expire as long as the same file metadata is used in the query. This is because the cache key consists of the filename, mtime (last modified time of the file), and file offset. If the mtime in the file metadata remains unchanged, the scan request will consistently access the cache (provided that there is enough capacity).

Testing Impala Performance

Test to ensure that Impala is configured for optimal performance. If you have installed Impala with cluster management software, complete the processes described in this topic to help ensure a proper configuration. These procedures can be used to verify that Impala is set up correctly.

Checking Impala Configuration Values

You can inspect Impala configuration values by connecting to your Impala server using a browser.

To check Impala configuration values:

1. Use a browser to connect to one of the hosts running `impalad` in your environment. Connect using an address of the form `http://hostname:port/varz`.

Note: In the preceding example, replace `hostname` and `port` with the name and port of your Impala server. The default port is 25000.

2. Review the configured values.

For example, to check that your system is configured to use block locality tracking information, you would check that the value for `dfs.datanode.hdfs-blocks-metadata.enabled` is `true`.

To check data locality:

1. Execute a query on a dataset that is available across multiple nodes. For example, for a table named `MyTable` that has a reasonable chance of being spread across multiple `DataNodes`:

```
[impalad-host:21000] > SELECT COUNT (*) FROM MyTable
```

2. After the query completes, review the contents of the Impala logs. You should find a recent message similar to the following:

```
Total remote scan volume = 0
```

The presence of remote scans may indicate `impalad` is not running on the correct nodes. This can be because some `DataNodes` do not have `impalad` running or it can be because the `impalad` instance that is starting the query is unable to contact one or more of the `impalad` instances.

To understand the causes of this issue:

1. Connect to the debugging web server. By default, this server runs on port 25000. This page lists all `impalad` instances running in your cluster. If there are fewer instances than you expect, this often indicates some `DataNodes` are not running `impalad`. Ensure `impalad` is started on all `DataNodes`.
2. If you are using multi-homed hosts, ensure that the Impala daemon's hostname resolves to the interface on which `impalad` is running. The hostname Impala is using is displayed when `impalad` starts. To explicitly set the hostname, use the `--hostname` flag.
3. Check that `statestored` is running as expected. Review the contents of the state store log to ensure all instances of `impalad` are listed as having connected to the state store.

Reviewing Impala Logs

You can review the contents of the Impala logs for signs that short-circuit reads or block location tracking are not functioning. Before checking logs, execute a simple query against a small HDFS dataset. Completing a query task generates log messages using current settings. Information on starting Impala and executing queries can be found in [Starting Impala](#) on page 31 and [Using the Impala Shell \(`impala-shell` Command\)](#) on page 790. Information on logging can be found in [Using Impala Logging](#) on page 784. Log messages and their interpretations are as follows:

Log Message	Interpretation
Unknown disk id. This will negatively affect performance. Check your hdfs settings to enable block location metadata	Tracking block locality is not enabled.
Unable to load native-hadoop library for your platform... using builtin-java classes where applicable	Native checksumming is not enabled.

Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles

To understand the high-level performance considerations for Impala queries, read the output of the `EXPLAIN` statement for the query. You can get the `EXPLAIN` plan without actually running the query itself.

For an overview of the physical performance characteristics for a query, issue the `SUMMARY` statement in `impala-shell` immediately after executing a query. This condensed information shows which phases of execution took the most time, and how the estimates for memory usage and number of rows at each phase compare to the actual values.

To understand the detailed performance characteristics for a query, issue the `PROFILE` statement in `impala-shell` immediately after executing a query. This low-level information includes physical details about memory, CPU, I/O, and network usage, and thus is only available after the query is actually run.

Also, see [Performance Considerations for the Impala-HBase Integration](#) on page 751 and [Understanding and Tuning Impala Query Performance for S3 Data](#) on page 774 for examples of interpreting `EXPLAIN` plans for queries against HBase tables and data stored in the Amazon Simple Storage System (S3).

Using the EXPLAIN Plan for Performance Tuning

The `EXPLAIN` statement gives you an outline of the logical steps that a query will perform, such as how the work will be distributed among the nodes and how intermediate results will be combined to produce the final result set. You can see these details before actually running the query. You can use this information to check that the query will not operate in some very unexpected or inefficient way.

```
[impalad-host:21000] > EXPLAIN SELECT COUNT(*) FROM customer_address;
+-----+
| Explain String |
+-----+
| ...           |
| 03:AGGREGATE [FINALIZE] |
|   output: sum(count(*)) |
| 02:EXCHANGE [UNPARTITIONED] |
| 01:AGGREGATE |
|   output: count(*) |
| 00:SCAN HDFS [default.customer_address] |
|   partitions=1/1 size=5.25MB |
+-----+
```

Read the `EXPLAIN` plan from bottom to top:

- The last part of the plan shows the low-level details such as the expected amount of data that will be read, where you can judge the effectiveness of your partitioning strategy and estimate how long it will take to scan a table based on total data size and the size of the cluster.
- As you work your way up, next you see the operations that will be parallelized and performed on each Impala node.
- At the higher levels, you see how data flows when intermediate result sets are combined and transmitted from one node to another.
- See [EXPLAIN_LEVEL Query Option](#) on page 357 for details about the `EXPLAIN_LEVEL` query option, which lets you customize how much detail to show in the `EXPLAIN` plan depending on whether you are doing high-level or low-level tuning, dealing with logical or physical aspects of the query.

The `EXPLAIN` plan is also printed at the beginning of the query profile report described in [Using the Query Profile for Performance Tuning](#) on page 656, for convenience in examining both the logical and physical aspects of the query side-by-side.

The amount of detail displayed in the `EXPLAIN` output is controlled by the `EXPLAIN_LEVEL` query option. You typically increase this setting from `standard` to `extended` (or from 1 to 2) when doublechecking the presence of table and column statistics during performance tuning, or when estimating query resource usage in conjunction with the resource management features.

Using the SUMMARY Report for Performance Tuning

The `SUMMARY` command within the `impala-shell` interpreter gives you an easy-to-digest overview of the timings for the different phases of execution for a query. Like the `EXPLAIN` plan, it is easy to see potential performance bottlenecks. Like the `PROFILE` output, it is available after the query is run and so displays actual timing numbers.

The SUMMARY report is also printed at the beginning of the query profile report described in [Using the Query Profile for Performance Tuning](#) on page 656, for convenience in examining high-level and low-level aspects of the query side-by-side.

When the MT_DOP query option is set to a value larger than 0, the #Inst column in the output shows the number of fragment instances. Impala decomposes each query into smaller units of work that are distributed across the cluster, and these units are referred as fragments.

When the MT_DOP query option is set to 0, the #Inst column in the output shows the same value as the #Hosts column, since there is exactly one fragment for each host.

For example, here is a query involving an aggregate function, on a single-node cluster. The different stages of the query and their timings are shown (rolled up for all nodes), along with estimated and actual values used in planning the query. In this case, the AVG() function is computed for a subset of data on each node (stage 01) and then the aggregated results from all nodes are combined at the end (stage 03). You can see which stages took the most time, and whether any estimates were substantially different than the actual data distribution.

```
> SELECT AVG(ss_sales_price) FROM store_sales WHERE ss_coupon_amt = 0;
> SUMMARY;
```

Operator	#Hosts	#Inst	Avg Time	Max Time	#Rows	Est. #Rows
Peak Mem	Est. Peak Mem	Detail				
03:AGGREGATE	1	1	1.03ms	1.03ms	1	1
48.00 KB	-1 B	MERGE FINALIZE				
02:EXCHANGE	1	1	0ns	0ns	1	1
0 B	-1 B	UNPARTITIONED				
01:AGGREGATE	1	1	30.79ms	30.79ms	1	1
80.00 KB	10.00 MB					
00:SCAN HDFS	1	1	5.45s	5.45s	2.21M	-1
64.05 MB	432.00 MB	tpc.store_sales				

Notice how the longest initial phase of the query is measured in seconds (s), while later phases working on smaller intermediate results are measured in milliseconds (ms) or even nanoseconds (ns).

Using the Query Profile for Performance Tuning

The PROFILE command, available in the `impala-shell` interpreter, produces a detailed low-level report showing how the most recent query was executed. Unlike the EXPLAIN plan described in [Using the EXPLAIN Plan for Performance Tuning](#) on page 655, this information is only available after the query has finished. It shows physical details such as the number of bytes read, maximum memory usage, and so on for each node. You can use this information to determine if the query is I/O-bound or CPU-bound, whether some network condition is imposing a bottleneck, whether a slowdown is affecting some nodes but not others, and to check that recommended configuration settings such as short-circuit local reads are in effect.

By default, time values in the profile output reflect the wall-clock time taken by an operation. For values denoting system time or user time, the measurement unit is reflected in the metric name, such as `ScannerThreadsSysTime` or `ScannerThreadsUserTime`. For example, a multi-threaded I/O operation might show a small figure for wall-clock time, while the corresponding system time is larger, representing the sum of the CPU time taken by each thread. Or a wall-clock time figure might be larger because it counts time spent waiting, while the corresponding system and user time figures only measure the time while the operation is actively using CPU cycles.

The [EXPLAIN plan](#) is also printed at the beginning of the query profile report, for convenience in examining both the logical and physical aspects of the query side-by-side. The [EXPLAIN_LEVEL](#) query option also controls the verbosity of the EXPLAIN output printed by the PROFILE command.

In Impala 3.2, a new `Per Node Profiles` section was added to the profile output. The new section includes the following metrics that can be controlled by the `RESOURCE_TRACE_RATIO` query option.

- `CpuIoWaitPercentage`
- `CpuSysPercentage`
- `CpuUserPercentage`
- `HostDiskReadThroughput`: All data read by the host as part of the execution of this query (spilling), by the HDFS data node, and by other processes running on the same system.
- `HostDiskWriteThroughput`: All data written by the host as part of the execution of this query (spilling), by the HDFS data node, and by other processes running on the same system.
- `HostNetworkRx`: All data received by the host as part of the execution of this query, other queries, and other processes running on the same system.
- `HostNetworkTx`: All data transmitted by the host as part of the execution of this query, other queries, and other processes running on the same system.

Scalability Considerations for Impala

This section explains how the size of your cluster and the volume of data influences SQL performance and schema design for Impala tables. Typically, adding more cluster capacity reduces problems due to memory limits or disk throughput. On the other hand, larger clusters are more likely to have other kinds of scalability issues, such as a single slow node that causes performance problems for queries.

A good source of tips related to scalability and performance tuning is the [Impala Cookbook](#) presentation. These slides are updated periodically as new features come out and new benchmarks are performed.

Impact of Many Tables or Partitions on Impala Catalog Performance and Memory Usage

Because Hadoop I/O is optimized for reading and writing large files, Impala is optimized for tables containing relatively few, large data files. Schemas containing thousands of tables, or tables containing thousands of partitions, can encounter performance issues during startup or during DDL operations such as `ALTER TABLE` statements.

Important:

Because of a change in the default heap size for the `catalogd` daemon in Impala 2.5 and higher, the following procedure to increase the `catalogd` memory limit might be required following an upgrade to Impala 2.5 even if not needed previously.

For schemas with large numbers of tables, partitions, and data files, the `catalogd` daemon might encounter an out-of-memory error. To increase the memory limit for the `catalogd` daemon:

1. Check current memory usage for the `catalogd` daemon by running the following commands on the host where that daemon runs on your cluster:

```
jcmd catalogd_pid VM.flags
jmap -heap catalogd_pid
```

2. Decide on a large enough value for the `catalogd` heap. You use the `JAVA_TOOL_OPTIONS` environment variable to set the maximum heap size. For example, the following environment variable setting specifies the maximum heap size of 8 GB.

```
JAVA_TOOL_OPTIONS="-Xmx8g"
```

3. On systems not using cluster management software, put this environment variable setting into the startup script for the `catalogd` daemon, then restart the `catalogd` daemon.
4. Use the same `jcmd` and `jmap` commands as earlier to verify that the new settings are in effect.

Scalability Considerations for the Impala Statestore

Before Impala 2.1, the statestore sent only one kind of message to its subscribers. This message contained all updates for any topics that a subscriber had subscribed to. It also served to let subscribers know that the statestore had not failed, and conversely the statestore used the success of sending a heartbeat to a subscriber to decide whether or not the subscriber had failed.

Combining topic updates and failure detection in a single message led to bottlenecks in clusters with large numbers of tables, partitions, and HDFS data blocks. When the statestore was overloaded with metadata updates to transmit, heartbeat messages were sent less frequently, sometimes causing subscribers to time out their connection with the statestore. Increasing the subscriber timeout and decreasing the frequency of statestore heartbeats worked around the problem, but reduced responsiveness when the statestore failed or restarted.

As of Impala 2.1, the statestore now sends topic updates and heartbeats in separate messages. This allows the statestore to send and receive a steady stream of lightweight heartbeats, and removes the requirement to send topic updates according to a fixed schedule, reducing statestore network overhead.

The statestore now has the following relevant configuration flags for the `statestored` daemon:

`-statestore_num_update_threads`

The number of threads inside the statestore dedicated to sending topic updates. You should not typically need to change this value.

Default: 10

`-statestore_update_frequency_ms`

The frequency, in milliseconds, with which the statestore tries to send topic updates to each subscriber. This is a best-effort value; if the statestore is unable to meet this frequency, it sends topic updates as fast as it can. You should not typically need to change this value.

Default: 2000

`-statestore_num_heartbeat_threads`

The number of threads inside the statestore dedicated to sending heartbeats. You should not typically need to change this value.

Default: 10

`-statestore_heartbeat_frequency_ms`

The frequency, in milliseconds, with which the statestore tries to send heartbeats to each subscriber. This value should be good for large catalogs and clusters up to approximately 150 nodes. Beyond that, you might need to increase this value to make the interval longer between heartbeat messages.

Default: 1000 (one heartbeat message every second)

`-`

`statestore_heartbeat_tcp_timeout_seconds`

The time after which a heartbeat RPC to a subscriber will timeout. This setting protects against badly hung machines that are not able to respond to the heartbeat RPC in short order. Increase this if there are intermittent heartbeat RPC timeouts shown in statestore's log. You can reference the max value of "statestore.priority-topic-

	update-durations" metric on statestore to get a reasonable value. Note that priority topic updates are assumed to be small amounts of data that take a small amount of time to process (similar to the heartbeat complexity).
	Default: 3
-statestore_max_missed_heartbeats	Maximum number of consecutive heartbeat messages an impalad can miss before being declared failed by the statestore. You should not typically need to change this value.
	Default: 10
-statestore_subscriber_timeout_secs	The amount of time (in seconds) that may elapse before the connection with the statestore is considered lost by subscribers (impalad/catalogd). Impalad will reregister itself to statestore, which may cause its absence in the next round of cluster membership update. This will cause query failures like "Cancelled due to unreachable impalad(s)". The value of this flag should be comparable to $(\text{statestore_heartbeat_frequency_ms} / 1000 + \text{statestore_heartbeat_tcp_timeout_seconds}) * \text{statestore_max_missed_heartbeats}$, so subscribers won't reregister themselves too early and allow statestore to resend heartbeats. You can also reference the max value of "statestore-subscriber.heartbeat-interval-time" metrics on impalads to get a reasonable value.
	Default: 30

If it takes a very long time for a cluster to start up, and `impala-shell` consistently displays `This Impala daemon is not ready to accept user requests`, the statestore might be taking too long to send the entire catalog topic to the cluster. In this case, consider adding `--load_catalog_in_background=false` to your catalog service configuration. This setting stops the statestore from loading the entire catalog into memory at cluster startup. Instead, metadata for each table is loaded when the table is accessed for the first time.

Effect of Buffer Pool on Memory Usage (Impala 2.10 and higher)

The buffer pool feature, available in Impala 2.10 and higher, changes the way Impala allocates memory during a query. Most of the memory needed is reserved at the beginning of the query, avoiding cases where a query might run for a long time before failing with an out-of-memory error. The actual memory estimates and memory buffers are typically smaller than before, so that more queries can run concurrently or process larger volumes of data than previously.

The buffer pool feature includes some query options that you can fine-tune: [BUFFER_POOL_LIMIT Query Option](#) on page 348, [DEFAULT_SPILLABLE_BUFFER_SIZE Query Option](#) on page 352, [MAX_ROW_SIZE Query Option](#) on page 367, and [MIN_SPILLABLE_BUFFER_SIZE Query Option](#) on page 373.

Most of the effects of the buffer pool are transparent to you as an Impala user. Memory use during spilling is now steadier and more predictable, instead of increasing rapidly as more data is spilled to disk. The main change from a user perspective is the need to increase the `MAX_ROW_SIZE` query option setting when querying tables with columns containing long strings, many columns, or other combinations of factors that produce very large rows. If Impala encounters rows that are too large to process with the default query option settings, the query fails with an error message suggesting to increase the `MAX_ROW_SIZE` setting.

SQL Operations that Spill to Disk

Certain memory-intensive operations write temporary data to disk (known as *spilling* to disk) when Impala is close to exceeding its memory limit on a particular host.

The result is a query that completes successfully, rather than failing with an out-of-memory error. The tradeoff is decreased performance due to the extra disk I/O to write the temporary data and read it back in. The slowdown could be potentially be significant. Thus, while this feature improves reliability, you should optimize your queries, system parameters, and hardware configuration to make this spilling a rare occurrence.

Note:

In Impala 2.10 and higher, also see [Scalability Considerations for Impala](#) on page 657 for changes to Impala memory allocation that might change the details of which queries spill to disk, and how much memory and disk space is involved in the spilling operation.

What kinds of queries might spill to disk:

Several SQL clauses and constructs require memory allocations that could activate the spilling mechanism:

- when a query uses a `GROUP BY` clause for columns with millions or billions of distinct values, Impala keeps a similar number of temporary results in memory, to accumulate the aggregate results for each value in the group.
- When large tables are joined together, Impala keeps the values of the join columns from one table in memory, to compare them to incoming values from the other table.
- When a large result set is sorted by the `ORDER BY` clause, each node sorts its portion of the result set in memory.
- The `DISTINCT` and `UNION` operators build in-memory data structures to represent all values found so far, to eliminate duplicates as the query progresses.

When the spill-to-disk feature is activated for a join node within a query, Impala does not produce any runtime filters for that join operation on that host. Other join nodes within the query are not affected.

How Impala handles scratch disk space for spilling:

By default, intermediate files used during large sort, join, aggregation, or analytic function operations are stored in the directory `/tmp/impala-scratch`, and these intermediate files are removed when the operation finishes. You can specify a different location by starting the `impalad` daemon with the `##scratch_dirs="path_to_directory"` configuration option.

Memory usage for SQL operators:

In Impala 2.10 and higher, the way SQL operators such as `GROUP BY`, `DISTINCT`, and joins, transition between using additional memory or activating the spill-to-disk feature is changed. The memory required to spill to disk is reserved up front, and you can examine it in the `EXPLAIN` plan when the `EXPLAIN_LEVEL` query option is set to 2 or higher.

The infrastructure of the spilling feature affects the way the affected SQL operators, such as `GROUP BY`, `DISTINCT`, and joins, use memory. On each host that participates in the query, each such operator in a query requires memory to store rows of data and other data structures. Impala reserves a certain amount of memory up front for each operator that supports spill-to-disk that is sufficient to execute the operator. If an operator accumulates more data than can fit in the reserved memory, it can either reserve more memory to continue processing data in memory or start spilling data to temporary scratch files on disk. Thus, operators with spill-to-disk support can adapt to different memory constraints by using however much memory is available to speed up execution, yet tolerate low memory conditions by spilling data to disk.

The amount data depends on the portion of the data being handled by that host, and thus the operator may end up consuming different amounts of memory on different hosts.

Added in: This feature was added to the `ORDER BY` clause in Impala 1.4. This feature was extended to cover join queries, aggregation functions, and analytic functions in Impala 2.0. The size of the memory work area required by each operator that spills was reduced from 512 megabytes to 256 megabytes in Impala 2.2. The spilling mechanism was reworked to take advantage of the Impala buffer pool feature and be more predictable and stable in Impala 2.10.

Avoiding queries that spill to disk:

Because the extra I/O can impose significant performance overhead on these types of queries, try to avoid this situation by using the following steps:

1. Detect how often queries spill to disk, and how much temporary data is written. Refer to the following sources:
 - The output of the `PROFILE` command in the `impala-shell` interpreter. This data shows the memory usage for each host and in total across the cluster. The `WriteIoBytes` counter reports how much data was written to disk for each operator during the query. (In Impala 2.9, the counter was named `ScratchBytesWritten`; in Impala 2.8 and earlier, it was named `BytesWritten`.)
 - The **Queries** tab in the Impala debug web user interface. Select the query to examine and click the corresponding **Profile** link. This data breaks down the memory usage for a single host within the cluster, the host whose web interface you are connected to.
2. Use one or more techniques to reduce the possibility of the queries spilling to disk:
 - Increase the Impala memory limit if practical, for example, if you can increase the available memory by more than the amount of temporary data written to disk on a particular node. Remember that in Impala 2.0 and later, you can issue `SET MEM_LIMIT` as a SQL statement, which lets you fine-tune the memory usage for queries from JDBC and ODBC applications.
 - Increase the number of nodes in the cluster, to increase the aggregate memory available to Impala and reduce the amount of memory required on each node.
 - Add more memory to the hosts running Impala daemons.
 - On a cluster with resources shared between Impala and other Hadoop components, use resource management features to allocate more memory for Impala. See [Resource Management](#) on page 675 for details.
 - If the memory pressure is due to running many concurrent queries rather than a few memory-intensive ones, consider using the Impala admission control feature to lower the limit on the number of concurrent queries. By spacing out the most resource-intensive queries, you can avoid spikes in memory usage and improve overall response times. See [Admission Control and Query Queuing](#) on page 675 for details.
 - Tune the queries with the highest memory requirements, using one or more of the following techniques:
 - Run the `COMPUTE STATS` statement for all tables involved in large-scale joins and aggregation queries.
 - Minimize your use of `STRING` columns in join columns. Prefer numeric values instead.
 - Examine the `EXPLAIN` plan to understand the execution strategy being used for the most resource-intensive queries. See [Using the EXPLAIN Plan for Performance Tuning](#) on page 655 for details.
 - If Impala still chooses a suboptimal execution strategy even with statistics available, or if it is impractical to keep the statistics up to date for huge or rapidly changing tables, add hints to the most resource-intensive queries to select the right execution strategy. See [Optimizer Hints](#) on page 422 for details.
 - If your queries experience substantial performance overhead due to spilling, enable the `DISABLE_UNSAFE_SPILLS` query option. This option prevents queries whose memory usage is likely to be exorbitant from spilling to disk. See [DISABLE_UNSAFE_SPILLS Query Option \(Impala 2.0 or higher only\)](#) on page 355 for details. As you tune problematic queries using the preceding steps, fewer and fewer will be cancelled by this option setting.

Testing performance implications of spilling to disk:

To artificially provoke spilling, to test this feature and understand the performance implications, use a test environment with a memory limit of at least 2 GB. Issue the `SET` command with no arguments to check the current setting for the `MEM_LIMIT` query option. Set the query option `DISABLE_UNSAFE_SPILLS=true`. This option limits the spill-to-disk feature to prevent runaway disk usage from queries that are known in advance to be suboptimal. Within `impala-shell`, run a query that you expect to be memory-intensive, based on the criteria explained earlier. A self-join of a large table is a good candidate:

```
select count(*) from big_table a join big_table b using
(column_with_many_values);
```

Issue the `PROFILE` command to get a detailed breakdown of the memory usage on each node during the query.

Set the `MEM_LIMIT` query option to a value that is smaller than the peak memory usage reported in the profile output. Now try the memory-intensive query again.

Check if the query fails with a message like the following:

```
WARNINGS: Spilling has been disabled for plans that do not have stats and
are not hinted
to prevent potentially bad plans from using too many cluster resources.
Compute stats on
these tables, hint the plan or disable this behavior via query options to
enable spilling.
```

If so, the query could have consumed substantial temporary disk space, slowing down so much that it would not complete in any reasonable time. Rather than rely on the spill-to-disk feature in this case, issue the `COMPUTE STATS` statement for the table or tables in your sample query. Then run the query again, check the peak memory usage again in the `PROFILE` output, and adjust the memory limit again if necessary to be lower than the peak memory usage.

At this point, you have a query that is memory-intensive, but Impala can optimize it efficiently so that the memory usage is not exorbitant. You have set an artificial constraint through the `MEM_LIMIT` option so that the query would normally fail with an out-of-memory error. But the automatic spill-to-disk feature means that the query should actually succeed, at the expense of some extra disk I/O to read and write temporary work data.

Try the query again, and confirm that it succeeds. Examine the `PROFILE` output again. This time, look for lines of this form:

```
- SpilledPartitions: N
```

If you see any such lines with *N* greater than 0, that indicates the query would have failed in Impala releases prior to 2.0, but now it succeeded because of the spill-to-disk feature. Examine the total time taken by the `AGGREGATION_NODE` or other query fragments containing non-zero `SpilledPartitions` values. Compare the times to similar fragments that did not spill, for example in the `PROFILE` output when the same query is run with a higher memory limit. This gives you an idea of the performance penalty of the spill operation for a particular query with a particular memory limit. If you make the memory limit just a little lower than the peak memory usage, the query only needs to write a small amount of temporary data to disk. The lower you set the memory limit, the more temporary data is written and the slower the query becomes.

Now repeat this procedure for actual queries used in your environment. Use the `DISABLE_UNSAFE_SPILLS` setting to identify cases where queries used more memory than necessary due to lack of statistics on the relevant tables and columns, and issue `COMPUTE STATS` where necessary.

When to use `DISABLE_UNSAFE_SPILLS`:

You might wonder, why not leave `DISABLE_UNSAFE_SPILLS` turned on all the time. Whether and how frequently to use this option depends on your system environment and workload.

`DISABLE_UNSAFE_SPILLS` is suitable for an environment with ad hoc queries whose performance characteristics and memory usage are not known in advance. It prevents “worst-case scenario” queries that use large amounts of memory unnecessarily. Thus, you might turn this option on within a session while developing new SQL code, even though it is turned off for existing applications.

Organizations where table and column statistics are generally up-to-date might leave this option turned on all the time, again to avoid worst-case scenarios for untested queries or if a problem in the ETL pipeline results in a table with no statistics. Turning on `DISABLE_UNSAFE_SPILLS` lets you “fail fast” in this case and immediately gather statistics or tune the problematic queries.

Some organizations might leave this option turned off. For example, you might have tables large enough that the `COMPUTE STATS` takes substantial time to run, making it impractical to re-run after loading new data. If you have examined the `EXPLAIN` plans of your queries and know that they are operating efficiently, you might leave `DISABLE_UNSAFE_SPILLS` turned off. In that case, you know that any queries that spill will not go overboard with their memory consumption.

Limits on Query Size and Complexity

There are hardcoded limits on the maximum size and complexity of queries. Currently, the maximum number of expressions in a query is 2000. You might exceed the limits with large or deeply nested queries produced by business intelligence tools or other query generators.

If you have the ability to customize such queries or the query generation logic that produces them, replace sequences of repetitive expressions with single operators such as `IN` or `BETWEEN` that can represent multiple values or ranges. For example, instead of a large number of `OR` clauses:

```
WHERE val = 1 OR val = 2 OR val = 6 OR val = 100 ...
```

use a single `IN` clause:

```
WHERE val IN (1,2,6,100,...)
```

Scalability Considerations for Impala I/O

Impala parallelizes its I/O operations aggressively, therefore the more disks you can attach to each host, the better. Impala retrieves data from disk so quickly using bulk read operations on large blocks, that most queries are CPU-bound rather than I/O-bound.

Because the kind of sequential scanning typically done by Impala queries does not benefit much from the random-access capabilities of SSDs, spinning disks typically provide the most cost-effective kind of storage for Impala data, with little or no performance penalty as compared to SSDs.

Resource management features such as YARN, Llama, and admission control typically constrain the amount of memory, CPU, or overall number of queries in a high-concurrency environment. Currently, there is no throttling mechanism for Impala I/O.

Scalability Considerations for Table Layout

Due to the overhead of retrieving and updating table metadata in the metastore database, try to limit the number of columns in a table to a maximum of approximately 2000. Although Impala can handle wider tables than this, the metastore overhead can become significant, leading to query performance that is slower than expected based on the actual data volume.

To minimize overhead related to the metastore database and Impala query planning, try to limit the number of partitions for any partitioned table to a few tens of thousands.

If the volume of data within a table makes it impractical to run exploratory queries, consider using the `TABLESAMPLE` clause to limit query processing to only a percentage of data within the table. This technique reduces the overhead for query startup, I/O to read the data, and the amount of network, CPU, and memory needed to process intermediate results during the query. See [TABLESAMPLE Clause](#) on page 338 for details.

Kerberos-Related Network Overhead for Large Clusters

When Impala starts up, or after each `kinit` refresh, Impala sends a number of simultaneous requests to the KDC. For a cluster with 100 hosts, the KDC might be able to process all the requests within roughly 5 seconds. For a cluster with 1000 hosts, the time to process the requests would be roughly 500 seconds. Impala also makes a number of DNS requests at the same time as these Kerberos-related requests.

While these authentication requests are being processed, any submitted Impala queries will fail. During this period, the KDC and DNS may be slow to respond to requests from components other than Impala, so other secure services might be affected temporarily.

In Impala 2.12 or earlier, to reduce the frequency of the `kinit` renewal that initiates a new set of authentication requests, increase the `kerberos_reinit_interval` configuration setting for the `impalad` daemons. Currently, the default is 60 minutes. Consider using a higher value such as 360 (6 hours).

The `kerberos_reinit_interval` configuration setting is removed in Impala 3.0, and the above step is no longer needed.

Avoiding CPU Hotspots for HDFS Cached Data

You can use the HDFS caching feature, described in [Using HDFS Caching with Impala \(Impala 2.1 or higher only\)](#) on page 646, with Impala to reduce I/O and memory-to-memory copying for frequently accessed tables or partitions.

In the early days of this feature, you might have found that enabling HDFS caching resulted in little or no performance improvement, because it could result in “hotspots”: instead of the I/O to read the table data being parallelized across the cluster, the I/O was reduced but the CPU load to process the data blocks might be concentrated on a single host.

To avoid hotspots, include the `WITH REPLICATION` clause with the `CREATE TABLE` or `ALTER TABLE` statements for tables that use HDFS caching. This clause allows more than one host to cache the relevant data blocks, so the CPU load can be shared, reducing the load on any one host. See [CREATE TABLE Statement](#) on page 248 and [ALTER TABLE Statement](#) on page 215 for details.

Hotspots with high CPU load for HDFS cached data could still arise in some cases, due to the way that Impala schedules the work of processing data blocks on different hosts. In Impala 2.5 and higher, scheduling improvements mean that the work for HDFS cached data is divided better among all the hosts that have cached replicas for a particular data block. When more than one host has a cached replica for a data block, Impala assigns the work of processing that block to whichever host has done the least work (in terms of number of bytes read) for the current query. If hotspots persist even with this load-based scheduling algorithm, you can enable the query option `SCHEDULE_RANDOM_REPLICA=TRUE` to further distribute the CPU load. This setting causes Impala to randomly pick a host to process a cached data block if the scheduling algorithm encounters a tie when deciding which host has done the least work.

Scalability Considerations for File Handle Caching

One scalability aspect that affects heavily loaded clusters is the load on the metadata layer from looking up the details as each file is opened. On HDFS, that can lead to increased load on the NameNode, and on S3, this can lead to an excessive number of S3 metadata requests. For example, a query that does a full table scan on a partitioned table may need to read thousands of partitions, each partition containing multiple data files. Accessing each column of a Parquet file also involves a separate “open” call, further increasing the load on the NameNode. High NameNode overhead can add startup time (that is, increase latency) to Impala queries, and reduce overall throughput for non-Impala workloads that also require accessing HDFS files.

You can reduce the number of calls made to your file system's metadata layer by enabling the file handle caching feature. Data files that are accessed by different queries, or even multiple times within the same query, can be accessed without a new “open” call and without fetching the file details multiple times.

Impala supports file handle caching for the following file systems:

- HDFS in Impala 2.10 and higher

In Impala 3.2 and higher, file handle caching also applies to remote HDFS file handles. This is controlled by the `cache_remote_file_handles` flag for an `impalad`. It is recommended that you use the default value of `true` as this caching prevents your NameNode from overloading when your cluster has many remote HDFS reads.

- S3 in Impala 3.3 and higher

The `cache_s3_file_handles` `impalad` flag controls the S3 file handle caching. The feature is enabled by default with the flag set to `true`.

The feature is enabled by default with 20,000 file handles to be cached. To change the value, set the configuration option `max_cached_file_handles` to a non-zero value for each `impalad` daemon. From the initial default value of 20000, adjust upward if NameNode request load is still significant, or downward if it is more important to reduce the extra memory usage on each host. Each cache entry consumes 6 KB, meaning that caching 20,000 file handles requires up to 120 MB on each Impala executor. The exact memory usage varies depending on how many file handles have actually been cached; memory is freed as file handles are evicted from the cache.

If a manual operation moves a file to the trashcan while the file handle is cached, Impala still accesses the contents of that file. This is a change from prior behavior. Previously, accessing a file that was in the trashcan would cause an error. This behavior only applies to non-Impala methods of removing files, not the Impala mechanisms such as `TRUNCATE TABLE` or `DROP TABLE`.

If files are removed, replaced, or appended by operations outside of Impala, the way to bring the file information up to date is to run the `REFRESH` statement on the table.

File handle cache entries are evicted as the cache fills up, or based on a timeout period when they have not been accessed for some time.

To evaluate the effectiveness of file handle caching for a particular workload, issue the `PROFILE` statement in `impala-shell` or examine query profiles in the Impala Web UI. Look for the ratio of `CachedFileHandlesHitCount` (ideally, should be high) to `CachedFileHandlesMissCount` (ideally, should be low). Before starting any evaluation, run several representative queries to “warm up” the cache because the first time each data file is accessed is always recorded as a cache miss.

To see metrics about file handle caching for each `impalad` instance, examine the following fields on the `/metrics` page in the Impala Web UI:

- `impala-server.io.mgr.cached-file-handles-miss-count`
- `impala-server.io.mgr.num-cached-file-handles`

Scaling Limits and Guidelines

This topic lists the *scalability* limitation in Impala. For a given functional feature, it is recommended that you respect these limitations to achieve optimal scalability and performance. For example, you might be able to create a table with 2000 columns, you will experience performance problems while querying the table. This topic does not cover functional limitations in Impala.

Unless noted otherwise, the limits were tested and certified.

The limits noted as “*generally safe*” are not certified, but recommended as generally safe. A safe range is not a hard limit as unforeseen errors or troubles in your particular environment can affect the range.

Deployment Limits

- Number of Impalad Executors
 - 80 nodes in Impala 2.11 and lower
 - 150 nodes in Impala 2.12 and higher
- Number of Impalad Coordinators: 1 coordinator for at most every 50 executors
- The number of Impala clusters per deployment
 - 1 Impala cluster in Impala 3.1 and lower
 - Multiple clusters in Impala 3.2 and higher is *generally safe*.

Data Storage Limits

There are no hard limits for the following, but you will experience gradual performance degradation as you increase these numbers.

- Number of databases
- Number of tables - total, per database
- Number of partitions - total, per table
- Number of files - total, per table, per table per partition
- Number of views - total, per database
- Number of user-defined functions - total, per database
- Parquet
 - Number of columns per row group
 - Number of row groups per block
 - Number of HDFS blocks per file

Schema Design Limits

- Number of columns
 - 300 for Kudu tables
- See [Kudu Usage Limitations](#) for more information.
- 1000 for other types of tables

Security Limits

- Number of roles: 10,000 for Ranger

Query Limits - Compile Time

- Maximum number of columns in a query, included in a `SELECT` list, `INSERT`, and in an expression: no limit
- Number of tables referenced: no limit
- Number of plan nodes: no limit
- Number of plan fragments: no limit
- Depth of expression tree: 1000 hard limit
- Width of expression tree: 10,000 hard limit

Query Limits - Runtime Time

- Codegen
 - Very deeply nested expressions within queries can exceed internal Impala limits, leading to excessive memory usage. Setting the query option `disable_codegen=true` may reduce the impact, at a cost of longer query runtime.

How to Configure Impala with Dedicated Coordinators

Each host that runs the Impala Daemon acts as both a coordinator and as an executor, by default, managing metadata caching, query compilation, and query execution. In this configuration, Impala clients can connect to any Impala daemon and send query requests.

During highly concurrent workloads for large-scale queries, the dual roles can cause scalability issues because:

- The extra work required for a host to act as the coordinator could interfere with its capacity to perform other work for the later phases of the query. For example, coordinators can experience significant network and CPU overhead with queries containing a large number of query fragments. Each coordinator caches metadata for all

table partitions and data files, which requires coordinators to be configured with a large JVM heap. Executor-only Impala daemons should be configured with the default JVM heaps, which leaves more memory available to process joins, aggregations, and other operations performed by query executors.

- Having a large number of hosts act as coordinators can cause unnecessary network overhead, or even timeout errors, as each of those hosts communicates with the Statestored daemon for metadata updates.
- The "soft limits" imposed by the admission control feature are more likely to be exceeded when there are a large number of heavily loaded hosts acting as coordinators. Check [IMPALA-3649](#) and [IMPALA-6437](#) to see the status of the enhancements to mitigate this issue.

The following factors can further exacerbate the above issues:

- High number of concurrent query fragments due to query concurrency and/or query complexity
- Large metadata topic size related to the number of partitions/files/blocks
- High number of coordinator nodes
- High number of coordinators used in the same resource pool

If such scalability bottlenecks occur, in Impala 2.9 and higher, you can assign one dedicated role to each Impala daemon host, either as a coordinator or as an executor, to address the issues.

- All explicit or load-balanced client connections must go to the coordinator hosts. These hosts perform the network communication to keep metadata up-to-date and route query results to the appropriate clients. The dedicated coordinator hosts do not participate in I/O-intensive operations such as scans, and CPU-intensive operations such as aggregations.
- The executor hosts perform the intensive I/O, CPU, and memory operations that make up the bulk of the work for each query. The executors do communicate with the Statestored daemon for membership status, but the dedicated executor hosts do not process the final result sets for queries.

Using dedicated coordinators offers the following benefits:

- Reduces memory usage by limiting the number of Impala nodes that need to cache metadata.
- Provides better concurrency by avoiding coordinator bottleneck.
- Eliminates query over-admission.
- Reduces resource, especially network, utilization on the Statestored daemon by limiting metadata broadcast to a subset of nodes.
- Improves reliability and performance for highly concurrent workloads by reducing workload stress on coordinators. Dedicated coordinators require 50% or fewer connections and threads.
- Reduces the number of explicit metadata refreshes required.
- Improves diagnosability if a bottleneck or other performance issue arises on a specific host, you can narrow down the cause more easily because each host is dedicated to specific operations within the overall Impala workload.

In this configuration with dedicated coordinators / executors, you cannot connect to the dedicated executor hosts through clients such as `impala-shell` or business intelligence tools as only the coordinator nodes support client connections.

Determining the Optimal Number of Dedicated Coordinators

You should have the smallest number of coordinators that will still satisfy your workload requirements in a cluster. A rough estimation is 1 coordinator for every 50 executors.

To maintain a healthy state and optimal performance, it is recommended that you keep the peak utilization of all resources used by Impala, including CPU, the number of threads, the number of connections, and RPCs, under 80%.

Consider the following factors to determine the right number of coordinators in your cluster:

- What is the number of concurrent queries?
- What percentage of the workload is DDL?
- What is the average query resource usage at the various stages (merge, runtime filter, result set size, etc.)?
- How many Impala Daemons (`impalad`) is in the cluster?
- Is there a high availability requirement?

- Compute/storage capacity reduction factor

Start with the below set of steps to determine the initial number of coordinators:

1. If your cluster has less than 10 nodes, we recommend that you configure one dedicated coordinator. Deploy the dedicated coordinator on a DataNode to avoid losing storage capacity. In most of cases, one dedicated coordinator is enough to support all workloads on a cluster.
2. Add more coordinators if the dedicated coordinator CPU or network peak utilization is 80% or higher. You might need 1 coordinator for every 50 executors.
3. If the Impala service is shared by multiple workgroups with a dynamic resource pool assigned, use one coordinator per pool to avoid admission control over admission.
4. If high availability is required, double the number of coordinators. One set as an active set and the other as a backup set.

Advanced Tuning

Use the following guidelines to further tune the throughput and stability.

1. The concurrency of DML statements does not typically depend on the number of coordinators or size of the cluster. Queries that return large result sets (10,000+ rows) consume more CPU and memory resources on the coordinator. Add one or two coordinators if the workload has many such queries.
2. DDL queries, excluding `COMPUTE STATS` and `CREATE TABLE AS SELECT`, are executed only on coordinators. If your workload contains many DDL queries running concurrently, you could add one coordinator.
3. The CPU contention on coordinators can slow down query executions when concurrency is high, especially for very short queries (<10s). Add more coordinators to avoid CPU contention.
4. On a large cluster with 50+ nodes, the number of network connections from a coordinator to executors can grow quickly as query complexity increases. The growth is much greater on coordinators than executors. Add a few more coordinators if workloads are complex, i.e. (an average number of fragments * number of Impalad) > 500, but with the low memory/CPU usage to share the load. Watch IMPALA-4603 and IMPALA-7213 to track the progress on fixing this issue.
5. When using multiple coordinators for DML statements, divide queries to different groups (number of groups = number of coordinators). Configure a separate dynamic resource pool for each group and direct each group of query requests to a specific coordinator. This is to avoid query over admission.
6. The front-end connection requirement is not a factor in determining the number of dedicated coordinators. Consider setting up a connection pool at the client side instead of adding coordinators. For a short-term solution, you could increase the value of `fe_service_threads` on coordinators to allow more client connections.
7. In general, you should have a very small number of coordinators so storage capacity reduction is not a concern. On a very small cluster (less than 10 nodes), deploy a dedicated coordinator on a DataNode to avoid storage capacity reduction.

Estimating Coordinator Resource Usage

Resource	Safe range	Notes / CM tsquery to monitor
Memory	(Max JVM heap setting + query concurrency * query mem_limit) <= 80% of Impala process memory allocation	<i>Memory usage:</i> <pre>SELECT mem_rss WHERE entityName = "Coordinator Instance ID" AND category = ROLE</pre> <i>JVM heap usage (metadata cache):</i> <pre>SELECT impala_jvm_heap_current_usage_bytes WHERE entityName = "Coordinator Instance ID" AND category = ROLE (only in release 5.15 and above)</pre>

TCP Connection	Incoming + outgoing < 16K	<i>Incoming connection usage:</i> <pre>SELECT thrift_server_backend_connections_in_use WHERE entityName = "Coordinator Instance ID" AND category = ROLE</pre> <i>Outgoing connection usage:</i> <pre>SELECT backends_client_cache_clients_in_use WHERE entityName = "Coordinator Instance ID" AND category = ROLE</pre>
Threads	< 32K	<pre>SELECT thread_manager_running_threads WHERE entityName = "Coordinator Instance ID" AND category = ROLE</pre>
CPU	Concurrencey = non-DDL query concurrencey <= number of virtual cores allocated to Impala per node	<p>CPU usage estimation should be based on how many cores are allocated to Impala per node, not a sum of all cores of the cluster.</p> <p>It is recommended that concurrencey should not be more than the number of virtual cores allocated to Impala per node.</p> <p><i>Query concurrencey:</i></p> <pre>SELECT total_impala_num_queries_registered_across_imp WHERE entityName = "IMPALA-1" AND category = SERVICE</pre>

If usage of any of the above resources exceeds the safe range, add one more coordinator.

Deploying Dedicated Coordinators and Executors

This section describes the process to configure a dedicated coordinator and a dedicated executor roles for Impala.

- **Dedicated coordinator:** They should be on edge node with no other services running on it. They don't need large local disks but still need some that can be used for Spilling. They require at least same or even larger memory allocation.
- **(Dedicated) Executors:** They should be colocated with DataNodes as usual. The number of hosts with this setting typically increases as the cluster grows larger and handles more table partitions, data files, and concurrent queries.

To configuring dedicated coordinators/executors, you specify one of the following startup flags for the `impalad` daemon on each host:

- `##is_executor=false` for each host that does not act as an executor for Impala queries. These hosts act exclusively as query coordinators. This setting typically applies to a relatively small number of hosts, because the most common topology is to have nearly all DataNodes doing work for query execution.

- `##is_coordinator=false` for each host that does not act as a coordinator for Impala queries. These hosts act exclusively as executors. The number of hosts with this setting typically increases as the cluster grows larger and handles more table partitions, data files, and concurrent queries. As the overhead for query coordination increases, it becomes more important to centralize that work on dedicated hosts.

Metadata Management

This topic describes various knobs you can use to control how Impala manages its metadata in order to improve performance and scalability.

On-demand Metadata

In previous versions of Impala, every coordinator kept a replica of all the cache in `catalogd`, consuming large memory on each coordinator with no option to evict. Metadata always propagated through the `statestored` and suffers from head-of-line blocking, for example, one user loading a big table blocking another user loading a small table.

With this new feature, the coordinators pull metadata as needed from `catalogd` and cache it locally. The cached metadata gets evicted automatically under memory pressure.

The granularity of on-demand metadata fetches is now at the partition level between the coordinator and `catalogd`. Common use cases like add/drop partitions do not trigger unnecessary serialization/deserialization of large metadata.

This feature is disabled by default.

The feature can be used in either of the following modes.

Metadata on-demand mode

In this mode, all coordinators use the metadata on-demand.

Set the following on `catalogd`:

```
--catalog_topic_mode=minimal
```

Set the following on all `impalad` coordinators:

```
--use_local_catalog=true
```

Mixed mode

In this mode, only some coordinators are enabled to use the metadata on-demand.

We recommend that you use the mixed mode only for testing local catalog's impact on heap usage.

Set the following on `catalogd`:

```
--catalog_topic_mode=mixed
```

Set the following on `impalad` coordinators with metadata on-demand:

```
--use_local_catalog=true
```

Flags related to `use_local_catalog`

When `use_local_catalog` is enabled or set to `True` on the `impalad` coordinators the following list of flags configure various parameters as described below. It is not recommended to change the default values on these flags.

- The flag `local_catalog_cache_mb` (defaults to -1) configures the size of the catalog cache within each coordinator. With the default set to -1, the cache is auto-configured to 60% of the configured Java heap size. Note that the Java heap size is distinct from and typically smaller than the overall Impala memory limit.
- The flag `local_catalog_cache_expiration_s` (defaults to 3600) configures the expiration time of the catalog cache within each impalad. Even if the configured cache capacity has not been reached, items are removed from the cache if they have not been accessed in the defined amount of time.
- The flag `local_catalog_max_fetch_retries` (defaults to 40) configures the maximum number of retries needed for queries to fetch a metadata object from the impalad coordinator's local catalog cache.

Automatic Invalidation of Metadata Cache

To keep the size of metadata bounded, `catalogd` periodically scans all the tables and invalidates those not recently used. There are two types of configurations for `catalogd` and `impalad`.

Time-based cache invalidation

`Catalogd` invalidates tables that are not recently used in the specified time period (in seconds).

The `##invalidate_tables_timeout_s` flag needs to be applied to both `impalad` and `catalogd`.

Memory-based cache invalidation

When the memory pressure reaches 60% of JVM heap size after a Java garbage collection in `catalogd`, Impala invalidates 10% of the least recently used tables.

The `##invalidate_tables_on_memory_pressure` flag needs to be applied to both `impalad` and `catalogd`.

Automatic invalidation of metadata provides more stability with lower chances of running out of memory, but the feature could potentially cause performance issues and may require tuning.

Automatic Invalidation/Refresh of Metadata

When tools such as Hive and Spark are used to process the raw data ingested into Hive tables, new HMS metadata (database, tables, partitions) and filesystem metadata (new files in existing partitions/tables) is generated. In previous versions of Impala, in order to pick up this new information, Impala users needed to manually issue an `INVALIDATE` or `REFRESH` commands.

When automatic invalidate/refresh of metadata is enabled, `catalogd` polls Hive Metastore (HMS) notification events at a configurable interval and processes the following changes:

Note: This is a preview feature in Impala 3.3 and Impala 4.0. It is generally available and enabled by default from Impala 4.1 onwards.

- Invalidates the tables when it receives the `ALTER TABLE` event.
- Refreshes the partition when it receives the `ALTER`, `ADD`, or `DROP` partitions.
- Adds the tables or databases when it receives the `CREATE TABLE` or `CREATE DATABASE` events.

- Removes the tables from `catalogd` when it receives the `DROP TABLE` or `DROP DATABASE` events.
- Refreshes the table and partitions when it receives the `INSERT` events.

If the table is not loaded at the time of processing the `INSERT` event, the event processor does not need to refresh the table and skips it.

- Changes the database and updates `catalogd` when it receives the `ALTER DATABASE` events. The following changes are supported. This event does not invalidate the tables in the database.
 - Change the database properties
 - Change the comment on the database
 - Change the owner of the database
 - Change the default location of the database

Changing the default location of the database does not move the tables of that database to the new location. Only the new tables which are created subsequently use the default location of the database in case it is not provided in the create table statement.

This feature is controlled by the `##hms_event_polling_interval_s` flag. Start the `catalogd` with the `##hms_event_polling_interval_s` flag set to a positive integer to enable the feature and set the polling frequency in seconds. We recommend the value to be less than 5 seconds.

The following use cases are not supported:

- When you bypass HMS and add or remove data into table by adding files directly on the filesystem, HMS does not generate the `INSERT` event, and the event processor will not invalidate the corresponding table or refresh the corresponding partition.

It is recommended that you use the `LOAD DATA` command to do the data load in such cases, so that event processor can act on the events generated by the `LOAD` command.

- The Spark API that saves data to a specified location does not generate events in HMS, thus is not supported. For example:

```
Seq((1, 2)).toDF("i", "j").write.save("/user/hive/warehouse/spark_etl.db/
customers/date=01012019")
```

This feature is turned off by default with the `##hms_event_polling_interval_s` flag set to 0.

Configure HMS for Event Based Automatic Metadata Sync

To use the HMS event based metadata sync:

1. Add the following entries to the `hive-site.xml` of the Hive Metastore service.

```
<property>
  <name>hive.metastore.transactional.event.listeners</name>
  <value>org.apache.hive.hcatalog.listener.DbNotificationListener</
value>
</property>
<property>
  <name>hive.metastore.dml.events</name>
  <value>true</true>
</property>
```

2. Save `hive-site.xml`.
3. Set the `hive.metastore.dml.events` configuration key to `true` in `HiveServer2` service's `hive-site.xml`. This configuration key needs to be set to `true` in both Hive services, `HiveServer2` and `Hive Metastore`.
4. If applicable, set the `hive.metastore.dml.events` configuration key to `true` in `hive-site.xml` used by the Spark applications (typically, `/etc/hive/conf/hive-site.xml`) so that the `INSERT` events are generated when the Spark application inserts data into existing tables and partitions.
5. Restart the `HiveServer2`, `Hive Metastore`, and `Spark` (if applicable) services.

Disable Event Based Automatic Metadata Sync

When the `##hms_event_polling_interval_s` flag is set to a non-zero value for your `catalogd`, the event-based automatic invalidation is enabled for all databases and tables. If you wish to have the fine-grained control on which tables or databases need to be synced using events, you can use the `impala.disableHmsSync` property to disable the event processing at the table or database level.

When you add the `DBPROPERTIES` or `TBLPROPERTIES` with the `impala.disableHmsSync` key, the HMS event based sync is turned on or off. The value of the `impala.disableHmsSync` property determines if the event processing needs to be disabled for a particular table or database.

- If `'impala.disableHmsSync'='true'`, the events for that table or database are ignored and not synced with HMS.
- If `'impala.disableHmsSync'='false'` or if `impala.disableHmsSync` is not set, the automatic sync with HMS is enabled if the `##hms_event_polling_interval_s` global flag is set to non-zero.
- To disable the event based HMS sync for a new database, set the `impala.disableHmsSync` database properties in Hive as currently, Impala does not support setting database properties:

```
CREATE DATABASE <name> WITH DBPROPERTIES ('impala.disableHmsSync'='true');
```

- To enable or disable the event based HMS sync for a table:

```
CREATE TABLE <name> WITH TBLPROPERTIES ('impala.disableHmsSync'='true' | 'false');
```

- To change the event based HMS sync at the table level:

```
ALTER TABLE <name> WITH TBLPROPERTIES ('impala.disableHmsSync'='true' | 'false');
```

When both table and database level properties are set, the table level property takes precedence. If the table level property is not set, then the database level property is used to evaluate if the event needs to be processed or not.

If the property is changed from `true` (meaning events are skipped) to `false` (meaning events are not skipped), you need to issue a manual `INVALIDATE METADATA` command to reset event processor because it doesn't know how many events have been skipped in the past and cannot know if the object in the event is the latest. In such a case, the status of the event processor changes to `NEEDS_INVALIDATE`.

Metrics for Event Based Automatic Metadata Sync

You can use the web UI of the `catalogd` to check the state of the automatic invalidate event processor.

Under the web UI, there are two pages that presents the metrics for HMS event processor that is responsible for the event based automatic metadata sync.

- `/metrics#events`
- `/events`

This provides a detailed view of the metrics of the event processor, including min, max, mean, median, of the durations and rate metrics for all the counters listed on the `/metrics#events` page.

`/metrics#events` Page

The `/metrics#events` page provides the following metrics about the HMS event processor.

Name	Description
events-processor.avg-events-fetch-duration	Average duration to fetch a batch of events and process it.
events-processor.avg-events-process-duration	Average time taken to process a batch of events received from the Metastore.

Name	Description
events-processor.events-received	Total number of the Metastore events received.
events-processor.events-received-15min-rate	<p>Exponentially weighted moving average (EWMA) of number of events received in last 15 min.</p> <p>This rate of events can be used to determine if there are spikes in event processor activity during certain hours of the day.</p>
events-processor.events-received-1min-rate	<p>Exponentially weighted moving average (EWMA) of number of events received in last 1 min.</p> <p>This rate of events can be used to determine if there are spikes in event processor activity during certain hours of the day.</p>
events-processor.events-received-5min-rate	<p>Exponentially weighted moving average (EWMA) of number of events received in last 5 min.</p> <p>This rate of events can be used to determine if there are spikes in event processor activity during certain hours of the day.</p>
events-processor.events-skipped	<p>Total number of the Metastore events skipped.</p> <p>Events can be skipped based on certain flags are table and database level. You can use this metric to make decisions, such as:</p> <ul style="list-style-type: none"> • If most of the events are being skipped, see if you might just turn off the event processing. • If most of the events are not skipped, see if you need to add flags on certain databases.
events-processor.status	<p>Metastore event processor status to see if there are events being received or not. Possible states are:</p> <ul style="list-style-type: none"> • PAUSED The event processor is paused because catalog is being reset concurrently. • ACTIVE The event processor is scheduled at a given frequency. • ERROR The event processor is in error state and event processing has stopped. • NEEDS_INVALIDATE The event processor could not resolve certain events and needs a manual INVALIDATE command to reset the state. • STOPPED The event processing has been shutdown. No events will be processed. • DISABLED The event processor is not configured to run.

Resource Management

Impala includes the features that balance and maximize resources in your Apache Hadoop cluster. This topic describes how you can improve efficiency of your a Apache Hadoop cluster using the admission control feature. See the following topics for an overview and the configuration steps for admission control.

Admission Control and Query Queuing

Admission control is an Impala feature that imposes limits on concurrent SQL queries, to avoid resource usage spikes and out-of-memory conditions on busy clusters. The admission control feature lets you set an upper limit on the number of concurrent Impala queries and on the memory used by those queries. Any additional queries are queued until the earlier ones finish, rather than being cancelled or running slowly and causing contention. As other queries finish, the queued queries are allowed to proceed.

In Impala 2.5 and higher, you can specify these limits and thresholds for each pool rather than globally. That way, you can balance the resource usage and throughput between steady well-defined workloads, rare resource-intensive queries, and ad-hoc exploratory queries.

In addition to the threshold values for currently executing queries, you can place limits on the maximum number of queries that are queued (waiting) and a limit on the amount of time they might wait before returning with an error. These queue settings let you ensure that queries do not wait indefinitely so that you can detect and correct “starvation” scenarios.

Queries, DML statements, and some DDL statements, including `CREATE TABLE AS SELECT` and `COMPUTE STATS` are affected by admission control.

On a busy cluster, you might find there is an optimal number of Impala queries that run concurrently. For example, when the I/O capacity is fully utilized by I/O-intensive queries, you might not find any throughput benefit in running more concurrent queries. By allowing some queries to run at full speed while others wait, rather than having all queries contend for resources and run slowly, admission control can result in higher overall throughput.

For another example, consider a memory-bound workload such as many large joins or aggregation queries. Each such query could briefly use many gigabytes of memory to process intermediate results. Because Impala by default cancels queries that exceed the specified memory limit, running multiple large-scale queries at once might require re-running some queries that are cancelled. In this case, admission control improves the reliability and stability of the overall workload by only allowing as many concurrent queries as the overall memory of the cluster can accommodate.

Concurrent Queries and Admission Control

One way to limit resource usage through admission control is to set an upper limit on the number of concurrent queries. This is the initial technique you might use when you do not have extensive information about memory usage for your workload. The settings can be specified separately for each dynamic resource pool.

Max Running Queries

Maximum number of concurrently running queries in this pool. The default value is unlimited for Impala 2.5 or higher. (optional)

The maximum number of queries that can run concurrently in this pool. The default value is unlimited. Any queries for this pool that exceed **Max Running Queries** are added to the admission control queue until other queries finish. You can use **Max Running Queries** in the early stages of resource management, when you do not have extensive data about query memory usage,

to determine if the cluster performs better overall if throttling is applied to Impala queries.

For a workload with many small queries, you typically specify a high value for this setting, or leave the default setting of “unlimited”. For a workload with expensive queries, where some number of concurrent queries saturate the memory, I/O, CPU, or network capacity of the cluster, set the value low enough that the cluster resources are not overcommitted for Impala.

Once you have enabled memory-based admission control using other pool settings, you can still use **Max Running Queries** as a safeguard. If queries exceed either the total estimated memory or the maximum number of concurrent queries, they are added to the queue.

Max Queued Queries

Maximum number of queries that can be queued in this pool. The default value is 200 for Impala 2.1 or higher and 50 for previous versions of Impala. (optional)

Queue Timeout

The amount of time, in milliseconds, that a query waits in the admission control queue for this pool before being canceled. The default value is 60,000 milliseconds.

In the following cases, **Queue Timeout** is not significant, and you can specify a high value to avoid canceling queries unexpectedly:

- In a low-concurrency workload where few or no queries are queued
- In an environment without a strict SLA, where it does not matter if queries occasionally take longer than usual because they are held in admission control

You might also need to increase the value to use Impala with some business intelligence tools that have their own timeout intervals for queries.

In a high-concurrency workload, especially for queries with a tight SLA, long wait times in admission control can cause a serious problem. For example, if a query needs to run in 10 seconds, and you have tuned it so that it runs in 8 seconds, it violates its SLA if it waits in the admission control queue longer than 2 seconds. In a case like this, set a low timeout value and monitor how many queries are cancelled because of timeouts. This technique helps you to discover capacity, tuning, and scaling problems early, and helps avoid wasting resources by running expensive queries that have already missed their SLA.

If you identify some queries that can have a high timeout value, and others that benefit from a low timeout value, you can create separate pools with different values for this setting.

You can combine these settings with the memory-based approach described in [Memory Limits and Admission Control](#) on page 677. If either the maximum number of or the expected memory usage of the concurrent queries is exceeded, subsequent queries are queued until the concurrent workload falls below the threshold again.

Memory Limits and Admission Control

Each dynamic resource pool can have an upper limit on the cluster-wide memory used by queries executing in that pool. This is the technique to use once you have a stable workload with well-understood memory requirements.

Use the following settings to manage memory-based admission control.

Max Memory

The maximum amount of aggregate memory available across the cluster to all queries executing in this pool. This should be a portion of the aggregate configured memory for Impala daemons, which will be shown in the settings dialog next to this option for convenience. Setting this to a non-zero value enables memory based admission control.

Impala determines the expected maximum memory used by all queries in the pool and holds back any further queries that would result in Max Memory being exceeded.

You set Max Memory in `fair-scheduler.xml` file with the `maxResources` tag. For example:

```
<maxResources>2500 mb</maxResources>
```

If you specify Max Memory, you should specify the amount of memory to allocate to each query in this pool. You can do this in two ways:

- By setting Maximum Query Memory Limit and Minimum Query Memory Limit. This is preferred in Impala 3.1 and greater and gives Impala flexibility to set aside more memory to queries that are expected to be memory-hungry.
- By setting Default Query Memory Limit to the exact amount of memory that Impala should set aside for queries in that pool.

Note that in the following cases, Impala will rely entirely on memory estimates to determine how much memory to set aside for each query. This is not recommended because it can result in queries not running or being starved for memory if the estimates are inaccurate. And it can affect other queries running on the same node.

- Max Memory, Maximum Query Memory Limit, and Minimum Query Memory Limit are not set, and the `MEM_LIMIT` query option is not set for the query.
- Default Query Memory Limit is set to 0, and the `MEM_LIMIT` query option is not set for the query.

Minimum Query Memory Limit and Maximum Query Memory Limit

These two options determine the minimum and maximum per-host memory limit that will be chosen by Impala Admission control for queries in this resource pool. If set, Impala Admission Control will choose a memory limit between the minimum and maximum values based on the per-host memory estimate for the

query. The memory limit chosen determines the amount of memory that Impala Admission control will set aside for this query on each host that the query is running on. The aggregate memory across all of the hosts that the query is running on is counted against the pool's Max Memory.

Minimum Query Memory Limit must be less than or equal to Maximum Query Memory Limit and Max Memory.

A user can override Impala's choice of memory limit by setting the `MEM_LIMIT` query option. If the `Clamp MEM_LIMIT Query Option` setting is set to `TRUE` and the user sets `MEM_LIMIT` to a value that is outside of the range specified by these two options, then the effective memory limit will be either the minimum or maximum, depending on whether `MEM_LIMIT` is lower than or higher the range.

For example, assume a resource pool with the following parameters set:

- Minimum Query Memory Limit = 2GB
- Maximum Query Memory Limit = 10GB

If a user tries to submit a query with the `MEM_LIMIT` query option set to 14 GB, the following would happen:

- If `Clamp MEM_LIMIT Query Option` = `true`, admission controller would override `MEM_LIMIT` with 10 GB and attempt admission using that value.
- If `Clamp MEM_LIMIT Query Option` = `false`, the admission controller will retain the `MEM_LIMIT` of 14 GB set by the user and will attempt admission using the value.

Default Query Memory Limit

The default memory limit applied to queries executing in this pool when no explicit `MEM_LIMIT` query option is set. The memory limit chosen determines the amount of memory that Impala Admission control will set aside for this query on each host that the query is running on. The aggregate memory across all of the hosts that the query is running on is counted against the pool's Max Memory. This option is deprecated in Impala 3.1 and higher and is replaced by Maximum Query Memory Limit and Minimum Query Memory Limit. Do not set this if either Maximum Query Memory Limit or Minimum Query Memory Limit is set.

Clamp MEM_LIMIT Query Option

If this field is not selected, the `MEM_LIMIT` query option will not be bounded by the **Maximum Query Memory Limit** and the **Minimum Query Memory Limit** values specified for this resource pool. By default, this field is selected in Impala 3.1 and higher. The field is disabled if both **Minimum Query Memory Limit** and **Maximum Query Memory Limit** are not set.

For example, consider the following scenario:

- The cluster is running `impalad` daemons on five hosts.
- A dynamic resource pool has Max Memory set to 100 GB.
- The Maximum Query Memory Limit for the pool is 10 GB and Minimum Query Memory Limit is 2 GB. Therefore, any query running in this pool could use up to 50 GB of memory (Maximum Query Memory Limit * number of Impala nodes).
- Impala will execute varying numbers of queries concurrently because queries may be given memory limits anywhere between 2 GB and 10 GB, depending on the estimated memory requirements. For example, Impala may execute up to 10 small queries with 2 GB memory limits or two large queries with 10 GB memory limits because that is what will fit in the 100 GB cluster-wide limit when executing on five hosts.
- The executing queries may use less memory than the per-host memory limit or the Max Memory cluster-wide limit if they do not need that much memory. In general this is not a problem so long as you are able to execute enough queries concurrently to meet your needs.

You can combine the memory-based settings with the upper limit on concurrent queries described in [Concurrent Queries and Admission Control](#) on page 675. If either the maximum number of or the expected memory usage of the concurrent queries is exceeded, subsequent queries are queued until the concurrent workload falls below the threshold again.

Setting Per-query Memory Limits

Use per-query memory limits to prevent queries from consuming excessive memory resources that impact other queries. We recommend that you set the query memory limits whenever possible.

If you set the **Max Memory** for a resource pool, Impala attempts to throttle queries if there is not enough memory to run them within the specified resources.

Only use admission control with maximum memory resources if you can ensure there are query memory limits. Set the pool **Maximum Query Memory Limit** to be certain. You can override this setting with the `MEM_LIMIT` query option, if necessary.

Typically, you set query memory limits using the `set MEM_LIMIT=Xg;` query option. When you find the right value for your business case, memory-based admission control works well. The potential downside is that queries that attempt to use more memory might perform poorly or even be cancelled.

How Impala Admission Control Relates to Other Resource Management Tools

The admission control feature is similar in some ways to the YARN resource management framework. These features can be used separately or together. This section describes some similarities and differences, to help you decide which combination of resource management features to use for Impala.

Admission control is a lightweight, decentralized system that is suitable for workloads consisting primarily of Impala queries and other SQL statements. It sets “soft” limits that smooth out Impala memory usage during times of heavy load, rather than taking an all-or-nothing approach that cancels jobs that are too resource-intensive.

Because the admission control system does not interact with other Hadoop workloads such as MapReduce jobs, you might use YARN with static service pools on clusters where resources are shared between Impala and other Hadoop components. This configuration is recommended when using Impala in a *multitenant* cluster. Devote a percentage of cluster resources to Impala, and allocate another percentage for MapReduce and other batch-style workloads. Let admission control handle the concurrency and memory usage for the Impala work within the cluster, and let YARN manage the work for other components within the cluster. In this scenario, Impala's resources are not managed by YARN.

The Impala admission control feature uses the same configuration mechanism as the YARN resource manager to map users to pools and authenticate them.

Although the Impala admission control feature uses a `fair-scheduler.xml` configuration file behind the scenes, this file does not depend on which scheduler is used for YARN. You still use this file even when YARN is using the capacity scheduler.

How Impala Schedules and Enforces Limits on Concurrent Queries

The admission control system is decentralized, embedded in each Impala daemon and communicating through the statestore mechanism. Although the limits you set for memory usage and number of concurrent queries apply cluster-wide, each Impala daemon makes its own decisions about whether to allow each query to run immediately or to queue it for a less-busy time. These decisions are fast, meaning the admission control mechanism is low-overhead, but might be imprecise during times of heavy load across many coordinators. There could be times when the more queries were queued (in aggregate across the cluster) than the specified limit, or when number of admitted queries exceeds the expected number. Thus, you typically err on the high side for the size of the queue, because there is not a big penalty for having a large number of queued queries; and you typically err on the low side for configuring memory resources, to leave some headroom in case more queries are admitted than expected, without running out of memory and being cancelled as a result.

To avoid a large backlog of queued requests, you can set an upper limit on the size of the queue for queries that are queued. When the number of queued queries exceeds this limit, further queries are cancelled rather than being queued. You can also configure a timeout period per pool, after which queued queries are cancelled, to avoid indefinite waits. If a cluster reaches this state where queries are cancelled due to too many concurrent requests or long waits for query execution to begin, that is a signal for an administrator to take action, either by provisioning more resources, scheduling work on the cluster to smooth out the load, or by doing [Impala performance tuning](#) to enable higher throughput.

How Admission Control works with Impala Clients (JDBC, ODBC, HiveServer2)

Most aspects of admission control work transparently with client interfaces such as JDBC and ODBC:

- If a SQL statement is put into a queue rather than running immediately, the API call blocks until the statement is dequeued and begins execution. At that point, the client program can request to fetch results, which might also block until results become available.
- If a SQL statement is cancelled because it has been queued for too long or because it exceeded the memory limit during execution, the error is returned to the client program with a descriptive error message.

In Impala 2.0 and higher, you can submit a SQL `SET` statement from the client application to change the `REQUEST_POOL` query option. This option lets you submit queries to different resource pools, as described in [REQUEST_POOL Query Option](#) on page 386.

At any time, the set of queued queries could include queries submitted through multiple different Impala daemon hosts. All the queries submitted through a particular host will be executed in order, so a `CREATE TABLE` followed by an `INSERT` on the same table would succeed. Queries submitted through different hosts are not guaranteed to be executed in the order they were received. Therefore, if you are using load-balancing or other round-robin scheduling where different statements are submitted through different hosts, set up all table structures ahead of time so that the statements controlled by the queuing system are primarily queries, where order is not significant. Or, if a sequence of statements needs to happen in strict order (such as an `INSERT` followed by a `SELECT`), submit all those statements through a single session, while connected to the same Impala daemon host.

Admission control has the following limitations or special behavior when used with JDBC or ODBC applications:

- The other resource-related query options, `RESERVATION_REQUEST_TIMEOUT` and `V_CPU_CORES`, are no longer used. Those query options only applied to using Impala with Llama, which is no longer supported.

SQL and Schema Considerations for Admission Control

When queries complete quickly and are tuned for optimal memory usage, there is less chance of performance or capacity problems during times of heavy load. Before setting up admission control, tune your Impala queries to ensure that the query plans are efficient and the memory estimates are accurate. Understanding the nature of your workload, and which queries are the most resource-intensive, helps you to plan how to divide the queries into different pools and decide what limits to define for each pool.

For large tables, especially those involved in join queries, keep their statistics up to date after loading substantial amounts of new data or adding new partitions. Use the `COMPUTE STATS` statement for unpartitioned tables, and `COMPUTE INCREMENTAL STATS` for partitioned tables.

When you use dynamic resource pools with a **Max Memory** setting enabled, you typically override the memory estimates that Impala makes based on the statistics from the `COMPUTE STATS` statement. You either set the `MEM_LIMIT` query option within a particular session to set an upper memory limit for queries within that session, or a default `MEM_LIMIT` setting for all queries processed by the `impalad` instance, or a default `MEM_LIMIT` setting for all queries assigned to a particular dynamic resource pool. By designating a consistent memory limit for a set of similar queries that use the same resource pool, you avoid unnecessary query queuing or out-of-memory conditions that can arise during high-concurrency workloads when memory estimates for some queries are inaccurate.

Follow other steps from [Tuning Impala for Performance](#) on page 614 to tune your queries.

Guidelines for Using Admission Control

The limits imposed by admission control are de-centrally managed “soft” limits. Each Impala coordinator node makes its own decisions about whether to allow queries to run immediately or to queue them. These decisions rely on information passed back and forth between nodes by the StateStore service. If a sudden surge in requests causes more queries than anticipated to run concurrently, then the throughput could decrease due to queries spilling to disk or contending for resources. Or queries could be cancelled if they exceed the `MEM_LIMIT` setting while running.

In `impala-shell`, you can also specify which resource pool to direct queries to by setting the `REQUEST_POOL` query option.

To see how admission control works for particular queries, examine the profile output or the summary output for the query.

- Profile

The information is available through the `PROFILE` statement in `impala-shell` immediately after running a query in the shell, on the **queries** page of the Impala debug web UI, or in the Impala log file (basic information at log level 1, more detailed information at log level 2).

The profile output contains details about the admission decision, such as whether the query was queued or not and which resource pool it was assigned to. It also includes the estimated and actual memory usage for the query, so you can fine-tune the configuration for the memory limits of the resource pools.

- Summary

Starting in Impala 3.1, the information is available in `impala-shell` when the `LIVE_PROGRESS` or `LIVE_SUMMARY` query option is set to `TRUE`.

You can also start an `impala-shell` session with the `--live_progress` or `--live_summary` flags to monitor all queries in that `impala-shell` session.

The summary output includes the queuing status consisting of whether the query was queued and what was the latest queuing reason.

For details about all the Fair Scheduler configuration settings, see [Fair Scheduler Configuration](#), in particular the tags such as `<queue>` and `<aclSubmitApps>` to map users and groups to particular resource pools (queues).

Configuring Admission Control

Impala includes features that balance and maximize resources in your Apache Hadoop cluster. This topic describes how you can improve efficiency of your a Apache Hadoop cluster using those features.

The configuration options for admission control range from the simple (a single resource pool with a single set of options) to the complex (multiple resource pools with different options, each pool handling queries for a different set of users and groups).

Configuring Admission Control in Command Line Interface

To configure admission control, use a combination of startup options for the Impala daemon and edit or create the configuration files `fair-scheduler.xml` and `llama-site.xml`.

For a straightforward configuration using a single resource pool named `default`, you can specify configuration options on the command line and skip the `fair-scheduler.xml` and `llama-site.xml` configuration files.

For an advanced configuration with multiple resource pools using different settings:

1. Set up the `fair-scheduler.xml` and `llama-site.xml` configuration files manually.
2. Provide the paths to each one using the `impalad` command-line options, `##fair_scheduler_allocation_path` and `##llama_site_path` respectively.

The Impala admission control feature uses the Fair Scheduler configuration settings to determine how to map users and groups to different resource pools. For example, you might set up different resource pools with separate memory limits, and maximum number of concurrent and queued queries, for different categories of users within your organization. For details about all the Fair Scheduler configuration settings, see the [Apache wiki](#).

The Impala admission control feature uses a small subset of possible settings from the `llama-site.xml` configuration file:

```
llama.am.throttling.maximum.placed.reservations.queue_name
llama.am.throttling.maximum.queued.reservations.queue_name
impala.admission-control.pool-default-query-options.queue_name
impala.admission-control.pool-queue-timeout-ms.queue_name
```

The `impala.admission-control.pool-queue-timeout-ms` setting specifies the timeout value for this pool in milliseconds.

The `impala.admission-control.pool-default-query-options` settings designates the default query options for all queries that run in this pool. Its argument value is a comma-delimited string of 'key=value' pairs, 'key1=val1,key2=val2, ...'. For example, this is where you might set a default memory limit for all queries in the pool, using an argument such as `MEM_LIMIT=5G`.

The `impala.admission-control.*` configuration settings are available in Impala 2.5 and higher.

Example of Admission Control Configuration

Here are sample `fair-scheduler.xml` and `llama-site.xml` files that define resource pools `root.default`, `root.development`, and `root.production`. These files define resource pools for Impala admission control and are separate from the similar `fair-scheduler.xml` that defines resource pools for YARN.

fair-scheduler.xml:

Although Impala does not use the `vcores` value, you must still specify it to satisfy YARN requirements for the file contents.

Each `<aclSubmitApps>` tag (other than the one for `root`) contains a comma-separated list of users, then a space, then a comma-separated list of groups; these are the users and groups allowed to submit Impala statements to the corresponding resource pool.

If you leave the `<aclSubmitApps>` element empty for a pool, nobody can submit directly to that pool; child pools can specify their own `<aclSubmitApps>` values to authorize users and groups to submit to those pools.

```
<allocations>

  <queue name="root">
    <aclSubmitApps> </aclSubmitApps>
    <queue name="default">
      <maxResources>50000 mb, 0 vcores</maxResources>
      <aclSubmitApps>*</aclSubmitApps>
    </queue>
    <queue name="development">
      <maxResources>200000 mb, 0 vcores</maxResources>
      <aclSubmitApps>user1,user2 dev,ops,admin</aclSubmitApps>
    </queue>
    <queue name="production">
      <maxResources>1000000 mb, 0 vcores</maxResources>
```

```

        <aclSubmitApps> ops,admin</aclSubmitApps>
    </queue>
</queue>
<queuePlacementPolicy>
    <rule name="specified" create="false"/>
    <rule name="default" />
</queuePlacementPolicy>
</allocations>

```

llama-site.xml:

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <property>
    <name>llama.am.throttling.maximum.placed.reservations.root.default</name>
    <value>10</value>
  </property>
  <property>
    <name>llama.am.throttling.maximum.queued.reservations.root.default</name>
    <value>50</value>
  </property>
  <property>
    <name>impala.admission-control.pool-default-query-options.root.default</name>
    <value>mem_limit=128m,query_timeout_s=20,max_io_buffers=10</value>
  </property>
  <property>
    <name>impala.admission-control.pool-queue-timeout-ms.root.default</name>
    <value>30000</value>
  </property>
  <property>
    <name>impala.admission-control.max-query-mem-limit.root.default.regularPool</name>
    <value>1610612736</value><!--1.5GB-->
  </property>
  <property>
    <name>impala.admission-control.min-query-mem-limit.root.default.regularPool</name>
    <value>52428800</value><!--50MB-->
  </property>
  <property>
    <name>impala.admission-control.clamp-mem-limit-query-option.root.default.regularPool</name>
    <value>true</value>
  </property>
  <property>
    <name>impala.admission-control.max-query-cpu-core-per-node-limit.root.default.regularPool</name>
    <value>8</value>
  </property>
  <property>
    <name>impala.admission-control.max-query-cpu-core-coordinator-limit.root.default.regularPool</name>
    <value>8</value>
  </property>
</configuration>

```

Configuring Cluster-wide Admission Control

Important: These settings only apply if you enable admission control but leave dynamic resource pools disabled. In Impala 2.5 and higher, we recommend that you set up dynamic resource pools and customize the settings for each pool as described in [Configuring Admission Control in Command Line Interface](#) on page 681.

The following Impala configuration options let you adjust the settings of the admission control feature. When supplying the options on the `impalad` command line, prepend the option name with `--`.

`queue_wait_timeout_ms`

Purpose: Maximum amount of time (in milliseconds) that a request waits to be admitted before timing out.

Type: `int64`

Default: 60000

`default_pool_max_requests`

Purpose: Maximum number of concurrent outstanding requests allowed to run before incoming requests are queued. Because this limit applies cluster-wide, but each Impala node makes independent decisions to run queries immediately or queue them, it is a soft limit; the overall number of concurrent queries might be slightly higher during times of heavy load. A negative value indicates no limit. Ignored if `fair_scheduler_config_path` and `llama_site_path` are set.

Type: `int64`

Default: -1, meaning unlimited (prior to Impala 2.5 the default was 200)

`default_pool_max_queued`

Purpose: Maximum number of requests allowed to be queued before rejecting requests. Because this limit applies cluster-wide, but each Impala node makes independent decisions to run queries immediately or queue them, it is a soft limit; the overall number of queued queries might be slightly higher during times of heavy load. A negative value or 0 indicates requests are always rejected once the maximum concurrent requests are executing. Ignored if `fair_scheduler_config_path` and `llama_site_path` are set.

Type: `int64`

Default: unlimited

`default_pool_mem_limit`

Purpose: Maximum amount of memory (across the entire cluster) that all outstanding requests in this pool can use before new requests to this pool are queued. Specified in bytes, megabytes, or gigabytes by a number followed by the suffix `b` (optional), `m`, or `g`, either uppercase or lowercase. You can specify floating-point values for megabytes and gigabytes, to represent fractional numbers such as `1.5`. You can also specify it as a percentage of the physical memory by specifying the suffix `%`. 0 or no setting indicates no limit. Defaults to bytes if no unit is given. Because this limit applies cluster-wide, but each Impala node makes independent decisions to run queries immediately or queue them, it is a soft limit; the overall memory used by concurrent

queries might be slightly higher during times of heavy load. Ignored if `fair_scheduler_config_path` and `llama_site_path` are set.

Note: Impala relies on the statistics produced by the `COMPUTE STATS` statement to estimate memory usage for each query. See [COMPUTE STATS Statement](#) on page 232 for guidelines about how and when to use this statement.

Type: string

Default: " " (empty string, meaning unlimited)

`disable_pool_max_requests`

Purpose: Disables all per-pool limits on the maximum number of running requests.

Type: Boolean

Default: false

`disable_pool_mem_limits`

Purpose: Disables all per-pool mem limits.

Type: Boolean

Default: false

`fair_scheduler_allocation_path`

Purpose: Path to the fair scheduler allocation file (`fair-scheduler.xml`).

Type: string

Default: " " (empty string)

Usage notes: Admission control only uses a small subset of the settings that can go in this file, as described below. For details about all the Fair Scheduler configuration settings, see the [Apache wiki](#).

`llama_site_path`

Purpose: Path to the configuration file used by admission control (`llama-site.xml`). If set, `fair_scheduler_allocation_path` must also be set.

Type: string

Default: " " (empty string)

Usage notes: Admission control only uses a few of the settings that can go in this file, as described below.

Partitioning for Impala Tables

By default, all the data files for a table are located in a single directory. Partitioning is a technique for physically dividing the data during loading, based on values from one or more columns, to speed up queries that test those columns. For example, with a `school_records` table partitioned on a `year` column, there is a separate data directory for each different year value, and all the data for that year is stored in a data file in that directory. A query that includes a `WHERE` condition such as `YEAR=1966`, `YEAR IN (1989,1999)`, or `YEAR BETWEEN 1984 AND 1989` can examine only the data files from the appropriate directory or directories, greatly reducing the amount of data to read and test.

See [Attaching an External Partitioned Table to an HDFS Directory Structure](#) on page 48 for an example that illustrates the syntax for creating partitioned tables, the underlying directory structure in HDFS, and how to attach a partitioned Impala external table to data files stored elsewhere in HDFS.

Parquet is a popular format for partitioned Impala tables because it is well suited to handle huge data volumes. See [Query Performance for Impala Parquet Tables](#) on page 707 for performance considerations for partitioned Parquet tables.

See [NULL](#) on page 177 for details about how NULL values are represented in partitioned tables.

See [Using Impala with Amazon S3 Object Store](#) on page 769 for details about setting up tables where some or all partitions reside on the Amazon Simple Storage Service (S3).

When to Use Partitioned Tables

Partitioning is typically appropriate for:

- Tables that are very large, where reading the entire data set takes an impractical amount of time.
- Tables that are always or almost always queried with conditions on the partitioning columns. In our example of a table partitioned by year, `SELECT COUNT(*) FROM school_records WHERE year = 1985` is efficient, only examining a small fraction of the data; but `SELECT COUNT(*) FROM school_records` has to process a separate data file for each year, resulting in more overall work than in an unpartitioned table. You would probably not partition this way if you frequently queried the table based on last name, student ID, and so on without testing the year.
- Columns that have reasonable cardinality (number of different values). If a column only has a small number of values, for example Male or Female, you do not gain much efficiency by eliminating only about 50% of the data to read for each query. If a column has only a few rows matching each value, the number of directories to process can become a limiting factor, and the data file in each directory could be too small to take advantage of the Hadoop mechanism for transmitting data in multi-megabyte blocks. For example, you might partition census data by year, store sales data by year and month, and web traffic data by year, month, and day. (Some users with high volumes of incoming data might even partition down to the individual hour and minute.)
- Data that already passes through an extract, transform, and load (ETL) pipeline. The values of the partitioning columns are stripped from the original data files and represented by directory names, so loading data into a partitioned table involves some sort of transformation or preprocessing.

SQL Statements for Partitioned Tables

In terms of Impala SQL syntax, partitioning affects these statements:

- [CREATE TABLE](#): you specify a `PARTITIONED BY` clause when creating the table to identify names and data types of the partitioning columns. These columns are not included in the main list of columns for the table.
- In Impala 2.5 and higher, you can also use the `PARTITIONED BY` clause in a `CREATE TABLE AS SELECT` statement. This syntax lets you use a single statement to create a partitioned table, copy data into it, and create new partitions based on the values in the inserted data.
- [ALTER TABLE](#): you can add or drop partitions, to work with different portions of a huge data set. You can designate the HDFS directory that holds the data files for a specific partition. With data partitioned by date values, you might “age out” data that is no longer relevant.

Note: If you are creating a partition for the first time and specifying its location, for maximum efficiency, use a single `ALTER TABLE` statement including both the `ADD PARTITION` and `LOCATION` clauses, rather than separate statements with `ADD PARTITION` and `SET LOCATION` clauses.

- [INSERT](#): When you insert data into a partitioned table, you identify the partitioning columns. One or more values from each inserted row are not stored in data files, but instead determine the directory where that row value is stored. You can also specify which partition to load a set of data into, with `INSERT OVERWRITE` statements; you can replace the contents of a specific partition but you cannot append data to a specific partition.

By default, if an `INSERT` statement creates any new subdirectories underneath a partitioned table, those subdirectories are assigned default HDFS permissions for the `impala` user. To make each subdirectory have the same permissions as its parent directory in HDFS, specify the `##insert_inherit_permissions` startup option for the `impalad` daemon.

- Although the syntax of the [SELECT](#) statement is the same whether or not the table is partitioned, the way queries interact with partitioned tables can have a dramatic impact on performance and scalability. The mechanism that lets queries skip certain partitions during a query is known as partition pruning; see [Partition Pruning for Queries](#) on page 688 for details.
- In Impala 1.4 and later, there is a `SHOW PARTITIONS` statement that displays information about each partition in a table. See [SHOW Statement](#) on page 395 for details.

Static and Dynamic Partitioning Clauses

Specifying all the partition columns in a SQL statement is called *static partitioning*, because the statement affects a single predictable partition. For example, you use static partitioning with an `ALTER TABLE` statement that affects only one partition, or with an `INSERT` statement that inserts all values into the same partition:

```
insert into t1 partition(x=10, y='a') select c1 from some_other_table;
```

When you specify some partition key columns in an `INSERT` statement, but leave out the values, Impala determines which partition to insert. This technique is called *dynamic partitioning*:

```
insert into t1 partition(x, y='b') select c1, c2 from some_other_table;
-- Create new partition if necessary based on variable year, month, and day;
insert a single value.
insert into weather partition (year, month, day) select 'cloudy',2014,4,21;
-- Create new partition if necessary for specified year and month but
variable day; insert a single value.
insert into weather partition (year=2014, month=04, day) select 'sunny',22;
```

The more key columns you specify in the `PARTITION` clause, the fewer columns you need in the `SELECT` list. The trailing columns in the `SELECT` list are substituted in order for the partition key columns with no specified value.

Refreshing a Single Partition

The `REFRESH` statement is typically used with partitioned tables when new data files are loaded into a partition by some non-Impala mechanism, such as a Hive or Spark job. The `REFRESH` statement makes Impala aware of the new data files so that they can be used in Impala queries. Because partitioned tables typically contain a high volume of data, the `REFRESH` operation for a full partitioned table can take significant time.

In Impala 2.7 and higher, you can include a `PARTITION (partition_spec)` clause in the `REFRESH` statement so that only a single partition is refreshed. For example, `REFRESH big_table PARTITION (year=2017, month=9, day=30)`. The partition spec must include all the partition key columns. See [REFRESH Statement](#) on page 312 for more details and examples of `REFRESH` syntax and usage.

Permissions for Partition Subdirectories

By default, if an `INSERT` statement creates any new subdirectories underneath a partitioned table, those subdirectories are assigned default HDFS permissions for the `impala` user. To make each subdirectory have the same permissions as its parent directory in HDFS, specify the `##insert_inherit_permissions` startup option for the `impalad` daemon.

Partition Pruning for Queries

Partition pruning refers to the mechanism where a query can skip reading the data files corresponding to one or more partitions. If you can arrange for queries to prune large numbers of unnecessary partitions from the query execution plan, the queries use fewer resources and are thus proportionally faster and more scalable.

For example, if a table is partitioned by columns YEAR, MONTH, and DAY, then WHERE clauses such as WHERE year = 2013, WHERE year < 2010, or WHERE year BETWEEN 1995 AND 1998 allow Impala to skip the data files in all partitions outside the specified range. Likewise, WHERE year = 2013 AND month BETWEEN 1 AND 3 could prune even more partitions, reading the data files for only a portion of one year.

Checking if Partition Pruning Happens for a Query

To check the effectiveness of partition pruning for a query, check the EXPLAIN output for the query before running it. For example, this example shows a table with 3 partitions, where the query only reads 1 of them. The notation #partitions=1/3 in the EXPLAIN plan confirms that Impala can do the appropriate partition pruning.

```
[localhost:21000] > insert into census partition (year=2010) values
('Smith'),('Jones');
[localhost:21000] > insert into census partition (year=2011) values
('Smith'),('Jones'),('Doe');
[localhost:21000] > insert into census partition (year=2012) values
('Smith'),('Doe');
[localhost:21000] > select name from census where year=2010;
+-----+
| name |
+-----+
| Smith|
| Jones|
+-----+
[localhost:21000] > explain select name from census where year=2010;
+-----+
| Explain String |
+-----+
| PLAN FRAGMENT 0 |
| PARTITION: UNPARTITIONED |
| 1:EXCHANGE |
| PLAN FRAGMENT 1 |
| PARTITION: RANDOM |
| STREAM DATA SINK |
| EXCHANGE ID: 1 |
| UNPARTITIONED |
| 0:SCAN HDFS |
| table=predicate_propagation.census #partitions=1/3 size=12B |
+-----+
```

For a report of the volume of data that was actually read and processed at each stage of the query, check the output of the SUMMARY command immediately after running the query. For a more detailed analysis, look at the output of the PROFILE command; it includes this same summary report near the start of the profile output.

What SQL Constructs Work with Partition Pruning

Impala can even do partition pruning in cases where the partition key column is not directly compared to a constant, by applying the transitive property to other parts of the WHERE clause. This technique is known as predicate propagation, and is available in Impala 1.2.2 and later. In this example, the census table includes another column

indicating when the data was collected, which happens in 10-year intervals. Even though the query does not compare the partition key column (YEAR) to a constant value, Impala can deduce that only the partition YEAR=2010 is required, and again only reads 1 out of 3 partitions.

```
[localhost:21000] > drop table census;
[localhost:21000] > create table census (name string, census_year int)
partitioned by (year int);
[localhost:21000] > insert into census partition (year=2010) values
('Smith',2010),('Jones',2010);
[localhost:21000] > insert into census partition (year=2011) values
('Smith',2020),('Jones',2020),('Doe',2020);
[localhost:21000] > insert into census partition (year=2012) values
('Smith',2020),('Doe',2020);
[localhost:21000] > select name from census where year = census_year and
census_year=2010;
+-----+
| name |
+-----+
| Smith |
| Jones |
+-----+
[localhost:21000] > explain select name from census where year = census_year
and census_year=2010;
+-----+
| Explain String |
+-----+
| PLAN FRAGMENT 0
|   PARTITION: UNPARTITIONED
|
|   1:EXCHANGE
|
| PLAN FRAGMENT 1
|   PARTITION: RANDOM
|
|   STREAM DATA SINK
|     EXCHANGE ID: 1
|     UNPARTITIONED
|
|   0:SCAN HDFS
|     table=predicate_propagation.census #partitions=1/3 size=22B
|     predicates: census_year = 2010, year = census_year
+-----+
```

If a view applies to a partitioned table, any partition pruning considers the clauses on both the original query and any additional WHERE predicates in the query that refers to the view. Prior to Impala 1.4, only the WHERE clauses on the original query from the CREATE VIEW statement were used for partition pruning.

In queries involving both analytic functions and partitioned tables, partition pruning only occurs for columns named in the PARTITION BY clause of the analytic function call. For example, if an analytic function query has a clause such as WHERE year=2016, the way to make the query prune all other YEAR partitions is to include PARTITION BY year in the analytic function call; for example, OVER (PARTITION BY year, other_columns other_analytic_clauses).

Dynamic Partition Pruning

The original mechanism uses to prune partitions is *static partition pruning*, in which the conditions in the WHERE clause are analyzed to determine in advance which partitions can be safely skipped. In Impala 2.5 and higher, Impala can perform *dynamic partition pruning*, where information about the partitions is collected during the query, and Impala prunes unnecessary partitions in ways that were impractical to predict in advance.

For example, if partition key columns are compared to literal values in a WHERE clause, Impala can perform static partition pruning during the planning phase to only read the relevant partitions:

```
-- The query only needs to read 3 partitions whose key values are known
  ahead of time.
-- That's static partition pruning.
SELECT COUNT(*) FROM sales_table WHERE year IN (2005, 2010, 2015);
```

Dynamic partition pruning involves using information only available at run time, such as the result of a subquery. The following example shows a simple dynamic partition pruning.

```
CREATE TABLE yy (s STRING) PARTITIONED BY (year INT);
INSERT INTO yy PARTITION (year) VALUES ('1999', 1999), ('2000', 2000),
  ('2001', 2001), ('2010', 2010), ('2018', 2018);
COMPUTE STATS yy;

CREATE TABLE yy2 (s STRING, year INT);
INSERT INTO yy2 VALUES ('1999', 1999), ('2000', 2000), ('2001', 2001);
COMPUTE STATS yy2;

-- The following query reads an unknown number of partitions, whose key
  values
-- are only known at run time. The runtime filters line shows the
-- information used in query fragment 02 to decide which partitions to skip.

EXPLAIN SELECT s FROM yy WHERE year IN (SELECT year FROM yy2);
+-----+
| PLAN-ROOT SINK |
| 04:EXCHANGE [UNPARTITIONED] |
| 02:HASH JOIN [LEFT SEMI JOIN, BROADCAST] |
|   hash predicates: year = year |
|   runtime filters: RF000 <- year |
| --03:EXCHANGE [BROADCAST] |
|   |
|   01:SCAN HDFS [default.yy2] |
|     partitions=1/1 files=1 size=620B |
| 00:SCAN HDFS [default.yy] |
|   partitions=5/5 files=5 size=1.71KB |
|   runtime filters: RF000 -> year |
+-----+

SELECT s FROM yy WHERE year IN (SELECT year FROM yy2); -- Returns 3 rows
from yy
PROFILE;
```

In the above example, Impala evaluates the subquery, sends the subquery results to all Impala nodes participating in the query, and then each `impalad` daemon uses the dynamic partition pruning optimization to read only the partitions with the relevant key values.

The output query plan from the EXPLAIN statement shows that runtime filters are enabled. The plan also shows that it expects to read all 5 partitions of the `yy` table, indicating that static partition pruning will not happen.

The Filter summary in the PROFILE output shows that the scan node filtered out based on a runtime filter of dynamic partition pruning.

```
Filter 0 (1.00 MB):
```

```
- Files processed: 3
- Files rejected: 1 (1)
- Files total: 3 (3)
```

Dynamic partition pruning is especially effective for queries involving joins of several large partitioned tables. Evaluating the ON clauses of the join predicates might normally require reading data from all partitions of certain tables. If the WHERE clauses of the query refer to the partition key columns, Impala can now often skip reading many of the partitions while evaluating the ON clauses. The dynamic partition pruning optimization reduces the amount of I/O and the amount of intermediate data stored and transmitted across the network during the query.

When the spill-to-disk feature is activated for a join node within a query, Impala does not produce any runtime filters for that join operation on that host. Other join nodes within the query are not affected.

Dynamic partition pruning is part of the runtime filtering feature, which applies to other kinds of queries in addition to queries against partitioned tables. See [Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641 for full details about this feature.

Partition Key Columns

The columns you choose as the partition keys should be ones that are frequently used to filter query results in important, large-scale queries. Popular examples are some combination of year, month, and day when the data has associated time values, and geographic region when the data is associated with some place.

- For time-based data, split out the separate parts into their own columns, because Impala cannot partition based on a `TIMESTAMP` column.
- The data type of the partition columns does not have a significant effect on the storage required, because the values from those columns are not stored in the data files, rather they are represented as strings inside HDFS directory names.
- In Impala 2.5 and higher, you can enable the `OPTIMIZE_PARTITION_KEY_SCANS` query option to speed up queries that only refer to partition key columns, such as `SELECT MAX(year)`. This setting is not enabled by default because the query behavior is slightly different if the table contains partition directories without actual data inside. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(Impala 2.5 or higher only\)](#) on page 377 for details.
- Partitioned tables can contain complex type columns. All the partition key columns must be scalar types.
- Remember that when Impala queries data stored in HDFS, it is most efficient to use multi-megabyte files to take advantage of the HDFS block size. For Parquet tables, the block size (and ideal size of the data files) is 256 MB in Impala 2.0 and later. Therefore, avoid specifying too many partition key columns, which could result in individual partitions containing only small amounts of data. For example, if you receive 1 GB of data per day, you might partition by year, month, and day; while if you receive 5 GB of data per minute, you might partition by year, month, day, hour, and minute. If you have data with a geographic component, you might partition based on postal code if you have many megabytes of data for each postal code, but if not, you might partition by some larger region such as city, state, or country. state

If you frequently run aggregate functions such as `MIN()`, `MAX()`, and `COUNT(DISTINCT)` on partition key columns, consider enabling the `OPTIMIZE_PARTITION_KEY_SCANS` query option, which optimizes such queries. This feature is available in Impala 2.5 and higher. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(Impala 2.5 or higher only\)](#) on page 377 for the kinds of queries that this option applies to, and slight differences in how partitions are evaluated when this query option is enabled.

Setting Different File Formats for Partitions

Partitioned tables have the flexibility to use different file formats for different partitions. (For background information about the different file formats Impala supports, see [How Impala Works with Hadoop File Formats](#) on page 695.) For example, if you originally received data in text format, then received new data in RCFile format, and eventually began receiving data in Parquet format, all that data could reside in the same table for queries. You just need to ensure that the table is structured so that the data files that use different file formats reside in separate partitions.

For example, here is how you might switch from text to Parquet data as you receive data for different years:

```
[localhost:21000] > create table census (name string) partitioned by (year
smallint);
[localhost:21000] > alter table census add partition (year=2012); -- Text
format;

[localhost:21000] > alter table census add partition (year=2013); -- Text
format switches to Parquet before data loaded;
[localhost:21000] > alter table census partition (year=2013) set fileformat
parquet;

[localhost:21000] > insert into census partition (year=2012) values
('Smith'),('Jones'),('Lee'),('Singh');
[localhost:21000] > insert into census partition (year=2013) values
('Flores'),('Bogomolov'),('Cooper'),('Appiah');
```

At this point, the HDFS directory for year=2012 contains a text-format data file, while the HDFS directory for year=2013 contains a Parquet data file. As always, when loading non-trivial data, you would use `INSERT ... SELECT` or `LOAD DATA` to import data in large batches, rather than `INSERT ... VALUES` which produces small files that are inefficient for real-world queries.

For other file types that Impala cannot create natively, you can switch into Hive and issue the `ALTER TABLE ... SET FILEFORMAT` statements and `INSERT` or `LOAD DATA` statements there. After switching back to Impala, issue a `REFRESH table_name` statement so that Impala recognizes any partitions or new data added through Hive.

Managing Partitions

You can add, drop, set the expected file format, or set the HDFS location of the data files for individual partitions within an Impala table. See [ALTER TABLE Statement](#) on page 215 for syntax details, and [Setting Different File Formats for Partitions](#) on page 691 for tips on managing tables containing partitions with different file formats.

Note: If you are creating a partition for the first time and specifying its location, for maximum efficiency, use a single `ALTER TABLE` statement including both the `ADD PARTITION` and `LOCATION` clauses, rather than separate statements with `ADD PARTITION` and `SET LOCATION` clauses.

What happens to the data files when a partition is dropped depends on whether the partitioned table is designated as internal or external. For an internal (managed) table, the data files are deleted. For example, if data in the partitioned table is a copy of raw data files stored elsewhere, you might save disk space by dropping older partitions that are no longer required for reporting, knowing that the original data is still available if needed later. For an external table, the data files are left alone. For example, dropping a partition without deleting the associated files lets Impala consider a smaller set of partitions, improving query efficiency and reducing overhead for DDL operations on the table; if the data is needed again later, you can add the partition again. See [Overview of Impala Tables](#) on page 206 for details and examples.

Using Partitioning with Kudu Tables

Kudu tables use a more fine-grained partitioning scheme than tables containing HDFS data files. You specify a `PARTITION BY` clause with the `CREATE TABLE` statement to identify how to divide the values from the partition key columns.

See [Partitioning for Kudu Tables](#) on page 740 for details and examples of the partitioning techniques for Kudu tables.

Keeping Statistics Up to Date for Partitioned Tables

Because the `COMPUTE STATS` statement can be resource-intensive to run on a partitioned table as new partitions are added, Impala includes a variation of this statement that allows computing statistics on a per-partition basis such that stats can be incrementally updated when new partitions are added.

Important:

For a particular table, use either `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS`, but never combine the two or alternate between them. If you switch from `COMPUTE STATS` to `COMPUTE INCREMENTAL STATS` during the lifetime of a table, or vice versa, drop all statistics by running `DROP STATS` before making the switch.

When you run `COMPUTE INCREMENTAL STATS` on a table for the first time, the statistics are computed again from scratch regardless of whether the table already has statistics. Therefore, expect a one-time resource-intensive operation for scanning the entire table when running `COMPUTE INCREMENTAL STATS` for the first time on a given table.

In Impala 3.0 and lower, approximately 400 bytes of metadata per column per partition are needed for caching. Tables with a big number of partitions and many columns can add up to a significant memory overhead as the metadata must be cached on the catalogd host and on every impalad host that is eligible to be a coordinator. If this metadata for all tables exceeds 2 GB, you might experience service downtime. In Impala 3.1 and higher, the issue was alleviated with an improved handling of incremental stats.

The `COMPUTE INCREMENTAL STATS` variation computes statistics only for partitions that were added or changed since the last `COMPUTE INCREMENTAL STATS` statement, rather than the entire table. It is typically used for tables where a full `COMPUTE STATS` operation takes too long to be practical each time a partition is added or dropped. See [#unique_312](#) for full usage details.

```
-- Initially the table has no incremental stats, as indicated
-- 'false' under Incremental stats.
show table stats item_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| i_category | #Rows | #Files | Size      | Bytes Cached | Format  | Incremental stats |
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| Books      | -1    | 1      | 223.74KB  | NOT CACHED   | PARQUET | false             |
| Children   | -1    | 1      | 230.05KB  | NOT CACHED   | PARQUET | false             |
| Electronics| -1    | 1      | 232.67KB  | NOT CACHED   | PARQUET | false             |
| Home       | -1    | 1      | 232.56KB  | NOT CACHED   | PARQUET | false             |
| Jewelry    | -1    | 1      | 223.72KB  | NOT CACHED   | PARQUET | false             |
| Men        | -1    | 1      | 231.25KB  | NOT CACHED   | PARQUET | false             |
| Music      | -1    | 1      | 237.90KB  | NOT CACHED   | PARQUET | false             |
| Shoes      | -1    | 1      | 234.90KB  | NOT CACHED   | PARQUET | false             |
| Sports     | -1    | 1      | 227.97KB  | NOT CACHED   | PARQUET | false             |
| Women      | -1    | 1      | 226.27KB  | NOT CACHED   | PARQUET | false             |
| Total      | -1    | 10     | 2.25MB    | 0B           |         |                   |
+-----+-----+-----+-----+-----+-----+-----+
+-----+

-- After the first COMPUTE INCREMENTAL STATS,
-- all partitions have stats. The first
-- COMPUTE INCREMENTAL STATS scans the whole
-- table, discarding any previous stats from
-- a traditional COMPUTE STATS statement.
compute incremental stats item_partitioned;
+-----+-----+-----+-----+-----+-----+-----+
+-----+
| summary                                         |
+-----+-----+-----+-----+-----+-----+-----+
| Updated 10 partition(s) and 21 column(s).      |
+-----+-----+-----+-----+-----+-----+-----+
```

```
show table stats item_partitioned;
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	
Incremental stats						
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	1783	1	227.97KB	NOT CACHED	PARQUET	true
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	10	2.25MB	0B		

```
-- Add a new partition...
```

```
alter table item_partitioned add partition (i_category='Camping');
```

```
-- Add or replace files in HDFS outside of Impala,
```

```
-- rendering the stats for a partition obsolete.
```

```
!import_data_into_sports_partition.sh
```

```
refresh item_partitioned;
```

```
drop incremental stats item_partitioned partition (i_category='Sports');
```

```
-- Now some partitions have incremental stats
```

```
-- and some do not.
```

```
show table stats item_partitioned;
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	
Incremental stats						
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Camping	-1	1	408.02KB	NOT CACHED	PARQUET	false
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	-1	1	227.97KB	NOT CACHED	PARQUET	false
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	11	2.65MB	0B		

```
-- After another COMPUTE INCREMENTAL STATS,
```

```
-- all partitions have incremental stats, and only the 2
```

```
-- partitions without incremental stats were scanned.
```

```
compute incremental stats item_partitioned;
```

```
| summary
```

```
| Updated 2 partition(s) and 21 column(s).
```

```
show table stats item_partitioned;
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	
Incremental stats						
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Camping	5328	1	408.02KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	1783	1	227.97KB	NOT CACHED	PARQUET	true
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	11	2.65MB	0B		

How Impala Works with Hadoop File Formats

Impala supports several familiar file formats used in Apache Hadoop. Impala can load and query data files produced by other Hadoop components such as Spark, and data files produced by Impala can be used by other components also. The following sections discuss the procedures, limitations, and performance considerations for using each file format with Impala.

The file format used for an Impala table has significant performance consequences. Some file formats include compression support that affects the size of data on the disk and, consequently, the amount of I/O and CPU resources required to deserialize data. The amounts of I/O and CPU resources required can be a limiting factor in query performance since querying often begins with moving and decompressing data. To reduce the potential impact of this part of the process, data is often compressed. By compressing data, a smaller total number of bytes are transferred from disk to memory. This reduces the amount of time taken to transfer the data, but a tradeoff occurs when the CPU decompresses the content.

For the file formats that Impala cannot write to, create the table from within Impala whenever possible and insert data using another component such as Hive or Spark. See the table below for specific file formats.

The following table lists the file formats that Impala supports.

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
<i>Parquet</i>	Structured	Snappy, gzip, zstd, lz4; currently Snappy by default	Yes.	Yes: CREATE TABLE, INSERT, LOAD DATA, and query.
<i>ORC</i>	Structured	gzip, Snappy, LZO, LZ4; currently gzip by default	Yes, in Impala 2.12.0 and higher. By default, ORC reads are enabled in Impala 3.4.0 and higher.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
<i>Text</i>	Unstructured	bzip2, deflate, gzip, LZO, Snappy, zstd	Yes. For CREATE TABLE with no STORED AS clause, the default file format is uncompressed text, with values separated by ASCII 0x01 characters (typically represented as Ctrl-A).	Yes if uncompressed. No if compressed. If LZO compression is used, you must create the table and load data in Hive. If other kinds of compression are used, you must load data through LOAD DATA, Hive, or manually in HDFS.
<i>Avro</i>	Structured	Snappy, gzip, deflate	Yes, in Impala 1.4.0 and higher. In lower versions, create the table using Hive.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.
<i>Hudi</i>	Structured	Snappy, gzip, zstd, lz4; currently Snappy by default	Yes, support for Read Optimized Queries is experimental.	No. Create an external table in Impala. Set the table location to the Hudi table directory. Alternatively, create the Hudi table in Hive.
<i>RCFile</i>	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.
<i>SequenceFile</i>	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.

Impala supports the following compression codecs:

Snappy

Recommended for its effective balance between compression ratio and decompression speed. Snappy compression is very fast, but gzip provides greater space savings. Supported for text, RC, Sequence, and Avro files in Impala 2.0 and higher.

Gzip

Recommended when achieving the highest level of compression (and therefore greatest disk-space savings) is desired. Supported for text, RC, Sequence and Avro files in Impala 2.0 and higher.

Deflate

Supported for AVRO, RC, Sequence, and text files.

Bzip2	Supported for text, RC, and Sequence files in Impala 2.0 and higher.
LZO	For text files only. Impala can query LZO-compressed text tables, but currently cannot create them or insert data into them. You need to perform these operations in Hive.
Zstd	For Parquet and text files only.
Lz4	For Parquet files only.

Choosing the File Format for a Table

Different file formats and compression codecs work better for different data sets. Choosing the proper format for your data can yield performance improvements. Use the following considerations to decide which combination of file format and compression to use for a particular table:

- If you are working with existing files that are already in a supported file format, use the same format for the Impala table if performance is acceptable. If the original format does not yield acceptable query performance or resource usage, consider creating a new Impala table with different file format or compression characteristics, and doing a one-time conversion by rewriting the data to the new table.
- Text files are convenient to produce through many different tools, and are human-readable for ease of verification and debugging. Those characteristics are why text is the default format for an Impala `CREATE TABLE` statement. However, when performance and resource usage are the primary considerations, use one of the structured file formats that include metadata and built-in compression.

A typical workflow might involve bringing data into an Impala table by copying CSV or TSV files into the appropriate data directory, and then using the `INSERT . . . SELECT` syntax to rewrite the data into a table using a different, more compact file format.

Using Text Data Files with Impala Tables

Impala supports using text files as the storage format for input and output. Text files are a convenient format to use for interchange with other applications or scripts that produce or read delimited text files, such as CSV or TSV with commas or tabs for delimiters.

Text files are also very flexible in their column definitions. For example, a text file could have more fields than the Impala table, and those extra fields are ignored during queries; or it could have fewer fields than the Impala table, and those missing fields are treated as `NULL` values in queries. You could have fields that were treated as numbers or timestamps in a table, then use `ALTER TABLE . . . REPLACE COLUMNS` to switch them to strings, or the reverse.

Table 1: Text Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
<i>Text</i>	Unstructured	bzip2, deflate, gzip, LZO, Snappy, zstd	Yes. For <code>CREATE TABLE</code> with no <code>STORED AS</code> clause, the default file format is uncompressed text, with values separated by ASCII 0x01 characters (typically represented as Ctrl-A).	Yes if uncompressed. No if compressed. If LZO compression is used, you must create the table and load data in Hive. If other kinds of compression are used, you must load data through <code>LOAD DATA</code> , Hive, or manually in HDFS.

Query Performance for Impala Text Tables

Data stored in text format is relatively bulky, and not as efficient to query as binary formats such as Parquet. You typically use text tables with Impala if that is the format you receive the data and you do not have control over that process, or if you are a relatively new Hadoop user and not familiar with techniques to generate files in other formats. (Because the default format for `CREATE TABLE` is text, you might create your first Impala tables as text without giving performance much thought.) Either way, look for opportunities to use more efficient file formats for the tables used in your most performance-critical queries.

For frequently queried data, you might load the original text data files into one Impala table, then use an `INSERT` statement to transfer the data to another table that uses the Parquet file format; the data is converted automatically as it is stored in the destination table.

For more compact data, consider using LZO compression for the text files. LZO is the only compression codec that Impala supports for text data, because the “splittable” nature of LZO data files lets different nodes work on different parts of the same file in parallel. See [Using LZO-Compressed Text Files](#) on page 702 for details.

You can also use text data compressed in the bzip2, deflate, gzip, Snappy, or zstd formats. Because these compressed formats are not “splittable” in the way that LZO is, there is less opportunity for Impala to parallelize queries on them. Therefore, use these types of compressed data only for convenience if that is the format in which you receive the data. Prefer to use LZO compression for text data if you have the choice, or convert the data to Parquet using an `INSERT . . . SELECT` statement to copy the original data into a Parquet table.

Note:

Impala supports bzip files created by the `bzip2` command, but not bzip files with multiple streams created by the `pbzip2` command. Impala decodes only the data from the first part of such files, leading to incomplete results.

The maximum size that Impala can accommodate for an individual bzip file is 1 GB (after uncompressed).

Impala supports zstd files created by the `zstd` command line tool.

In Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, ORC, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Creating Text Tables

To create a table using text data files:

If the exact format of the text data files (such as the delimiter character) is not significant, use the `CREATE TABLE` statement with no extra clauses at the end to create a text-format table. For example:

```
create table my_table(id int, s string, n int, t timestamp, b boolean);
```

The data files created by any `INSERT` statements will use the Ctrl-A character (hex 01) as a separator between each column value.

A common use case is to import existing text files into an Impala table. The syntax is more verbose; the significant part is the `FIELDS TERMINATED BY` clause, which must be preceded by the `ROW FORMAT DELIMITED` clause. The statement can end with a `STORED AS TEXTFILE` clause, but that clause is optional because text format tables are the default. For example:

```
create table csv(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by ',';

create table tsv(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by '\t';

create table pipe_separated(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by '|'
  stored as textfile;
```

You can create tables with specific separator characters to import text files in familiar formats such as CSV, TSV, or pipe-separated. You can also use these tables to produce output data files, by copying data into them through the `INSERT ... SELECT` syntax and then extracting the data files from the Impala data directory.

In Impala 1.3.1 and higher, you can specify a delimiter character `'\0'` to use the ASCII 0 (nul) character for text tables:

```
create table nul_separated(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by '\0'
  stored as textfile;
```

Note:

Do not surround string values with quotation marks in text data files that you construct. If you need to include the separator character inside a field value, for example to put a string value with a comma inside a CSV-format data file, specify an escape character on the `CREATE TABLE` statement with the `ESCAPED BY` clause, and insert that character immediately before any separator characters that need escaping.

Issue a `DESCRIBE FORMATTED table_name` statement to see the details of how each table is represented internally in Impala.

Complex type considerations: Although you can create tables in this file format using the complex types (`ARRAY`, `STRUCT`, and `MAP`) available in Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in Impala 2.6 and higher.

Data Files for Text Tables

When Impala queries a table with data in text format, it consults all the data files in the data directory for that table, with some exceptions:

- Impala ignores any hidden files, that is, files whose names start with a dot or an underscore.
- Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.
- Impala uses suffixes to recognize when text data files are compressed text. For Impala to recognize the compressed text files, they must have the appropriate file extension corresponding to the compression codec, either `.bz2`, `.deflate`, `.gz`, `.snappy`, or `.zst`. The extensions can be in uppercase or lowercase.
- Otherwise, the file names are not significant. When you put files into an HDFS directory through ETL jobs, or point Impala to an existing HDFS directory with the `CREATE EXTERNAL TABLE` statement, or move data files under external control with the `LOAD DATA` statement, Impala preserves the original file names.

File names for data produced through Impala `INSERT` statements are given unique names to avoid file name conflicts.

An `INSERT ... SELECT` statement produces one data file from each node that processes the `SELECT` part of the statement. An `INSERT ... VALUES` statement produces a separate data file for each statement; because Impala is more efficient querying a small number of huge files than a large number of tiny files, the `INSERT ... VALUES` syntax is not recommended for loading a substantial volume of data. If you find yourself with a table that is inefficient due to too many small data files, reorganize the data into a few large files by doing `INSERT ... SELECT` to transfer the data to a new table.

Special values within text data files:

- Impala recognizes the literal strings `inf` for infinity and `nan` for “Not a Number”, for `FLOAT` and `DOUBLE` columns.
- Impala recognizes the literal string `\N` to represent `NULL`. When using Sqoop, specify the options `--null-non-string` and `--null-string` to ensure all `NULL` values are represented correctly in the Sqoop output files. `\N` needs to be escaped as in the below example:

```
--null-string '\\N' --null-non-string '\\N'
```

- By default, Sqoop writes `NULL` values using the string `null`, which causes a conversion error when such rows are evaluated by Impala. A workaround for existing tables and data files is to change the table properties through `ALTER TABLE name SET TBLPROPERTIES("serialization.null.format"="null")`.
- In Impala 2.6 and higher, Impala can optionally skip an arbitrary number of header lines from text input files on HDFS based on the `skip.header.line.count` value in the `TBLPROPERTIES` field of the table metadata. For example:

```
create table header_line(first_name string, age int)
  row format delimited fields terminated by ',';

-- Back in the shell, load data into the table with commands such as:
-- cat >data.csv
-- Name,Age
-- Alice,25
-- Bob,19
-- hdfs dfs -put data.csv /user/hive/warehouse/header_line

refresh header_line;

-- Initially, the Name,Age header line is treated as a row of the table.
select * from header_line limit 10;
+-----+-----+
| first_name | age |
+-----+-----+
| Name       | NULL |
| Alice      | 25   |
| Bob        | 19   |
+-----+-----+

alter table header_line set tblproperties('skip.header.line.count'='1');
```

```
-- Once the table property is set, queries skip the specified number of
-- lines
-- at the beginning of each text data file. Therefore, all the files in
-- the table
-- should follow the same convention for header lines.
select * from header_line limit 10;
```

first_name	age
Alice	25
Bob	19

Loading Data into Impala Text Tables

To load an existing text file into an Impala text table, use the `LOAD DATA` statement and specify the path of the file in HDFS. That file is moved into the appropriate Impala data directory.

To load multiple existing text files into an Impala text table, use the `LOAD DATA` statement and specify the HDFS path of the directory containing the files. All non-hidden files are moved into the appropriate Impala data directory.

To convert data to text from any other file format supported by Impala, use a SQL statement such as:

```
-- Text table with default delimiter, the hex 01 character.
CREATE TABLE text_table AS SELECT * FROM other_file_format_table;
```

```
-- Text table with user-specified delimiter. Currently, you cannot specify
-- the delimiter as part of CREATE TABLE LIKE or CREATE TABLE AS SELECT.
-- But you can change an existing text table to have a different delimiter.
CREATE TABLE csv LIKE other_file_format_table;
ALTER TABLE csv SET SERDEPROPERTIES ('serialization.format'=';',
    'field.delim'=';');
INSERT INTO csv SELECT * FROM other_file_format_table;
```

This can be a useful technique to see how Impala represents special values within a text-format data file. Use the `DESCRIBE FORMATTED` statement to see the HDFS directory where the data files are stored, then use Linux commands such as `hdfs dfs -ls hdfs_directory` and `hdfs dfs -cat hdfs_file` to display the contents of an Impala-created text file.

To create a few rows in a text table for test purposes, you can use the `INSERT ... VALUES` syntax:

```
INSERT INTO text_table VALUES ('string_literal',100,hex('hello world'));
```

Note: Because Impala and the HDFS infrastructure are optimized for multi-megabyte files, avoid the `INSERT ... VALUES` notation when you are inserting many rows. Each `INSERT ... VALUES` statement produces a new tiny file, leading to fragmentation and reduced performance. When creating any substantial volume of new data, use one of the bulk loading techniques such as `LOAD DATA` or `INSERT ... SELECT`. Or, [use an HBase table](#) for single-row `INSERT` operations, because HBase tables are not subject to the same fragmentation issues as tables stored on HDFS.

When you create a text file for use with an Impala text table, specify `\N` to represent a `NULL` value. For the differences between `NULL` and empty strings, see [NULL](#) on page 177.

If a text file has fewer fields than the columns in the corresponding Impala table, all the corresponding columns are set to `NULL` when the data in that file is read by an Impala query.

If a text file has more fields than the columns in the corresponding Impala table, the extra fields are ignored when the data in that file is read by an Impala query.

You can also use manual HDFS operations such as `hdfs dfs -put` or `hdfs dfs -cp` to put data files in the data directory for an Impala table. When you copy or move new data files into the HDFS directory for the Impala

table, issue a `REFRESH table_name` statement in `impala-shell` before issuing the next query against that table, to make Impala recognize the newly added files.

Using LZO-Compressed Text Files

Impala supports using text data files that employ LZO compression. Where practical, apply compression to text data files. Impala queries are usually I/O-bound; reducing the amount of data read from disk typically speeds up a query, despite the extra CPU work to uncompress the data in memory.

Impala can work with LZO-compressed text files are preferable to files compressed by other codecs, because LZO-compressed files are “splittable”, meaning that different portions of a file can be uncompressed and processed independently by different nodes.

Impala does not currently support writing LZO-compressed text files.

Because Impala can query LZO-compressed files but currently cannot write them, you use Hive to do the initial `CREATE TABLE` and load the data, then switch back to Impala to run queries. For instructions on setting up LZO compression for Hive `CREATE TABLE` and `INSERT` statements, see [the LZO page on the Hive wiki](#). Once you have created an LZO text table, you can also manually add LZO-compressed text files to it, produced by the `lzop` command or similar method.

Preparing to Use LZO-Compressed Text Files

Before using LZO-compressed tables in Impala, do the following one-time setup for each machine in the cluster. Install the necessary packages using either the public repository, a private repository you establish, or by using packages. You must do these steps manually, whether or not you are using cluster management software.

1. Prepare your systems to work with LZO by downloading and installing the appropriate libraries:

Download and install the appropriate file to each machine on which you intend to use LZO with Impala.

2. Configure Impala to use LZO:

Use **one** of the following sets of commands to refresh your package management system's repository information, install the base LZO support for Hadoop, and install the LZO support for Impala.

Note:

The name of the Hadoop LZO package changed in the distant past. Currently, the package name is `hadoop-lzo`.

For RHEL/CentOS systems:

```
$ sudo yum update
$ sudo yum install hadoop-lzo
$ sudo yum install impala-lzo
```

For SUSE systems:

```
$ sudo apt-get update
$ sudo zypper install hadoop-lzo
$ sudo zypper install impala-lzo
```

For Debian/Ubuntu systems:

```
$ sudo zypper update
$ sudo apt-get install hadoop-lzo
$ sudo apt-get install impala-lzo
```

Note:

The level of the `impala-lzo` package is closely tied to the version of Impala you use. Any time you upgrade Impala, re-do the installation command for `impala-lzo` on each applicable machine to make sure you have the appropriate version of that package.

- For `core-site.xml` on the client **and** server (that is, in the configuration directories for both Impala and Hadoop), append `com.hadoop.compression.lzo.LzopCodec` to the comma-separated list of codecs. For example:

```
<property>
  <name>io.compression.codecs</name>

  <value>org.apache.hadoop.io.compress.DefaultCodec,org.apache.hadoop.io.compress.Gzip
org.apache.hadoop.io.compress.BZip2Codec,org.apache.hadoop.io.compress.DeflateCodec,
org.apache.hadoop.io.compress.SnappyCodec,com.hadoop.compression.lzo.LzopCodec</
value>
</property>
```

Note:

If this is the first time you have edited the Hadoop `core-site.xml` file, note that the `/etc/hadoop/conf` directory is typically a symbolic link, so the canonical `core-site.xml` might reside in a different directory:

```
$ ls -l /etc/hadoop
total 8
lrwxrwxrwx. 1 root root 29 Feb 26 2013 conf -> /etc/alternatives/
hadoop-conf
lrwxrwxrwx. 1 root root 10 Feb 26 2013 conf.dist -> conf.empty
drwxr-xr-x. 2 root root 4096 Feb 26 2013 conf.empty
drwxr-xr-x. 2 root root 4096 Oct 28 15:46 conf.pseudo
```

If the `io.compression.codecs` property is missing from `core-site.xml`, only add `com.hadoop.compression.lzo.LzopCodec` to the new property value, not all the names from the preceding example.

- Restart the MapReduce and Impala services.

Creating LZO Compressed Text Tables

A table containing LZO-compressed text files must be created in Hive with the following storage clause:

```
STORED AS
  INPUTFORMAT 'com.hadoop.mapred.DeprecatedLzoTextInputFormat'
  OUTPUTFORMAT
  'org.apache.hadoop.hive ql.io.HiveIgnoreKeyTextOutputFormat'
```

Also, certain Hive settings need to be in effect. For example:

```
hive> SET mapreduce.output.fileoutputformat.compress=true;
hive> SET hive.exec.compress.output=true;
hive> SET
  mapreduce.output.fileoutputformat.compress.codec=com.hadoop.compression.lzo.LzopCodec;
hive> CREATE TABLE lzo_t (s string) STORED AS
  > INPUTFORMAT 'com.hadoop.mapred.DeprecatedLzoTextInputFormat'
  > OUTPUTFORMAT
  'org.apache.hadoop.hive ql.io.HiveIgnoreKeyTextOutputFormat';
hive> INSERT INTO TABLE lzo_t SELECT col1, col2 FROM
  uncompressed_text_table;
```

Once you have created LZO-compressed text tables, you can convert data stored in other tables (regardless of file format) by using the `INSERT ... SELECT` statement in Hive.

Files in an LZO-compressed table must use the `.lzo` extension. Examine the files in the HDFS data directory after doing the `INSERT` in Hive, to make sure the files have the right extension. If the required settings are not in place,

you end up with regular uncompressed files, and Impala cannot access the table because it finds data files with the wrong (uncompressed) format.

After loading data into an LZO-compressed text table, index the files so that they can be split. You index the files by running a Java class, `com.hadoop.compression.lzo.DistributedLzoIndexer`, through the Linux command line. This Java class is included in the `hadoop-lzo` package.

Run the indexer using a command like the following:

```
$ hadoop jar /usr/lib/hadoop/lib/hadoop-lzo-version-gplextras.jar
  com.hadoop.compression.lzo.DistributedLzoIndexer /hdfs_location_of_table/
```

Note: If the path of the JAR file in the preceding example is not recognized, do a `find` command to locate `hadoop-lzo-*-gplextras.jar` and use that path.

Indexed files have the same name as the file they index, with the `.index` extension. If the data files are not indexed, Impala queries still work, but the queries read the data from remote DataNodes, which is very inefficient.

Once the LZO-compressed tables are created, and data is loaded and indexed, you can query them through Impala. As always, the first time you start `impala-shell` after creating a table in Hive, issue an `INVALIDATE METADATA` statement so that Impala recognizes the new table. (In Impala 1.2 and higher, you only have to run `INVALIDATE METADATA` on one node, rather than on all the Impala nodes.)

Using bzip2, deflate, gzip, Snappy, or zstd Text Files

Impala supports using text data files that employ bzip2, deflate, gzip, Snappy, or zstd compression. These compression types are primarily for convenience within an existing ETL pipeline rather than maximum performance. Although it requires less I/O to read compressed text than the equivalent uncompressed text, files compressed by these codecs are not “splittable” and therefore cannot take full advantage of the Impala parallel query capability. Impala can read compressed text files written by Hive.

As each Snappy-compressed file is processed, the node doing the work reads the entire file into memory and then decompresses it. Therefore, the node must have enough memory to hold both the compressed and uncompressed data from the text file. The memory required to hold the uncompressed data is difficult to estimate in advance, potentially causing problems on systems with low memory limits or with resource management enabled. This memory overhead is reduced for bzip2-, deflate-, gzip-, and zstd-compressed text files. The compressed data is decompressed as it is read, rather than all at once.

To create a table to hold compressed text, create a text table with no special compression options. Specify the delimiter and escape character if required, using the `ROW FORMAT` clause.

Because Impala can query compressed text files but currently cannot write them, produce the compressed text files outside Impala and use the `LOAD DATA` statement, manual HDFS commands to move them to the appropriate Impala data directory. (Or, you can use `CREATE EXTERNAL TABLE` and point the `LOCATION` attribute at a directory containing existing compressed text files.)

The following example shows how you can create a regular text table, put different kinds of compressed and uncompressed files into it, and Impala automatically recognizes and decompresses each one based on their file extensions:

```
create table csv_compressed (a string, b string, c string)
  row format delimited fields terminated by ",";

insert into csv_compressed values
  ('one - uncompressed', 'two - uncompressed', 'three - uncompressed'),
  ('abc - uncompressed', 'xyz - uncompressed', '123 - uncompressed');
...make equivalent .bz2, .gz, .snappy, and .zst files and load them into
  same table directory...
```

```
select * from csv_compressed;
```

a	b	c
one - uncompressed	two - uncompressed	three - uncompressed
abc - uncompressed	xyz - uncompressed	123 - uncompressed

one - snappy	two - snappy	three - snappy
one - uncompressed	two - uncompressed	three - uncompressed
abc - uncompressed	xyz - uncompressed	123 - uncompressed
one - bz2	two - bz2	three - bz2
abc - bz2	xyz - bz2	123 - bz2
one - gzip	two - gzip	three - gzip
abc - gzip	xyz - gzip	123 - gzip
one - zstd	two - zstd	three - zstd
abc - zstd	xyz - zstd	123 - zstd
one - deflate	two - deflate	three - deflate
abc - deflate	xyz - deflate	123 - deflate

```
$ hdfs dfs -ls 'hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/
csv_compressed/';
...truncated for readability...
75 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/
csv_compressed.snappy
79 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/
csv_compressed_bz2.csv.bz2
80 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/
csv_compressed_gzip.csv.gz
58 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/
csv_compressed_zstd.csv.zst
48 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/
csv_compressed_deflate.csv.deflate
116 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/
csv_compressed/dd414df64d67d49b_data.0.
```

Using the Parquet File Format with Impala Tables

Impala allows you to create, manage, and query Parquet tables. Parquet is a column-oriented binary file format intended to be highly efficient for the types of large-scale queries that Impala is best at. Parquet is especially good for queries scanning particular columns within a table, for example, to query “wide” tables with many columns, or to perform aggregation operations such as `SUM()` and `AVG()` that need to process most or all of the values from a column. Each Parquet data file written by Impala contains the values for a set of rows (referred to as the “row group”). Within a data file, the values from each column are organized so that they are all adjacent, enabling good compression for the values from that column. Queries against a Parquet table can retrieve and analyze these values from any column quickly and with minimal I/O.

See [How Impala Works with Hadoop File Formats](#) on page 695 for the summary of Parquet format support.

Creating Parquet Tables in Impala

To create a table named `PARQUET_TABLE` that uses the Parquet format, you would use a command like the following, substituting your own table name, column names, and data types:

```
[impala-host:21000] > create table parquet_table_name (x INT, y STRING)
  STORED AS PARQUET;
```

Or, to clone the column names and data types of an existing table:

```
[impala-host:21000] > create table parquet_table_name LIKE other_table_name
  STORED AS PARQUET;
```

In Impala 1.4.0 and higher, you can derive column definitions from a raw Parquet data file, even without an existing Impala table. For example, you can create an external table pointing to an HDFS directory, and base the column definitions on one of the files in that directory:

```
CREATE EXTERNAL TABLE ingest_existing_files LIKE PARQUET '/user/etl/
destination/datafile1.dat'
  STORED AS PARQUET
  LOCATION '/user/etl/destination';
```

Or, you can refer to an existing data file and create a new empty table with suitable column definitions. Then you can use `INSERT` to create new data files or `LOAD DATA` to transfer existing data files into the new table.

```
CREATE TABLE columns_from_data_file LIKE PARQUET '/user/etl/destination/
datafile1.dat'
  STORED AS PARQUET;
```

The default properties of the newly created table are the same as for any other `CREATE TABLE` statement. For example, the default file format is text; if you want the new table to use the Parquet file format, include the `STORED AS PARQUET` file also.

In this example, the new table is partitioned by year, month, and day. These partition key columns are not part of the data file, so you specify them in the `CREATE TABLE` statement:

```
CREATE TABLE columns_from_data_file LIKE PARQUET '/user/etl/destination/
datafile1.dat'
  PARTITION (year INT, month TINYINT, day TINYINT)
  STORED AS PARQUET;
```

See [CREATE TABLE Statement](#) on page 248 for more details about the `CREATE TABLE LIKE PARQUET` syntax.

Once you have created a table, to insert data into that table, use a command similar to the following, again with your own table names:

```
[impala-host:21000] > insert overwrite table parquet_table_name select *
  from other_table_name;
```

If the Parquet table has a different number of columns or different column names than the other table, specify the names of columns from the other table rather than `*` in the `SELECT` statement.

Loading Data into Parquet Tables

Choose from the following techniques for loading data into Parquet tables, depending on whether the original data is already in an Impala table, or exists as raw data files outside Impala.

If you already have data in an Impala or Hive table, perhaps in a different file format or partitioning scheme, you can transfer the data to a Parquet table using the Impala `INSERT . . . SELECT` syntax. You can convert, filter, repartition, and do other things to the data as part of this same `INSERT` statement. See [Compressions for Parquet Data Files](#) on page 709 for some examples showing how to insert data into Parquet tables.

When inserting into partitioned tables, especially using the Parquet file format, you can include a hint in the `INSERT` statement to fine-tune the overall performance of the operation and its resource usage. See [Optimizer Hints](#) for using hints in the `INSERT` statements.

Any `INSERT` statement for a Parquet table requires enough free space in the HDFS filesystem to write one block. Because Parquet data files use a block size of 1 GB by default, an `INSERT` might fail (even for a very small amount of data) if your HDFS is running low on space.

Avoid the `INSERT . . . VALUES` syntax for Parquet tables, because `INSERT . . . VALUES` produces a separate tiny data file for each `INSERT . . . VALUES` statement, and the strength of Parquet is in its handling of data (compressing, parallelizing, and so on) in large chunks.

If you have one or more Parquet data files produced outside of Impala, you can quickly make the data queryable through Impala by one of the following methods:

- The `LOAD DATA` statement moves a single data file or a directory full of data files into the data directory for an Impala table. It does no validation or conversion of the data. The original data files must be somewhere in HDFS, not the local filesystem.
- The `CREATE TABLE` statement with the `LOCATION` clause creates a table where the data continues to reside outside the Impala data directory. The original data files must be somewhere in HDFS, not the local filesystem. For extra safety, if the data is intended to be long-lived and reused by other applications, you can use the `CREATE EXTERNAL TABLE` syntax so that the data files are not deleted by an `IMPALA DROP TABLE` statement.
- If the Parquet table already exists, you can copy Parquet data files directly into it, then use the `REFRESH` statement to make Impala recognize the newly added data. Remember to preserve the block size of the Parquet data files by using the `hadoop distcp -pb` command rather than a `-put` or `-cp` operation on the Parquet files. See [Example of Copying Parquet Data Files](#) on page 711 for an example of this kind of operation.

Note:

Currently, Impala always decodes the column data in Parquet files based on the ordinal position of the columns, not by looking up the position of each column based on its name. Parquet files produced outside of Impala must write column data in the same order as the columns are declared in the Impala table. Any optional columns that are omitted from the data files must be the rightmost columns in the Impala table definition.

If you created compressed Parquet files through some tool other than Impala, make sure that any compression codecs are supported in Parquet by Impala. For example, Impala does not currently support LZO compression in Parquet files. Also doublecheck that you used any recommended compatibility settings in the other tool, such as `spark.sql.parquet.binaryAsString` when writing Parquet files through Spark.

Recent versions of Sqoop can produce Parquet output files using the `--as-parquetfile` option.

If the data exists outside Impala and is in some other format, combine both of the preceding techniques. First, use a `LOAD DATA` or `CREATE EXTERNAL TABLE ... LOCATION` statement to bring the data into an Impala table that uses the appropriate file format. Then, use an `INSERT ... SELECT` statement to copy the data to the Parquet table, converting to Parquet format as part of the process.

Loading data into Parquet tables is a memory-intensive operation, because the incoming data is buffered until it reaches one data block in size, then that chunk of data is organized and compressed in memory before being written out. The memory consumption can be larger when inserting data into partitioned Parquet tables, because a separate data file is written for each combination of partition key column values, potentially requiring several large chunks to be manipulated in memory at once.

When inserting into a partitioned Parquet table, Impala redistributes the data among the nodes to reduce memory consumption. You might still need to temporarily increase the memory dedicated to Impala during the insert operation, or break up the load operation into several `INSERT` statements, or both.

Note: All the preceding techniques assume that the data you are loading matches the structure of the destination table, including column order, column names, and partition layout. To transform or reorganize the data, start by loading the data into a Parquet table that matches the underlying structure of the data, then use one of the table-copying techniques such as `CREATE TABLE AS SELECT` or `INSERT ... SELECT` to reorder or rename columns, divide the data among multiple partitions, and so on. For example to take a single comprehensive Parquet data file and load it into a partitioned table, you would use an `INSERT ... SELECT` statement with dynamic partitioning to let Impala create separate data files with the appropriate partition values; for an example, see [INSERT Statement](#) on page 298.

Query Performance for Impala Parquet Tables

Query performance for Parquet tables depends on the number of columns needed to process the `SELECT` list and `WHERE` clauses of the query, the way data is divided into large data files with block size equal to file size, the reduction in I/O by reading the data for each column in compressed format, which data files can be skipped (for partitioned tables), and the CPU overhead of decompressing the data for each column.

For example, the following is an efficient query for a Parquet table:

```
select avg(income) from census_data where state = 'CA';
```

The query processes only 2 columns out of a large number of total columns. If the table is partitioned by the `STATE` column, it is even more efficient because the query only has to read and decode 1 column from each data file, and it can read only the data files in the partition directory for the state 'CA', skipping the data files for all the other states, which will be physically located in other directories.

The following is a relatively inefficient query for a Parquet table:

```
select * from census_data;
```

Impala would have to read the entire contents of each large data file, and decompress the contents of each column for each row group, negating the I/O optimizations of the column-oriented format. This query might still be faster for a Parquet table than a table with some other file format, but it does not take advantage of the unique strengths of Parquet data files.

Impala can optimize queries on Parquet tables, especially join queries, better when statistics are available for all the tables. Issue the `COMPUTE STATS` statement for each table after substantial amounts of data are loaded into or appended to it. See [COMPUTE STATS Statement](#) on page 232 for details.

The runtime filtering feature, available in Impala 2.5 and higher, works best with Parquet tables. The per-row filtering aspect only applies to Parquet tables. See [Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641 for details.

In Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, ORC, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Starting in Impala 3.4.0, use the query option `PARQUET_OBJECT_STORE_SPLIT_SIZE` to control the Parquet split size for non-block stores (e.g. S3, ADLS, etc.). The default value is 256 MB.

In Impala 2.9 and higher, Parquet files written by Impala include embedded metadata specifying the minimum and maximum values for each column, within each row group and each data page within the row group. Impala-written Parquet files typically contain a single row group; a row group can contain many data pages. Impala uses this information (currently, only the metadata for each row group) when reading each Parquet data file during a query, to quickly determine whether each row group within the file potentially includes any rows that match the conditions in the `WHERE` clause. For example, if the column `X` within a particular Parquet file has a minimum value of 1 and a maximum value of 100, then a query including the clause `WHERE x > 200` can quickly determine that it is safe to skip that particular file, instead of scanning all the associated column values. This optimization technique is especially effective for tables that use the `SORT BY` clause for the columns most frequently checked in `WHERE` clauses, because any `INSERT` operation on such tables produces Parquet data files with relatively narrow ranges of column values within each file.

To disable Impala from writing the Parquet page index when creating Parquet files, set the `PARQUET_WRITE_PAGE_INDEX` query option to `FALSE`.

Partitioning for Parquet Tables

As explained in [Partitioning for Impala Tables](#) on page 685, partitioning is an important performance technique for Impala generally. This section explains some of the performance considerations for partitioned Parquet tables.

The Parquet file format is ideal for tables containing many columns, where most queries only refer to a small subset of the columns. As explained in [How Parquet Data Files Are Organized](#) on page 715, the physical layout of Parquet data files lets Impala read only a small fraction of the data for many queries. The performance benefits of this

approach are amplified when you use Parquet tables in combination with partitioning. Impala can skip the data files for certain partitions entirely, based on the comparisons in the `WHERE` clause that refer to the partition key columns. For example, queries on partitioned tables often analyze data for time intervals based on columns such as `YEAR`, `MONTH`, and/or `DAY`, or for geographic regions. Remember that Parquet data files use a large block size, so when deciding how finely to partition the data, try to find a granularity where each partition contains 256 MB or more of data, rather than creating a large number of smaller files split among many partitions.

Inserting into a partitioned Parquet table can be a resource-intensive operation, because each Impala node could potentially be writing a separate data file to HDFS for each combination of different values for the partition key columns. The large number of simultaneous open files could exceed the HDFS “transceivers” limit. To avoid exceeding this limit, consider the following techniques:

- Load different subsets of data using separate `INSERT` statements with specific values for the `PARTITION` clause, such as `PARTITION (year=2010)`.
- Increase the “transceivers” value for HDFS, sometimes spelled “xcievers” (sic). The property value in the `hdfs-site.xml` configuration file is `dfs.datanode.max.transfer.threads`. For example, if you were loading 12 years of data partitioned by year, month, and day, even a value of 4096 might not be high enough. This [blog post](#) explores the considerations for setting this value higher or lower, using HBase examples for illustration.
- Use the `COMPUTE STATS` statement to collect [column statistics](#) on the source table from which data is being copied, so that the Impala query can estimate the number of different values in the partition key columns and distribute the work accordingly.

Compressions for Parquet Data Files

When Impala writes Parquet data files using the `INSERT` statement, the underlying compression is controlled by the `COMPRESSION_CODEC` query option. (Prior to Impala 2.0, the query option name was `PARQUET_COMPRESSION_CODEC`.) The allowed values for this query option are `snappy` (the default), `gzip`, `zstd`, `lz4`, and `none`. The option value is not case-sensitive. If the option is set to an unrecognized value, all kinds of queries will fail due to the invalid option setting, not just queries involving Parquet tables.

Example of Parquet Table with Snappy Compression

By default, the underlying data files for a Parquet table are compressed with Snappy. The combination of fast compression and decompression makes it a good choice for many data sets. To ensure Snappy compression is used, for example after experimenting with other compression codecs, set the `COMPRESSION_CODEC` query option to `snappy` before inserting the data:

```
[localhost:21000] > create database parquet_compression;
[localhost:21000] > use parquet_compression;
[localhost:21000] > create table parquet_snappy like raw_text_data;
[localhost:21000] > set COMPRESSION_CODEC=snappy;
[localhost:21000] > insert into parquet_snappy select * from raw_text_data;
Inserted 1000000000 rows in 181.98s
```

Example of Parquet Table with GZip Compression

If you need more intensive compression (at the expense of more CPU cycles for uncompressing during queries), set the `COMPRESSION_CODEC` query option to `gzip` before inserting the data:

```
[localhost:21000] > create table parquet_gzip like raw_text_data;
[localhost:21000] > set COMPRESSION_CODEC=gzip;
[localhost:21000] > insert into parquet_gzip select * from raw_text_data;
Inserted 1000000000 rows in 1418.24s
```

Example of Uncompressed Parquet Table

If your data compresses very poorly, or you want to avoid the CPU overhead of compression and decompression entirely, set the `COMPRESSION_CODEC` query option to `none` before inserting the data:

```
[localhost:21000] > create table parquet_none like raw_text_data;
[localhost:21000] > set COMPRESSION_CODEC=none;
[localhost:21000] > insert into parquet_none select * from raw_text_data;
Inserted 10000000000 rows in 146.90s
```

Examples of Sizes and Speeds for Compressed Parquet Tables

Here are some examples showing differences in data sizes and query speeds for 1 billion rows of synthetic data, compressed with each kind of codec. As always, run similar tests with realistic data sets of your own. The actual compression ratios, and relative insert and query speeds, will vary depending on the characteristics of the actual data.

In this case, switching from Snappy to GZip compression shrinks the data by an additional 40% or so, while switching from Snappy compression to no compression expands the data also by about 40%:

```
$ hdfs dfs -du -h /user/hive/warehouse/parquet_compression.db
23.1 G /user/hive/warehouse/parquet_compression.db/parquet_snappy
13.5 G /user/hive/warehouse/parquet_compression.db/parquet_gzip
32.8 G /user/hive/warehouse/parquet_compression.db/parquet_none
```

Because Parquet data files are typically large, each directory will have a different number of data files and the row groups will be arranged differently.

At the same time, the less aggressive the compression, the faster the data can be decompressed. In this case using a table with a billion rows, a query that evaluates all the values for a particular column runs faster with no compression than with Snappy compression, and faster with Snappy compression than with Gzip compression. Query performance depends on several other factors, so as always, run your own benchmarks with your own data to determine the ideal tradeoff between data size, CPU efficiency, and speed of insert and query operations.

```
[localhost:21000] > desc parquet_snappy;
Query finished, fetching results ...
+-----+-----+-----+
| name   | type  | comment |
+-----+-----+-----+
| id     | int   |         |
| val    | int   |         |
| zfill  | string|         |
| name   | string|         |
| assertion | boolean|       |
+-----+-----+-----+
Returned 5 row(s) in 0.14s
[localhost:21000] > select avg(val) from parquet_snappy;
Query finished, fetching results ...
+-----+
| _c0   |
+-----+
| 250000.93577915 |
+-----+
Returned 1 row(s) in 4.29s
[localhost:21000] > select avg(val) from parquet_gzip;
Query finished, fetching results ...
+-----+
| _c0   |
+-----+
| 250000.93577915 |
+-----+
Returned 1 row(s) in 6.97s
[localhost:21000] > select avg(val) from parquet_none;
```

```
Query finished, fetching results ...
+-----+
| _c0    |
+-----+
| 250000.93577915 |
+-----+
Returned 1 row(s) in 3.67s
```

Example of Copying Parquet Data Files

Here is a final example, to illustrate how the data files using the various compression codecs are all compatible with each other for read operations. The metadata about the compression format is written into each data file, and can be decoded during queries regardless of the `COMPRESSION_CODEC` setting in effect at the time. In this example, we copy data files from the `PARQUET_SNAPPY`, `PARQUET_GZIP`, and `PARQUET_NONE` tables used in the previous examples, each containing 1 billion rows, all to the data directory of a new table `PARQUET_EVERYTHING`. A couple of sample queries demonstrate that the new table now contains 3 billion rows featuring a variety of compression codecs for the data files.

First, we create the table in Impala so that there is a destination directory in HDFS to put the data files:

```
[localhost:21000] > create table parquet_everything like parquet_snappy;
Query: create table parquet_everything like parquet_snappy
```

Then in the shell, we copy the relevant data files into the data directory for this new table. Rather than using `hdfs dfs -cp` as with typical files, we use `hadoop distcp -pb` to ensure that the special block size of the Parquet data files is preserved.

```
$ hadoop distcp -pb /user/hive/warehouse/parquet_compression.db/
parquet_snappy \
  /user/hive/warehouse/parquet_compression.db/parquet_everything
...MapReduce output...
$ hadoop distcp -pb /user/hive/warehouse/parquet_compression.db/parquet_gzip
\
  /user/hive/warehouse/parquet_compression.db/parquet_everything
...MapReduce output...
$ hadoop distcp -pb /user/hive/warehouse/parquet_compression.db/parquet_none
\
  /user/hive/warehouse/parquet_compression.db/parquet_everything
...MapReduce output...
```

Back in the `impala-shell` interpreter, we use the `REFRESH` statement to alert the Impala server to the new data files for this table, then we can run queries demonstrating that the data files represent 3 billion rows, and the values for one of the numeric columns match what was in the original smaller tables:

```
[localhost:21000] > refresh parquet_everything;
Query finished, fetching results ...

Returned 0 row(s) in 0.32s
[localhost:21000] > select count(*) from parquet_everything;
Query finished, fetching results ...
+-----+
| _c0    |
+-----+
| 3000000000 |
+-----+
Returned 1 row(s) in 8.18s
[localhost:21000] > select avg(val) from parquet_everything;
Query finished, fetching results ...
+-----+
| _c0    |
+-----+
```



```
| 250000.93577915 |
+-----+
Returned 1 row(s) in 13.35s
```

Parquet Tables for Impala Complex Types

In Impala 2.3 and higher, Impala supports the complex types ARRAY, STRUCT, and MAP. In Impala 3.2 and higher, Impala also supports these complex types in ORC. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details. These Complex types are currently supported only for the Parquet or ORC file formats. Because Impala has better performance on Parquet than ORC, if you plan to use complex types, become familiar with the performance and storage aspects of Parquet first.

Exchanging Parquet Data Files with Other Hadoop Components

You can read and write Parquet data files from other Hadoop components. See the documentation for your Apache Hadoop distribution for details.

Previously, it was not possible to create Parquet data through Impala and reuse that table within Hive. Now that Parquet support is available for Hive, reusing existing Impala Parquet data files in Hive requires updating the table metadata. Use the following command if you are already running Impala 1.1.1 or higher:

```
ALTER TABLE table_name SET FILEFORMAT PARQUET;
```

If you are running a level of Impala that is older than 1.1.1, do the metadata update through Hive:

```
ALTER TABLE table_name SET SERDE 'parquet.hive.serde.ParquetHiveSerDe';
ALTER TABLE table_name SET FILEFORMAT
  INPUTFORMAT "parquet.hive.DeprecatedParquetInputFormat"
  OUTPUTFORMAT "parquet.hive.DeprecatedParquetOutputFormat";
```

Impala 1.1.1 and higher can reuse Parquet data files created by Hive, without any action required.

Impala supports the scalar data types that you can encode in a Parquet data file, but not composite or nested types such as maps or arrays. In Impala 2.2 and higher, Impala can query Parquet data files that include composite or nested types, as long as the query only refers to columns with scalar types.

If you copy Parquet data files between nodes, or even between different directories on the same node, make sure to preserve the block size by using the command `hadoop distcp -pb`. To verify that the block size was preserved, issue the command `hdfs fsck -blocks HDFS_path_of_impala_table_dir` and check that the average block size is at or near 256 MB (or whatever other size is defined by the `PARQUET_FILE_SIZE` query option).. (The `hadoop distcp` operation typically leaves some directories behind, with names matching `_distcp_logs_*`, that you can delete from the destination directory afterward.) Issue the command `hadoop distcp` for details about `distcp` command syntax.

Impala can query Parquet files that use the PLAIN, PLAIN_DICTIONARY, BIT_PACKED, RLE and RLE_DICTIONARY encodings. RLE_DICTIONARY is supported only in Impala 4.0 and up. When creating files outside of Impala for use by Impala, make sure to use one of the supported encodings. In particular, for MapReduce jobs, `parquet.writer.version` must not be defined (especially as `PARQUET_2_0`) for writing the configurations of Parquet MR jobs. Use the default version (or format). The default format, 1.0, includes some enhancements that are compatible with older versions. Data using the 2.0 format might not be consumable by Impala, due to use of the RLE_DICTIONARY encoding.

To examine the internal structure and data of Parquet files, you can use the `parquet-tools` command. Make sure this command is in your `$PATH`. (Typically, it is symlinked from `/usr/bin`; sometimes, depending on your installation setup, you might need to locate it under an alternative `bin` directory.) The arguments to this command let you perform operations such as:

- `cat`: Print a file's contents to standard out. In Impala 2.3 and higher, you can use the `-j` option to output JSON.
- `head`: Print the first few records of a file to standard output.
- `schema`: Print the Parquet schema for the file.

- meta: Print the file footer metadata, including key-value properties (like Avro schema), compression ratios, encodings, compression used, and row group information.
- dump: Print all data and metadata.

Use `parquet-tools -h` to see usage information for all the arguments. Here are some examples showing `parquet-tools` usage:

```
$ # Be careful doing this for a big file! Use parquet-tools head to be safe.
$ parquet-tools cat sample.parq
year = 1992
month = 1
day = 2
dayofweek = 4
dep_time = 748
crs_dep_time = 750
arr_time = 851
crs_arr_time = 846
carrier = US
flight_num = 53
actual_elapsed_time = 63
crs_elapsed_time = 56
arrdelay = 5
depdelay = -2
origin = CMH
dest = IND
distance = 182
cancelled = 0
diverted = 0

year = 1992
month = 1
day = 3
...
```

```
$ parquet-tools head -n 2 sample.parq
year = 1992
month = 1
day = 2
dayofweek = 4
dep_time = 748
crs_dep_time = 750
arr_time = 851
crs_arr_time = 846
carrier = US
flight_num = 53
actual_elapsed_time = 63
crs_elapsed_time = 56
arrdelay = 5
depdelay = -2
origin = CMH
dest = IND
distance = 182
cancelled = 0
diverted = 0

year = 1992
month = 1
day = 3
...
```

```
$ parquet-tools schema sample.parq
message schema {
  optional int32 year;
  optional int32 month;
  optional int32 day;
  optional int32 dayofweek;
  optional int32 dep_time;
  optional int32 crs_dep_time;
  optional int32 arr_time;
  optional int32 crs_arr_time;
  optional binary carrier;
  optional int32 flight_num;
  ...
}
```

```
$ parquet-tools meta sample.parq
creator:          impala version 2.2.0-...

file schema:      schema
-----
year:             OPTIONAL INT32 R:0 D:1
month:           OPTIONAL INT32 R:0 D:1
day:             OPTIONAL INT32 R:0 D:1
dayofweek:       OPTIONAL INT32 R:0 D:1
dep_time:        OPTIONAL INT32 R:0 D:1
crs_dep_time:    OPTIONAL INT32 R:0 D:1
arr_time:        OPTIONAL INT32 R:0 D:1
crs_arr_time:    OPTIONAL INT32 R:0 D:1
carrier:         OPTIONAL BINARY R:0 D:1
flight_num:      OPTIONAL INT32 R:0 D:1
...

row group 1:      RC:20636601 TS:265103674
-----
year:             INT32 SNAPPY DO:4 FPO:35 SZ:10103/49723/4.92
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
month:           INT32 SNAPPY DO:10147 FPO:10210 SZ:11380/35732/3.14
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
day:             INT32 SNAPPY DO:21572 FPO:21714
SZ:3071658/9868452/3.21 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
dayofweek:       INT32 SNAPPY DO:3093276 FPO:3093319
SZ:2274375/5941876/2.61 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
dep_time:        INT32 SNAPPY DO:5367705 FPO:5373967
SZ:28281281/28573175/1.01 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
crs_dep_time:    INT32 SNAPPY DO:33649039 FPO:33654262
SZ:10220839/11574964/1.13 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
arr_time:        INT32 SNAPPY DO:43869935 FPO:43876489
SZ:28562410/28797767/1.01 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
crs_arr_time:    INT32 SNAPPY DO:72432398 FPO:72438151
SZ:10908972/12164626/1.12 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
carrier:         BINARY SNAPPY DO:83341427 FPO:83341558
SZ:114916/128611/1.12 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
flight_num:      INT32 SNAPPY DO:83456393 FPO:83488603
SZ:10216514/11474301/1.12 VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
...
```

How Parquet Data Files Are Organized

Although Parquet is a column-oriented file format, do not expect to find one data file for each column. Parquet keeps all the data for a row within the same data file, to ensure that the columns for a row are always available on the same node for processing. What Parquet does is to set a large HDFS block size and a matching maximum data file size, to ensure that I/O and network transfer requests apply to large batches of data.

Within that data file, the data for a set of rows is rearranged so that all the values from the first column are organized in one contiguous block, then all the values from the second column, and so on. Putting the values from the same column next to each other lets Impala use effective compression techniques on the values in that column.

Note:

Impala `INSERT` statements write Parquet data files using an HDFS block size that matches the data file size, to ensure that each data file is represented by a single HDFS block, and the entire file can be processed on a single node without requiring any remote reads.

If you create Parquet data files outside of Impala, such as through a MapReduce or Pig job, ensure that the HDFS block size is greater than or equal to the file size, so that the “one file per block” relationship is maintained. Set the `dfs.block.size` or the `dfs.blocksize` property large enough that each file fits within a single HDFS block, even if that size is larger than the normal HDFS block size.

If the block size is reset to a lower value during a file copy, you will see lower performance for queries involving those files, and the `PROFILE` statement will reveal that some I/O is being done suboptimally, through remote reads. See [Example of Copying Parquet Data Files](#) on page 711 for an example showing how to preserve the block size when copying Parquet data files.

When Impala retrieves or tests the data for a particular column, it opens all the data files, but only reads the portion of each file containing the values for that column. The column values are stored consecutively, minimizing the I/O required to process the values within a single column. If other columns are named in the `SELECT` list or `WHERE` clauses, the data for all columns in the same row is available within that same data file.

If an `INSERT` statement brings in less than one Parquet block's worth of data, the resulting data file is smaller than ideal. Thus, if you do split up an ETL job to use multiple `INSERT` statements, try to keep the volume of data for each `INSERT` statement to approximately 256 MB, or a multiple of 256 MB.

RLE and Dictionary Encoding for Parquet Data Files

Parquet uses some automatic compression techniques, such as run-length encoding (RLE) and dictionary encoding, based on analysis of the actual data values. Once the data values are encoded in a compact form, the encoded data can optionally be further compressed using a compression algorithm. Parquet data files created by Impala can use Snappy, GZip, or no compression; the Parquet spec also allows LZO compression, but currently Impala does not support LZO-compressed Parquet files.

RLE and dictionary encoding are compression techniques that Impala applies automatically to groups of Parquet data values, in addition to any Snappy or GZip compression applied to the entire data files. These automatic optimizations can save you time and planning that are normally needed for a traditional data warehouse. For example, dictionary encoding reduces the need to create numeric IDs as abbreviations for longer string values.

Run-length encoding condenses sequences of repeated data values. For example, if many consecutive rows all contain the same value for a country code, those repeating values can be represented by the value followed by a count of how many times it appears consecutively.

Dictionary encoding takes the different values present in a column, and represents each one in compact 2-byte form rather than the original value, which could be several bytes. (Additional compression is applied to the compacted values, for extra space savings.) This type of encoding applies when the number of different values for a column is less than 2^{16} (16,384). It does not apply to columns of data type `BOOLEAN`, which are already very short. `TIMESTAMP` columns sometimes have a unique value for each row, in which case they can quickly exceed the 2^{16} limit on distinct values. The 2^{16} limit on different values within a column is reset for each data file, so if several different data files each contained 10,000 different city names, the city name column in each data file could still be condensed using dictionary encoding.

Compacting Data Files for Parquet Tables

If you reuse existing table structures or ETL processes for Parquet tables, you might encounter a “many small files” situation, which is suboptimal for query efficiency. For example, statements like these might produce inefficiently organized data files:

```
-- In an N-node cluster, each node produces a data file
-- for the INSERT operation. If you have less than
-- N GB of data to copy, some files are likely to be
-- much smaller than the default Parquet block size.
insert into parquet_table select * from text_table;

-- Even if this operation involves an overall large amount of data,
-- when split up by year/month/day, each partition might only
-- receive a small amount of data. Then the data files for
-- the partition might be divided between the N nodes in the cluster.
-- A multi-gigabyte copy operation might produce files of only
-- a few MB each.
insert into partitioned_parquet_table partition (year, month, day)
  select year, month, day, url, referer, user_agent, http_code,
  response_time
  from web_stats;
```

Here are techniques to help you produce large data files in Parquet INSERT operations, and to compact existing too-small data files:

- When inserting into a partitioned Parquet table, use statically partitioned INSERT statements where the partition key values are specified as constant values. Ideally, use a separate INSERT statement for each partition.
- You might set the NUM_NODES option to 1 briefly, during INSERT or CREATE TABLE AS SELECT statements. Normally, those statements produce one or more data files per data node. If the write operation involves small amounts of data, a Parquet table, and/or a partitioned table, the default behavior could produce many small files when intuitively you might expect only a single output file. SET NUM_NODES=1 turns off the “distributed” aspect of the write operation, making it more likely to produce only one or a few data files.
- Be prepared to reduce the number of partition key columns from what you are used to with traditional analytic database systems.
- Do not expect Impala-written Parquet files to fill up the entire Parquet block size. Impala estimates on the conservative side when figuring out how much data to write to each Parquet file. Typically, the of uncompressed data in memory is substantially reduced on disk by the compression and encoding techniques in the Parquet file format. The final data file size varies depending on the compressibility of the data. Therefore, it is not an indication of a problem if 256 MB of text data is turned into 2 Parquet data files, each less than 256 MB.
- If you accidentally end up with a table with many small data files, consider using one or more of the preceding techniques and copying all the data into a new Parquet table, either through CREATE TABLE AS SELECT or INSERT ... SELECT statements.

To avoid rewriting queries to change table names, you can adopt a convention of always running important queries against a view. Changing the view definition immediately switches any subsequent queries to use the new underlying tables:

```
create view production_table as select * from table_with_many_small_files;
-- CTAS or INSERT...SELECT all the data into a more efficient layout...
alter view production_table as select * from table_with_few_big_files;
select * from production_table where c1 = 100 and c2 < 50 and ...;
```

Schema Evolution for Parquet Tables

Schema evolution refers to using the statement ALTER TABLE ... REPLACE COLUMNS to change the names, data type, or number of columns in a table. You can perform schema evolution for Parquet tables as follows:

- The Impala `ALTER TABLE` statement never changes any data files in the tables. From the Impala side, schema evolution involves interpreting the same data files in terms of a new table definition. Some types of schema changes make sense and are represented correctly. Other types of changes cannot be represented in a sensible way, and produce special result values or conversion errors during queries.
- The `INSERT` statement always creates data using the latest table definition. You might end up with data files with different numbers of columns or internal data representations if you do a sequence of `INSERT` and `ALTER TABLE ... REPLACE COLUMNS` statements.
- If you use `ALTER TABLE ... REPLACE COLUMNS` to define additional columns at the end, when the original data files are used in a query, these final columns are considered to be all `NULL` values.
- If you use `ALTER TABLE ... REPLACE COLUMNS` to define fewer columns than before, when the original data files are used in a query, the unused columns still present in the data file are ignored.
- Parquet represents the `TINYINT`, `SMALLINT`, and `INT` types the same internally, all stored in 32-bit integers.
 - That means it is easy to promote a `TINYINT` column to `SMALLINT` or `INT`, or a `SMALLINT` column to `INT`. The numbers are represented exactly the same in the data file, and the columns being promoted would not contain any out-of-range values.
 - If you change any of these column types to a smaller type, any values that are out-of-range for the new type are returned incorrectly, typically as negative numbers.
 - You cannot change a `TINYINT`, `SMALLINT`, or `INT` column to `BIGINT`, or the other way around. Although the `ALTER TABLE` succeeds, any attempt to query those columns results in conversion errors.
 - Any other type conversion for columns produces a conversion error during queries. For example, `INT` to `STRING`, `FLOAT` to `DOUBLE`, `TIMESTAMP` to `STRING`, `DECIMAL(9,0)` to `DECIMAL(5,2)`, and so on.

You might find that you have Parquet files where the columns do not line up in the same order as in your Impala table. For example, you might have a Parquet file that was part of a table with columns `C1`, `C2`, `C3`, `C4`, and now you want to reuse the same Parquet file in a table with columns `C4`, `C2`. By default, Impala expects the columns in the data file to appear in the same order as the columns defined for the table, making it impractical to do some kinds of file reuse or schema evolution. In Impala 2.6 and higher, the query option `PARQUET_FALLBACK_SCHEMA_RESOLUTION=name` lets Impala resolve columns by name, and therefore handle out-of-order or extra columns in the data file. For example:

```
create database schema_evolution;
use schema_evolution;
create table t1 (c1 int, c2 boolean, c3 string, c4 timestamp)
  stored as parquet;
insert into t1 values
  (1, true, 'yes', now()),
  (2, false, 'no', now() + interval 1 day);

select * from t1;
+-----+-----+-----+-----+
| c1 | c2 | c3 | c4 |
+-----+-----+-----+-----+
| 1 | true | yes | 2016-06-28 14:53:26.554369000 |
| 2 | false | no | 2016-06-29 14:53:26.554369000 |
+-----+-----+-----+-----+

desc formatted t1;
...
| Location: | /user/hive/warehouse/schema_evolution.db/t1 |
...

-- Make T2 have the same data file as in T1, including 2
-- unused columns and column order different than T2 expects.
load data inpath '/user/hive/warehouse/schema_evolution.db/t1'
  into table t2;

+-----+-----+
| summary |
+-----+-----+
```

```
| Loaded 1 file(s). Total files in destination location: 1 |
+-----+

-- 'position' is the default setting.
-- Impala cannot read the Parquet file if the column order does not match.
set PARQUET_FALLBACK_SCHEMA_RESOLUTION=position;
PARQUET_FALLBACK_SCHEMA_RESOLUTION set to position

select * from t2;
WARNINGS:
File 'schema_evolution.db/t2/45331705_data.0.parq'
has an incompatible Parquet schema for column 'schema_evolution.t2.c4'.
Column type: TIMESTAMP, Parquet schema: optional int32 c1 [i:0 d:1 r:0]

File 'schema_evolution.db/t2/45331705_data.0.parq'
has an incompatible Parquet schema for column 'schema_evolution.t2.c4'.
Column type: TIMESTAMP, Parquet schema: optional int32 c1 [i:0 d:1 r:0]

-- With the 'name' setting, Impala can read the Parquet data files
-- despite mismatching column order.
set PARQUET_FALLBACK_SCHEMA_RESOLUTION=name;
PARQUET_FALLBACK_SCHEMA_RESOLUTION set to name

select * from t2;
+-----+-----+
| c4                | c2    |
+-----+-----+
| 2016-06-28 14:53:26.554369000 | true  |
| 2016-06-29 14:53:26.554369000 | false |
+-----+-----+
```

See [PARQUET_FALLBACK_SCHEMA_RESOLUTION Query Option \(Impala 2.6 or higher only\)](#) on page 382 for more details.

Data Type Considerations for Parquet Tables

The Parquet format defines a set of data types whose names differ from the names of the corresponding Impala data types. If you are preparing Parquet files using other Hadoop components such as Pig or MapReduce, you might need to work with the type names defined by Parquet. The following tables list the Parquet-defined types and the equivalent types in Impala.

Primitive types

Parquet type	Impala type
BINARY	STRING
BOOLEAN	BOOLEAN
DOUBLE	DOUBLE
FLOAT	FLOAT
INT32	INT
INT64	BIGINT
INT96	TIMESTAMP

Logical types

Parquet uses type annotations to extend the types that it can store, by specifying how the primitive types should be interpreted.

Parquet primitive type and annotation	Impala type
BINARY annotated with the UTF8 OriginalType	STRING
BINARY annotated with the STRING LogicalType	STRING
BINARY annotated with the ENUM OriginalType	STRING
BINARY annotated with the DECIMAL OriginalType	DECIMAL
INT64 annotated with the TIMESTAMP_MILLIS OriginalType	TIMESTAMP (in Impala 3.2 or higher) or BIGINT (for backward compatibility)
INT64 annotated with the TIMESTAMP_MICROS OriginalType	TIMESTAMP (in Impala 3.2 or higher) or BIGINT (for backward compatibility)
INT64 annotated with the TIMESTAMP LogicalType	TIMESTAMP (in Impala 3.2 or higher) or BIGINT (for backward compatibility)

Complex types:

For the complex types (ARRAY, MAP, and STRUCT) available in Impala 2.3 and higher, Impala only supports queries against those types in Parquet tables.

Using the ORC File Format with Impala Tables

Impala supports using ORC data files. By default, ORC reads are enabled in Impala 3.4.0 and higher.

Table 2: ORC Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
<i>ORC</i>	Structured	gzip, Snappy, LZO, LZ4; currently gzip by default	Yes, in Impala 2.12.0 and higher. By default, ORC reads are enabled in Impala 3.4.0 and higher.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.

Creating ORC Tables and Loading Data

If you do not have an existing data file to use, begin by creating one in the appropriate format.

To create an ORC table:

In the `impala-shell` interpreter, issue a command similar to:

```
CREATE TABLE orc_table (column_specs) STORED AS ORC;
```

Because Impala can query some kinds of tables that it cannot currently write to, after creating tables of certain file formats, you might use the Hive shell to load the data. See [How Impala Works with Hadoop File Formats](#) on page 695 for details. After loading data into a table through Hive or other mechanism outside of Impala, issue

a `REFRESH table_name` statement the next time you connect to the Impala node, before querying the table, to make Impala recognize the new data.

For example, here is how you might create some ORC tables in Impala (by specifying the columns explicitly, or cloning the structure of another table), load data through Hive, and query them through Impala:

```
$ impala-shell -i localhost
[localhost:21000] default> CREATE TABLE orc_table (x INT) STORED AS ORC;
[localhost:21000] default> CREATE TABLE orc_clone LIKE some_other_table
  STORED AS ORC;
[localhost:21000] default> quit;

$ hive
hive> INSERT INTO TABLE orc_table SELECT x FROM some_other_table;
3 Rows loaded to orc_table
Time taken: 4.169 seconds
hive> quit;

$ impala-shell -i localhost
[localhost:21000] default> SELECT * FROM orc_table;
Fetched 0 row(s) in 0.11s
[localhost:21000] default> -- Make Impala recognize the data loaded through
  Hive;
[localhost:21000] default> REFRESH orc_table;
[localhost:21000] default> SELECT * FROM orc_table;
+----+
|  x  |
+----+
|  1  |
|  2  |
|  3  |
+----+
Fetched 3 row(s) in 0.11s
```

Enabling Compression for ORC Tables

ORC tables are in zlib (Deflate in Impala) compression in default. You may want to use Snappy or LZO compression on existing tables for different balance between compression ratio and decompression speed. In Hive-1.1.0, the supported compressions for ORC tables are NONE, ZLIB, SNAPPY and LZO. For example, to enable Snappy compression, you would specify the following additional settings when loading data through the Hive shell:

```
hive> SET hive.exec.compress.output=true;
hive> SET orc.compress=SNAPPY;
hive> INSERT OVERWRITE TABLE new_table SELECT * FROM old_table;
```

If you are converting partitioned tables, you must complete additional steps. In such a case, specify additional settings similar to the following:

```
hive> CREATE TABLE new_table (your_cols) PARTITIONED BY (partition_cols)
  STORED AS new_format;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE new_table
  PARTITION(comma_separated_partition_cols) SELECT * FROM old_table;
```

Remember that Hive does not require that you specify a source format for it. Consider the case of converting a table with two partition columns called `year` and `month` to a Snappy compressed ORC table. Combining the components outlined previously to complete this table conversion, you would specify settings similar to the following:

```
hive> CREATE TABLE tbl_orc (int_col INT, string_col STRING) STORED AS ORC;
hive> SET hive.exec.compress.output=true;
```



```
hive> SET orc.compress=SNAPPY;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_orc SELECT * FROM tbl;
```

To complete a similar process for a table that includes partitions, you would specify settings similar to the following:

```
hive> CREATE TABLE tbl_orc (int_col INT, string_col STRING) PARTITIONED BY
  (year INT) STORED AS ORC;
hive> SET hive.exec.compress.output=true;
hive> SET orc.compress=SNAPPY;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_orc PARTITION(year) SELECT * FROM tbl;
```

Note:

The compression type is specified in the following command:

```
SET orc.compress=SNAPPY;
```

You could elect to specify alternative codecs such as `NONE`, `GZIP`, `LZO` here.

Query Performance for Impala ORC Tables

In general, expect query performance with ORC tables to be faster than with tables using text data, but slower than with Parquet tables since there're bunch of optimizations for Parquet. See [Using the Parquet File Format with Impala Tables](#) on page 705 for information about using the Parquet file format for high-performance analytic queries.

In Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, ORC, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Data Type Considerations for ORC Tables

The ORC format defines a set of data types whose names differ from the names of the corresponding Impala data types. If you are preparing ORC files using other Hadoop components such as Pig or MapReduce, you might need to work with the type names defined by ORC. The following figure lists the ORC-defined types and the equivalent types in Impala.

Primitive types:

```
BINARY -> STRING
BOOLEAN -> BOOLEAN
DOUBLE -> DOUBLE
FLOAT -> FLOAT
TINYINT -> TINYINT
SMALLINT -> SMALLINT
INT -> INT
BIGINT -> BIGINT
TIMESTAMP -> TIMESTAMP
DATE (not supported)
```

Complex types:

In Impala 2.3 and higher, Impala supports the complex types ARRAY, STRUCT, and MAP. In Impala 3.2 and higher, Impala also supports these complex types in ORC. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details. These Complex types are currently supported only for the Parquet or ORC file formats. Because Impala has better performance on Parquet than ORC, if you plan to use complex types, become familiar with the performance and storage aspects of Parquet first.

Using the Avro File Format with Impala Tables

Impala supports using tables whose data files use the Avro file format. Impala can query Avro tables. In Impala 1.4.0 and higher, Impala can create Avro tables, but cannot insert data into them. For insert operations, use Hive, then switch back to Impala to run queries.

Table 3: Avro Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
Avro	Structured	Snappy, gzip, deflate	Yes, in Impala 1.4.0 and higher. In lower versions, create the table using Hive.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.

Creating Avro Tables

To create a new table using the Avro file format, issue the CREATE TABLE statement through Impala with the STORED AS AVRO clause, or through Hive. If you create the table through Impala, you must include column definitions that match the fields specified in the Avro schema. With Hive, you can omit the columns and just specify the Avro schema.

In Impala 2.3 and higher, the CREATE TABLE for Avro tables can include SQL-style column definitions rather than specifying Avro notation through the TBLPROPERTIES clause. Impala issues warning messages if there are any mismatches between the types specified in the SQL column definitions and the underlying types; for example, any TINYINT or SMALLINT columns are treated as INT in the underlying Avro files, and therefore are displayed as INT in any DESCRIBE or SHOW CREATE TABLE output.

Note:

Currently, Avro tables cannot contain TIMESTAMP columns. If you need to store date and time values in Avro tables, as a workaround you can use a STRING representation of the values, convert the values to BIGINT with the UNIX_TIMESTAMP() function, or create separate numeric columns for individual date and time fields using the EXTRACT() function.

The following examples demonstrate creating an Avro table in Impala, using either an inline column specification or one taken from a JSON file stored in HDFS:

```
[localhost:21000] > CREATE TABLE avro_only_sql_columns
> (
>   id INT,
>   bool_col BOOLEAN,
>   tinyint_col TINYINT, /* Gets promoted to INT */
>   smallint_col SMALLINT, /* Gets promoted to INT */
>   int_col INT,
>   bigint_col BIGINT,
>   float_col FLOAT,
>   double_col DOUBLE,
```

```

> date_string_col STRING,
> string_col STRING
> )
> STORED AS AVRO;

[localhost:21000] > CREATE TABLE impala_avro_table
> (bool_col BOOLEAN, int_col INT, long_col BIGINT,
float_col FLOAT, double_col DOUBLE, string_col STRING, nullable_int INT)
> STORED AS AVRO
> TBLPROPERTIES ('avro.schema.literal'='{
>   "name": "my_record",
>   "type": "record",
>   "fields": [
>     {"name": "bool_col", "type": "boolean"},
>     {"name": "int_col", "type": "int"},
>     {"name": "long_col", "type": "long"},
>     {"name": "float_col", "type": "float"},
>     {"name": "double_col", "type": "double"},
>     {"name": "string_col", "type": "string"},
>     {"name": "nullable_int", "type": ["null",
"int"]}]})');

[localhost:21000] > CREATE TABLE avro_examples_of_all_types (
>   id INT,
>   bool_col BOOLEAN,
>   tinyint_col TINYINT,
>   smallint_col SMALLINT,
>   int_col INT,
>   bigint_col BIGINT,
>   float_col FLOAT,
>   double_col DOUBLE,
>   date_string_col STRING,
>   string_col STRING
> )
> STORED AS AVRO
> TBLPROPERTIES ('avro.schema.url'='hdfs://
localhost:8020/avro_schemas/alltypes.json');

```

The following example demonstrates creating an Avro table in Hive:

```

hive> CREATE TABLE hive_avro_table
> ROW FORMAT SERDE 'org.apache.hadoop.hive.serde2.avro.AvroSerDe'
> STORED AS INPUTFORMAT
'org.apache.hadoop.hive.ql.io.avro.AvroContainerInputFormat'
> OUTPUTFORMAT
'org.apache.hadoop.hive.ql.io.avro.AvroContainerOutputFormat'
> TBLPROPERTIES ('avro.schema.literal'='{
>   "name": "my_record",
>   "type": "record",
>   "fields": [
>     {"name": "bool_col", "type": "boolean"},
>     {"name": "int_col", "type": "int"},
>     {"name": "long_col", "type": "long"},
>     {"name": "float_col", "type": "float"},
>     {"name": "double_col", "type": "double"},
>     {"name": "string_col", "type": "string"},
>     {"name": "nullable_int", "type": ["null", "int"]}]})');

```

Each field of the record becomes a column of the table. Note that any other information, such as the record name, is ignored.

Note: For nullable Avro columns, make sure to put the "null" entry before the actual type name. In Impala, all columns are nullable; Impala currently does not have a NOT NULL clause. Any non-nullable property is only enforced on the Avro side.

Most column types map directly from Avro to Impala under the same names. These are the exceptions and special cases to consider:

- The DECIMAL type is defined in Avro as a BYTE type with the `logicalType` property set to "decimal" and a specified precision and scale.
- The Avro long type maps to BIGINT in Impala.

If you create the table through Hive, switch back to `impala-shell` and issue an `INVALIDATE METADATA table_name` statement. Then you can run queries for that table through `impala-shell`.

In rare instances, a mismatch could occur between the Avro schema and the column definitions in the metastore database. In Impala 2.3 and higher, Impala checks for such inconsistencies during a `CREATE TABLE` statement and each time it loads the metadata for a table (for example, after `INVALIDATE METADATA`). Impala uses the following rules to determine how to treat mismatching columns, a process known as *schema reconciliation*:

- If there is a mismatch in the number of columns, Impala uses the column definitions from the Avro schema.
- If there is a mismatch in column name or type, Impala uses the column definition from the Avro schema. Because a CHAR or VARCHAR column in Impala maps to an Avro STRING, this case is not considered a mismatch and the column is preserved as CHAR or VARCHAR in the reconciled schema. Prior to Impala 2.7 the column name and comment for such CHAR and VARCHAR columns was also taken from the SQL column definition. In Impala 2.7 and higher, the column name and comment from the Avro schema file take precedence for such columns, and only the CHAR or VARCHAR type is preserved from the SQL column definition.
- An Impala TIMESTAMP column definition maps to an Avro STRING and is presented as a STRING in the reconciled schema, because Avro has no binary TIMESTAMP representation. As a result, no Avro table can have a TIMESTAMP column; this restriction is the same as in earlier Impala releases.

Complex type considerations: Although you can create tables in this file format using the complex types (ARRAY, STRUCT, and MAP) available in Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in Impala 2.6 and higher.

Using a Hive-Created Avro Table in Impala

If you have an Avro table created through Hive, you can use it in Impala as long as it contains only Impala-compatible data types. It cannot contain:

- Complex types: array, map, record, struct, union other than `[supported_type, null]` or `[null, supported_type]`
- The Avro-specific types enum, bytes, and fixed
- Any scalar type other than those listed in [Data Types](#) on page 102

Because Impala and Hive share the same metastore database, Impala can directly access the table definitions and data for tables that were created in Hive.

If you create an Avro table in Hive, issue an `INVALIDATE METADATA` the next time you connect to Impala through `impala-shell`. This is a one-time operation to make Impala aware of the new table. You can issue the statement while connected to any Impala node, and the catalog service broadcasts the change to all other Impala nodes.

If you load new data into an Avro table through Hive, either through a Hive `LOAD DATA` or `INSERT` statement, or by manually copying or moving files into the data directory for the table, issue a `REFRESH table_name` statement the next time you connect to Impala through `impala-shell`. You can issue the statement while connected to any Impala node, and the catalog service broadcasts the change to all other Impala nodes. If you issue the `LOAD DATA` statement through Impala, you do not need a `REFRESH` afterward.

Impala only supports fields of type boolean, int, long, float, double, and string, or unions of these types with null; for example, `["string", "null"]`. Unions with null essentially create a nullable type.

Specifying the Avro Schema through JSON

While you can embed a schema directly in your `CREATE TABLE` statement, as shown above, column width restrictions in the Hive metastore limit the length of schema you can specify. If you encounter problems with long schema literals, try storing your schema as a JSON file in HDFS instead. Specify your schema in HDFS using table properties similar to the following:

```
tblproperties ('avro.schema.url'='hdfs://your-name-node:port/path/to/
schema.json');
```

Loading Data into an Avro Table

Currently, Impala cannot write Avro data files. Therefore, an Avro table cannot be used as the destination of an Impala `INSERT` statement or `CREATE TABLE AS SELECT`.

To copy data from another table, issue any `INSERT` statements through Hive. For information about loading data into Avro tables through Hive, see [Avro page on the Hive wiki](#).

If you already have data files in Avro format, you can also issue `LOAD DATA` in either Impala or Hive. Impala can move existing Avro data files into an Avro table, it just cannot create new Avro data files.

Enabling Compression for Avro Tables

To enable compression for Avro tables, specify settings in the Hive shell to enable compression and to specify a codec, then issue a `CREATE TABLE` statement as in the preceding examples. Impala supports the `snappy` and `deflate` codecs for Avro tables.

For example:

```
hive> set hive.exec.compress.output=true;
hive> set avro.output.codec=snappy;
```

How Impala Handles Avro Schema Evolution

Starting in Impala 1.1, Impala can deal with Avro data files that employ *schema evolution*, where different data files within the same table use slightly different type definitions. (You would perform the schema evolution operation by issuing an `ALTER TABLE` statement in the Hive shell.) The old and new types for any changed columns must be compatible, for example a column might start as an `int` and later change to a `bigint` or `float`.

As with any other tables where the definitions are changed or data is added outside of the current `impalad` node, ensure that Impala loads the latest metadata for the table if the Avro schema is modified through Hive. Issue a `REFRESH table_name` or `INVALIDATE METADATA table_name` statement. `REFRESH` reloads the metadata immediately, `INVALIDATE METADATA` reloads the metadata the next time the table is accessed.

When Avro data files or columns are not consulted during a query, Impala does not check for consistency. Thus, if you issue `SELECT c1, c2 FROM t1`, Impala does not return any error if the column `c3` changed in an incompatible way. If a query retrieves data from some partitions but not others, Impala does not check the data files for the unused partitions.

In the Hive DDL statements, you can specify an `avro.schema.literal` table property (if the schema definition is short) or an `avro.schema.url` property (if the schema definition is long, or to allow convenient editing for the definition).

For example, running the following SQL code in the Hive shell creates a table using the Avro file format and puts some sample data into it:

```
CREATE TABLE avro_table (a string, b string)
ROW FORMAT SERDE 'org.apache.hadoop.hive.serde2.avro.AvroSerDe'
STORED AS INPUTFORMAT
  'org.apache.hadoop.hive.ql.io.avro.AvroContainerInputFormat'
OUTPUTFORMAT 'org.apache.hadoop.hive.ql.io.avro.AvroContainerOutputFormat'
```

```
TBLPROPERTIES (
  'avro.schema.literal'='{
    "type": "record",
    "name": "my_record",
    "fields": [
      {"name": "a", "type": "int"},
      {"name": "b", "type": "string"}
    ]}' );

INSERT OVERWRITE TABLE avro_table SELECT 1, "avro" FROM functional.alltypes
LIMIT 1;
```

Once the Avro table is created and contains data, you can query it through the `impala-shell` command:

```
[localhost:21000] > select * from avro_table;
+---+-----+
| a | b      |
+---+-----+
| 1 | avro   |
+---+-----+
```

Now in the Hive shell, you change the type of a column and add a new column with a default value:

```
-- Promote column "a" from INT to FLOAT (no need to update Avro schema)
ALTER TABLE avro_table CHANGE A A FLOAT;

-- Add column "c" with default
ALTER TABLE avro_table ADD COLUMNS (c int);
ALTER TABLE avro_table SET TBLPROPERTIES (
  'avro.schema.literal'='{
    "type": "record",
    "name": "my_record",
    "fields": [
      {"name": "a", "type": "int"},
      {"name": "b", "type": "string"},
      {"name": "c", "type": "int", "default": 10}
    ]}' );
```

Once again in `impala-shell`, you can query the Avro table based on its latest schema definition. Because the table metadata was changed outside of Impala, you issue a `REFRESH` statement first so that Impala has up-to-date metadata for the table.

```
[localhost:21000] > refresh avro_table;
[localhost:21000] > select * from avro_table;
+---+-----+-----+
| a | b      | c      |
+---+-----+-----+
| 1 | avro   | 10     |
+---+-----+-----+
```

Data Type Considerations for Avro Tables

The Avro format defines a set of data types whose names differ from the names of the corresponding Impala data types. If you are preparing Avro files using other Hadoop components such as Pig or MapReduce, you might need to work with the type names defined by Avro. The following figure lists the Avro-defined types and the equivalent types in Impala.

Primitive types:

Avro type	Impala type
STRING	STRING
STRING	CHAR
STRING	VARCHAR
INT	INT
BOOLEAN	BOOLEAN
LONG	BIGINT
FLOAT	FLOAT
DOUBLE	DOUBLE

The Avro specification allows string values up to 2^{64} bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths.

In Impala 2.5 and higher, Impala truncates CHAR and VARCHAR values in Avro tables to $(2^{31})-1$ bytes. If a query encounters a STRING value longer than $(2^{31})-1$ bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Logical types:

Avro type	Impala type
BYTES annotated	DECIMAL
INT32 annotated	DATE

Impala does not support the following Avro data types: RECORD, MAP, ARRAY, UNION, ENUM, FIXED, NULL

Query Performance for Impala Avro Tables

In general, expect query performance with Avro tables to be faster than with tables using text data, but slower than with Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 705 for information about using the Parquet file format for high-performance analytic queries.

In Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, ORC, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Using the Hudi File Format

Impala supports Read Optimized Queries on Hudi tables as an experimental feature. Read Optimized Queries treat the latest table snapshot as the commit or compaction action, expose only base/columnar files in latest file slices, and guarantee the same columnar query performance as a non-Hudi columnar table.

Table 4: Hudi Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
<i>Hudi</i>	Structured	Snappy, gzip, zstd, lz4; currently Snappy by default	Yes, support for Read Optimized Queries is experimental.	No. Create an external table in Impala. Set the table location to the Hudi table directory. Alternatively, create the Hudi table in Hive.

Using the RCFile File Format with Impala Tables

Impala supports using RCFile data files.

Table 5: RCFile Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
<i>RCFile</i>	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.

Creating RCFile Tables and Loading Data

If you do not have an existing data file to use, begin by creating one in the appropriate format.

To create an RCFile table:

In the `impala-shell` interpreter, issue a command similar to:

```
create table rcfile_table (column_specs) stored as rcfile;
```

Because Impala can query some kinds of tables that it cannot currently write to, after creating tables of certain file formats, you might use the Hive shell to load the data. See [How Impala Works with Hadoop File Formats](#) on page 695 for details. After loading data into a table through Hive or other mechanism outside of Impala, issue a `REFRESH table_name` statement the next time you connect to the Impala node, before querying the table, to make Impala recognize the new data.

Important: See [Known Issues and Workarounds in Impala](#) on page 878 for potential compatibility issues with RCFile tables created in Hive 0.12, due to a change in the default RCFile SerDe for Hive.

For example, here is how you might create some RCFile tables in Impala (by specifying the columns explicitly, or cloning the structure of another table), load data through Hive, and query them through Impala:

```
$ impala-shell -i localhost
[localhost:21000] > create table rcfile_table (x int) stored as rcfile;
[localhost:21000] > create table rcfile_clone like some_other_table stored
as rcfile;
[localhost:21000] > quit;

$ hive
hive> insert into table rcfile_table select x from some_other_table;
3 Rows loaded to rcfile_table
```



```

Time taken: 19.015 seconds
hive> quit;

$ impala-shell -i localhost
[localhost:21000] > select * from rcfile_table;
Returned 0 row(s) in 0.23s
[localhost:21000] > -- Make Impala recognize the data loaded through Hive;
[localhost:21000] > refresh rcfile_table;
[localhost:21000] > select * from rcfile_table;
+----+
| x |
+----+
| 1 |
| 2 |
| 3 |
+----+
Returned 3 row(s) in 0.23s

```

Complex type considerations: Although you can create tables in this file format using the complex types (ARRAY, STRUCT, and MAP) available in Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is COUNT(*) queries on RCFile tables that include complex types. Such queries are allowed in Impala 2.6 and higher.

Enabling Compression for RCFile Tables

You may want to enable compression on existing tables. Enabling compression provides performance gains in most cases and is supported for RCFile tables. For example, to enable Snappy compression, you would specify the following additional settings when loading data through the Hive shell:

```

hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET
    mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> INSERT OVERWRITE TABLE new_table SELECT * FROM old_table;

```

If you are converting partitioned tables, you must complete additional steps. In such a case, specify additional settings similar to the following:

```

hive> CREATE TABLE new_table (your_cols) PARTITIONED BY (partition_cols)
    STORED AS new_format;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE new_table
    PARTITION(comma_separated_partition_cols) SELECT * FROM old_table;

```

Remember that Hive does not require that you specify a source format for it. Consider the case of converting a table with two partition columns called year and month to a Snappy compressed RCFile. Combining the components outlined previously to complete this table conversion, you would specify settings similar to the following:

```

hive> CREATE TABLE tbl_rc (int_col INT, string_col STRING) STORED AS RCFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET
    mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_rc SELECT * FROM tbl;

```

To complete a similar process for a table that includes partitions, you would specify settings similar to the following:

```
hive> CREATE TABLE tbl_rc (int_col INT, string_col STRING) PARTITIONED BY
  (year INT) STORED AS RCFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET
  mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_rc PARTITION(year) SELECT * FROM tbl;
```

Note:

The compression type is specified in the following command:

```
SET
  mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
```

You could elect to specify alternative codecs such as GzipCodec here.

Query Performance for Impala RCFile Tables

In general, expect query performance with RCFile tables to be faster than with tables using text data, but slower than with Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 705 for information about using the Parquet file format for high-performance analytic queries.

In Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, ORC, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Using the SequenceFile File Format with Impala Tables

Impala supports using SequenceFile data files.

Table 6: SequenceFile Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
SequenceFile	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH <i>table_name</i> in Impala.

Creating SequenceFile Tables and Loading Data

If you do not have an existing data file to use, begin by creating one in the appropriate format.

To create a SequenceFile table:

In the `impala-shell` interpreter, issue a command similar to:

```
create table sequencefile_table (column_specs) stored as sequencefile;
```

Because Impala can query some kinds of tables that it cannot currently write to, after creating tables of certain file formats, you might use the Hive shell to load the data. See [How Impala Works with Hadoop File Formats](#) on page 695 for details. After loading data into a table through Hive or other mechanism outside of Impala, issue a `REFRESH table_name` statement the next time you connect to the Impala node, before querying the table, to make Impala recognize the new data.

For example, here is how you might create some SequenceFile tables in Impala (by specifying the columns explicitly, or cloning the structure of another table), load data through Hive, and query them through Impala:

```
$ impala-shell -i localhost
[localhost:21000] > create table seqfile_table (x int) stored as
sequencefile;
[localhost:21000] > create table seqfile_clone like some_other_table stored
as sequencefile;
[localhost:21000] > quit;

$ hive
hive> insert into table seqfile_table select x from some_other_table;
3 Rows loaded to seqfile_table
Time taken: 19.047 seconds
hive> quit;

$ impala-shell -i localhost
[localhost:21000] > select * from seqfile_table;
Returned 0 row(s) in 0.23s
[localhost:21000] > -- Make Impala recognize the data loaded through Hive;
[localhost:21000] > refresh seqfile_table;
[localhost:21000] > select * from seqfile_table;
+----+
| x |
+----+
| 1 |
| 2 |
| 3 |
+----+
Returned 3 row(s) in 0.23s
```

Complex type considerations: Although you can create tables in this file format using the complex types (ARRAY, STRUCT, and MAP) available in Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in Impala 2.6 and higher.

Enabling Compression for SequenceFile Tables

You may want to enable compression on existing tables. Enabling compression provides performance gains in most cases and is supported for SequenceFile tables. For example, to enable Snappy compression, you would specify the following additional settings when loading data through the Hive shell:

```
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET
  mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> insert overwrite table new_table select * from old_table;
```

If you are converting partitioned tables, you must complete additional steps. In such a case, specify additional settings similar to the following:

```
hive> create table new_table (your_cols) partitioned by (partition_cols)
  stored as new_format;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> insert overwrite table new_table
  partition(comma_separated_partition_cols) select * from old_table;
```

Remember that Hive does not require that you specify a source format for it. Consider the case of converting a table with two partition columns called `year` and `month` to a Snappy compressed SequenceFile. Combining the components outlined previously to complete this table conversion, you would specify settings similar to the following:

```
hive> create table TBL_SEQ (int_col int, string_col string) STORED AS
  SEQUENCEFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET
  mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_seq SELECT * FROM tbl;
```

To complete a similar process for a table that includes partitions, you would specify settings similar to the following:

```
hive> CREATE TABLE tbl_seq (int_col INT, string_col STRING) PARTITIONED BY
  (year INT) STORED AS SEQUENCEFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET
  mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_seq PARTITION(year) SELECT * FROM tbl;
```

Note:

The compression type is specified in the following command:

```
SET
  mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
```

You could elect to specify alternative codecs such as `GzipCodec` here.

Query Performance for Impala SequenceFile Tables

In general, expect query performance with SequenceFile tables to be faster than with tables using text data, but slower than with Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 705 for information about using the Parquet file format for high-performance analytic queries.

In Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, ORC, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128

MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Using Impala to Query Kudu Tables

You can use Impala to query tables stored by Apache Kudu. This capability allows convenient access to a storage system that is tuned for different kinds of workloads than the default with Impala.

By default, Impala tables are stored on HDFS using data files with various file formats. HDFS files are ideal for bulk loads (append operations) and queries using full-table scans, but do not support in-place updates or deletes. Kudu is an alternative storage engine used by Impala which can do both in-place updates (for mixed read/write workloads) and fast scans (for data-warehouse/analytic operations). Using Kudu tables with Impala can simplify the ETL pipeline by avoiding extra steps to segregate and reorganize newly arrived data.

Certain Impala SQL statements and clauses, such as `DELETE`, `UPDATE`, `UPSERT`, and `PRIMARY KEY` work only with Kudu tables. Other statements and clauses, such as `LOAD DATA`, `TRUNCATE TABLE`, and `INSERT OVERWRITE`, are not applicable to Kudu tables.

Benefits of Using Kudu Tables with Impala

The combination of Kudu and Impala works best for tables where scan performance is important, but data arrives continuously, in small batches, or needs to be updated without being completely replaced. HDFS-backed tables can require substantial overhead to replace or reorganize data files as new data arrives. Impala can perform efficient lookups and scans within Kudu tables, and Impala can also perform update or delete operations efficiently. You can also use the Kudu Java, C++, and Python APIs to do ingestion or transformation operations outside of Impala, and Impala can query the current data at any time.

Configuring Impala for Use with Kudu

The `-kudu_master_hosts` configuration property must be set correctly for the `impalad` daemon, for `CREATE TABLE ... STORED AS KUDU` statements to connect to the appropriate Kudu server. Typically, the required value for this setting is `kudu_host:7051`. In a high-availability Kudu deployment, specify the names of multiple Kudu hosts separated by commas.

If the `-kudu_master_hosts` configuration property is not set, you can still associate the appropriate value for each table by specifying a `TBLPROPERTIES('kudu.master_addresses')` clause in the `CREATE TABLE` statement or changing the `TBLPROPERTIES('kudu.master_addresses')` value with an `ALTER TABLE` statement.

Cluster Topology for Kudu Tables

With HDFS-backed tables, you are typically concerned with the number of DataNodes in the cluster, how many and how large HDFS data files are read during a query, and therefore the amount of work performed by each DataNode and the network communication to combine intermediate results and produce the final result set.

With Kudu tables, the topology considerations are different, because:

- The underlying storage is managed and organized by Kudu, not represented as HDFS data files.
- Kudu handles some of the underlying mechanics of partitioning the data. You can specify the partitioning scheme with combinations of hash and range partitioning, so that you can decide how much effort to expend to manage the partitions as new data arrives. For example, you can construct partitions that apply to date ranges rather than a separate partition for each day or each hour.
- Data is physically divided based on units of storage called *tablets*. Tablets are stored by *tablet servers*. Each tablet server can store multiple tablets, and each tablet is replicated across multiple tablet servers, managed

automatically by Kudu. Where practical, co-locate the tablet servers on the same hosts as the Impala daemons, although that is not required.

Kudu Replication Factor

By default, Kudu tables created through Impala use a tablet replication factor of 3. To change the replication factor for a Kudu table, specify the replication factor using `TBLPROPERTIES ('kudu.num_tablet_replicas' = 'n')` in the [CREATE TABLE Statement](#).

The number of replicas for a Kudu table must be odd.

Altering the `kudu.num_tablet_replicas` property after table creation currently has no effect.

Impala DDL Enhancements for Kudu Tables (CREATE TABLE and ALTER TABLE)

You can use the Impala `CREATE TABLE` and `ALTER TABLE` statements to create and fine-tune the characteristics of Kudu tables. Because Kudu tables have features and properties that do not apply to other kinds of Impala tables, familiarize yourself with Kudu-related concepts and syntax first. For the general syntax of the `CREATE TABLE` statement for Kudu tables, see [CREATE TABLE Statement](#) on page 248.

Non-unique Primary Keys for Kudu Tables

Kudu now allows a user to create a non-unique primary key for a table when creating a table. The data engine handles this by appending a system generated auto-incrementing column to the non-unique primary key columns. This is done to guarantee the uniqueness of the primary key. This auto-incrementing column is named as 'auto_incrementing_id' with bigint type and this column is only system generated and cannot be explicitly created by the user. This auto_incrementing_id column is unique across a partition/tablet i.e. every partition/tablet would have this column starting from one and incrementing monotonically. The assignment to this column during insertion is automatic.

Create a Kudu Table with a non-unique PRIMARY KEY

The following example shows creating a table with a non-unique PRIMARY KEY.

```
CREATE TABLE kudu_tbl1
(
  id INT NON UNIQUE PRIMARY KEY,
  name STRING
)
PARTITION BY HASH (id) PARTITIONS 3 STORED as KUDU;
```

The effective PRIMARY KEY in the above case will be {id, auto_increment_id}

Note: "auto_incrementing_id" column cannot be added, removed or renamed with `ALTER TABLE` statements.

Verify the PRIMARY KEY is non-unique

You can now check the PRIMARY KEY created is non-unique by running the following `DESCRIBE` command. A new property "key_unique" shows if the primary key is unique. System generated column "auto_incrementing_id" is shown in the output for the table as a non-unique primary key.

```
describe kudu_tbl1
+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+
+-----+
```

```

+-----+-----+-----+-----+-----+
| name   | default_value | type   | comment | primary_key | key_unique | key_block_size |
+-----+-----+-----+-----+-----+
| id      |                | int    |          | true         | false      | 0               |
|         |                | AUTO_ENCODING |         | DEFAULT_COMPRESSION |         |                 |
| auto_incrementing_id |          | bigint |          | true         | false      | 0               |
|         |                | AUTO_ENCODING |         | DEFAULT_COMPRESSION |         |                 |
| name    |                | string |          | false        |            |                 |
|         |                | AUTO_ENCODING |         | DEFAULT_COMPRESSION |         |                 |
+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+
  Fetched 3 row(s) in 4.72s

```

Query Auto Incrementing Column

When you query a table using the `SELECT` statement, it will not display the system generated auto incrementing column unless the column is explicitly specified in the select list.

Create a Kudu table without a PRIMARY KEY attribute

You can create a Kudu table without specifying a PRIMARY KEY or a PARTITION KEY since they are optional, however you cannot create a Kudu table without specifying both PRIMARY KEY and PARTITION KEY. If you do not specify the primary key attribute, the partition key columns can be promoted as a non-unique primary key. This is possible only if those columns are the beginning columns of the table.

In the following example, 'a' and 'b' will be promoted as a non-unique primary key, 'auto_incrementing_id' column will be added by Kudu engine. 'a', 'b' and 'auto_incrementing_id' form the effective unique composite primary key.

```
CREATE TABLE auto_table
(
  a BIGINT,
  b STRING,
)
PARTITION BY HASH(a, b) PARTITIONS 2 STORED AS KUDU;
```

The effective primary key in this case would be {a, b, auto_incrementing_id}

Limitations

- UPSERT operation is not supported for Kudu tables with non-unique primary key. If you run an UPSERT statement for a Kudu table with a non-unique primary key it will fail with an error.
- Since the auto generated key for each row will be assigned after the row's data is generated and after the row lands in the tablet, you cannot use this column in the partition key.

Primary Key Columns for Kudu Tables

Kudu tables introduce the notion of primary keys to Impala for the first time. The primary key is made up of one or more columns, whose values are combined and used as a lookup key during queries. The primary key can be non-unique. The uniqueness of the primary key is guaranteed by appending a system-generated auto-incrementing column to the non-unique primary key columns. The tuple represented by these columns cannot contain any NULL values,

and can never be updated once inserted. For a Kudu table, all the partition key columns must come from the set of primary key columns.

The primary key has both physical and logical aspects:

- On the physical side, it is used to map the data values to particular tablets for fast retrieval. Because the tuples formed by the primary key values are unique, the primary key columns are typically highly selective.
- You can insert non-unique data using an INSERT statement but the data saved in Kudu table for each row which will be turned to unique by the system generated auto-incrementing column. If the primary key is non-unique, the uniqueness will not cause insertion failure. However, if the primary key is set as non-unique and if an INSERT operation fails part way through, all rows except the rows with writing errors will be added into the table. The duplicated rows will be added with different values for auto-incrementing columns.

Note:

Impala only allows PRIMARY KEY clauses and NOT NULL constraints on columns for Kudu tables. These constraints are enforced on the Kudu side.

Kudu-Specific Column Attributes for CREATE TABLE

For the general syntax of the CREATE TABLE statement for Kudu tables, see [CREATE TABLE Statement](#) on page 248. The following sections provide more detail for some of the Kudu-specific keywords you can use in column definitions.

The column list in a CREATE TABLE statement can include the following attributes, which only apply to Kudu tables:

```
[NON UNIQUE] PRIMARY KEY
| [NOT] NULL
| ENCODING codec
| COMPRESSION algorithm
| DEFAULT constant_expression
| BLOCK_SIZE number
```

See the following sections for details about each column attribute.

PRIMARY KEY Attribute

The primary key for a Kudu table is a column, or set of columns, that uniquely identifies every row. The primary key value also is used as the natural sort order for the values from the table. The primary key value for each row is based on the combination of values for the columns.

Because all of the primary key columns must have non-null values, specifying a column in the PRIMARY KEY or NON-UNIQUE PRIMARY KEY clause implicitly adds the NOT NULL attribute to that column.

The primary key columns must be the first ones specified in the CREATE TABLE statement. For a single-column primary key, you can include a PRIMARY KEY attribute inline with the column definition. For a multi-column primary key, you include a PRIMARY KEY (*c1*, *c2*, ...) clause as a separate entry at the end of the column list.

You can specify the PRIMARY KEY attribute either inline in a single column definition, or as a separate clause at the end of the column list:

```
CREATE TABLE pk_inline
(
  col1 BIGINT PRIMARY KEY,
  col2 STRING,
  col3 BOOLEAN
) PARTITION BY HASH(col1) PARTITIONS 2 STORED AS KUDU;

CREATE TABLE pk_at_end
```



```
(
  col1 BIGINT,
  col2 STRING,
  col3 BOOLEAN,
  PRIMARY KEY (col1)
) PARTITION BY HASH(col1) PARTITIONS 2 STORED AS KUDU;

CREATE TABLE pk_inline
(
  col1 BIGINT [NON UNIQUE] PRIMARY KEY,
  col2 STRING,
  col3 BOOLEAN
) PARTITION BY HASH(col1) PARTITIONS 2 STORED AS KUDU;

CREATE TABLE pk_at_end
(
  col1 BIGINT,
  col2 STRING,
  col3 BOOLEAN,
  [NON UNIQUE] PRIMARY KEY (col1)
) PARTITION BY HASH(col1) PARTITIONS 2 STORED AS KUDU;
```

When the primary key is a single column, these two forms are equivalent. If the primary key consists of more than one column, you must specify the primary key using a separate entry in the column list:

```
CREATE TABLE pk_multiple_columns
(
  col1 BIGINT,
  col2 STRING,
  col3 BOOLEAN,
  PRIMARY KEY (col1, col2)
) PARTITION BY HASH(col2) PARTITIONS 2 STORED AS KUDU;
```

The `SHOW CREATE TABLE` statement always represents the `PRIMARY KEY` specification as a separate item in the column list:

```
CREATE TABLE inline_pk_rewritten (id BIGINT PRIMARY KEY, s STRING)
  PARTITION BY HASH(id) PARTITIONS 2 STORED AS KUDU;

SHOW CREATE TABLE inline_pk_rewritten;
+-----+
+
| result
|
+-----+
+
| CREATE TABLE user.inline_pk_rewritten (
|   id BIGINT NOT NULL ENCODING AUTO_ENCODING COMPRESSION
|   DEFAULT_COMPRESSION, |
|   s STRING NULL ENCODING AUTO_ENCODING COMPRESSION DEFAULT_COMPRESSION,
|   PRIMARY KEY (id)
| )
|
| PARTITION BY HASH (id) PARTITIONS 2
|
| STORED AS KUDU
|
```

```
| TBLPROPERTIES ( 'kudu.master_addresses'='host.example.com' )
+-----+
+
```

The notion of primary key only applies to Kudu tables. Every Kudu table requires a primary key. The primary key consists of one or more columns. You must specify any primary key columns first in the column list or specify partition key with the beginning columns of the table.

The contents of the primary key columns cannot be changed by an `UPDATE` or `UPSERT` statement. Including too many columns in the primary key (more than 5 or 6) can also reduce the performance of write operations. Therefore, pick the most selective and most frequently tested non-null columns for the primary key specification. If a column must always have a value, but that value might change later, leave it out of the primary key and use a `NOT NULL` clause for that column instead. If an existing row has an incorrect or outdated key column value, delete the old row and insert an entirely new row with the correct primary key.

NULL | NOT NULL Attribute

For Kudu tables, you can specify which columns can contain nulls or not. This constraint offers an extra level of consistency enforcement for Kudu tables. If an application requires a field to always be specified, include a `NOT NULL` clause in the corresponding column definition, and Kudu prevents rows from being inserted with a `NULL` in that column.

For example, a table containing geographic information might require the latitude and longitude coordinates to always be specified. Other attributes might be allowed to be `NULL`. For example, a location might not have a designated place name, its altitude might be unimportant, and its population might be initially unknown, to be filled in later.

Because all of the primary key columns must have non-null values, specifying a column in the `PRIMARY KEY` clause implicitly adds the `NOT NULL` attribute to that column.

For non-Kudu tables, Impala allows any column to contain `NULL` values, because it is not practical to enforce a “not null” constraint on HDFS data files that could be prepared using external tools and ETL processes.

```
CREATE TABLE required_columns
(
  id BIGINT PRIMARY KEY,
  latitude DOUBLE NOT NULL,
  longitude DOUBLE NOT NULL,
  place_name STRING,
  altitude DOUBLE,
  population BIGINT
) PARTITION BY HASH(id) PARTITIONS 2 STORED AS KUDU;
```

During performance optimization, Kudu can use the knowledge that nulls are not allowed to skip certain checks on each input row, speeding up queries and join operations. Therefore, specify `NOT NULL` constraints when appropriate.

The `NULL` clause is the default condition for all columns that are not part of the primary key. You can omit it, or specify it to clarify that you have made a conscious design decision to allow nulls in a column.

Because primary key columns cannot contain any `NULL` values, the `NOT NULL` clause is not required for the primary key columns, but you might still specify it to make your code self-describing.

DEFAULT Attribute

You can specify a default value for columns in Kudu tables. The default value can be any constant expression, for example, a combination of literal values, arithmetic and string operations. It cannot contain references to columns or non-deterministic function calls.

The following example shows different kinds of expressions for the `DEFAULT` clause. The requirement to use a constant value means that you can fill in a placeholder value such as `NULL`, empty string, 0, -1, 'N/A' and so on, but you cannot reference functions or column names. Therefore, you cannot use `DEFAULT` to do things such as

automatically making an uppercase copy of a string value, storing Boolean values based on tests of other columns, or add or subtract one from another column representing a sequence number.

```
CREATE TABLE default_vals
(
  id BIGINT PRIMARY KEY,
  name STRING NOT NULL DEFAULT 'unknown',
  address STRING DEFAULT upper('no fixed address'),
  age INT DEFAULT -1,
  earthling BOOLEAN DEFAULT TRUE,
  planet_of_origin STRING DEFAULT 'Earth',
  optional_col STRING DEFAULT NULL
) PARTITION BY HASH(id) PARTITIONS 2 STORED AS KUDU;
```

Note:

When designing an entirely new schema, prefer to use NULL as the placeholder for any unknown or missing values, because that is the universal convention among database systems. Null values can be stored efficiently, and easily checked with the `IS NULL` or `IS NOT NULL` operators. The `DEFAULT` attribute is appropriate when ingesting data that already has an established convention for representing unknown or missing values, or where the vast majority of rows have some common non-null value.

ENCODING Attribute

Each column in a Kudu table can optionally use an encoding, a low-overhead form of compression that reduces the size on disk, then requires additional CPU cycles to reconstruct the original values during queries. Typically, highly compressible data benefits from the reduced I/O to read the data back from disk.

The encoding keywords that Impala recognizes are:

- `AUTO_ENCODING`: use the default encoding based on the column type, which are bitshuffle for the numeric type columns and dictionary for the string type columns.
- `PLAIN_ENCODING`: leave the value in its original binary format.
- `RLE`: compress repeated values (when sorted in primary key order) by including a count.
- `DICTIONARY_ENCODING`: when the number of different string values is low, replace the original string with a numeric ID.
- `BIT_SHUFFLE`: rearrange the bits of the values to efficiently compress sequences of values that are identical or vary only slightly based on primary key order. The resulting encoded data is also compressed with LZ4.
- `PREFIX_ENCODING`: compress common prefixes in string values; mainly for use internally within Kudu.

The following example shows the Impala keywords representing the encoding types. (The Impala keywords match the symbolic names used within Kudu.) For usage guidelines on the different kinds of encoding, see [the Kudu documentation](#). The `DESCRIBE` output shows how the encoding is reported after the table is created, and that omitting the encoding (in this case, for the `ID` column) is the same as specifying `DEFAULT_ENCODING`.

```
CREATE TABLE various_encodings
(
  id BIGINT PRIMARY KEY,
  c1 BIGINT ENCODING PLAIN_ENCODING,
  c2 BIGINT ENCODING AUTO_ENCODING,
  c3 TINYINT ENCODING BIT_SHUFFLE,
  c4 DOUBLE ENCODING BIT_SHUFFLE,
  c5 BOOLEAN ENCODING RLE,
  c6 STRING ENCODING DICTIONARY_ENCODING,
  c7 STRING ENCODING PREFIX_ENCODING
) PARTITION BY HASH(id) PARTITIONS 2 STORED AS KUDU;

-- Some columns are omitted from the output for readability.
describe various_encodings;
```

name	type	primary_key	nullable	encoding
id	bigint	true	false	AUTO_ENCODING
c1	bigint	false	true	PLAIN_ENCODING
c2	bigint	false	true	AUTO_ENCODING
c3	tinyint	false	true	BIT_SHUFFLE
c4	double	false	true	BIT_SHUFFLE
c5	boolean	false	true	RLE
c6	string	false	true	DICT_ENCODING
c7	string	false	true	PREFIX_ENCODING

COMPRESSION Attribute

You can specify a compression algorithm to use for each column in a Kudu table. This attribute imposes more CPU overhead when retrieving the values than the `ENCODING` attribute does. Therefore, use it primarily for columns with long strings that do not benefit much from the less-expensive `ENCODING` attribute.

The choices for `COMPRESSION` are `LZ4`, `SNAPPY`, and `ZLIB`.

Note:

Columns that use the `BITSHUFFLE` encoding are already compressed using `LZ4`, and so typically do not need any additional `COMPRESSION` attribute.

The following example shows design considerations for several `STRING` columns with different distribution characteristics, leading to choices for both the `ENCODING` and `COMPRESSION` attributes. The `country` values come from a specific set of strings, therefore this column is a good candidate for dictionary encoding. The `post_id` column contains an ascending sequence of integers, where several leading bits are likely to be all zeroes, therefore this column is a good candidate for bitshuffle encoding. The `body` column and the corresponding columns for translated versions tend to be long unique strings that are not practical to use with any of the encoding schemes, therefore they employ the `COMPRESSION` attribute instead. The ideal compression codec in each case would require some experimentation to determine how much space savings it provided and how much CPU overhead it added, based on real-world data.

```
CREATE TABLE blog_posts
(
  user_id STRING ENCODING DICT_ENCODING,
  post_id BIGINT ENCODING BIT_SHUFFLE,
  subject STRING ENCODING PLAIN_ENCODING,
  body STRING COMPRESSION LZ4,
  spanish_translation STRING COMPRESSION SNAPPY,
  esperanto_translation STRING COMPRESSION ZLIB,
  PRIMARY KEY (user_id, post_id)
) PARTITION BY HASH(user_id, post_id) PARTITIONS 2 STORED AS KUDU;
```

BLOCK_SIZE Attribute

Although Kudu does not use HDFS files internally, and thus is not affected by the HDFS block size, it does have an underlying unit of I/O called the *block size*. The `BLOCK_SIZE` attribute lets you set the block size for any column.

The block size attribute is a relatively advanced feature. Refer to [the Kudu documentation](#) for usage details.

Partitioning for Kudu Tables

Kudu tables use special mechanisms to distribute data among the underlying tablet servers. Although we refer to such tables as partitioned tables, they are distinguished from traditional Impala partitioned tables by use of different clauses on the `CREATE TABLE` statement. Kudu tables use `PARTITION BY`, `HASH`, `RANGE`, and range specification clauses rather than the `PARTITIONED BY` clause for HDFS-backed tables, which specifies only a column name and creates a new partition for each different value.

For background information and architectural details about the Kudu partitioning mechanism, see [the Kudu white paper, section 3.2](#).

Note:

The Impala DDL syntax for Kudu tables is different than in early Kudu versions, which used an experimental fork of the Impala code. For example, the `DISTRIBUTE BY` clause is now `PARTITION BY`, the `INTO n BUCKETS` clause is now `PARTITIONS n` and the range partitioning syntax is reworked to replace the `SPLIT ROWS` clause with more expressive syntax involving comparison operators.

Hash Partitioning

Hash partitioning is the simplest type of partitioning for Kudu tables. For hash-partitioned Kudu tables, inserted rows are divided up between a fixed number of “buckets” by applying a hash function to the values of the columns specified in the `HASH` clause. Hashing ensures that rows with similar values are evenly distributed, instead of clumping together all in the same bucket. Spreading new rows across the buckets this way lets insertion operations work in parallel across multiple tablet servers. Separating the hashed values can impose additional overhead on queries, where queries with range-based predicates might have to read multiple tablets to retrieve all the relevant values.

```
-- 1M rows with 50 hash partitions = approximately 20,000 rows per
partition.
-- The values in each partition are not sequential, but rather based on a
hash function.
-- Rows 1, 99999, and 123456 might be in the same partition.
CREATE TABLE million_rows (id string primary key, s string)
  PARTITION BY HASH(id) PARTITIONS 50
  STORED AS KUDU;

-- Because the ID values are unique, we expect the rows to be roughly
-- evenly distributed between the buckets in the destination table.
INSERT INTO million_rows SELECT * FROM billion_rows ORDER BY id LIMIT 1e6;
```

Note:

The largest number of buckets that you can create with a `PARTITIONS` clause varies depending on the number of tablet servers in the cluster, while the smallest is 2. For simplicity, some of the simple `CREATE TABLE` statements throughout this section use `PARTITIONS 2` to illustrate the minimum requirements for a Kudu table. For large tables, prefer to use roughly 10 partitions per server in the cluster.

Range Partitioning

Range partitioning lets you specify partitioning precisely, based on single values or ranges of values within one or more columns. You add one or more `RANGE` clauses to the `CREATE TABLE` statement, following the `PARTITION BY` clause.

Range-partitioned Kudu tables use one or more range clauses, which include a combination of constant expressions, `VALUE` or `VALUES` keywords, and comparison operators. (This syntax replaces the `SPLIT ROWS` clause used with early Kudu versions.) For the full syntax, see [CREATE TABLE Statement](#) on page 248.

```
-- 50 buckets, all for IDs beginning with a lowercase letter.
-- Having only a single range enforces the allowed range of values
-- but does not add any extra parallelism.
create table million_rows_one_range (id string primary key, s string)
  partition by hash(id) partitions 50,
  range (partition 'a' <= values < '{')
  stored as kudu;

-- 50 buckets for IDs beginning with a lowercase letter
-- plus 50 buckets for IDs beginning with an uppercase letter.
```

```
-- Total number of buckets = number in the PARTITIONS clause x number of
-- ranges.
-- We are still enforcing constraints on the primary key values
-- allowed in the table, and the 2 ranges provide better parallelism
-- as rows are inserted or the table is scanned.
create table million_rows_two_ranges (id string primary key, s string)
  partition by hash(id) partitions 50,
  range (partition 'a' <= values < '{', partition 'A' <= values < '[')
  stored as kudu;

-- Same as previous table, with an extra range covering the single key value
-- '00000'.
create table million_rows_three_ranges (id string primary key, s string)
  partition by hash(id) partitions 50,
  range (partition 'a' <= values < '{', partition 'A' <= values < '[' ,
  partition value = '00000')
  stored as kudu;

-- The range partitioning can be displayed with a SHOW command in impala-
-- shell.
show range partitions million_rows_three_ranges;
+-----+
| RANGE (id) |
+-----+
| VALUE = "00000" |
| "A" <= VALUES < "[" |
| "a" <= VALUES < "{" |
+-----+
```

Note:

When defining ranges, be careful to avoid “fencepost errors” where values at the extreme ends might be included or omitted by accident. For example, in the tables defined in the preceding code listings, the range `"a" <= VALUES < "{"` ensures that any values starting with `z`, such as `za` or `zzz` or `zzz-ZZZ`, are all included, by using a less-than operator for the smallest value after all the values starting with `z`.

For range-partitioned Kudu tables, an appropriate range must exist before a data value can be created in the table. Any `INSERT`, `UPDATE`, or `UPSERT` statements fail if they try to create column values that fall outside the specified ranges. The error checking for ranges is performed on the Kudu side; Impala passes the specified range information to Kudu, and passes back any error or warning if the ranges are not valid. (A nonsensical range specification causes an error for a DDL statement, but only a warning for a DML statement.)

Ranges can be non-contiguous:

```
partition by range (year) (partition 1885 <= values <= 1889, partition 1893
  <= values <= 1897)

partition by range (letter_grade) (partition value = 'A', partition value =
  'B',
  partition value = 'C', partition value = 'D', partition value = 'F')
```

The `ALTER TABLE` statement with the `ADD PARTITION` or `DROP PARTITION` clauses can be used to add or remove ranges from an existing Kudu table.

```
ALTER TABLE foo ADD PARTITION 30 <= VALUES < 50;
ALTER TABLE foo DROP PARTITION 1 <= VALUES < 5;
```

When a range is added, the new range must not overlap with any of the previous ranges; that is, it can only fill in gaps within the previous ranges.

```
alter table test_scores add range partition value = 'E';

alter table year_ranges add range partition 1890 <= values < 1893;
```

When a range is removed, all the associated rows in the table are deleted. (This is true whether the table is internal or external.)

```
alter table test_scores drop range partition value = 'E';

alter table year_ranges drop range partition 1890 <= values < 1893;
```

Kudu tables can also use a combination of hash and range partitioning.

```
partition by hash (school) partitions 10,
  range (letter_grade) (partition value = 'A', partition value = 'B',
    partition value = 'C', partition value = 'D', partition value = 'F')
```

Working with Partitioning in Kudu Tables

To see the current partitioning scheme for a Kudu table, you can use the `SHOW CREATE TABLE` statement or the `SHOW PARTITIONS` statement. The `CREATE TABLE` syntax displayed by this statement includes all the hash, range, or both clauses that reflect the original table structure plus any subsequent `ALTER TABLE` statements that changed the table structure.

To see the underlying buckets and partitions for a Kudu table, use the `SHOW TABLE STATS` or `SHOW PARTITIONS` statement.

Handling Date, Time, or Timestamp Data with Kudu

In Impala 2.9 and higher, you can include `TIMESTAMP` columns in Kudu tables, instead of representing the date and time as a `BIGINT` value. The behavior of `TIMESTAMP` for Kudu tables has some special considerations:

- Any nanoseconds in the original 96-bit value produced by Impala are not stored, because Kudu represents date/time columns using 64-bit values. The nanosecond portion of the value is rounded, not truncated. Therefore, a `TIMESTAMP` value that you store in a Kudu table might not be bit-for-bit identical to the value returned by a query.
- The conversion between the Impala 96-bit representation and the Kudu 64-bit representation introduces some performance overhead when reading or writing `TIMESTAMP` columns. You can minimize the overhead during writes by performing inserts through the Kudu API. Because the overhead during reads applies to each query, you might continue to use a `BIGINT` column to represent date/time values in performance-critical applications.
- The Impala `TIMESTAMP` type has a narrower range for years than the underlying Kudu data type. Impala can represent years 1400-9999. If year values outside this range are written to a Kudu table by a non-Impala client, Impala returns `NULL` by default when reading those `TIMESTAMP` values during a query. Or, if the `ABORT_ON_ERROR` query option is enabled, the query fails when it encounters a value with an out-of-range year.

```
--- Make a table representing a date/time value as TIMESTAMP.
-- The strings representing the partition bounds are automatically
-- cast to TIMESTAMP values.
create table native_timestamp(id bigint, when_exactly timestamp, event
  string, primary key (id, when_exactly))
  partition by hash (id) partitions 20,
```

```

range (when_exactly)
(
  partition '2015-01-01' <= values < '2016-01-01',
  partition '2016-01-01' <= values < '2017-01-01',
  partition '2017-01-01' <= values < '2018-01-01'
)
stored as kudu;

insert into native_timestamp values (12345, now(), 'Working on doc
examples');

select * from native_timestamp;
+-----+-----+-----+
| id      | when_exactly                | event                        |
+-----+-----+-----+
| 12345   | 2017-05-31 16:27:42.667542000 | Working on doc examples |
+-----+-----+-----+

```

Because Kudu tables have some performance overhead to convert `TIMESTAMP` columns to the Impala 96-bit internal representation, for performance-critical applications you might store date/time information as the number of seconds, milliseconds, or microseconds since the Unix epoch date of January 1, 1970. Specify the column as `BIGINT` in the Impala `CREATE TABLE` statement, corresponding to an 8-byte integer (an `int64`) in the underlying Kudu table). Then use Impala date/time conversion functions as necessary to produce a numeric, `TIMESTAMP`, or `STRING` value depending on the context.

For example, the `unix_timestamp()` function returns an integer result representing the number of seconds past the epoch. The `now()` function produces a `TIMESTAMP` representing the current date and time, which can be passed as an argument to `unix_timestamp()`. And string literals representing dates and date/times can be cast to `TIMESTAMP`, and from there converted to numeric values. The following examples show how you might store a date/time column as `BIGINT` in a Kudu table, but still use string literals and `TIMESTAMP` values for convenience.

```

-- now() returns a TIMESTAMP and shows the format for string literals you
-- can cast to TIMESTAMP.
select now();
+-----+
| now() |
+-----+
| 2017-01-25 23:50:10.132385000 |
+-----+

-- unix_timestamp() accepts either a TIMESTAMP or an equivalent string
-- literal.
select unix_timestamp(now());
+-----+
| unix_timestamp() |
+-----+
| 1485386670        |
+-----+

select unix_timestamp('2017-01-01');
+-----+
| unix_timestamp('2017-01-01') |
+-----+
| 1483228800                    |
+-----+

-- Make a table representing a date/time value as BIGINT.
-- Construct 1 range partition and 20 associated hash partitions for each
-- year.

```



```
-- Use date/time conversion functions to express the ranges as human-
readable dates.
create table time_series(id bigint, when_exactly bigint, event string,
primary key (id, when_exactly))
partition by hash (id) partitions 20,
range (when_exactly)
(
partition unix_timestamp('2015-01-01') <= values <
unix_timestamp('2016-01-01'),
partition unix_timestamp('2016-01-01') <= values <
unix_timestamp('2017-01-01'),
partition unix_timestamp('2017-01-01') <= values <
unix_timestamp('2018-01-01')
)
stored as kudu;

-- On insert, we can transform a human-readable date/time into a numeric
value.
insert into time_series values (12345, unix_timestamp('2017-01-25
23:24:56'), 'Working on doc examples');

-- On retrieval, we can examine the numeric date/time value or turn it back
into a string for readability.
select id, when_exactly, from_unixtime(when_exactly) as 'human-readable
date/time', event
from time_series order by when_exactly limit 100;
```

id	when_exactly	human-readable date/time	event
12345	1485386696	2017-01-25 23:24:56	Working on doc examples

Note:

If you do high-precision arithmetic involving numeric date/time values, when dividing millisecond values by 1000, or microsecond values by 1 million, always cast the integer numerator to a DECIMAL with sufficient precision and scale to avoid any rounding or loss of precision.

```
-- 1 million and 1 microseconds = 1.000001 seconds.
select microseconds,
cast (microseconds as decimal(20,7)) / 1e6 as fractional_seconds
from table_with_microsecond_column;
```

microseconds	fractional_seconds
1000001	1.000001000000000000

How Impala Handles Kudu Metadata

Note: This section only applies the Kudu services that are not integrated with the Hive Metastore (HMS).

By default, much of the metadata for Kudu tables is handled by the underlying storage layer. Kudu tables have less reliance on the Metastore database, and require less metadata caching on the Impala side. For example, information

about partitions in Kudu tables is managed by Kudu, and Impala does not cache any block locality metadata for Kudu tables. If the Kudu service is not integrated with the Hive Metastore, Impala will manage Kudu table metadata in the Hive Metastore.

The `REFRESH` and `INVALIDATE METADATA` statements are needed less frequently for Kudu tables than for HDFS-backed tables. Neither statement is needed when data is added to, removed, or updated in a Kudu table, even if the changes are made directly to Kudu through a client program using the Kudu API. Run `REFRESH table_name` or `INVALIDATE METADATA table_name` for a Kudu table only after making a change to the Kudu table schema, such as adding or dropping a column.

Because Kudu manages the metadata for its own tables separately from the metastore database, there is a table name stored in the metastore database for Impala to use, and a table name on the Kudu side, and these names can be modified independently through `ALTER TABLE` statements.

To avoid potential name conflicts, the prefix `impala::` and the Impala database name are encoded into the underlying Kudu table name:

```
create database some_database;
use some_database;

create table table_name_demo (x int primary key, y int)
  partition by hash (x) partitions 2 stored as kudu;

describe formatted table_name_demo;
...
kudu.table_name | impala::some_database.table_name_demo
```

See [Overview of Impala Tables](#) on page 206 for examples of how to change the name of the Impala table in the metastore database, the name of the underlying Kudu table, or both.

Working with Kudu Integrated with Hive Metastore

Starting from Kudu 1.10 and Impala 3.3, Impala supports Kudu services integrated with the Hive Metastore (HMS). See [the HMS integration documentation](#) for more details on Kudu's Hive Metastore integration.

The following are some of the changes you need to consider when working with Kudu services integrated with the HMS.

- When Kudu is integrated with the Hive Metastore, Impala must be configured to use the same HMS as Kudu.
- Since there may be no one-to-one mapping between Kudu tables and external tables, only internal tables are automatically synchronized.
- When you create a table in Kudu, Kudu will create an HMS entry for that table with the internal table type.
- When the Kudu service is integrated with the HMS, internal table entries will be created automatically in the HMS when tables are created in Kudu without Impala. To access these tables through Impala, run `INVALIDATE METADATA` statement so Impala picks up the latest metadata.

Loading Data into Kudu Tables

Kudu tables are well-suited to use cases where data arrives continuously, in small or moderate volumes. To bring data into Kudu tables, use the Impala `INSERT` and `UPSERT` statements. The `LOAD DATA` statement does not apply to Kudu tables.

Because Kudu manages its own storage layer that is optimized for smaller block sizes than HDFS, and performs its own housekeeping to keep data evenly distributed, it is not subject to the “many small files” issue and does not need explicit reorganization and compaction as the data grows over time. The partitions within a Kudu table can be

specified to cover a variety of possible data distributions, instead of hardcoding a new partition for each new day, hour, and so on, which can lead to inefficient, hard-to-scale, and hard-to-manage partition schemes with HDFS tables.

Your strategy for performing ETL or bulk updates on Kudu tables should take into account the limitations on consistency for DML operations.

Make `INSERT`, `UPDATE`, and `UPSERT` operations *idempotent*: that is, able to be applied multiple times and still produce an identical result.

If a bulk operation is in danger of exceeding capacity limits due to timeouts or high memory usage, split it into a series of smaller operations.

Avoid running concurrent ETL operations where the end results depend on precise ordering. In particular, do not rely on an `INSERT . . . SELECT` statement that selects from the same table into which it is inserting, unless you include extra conditions in the `WHERE` clause to avoid reading the newly inserted rows within the same statement.

Because relationships between tables cannot be enforced by Impala and Kudu, and cannot be committed or rolled back together, do not expect transactional semantics for multi-table operations.

Impala DML Support for Kudu Tables (`INSERT`, `UPDATE`, `DELETE`, `UPSERT`)

Impala supports certain DML statements for Kudu tables only. The `UPDATE` and `DELETE` statements let you modify data within Kudu tables without rewriting substantial amounts of table data. The `UPSERT` statement acts as a combination of `INSERT` and `UPDATE`, inserting rows where the primary key does not already exist, and updating the non-primary key columns where the primary key does already exist in the table.

The `INSERT` statement for Kudu tables honors the unique and `NOT NULL` requirements for the primary key columns.

Because Impala and Kudu do not support transactions, the effects of any `INSERT`, `UPDATE`, or `DELETE` statement are immediately visible. For example, you cannot do a sequence of `UPDATE` statements and only make the changes visible after all the statements are finished. Also, if a DML statement fails partway through, any rows that were already inserted, deleted, or changed remain in the table; there is no rollback mechanism to undo the changes.

In particular, an `INSERT . . . SELECT` statement that refers to the table being inserted into might insert more rows than expected, because the `SELECT` part of the statement sees some of the new rows being inserted and processes them again.

Note:

The `LOAD DATA` statement, which involves manipulation of HDFS data files, does not apply to Kudu tables.

Starting from Impala 2.9, the `INSERT` or `UPSERT` operations into Kudu tables automatically add an exchange and a sort node to the plan that partitions and sorts the rows according to the partitioning/primary key scheme of the target table (unless the number of rows to be inserted is small enough to trigger single node execution). Since Kudu partitions and sorts rows on write, pre-partitioning and sorting takes some of the load off of Kudu and helps large `INSERT` operations to complete without timing out. However, this default behavior may slow down the end-to-end performance of the `INSERT` or `UPSERT` operations. Starting from Impala 2.10, you can use the `/* +NOCLUSTERED */` and `/* +NOSHUFFLE */` hints together to disable partitioning and sorting before the rows are sent to Kudu. Additionally, since sorting may consume a large amount of memory, consider setting the `MEM_LIMIT` query option for those queries.

Multi-row Transactions for Kudu Tables

When you use Impala to query Kudu tables, you can insert multiple rows into a Kudu table in a single transaction. This broader transactional support between Kudu and Impala is available to you at a query level and at a session level.

Using Multi-row Transaction Capability

You can control this multi-row transaction feature by using the following query option. You may set this option at per-query or per-session level. When the option is enabled for a session, Impala will open one Kudu transaction for each INSERT or CTAS statement.

```
set ENABLE_KUDU_TRANSACTION=true
```

The following example shows how to insert three rows into a table in a single transaction.

Example:

1. Create table kudu-test-tbl-1.

```
create table kudu-test-tbl-1 (a int primary key, b string) partition by
hash(a) partitions 8 stored as kudu;
```

2. Enable the multi-row transaction feature at the query level.

```
set ENABLE_KUDU_TRANSACTION=true;
```

3. Insert three rows into the newly created table in a single transaction.

```
insert into kudu-test-tbl-1 values (0, 'a'), (1, 'b'), (2, 'c');
```

4. Verify the number of rows of this table.

```
select count(*) from kudu-test-tbl-1;
```

Note:

If you insert multiple rows with duplicate keys into a table, the transaction is aborted. To ignore the conflicts with duplicate keys during the transaction, start Impala daemons with the flag `--kudu_ignore_conflicts_in_transaction=true`. This flag is set to False by default. Note that this flag takes effect only if the flag `--kudu_ignore_conflicts` is set as True. The flag `--kudu_ignore_conflicts` is set to True by default.

When you enable the option `ENABLE_KUDU_TRANSACTION`, each Impala statement is executed with a new opened transaction. If the statement is executed successfully, then the Impala Coordinator commits the transaction. If there is an error returned by Kudu, then Impala aborts the transaction.

This applies to the following statements:

- INSERT
- CREATE TABLE AS SELECT

Advantages of Using This Capability

You can now easily build and manage Kudu applications, especially when Impala is used to interact with the data in the Kudu table. With multi-row transaction, you can atomically ingest large number of rows into a Kudu table with INSERT-SELECT or CTAS statement.

Limitation

INSERT and CTAS statements are supported for Kudu tables in the context of a multi-row transaction, but UPDATE/UPSERT/DELETE statements are not supported in multi-row transaction as of now.

Consistency Considerations for Kudu Tables

Kudu tables have consistency characteristics such as uniqueness, controlled by the primary key columns, and non-nullable columns. The emphasis for consistency is on preventing duplicate or incomplete data from being stored in a table.

Currently, Kudu does not enforce strong consistency for order of operations, or data that is read while a write operation is in progress. If multi-rows transaction is enabled, insertion of multiple rows in one insertion statement will be atomic, i.e. total success or total failure. But if multi-row transaction is not enabled, changes are applied atomically to each row, not applied as a single unit to all rows affected by a multi-row DML statement.

When multi-row transaction is not enabled and if some rows are rejected during a DML operation because of a mismatch with duplicate primary key values, NOT NULL constraints, and so on, the statement succeeds with a warning. Impala still inserts, deletes, or updates the other rows that are not affected by the constraint violation.

Consequently, the number of rows affected by a DML operation on a Kudu table might be different than you expect.

Because there is no strong consistency guarantee for information being inserted into with separate INSERT statements, deleted from, or updated across multiple tables simultaneously, consider denormalizing the data where practical. That is, if you run separate INSERT statements to insert related rows into two different tables, one INSERT might fail while the other succeeds, leaving the data in an inconsistent state. Even if both inserts succeed, a join query might happen during the interval between the completion of the first and second statements, and the query would encounter incomplete inconsistent data. Denormalizing the data into a single wide table can reduce the possibility of inconsistency due to multi-table operations.

Information about the number of rows affected by a DML operation is reported in `impala-shell` output, and in the `PROFILE` output, but is not currently reported to HiveServer2 clients such as JDBC or ODBC applications.

Security Considerations for Kudu Tables

Security for Kudu tables involves:

- Ranger authorization.

Access to Kudu tables must be granted to and revoked from principal with the following considerations:

- Only users with the ALL privilege on SERVER can create external Kudu tables.
- The ALL privileges on SERVER is required to specify the `kudu.master_addresses` property in the CREATE TABLE statements for managed tables as well as external tables.
- Access to Kudu tables is enforced at the table level and at the column level.
- The SELECT- and INSERT-specific permissions are supported.
- The DELETE, UPDATE, and UPSERT operations require the ALL privilege.
- Kerberos authentication. See [Kudu Security](#) for details.
- TLS encryption. See [Kudu Security](#) for details.
- Lineage tracking.
- Auditing.
- Redaction of sensitive information from log files.

Impala Query Performance for Kudu Tables

For queries involving Kudu tables, Impala can delegate much of the work of filtering the result set to Kudu, avoiding some of the I/O involved in full table scans of tables containing HDFS data files. This type of optimization is especially effective for partitioned Kudu tables, where the Impala query WHERE clause refers to one or more primary key columns that are also used as partition key columns. For example, if a partitioned Kudu table uses a HASH clause for `col1` and a RANGE clause for `col2`, a query using a clause such as `WHERE col1 IN (1,2,3) AND col2`

> 100 can determine exactly which tablet servers contain relevant data, and therefore parallelize the query very efficiently.

In Impala 2.11 and higher, Impala can push down additional information to optimize join queries involving Kudu tables. If the join clause contains predicates of the form `column = expression`, after Impala constructs a hash table of possible matching values for the join columns from the bigger table (either an HDFS table or a Kudu table), Impala can “push down” the minimum and maximum matching column values to Kudu, so that Kudu can more efficiently locate matching rows in the second (smaller) table. These min/max filters are affected by the `RUNTIME_FILTER_MODE`, `RUNTIME_FILTER_WAIT_TIME_MS`, and `DISABLE_ROW_RUNTIME_FILTERING` query options; the min/max filters are not affected by the `RUNTIME_BLOOM_FILTER_SIZE`, `RUNTIME_FILTER_MIN_SIZE`, `RUNTIME_FILTER_MAX_SIZE`, and `MAX_NUM_RUNTIME_FILTERS` query options.

See [EXPLAIN Statement](#) on page 291 for examples of evaluating the effectiveness of the predicate pushdown for a specific query against a Kudu table.

The `TABLESAMPLE` clause of the `SELECT` statement does not apply to a table reference derived from a view, a subquery, or anything other than a real base table. This clause only works for tables backed by HDFS or HDFS-like data files, therefore it does not apply to Kudu or HBase tables.

Using Impala to Query HBase Tables

You can use Impala to query HBase tables. This is useful for accessing any of your existing HBase tables via SQL and performing analytics over them. HDFS and Kudu tables are preferred over HBase for analytic workloads and offer superior performance. Kudu supports efficient inserts, updates and deletes of small numbers of rows and can replace HBase for most analytics-oriented use cases. See [Using Impala to Query Kudu Tables](#) on page 733 for information on using Impala with Kudu.

From the perspective of an Impala user, coming from an RDBMS background, HBase is a kind of key-value store where the value consists of multiple fields. The key is mapped to one column in the Impala table, and the various fields of the value are mapped to the other columns in the Impala table.

For background information on HBase, see [the Apache HBase documentation](#).

Overview of Using HBase with Impala

When you use Impala with HBase:

- You create the tables on the Impala side using the Hive shell, because the Impala `CREATE TABLE` statement currently does not support custom SerDes and some other syntax needed for these tables:
 - You designate it as an HBase table using the `STORED BY 'org.apache.hadoop.hive.hbase.HBaseStorageHandler'` clause on the Hive `CREATE TABLE` statement.
 - You map these specially created tables to corresponding tables that exist in HBase, with the clause `TBLPROPERTIES("hbase.table.name" = "table_name_in_hbase")` on the Hive `CREATE TABLE` statement.
 - See [Examples of Querying HBase Tables from Impala](#) on page 758 for a full example.
- You define the column corresponding to the HBase row key as a string with the `#string` keyword, or map it to a `STRING` column.
- Because Impala and Hive share the same metastore database, once you create the table in Hive, you can query or insert into it through Impala. (After creating a new table through Hive, issue the `INVALIDATE METADATA` statement in `impala-shell` to make Impala aware of the new table.)

- You issue queries against the Impala tables. For efficient queries, use the `WHERE` clause to find a single key value or a range of key values wherever practical, by testing the Impala column corresponding to the HBase row key. Avoid queries that do full-table scans, which are efficient for regular Impala tables but inefficient in HBase.

To work with an HBase table from Impala, ensure that the `impala` user has read/write privileges for the HBase table, using the `GRANT` command in the HBase shell. For details about HBase security, see [the Security chapter in the Apache HBase documentation](#).

Configuring HBase for Use with Impala

HBase works out of the box with Impala. There is no mandatory configuration needed to use these two components together.

To avoid delays if HBase is unavailable during Impala startup or after an `INVALIDATE METADATA` statement, set timeout values similar to the following in `/etc/impala/conf/hbase-site.xml`:

```
<property>
  <name>hbase.client.retries.number</name>
  <value>3</value>
</property>
<property>
  <name>hbase.rpc.timeout</name>
  <value>3000</value>
</property>
```

Supported Data Types for HBase Columns

To understand how Impala column data types are mapped to fields in HBase, you should have some background knowledge about HBase first. You set up the mapping by running the `CREATE TABLE` statement in the Hive shell. See [the Hive wiki](#) for a starting point, and [Examples of Querying HBase Tables from Impala](#) on page 758 for examples.

HBase works as a kind of “bit bucket”, in the sense that HBase does not enforce any typing for the key or value fields. All the type enforcement is done on the Impala side.

For best performance of Impala queries against HBase tables, most queries will perform comparisons in the `WHERE` clause against the column that corresponds to the HBase row key. When creating the table through the Hive shell, use the `STRING` data type for the column that corresponds to the HBase row key. Impala can translate predicates (through operators such as `=`, `<`, and `BETWEEN`) against this column into fast lookups in HBase, but this optimization (“predicate pushdown”) only works when that column is defined as `STRING`.

Starting in Impala 1.1, Impala also supports reading and writing to columns that are defined in the Hive `CREATE TABLE` statement using binary data types, represented in the Hive table definition using the `#binary` keyword, often abbreviated as `#b`. Defining numeric columns as binary can reduce the overall data volume in the HBase tables. You should still define the column that corresponds to the HBase row key as a `STRING`, to allow fast lookups using those columns.

Performance Considerations for the Impala-HBase Integration

To understand the performance characteristics of SQL queries against data stored in HBase, you should have some background knowledge about how HBase interacts with SQL-oriented systems first. See [the Hive wiki](#) for a starting point; because Impala shares the same metastore database as Hive, the information about mapping columns from Hive tables to HBase tables is generally applicable to Impala too.

Impala uses the HBase client API via Java Native Interface (JNI) to query data stored in HBase. This querying does not read HFiles directly. The extra communication overhead makes it important to choose what data to store in HBase or in HDFS, and construct efficient queries that can retrieve the HBase data efficiently:

- Use HBase table for queries that return a single row or a small range of rows, not queries that perform a full table scan of an entire table. (If a query has a HBase table and no WHERE clause referencing that table, that is a strong indicator that it is an inefficient query for an HBase table.)
- HBase may offer acceptable performance for storing small dimension tables where the table is small enough that executing a full table scan for every query is efficient enough. However, Kudu is almost always a superior alternative for storing dimension tables. HDFS tables are also appropriate for dimension tables that do not need to support update queries, delete queries or insert queries with small numbers of rows.

Query predicates are applied to row keys as start and stop keys, thereby limiting the scope of a particular lookup. If row keys are not mapped to string columns, then ordering is typically incorrect and comparison operations do not work. For example, if row keys are not mapped to string columns, evaluating for greater than (>) or less than (<) cannot be completed.

Predicates on non-key columns can be sent to HBase to scan as `SingleColumnValueFilters`, providing some performance gains. In such a case, HBase returns fewer rows than if those same predicates were applied using Impala. While there is some improvement, it is not as great when start and stop rows are used. This is because the number of rows that HBase must examine is not limited as it is when start and stop rows are used. As long as the row key predicate only applies to a single row, HBase will locate and return that row. Conversely, if a non-key predicate is used, even if it only applies to a single row, HBase must still scan the entire table to find the correct result.

Interpreting EXPLAIN Output for HBase Queries

For example, here are some queries against the following Impala table, which is mapped to an HBase table. The examples show excerpts from the output of the EXPLAIN statement, demonstrating what things to look for to indicate an efficient or inefficient query against an HBase table.

The first column (`cust_id`) was specified as the key column in the `CREATE EXTERNAL TABLE` statement; for performance, it is important to declare this column as `STRING`. Other columns, such as `BIRTH_YEAR` and `NEVER_LOGGED_ON`, are also declared as `STRING`, rather than their “natural” types of `INT` or `BOOLEAN`, because Impala can optimize those types more effectively in HBase tables. For comparison, we leave one column, `YEAR_REGISTERED`, as `INT` to show that filtering on this column is inefficient.

```
describe hbase_table;
Query: describe hbase_table
+-----+-----+-----+
| name          | type   | comment |
+-----+-----+-----+
| cust_id       | string |          |
| birth_year    | string |          |
| never_logged_on | string |          |
| private_email_address | string |          |
| year_registered | int    |          |
+-----+-----+-----+
```

The best case for performance involves a single row lookup using an equality comparison on the column defined as the row key:

```
explain select count(*) from hbase_table where cust_id =
'some_user@example.com';
+-----+
+
| Explain String
+-----+
+
| Estimated Per-Host Requirements: Memory=1.01GB VCores=1
+-----+
| WARNING: The following tables are missing relevant table and/
or column statistics. |
```



```

| hbase.hbase_table
|
|
| 03:AGGREGATE [MERGE FINALIZE]
| |   output: sum(count(*))
| |
|
| 02:EXCHANGE [PARTITION=UNPARTITIONED]
| |
|
| 01:AGGREGATE
| |   output: count(*)
| |
|
| 00:SCAN HBASE [hbase.hbase_table]
|   start key: some_user@example.com
|   stop key: some_user@example.com\0
|
+-----+
+

```

Another type of efficient query involves a range lookup on the row key column, using SQL operators such as greater than (or equal), less than (or equal), or `BETWEEN`. This example also includes an equality test on a non-key column; because that column is a `STRING`, Impala can let HBase perform that test, indicated by the `hbase filters:` line in the `EXPLAIN` output. Doing the filtering within HBase is more efficient than transmitting all the data to Impala and doing the filtering on the Impala side.

```

explain select count(*) from hbase_table where cust_id between
'a' and 'b'
and never_logged_on = 'true';
+-----+
+
| Explain String
|
+-----+
+
...
| 01:AGGREGATE
| |   output: count(*)
| |
|
| 00:SCAN HBASE [hbase.hbase_table]
|   start key: a
|   stop key: b\0
|   hbase filters: cols:never_logged_on EQUAL 'true'
|

```

```
+-----+
+
```

The query is less efficient if Impala has to evaluate any of the predicates, because Impala must scan the entire HBase table. Impala can only push down predicates to HBase for columns declared as `STRING`. This example tests a column declared as `INT`, and the `predicates:` line in the `EXPLAIN` output indicates that the test is performed after the data is transmitted to Impala.

```
explain select count(*) from hbase_table where year_registered =
  2010;
```

```
+-----+
+
```

```
| Explain String
```

```
|
```

```
+-----+
+
```

```
...
```

```
| 01:AGGREGATE
```

```
|
```

```
| | output: count(*)
```

```
|
```

```
|
```

```
| 00:SCAN HBASE [hbase.hbase_table]
```

```
|
```

```
| predicates: year_registered = 2010
```

```
|
```

```
+-----+
+
```

The same inefficiency applies if the key column is compared to any non-constant value. Here, even though the key column is a `STRING`, and is tested using an equality operator, Impala must scan the entire HBase table because the key column is compared to another column value rather than a constant.

```
explain select count(*) from hbase_table where cust_id =
  private_email_address;
```

```
+-----+
+
```

```
|
```

```
| Explain String
```

```
|
```

```
+-----+
+
```

```
...
```

```
| 01:AGGREGATE
```

```
|
```

```
| | output: count(*)
```

```
|
```

```
|
```

```
| 00:SCAN HBASE [hbase.hbase_table]
```

```
|
```

```
| predicates: cust_id = private_email_address
```

```
|
```

```
+-----+
+
```

Currently, tests on the row key using OR or IN clauses are not optimized into direct lookups either. Such limitations might be lifted in the future, so always check the EXPLAIN output to be sure whether a particular SQL construct results in an efficient query or not for HBase tables.

```
explain select count(*) from hbase_table where
  cust_id = 'some_user@example.com' or cust_id =
  'other_user@example.com';
+-----+
+
| Explain String
+-----+
+
...

| 01:AGGREGATE
| |   output: count(*)
| |
|
| 00:SCAN HBASE [hbase.hbase_table]
|   predicates: cust_id = 'some_user@example.com' OR cust_id =
|   'other_user@example.com'
+-----+
+

explain select count(*) from hbase_table where
  cust_id in ('some_user@example.com',
  'other_user@example.com');
+-----+
+
| Explain String
+-----+
+
...

| 01:AGGREGATE
| |   output: count(*)
| |
|
| 00:SCAN HBASE [hbase.hbase_table]
|   predicates: cust_id IN ('some_user@example.com',
|   'other_user@example.com')
+-----+
+
```

Either rewrite into separate queries for each value and combine the results in the application, or combine the single-row queries using UNION ALL:

```
select count(*) from hbase_table where cust_id =
  'some_user@example.com';
select count(*) from hbase_table where cust_id =
  'other_user@example.com';

explain
```

```

select count(*) from hbase_table where cust_id =
'some_user@example.com'
union all
select count(*) from hbase_table where cust_id =
'other_user@example.com';

```

```

+-----+
+
| Explain String
|
+-----+
+
...
| | 04:AGGREGATE
| | | output: count(*)
| | |
| | 03:SCAN HBASE [hbase.hbase_table]
| | | start key: other_user@example.com
| | | stop key: other_user@example.com\0
| | |
| 10:MERGE
|
...
| 02:AGGREGATE
| | output: count(*)
| |
| 01:SCAN HBASE [hbase.hbase_table]
| | start key: some_user@example.com
| | stop key: some_user@example.com\0
|
+-----+
+

```

Configuration Options for Java HBase Applications

If you have an HBase Java application that calls the `setCacheBlocks` or `setCaching` methods of the class [org.apache.hadoop.hbase.client.Scan](#), you can set these same caching behaviors through Impala query options, to control the memory pressure on the HBase RegionServer. For example, when doing queries in HBase that result in full-table scans (which by default are inefficient for HBase), you can reduce memory usage and speed up the queries by turning off the `HBASE_CACHE_BLOCKS` setting and specifying a large number for the `HBASE_CACHING` setting.

To set these options, issue commands like the following in `impala-shell`:

```

-- Same as calling setCacheBlocks(true) or
setCacheBlocks(false).
set hbase_cache_blocks=true;

```

```
set hbase_cache_blocks=false;

-- Same as calling setCaching(rows).
set hbase_caching=1000;
```

Or update the `impalad` defaults file `/etc/default/impala` and include settings for `HBASE_CACHE_BLOCKS` and/or `HBASE_CACHING` in the `-default_query_options` setting for `IMPALA_SERVER_ARGS`. See [Modifying Impala Startup Options](#) on page 32 for details.

Note: In Impala 2.0 and later, these options are settable through the JDBC or ODBC interfaces using the `SET` statement.

Use Cases for Querying HBase through Impala

The following are representative use cases for using Impala to query HBase tables:

- Using HBase to store rapidly incrementing counters, such as how many times a web page has been viewed, or on a social network, how many connections a user has or how many votes a post received. HBase is efficient for capturing such changeable data: the append-only storage mechanism is efficient for writing each change to disk, and a query always returns the latest value. An application could query specific totals like these from HBase, and combine the results with a broader set of data queried from Impala.
- Storing very wide tables in HBase. Wide tables have many columns, possibly thousands, typically recording many attributes for an important subject such as a user of an online service. These tables are also often sparse, that is, most of the columns values are `NULL`, `0`, `false`, empty string, or other blank or placeholder value. (For example, any particular web site user might have never used some site feature, filled in a certain field in their profile, visited a particular part of the site, and so on.) A typical query against this kind of table is to look up a single row to retrieve all the information about a specific subject, rather than summing, averaging, or filtering millions of rows as in typical Impala-managed tables.

Loading Data into an HBase Table

The Impala `INSERT` statement works for HBase tables. The `INSERT . . . VALUES` syntax is ideally suited to HBase tables, because inserting a single row is an efficient operation for an HBase table. (For regular Impala tables, with data files in HDFS, the tiny data files produced by `INSERT . . . VALUES` are extremely inefficient, so you would not use that technique with tables containing any significant data volume.)

When you use the `INSERT . . . SELECT` syntax, the result in the HBase table could be fewer rows than you expect. HBase only stores the most recent version of each unique row key, so if an `INSERT . . . SELECT` statement copies over multiple rows containing the same value for the key column, subsequent queries will only return one row with each key column value:

Although Impala does not have an `UPDATE` statement, you can achieve the same effect by doing successive `INSERT` statements using the same value for the key column each time:

Limitations and Restrictions of the Impala and HBase Integration

The Impala integration with HBase has the following limitations and restrictions, some inherited from the integration between HBase and Hive, and some unique to Impala:

- If you issue a `DROP TABLE` for an internal (Impala-managed) table that is mapped to an HBase table, the underlying table is not removed in HBase. The Hive `DROP TABLE` statement also removes the HBase table in this case.

- The `INSERT OVERWRITE` statement is not available for HBase tables. You can insert new data, or modify an existing row by inserting a new row with the same key value, but not replace the entire contents of the table. You can do an `INSERT OVERWRITE` in Hive if you need this capability.
- If you issue a `CREATE TABLE LIKE` statement for a table mapped to an HBase table, the new table is also an HBase table, but inherits the same underlying HBase table name as the original. The new table is effectively an alias for the old one, not a new table with identical column structure. Avoid using `CREATE TABLE LIKE` for HBase tables, to avoid any confusion.
- Copying data into an HBase table using the Impala `INSERT . . . SELECT` syntax might produce fewer new rows than are in the query result set. If the result set contains multiple rows with the same value for the key column, each row supercedes any previous rows with the same key value. Because the order of the inserted rows is unpredictable, you cannot rely on this technique to preserve the “latest” version of a particular key value.
- Because the complex data types (`ARRAY`, `STRUCT`, and `MAP`) available in Impala 2.3 and higher are currently only supported in Parquet tables, you cannot use these types in HBase tables that are queried through Impala.
- The `LOAD DATA` statement cannot be used with HBase tables.
- The `TABLESAMPLE` clause of the `SELECT` statement does not apply to a table reference derived from a view, a subquery, or anything other than a real base table. This clause only works for tables backed by HDFS or HDFS-like data files, therefore it does not apply to Kudu or HBase tables.

Examples of Querying HBase Tables from Impala

The following examples create an HBase table with four column families, create a corresponding table through Hive, then insert and query the table through Impala.

In HBase shell, the table name is quoted in `CREATE` and `DROP` statements. Tables created in HBase begin in “enabled” state; before dropping them through the HBase shell, you must issue a `disable 'table_name'` statement.

```
$ hbase shell
15/02/10 16:07:45
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
...

hbase(main):001:0> create 'hbasealltypesmall', 'boolsCF', 'intsCF',
'floatsCF', 'stringsCF'
0 row(s) in 4.6520 seconds

=> Hbase::Table - hbasealltypesmall
hbase(main):006:0> quit
```

Issue the following `CREATE TABLE` statement in the Hive shell. (The Impala `CREATE TABLE` statement currently does not support the `STORED BY` clause, so you switch into Hive to create the table, then back to Impala and the `impala-shell` interpreter to issue the queries.)

This example creates an external table mapped to the HBase table, usable by both Impala and Hive. It is defined as an external table so that when dropped by Impala or Hive, the original HBase table is not touched at all.

The `WITH SERDEPROPERTIES` clause specifies that the first column (`ID`) represents the row key, and maps the remaining columns of the `SQL` table to HBase column families. The mapping relies on the ordinal order of the columns in the table, not the column names in the `CREATE TABLE` statement. The first column is defined to be the lookup key; the `STRING` data type produces the fastest key-based lookups for HBase tables.

Note: For Impala with HBase tables, the most important aspect to ensure good performance is to use a `STRING` column as the row key, as shown in this example.

```
$ hive
...
hive> use hbase;
```

```

OK
Time taken: 4.095 seconds
hive> CREATE EXTERNAL TABLE hbasestringids (
  >   id string,
  >   bool_col boolean,
  >   tinyint_col tinyint,
  >   smallint_col smallint,
  >   int_col int,
  >   bigint_col bigint,
  >   float_col float,
  >   double_col double,
  >   date_string_col string,
  >   string_col string,
  >   timestamp_col timestamp)
  > STORED BY 'org.apache.hadoop.hive.hbase.HBaseStorageHandler'
  > WITH SERDEPROPERTIES (
  >   "hbase.columns.mapping" =
  >
  > ":key,boolsCF:bool_col,intsCF:tinyint_col,intsCF:smallint_col,intsCF:int_col,intsCF:
  \
  >
  > bigint_col,floatsCF:float_col,floatsCF:double_col,stringsCF:date_string_col,
  \
  >   stringsCF:string_col,stringsCF:timestamp_col"
  > )
  > TBLPROPERTIES("hbase.table.name" = "hbasealltypesmall");
OK
Time taken: 2.879 seconds
hive> quit;

```

Once you have established the mapping to an HBase table, you can issue DML statements and queries from Impala. The following example shows a series of INSERT statements followed by a query. The ideal kind of query from a performance standpoint retrieves a row from the table based on a row key mapped to a string column. An initial `INVALIDATE METADATA table_name` statement makes the table created through Hive visible to Impala.

```

$ impala-shell -i localhost -d hbase
Starting Impala Shell without Kerberos authentication
Connected to localhost:21000
...
Query: use `hbase`
[localhost:21000] > invalidate metadata hbasestringids;
Fetched 0 row(s) in 0.09s
[localhost:21000] > desc hbasestringids;
+-----+-----+-----+
| name          | type      | comment |
+-----+-----+-----+
| id            | string    |         |
| bool_col      | boolean   |         |
| double_col    | double    |         |
| float_col     | float     |         |
| bigint_col    | bigint    |         |
| int_col       | int       |         |
| smallint_col  | smallint  |         |
| tinyint_col   | tinyint   |         |
| date_string_col | string    |         |
| string_col     | string    |         |
| timestamp_col | timestamp |         |
+-----+-----+-----+
Fetched 11 row(s) in 0.02s
[localhost:21000] > insert into hbasestringids values
('0001',true,3.141,9.94,1234567,32768,4000,76,'2014-12-31','Hello
world',now());
Inserted 1 row(s) in 0.26s

```

```
[localhost:21000] > insert into hbasestringids values
('0002',false,2.004,6.196,1500,8000,129,127,'2014-01-01','Foo bar',now());
Inserted 1 row(s) in 0.12s
[localhost:21000] > select * from hbasestringids where id = '0001';
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
| id      | bool_col | double_col | float_col          | bigint_col | int_col |
smallint_col | tinyint_col | date_string_col | string_col | timestamp_col
|
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
| 0001 | true      | 3.141      | 9.939999580383301 | 1234567    | 32768
| 4000      | 76          | 2014-12-31    | Hello world | 2015-02-10
16:36:59.764838000 |
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
+-----+-----+-----+-----+-----+-----+-----+
Fetched 1 row(s) in 0.54s
```

Note: After you create a table in Hive, such as the HBase mapping table in this example, issue an `INVALIDATE METADATA table_name` statement the next time you connect to Impala, make Impala aware of the new table. (Prior to Impala 1.2.4, you could not specify the table name if Impala was not aware of the table yet; in Impala 1.2.4 and higher, specifying the table name avoids reloading the metadata for other tables that are not changed.)

Using Impala with Iceberg Tables

Impala now supports Apache Iceberg which is an open table format for huge analytic datasets. With this functionality, you can access any existing Iceberg tables using SQL and perform analytics over them. Using Impala you can create and write Iceberg tables in different Iceberg Catalogs (e.g. HiveCatalog, HadoopCatalog). It also supports location-based tables (HadoopTables).

For more information on Iceberg, see [the Apache Iceberg site](#).

Overview of Iceberg features

- ACID compliance: DML operations are atomic, queries always read a consistent snapshot.
- Hidden partitioning: Iceberg produces partition values by taking a column value and optionally transforming it. Partition information is stored in the Iceberg metadata files. Iceberg is able to TRUNCATE column values or calculate a hash of them and use it for partitioning. Readers don't need to be aware of the partitioning of the table.
- Partition layout evolution: When the data volume or the query patterns change you can update the layout of a table. Since hidden partitioning is used, you don't need to rewrite the data files during partition layout evolution.
- Schema evolution: supports add, drop, update, or rename schema elements, and has no side-effects.
- Time travel: enables reproducible queries that use exactly the same table snapshot, or lets users easily examine changes.
- Cloning Iceberg tables: create an empty Iceberg table based on the definition of another Iceberg table.

Creating Iceberg tables with Impala

When you have an existing Iceberg table that is not yet present in the Hive Metastore, you can use the `CREATE EXTERNAL TABLE` command in Impala to add the table to the Hive Metastore and make Impala able to interact with this table. Currently Impala supports HadoopTables, HadoopCatalog, and HiveCatalog. If you have an existing table in HiveCatalog, and you are using the same Hive Metastore, you need no further actions.

- **HadoopTables.** When the table already exists in a HadoopTable it means there is a location on the file system that contains your table. Use the following command to add this table to Impala's catalog:

```
CREATE EXTERNAL TABLE ice_hadoop_tbl
STORED AS ICEBERG
LOCATION '/path/to/table'
TBLPROPERTIES('iceberg.catalog'='hadoop.tables');
```

- **HadoopCatalog.** A table in HadoopCatalog means that there is a catalog location in the file system under which Iceberg tables are stored. Use the following command to add a table in a HadoopCatalog to Impala:

```
CREATE EXTERNAL TABLE ice_hadoop_cat
STORED AS ICEBERG
TBLPROPERTIES('iceberg.catalog'='hadoop.catalog',
               'iceberg.catalog_location'='/path/to/catalog',
               'iceberg.table_identifier'='namespace.table');
```

- Alternatively, you can also use custom catalogs to use existing tables. It means you need to define your catalog in hive-site.xml. The advantage of this method is that other engines are more likely to be able to interact with this table. Please note that the automatic metadata update will not work for these tables, you will have to manually call REFRESH on the table when it changes outside Impala. To globally register different catalogs, set the following Hadoop configurations:

Config Key	Description
iceberg.catalog.<catalog_name>.type	type of catalog: hive, hadoop, or left unset if using a custom catalog
iceberg.catalog.<catalog_name>.catalog-impl	catalog implementation, must not be null if type is empty
iceberg.catalog.<catalog_name>.<key>	any config key and value pairs for the catalog

For example, to register a HadoopCatalog called 'hadoop', set the following properties in hive-site.xml:

```
iceberg.catalog.hadoop.type=hadoop;
iceberg.catalog.hadoop.warehouse=hdfs://example.com:8020/warehouse;
```

Then in the CREATE TABLE statement you can just refer to the catalog name:

```
CREATE EXTERNAL TABLE ice_catalogs STORED AS ICEBERG
TBLPROPERTIES('iceberg.catalog'='<CATALOG-NAME>');
```

- If the table already exists in HiveCatalog then Impala should be able to see it without any additional commands.

You can also create new Iceberg tables with Impala. You can use the same commands as above, just omit the EXTERNAL keyword. To create an Iceberg table in HiveCatalog the following CREATE TABLE statement can be used:

```
CREATE TABLE ice_t (i INT) STORED AS ICEBERG;
```

By default Impala assumes that the Iceberg table uses Parquet data files. ORC and AVRO are also supported, but we need to tell Impala via setting the table property 'write.format.default' to e.g. 'ORC'.

You can also use `CREATE TABLE AS SELECT` to create new Iceberg tables, e.g.:

```
CREATE TABLE ice_ctas STORED AS ICEBERG AS SELECT i, b FROM value_tbl;

CREATE TABLE ice_ctas_part PARTITIONED BY(d) STORED AS ICEBERG AS SELECT s,
ts, d FROM value_tbl;

CREATE TABLE ice_ctas_part_spec PARTITIONED BY SPEC (truncate(3, s)) STORED
AS ICEBERG AS SELECT cast(t as INT), s, d FROM value_tbl;
```

Iceberg V2 tables

Iceberg V2 tables support row-level modifications (DELETE, UPDATE) via "merge-on-read", which means instead of rewriting existing data files, separate so-called delete files are being written that store information about the deleted records. There are two kinds of delete files in Iceberg:

- position deletes
- equality deletes

Impala only supports position delete files. These files contain the file path and file position of the deleted rows.

One can create Iceberg V2 tables via the `CREATE TABLE` statement, they just need to specify the 'format-version' table property:

```
CREATE TABLE ice_v2 (i int) STORED BY ICEBERG TBLPROPERTIES('format-
version'='2');
```

It is also possible to upgrade existing Iceberg V1 tables to Iceberg V2 tables. One can use the following `ALTER TABLE` statement to do so:

```
ALTER TABLE ice_v1_to_v2 SET TBLPROPERTIES('format-version'='2');
```

Dropping Iceberg tables

One can use `DROP TABLE` statement to remove an Iceberg table:

```
DROP TABLE ice_t;
```

When `external.table.purge` table property is set to true, then the `DROP TABLE` statement will also delete the data files. This property is set to true when Impala creates the Iceberg table via `CREATE TABLE`. When `CREATE EXTERNAL TABLE` is used (the table already exists in some catalog) then this `external.table.purge` is set to false, i.e. `DROP TABLE` doesn't remove any files, only the table definition in HMS.

Supported Data Types for Iceberg Columns

You can get information about the supported Iceberg data types in [the Iceberg spec](#).

The Iceberg data types can be mapped to the following SQL types in Impala:

Iceberg type	SQL type in Impala
boolean	BOOLEAN
int	INTEGER
long	BIGINT
float	FLOAT
double	DOUBLE
decimal(P, S)	DECIMAL(P, S)
date	DATE
time	Not supported
timestamp	TIMESTAMP
timestampz	Only read support via TIMESTAMP
string	STRING
uuid	Not supported
fixed(L)	Not supported
binary	Not supported
struct	STRUCT (read only)
list	ARRAY (read only)
map	MAP (read only)

Schema evolution of Iceberg tables

Iceberg assigns unique field ids to schema elements which means it is possible to reorder/delete/change columns and still be able to correctly read current and old data files. Impala supports the following statements to modify a table's schema:

- `ALTER TABLE ... RENAME TO ...` (renames the table if the Iceberg catalog supports it)
- `ALTER TABLE ... CHANGE COLUMN ...` (change name and type of a column iff the new type is compatible with the old type)
- `ALTER TABLE ... ADD COLUMNS ...` (adds columns to the end of the table)
- `ALTER TABLE ... DROP COLUMN ...`

Valid type promotions are:

- int to long
- float to double
- decimal(P, S) to decimal(P', S) if $P' > P$ – widen the precision of decimal types.

Impala currently does not support schema evolution for tables with AVRO file format.

See [schema evolution](#) for more details.

Partitioning Iceberg tables

The Iceberg spec has information about partitioning Iceberg tables. With Iceberg, we are not limited to value-based partitioning, we can also partition our tables via several partition transforms.

Partition transforms are IDENTITY, BUCKET, TRUNCATE, YEAR, MONTH, DAY, HOUR, and VOID. Impala supports all of these transforms. To create a partitioned Iceberg table, one needs to add a `PARTITIONED BY SPEC` clause to the `CREATE TABLE` statement, e.g.:

```
CREATE TABLE ice_p (i INT, d DATE, s STRING, t TIMESTAMP)
PARTITIONED BY SPEC (BUCKET(5, i), MONTH(d), TRUNCATE(3, s), HOUR(t))
STORED AS ICEBERG;
```

Iceberg also supports *partition evolution* which means that the partitioning of a table can be changed, even without the need of rewriting existing data files. You can change an existing table's partitioning via an `ALTER TABLE SET PARTITION SPEC` statement, e.g.:

```
ALTER TABLE ice_p SET PARTITION SPEC (VOID(i), VOID(d), TRUNCATE(3, s),
HOUR(t), i);
```

Please keep in mind that for Iceberg V1 tables:

- Do not reorder partition fields
- Do not drop partition fields; instead replace the field's transform with the void transform
- Only add partition fields at the end of the previous partition spec

You can also use the legacy syntax to create identity-partitioned Iceberg tables:

```
CREATE TABLE ice_p (i INT, b INT) PARTITIONED BY (p1 INT, p2 STRING) STORED
AS ICEBERG;
```

One can inspect a table's partition spec by the `SHOW PARTITIONS` or `SHOW CREATE TABLE` commands.

Inserting data into Iceberg tables

Impala is also able to insert new data to Iceberg tables. Currently the `INSERT INTO` and `INSERT OVERWRITE` DML statements are supported. One can also remove the contents of an Iceberg table via the `TRUNCATE` command.

Since Iceberg uses hidden partitioning it means you don't need a partition clause in your `INSERT` statements. E.g. insertion to a partitioned table looks like:

```
CREATE TABLE ice_p (i INT, b INT) PARTITIONED BY SPEC (bucket(17, i)) STORED
AS ICEBERG;
INSERT INTO ice_p VALUES (1, 2);
```

`INSERT OVERWRITE` statements can replace data in the table with the result of a query. For partitioned tables Impala does a dynamic overwrite, which means partitions that have rows produced by the `SELECT` query will be replaced. And partitions that have no rows produced by the `SELECT` query remain untouched. `INSERT OVERWRITE` is not allowed for tables that use the `BUCKET` partition transform because dynamic overwrite

behavior would be too random in this case. If one needs to replace all contents of a table, they can still use `TRUNCATE` and `INSERT INTO`.

Impala can only write Iceberg tables with Parquet data files.

Delete data from Iceberg tables

Since Impala 4.3 Impala is able to run `DELETE` statements against Iceberg V2 tables. E.g.:

```
DELETE FROM ice_t where i = 3;
```

More information about the `DELETE` statement can be found at [DELETE Statement \(Impala 2.8 or higher only\)](#) on page 266.

Updating data int Iceberg tables

Since Impala 4.4 Impala is able to run `UPDATE` statements against Iceberg V2 tables. E.g.:

```
UPDATE ice_t SET val = val + 1;
UPDATE ice_t SET k = 4 WHERE i = 5;
UPDATE ice_t SET ice_t.k = o.k, ice_t.j = o.j, FROM ice_t, other_table o
where ice_t.id = o.id;
```

The `UPDATE FROM` statement can be used to update a target Iceberg table based on a source table (or view) that doesn't need to be an Iceberg table. If there are multiple matches on the `JOIN` condition, Impala will raise an error.

Limitations:

- Only the merge-on-read update mode is supported.
- Only writes position delete files, i.e. no support for writing equality deletes.
- Cannot update tables with complex types.
- Can only write data and delete files in Parquet format. This means if table properties 'write.format.default' and 'write.delete.format.default' are set, their values must be `PARQUET`.
- Updating partitioning column with non-constant expression via the `UPDATE FROM` statement is not allowed. The upcoming `MERGE` statement will not have this limitation.

More information about the `UPDATE` statement can be found at [UPDATE Statement \(Impala 2.8 or higher only\)](#) on page 418.

Loading data into Iceberg tables

`LOAD DATA` statement can be used to load a single file or directory into an existing Iceberg table. This operation is executed differently compared to HMS tables, the data is being inserted into the table via sequentially executed statements, which has some limitations:

- Only Parquet or ORC files can be loaded.
- `PARTITION` clause is not supported, but the partition transformations are respected.
- The loaded files will be re-written as Parquet files.

Optimizing (Compacting) Iceberg tables

Frequent updates and row-level modifications on Iceberg tables can write many small data files and delete files, which have to be merged-on-read. This causes read performance to degrade over time. The following statement can be used to compact the table and optimize it for reading.

```
OPTIMIZE TABLE [db_name.]table_name;
```

The current implementation of the `OPTIMIZE TABLE` statement rewrites the entire table, executing the following tasks:

- compact small files
- merge delete and update deltas
- rewrite all files, converting them to the latest table schema
- rewrite all partitions according to the latest partition spec

To execute table optimization:

- The user needs ALL privileges on the table.
- The table can contain any file formats that Impala can read, but `write.format.default` has to be `parquet`.
- The table cannot contain complex types.

When a table is optimized, a new snapshot is created. The old table state is still accessible by time travel to previous snapshots, because the rewritten data and delete files are not removed physically.

Note that the current implementation of `OPTIMIZE TABLE` rewrites the entire table, therefore this operation can take a long time to complete depending on the size of the table.

Time travel for Iceberg tables

Iceberg stores the table states in a chain of snapshots. By default, Impala uses the current snapshot of the table. But for Iceberg tables, it is also possible to query an earlier state of the table.

We can use the `FOR SYSTEM_TIME AS OF` and `FOR SYSTEM_VERSION AS OF` clauses in `SELECT` queries, e.g.:

```
SELECT * FROM ice_t FOR SYSTEM_TIME AS OF '2022-01-04 10:00:00';
SELECT * FROM ice_t FOR SYSTEM_TIME AS OF now() - interval 5 days;
SELECT * FROM ice_t FOR SYSTEM_VERSION AS OF 123456;
```

If one needs to check the available snapshots of a table they can use the `DESCRIBE HISTORY` statement with the following syntax:

```
DESCRIBE HISTORY [db_name.]table_name
  [FROM timestamp];

DESCRIBE HISTORY [db_name.]table_name
  [BETWEEN timestamp AND timestamp]
```

For example:

```
DESCRIBE HISTORY ice_t FROM '2022-01-04 10:00:00';
DESCRIBE HISTORY ice_t FROM now() - interval 5 days;
DESCRIBE HISTORY ice_t BETWEEN '2022-01-04 10:00:00' AND '2022-01-05
10:00:00';
```

The output of the DESCRIBE HISTORY statement is formed of the following columns:

- `creation_time`: the snapshot's creation timestamp.
- `snapshot_id`: the snapshot's ID or null.
- `parent_id`: the snapshot's parent ID or null.
- `is_current_ancestor`: TRUE if the snapshot is a current ancestor of the table.

Please note that time travel queries are executed using the old schema of the table from the point specified by the time travel parameters. Prior to Impala 4.3.0 the current table schema is used to query an older snapshot of the table, which might have had a different schema in the past.

Rolling Iceberg tables back to a previous state

Iceberg table modifications cause new table snapshots to be created; these snapshots represent an earlier version of the table. The `ALTER TABLE [db_name.]table_name EXECUTE ROLLBACK` statement can be used to roll back the table to a previous snapshot.

For example, to roll the table back to the snapshot id 123456 use:

```
ALTER TABLE ice_tbl EXECUTE ROLLBACK(123456);
```

To roll the table back to the most recent (newest) snapshot that has a creation timestamp that is older than the timestamp '2022-01-04 10:00:00' use:

```
ALTER TABLE ice_tbl EXECUTE ROLLBACK('2022-01-04 10:00:00');
```

The timestamp is evaluated using the Timezone for the current session.

It is only possible to roll back to a snapshot that is a current ancestor of the table.

When a table is rolled back to a snapshot, a new snapshot is created with the same snapshot id, but with a new creation timestamp.

Expiring snapshots

Iceberg snapshots accumulate until they are deleted by a user action. Snapshots can be deleted with `ALTER TABLE ... EXECUTE expire_snapshots(...)` statement, which will expire snapshots that are older than the specified timestamp. For example:

```
ALTER TABLE ice_tbl EXECUTE expire_snapshots('2022-01-04 10:00:00');
ALTER TABLE ice_tbl EXECUTE expire_snapshots(now() - interval 5 days);
```

Expire snapshots:

- does not remove old metadata files by default.
- does not remove orphaned data files.
- respects the minimum number of snapshots to keep: `history.expire.min-snapshots-to-keep` table property.

Old metadata file clean up can be configured with `write.metadata.delete-after-commit.enabled=true` and `write.metadata.previous-versions-max` table properties. This allows automatic metadata file removal after operations that modify metadata such as expiring snapshots or inserting data.

Cloning Iceberg tables (LIKE clause)

Use `CREATE TABLE ... LIKE ...` to create an empty Iceberg table based on the definition of another Iceberg table, including any column attributes in the original table:

```
CREATE TABLE new_ice_tbl LIKE orig_ice_tbl;
```

Because of the Data Types of Iceberg and Impala do not correspond one by one, Impala can only clone between Iceberg tables.

Iceberg table properties

We can set the following table properties for Iceberg tables:

- `iceberg.catalog`: controls which catalog is used for this Iceberg table. It can be 'hive.catalog' (default), 'hadoop.catalog', 'hadoop.tables', or a name that identifies a catalog defined in the Hadoop configurations, e.g. `hive-site.xml`
- `iceberg.catalog_location`: Iceberg table catalog location when `iceberg.catalog` is 'hadoop.catalog'
- `iceberg.table_identifier`: Iceberg table identifier. We use `<database>.<table>` instead if this property is not set
- `write.format.default`: data file format of the table. Impala can read AVRO, ORC and PARQUET data files in Iceberg tables, and can write PARQUET data files only.
- `write.parquet.compression-codec`: Parquet compression codec. Supported values are: NONE, GZIP, SNAPPY (default value), LZ4, ZSTD. The table property will be ignored if `COMPRESSION_CODEC` query option is set.
- `write.parquet.compression-level`: Parquet compression level. Used with ZSTD compression only. Supported range is [1, 22]. Default value is 3. The table property will be ignored if `COMPRESSION_CODEC` query option is set.
- `write.parquet.row-group-size-bytes`: Parquet row group size in bytes. Supported range is [8388608, 2146435072] (8MB - 2047MB). The table property will be ignored if `PARQUET_FILE_SIZE` query option is set. If neither the table property nor the `PARQUET_FILE_SIZE` query option is set, the way Impala calculates row group size will remain unchanged.
- `write.parquet.page-size-bytes`: Parquet page size in bytes. Used for PLAIN encoding. Supported range is [65536, 1073741824] (64KB - 1GB). If the table property is unset, the way Impala calculates page size will remain unchanged.
- `write.parquet.dict-size-bytes`: Parquet dictionary page size in bytes. Used for dictionary encoding. Supported range is [65536, 1073741824] (64KB - 1GB). If the table property is unset, the way Impala calculates dictionary page size will remain unchanged.

Iceberg manifest caching

Starting from version 1.1.0, Apache Iceberg provides a mechanism to cache the contents of Iceberg manifest files in memory. This manifest caching feature helps to reduce repeated reads of small Iceberg manifest files from remote storage by Coordinators and Catalogd. This feature can be enabled for Impala Coordinators and Catalogd by setting properties in Hadoop's `core-site.xml` as in the following:

```
iceberg.io.impl=org.apache.iceberg.hadoop.HadoopFileIO;
iceberg.io.manifest.cache-enabled=true;
iceberg.io.manifest.cache.max-total-bytes=104857600;
iceberg.io.manifest.cache.expiration-interval-ms=3600000;
iceberg.io.manifest.cache.max-content-length=8388608;
```

The description of each property is as follows:

- `iceberg.io.impl`: custom FileIO implementation to use in a catalog. Must be set to enable manifest caching. Impala defaults to `HadoopFileIO`. It is recommended to not change this to other than `HadoopFileIO`.
- `iceberg.io.manifest.cache-enabled`: enable/disable the manifest caching feature.
- `iceberg.io.manifest.cache.max-total-bytes`: maximum total amount of bytes to cache in the manifest cache. Must be a positive value.
- `iceberg.io.manifest.cache.expiration-interval-ms`: maximum duration for which an entry stays in the manifest cache. Must be a non-negative value. Setting zero means cache entries expire only if it gets evicted due to memory pressure from `iceberg.io.manifest.cache.max-total-bytes`.
- `iceberg.io.manifest.cache.max-content-length`: maximum length of a manifest file to be considered for caching in bytes. Manifest files with a length exceeding this property value will not be cached. Must be set with a positive value and lower than `iceberg.io.manifest.cache.max-total-bytes`.

Manifest caching only works for tables that are loaded with either of `HadoopCatalogs` or `HiveCatalogs`. Individual `HadoopCatalog` and `HiveCatalog` will have separate manifest caches with the same configuration. By default, only 8 catalogs can have their manifest cache active in memory. This number can be raised by setting a higher value in the java system property `iceberg.io.manifest.cache.fileio-max`.

Using Impala with Amazon S3 Object Store

You can use Impala to query data residing on the Amazon S3 object store. This capability allows convenient access to a storage system that is remotely managed, accessible from anywhere, and integrated with various cloud-based services. Impala can query files in any supported file format from S3. The S3 storage location can be for an entire table, or individual partitions in a partitioned table.

Best Practices for Using Impala with S3

The following guidelines summarize the best practices described in the rest of this topic:

- Any reference to an S3 location must be fully qualified when S3 is not designated as the default storage, for example, `s3a:///s3-bucket-name/`.
- Set `fs.s3a.connection.maximum` to 1500 for `impalad`.
- Set `fs.s3a.block.size` to 134217728 (128 MB in bytes) if most Parquet files queried by Impala were written by Hive or ParquetMR jobs.

Set the block size to 268435456 (256 MB in bytes) if most Parquet files queried by Impala were written by Impala.

Starting in Impala 3.4.0, instead of `fs.s3a.block.size`, the `PARQUET_OBJECT_STORE_SPLIT_SIZE` query option controls the Parquet-specific split size. The default value is 256 MB.

- `DROP TABLE . . . PURGE` is much faster than the default `DROP TABLE`. The same applies to `ALTER TABLE . . . DROP PARTITION PURGE` versus the default `DROP PARTITION` operation. Due to the eventually consistent nature of S3, the files for that table or partition could remain for some unbounded time when using `PURGE`. The default `DROP TABLE/PARTITION` is slow because Impala copies the files to the S3A trash folder, and Impala waits until all the data is moved. `DROP TABLE/PARTITION . . . PURGE` is a fast delete operation, and the Impala statement finishes quickly even though the change might not have propagated fully throughout S3.
- `INSERT` statements are faster than `INSERT OVERWRITE` for S3. The query option `S3_SKIP_INSERT_STAGING`, which is set to `true` by default, skips the staging step for regular `INSERT` (but not `INSERT OVERWRITE`). This makes the operation much faster, but consistency is not guaranteed: if a node fails during execution, the table could end up with inconsistent data. Set this option to `false` if stronger consistency is required, however, this setting will make the `INSERT` operations slower.
 - For Impala-ACID tables, both `INSERT` and `INSERT OVERWRITE` tables for S3 are fast, regardless of the setting of `S3_SKIP_INSERT_STAGING`. Plus, consistency is guaranteed with ACID tables.
- Enable [data cache for remote reads](#).
- Enable [S3Guard](#) in your cluster for data consistency.
- Too many files in a table can make metadata load and update slow in S3. If too many requests are made to S3, S3 has a back-off mechanism and responds slower than usual.
 - If you have many small files due to over-granular partitioning, configure partitions with many megabytes of data so that even a query against a single partition can be parallelized effectively.
 - If you have many small files because of many small `INSERT` queries, use bulk `INSERT`s so that more data is written to fewer files.

How Impala SQL Statements Work with S3

Impala SQL statements work with data in S3 as follows:

- The [CREATE TABLE](#) or [ALTER TABLE](#) statement can specify that a table resides in the S3 object store by encoding an `s3a://` prefix for the `LOCATION` property. `ALTER TABLE` can also set the `LOCATION` property for an individual partition so that some data in a table resides in S3 and other data in the same table resides on HDFS.
- Once a table or partition is designated as residing in S3, the [SELECT Statement](#) on page 316 statement transparently accesses the data files from the appropriate storage layer.
- If the S3 table is an internal table, the [DROP TABLE](#) statement removes the corresponding data files from S3 when the table is dropped.
- The [TRUNCATE TABLE](#) statement always removes the corresponding data files from S3 when the table is truncated.
- The [LOAD DATA](#) statement can move data files residing in HDFS into an S3 table.
- The [INSERT](#) statement, or the `CREATE TABLE AS SELECT` form of the `CREATE TABLE` statement, can copy data from an HDFS table or another S3 table into an S3 table. The [S3_SKIP_INSERT_STAGING](#) query option chooses whether or not to use a fast code path for these write operations to S3, with the tradeoff of potential inconsistency in the case of a failure during the statement.

For usage information about Impala SQL statements with S3 tables, see [Creating Impala Databases, Tables, and Partitions for Data Stored in S3](#) on page 772 and [Using Impala DML Statements for S3 Data](#) on page 771.

Specifying Impala Credentials to Access Data in S3

To allow Impala to access data in S3, specify values for the following configuration settings in your `core-site.xml` file:

```
<property>
<name>fs.s3a.access.key</name>
<value>your_access_key</value>
</property>
<property>
<name>fs.s3a.secret.key</name>
<value>your_secret_key</value>
</property>
```

After specifying the credentials, restart both the Impala and Hive services. Restarting Hive is required because Impala statements, such as `CREATE TABLE`, go through the Hive Metastore.

Important:

Although you can specify the access key ID and secret key as part of the `s3a://URL` in the `LOCATION` attribute, doing so makes this sensitive information visible in many places, such as `DESCRIBE FORMATTED` output and Impala log files. Therefore, specify this information centrally in the `core-site.xml` file, and restrict read access to that file to only trusted users.

See [Authenticating with S3](#) for additional authentication mechanisms to access S3.

Loading Data into S3 for Impala Queries

If your ETL pipeline involves moving data into S3 and then querying through Impala, you can either use Impala DML statements to create, move, or copy the data, or use the same data loading techniques as you would for non-Impala data.

Using Impala DML Statements for S3 Data

The Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in S3. The syntax of the DML statements is the same as for any other tables because the S3 location for tables and partitions is specified by an `s3a://` prefix in the `LOCATION` attribute of `CREATE TABLE` or `ALTER TABLE` statements. If you bring data into S3 using the normal S3 transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the S3 data.

Because of differences between S3 and traditional filesystems, DML operations for S3 tables can take longer than for tables on HDFS. For example, both the `LOAD DATA` statement and the final stage of the `INSERT` and `CREATE TABLE AS SELECT` statements involve moving files from one directory to another. (In the case of `INSERT` and `CREATE TABLE AS SELECT`, the files are moved from a temporary staging directory to the final destination directory.) Because S3 does not support a “rename” operation for existing objects, in these cases Impala actually copies the data files from one location to another and then removes the original files. In Impala 2.6, the `S3_SKIP_INSERT_STAGING` query option provides a way to speed up `INSERT` statements for S3 tables and partitions, with the tradeoff that a problem during statement execution could leave data in an inconsistent state. It does not apply to `INSERT OVERWRITE` or `LOAD DATA` statements. See [S3_SKIP_INSERT_STAGING Query Option](#) for details.

Manually Loading Data into Impala Tables in S3

As an alternative, or on earlier Impala releases without DML support for S3, you can use the Amazon-provided methods to bring data files into S3 for querying through Impala. See [the Amazon S3 web site](#) for details.

Important:

For best compatibility with the S3 write support in Impala 2.6 and higher:

- Use native Hadoop techniques to create data files in S3 for querying through Impala.
- Use the `PURGE` clause of `DROP TABLE` when dropping internal (managed) tables.

By default, when you drop an internal (managed) table, the data files are moved to the HDFS trashcan. This operation is expensive for tables that reside on the Amazon S3 object store. Therefore, for S3 tables, prefer to use `DROP TABLE table_name PURGE` rather than the default `DROP TABLE` statement. The `PURGE` clause makes Impala delete the data files immediately, skipping the HDFS trashcan. For the `PURGE` clause to work effectively, you must originally create the data files on S3 using one of the tools from the Hadoop ecosystem, such as `hadoop fs -cp`, or `INSERT` in Impala or Hive.

After you upload data files to a location already mapped to an Impala table or partition, or if you delete files in S3 from such a location, issue the `REFRESH` statement to make Impala aware of the new set of data files.

Creating Impala Databases, Tables, and Partitions for Data Stored in S3

To create a table that resides in S3, run the `CREATE TABLE` or `ALTER TABLE` statement with the `LOCATION` clause.

`ALTER TABLE` can set the `LOCATION` property for an individual partition, so that some data in a table resides in S3 and other data in the same table resides on HDFS.

The syntax for the `LOCATION` clause is:

```
LOCATION 's3a://bucket_name/path/to/file'
```

The file system prefix is always `s3a://`. Impala does not support the `s3://` or `s3n://` prefixes.

For a partitioned table, either specify a separate `LOCATION` clause for each new partition, or specify a base `LOCATION` for the table and set up a directory structure in S3 to mirror the way Impala partitioned tables are structured in S3.

You point a nonpartitioned table or an individual partition at S3 by specifying a single directory path in S3, which could be any arbitrary directory. To replicate the structure of an entire Impala partitioned table or database in S3 requires more care, with directories and subdirectories nested and named to match the equivalent directory tree in HDFS. Consider setting up an empty staging area if necessary in HDFS, and recording the complete directory structure so that you can replicate it in S3.

When working with multiple tables with data files stored in S3, you can create a database with a `LOCATION` attribute pointing to an S3 path. Specify a URL of the form `s3a://bucket/root/path/for/database` for the `LOCATION` attribute of the database. Any tables created inside that database automatically create directories underneath the one specified by the database `LOCATION` attribute.

The following example creates a table with one partition for the year 2017 resides on HDFS and one partition for the year 2018 resides in S3.

The partition for year 2018 includes a `LOCATION` attribute with an `s3a://` URL, and so refers to data residing in S3, under a specific path underneath the bucket `impala-demo`.

```
CREATE TABLE mostly_on_hdfs (x int) PARTITIONED BY (year INT);
ALTER TABLE mostly_on_hdfs ADD PARTITION (year=2017);
ALTER TABLE mostly_on_hdfs ADD PARTITION (year=2018)
  LOCATION 's3a://impala-demo/dir1/dir2/dir3/t1';
```

The following session creates a database and two partitioned tables residing entirely in S3, one partitioned by a single column and the other partitioned by multiple columns.

- Because a `LOCATION` attribute with an `s3a://` URL is specified for the database, the tables inside that database are automatically created in S3 underneath the database directory.

- To see the names of the associated subdirectories, including the partition key values, use an S3 client tool to examine how the directory structure is organized in S3.

```
CREATE DATABASE db_on_s3 LOCATION 's3a://impala-demo/dir1/dir2/dir3';
CREATE TABLE partitioned_multiple_keys (x INT)
  PARTITIONED BY (year SMALLINT, month TINYINT, day TINYINT);

ALTER TABLE partitioned_multiple_keys
  ADD PARTITION (year=2015,month=1,day=1);
ALTER TABLE partitioned_multiple_keys
  ADD PARTITION (year=2015,month=1,day=31);

!hdfs dfs -ls -R s3a://impala-demo/dir1/dir2/dir3
2015-03-17 13:56:34      0 dir1/dir2/dir3/
2015-03-17 16:47:13      0 dir1/dir2/dir3/partitioned_multiple_keys/
2015-03-17 16:47:44      0 dir1/dir2/dir3/partitioned_multiple_keys/
year=2015/month=1/day=1/
2015-03-17 16:47:50      0 dir1/dir2/dir3/partitioned_multiple_keys/
year=2015/month=1/day=31/
```

The `CREATE DATABASE` and `CREATE TABLE` statements create the associated directory paths if they do not already exist. You can specify multiple levels of directories, and the `CREATE` statement creates all appropriate levels, similar to using `mkdir -p`.

Use the standard S3 file upload methods to put the actual data files into the right locations. You can also put the directory paths and data files in place before creating the associated Impala databases or tables, and Impala automatically uses the data from the appropriate location after the associated databases and tables are created.

Use the `ALTER TABLE` statement with the `LOCATION` clause to switch whether an existing table or partition points to data in HDFS or S3. For example, if you have an Impala table or partition pointing to data files in HDFS or S3, and you later transfer those data files to the other filesystem, use the `ALTER TABLE` statement to adjust the `LOCATION` attribute of the corresponding table or partition to reflect that change.

Internal and External Tables Located in S3

Just as with tables located on HDFS storage, you can designate S3-based tables as either internal (managed by Impala) or external, by using the syntax `CREATE TABLE` or `CREATE EXTERNAL TABLE` respectively.

When you drop an internal table, the files associated with the table are removed, even if they are in S3 storage. When you drop an external table, the files associated with the table are left alone, and are still available for access by other tools or components.

If the data in S3 is intended to be long-lived and accessed by other tools in addition to Impala, create any associated S3 tables with the `CREATE EXTERNAL TABLE` syntax, so that the files are not deleted from S3 when the table is dropped.

If the data in S3 is only needed for querying by Impala and can be safely discarded once the Impala workflow is complete, create the associated S3 tables using the `CREATE TABLE` syntax, so that dropping the table also deletes the corresponding data files in S3.

Running and Tuning Impala Queries for Data Stored in S3

Once a table or partition is designated as residing in S3, the `SELECT` statement transparently accesses the data files from the appropriate storage layer.

- Queries against S3 data support all the same file formats as for HDFS data.
- Tables can be unpartitioned or partitioned. For partitioned tables, either manually construct paths in S3 corresponding to the HDFS directories representing partition key values, or use `ALTER TABLE ... ADD PARTITION` to set up the appropriate paths in S3.

- HDFS and HBase tables can be joined to S3 tables, or S3 tables can be joined with each other.
- Authorization to control access to databases, tables, or columns works the same whether the data is in HDFS or in S3.
- The Catalog Server (`catalogd`) daemon caches metadata for both HDFS and S3 tables.
- Queries against S3 tables are subject to the same kinds of admission control and resource management as HDFS tables.
- Metadata about S3 tables is stored in the same Metastore database as for HDFS tables.
- You can set up views referring to S3 tables, the same as for HDFS tables.
- The `COMPUTE STATS`, `SHOW TABLE STATS`, and `SHOW COLUMN STATS` statements work for S3 tables.

Understanding and Tuning Impala Query Performance for S3 Data

Here are techniques you can use to interpret explain plans and profiles for queries against S3 data, and tips to achieve the best performance possible for such queries.

All else being equal, performance is expected to be lower for queries running against data in S3 rather than HDFS. The actual mechanics of the `SELECT` statement are somewhat different when the data is in S3. Although the work is still distributed across the DataNodes of the cluster, Impala might parallelize the work for a distributed query differently for data on HDFS and S3.

S3 does not have the same block notion as HDFS, so Impala uses heuristics to determine how to split up large S3 files for processing in parallel. Because all hosts can access any S3 data file with equal efficiency, the distribution of work might be different than for HDFS data, where the data blocks are physically read using short-circuit local reads by hosts that contain the appropriate block replicas. Although the I/O to read the S3 data might be spread evenly across the hosts of the cluster, the fact that all data is initially retrieved across the network means that the overall query performance is likely to be lower for S3 data than for HDFS data.

Use the `PARQUET_OBJECT_STORE_SPLIT_SIZE` query option to control the Parquet-specific split size. The default value is 256 MB.

When optimizing aspects of complex queries, such as the join order, Impala treats tables on HDFS and S3 the same way. Therefore, follow all the same tuning recommendations for S3 tables as for HDFS ones, such as using the `COMPUTE STATS` statement to help Impala construct accurate estimates of row counts and cardinality. See [Tuning Impala for Performance](#) on page 614 for details.

In query profile reports, the numbers for `BytesReadLocal`, `BytesReadShortCircuit`, `BytesReadDataNodeCached`, and `BytesReadRemoteUnexpected` are blank because those metrics come from HDFS. By definition, all the I/O for S3 tables involves remote reads.

Restrictions on Impala Support for S3

The following restrictions apply when using Impala with S3:

- Impala does not support the old `s3://` block-based and `s3n://` filesystem schemes, and it only supports `s3a://`.
- Although S3 is often used to store JSON-formatted data, the current Impala support for S3 does not include directly querying JSON data. For Impala queries, use data files in one of the file formats listed in [How Impala Works with Hadoop File Formats](#) on page 695. If you have data in JSON format, you can prepare a flattened version of that data for querying by Impala as part of your ETL cycle.
- You cannot use the `ALTER TABLE ... SET CACHED` statement for tables or partitions that are located in S3.

Using Impala with the Azure Data Lake Store (ADLS)

You can use Impala to query data residing on the Azure Data Lake Store (ADLS) filesystem. This capability allows convenient access to a storage system that is remotely managed, accessible from anywhere, and integrated with

various cloud-based services. Impala can query files in any supported file format from ADLS. The ADLS storage location can be for an entire table or individual partitions in a partitioned table.

The default Impala tables use data files stored on HDFS, which are ideal for bulk loads and queries using full-table scans. In contrast, queries against ADLS data are less performant, making ADLS suitable for holding “cold” data that is only queried occasionally, while more frequently accessed “hot” data resides in HDFS. In a partitioned table, you can set the `LOCATION` attribute for individual partitions to put some partitions on HDFS and others on ADLS, typically depending on the age of the data.

Starting in Impala 3.1, Impala supports ADLS Gen2 filesystem, Azure Blob File System (ABFS).

Prerequisites

These procedures presume that you have already set up an Azure account, configured an ADLS store, and configured your Hadoop cluster with appropriate credentials to be able to access ADLS. See the following resources for information:

- [Get started with Azure Data Lake Store using the Azure Portal](#)
- [Azure Data Lake Storage Gen2](#)
- [Hadoop Azure Data Lake Support](#)

How Impala SQL Statements Work with ADLS

Impala SQL statements work with data on ADLS as follows.

- The [CREATE TABLE Statement](#) on page 248 or [ALTER TABLE Statement](#) on page 215 statements can specify that a table resides on the ADLS filesystem by using one of the following ADLS prefixes in the `LOCATION` property.
 - For ADLS Gen1: `adl://`
 - For ADLS Gen2: `abfs://` or `abfss://`

`ALTER TABLE` can also set the `LOCATION` property for an individual partition, so that some data in a table resides on ADLS and other data in the same table resides on HDFS.

See [Creating Impala Databases, Tables, and Partitions for Data Stored on ADLS](#) on page 777 for usage information.

- Once a table or partition is designated as residing on ADLS, the [SELECT Statement](#) on page 316 statement transparently accesses the data files from the appropriate storage layer.
- If the ADLS table is an internal table, the [DROP TABLE Statement](#) on page 289 statement removes the corresponding data files from ADLS when the table is dropped.
- The [TRUNCATE TABLE Statement \(Impala 2.3 or higher only\)](#) on page 416 statement always removes the corresponding data files from ADLS when the table is truncated.
- The [LOAD DATA Statement](#) on page 309 can move data files residing in HDFS into an ADLS table.
- The [INSERT Statement](#) on page 298, or the `CREATE TABLE AS SELECT` form of the `CREATE TABLE` statement, can copy data from an HDFS table or another ADLS table into an ADLS table.

For usage information about Impala SQL statements with ADLS tables, see [Using Impala DML Statements for ADLS Data](#) on page 777.

Specifying Impala Credentials to Access Data in ADLS

To allow Impala to access data in ADLS, specify values for the following configuration settings in your `core-site.xml` file.

For ADLS Gen1:

```
<property>
  <name>dfs.adls.oauth2.access.token.provider.type</name>
  <value>ClientCredential</value>
</property>
<property>
  <name>dfs.adls.oauth2.client.id</name>
  <value>your_client_id</value>
</property>
<property>
  <name>dfs.adls.oauth2.credential</name>
  <value>your_client_secret</value>
</property>
<property>
  <name>dfs.adls.oauth2.refresh.url</name>
  <value>https://login.windows.net/your_azure_tenant_id/oauth2/token</
value>
</property>
```

For ADLS Gen2:

```
<property>
  <name>fs.azure.account.auth.type</name>
  <value>OAuth</value>
</property>

<property>
  <name>fs.azure.account.oauth.provider.type</name>
  <value>org.apache.hadoop.fs.azurebfs.oauth2.ClientCredsTokenProvider</
value>
</property>

<property>
  <name>fs.azure.account.oauth2.client.id</name>
  <value>your_client_id</value>
</property>

<property>
  <name>fs.azure.account.oauth2.client.secret</name>
  <value>your_client_secret</value>
</property>

<property>
  <name>fs.azure.account.oauth2.client.endpoint</name>
  <value>https://login.microsoftonline.com/your_azure_tenant_id/oauth2/
token</value>
</property>
```

Note:

Check if your Hadoop distribution or cluster management tool includes support for filling in and distributing credentials across the cluster in an automated way.

After specifying the credentials, restart both the Impala and Hive services. Restarting Hive is required because certain Impala queries, such as CREATE TABLE statements, go through the Hive metastore.

Loading Data into ADLS for Impala Queries

If your ETL pipeline involves moving data into ADLS and then querying through Impala, you can either use Impala DML statements to create, move, or copy the data, or use the same data loading techniques as you would for non-Impala data.

Using Impala DML Statements for ADLS Data

In Impala 2.9 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in the Azure Data Lake Store (ADLS). ADLS Gen2 is supported in Impala 3.1 and higher.

In the `CREATE TABLE` or `ALTER TABLE` statements, specify the ADLS location for tables and partitions with the `adl://` prefix for ADLS Gen1 and `abfs://` or `abfss://` for ADLS Gen2 in the `LOCATION` attribute.

If you bring data into ADLS using the normal ADLS transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the ADLS data.

Manually Loading Data into Impala Tables on ADLS

As an alternative, you can use the Microsoft-provided methods to bring data files into ADLS for querying through Impala. See [the Microsoft ADLS documentation](#) for details.

After you upload data files to a location already mapped to an Impala table or partition, or if you delete files in ADLS from such a location, issue the `REFRESH table_name` statement to make Impala aware of the new set of data files.

Creating Impala Databases, Tables, and Partitions for Data Stored on ADLS

Impala reads data for a table or partition from ADLS based on the `LOCATION` attribute for the table or partition. Specify the ADLS details in the `LOCATION` clause of a `CREATE TABLE` or `ALTER TABLE` statement. The syntax for the `LOCATION` clause is:

- For ADLS Gen1:

```
adl://account.azuredatalakestore.net/path/file
```

- For ADLS Gen2:

```
abfs://container@account.dfs.core.windows.net/path/file
```

or

```
abfss://container@account.dfs.core.windows.net/path/file
```

container denotes the parent location that holds the files and folders, which is the Containers in the Azure Storage Blobs service.

account is the name given for your storage account.

Note:

By default, TLS is enabled both with `abfs://` and `abfss://`.

When you set the `fs.azure.always.use.https=false` property, TLS is disabled with `abfs://`, and TLS is enabled with `abfss://`

For a partitioned table, either specify a separate `LOCATION` clause for each new partition, or specify a base `LOCATION` for the table and set up a directory structure in ADLS to mirror the way Impala partitioned tables are

structured in HDFS. Although, strictly speaking, ADLS filenames do not have directory paths, Impala treats ADLS filenames with / characters the same as HDFS pathnames that include directories.

To point a nonpartitioned table or an individual partition at ADLS, specify a single directory path in ADLS, which could be any arbitrary directory. To replicate the structure of an entire Impala partitioned table or database in ADLS requires more care, with directories and subdirectories nested and named to match the equivalent directory tree in HDFS. Consider setting up an empty staging area if necessary in HDFS, and recording the complete directory structure so that you can replicate it in ADLS.

For example, the following session creates a partitioned table where only a single partition resides on ADLS. The partitions for years 2013 and 2014 are located on HDFS. The partition for year 2015 includes a `LOCATION` attribute with an `adl://` URL, and so refers to data residing on ADLS, under a specific path underneath the store `impalademo`.

```
[localhost:21000] > create database db_on_hdfs;
[localhost:21000] > use db_on_hdfs;
[localhost:21000] > create table mostly_on_hdfs (x int) partitioned by (year
  int);
[localhost:21000] > alter table mostly_on_hdfs add partition (year=2013);
[localhost:21000] > alter table mostly_on_hdfs add partition (year=2014);
[localhost:21000] > alter table mostly_on_hdfs add partition (year=2015)
  > location 'adl://impalademo.azuredatalakestore.net/
  dir1/dir2/dir3/t1';
```

For convenience when working with multiple tables with data files stored in ADLS, you can create a database with a `LOCATION` attribute pointing to an ADLS path. Specify a URL of the form as shown above. Any tables created inside that database automatically create directories underneath the one specified by the database `LOCATION` attribute.

The following session creates a database and two partitioned tables residing entirely on ADLS, one partitioned by a single column and the other partitioned by multiple columns. Because a `LOCATION` attribute with an `adl://` URL is specified for the database, the tables inside that database are automatically created on ADLS underneath the database directory. To see the names of the associated subdirectories, including the partition key values, we use an ADLS client tool to examine how the directory structure is organized on ADLS. For example, Impala partition directories such as `month=1` do not include leading zeroes, which sometimes appear in partition directories created through Hive.

```
[localhost:21000] > create database db_on_adls location 'adl://
  impalademo.azuredatalakestore.net/dir1/dir2/dir3';
[localhost:21000] > use db_on_adls;

[localhost:21000] > create table partitioned_on_adls (x int) partitioned by
  (year int);
[localhost:21000] > alter table partitioned_on_adls add partition
  (year=2013);
[localhost:21000] > alter table partitioned_on_adls add partition
  (year=2014);
[localhost:21000] > alter table partitioned_on_adls add partition
  (year=2015);

[localhost:21000] > ! hadoop fs -ls adl://impalademo.azuredatalakestore.net/
  dir1/dir2/dir3 --recursive;
2015-03-17 13:56:34      0 dir1/dir2/dir3/
2015-03-17 16:43:28      0 dir1/dir2/dir3/partitioned_on_adls/
2015-03-17 16:43:49      0 dir1/dir2/dir3/partitioned_on_adls/year=2013/
2015-03-17 16:43:53      0 dir1/dir2/dir3/partitioned_on_adls/year=2014/
2015-03-17 16:43:58      0 dir1/dir2/dir3/partitioned_on_adls/year=2015/

[localhost:21000] > create table partitioned_multiple_keys (x int)
  > partitioned by (year smallint, month tinyint, day
  tinyint);
[localhost:21000] > alter table partitioned_multiple_keys
```

```

[localhost:21000] > add partition (year=2015,month=1,day=1);
[localhost:21000] > alter table partitioned_multiple_keys
[localhost:21000] > add partition (year=2015,month=1,day=31);
[localhost:21000] > alter table partitioned_multiple_keys
[localhost:21000] > add partition (year=2015,month=2,day=28);

[localhost:21000] > ! hadoop fs -ls adl://impalademo.azuredatalakestore.net/
dir1/dir2/dir3 --recursive;
2015-03-17 13:56:34      0 dir1/dir2/dir3/
2015-03-17 16:47:13      0 dir1/dir2/dir3/partitioned_multiple_keys/
2015-03-17 16:47:44      0 dir1/dir2/dir3/partitioned_multiple_keys/
year=2015/month=1/day=1/
2015-03-17 16:47:50      0 dir1/dir2/dir3/partitioned_multiple_keys/
year=2015/month=1/day=31/
2015-03-17 16:47:57      0 dir1/dir2/dir3/partitioned_multiple_keys/
year=2015/month=2/day=28/
2015-03-17 16:43:28      0 dir1/dir2/dir3/partitioned_on_adls/
2015-03-17 16:43:49      0 dir1/dir2/dir3/partitioned_on_adls/year=2013/
2015-03-17 16:43:53      0 dir1/dir2/dir3/partitioned_on_adls/year=2014/
2015-03-17 16:43:58      0 dir1/dir2/dir3/partitioned_on_adls/year=2015/

```

The `CREATE DATABASE` and `CREATE TABLE` statements create the associated directory paths if they do not already exist. You can specify multiple levels of directories, and the `CREATE` statement creates all appropriate levels, similar to using `mkdir -p`.

Use the standard ADLS file upload methods to actually put the data files into the right locations. You can also put the directory paths and data files in place before creating the associated Impala databases or tables, and Impala automatically uses the data from the appropriate location after the associated databases and tables are created.

You can switch whether an existing table or partition points to data in HDFS or ADLS. For example, if you have an Impala table or partition pointing to data files in HDFS or ADLS, and you later transfer those data files to the other filesystem, use an `ALTER TABLE` statement to adjust the `LOCATION` attribute of the corresponding table or partition to reflect that change. This location-switching technique is not practical for entire databases that have a custom `LOCATION` attribute.

Internal and External Tables Located on ADLS

Just as with tables located on HDFS storage, you can designate ADLS-based tables as either internal (managed by Impala) or external, by using the syntax `CREATE TABLE` or `CREATE EXTERNAL TABLE` respectively. When you drop an internal table, the files associated with the table are removed, even if they are on ADLS storage. When you drop an external table, the files associated with the table are left alone, and are still available for access by other tools or components. See [Overview of Impala Tables](#) on page 206 for details.

If the data on ADLS is intended to be long-lived and accessed by other tools in addition to Impala, create any associated ADLS tables with the `CREATE EXTERNAL TABLE` syntax, so that the files are not deleted from ADLS when the table is dropped.

If the data on ADLS is only needed for querying by Impala and can be safely discarded once the Impala workflow is complete, create the associated ADLS tables using the `CREATE TABLE` syntax, so that dropping the table also deletes the corresponding data files on ADLS.

For example, this session creates a table in ADLS with the same column layout as a table in HDFS, then examines the ADLS table and queries some data from it. The table in ADLS works the same as a table in HDFS as far as the expected file format of the data, table and column statistics, and other table properties. The only indication that it is not an HDFS table is the `adl:// URL` in the `LOCATION` property. Many data files can reside in the ADLS directory, and their combined contents form the table data. Because the data in this example is uploaded after the table is created, a `REFRESH` statement prompts Impala to update its cached information about the data files.

```

[localhost:21000] > create table usa_cities_adls like usa_cities location
'adl://impalademo.azuredatalakestore.net/usa_cities';

```

```
[localhost:21000] > desc usa_cities_adls;
```

name	type	comment
id	smallint	
city	string	
state	string	

```
-- Now from a web browser, upload the same data file(s) to ADLS as in the
HDFS table,
-- under the relevant store and path. If you already have the data in ADLS,
you would
-- point the table LOCATION at an existing path.
```

```
[localhost:21000] > refresh usa_cities_adls;
```

```
[localhost:21000] > select count(*) from usa_cities_adls;
```

count(*)
289

```
[localhost:21000] > select distinct state from sample_data_adls limit 5;
```

state
Louisiana
Minnesota
Georgia
Alaska
Ohio

```
[localhost:21000] > desc formatted usa_cities_adls;
```

name	comment	type
# col_name		data_type
	comment	
	NULL	NULL
id	NULL	smallint
city	NULL	string
state	NULL	string
	NULL	NULL
	NULL	NULL
# Detailed Table Information		NULL
	NULL	
Database:		adls_testing
Owner:		jrusSELL
CreateTime:		Mon Mar 16 11:36:25 PDT 2017
	NULL	
LastAccessTime:		UNKNOWN
	NULL	
Protect Mode:		None
	NULL	

```

| Retention:                                | 0
|         | NULL          |
| Location:                                | adl://impalademo.azuredatalakestore.net/
usa_cities | NULL          |
| Table Type:                             | MANAGED_TABLE
|         | NULL          |
...
+-----+
+-----+

```

In this case, we have already uploaded a Parquet file with a million rows of data to the `sample_data` directory underneath the `impalademo` store on ADLS. This session creates a table with matching column settings pointing to the corresponding location in ADLS, then queries the table. Because the data is already in place on ADLS when the table is created, no `REFRESH` statement is required.

```

[localhost:21000] > create table sample_data_adls
                   > (id int, id bigint, val int, zerofill string,
                   > name string, assertion boolean, city string, state
                   string)
                   > stored as parquet location 'adl://
impalademo.azuredatalakestore.net/sample_data';
[localhost:21000] > select count(*) from sample_data_adls;
+-----+
| count(*) |
+-----+
| 1000000  |
+-----+
[localhost:21000] > select count(*) howmany, assertion from sample_data_adls
group by assertion;
+-----+-----+
| howmany | assertion |
+-----+-----+
| 667149  | true      |
| 332851  | false     |
+-----+-----+

```

Running and Tuning Impala Queries for Data Stored on ADLS

Once the appropriate `LOCATION` attributes are set up at the table or partition level, you query data stored in ADLS exactly the same as data stored on HDFS or in HBase:

- Queries against ADLS data support all the same file formats as for HDFS data.
- Tables can be unpartitioned or partitioned. For partitioned tables, either manually construct paths in ADLS corresponding to the HDFS directories representing partition key values, or use `ALTER TABLE ... ADD PARTITION` to set up the appropriate paths in ADLS.
- HDFS, Kudu, and HBase tables can be joined to ADLS tables, or ADLS tables can be joined with each other.
- Authorization using the Ranger framework to control access to databases, tables, or columns works the same whether the data is in HDFS or in ADLS.
- The catalogd daemon caches metadata for both HDFS and ADLS tables. Use `REFRESH` and `INVALIDATE METADATA` for ADLS tables in the same situations where you would issue those statements for HDFS tables.
- Queries against ADLS tables are subject to the same kinds of admission control and resource management as HDFS tables.
- Metadata about ADLS tables is stored in the same metastore database as for HDFS tables.
- You can set up views referring to ADLS tables, the same as for HDFS tables.
- The `COMPUTE STATS`, `SHOW TABLE STATS`, and `SHOW COLUMN STATS` statements work for ADLS tables also.

Understanding and Tuning Impala Query Performance for ADLS Data

Although Impala queries for data stored in ADLS might be less performant than queries against the equivalent data stored in HDFS, you can still do some tuning. Here are techniques you can use to interpret explain plans and profiles for queries against ADLS data, and tips to achieve the best performance possible for such queries.

All else being equal, performance is expected to be lower for queries running against data on ADLS rather than HDFS. The actual mechanics of the `SELECT` statement are somewhat different when the data is in ADLS. Although the work is still distributed across the datanodes of the cluster, Impala might parallelize the work for a distributed query differently for data on HDFS and ADLS. ADLS does not have the same block notion as HDFS, so Impala uses heuristics to determine how to split up large ADLS files for processing in parallel. Because all hosts can access any ADLS data file with equal efficiency, the distribution of work might be different than for HDFS data, where the data blocks are physically read using short-circuit local reads by hosts that contain the appropriate block replicas. Although the I/O to read the ADLS data might be spread evenly across the hosts of the cluster, the fact that all data is initially retrieved across the network means that the overall query performance is likely to be lower for ADLS data than for HDFS data.

Because ADLS does not expose the block sizes of data files the way HDFS does, any Impala `INSERT` or `CREATE TABLE AS SELECT` statements use the `PARQUET_FILE_SIZE` query option setting to define the size of Parquet data files. (Using a large block size is more important for Parquet tables than for tables that use other file formats.)

When optimizing aspects of for complex queries such as the join order, Impala treats tables on HDFS and ADLS the same way. Therefore, follow all the same tuning recommendations for ADLS tables as for HDFS ones, such as using the `COMPUTE STATS` statement to help Impala construct accurate estimates of row counts and cardinality. See [Tuning Impala for Performance](#) on page 614 for details.

In query profile reports, the numbers for `BytesReadLocal`, `BytesReadShortCircuit`, `BytesReadDataNodeCached`, and `BytesReadRemoteUnexpected` are blank because those metrics come from HDFS. If you do see any indications that a query against an ADLS table performed “remote read” operations, do not be alarmed. That is expected because, by definition, all the I/O for ADLS tables involves remote reads.

Restrictions on Impala Support for ADLS

Impala requires that the default filesystem for the cluster be HDFS. You cannot use ADLS as the only filesystem in the cluster.

Although ADLS is often used to store JSON-formatted data, the current Impala support for ADLS does not include directly querying JSON data. For Impala queries, use data files in one of the file formats listed in [How Impala Works with Hadoop File Formats](#) on page 695. If you have data in JSON format, you can prepare a flattened version of that data for querying by Impala as part of your ETL cycle.

You cannot use the `ALTER TABLE . . . SET CACHED` statement for tables or partitions that are located in ADLS.

Best Practices for Using Impala with ADLS

The following guidelines represent best practices derived from testing and real-world experience with Impala on ADLS:

- Any reference to an ADLS location must be fully qualified. (This rule applies when ADLS is not designated as the default filesystem.)
- Set any appropriate configuration settings for `impalad`.

Using Impala with Isilon Storage

You can use Impala to query data files that reside on EMC Isilon storage devices, rather than in HDFS. This capability allows convenient query access to a storage system where you might already be managing large volumes of data. The combination of the Impala query engine and Isilon storage is certified on Impala 2.2.4 or higher.

Because the EMC Isilon storage devices use a global value for the block size rather than a configurable value for each file, the `PARQUET_FILE_SIZE` query option has no effect when Impala inserts data into a table or partition residing on Isilon storage. Use the `isi` command to set the default block size globally on the Isilon device. For example, to set the Isilon default block size to 256 MB, the recommended size for Parquet data files for Impala, issue the following command:

```
isi hdfs settings modify --default-block-size=256MB
```

The typical use case for Impala and Isilon together is to use Isilon for the default filesystem, replacing HDFS entirely. In this configuration, when you create a database, table, or partition, the data always resides on Isilon storage and you do not need to specify any special `LOCATION` attribute. If you do specify a `LOCATION` attribute, its value refers to a path within the Isilon filesystem. For example:

```
-- If the default filesystem is Isilon, all Impala data resides there
-- and all Impala databases and tables are located there.
CREATE TABLE t1 (x INT, s STRING);

-- You can specify LOCATION for database, table, or partition,
-- using values from the Isilon filesystem.
CREATE DATABASE d1 LOCATION '/some/path/on/isilon/server/d1.db';
CREATE TABLE d1.t2 (a TINYINT, b BOOLEAN);
```

Impala can write to, delete, and rename data files and database, table, and partition directories on Isilon storage. Therefore, Impala statements such as `CREATE TABLE`, `DROP TABLE`, `CREATE DATABASE`, `DROP DATABASE`, `ALTER TABLE`, and `INSERT` work the same with Isilon storage as with HDFS.

When the Impala spill-to-disk feature is activated by a query that approaches the memory limit, Impala writes all the temporary data to a local (not Isilon) storage device. Because the I/O bandwidth for the temporary data depends on the number of local disks, and clusters using Isilon storage might not have as many local disks attached, pay special attention on Isilon-enabled clusters to any queries that use the spill-to-disk feature. Where practical, tune the queries or allocate extra memory for Impala to avoid spilling. Although you can specify an Isilon storage device as the destination for the temporary data for the spill-to-disk feature, that configuration is not recommended due to the need to transfer the data both ways using remote I/O.

When tuning Impala queries on HDFS, you typically try to avoid any remote reads. When the data resides on Isilon storage, all the I/O consists of remote reads. Do not be alarmed when you see non-zero numbers for remote read measurements in query profile output. The benefit of the Impala and Isilon integration is primarily convenience of not having to move or copy large volumes of data to HDFS, rather than raw query performance. You can increase the performance of Impala I/O for Isilon systems by increasing the value for the `##num_remote_hdfs_io_threads` startup option for the `impalad` daemon.

Using Impala with Apache Ozone Storage

You can use Impala to query data files that reside on Apache Ozone distributed storage, rather than in HDFS. The combination of the Impala query engine and Apache Ozone storage is certified on Impala 4.2 or higher.

For more information on Ozone, see [the Apache Ozone site](#).

The typical use case for Impala and Ozone together is to use Ozone for the default filesystem, replacing HDFS entirely. In this configuration, when you create a database, table, or partition, the data always resides on Ozone storage and you do not need to specify any special `LOCATION` attribute. If you do specify a `LOCATION` attribute, its value refers to a path within the Ozone filesystem. For example:

```
-- If the default filesystem is Ozone, all Impala data resides there
-- and all Impala databases and tables are located there.
CREATE TABLE t1 (x INT, s STRING);

-- You can specify LOCATION for database, table, or partition,
-- using values from the Ozone filesystem.
CREATE DATABASE d1 LOCATION '/some/path/on/ozone/server/d1.db';
CREATE TABLE d1.t2 (a TINYINT, b BOOLEAN);
```

Impala can write to, delete, and rename data files and database, table, and partition directories on Ozone storage. Therefore, Impala statements such as `CREATE TABLE`, `DROP TABLE`, `CREATE DATABASE`, `DROP DATABASE`, `ALTER TABLE`, and `INSERT` work the same with Ozone storage as with HDFS.

Ozone supports multiple protocols: `ofs`, `o3fs`, and `s3a`. Impala supports reading `ofs` and `o3fs`. Impala can also read `s3a` (see [Using Impala with Amazon S3 Object Store](#) on page 769). However `ofs` is their newer protocol, and the only one Impala supports as a default filesystem. We recommend using it for [DDL Statements](#) on page 213 to avoid access limitations, and for [DML Statements](#) on page 214 and [SELECT Statement](#) on page 316 for performance.

Because Apache Ozone storage buckets use a global value for the block size rather than a configurable value for each file, the `PARQUET_FILE_SIZE` query option has no effect when Impala inserts data into a table or partition residing on Ozone storage.

Impala's spill-to-disk feature may be configured to use Ozone storage by specifying a full URI (e.g. `ofs://host:port/volume/bucket/key`) for the spill location. See [Managing Disk Space for Impala Data](#) on page 73 for details on configuring remote spill-to-disk.

Using Impala Logging

The Impala logs record information about:

- Any errors Impala encountered. If Impala experienced a serious error during startup, you must diagnose and troubleshoot that problem before you can do anything further with Impala.
- How Impala is configured.
- Jobs Impala has completed.

Note:

Formerly, the logs contained the query profile for each query, showing low-level details of how the work is distributed among nodes and how intermediate and final results are transmitted across the network. To save space, those query profiles are now stored in zlib-compressed files in `/var/log/impala/profiles`. You can access them through the Impala web user interface. For example, at `http://impalad-node-hostname:25000/queries`, each query is followed by a `Profile` link leading to a page showing extensive analytical data for the query execution.

The auditing feature introduced in Impala 1.1.1 produces a separate set of audit log files when enabled. See [Auditing Impala Operations](#) on page 99 for details.

In Impala 2.9 and higher, you can control how many audit event log files are kept on each host through the `##max_audit_event_log_files` startup option for the `impalad` daemon, similar to the `##max_log_files` option for regular log files.

The lineage feature introduced in Impala 2.2.0 produces a separate lineage log file when enabled. See [Viewing Lineage Information for Impala Data](#) on page 100 for details.

Locations and Names of Impala Log Files

- By default, the log files are under the directory `/var/log/impala`. To change log file locations, modify the defaults file described in [Starting Impala](#) on page 31.
- The significant files for the `impalad` process are `impalad.INFO`, `impalad.WARNING`, and `impalad.ERROR`. You might also see a file `impalad.FATAL`, although this is only present in rare conditions.
- The significant files for the `statestored` process are `statestored.INFO`, `statestored.WARNING`, and `statestored.ERROR`. You might also see a file `statestored.FATAL`, although this is only present in rare conditions.
- The significant files for the `catalogd` process are `catalogd.INFO`, `catalogd.WARNING`, and `catalogd.ERROR`. You might also see a file `catalogd.FATAL`, although this is only present in rare conditions.
- Examine the `.INFO` files to see configuration settings for the processes.
- Examine the `.WARNING` files to see all kinds of problem information, including such things as suboptimal settings and also serious runtime errors.
- Examine the `.ERROR` and/or `.FATAL` files to see only the most serious errors, if the processes crash, or queries fail to complete. These messages are also in the `.WARNING` file.
- A new set of log files is produced each time the associated daemon is restarted. These log files have long names including a timestamp. The `.INFO`, `.WARNING`, and `.ERROR` files are physically represented as symbolic links to the latest applicable log files.

Impala stores information using the `glog_v` logging system. You will see some messages referring to C++ file names. Logging is affected by:

- The `GLOG_v` environment variable specifies which types of messages are logged. See [Setting Logging Levels](#) on page 787 for details.
- The `##logbuflevel` startup flag for the `impalad` daemon specifies how often the log information is written to disk. The default is 0, meaning that the log is immediately flushed to disk when Impala outputs an important messages such as a warning or an error, but less important messages such as informational ones are buffered in memory rather than being flushed to disk immediately.

Rotating Impala Logs

Impala periodically switches the physical files representing the current log files, after which it is safe to remove the old files if they are no longer needed.

Impala can automatically remove older unneeded log files, a feature known as *log rotation*.

In Impala 2.2 and higher, the `##max_log_files` configuration option specifies how many log files to keep at each severity level (INFO, WARNING, ERROR, and FATAL). You can specify an appropriate setting for each Impala-related daemon (`impalad`, `statestored`, and `catalogd`).

- A value of 0 preserves all log files, in which case you would set up manual log rotation using your Linux tool or technique of choice.
- A value of 1 preserves only the very latest log file.
- The default value is 10.

Impala checks to see if any old logs need to be removed based on the interval specified in the `##logbufsecs` setting, every 5 seconds by default.

For some log levels, Impala logs are first temporarily buffered in memory and only written to disk periodically. The `##logbufsecs` setting controls the maximum time that log messages are buffered for. For example, with the default value of 5 seconds, there may be up to a 5 second delay before a logged message shows up in the log file.

It is not recommended that you set `##logbufsecs` to 0 as the setting makes the Impala daemon to spin in the thread that tries to delete old log files.

Changing Log Levels Dynamically

For debugging purposes you may be adjusting the logging configuration for Catalog and `impalad` servers. This required restarting the services. Impala supports adjusting the log levels dynamically without the need to restart the server. There is a `/log_level` tab in the debug page of all Impala servers. You can query the `log4j` log level of `root` or `org.apache.impala` by using the `Get Java Log Level` button. Also you can change the `vlog/log4j` levels to any supported levels of logging. You can select the log level using the `LOG LEVEL` drop down box. You also have an option to restore the log levels to their original configuration by using the `RESET` button.

Here is the format of a Glog:

```
${level}${month}${day} HH:MM:SS.${us} ${thread-id} ${source-file}:${line}]
${query-id}] ${message}
```

where

- `${level}` — Log Levels; displays the levels as I for INFO, W for WARNING, E for ERROR, F for FATAL.
- `${month}${day}` — Month and Date.
- `HH:MM:SS` — Hours, Minutes, Seconds.
- `${us}` — Microseconds.
- `${thread-id}` — TID of the thread.
- `${source-file}:${line}]` — File name and line number.
- `${query-id}]` — An unique id for each and every query that is run in Impala.
- `${message}` — Actual log message.

Reviewing Impala Logs

By default, the Impala log is stored at `/var/log/impalad/`. The most comprehensive log, showing informational, warning, and error messages, is in the file name `impalad.INFO`. View log file contents by using the web interface or by examining the contents of the log file. (When you examine the logs through the file system, you can troubleshoot problems by reading the `impalad.WARNING` and/or `impalad.ERROR` files, which contain the subsets of messages indicating potential problems.)

Note:

The web interface limits the amount of logging information displayed. To view every log entry, access the log files directly through the file system.

You can view the contents of the `impalad.INFO` log file in the file system. With the default configuration settings, the start of the log file appears as follows:

```
[user@example impalad]$ pwd
/var/log/impalad
[user@example impalad]$ more impalad.INFO
Log file created at: 2013/01/07 08:42:12
Running on machine: impala.example.com
Log line format: [IWEF]mmdd hh:mm:ss.uuuuuu threadid file:line] msg
I0107 08:42:12.292155 14876 daemon.cc:34] impalad version 0.4 RELEASE (build
9d7fadca0461ab40b9e9df8cdb47107ec6b27cff)
Built on Fri, 21 Dec 2012 12:55:19 PST
I0107 08:42:12.292484 14876 daemon.cc:35] Using hostname: impala.example.com
I0107 08:42:12.292706 14876 logging.cc:76] Flags (see also /varz are on
debug webserver):
--dump_ir=false
--module_output=
--be_port=22000
--classpath=
```

```
--hostname=impala.example.com
```

Note: The preceding example shows only a small part of the log file. Impala log files are often several megabytes in size.

Understanding Impala Log Contents

The logs store information about Impala startup options. This information appears once for each time Impala is started and may include:

- Machine name.
- Impala version number.
- Flags used to start Impala.
- CPU information.
- The number of available disks.

Setting Logging Levels

Impala uses the GLOG system, which supports three logging levels. You can adjust logging levels by exporting variable settings. To change logging settings manually, use a command similar to the following on each node before starting `impalad`:

```
export GLOG_v=1
```

Note: For performance reasons, do not enable the most verbose logging level of 3 unless there is no other alternative for troubleshooting.

For more information on how to configure GLOG, including how to set variable logging levels for different system components, see [documentation for the glog project on github](#).

Understanding What is Logged at Different Logging Levels

As logging levels increase, the categories of information logged are cumulative. For example, `GLOG_v=2` records everything `GLOG_v=1` records, as well as additional information.

Increasing logging levels imposes performance overhead and increases log size. Where practical, use `GLOG_v=1` for most cases: this level has minimal performance impact but still captures useful troubleshooting information.

Additional information logged at each level is as follows:

- `GLOG_v=1` - The default level. Logs information about each connection and query that is initiated to an `impalad` instance, including runtime profiles.
- `GLOG_v=2` - Everything from the previous level plus information for each RPC initiated. This level also records query execution progress information, including details on each file that is read.
- `GLOG_v=3` - Everything from the previous level plus logging of every row that is read. This level is only applicable for the most serious troubleshooting and tuning scenarios, because it can produce exceptionally large and detailed log files, potentially leading to its own set of performance and capacity problems.

Redacting Sensitive Information from Impala Log Files

Log redaction is a security feature that prevents sensitive information from being displayed in locations used by administrators for monitoring and troubleshooting, such as log files and the Impala debug web user interface. You configure regular expressions that match sensitive types of information processed by your system, such as credit card numbers or tax IDs, and literals matching these patterns are obfuscated wherever they would normally be recorded in log files or displayed in administration or debugging user interfaces.

In a security context, the log redaction feature is complementary to the Ranger authorization framework. Ranger prevents unauthorized users from being able to directly access table data. Redaction prevents administrators or support personnel from seeing the smaller amounts of sensitive or personally identifying information (PII) that might appear in queries issued by those authorized users.

See the documentation for your Apache Hadoop distribution for details about how to enable this feature and set up the regular expressions to detect and redact sensitive information within SQL statement text.

Impala Client Access

Application developers have a number of options to interface with Impala. The core development language with Impala is SQL. You can also use Java or other languages to interact with Impala through the standard JDBC and ODBC interfaces used by many business intelligence tools. For specialized kinds of analysis, you can supplement the Impala built-in functions by writing user-defined functions in C++ or Java.

You can connect and submit requests to the Impala through:

- The `impala-shell` interactive command interpreter
- The Hue web-based user interface
- JDBC
- ODBC

Impala clients can connect to the Coordinator Impala Daemon (`impalad`) via HiveServer2 over HTTP or over the TCP binary. Both HTTP and binary support the Kerberos SPNEGO and LDAP for authentication to Impala. See below for the default ports and the Impala flags to change the ports.

Protocol	Default Port	Flag to Specify an Alternate Port
HTTP	28000	<code>##hs2_http_port</code>
Binary TCP	21050	<code>##hs2_port</code>

Each `impalad` daemon process, running on separate nodes in a cluster, listens to *several ports* for incoming requests:

- Requests from `impala-shell` and Hue are routed to the `impalad` daemons through the same port.
- The `impalad` daemons listen on separate ports for JDBC and ODBC requests.

Impala Startup Options for Client Connections

Use the following flags when starting Impala Daemon coordinator to control client connections to Impala.

`--accepted_client_cnxn_timeout`

Controls how Impala treats new connection requests if it has run out of the number of threads configured by `--fe_service_threads`.

If `--accepted_client_cnxn_timeout > 0`, new connection requests are rejected if Impala can't get a server thread within the specified (in seconds) timeout.

If `--accepted_client_cnxn_timeout=0`, i.e. no timeout, clients wait indefinitely to open the new session until more threads are available.

The default timeout is 5 minutes.

The timeout applies only to client facing thrift servers, i.e., HS2 and Beeswax servers.

--disconnected_session_timeout

When a HiveServer2 session has had no open connections for longer than this value, the session will be closed, and any associated queries will be unregistered.

Specify the value in hours.

The default value is 1 hour.

This flag does not apply to Beeswax clients. When a Beeswax client connection is closed, Impala closes the session associated with that connection.

--fe_service_threads

Specifies the maximum number of concurrent client connections allowed. The default value is 64 with which 64 queries can run simultaneously.

If you have more clients trying to connect to Impala than the value of this setting, the later arriving clients have to wait for the duration specified by `--accepted_client_cnxn_timeout`. You can increase this value to allow more client connections. However, a large value means more threads to be maintained even if most of the connections are idle, and it could negatively impact query latency. Client applications should use the connection pool to avoid need for large number of sessions.

--hs2_http_port

Specifies the port for clients to connect to Impala server over HTTP.

The default port is 28000.

You can disable the HTTP end point for clients by setting the flag to 0.

To enable TLS/SSL for HiveServer2 HTTP endpoint use `--ssl_server_certificate` and `--ssl_private_key`. See [Configuring TLS/SSL for Impala](#) on page 81 for detail.

--idle_client_poll_period_s

The value of this setting specifies how frequently Impala polls to check if a client connection is idle and closes it if the connection is idle. A client connection is idle if all sessions associated with the client connection are idle.

By default, `--idle_client_poll_period_s` is set to 30 seconds.

If `--idle_client_poll_period_s` is set to 0, idle client connections stay open until explicitly closed by the clients.

The connection will only be closed if all the associated sessions are idle or closed. Sessions cannot be idle unless either the flag `--idle_session_timeout` or the `IDLE_SESSION_TIMEOUT` query option is set to greater than 0. If idle session timeout is not configured, a session cannot become idle by definition, and therefore its connection stays open until the client explicitly closes it.

--max_cookie_lifetime_s

Starting in Impala 3.4.0, Impala uses cookies for authentication when clients connect via HiveServer2 over HTTP. Use the `--max_cookie_lifetime_s` startup flag to control how long generated cookies are valid for.

Specify the value in seconds.

The default value is 1 day.

Setting the flag to 0 disables cookie support.

When an unexpired cookie is successfully verified, the user name contained in the cookie is set on the connection.

Each `impalad` uses its own key to generate the signature, so clients that reconnect to a different `impalad` have to re-authenticate.

On a single `impalad`, cookies are valid across sessions and connections.

Using the Impala Shell (`impala-shell` Command)

You can use the Impala shell tool (`impala-shell`) to set up databases and tables, insert data, and issue queries. For ad hoc queries and exploration, you can submit SQL statements in an interactive session. To automate your work, you can specify command-line options to process a single statement or a script file. The `impala-shell` interpreter accepts all the same SQL statements listed in [Impala SQL Statements](#) on page 213, plus some shell-only commands that you can use for tuning performance and diagnosing problems.

The `impala-shell` command fits into the familiar Unix toolchain:

- The `-q` option lets you issue a single query from the command line, without starting the interactive interpreter. You could use this option to run `impala-shell` from inside a shell script or with the command invocation syntax from a Python, Perl, or other kind of script.
- The `-f` option lets you process a file containing multiple SQL statements, such as a set of reports or DDL statements to create a group of tables and views.
- The `--var` option lets you pass substitution variables to the statements that are executed by that `impala-shell` session, for example the statements in a script file processed by the `-f` option. You encode the substitution variable on the command line using the notation `--var=variable_name=value`. Within a SQL statement, you substitute the value by using the notation `${var:variable_name}`. This feature is available in Impala 2.5 and higher.
- The `-o` option lets you save query output to a file.
- The `-B` option turns off pretty-printing, so that you can produce comma-separated, tab-separated, or other delimited text files as output. (Use the `--output_delimiter` option to choose the delimiter character; the default is the tab character.)
- In non-interactive mode, query output is printed to `stdout` or to the file specified by the `-o` option, while incidental output is printed to `stderr`, so that you can process just the query output as part of a Unix pipeline.
- In interactive mode, `impala-shell` uses the `readline` facility to recall and edit previous commands.

For information on installing the Impala shell, see [Installing Impala](#) on page 25.

For information about establishing a connection to a coordinator Impala daemon through the `impala-shell` command, see [Connecting to Impala Daemon from impala-shell](#) on page 796.

For a list of the `impala-shell` command-line options, see [impala-shell Configuration Options](#) on page 791. For reference information about the `impala-shell` interactive commands, see [impala-shell Command Reference](#) on page 799.

impala-shell Configuration Options

You can specify the following options when starting the `impala-shell` command to change how shell commands are executed. The table shows the format to use when specifying each option on the command line, or through the `impala-shell` configuration file.

Note:

These options are different than the configuration options for the `impalad` daemon itself. For the `impalad` options, see [Modifying Impala Startup Options](#) on page 32.

Summary of impala-shell Configuration Options

The following table shows the names and allowed arguments for the `impala-shell` configuration options. You can specify options on the command line, or in a configuration file as described in [impala-shell Configuration File](#) on page 795.

Command-Line Option	Configuration File Setting	Explanation
<code>-B</code> or <code>--delimited</code>	<code>write_delimited=true</code>	Causes all query results to be printed in plain format as a delimited text file. Useful for producing data files to be used with other Hadoop components. Also useful for avoiding the performance overhead of pretty-printing all output, especially when running benchmark tests using queries returning large result sets. Specify the delimiter character with the <code>--output_delimiter</code> option. Store all query results in a file rather than printing to the screen with the <code>-B</code> option. Added in Impala 1.0.1.
<code>-b</code> or <code>--kerberos_host_fqdn</code>	<code>kerberos_host_fqdn=</code> <code>load-balancer-hostname</code>	If set, the setting overrides the expected hostname of the Impala daemon's Kerberos service principal. <code>impala-shell</code> will check that the server's principal matches this hostname. This may be used when <code>impalad</code> is configured to be accessed via a load-balancer, but it is desired for <code>impala-shell</code> to talk to a specific <code>impalad</code> directly.
<code>--print_header</code>	<code>print_header=true</code>	
<code>-o filename</code> or <code>--output_file filename</code>	<code>output_file=filename</code>	Stores all query results in the specified file. Typically used to store the results of a single query issued from the command line with the <code>-q</code> option. Also works for interactive sessions; you see the messages such as number of rows fetched, but not the actual result set. To suppress these incidental messages when combining the <code>-q</code> and <code>-o</code> options, redirect <code>stderr</code> to <code>/dev/null</code> . Added in Impala 1.0.1.
<code>--</code> <code>output_delimiter=character</code>	<code>output_delimiter=character</code>	Specifies the character to use as a delimiter between fields when query results are printed in plain format by the <code>-B</code> option. Defaults to tab (<code>'\t'</code>). If an output value contains the delimiter character, that field is quoted, escaped by doubling quotation marks, or both. Added in Impala 1.0.1.

Command-Line Option	Configuration File Setting	Explanation
-E or --vertical	vertical=true	Print the output of a query (rows) vertically, no effects if -B is specified. Added in Impala 4.2.
-p or --show_profiles	show_profiles=true	Displays the query execution plan (same output as the EXPLAIN statement) and a more detailed low-level breakdown of execution steps, for every query executed by the shell.
-h or --help	N/A	Displays help information.
N/A	history_max=1000	Sets the maximum number of queries to store in the history file.
-i <i>hostname</i> or -- impalad= <i>hostname[:portnum]</i>	impalad= <i>hostname[:portnum]</i>	Connects to the impalad daemon on the specified host. The default port of 21050 is assumed unless you provide another value. You can connect to any host in your cluster that is running impalad. If you connect to an instance of impalad that was started with an alternate port specified by the --fe_port flag, provide that alternative port.
-q <i>query</i> or --query= <i>query</i>	query= <i>query</i>	Passes a query or other impala-shell command from the command line. The impala-shell interpreter immediately exits after processing the statement. It is limited to a single statement, which could be a SELECT, CREATE TABLE, SHOW TABLES, or any other statement recognized in impala-shell. Because you cannot pass a USE statement and another query, fully qualify the names for any tables outside the default database. (Or use the -f option to pass a file with a USE statement followed by other queries.)
-f <i>query_file</i> or --query_file= <i>query_file</i>	query_file= <i>path_to_query_file</i>	Passes a SQL query from a file. Multiple statements must be semicolon (;) delimited. In Impala 2.3 and higher, you can specify a filename of - to represent standard input. This feature makes it convenient to use impala-shell as part of a Unix pipeline where SQL statements are generated dynamically by other tools.
--query_option= "option= value" -Q "option= value"	Header line [impala.query_option= followed on subsequent lines by option=value, one option per line.	Sets default query options for an invocation of the impala-shell command. To set multiple query options at once, use more than one instance of this command-line option. The query option names are not case-sensitive.

Command-Line Option	Configuration File Setting	Explanation
-k or --kerberos	use_kerberos=true	Kerberos authentication is used when the shell connects to <code>impalad</code> . If Kerberos is not enabled on the instance of <code>impalad</code> to which you are connecting, errors are displayed. See Enabling Kerberos Authentication for Impala for the steps to set up and use Kerberos authentication in Impala.
-s <i>kerberos_service_name</i> or -- kerberos_service_name= <i>name</i>	kerberos_service_name= <i>name</i>	Instructs <code>impala-shell</code> to authenticate to a particular <code>impalad</code> service principal. If a <i>kerberos_service_name</i> is not specified, <code>impala</code> is used by default. If this option is used in conjunction with a connection in which Kerberos is not supported, errors are returned.
-V or --verbose	verbose=true	Enables verbose output.
--quiet	verbose=false	Disables verbose output.
-v or --version	version=true	Displays version information.
-c	ignore_query_failure=true	Continues on query failure.
-d <i>default_db</i> or --database= <i>default_db</i>	default_db= <i>default_db</i>	Specifies the database to be used on startup. Same as running the USE statement after connecting. If not specified, a database named <code>DEFAULT</code> is used.
-ssl -- ca_cert= <i>path_to_certificate</i>	ssl=true ca_cert= <i>path_to_certificate</i>	Enables TLS/SSL for <code>impala-shell</code> . The local pathname pointing to the third-party CA certificate, or to a copy of the server certificate for self-signed server certificates. If <code>--ca_cert</code> is not set, <code>impala-shell</code> enables TLS/SSL, but does not validate the server certificate. This is useful for connecting to a known-good Impala that is only running over TLS/SSL, when a copy of the certificate is not available (such as when debugging customer installations).
-l -u	use_ldap=true user= <i>user_name</i>	Enables LDAP authentication. Supplies the username, when LDAP authentication is enabled by the <code>-l</code> option. (Specify the short username, not the full LDAP distinguished name.) The shell then prompts interactively for the password.
-- ldap_password_cmd= <i>command</i>	N/A	Specifies a command to run to retrieve the LDAP password, when LDAP authentication is enabled by the <code>-l</code> option. If the command includes space-separated arguments, enclose the command and its arguments in quotation marks.

Command-Line Option	Configuration File Setting	Explanation
-- config_file=path_to_config_file	N/A	Specifies the path of the file containing <code>impala-shell</code> configuration settings. The default is <code>/etc/impalarc</code> . This setting can only be specified on the command line.
--live_progress	live_progress=true	Prints a progress bar showing roughly the percentage complete for each query. The information is updated interactively as the query progresses. See LIVE_PROGRESS Query Option (Impala 2.3 or higher only) on page 364.
--disable_live_progress	live_progress=false	A command line flag allows users to disable <code>live_progress</code> in the interactive mode.
--live_summary	N/A	Prints a detailed report, similar to the <code>SUMMARY</code> command, showing progress details for each phase of query execution. The information is updated interactively as the query progresses. See LIVE_SUMMARY Query Option (Impala 2.3 or higher only) on page 365.
-- var=variable_name=value	N/A	Defines a substitution variable that can be used within the <code>impala-shell</code> session. The variable can be substituted into statements processed by the <code>-q</code> or <code>-f</code> options, or in an interactive shell session. Within a SQL statement, you substitute the value by using the notation <code>\${var:variable_name}</code> . This feature is available in Impala 2.5 and higher.
--auth_creds_ok_in_clear	N/A	Allows LDAP authentication to be used with an insecure connection to the shell. WARNING: This will allow authentication credentials to be sent unencrypted, and hence may be vulnerable to an attack.
--protocol=protocol	N/A	<p>Protocol to use for the connection to Impala.</p> <p>Valid <i>protocol</i> values are:</p> <ul style="list-style-type: none"> '<code>hs2</code>': Impala-shell uses the binary TCP based transport to speak to the Impala Daemon via the HiveServer2 protocol. This is the current default setting. '<code>hs2-http</code>': Impala-shell uses HTTP transport to speak to the Impala Daemon via the HiveServer2 protocol. '<code>beeswax</code>': Impala-shell uses the binary TCP based transport to speak to the Impala Daemon via Beeswax. <p>You cannot connect to the 3.2 or earlier versions of Impala using the '<code>hs2</code>' or '<code>hs2-http</code>' option.</p> <p>Beeswax support is deprecated and will be removed in the future.</p>

Command-Line Option	Configuration File Setting	Explanation
-- hs2_fp_format=HS2_FP_FORMAT	hs2_fp_format=HS2_FP_FORMAT	HS2_FP_FORMAT printing format specification for floating point values when using HS2 protocol. The default behaviour makes the values handled by Python's str() built-in method. Use '16G' to match Beeswax protocol's floating-point output format. This feature is available in Impala 4.2 and higher.

impala-shell Configuration File

You can store a set of default settings for `impala-shell` in the `impala-shell` configuration file.

The global `impala-shell` configuration file is located in `/etc/impalarc`.

The user-level `impala-shell` configuration file is located in `~/.impalarc`.

Note that the global-level file name is different from the user-level file name. The global-level file name does not include a dot (.) in the file name.

The default path of the global configuration file can be changed by setting the `$IMPALA_SHELL_GLOBAL_CONFIG_FILE` environment variable.

To specify a different file name or path for the user-level configuration file, start `impala-shell` with the `--config_file` `impala-shell` option set to the path of the configuration file.

Typically, an administrator creates the global configuration file for the `impala-shell`, and if the user-level configuration file exists, the options set in the user configuration file take precedence over those in the global configuration file.

In turn, any options you specify on the `impala-shell` command line override any corresponding options within the configuration file.

The `impala-shell` configuration file (global or user) configuration file must contain a header label `[impala]`, followed by the options specific to `impala-shell`.

The `impala-shell` configuration file consists of key-value pairs, one option per line. Everything after the `#` character on a line is treated as a comment and ignored.

The names of the options in the configuration file are similar (although not necessarily identical) to the long-form command-line arguments to the `impala-shell` command. For the names to use, see [Summary of impala-shell Configuration Options](#) on page 791.

You can specify key-value pair options using `keyval`, similar to the `--var` command-line option. For example, `keyval=variable1=value1`.

The query options specified in the `[impala]` section override the options specified in the `[impala.query_options]` section.

The following example shows a configuration file that you might use during benchmarking tests. It sets verbose mode, so that the output from each SQL query is followed by timing information. `impala-shell` starts inside the database containing the tables with the benchmark data, avoiding the need to issue a `USE` statement or use fully qualified table names.

In this example, the query output is formatted as delimited text rather than enclosed in ASCII art boxes, and is stored in a file rather than printed to the screen. Those options are appropriate for benchmark situations, so that the overhead of `impala-shell` formatting and printing the result set does not factor into the timing measurements. It also enables the `show_profiles` option. That option prints detailed performance information after each query, which might be valuable in understanding the performance of benchmark queries.

```
[impala]
verbose=true
default_db=tpc_benchmarking
```

```
write_delimited=true
output_delimiter=,
output_file=/home/tester1/benchmark_results.csv
show_profiles=true
keyval=msg1=hello,keyval=msg2=world
```

The following example shows a configuration file that connects to a specific remote Impala node, runs a single query within a particular database, then exits. Any query options predefined under the `[impala.query_options]` section in the configuration file take effect during the session.

You would typically use this kind of single-purpose configuration setting with the `impala-shell` command-line option `--config_file=path_to_config_file`, to easily select between many predefined queries that could be run against different databases, hosts, or even different clusters. To run a sequence of statements instead of a single query, specify the configuration option `query_file=path_to_query_file` instead.

```
[impala]
impalad=impala-test-node1.example.com
default_db=site_stats
# Issue a predefined query and immediately exit.
query=select count(*) from web_traffic where event_date = trunc(now(),'dd')

[impala.query_options]
mem_limit=32g
```

Connecting to Impala Daemon from `impala-shell`

Within an `impala-shell` session, you can only issue queries while connected to an instance of the `impalad` daemon. You can specify the connection information:

- Through command-line options when you run the `impala-shell` command.
- Through a configuration file that is read when you run the `impala-shell` command.
- During an `impala-shell` session, by issuing a `CONNECT` command.

Note: You cannot connect to the 3.2 or earlier versions of Impala using the `'hs2'` or `'hs2-http'` protocol (`--protocol` option).

See [impala-shell Configuration Options](#) on page 791 for the command-line and configuration file options you can use.

You can connect to any Impala daemon (`impalad`), and that daemon coordinates the execution of all queries sent to it.

For simplicity during development, you might always connect to the same host, perhaps running `impala-shell` on the same host as `impalad` and specifying the hostname as `localhost`.

In a production environment, you might enable load balancing, in which you connect to specific host/port combination but queries are forwarded to arbitrary hosts. This technique spreads the overhead of acting as the coordinator node among all the Impala daemons in the cluster. See [Using Impala through a Proxy for High Availability](#) on page 67 for details.

To connect to an Impala during shell startup:

1. Locate the hostname that is running an instance of the `impalad` daemon. If that `impalad` uses a non-default port (something other than port 21000) for `impala-shell` connections, find out the port number also.
2. Use the `-i` option to the `impala-shell` interpreter to specify the connection information for that instance of `impalad`:

```
# When you are connecting to an impalad running on the same machine.
# The prompt will reflect the current hostname.
$ impala-shell
```

```
# When you are connecting to an impalad running on a remote machine, and
# impalad is listening
# on a non-default port over the HTTP HiveServer2 protocol.
$ impala-shell -i some.other.hostname:port_number --protocol='hs2-http'
# When you are connecting to an impalad running on a remote machine, and
# impalad is listening
# on a non-default port.
$ impala-shell -i some.other.hostname:port_number
```

To connect to an Impala in the `impala-shell` session:

1. Start the Impala shell with no connection:

```
$ impala-shell
```

2. Locate the hostname that is running the `impalad` daemon. If that `impalad` uses a non-default port (something other than port 21000) for `impala-shell` connections, find out the port number also.
3. Use the `connect` command to connect to an Impala instance. Enter a command of the form:

```
[Not connected] > connect impalad-host
```

Note: Replace *impalad-host* with the hostname you have configured to run Impala in your environment. The changed prompt indicates a successful connection.

To start `impala-shell` in a specific database:

You can use all the same connection options as in previous examples. For simplicity, these examples assume that you are logged into one of the Impala daemons.

1. Find the name of the database containing the relevant tables, views, and so on that you want to operate on.
2. Use the `-d` option to the `impala-shell` interpreter to connect and immediately switch to the specified database, without the need for a `USE` statement or fully qualified names:

```
# Subsequent queries with unqualified names operate on
# tables, views, and so on inside the database named 'staging'.
$ impala-shell -i localhost -d staging

# It is common during development, ETL, benchmarking, and so on
# to have different databases containing the same table names
# but with different contents or layouts.
$ impala-shell -i localhost -d parquet_snappy_compression
$ impala-shell -i localhost -d parquet_gzip_compression
```

To run one or several statements in non-interactive mode:

You can use all the same connection options as in previous examples. For simplicity, these examples assume that you are logged into one of the Impala daemons.

1. Construct a statement, or a file containing a sequence of statements, that you want to run in an automated way, without typing or copying and pasting each time.
2. Invoke `impala-shell` with the `-q` option to run a single statement, or the `-f` option to run a sequence of statements from a file. The `impala-shell` command returns immediately, without going into the interactive interpreter.

```
# A utility command that you might run while developing shell scripts
# to manipulate HDFS files.
$ impala-shell -i localhost -d database_of_interest -q 'show tables'

# A sequence of CREATE TABLE, CREATE VIEW, and similar DDL statements
# can go into a file to make the setup process repeatable.
$ impala-shell -i localhost -d database_of_interest -f recreate_tables.sql
```

Running Commands and SQL Statements in `impala-shell`

The following are a few of the key syntax and usage rules for running commands and SQL statements in `impala-shell`.

- To see the full set of available commands, press **TAB** twice.
- To cycle through and edit previous commands, click the up-arrow and down-arrow keys.
- Use the standard set of keyboard shortcuts in GNU Readline library for editing and cursor movement, such as **Ctrl-A** for the beginning of line and **Ctrl-E** for the end of line.
- Commands and SQL statements must be terminated by a semi-colon.
- Commands and SQL statements can span multiple lines.
- Use `--` to denote a single-line comment and `/* */` to denote a multi-line comment.

A comment is considered part of the statement it precedes, so when you enter a `--` or `/* */` comment, you get a continuation prompt until you finish entering a statement ending with a semicolon. For example:

```
[impala] > -- This is a test comment
           > SHOW TABLES LIKE 't*';
```

- If a comment contains the `${variable_name}` and it is not for a variable substitution, the `$` character must be escaped, e.g. `-- \${hello}`.

For information on available `impala-shell` commands, see [impala-shell Command Reference](#) on page 799.

Variable Substitution in `impala-shell`

In Impala 2.5 and higher, you can define substitution variables to be used within SQL statements processed by `impala-shell`.

1. You specify the variable and its value as below.
 - On the command line, you specify the option `--var=variable_name=value`
 - Within an interactive session or a script file processed by the `-f` option, use the `SET VAR:variable_name=value` command.
2. Use the above variable in SQL statements in the `impala-shell` session using the notation: `${VAR:variable_name}`.

Note: Because this feature is part of `impala-shell` rather than the `impalad` backend, make sure the client system you are connecting from has the most recent `impala-shell`. You can use this feature with a new `impala-shell` connecting to an older `impalad`, but not the reverse.

For example, here are some `impala-shell` commands that define substitution variables and then use them in SQL statements executed through the `-q` and `-f` options. Notice how the `-q` argument strings are single-quoted to prevent shell expansion of the `${var:value}` notation, and any string literals within the queries are enclosed by double quotation marks.

```
$ impala-shell --var=tname=table1 --var=colname=x --var=coltype=string
-q 'CREATE TABLE ${var:tname} (${var:colname} ${var:coltype}) STORED AS
  PARQUET'
Query: CREATE TABLE table1 (x STRING) STORED AS PARQUET
```

The below example shows a substitution variable passed in by the `--var` option, and then referenced by statements issued interactively. Then the variable is reset with the `SET` command.

```
$ impala-shell --quiet --var=tname=table1

[impala] > SELECT COUNT(*) FROM ${var:tname};

[impala] > SET VAR:tname=table2;
```

```
[impala] > SELECT COUNT(*) FROM ${var:tname};
```

impala-shell Command Reference

Use the following commands within `impala-shell` to pass requests to the `impalad` daemon that the shell is connected to. You can enter a command interactively at the prompt, or pass it as the argument to the `-q` option of `impala-shell`. Most of these commands are passed to the Impala daemon as SQL statements; refer to the corresponding [SQL language reference sections](#) for full syntax details.

Command	Explanation
<code>alter</code>	Changes the underlying structure or settings of an Impala table, or a table shared between Impala and Hive. See ALTER TABLE Statement on page 215 and ALTER VIEW Statement on page 230 for details.
<code>compute stats</code>	Gathers important performance-related information for a table, used by Impala to optimize queries. See COMPUTE STATS Statement on page 232 for details.
<code>connect</code>	<p>Connects to the specified instance of <code>impalad</code>. The default port of 21000 is assumed unless you provide another value. You can connect to any host in your cluster that is running <code>impalad</code>. If you connect to an instance of <code>impalad</code> that was started with an alternate port specified by the <code>--fe_port</code> flag, you must provide that alternate port. See Connecting to Impala Daemon from impala-shell on page 796 for examples.</p> <p>The SET statement has no effect until the <code>impala-shell</code> interpreter is connected to an Impala server. Once you are connected, any query options you set remain in effect as you issue a subsequent CONNECT command to connect to a different Impala host.</p>
<code>describe</code>	Shows the columns, column data types, and any column comments for a specified table. <code>DESCRIBE FORMATTED</code> shows additional information such as the HDFS data directory, partitions, and internal properties for the table. See DESCRIBE Statement on page 268 for details about the basic DESCRIBE output and the DESCRIBE FORMATTED variant. You can use <code>DESC</code> as shorthand for the DESCRIBE command.
<code>drop</code>	Removes a schema object, and in some cases its associated data files. See DROP TABLE Statement on page 289, DROP VIEW Statement on page 290, DROP DATABASE Statement on page 280, and DROP FUNCTION Statement on page 282 for details.
<code>explain</code>	Provides the execution plan for a query. EXPLAIN represents a query as a series of steps. For example, these steps might be map/reduce stages, metastore operations, or file system operations such as move or rename. See EXPLAIN Statement on page 291 and Using the EXPLAIN Plan for Performance Tuning on page 655 for details.
<code>help</code>	Help provides a list of all available commands and options.
<code>history</code>	Maintains an enumerated cross-session command history. This history is stored in the <code>~/.impalahistory</code> file.
<code>insert</code>	Writes the results of a query to a specified table. This either overwrites table data or appends data to the existing table content. See INSERT Statement on page 298 for details.

Command	Explanation
invalidate metadata	Updates <code>impalad</code> metadata for table existence and structure. Use this command after creating, dropping, or altering databases, tables, or partitions in Hive. See INVALIDATE METADATA Statement on page 307 for details.
profile	Displays low-level information about the most recent query. Used for performance diagnosis and tuning. The report starts with the same information as produced by the <code>EXPLAIN</code> statement and the <code>SUMMARY</code> command. See Using the Query Profile for Performance Tuning on page 656 for details.
quit	Exits the shell. Remember to include the final semicolon so that the shell recognizes the end of the command.
refresh	Refreshes <code>impalad</code> metadata for the locations of HDFS blocks corresponding to Impala data files. Use this command after loading new data files into an Impala table through Hive or through HDFS commands. See REFRESH Statement on page 312 for details.
rerun or @	<p>Executes a previous <code>impala-shell</code> command again, from the list of commands displayed by the <code>history</code> command. These could be SQL statements, or commands specific to <code>impala-shell</code> such as <code>quit</code> or <code>profile</code>.</p> <p>Specify an integer argument. A positive integer <code>N</code> represents the command labelled <code>N</code> in the output of the <code>HISTORY</code> command. A negative integer <code>-N</code> represents the <code>N</code>th command from the end of the list, such as <code>-1</code> for the most recent command. Commands that are executed again do not produce new entries in the <code>HISTORY</code> output list.</p>
select	Specifies the data set on which to complete some action. All information returned from <code>select</code> can be sent to some output such as the console or a file or can be used to complete some other element of query. See SELECT Statement on page 316 for details.
set	<p>Manages query options for an <code>impala-shell</code> session. The available options are the ones listed in SET Statement on page 345. These options are used for query tuning and troubleshooting. Issue <code>SET</code> with no arguments to see the current query options, either based on the <code>impalad</code> defaults, as specified by you at <code>impalad</code> startup, or based on earlier <code>SET</code> statements in the same session. To modify option values, issue commands with the syntax <code>set option=value</code>. To restore an option to its default, use the <code>unset</code> command.</p> <p>The <code>SET</code> statement has no effect until the <code>impala-shell</code> interpreter is connected to an Impala server. Once you are connected, any query options you set remain in effect as you issue a subsequent <code>CONNECT</code> command to connect to a different Impala host.</p> <p>In Impala 2.0 and later, <code>SET</code> is available as a SQL statement for any kind of application as well as in <code>impala-shell</code>. See SET Statement on page 345 for details.</p>
shell	<p>Executes the specified command in the operating system shell without exiting <code>impala-shell</code>. You can use the <code>!</code> character as shorthand for the <code>shell</code> command.</p> <p>Note: Quote any instances of the <code>--</code> or <code>/ *</code> tokens to avoid them being interpreted as the start of a comment. To embed comments within <code>source</code> or <code>!</code> commands, use the shell comment character <code>#</code> before the comment portion of the line.</p>

Command	Explanation
show	Displays metastore data for schema objects created and accessed through Impala, Hive, or both. <code>show</code> can be used to gather information about objects such as databases, tables, and functions. See SHOW Statement on page 395 for details.
source or src	Executes one or more statements residing in a specified file from the local filesystem. Allows you to perform the same kinds of batch operations as with the <code>-f</code> option, but interactively within the interpreter. The file can contain SQL statements and other <code>impala-shell</code> commands, including additional <code>SOURCE</code> commands to perform a flexible sequence of actions. Each command or statement, except the last one in the file, must end with a semicolon. See Running Commands and SQL Statements in impala-shell on page 798 for examples.
summary	<p>Summarizes the work performed in various stages of a query. It provides a higher-level view of the information displayed by the <code>EXPLAIN</code> command. Added in Impala 1.4.0. See Using the SUMMARY Report for Performance Tuning on page 655 for details about the report format and how to interpret it.</p> <p>In Impala 2.3 and higher, you can see a continuously updated report of the summary information while a query is in progress. See LIVE_SUMMARY Query Option (Impala 2.3 or higher only) on page 365 for details.</p>
unset	<p>Removes any user-specified value for a query option and returns the option to its default value. See SET Statement on page 345 for the available query options.</p> <p>In Impala 2.5 and higher, it can also remove user-specified substitution variables using the notation <code>UNSET VAR:variable_name</code>.</p>
use	Indicates the database against which to execute subsequent commands. Lets you avoid using fully qualified names when referring to tables in databases other than <code>default</code> . See USE Statement on page 421 for details. Not effective with the <code>-q</code> option, because that option only allows a single statement in the argument.
version	Returns Impala version information.

Configuring Impala to Work with ODBC

Third-party products, especially business intelligence and reporting tools, can access Impala using the ODBC protocol. For the best experience, ensure any third-party product you intend to use is supported. Verifying support includes checking that the versions of Impala, ODBC, the operating system, the Apache Hadoop distribution, and the third-party product have all been approved by the appropriate suppliers for use together. To configure your systems to use ODBC, download and install a connector, typically from the supplier of the third-party product or the Hadoop distribution. You may need to sign in and accept license agreements before accessing the pages required for downloading ODBC connectors.

Configuring Impala to Work with JDBC

Impala supports the standard JDBC interface, allowing access from commercial Business Intelligence tools and custom software written in Java or other programming languages. The JDBC driver allows you to access Impala from a Java program that you write, or a Business Intelligence or similar tool that uses JDBC to communicate with various database products.

Setting up a JDBC connection to Impala involves the following steps:

- Verifying the communication port where the Impala daemons in your cluster are listening for incoming JDBC requests.
- Installing the JDBC driver on every system that runs the JDBC-enabled application.
- Specifying a connection string for the JDBC application to access one of the servers running the `impalad` daemon, with the appropriate security settings.

Configuring the JDBC Port

The following are the default ports that Impala server accepts JDBC connections through:

Protocol	Default Port	Flag to Specify an Alternate Port
HTTP	28000	<code>##hs2_http_port</code>
Binary TCP	21050	<code>##hs2_port</code>

Make sure the port for the protocol you are using is available for communication with clients, for example, that it is not blocked by firewall software.

If your JDBC client software connects to a different port, specify that alternative port number with the flag in the above table when starting the `impalad`.

Choosing the JDBC Driver

In Impala 2.0 and later, you can use the Hive 0.13 or higher JDBC driver. If you are already using JDBC applications with an earlier Impala release, you should update your JDBC driver, because the Hive 0.12 driver that was formerly the only choice is not compatible with Impala 2.0 and later.

The Hive JDBC driver provides a substantial speed increase for JDBC applications with Impala 2.0 and higher, for queries that return large result sets.

Enabling Impala JDBC Support on Client Systems

Using the Hive JDBC Driver

You install the Hive JDBC driver (`hive-jdbc` package) through the Linux package manager, on hosts within the cluster. The driver consists of several JAR files. The same driver can be used by Impala and Hive.

To get the JAR files, install the Hive JDBC driver on each host in the cluster that will run JDBC applications.

Note: The latest JDBC driver, corresponding to Hive 0.13, provides substantial performance improvements for Impala queries that return large result sets. Impala 2.0 and later are compatible with the Hive 0.13 driver. If you already have an older JDBC driver installed, and are running Impala 2.0 or higher, consider upgrading to the latest Hive JDBC driver for best performance with JDBC applications.

If you are using JDBC-enabled applications on hosts outside the cluster, you cannot use the the same install procedure on the hosts. Install the JDBC driver on at least one cluster host using the preceding procedure. Then download the JAR files to each client machine that will use JDBC with Impala:

```
commons-logging-X.X.X.jar
hadoop-common.jar
hive-common-X.XX.X.jar
hive-jdbc-X.XX.X.jar
hive-metastore-X.XX.X.jar
hive-service-X.XX.X.jar
httpclient-X.X.X.jar
httpcore-X.X.X.jar
libfb303-X.X.X.jar
libthrift-X.X.X.jar
log4j-X.X.XX.jar
slf4j-api-X.X.X.jar
```

```
slf4j-log4jxx-X.X.X.jar
```

To enable JDBC support for Impala on the system where you run the JDBC application:

1. Download the JAR files listed above to each client machine.

Note: For Maven users, see [this sample github page](#) for an example of the dependencies you could add to a pom file instead of downloading the individual JARs.

2. Store the JAR files in a location of your choosing, ideally a directory already referenced in your CLASSPATH setting. For example:
 - On Linux, you might use a location such as `/opt/jars/`.
 - On Windows, you might use a subdirectory underneath `C:\Program Files`.
3. To successfully load the Impala JDBC driver, client programs must be able to locate the associated JAR files. This often means setting the CLASSPATH for the client process to include the JARs. Consult the documentation for your JDBC client for more details on how to install new JDBC drivers, but some examples of how to set CLASSPATH variables include:
 - On Linux, if you extracted the JARs to `/opt/jars/`, you might issue the following command to prepend the JAR files path to an existing classpath:

```
export CLASSPATH=/opt/jars/*.jar:$CLASSPATH
```

- On Windows, use the **System Properties** control panel item to modify the **Environment Variables** for your system. Modify the environment variables to include the path to which you extracted the files.

Note: If the existing CLASSPATH on your client machine refers to some older version of the Hive JARs, ensure that the new JARs are the first ones listed. Either put the new JAR files earlier in the listings, or delete the other references to Hive JAR files.

Establishing JDBC Connections

The JDBC driver class depends on which driver you select.

Note: If your JDBC or ODBC application connects to Impala through a load balancer such as haproxy, be cautious about reusing the connections. If the load balancer has set up connection timeout values, either check the connection frequently so that it never sits idle longer than the load balancer timeout value, or check the connection validity before using it and create a new one if the connection has been closed.

Using the Hive JDBC Driver

For example, with the Hive JDBC driver, the class name is `org.apache.hive.jdbc.HiveDriver`.

Once you have configured Impala to work with JDBC, you can establish connections between the two.

To do so for a cluster that does not use Kerberos authentication, use a connection string of the form `jdbc:hive2://host:port;/auth=noSasl`. For example, you might use:

```
jdbc:hive2://myhost.example.com:21050;/auth=noSasl
```

To connect to an instance of Impala that requires Kerberos authentication, use a connection string of the form `jdbc:hive2://host:port;/principal=principal_name`. The principal must be the same user principal you used when starting Impala. For example, you might use:

```
jdbc:hive2://myhost.example.com:21050;/principal=impala/
myhost.example.com@H2.EXAMPLE.COM
```

To connect to an instance of Impala that requires LDAP authentication, use a connection string of the form `jdbc:hive2://host:port/db_name;user=ldap_userid;password=ldap_password`. For example, you might use:

```
jdbc:hive2://myhost.example.com:21050/test_db;user=fred;password=xyz123
```

To connect to an instance of Impala over HTTP, specify the HTTP port, 28000 by default, and `transportMode=http` in the connection string. For example:

```
jdbc:hive2://myhost.example.com:28000/;transportMode=http
```

Note:

Prior to Impala 2.5, the Hive JDBC driver did not support connections that use both Kerberos authentication and SSL encryption. If your cluster is running an older release that has this restriction, use an alternative JDBC driver that supports both of these security features.

Notes about JDBC and ODBC Interaction with Impala SQL Features

Most Impala SQL features work equivalently through the `impala-shell` interpreter of the JDBC or ODBC APIs. The following are some exceptions to keep in mind when switching between the interactive shell and applications using the APIs:

- **Complex type considerations:**
 - Queries involving the complex types (ARRAY, STRUCT, and MAP) require notation that might not be available in all levels of JDBC and ODBC drivers. If you have trouble querying such a table due to the driver level or inability to edit the queries used by the application, you can create a view that exposes a “flattened” version of the complex columns and point the application at the view. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for details.
 - The complex types available in Impala 2.3 and higher are supported by the JDBC `getColumns()` API. Both MAP and ARRAY are reported as the JDBC SQL Type ARRAY, because this is the closest matching Java SQL type. This behavior is consistent with Hive. STRUCT types are reported as the JDBC SQL Type STRUCT.

To be consistent with Hive's behavior, the `TYPE_NAME` field is populated with the primitive type name for scalar types, and with the full `toSql()` for complex types. The resulting type names are somewhat inconsistent, because nested types are printed differently than top-level types. For example, the following list shows how `toSQL()` for Impala types are translated to `TYPE_NAME` values:

<code>DECIMAL(10,10)</code>	becomes	<code>DECIMAL</code>
<code>CHAR(10)</code>	becomes	<code>CHAR</code>
<code>VARCHAR(10)</code>	becomes	<code>VARCHAR</code>
<code>ARRAY<DECIMAL(10,10)></code>	becomes	<code>ARRAY<DECIMAL(10,10)></code>
<code>ARRAY<CHAR(10)></code>	becomes	<code>ARRAY<CHAR(10)></code>
<code>ARRAY<VARCHAR(10)></code>	becomes	<code>ARRAY<VARCHAR(10)></code>

Kudu Considerations for DML Statements

Currently, Impala INSERT, UPDATE, or other DML statements issued through the JDBC interface against a Kudu table do not return JDBC error codes for conditions such as duplicate primary key columns. Therefore, for applications that issue a high volume of DML statements, prefer to use the Kudu Java API directly rather than a JDBC application.

Spooling Impala Query Results

In Impala, you can control how query results are materialized and returned to clients, e.g. `impala-shell`, Hue, JDBC apps.

- When query result spooling is disabled, Impala relies on clients to fetch results to trigger the generation of more result row batches until all the result rows have been produced. If a client issues a query without fetching all the results, the query fragments continue to consume the resources until the query is cancelled and unregistered, potentially tying up resources and causing other queries to wait for an extended period of time in admission control.

Impala would materialize rows on-demand where rows are created only when the client requests them.

- When query result spooling is enabled, result sets of queries are eagerly fetched and spooled in the spooling location, either in memory or on disk.

Once all result rows have been fetched and stored in the spooling location, the resources are freed up. Incoming client fetches can get the data from the spooled results.

Result spooling is turned off by default, but can be enabled via the `SPOOL_QUERY_RESULTS` query option.

Admission Control and Result Spooling

Query results spooling collects and stores query results in memory that is controlled by admission control. Use the following query options to calibrate how much memory to use and when to spill to disk.

MAX_RESULT_SPOOLING_MEM

The maximum amount of memory used when spooling query results. If this value is exceeded when spooling results, all memory will most likely be spilled to disk. Set to 100 MB by default.

MAX_SPILLED_RESULT_SPOOLING_MEM

The maximum amount of memory that can be spilled to disk when spooling query results. Must be greater than or equal to `MAX_RESULT_SPOOLING_MEM`. If this value is exceeded, the coordinator fragment will block until the client has consumed enough rows to free up more memory. Set to 1 GB by default.

Fetch Timeout

Resources for a query are released when the query completes its execution. To prevent clients from indefinitely waiting for query results, use the `FETCH_ROWS_TIMEOUT_MS` query option to set the timeout when clients fetch rows. Timeout applies both when query result spooling is enabled and disabled:

- When result spooling is disabled (`SPOOL_QUERY_RESULTS = FALSE`), the timeout controls how long a client waits for a single row batch to be produced by the coordinator.
- When result spooling is enabled (`SPOOL_QUERY_RESULTS = TRUE`), a client can fetch multiple row batches at a time, so this timeout controls the total time a client waits for row batches to be produced.

Explain Plans

Below is the part of the `EXPLAIN` plan output for result spooling.

```
F01:PLAN FRAGMENT [UNPARTITIONED] hosts=1 instances=1
| Per-Host Resources: mem-estimate=4.02MB mem-reservation=4.00MB thread-
reservation=1
PLAN-ROOT SINK
| mem-estimate=4.00MB mem-reservation=4.00MB spill-buffer=2.00MB thread-
reservation=0
```

- The `mem-estimate` for the `PLAN-ROOT SINK` is an estimate of the amount of memory needed to spool all the rows returned by the query.
- The `mem-reservation` is the number and size of the buffers necessary to spool the query results. By default, the read and write buffers are 2 MB in size each, which is why the default is 4 MB.

PlanRootSink

In Impala, the `PlanRootSink` class controls the passing of batches of rows to the clients and acts as a queue of rows to be sent to clients.

- When result spooling is disabled, a single batch or rows is sent to the `PlanRootSink`, and then the client must consume that batch before another one can be sent.
- When result spooling is enabled, multiple batches of rows can be sent to the `PlanRootSink`, and multiple batches can be consumed by the client.

Related information: [MAX_RESULT_SPOOLING_MEM Query Option](#) on page 366, [MAX_SPILLED_RESULT_SPOOLING_MEM Query Option](#) on page 370, [SPOOL_QUERY_RESULTS Query Option](#) on page 392

Impala Fault Tolerance

This section describes the fault tolerance mechanisms built into Impala. Fault tolerance allows Impala to continue to operate in the face of hardware or process faults.

Impala uses the statestored process to provide cluster membership for an Impala cluster. This is one of the core ways Impala provides fault tolerance. The statestore periodically sends heartbeats (RPCs) to each `impalad` process. If an `impalad` stops responding to heartbeats, the statestore will consider the `impalad` as failed, and it will remove it from the cluster membership state. The updates to the cluster membership will be broadcasted to all `impalads`.

Impala Transparent Query Retries

Transparent query retries will automatically retry any queries that fail due to cluster membership changes. A cluster membership change typically entails a node leaving the cluster before it crashed or for some other reason stopped responding to statestore heartbeats.

Traditionally, if a query runs on a node in the Impala cluster, and that node crashes, then the query will fail and it is up to the user to retry the query. With transparent query retries, the query will be automatically retried.

- Queries are only retried if the query failed due to a cluster membership change. Trivial failures, like SQL parsing exceptions are **not** retried.
- Cluster membership changes fall into two categories: membership updates from the statestore or node blacklisting events.

`impalads` periodically send heartbeats to the statestore, if an `impalad` stops sending heartbeats to the statestore then that `impalad` is removed from the cluster membership

Node blacklisting events occur when a query fails and as a result, an `impalad` in the cluster is added to the Coordinator's node blacklist. In this scenario, the query is retried.

- For most users, query retries will be completely transparent, but users who want to know why a retry was necessary can use runtime profiles. Each query attempt is modelled as a completely new query. Thus, each query attempt has its own runtime profiles. Users can look through the profiles of the failed query attempts to determine why the query was retried.

Transparent query retries are turned off by default, but can be enabled via the `RETRY_FAILED_QUERIES` query option.

Related information: [RETRY_FAILED_QUERIES Query Option](#) on page 387

Impala Node Blacklisting

Node Blacklisting allows Impala Coordinators to be more aggressive about deciding that an executor is unhealthy or unavailable, to minimize failed queries in environments where cluster membership maybe more variable, rather than having to wait on the statestore heartbeat mechanism to decide that the executor is down.

Node blacklists are local to a coordinator. A node is put on the blacklist based on information from failed queries. Nodes are only blacklisted temporarily, and are taken off the blacklist after a certain period of time.

Troubleshooting Impala

Troubleshooting for Impala requires being able to diagnose and debug problems with performance, network connectivity, out-of-memory conditions, disk space usage, and crash or hang conditions in any of the Impala-related daemons.

Troubleshooting Impala SQL Syntax Issues

In general, if queries issued against Impala fail, you can try running these same queries against Hive.

- If a query fails against both Impala and Hive, it is likely that there is a problem with your query or other elements of your environment:
 - Review the [Language Reference](#) to ensure your query is valid.
 - Check [Impala Reserved Words](#) on page 821 to see if any database, table, column, or other object names in your query conflict with Impala reserved words. Quote those names with backticks (``) if so.
 - Check [Impala Built-In Functions](#) on page 428 to confirm whether Impala supports all the built-in functions being used by your query, and whether argument and return types are the same as you expect.
 - Review the [contents of the Impala logs](#) for any information that may be useful in identifying the source of the problem.
- If a query fails against Impala but not Hive, it is likely that there is a problem with your Impala installation.

Troubleshooting Crashes Caused by Memory Resource Limit

Under very high concurrency, Impala could encounter a serious error due to usage of various operating system resources. Errors similar to the following may be caused by operating system resource exhaustion:

```
F0629 08:20:02.956413 29088 llvm-codegen.cc:111] LLVM hit fatal error:
Unable to allocate section memory!
terminate called after throwing an instance of
'boost::exception_detail::clone_impl<boost::exception_detail::error_info_injector<boost
>'
```

The KRPC implementation in Impala 2.12 / 3.0 greatly reduces thread counts and the chances of hitting a resource limit.

If you still get an error similar to the above in Impala 3.0 and higher, try increasing the `max_map_count` OS virtual memory parameter. `max_map_count` defines the maximum number of memory map areas that a process can use. Configure each host running an `impalad` daemon with the command to increase `max_map_count` to 8 GB.

```
echo 8000000 > /proc/sys/vm/max_map_count
```

To make the above settings durable, refer to your OS documentation. For example, on RHEL 6.x:

1. Add the following line to `/etc/sysctl.conf`:

```
vm.max_map_count=8000000
```

2. Run the following command:

```
sysctl -p
```

Troubleshooting I/O Capacity Problems

Impala queries are typically I/O-intensive. If there is an I/O problem with storage devices, or with HDFS itself, Impala queries could show slow response times with no obvious cause on the Impala side. Slow I/O on even a single Impala daemon could result in an overall slowdown, because queries involving clauses such as `ORDER BY`, `GROUP BY`, or `JOIN` do not start returning results until all executor Impala daemons have finished their work.

To test whether the Linux I/O system itself is performing as expected, run Linux commands like the following on each host Impala daemon is running:

```
$ sudo sysctl -w vm.drop_caches=3 vm.drop_caches=0
vm.drop_caches = 3
vm.drop_caches = 0
$ sudo dd if=/dev/sda bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.60373 s, 192 MB/s
$ sudo dd if=/dev/sdb bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.51145 s, 195 MB/s
$ sudo dd if=/dev/sdc bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.58096 s, 192 MB/s
$ sudo dd if=/dev/sdd bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.43924 s, 197 MB/s
```

On modern hardware, a throughput rate of less than 100 MB/s typically indicates a performance issue with the storage device. Correct the hardware problem before continuing with Impala tuning or benchmarking.

Impala Troubleshooting Quick Reference

The following table lists common problems and potential solutions.

Symptom	Explanation	Recommendation
Impala takes a long time to start.	Impala instances with large numbers of tables, partitions, or data files take longer to start because the metadata for these objects is broadcast to all <code>impalad</code> nodes and cached.	Adjust timeout and synchronicity settings.

Symptom	Explanation	Recommendation
Joins fail to complete.	There may be insufficient memory. During a join, data from the second, third, and so on sets to be joined is loaded into memory. If Impala chooses an inefficient join order or join mechanism, the query could exceed the total memory available.	Start by gathering statistics with the <code>COMPUTE STATS</code> statement for each table involved in the join. Consider specifying the <code>[SHUFFLE]</code> hint so that data from the joined tables is split up between nodes rather than broadcast to each node. If tuning at the SQL level is not sufficient, add more memory to your system or join smaller data sets.
Queries return incorrect results.	Impala metadata may be outdated after changes are performed in Hive.	Where possible, use the appropriate Impala statement (<code>INSERT</code> , <code>LOAD DATA</code> , <code>CREATE TABLE</code> , <code>ALTER TABLE</code> , <code>COMPUTE STATS</code> , and so on) rather than switching back and forth between Impala and Hive. Impala automatically broadcasts the results of DDL and DML operations to all Impala nodes in the cluster, but does not automatically recognize when such changes are made through Hive. After inserting data, adding a partition, or other operation in Hive, refresh the metadata for the table as described in REFRESH Statement on page 312.
Queries are slow to return results.	<p>Some <code>impalad</code> instances may not have started. Using a browser, connect to the host running the Impala state store. Connect using an address of the form <code>http://hostname:port/metrics</code>.</p> <p>Note: Replace <i>hostname</i> and <i>port</i> with the hostname and port of your Impala state store host machine and web server port. The default port is 25010.</p> <p>The number of <code>impalad</code> instances listed should match the expected number of <code>impalad</code> instances installed in the cluster. There should also be one <code>impalad</code> instance installed on each DataNode.</p>	Ensure Impala is installed on all DataNodes. Start any <code>impalad</code> instances that are not running.
Queries are slow to return results.	Impala may not be configured to use native checksumming. Native checksumming uses machine-specific instructions to compute checksums over HDFS data very quickly. Review Impala logs. If you find instances of "INFO util.NativeCodeLoader: Loaded the native-hadoop" messages, native checksumming is not enabled.	Ensure Impala is configured to use native checksumming as described in Post-Installation Configuration for Impala on page 27.

Symptom	Explanation	Recommendation
Queries are slow to return results.	Impala may not be configured to use data locality tracking.	Test Impala for data locality tracking and make configuration changes as necessary. Information on this process can be found in Post-Installation Configuration for Impala on page 27.
Attempts to complete Impala tasks such as executing INSERT-SELECT actions fail. The Impala logs include notes that files could not be opened due to permission denied.	This can be the result of permissions issues. For example, you could use the Hive shell as the hive user to create a table. After creating this table, you could attempt to complete some action, such as an INSERT-SELECT on the table. Because the table was created using one user and the INSERT-SELECT is attempted by another, this action may fail due to permissions issues.	In general, ensure the Impala user has sufficient permissions. In the preceding example, ensure the Impala user has sufficient permissions to the table that the Hive user created.
Impala fails to start up, with the <code>impalad</code> logs referring to errors connecting to the statestore service and attempts to re-register.	A large number of databases, tables, partitions, and so on can require metadata synchronization, particularly on startup, that takes longer than the default timeout for the statestore service.	Configure the statestore timeout value and possibly other settings related to the frequency of statestore updates and metadata loading. See Increasing the Statestore Timeout on page 66 and Scalability Considerations for the Impala Statestore on page 658.

Impala Web User Interface for Debugging

Each of the Impala daemons (`impalad`, `statestored`, and `catalogd`) includes a built-in web server that displays diagnostic and status information.

impalad Web UI

The `impalad` Web UI includes information about configuration settings, running and completed queries, and associated performance and resource usage for queries. In particular, the **Details** link for each query displays alternative views of the query including a graphical representation of the plan, and the output of the `EXPLAIN`, `SUMMARY`, and `PROFILE` statements from `impala-shell`. Each host that runs the `impalad` daemon has its own instance of the Web UI, with details about those queries for which that host served as the coordinator. The `impalad` Web UI is primarily used

for diagnosing query problems that can be traced to a particular node.

statestored Web UI

The `statestored` Web UI includes information about memory usage, configuration settings, and ongoing health checks performed by `statestored`. Because there is only a single instance of the `statestored` within any Impala cluster, you access the Web UI only on the particular host that serves as the Impala StateStore.

catalogd Web UI

The `catalogd` Web UI includes information about the databases, tables, and other objects managed by Impala, in addition to the resource usage and configuration settings of the `catalogd`. Because there is only a single instance of the `catalogd` within any Impala cluster, you access the Web UI only on the particular host that serves as the Impala Catalog Server.

Configuring Debug Web UIs

Turning off the Web UI

To disable Web UI for the `impalad`, `statestored`, or `catalogd`:

1. Stop the Impala role you want to turn off the Web UI for, `impalad`, `statestored`, or `catalogd`.
2. Restart the role with the `##enable_webserver=false` startup flag.

Using Kerberos HTTP SPNEGO Authentication for Web UI

To provide security through Kerberos, Impala Web UIs support SPNEGO, a protocol for securing HTTP requests with Kerberos by passing negotiation tokens through HTTP headers.

To enable authorization using SPNEGO, set the `--webserver_require_spnego=true` startup flag and restart the Impala roles, `impalad`, `statestored`, or `catalogd`.

Debug Web UI for impalad

To debug and troubleshoot an `impalad` using a web-based interface, open the URL

`http://impala#server#hostname:25000/` in a browser. (For secure clusters, use the prefix `https://` instead of `http://`.)

Because each Impala node produces its own set of debug information, you should choose a specific node that you want to investigate an issue on.

Main Page

The main `impalad` Web UI page at `/` lists the following information about the `impalad`:

- The version of the `impalad` daemon

The **Version** section also contains other information, such as when Impala was built and what build flags were used.

- Process start time
- Hardware information
- OS information
- Process information
- CGroup information

Admission Controller Page

The **Admission Controller** `impalad` debug Web UI is at `/admission` page under the main `impalad` Web UI.

Use the `/admission` page to troubleshoot queued queries and the admission control.

The **admission** page provides the following information about each resource pool to which queries have been submitted at least once:

- Time since the `statestored` received the last update
- A warning if this `impalad` is considered disconnected from the `statestored` and thus the information on this page could be stale.
- Pool configuration
- Queued queries submitted to this coordinator, in the order of submission
- Running queries submitted to this coordinator
- Pool stats
 - Average of time in queue: An exponential moving average which represents the average time in queue over the last 10 to 12 queries. If a query is admitted immediately, the wait time of 0 is used in calculating this average wait time.
- Histogram of the distribution of peak memory used by queries admitted to the pool

Use the histogram to figure out settings for the minimum and maximum query `MEM_LIMIT` ranges for this pool.

The histogram displays data for all queries admitted to the pool, including the queries that finished, got canceled, or hit an error.

Click on the pool name to only display information relevant to that pool. You can then refresh the debug page to see only the information for that specific pool.

Click **Reset informational stats for all pools** to reset the stats that keep track of historical data, such as **Totals** stats, **Time in queue (exponential moving average)**, and the histogram.

The above information is also available as a JSON object from the following HTTP endpoint:

```
http://impala-server-hostname:port/admission?json
```

See [Admission Control and Query Queuing](#) on page 675 for the description of the properties in admission control.

Known Backends Page

The **Known backends** page of the `impalad` debug Web UI is at `/backends` under the main `impalad` Web UI.

This page lists the following info for each of the `impalad` nodes in the cluster. Because each `impalad` daemon knows about every other `impalad` daemon through the `StateStore`, this information should be the same regardless of which node you select.

- Address of the node: Host name and port
- KRPC address: The KRPC address of the `impalad`. Use this address when you issue the `SHUTDOWN` command for this `impalad`.
- Whether acting as a coordinator
- Whether acting as an executor
- Quiescing status: Specify whether the graceful shutdown process has been initiated on this `impalad`.
- Memory limit for admission: The amount of memory that can be admitted to this backend by the admission controller.
- Memory reserved: The amount of memory reserved by queries that are active, either currently executing or finished but not yet closed, on this backend.

The memory reserved for a query that is currently executing is its memory limit, if set. Otherwise, if the query has no limit or if the query finished executing, the current consumption is used.

- Memory of the queries admitted to this coordinator: The memory submitted to this particular host by the queries admitted by this coordinator.

Catalog Page

The **Catalog** page of the `impalad` debug Web UI is at `/catalog` under the main `impalad` Web UI.

This page displays a list of databases and associated tables recognized by this instance of `impalad`. You can use this page to locate which database a table is in, check the exact spelling of a database or table name, look for identical table names in multiple databases. The primary debugging use case would be to check if an `impalad` instance has knowledge of a particular table that someone expects to be in a particular database.

Hadoop Configuration

The **Hadoop Configuration** page of the `impalad` debug Web UI is at `/hadoop-varz` under the main `impalad` Web UI.

This page displays the Hadoop common configurations that Impala is running with.

JMX

The **JMX** page of the `impalad` debug Web UI is at `/jmx` under the main `impalad` Web UI.

This page displays monitoring information about various JVM subsystems, such as memory pools, thread management, runtime. etc.

Java Log Level

The **Change log level** page of the `impalad` debug Web UI is at `/log_level` under the main `impalad` Web UI.

This page displays the current Java and backend log levels, and it allows you to change the log levels dynamically without having to restart the `impalad`.

Logs Page

The **INFO logs** page of the `impalad` debug Web UI is at `/logs` under the main `impalad` Web UI.

This page shows the last portion of the `impalad.INFO` log file, including the info, warning, and error logs for the `impalad`. You can see the details of the most recent operations, whether the operations succeeded or encountered errors. This page provides one central place for the log files and saves you from looking around the filesystem for the log files, which could be in different locations on clusters that use cluster management software.

Memz Page

The **Memory Usage** page of the `impalad` debug Web UI is at `/memz` under the main `impalad` Web UI.

This page displays the summary and detailed information about memory usage by the `impalad`.

Metrics Page

The **Metrics** page of the `impalad` debug Web UI is at `/metrics` under the main `impalad` Web UI.

This page displays the current set of metrics, counters and flags representing various aspects of `impalad` internal operations.

Queries Page

The **Queries** page of the `impalad` debug Web UI is at `/queries` under the main `impalad` Web UI.

This page lists:

- Currently running queries
- Queries that have completed their execution, but have not been closed yet
- Completed queries whose details still reside in memory

The queries are listed in reverse chronological order, with the most recent at the top. You can control the amount of memory devoted to completed queries by specifying the `--#query_log_size` and `--#query_log_size_in_bytes` startup options for `impalad`.

This page provides:

- How many SQL statements are failing (State value of EXCEPTION)
- How large the result sets are (# rows fetched)
- How long each statement took (Start Time and End Time)

Click the **Details** link for a query to display the detailed performance characteristics of that query, such as the profile output.

On the query detail page, in the **Profile** tab, you have options to export the query profile output to the Thrift, text, or Json format.

The **Queries** page also includes the **Query Locations** section that lists the number of running queries with fragments on this host.

RPC Services Page

The **RPC durations** page of the `impalad` debug Web UI is at `/rpcz` under the main `impalad` Web UI.

This page displays information, such as the duration, about the RPC communications of this `impalad` with other Impala daemons.

Sessions Page

The **Sessions** page of the `impalad` debug Web UI is at `/session` under the main `impalad` Web UI.

This page displays information about the sessions currently connected to this `impalad` instance. For example, sessions could include connections from the `impala-shell` command, JDBC or ODBC applications, or the Impala Query UI in the Hue web interface.

Threadz Page

The **Threads** page of the `impalad` debug Web UI is at `/threadz` under the main `impalad` Web UI.

This page displays information about the threads used by this instance of `impalad`, and it shows which categories they are grouped into. Making use of this information requires substantial knowledge about Impala internals.

Varz Page

The **Varz** page of the `impalad` debug Web UI is at `/varz` under the main `impalad` Web UI.

This page shows the configuration settings in effect when this instance of `impalad` communicates with other Hadoop components such as HDFS and YARN. These settings are collected from a set of configuration files.

The bottom of this page also lists all the command-line settings in effect for this instance of `impalad`. See [Modifying Impala Startup Options](#) on page 32 for information about modifying these values.

Prometheus Metrics Page

At `/metrics_prometheus` under the main `impalad` Web UI, the metrics are generated in Prometheus exposition format that Prometheus can consume for event monitoring and alerting. The `/metrics_prometheus` is not shown in the Web UI list of pages.

Debug Web UI for statestored

To debug and troubleshoot the `statestored` daemon using a web-based interface, open the URL `http://impala#server#hostname:25010/` in a browser. (For secure clusters, use the prefix `https://` instead of `http://`.)

Main Page

The main `statestored` Web UI page at `/` lists the following information about the `statestored`:

- The version of the `statestored` daemon
- Process start time

- Hardware information
- OS information
- Process information
- CGroup information

Logs Page

The **INFO logs** page of the debug Web UI is at **/logs** under the main `statestored` Web UI.

This page shows the last portion of the `statestored.INFO` log file, including the info, warning, and error logs for the `statestored`. You can refer here to see the details of the most recent operations, whether the operations succeeded or encountered errors. This page provides one central place for the log files and saves you from looking around the filesystem for the log files, which could be in different locations on clusters that use cluster management software.

Memz Page

The **Memory Usage** page of the debug Web UI is at **/memz** under the main `statestored` Web UI.

This page displays summary and detailed information about memory usage by the `statestored`. You can see the memory limit in effect for the node, and how much of that memory Impala is currently using.

Metrics Page

The **Metrics** page of the debug Web UI is at **/metrics** under the main `statestored` Web UI.

This page displays the current set of metrics: counters and flags representing various aspects of `statestored` internal operation.

RPC Services Page

The **RPC durations** page of the `statestored` debug Web UI is at **/rpcz** under the main `statestored` Web UI.

This page displays information, such as the durations, about the RPC communications of this `statestored` with other Impala daemons.

Subscribers Page

The **Subscribers** page of the debug Web UI is at **/subscribers** under the main `statestored` Web UI.

This page displays information about the other Impala daemons that have registered with the `statestored` to receive and send updates.

Threadz Page

The **Threads** page of the debug Web UI is at **/threadz** under the main `statestored` Web UI.

This page displays information about the threads used by this instance of `statestored`, and shows which categories they are grouped into. Making use of this information requires substantial knowledge about Impala internals.

Topics Page

The **Topics** page of the debug Web UI is at **/topics** under the main `statestored` Web UI.

This page displays information about the topics to which the other Impala daemons have registered to receive updates.

Varz Page

The **Varz** page of the debug Web UI is at **/varz** under the main `statestored` Web UI.

This page shows the configuration settings in effect when this instance of `statestored` communicates with other Hadoop components such as HDFS and YARN. These settings are collected from a set of configuration files.

The bottom of this page also lists all the command-line settings in effect for this instance of `statestored`. See [Modifying Impala Startup Options](#) on page 32 for information about modifying these values.

Prometheus Metrics Page

At `/metrics_prometheus` under the main `statestored` Web UI, the metrics are generated in Prometheus exposition format that Prometheus can consume for event monitoring and alerting. The `/metrics_prometheus` is not shown in the Web UI list of pages.

Debug Web UI for catalogd

The main page of the debug Web UI is at `http://impala#server#hostname:25020/` (non-secure cluster) or `https://impala#server#hostname:25020/` (secure cluster).

Main Page

The main `catalogd` Web UI page at `/` lists the following information about the `catalogd`:

- The version of the `catalogd` daemon
- Process start time
- Hardware information
- OS information
- Process information
- CGroup information

Catalog Page

The **Catalog** page of the debug Web UI is at `/catalog` under the main `catalogd` Web UI.

This page displays a list of databases and associated tables recognized by this instance of `catalogd`. You can use this page to locate which database a table is in, check the exact spelling of a database or table name, look for identical table names in multiple databases. The catalog information is represented as the underlying Thrift data structures.

JMX

The **JMX** page of the `catalogd` debug Web UI is at `/jmx` under the main `catalogd` Web UI.

This page displays monitoring information about various JVM subsystems, such as memory pools, thread management, runtime. etc.

Java Log Level

The **Change log level** page of the `catalogd` debug Web UI is at `/log_level` under the main `catalogd` Web UI.

The page displays the current Java and backend log levels and allows you to change the log levels dynamically without having to restart the `catalogd`.

Logs Page

The **INFO logs** page of the debug Web UI is at `/logs` under the main `catalogd` Web UI.

This page shows the last portion of the `catalogd.INFO` log file, including the info, warning, and error logs for the `catalogd` daemon. You can refer here to see the details of the most recent operations, whether the operations succeeded or encountered errors. This page provides one central place for the log files and saves you from looking around the filesystem for the log files, which could be in different locations on clusters that use cluster management software.

Memz Page

The **Memory Usage** page of the debug Web UI is at `/memz` under the main `catalogd` Web UI.

This page displays summary and detailed information about memory usage by the `catalogd`. You can see the memory limit in effect for the node, and how much of that memory Impala is currently using.

Metrics Page

The **Metrics** page of the debug Web UI is at **/metrics** under the main catalogd Web UI.

This page displays the current set of metrics: counters and flags representing various aspects of catalogd internal operation.

RPC Services Page

The **RPC durations** page of the catalogd debug Web UI is at **/rpcz** under the main catalogd Web UI.

This page displays information, such as the durations, about the RPC communications of this catalogd with other Impala daemons.

Threadz Page

The **Threads** page of the debug Web UI is at **/threadz** under the main catalogd Web UI.

This page displays information about the threads used by this instance of catalogd, and shows which categories they are grouped into. Making use of this information requires substantial knowledge about Impala internals.

Varz Page

The **Varz** page of the debug Web UI is at **/varz** under the main catalogd Web UI.

This page shows the configuration settings in effect when this instance of catalogd communicates with other Hadoop components such as HDFS and YARN. These settings are collected from a set of configuration files.

The bottom of this page also lists all the command-line settings in effect for this instance of catalogd. See [Modifying Impala Startup Options](#) on page 32 for information about modifying these values.

Prometheus Metrics Page

At **/metrics_prometheus** under the main catalogd Web UI, the metrics are generated in Prometheus exposition format that Prometheus can consume for event monitoring and alerting. The **/metrics_prometheus** is not shown in the Web UI list of pages.

Breakpad Minidumps for Impala (Impala 2.6 or higher only)

The [breakpad](#) project is an open-source framework for crash reporting. In Impala 2.6 and higher, Impala can use breakpad to record stack information and register values when any of the Impala-related daemons crash due to an error such as SIGSEGV or unhandled exceptions. The dump files are much smaller than traditional core dump files. The dump mechanism itself uses very little memory, which improves reliability if the crash occurs while the system is low on memory.

Important: Because of the internal mechanisms involving Impala memory allocation and Linux signalling for out-of-memory (OOM) errors, if an Impala-related daemon experiences a crash due to an OOM condition, it does *not* generate a minidump for that error.

Enabling or Disabling Minidump Generation

By default, a minidump file is generated when an Impala-related daemon crashes.

To turn off generation of the minidump files, use one of the following options:

- Set the `--enable_minidumps` configuration setting to `false`. Restart the corresponding services or daemons.
- Set the `--minidump_path` configuration setting to an empty string. Restart the corresponding services or daemons.

In Impala 2.7 and higher, you can send a SIGUSR1 signal to any Impala-related daemon to write a Breakpad minidump. For advanced troubleshooting, you can now produce a minidump without triggering a crash.

Specifying the Location for Minidump Files

By default, all minidump files are written to the following location on the host where a crash occurs:

- Clusters not managed by cluster management software: *impala_log_dir/daemon_name/minidumps/daemon_name*

The minidump files for `impalad`, `catalogd`, and `statestored` are each written to a separate directory.

To specify a different location, set the **minidump_path** configuration setting of one or more Impala-related daemons, and restart the corresponding services or daemons.

If you specify a relative path for this setting, the value is interpreted relative to the default **minidump_path** directory.

Controlling the Number of Minidump Files

Like any files used for logging or troubleshooting, consider limiting the number of minidump files, or removing unneeded ones, depending on the amount of free storage space on the hosts in the cluster.

Because the minidump files are only used for problem resolution, you can remove any such files that are not needed to debug current issues.

To control how many minidump files Impala keeps around at any one time, set the **max_minidumps** configuration setting for one or more Impala-related daemon, and restart the corresponding services or daemons. The default for this setting is 9. A zero or negative value is interpreted as “unlimited”.

Detecting Crash Events

You can see in the Impala log files when crash events occur that generate minidump files. Because each restart begins a new log file, the “crashed” message is always at or near the bottom of the log file. There might be another later message if core dumps are also enabled.

Demonstration of Breakpad Feature

The following example uses the command `kill -11` to simulate a SIGSEGV crash for an `impalad` process on a single DataNode, then examines the relevant log files and minidump file.

First, as root on a worker node, kill the `impalad` process with a SIGSEGV error. The original process ID was 23114.

```
# ps ax | grep impalad
23114 ?        Sl      0:18 /opt/local/parcels/<parcel_version>/lib/impala/
sbin/impalad --flagfile=/var/run/impala/process/114-impala-IMPALAD/impala-
conf/impalad_flags
31259 pts/0    S+      0:00 grep impalad
#
# kill -11 23114
#
# ps ax | grep impalad
31374 ?        Rl      0:04 /opt/local/parcels/<parcel_version>/lib/impala/
sbin/impalad --flagfile=/var/run/impala/process/114-impala-IMPALAD/impala-
conf/impalad_flags
31475 pts/0    S+      0:00 grep impalad
```

We locate the log directory underneath `/var/log`. There is a `.INFO`, `.WARNING`, and `.ERROR` log file for the 23114 process ID. The minidump message is written to the `.INFO` file and the `.ERROR` file, but not the `.WARNING` file. In this case, a large core file was also produced.

```
# cd /var/log/impalad
# ls -la | grep 23114
```

```
-rw----- 1 impala impala 3539079168 Jun 23 15:20 core.23114
-rw-r--r-- 1 impala impala      99057 Jun 23 15:20 hs_err_pid23114.log
-rw-r--r-- 1 impala impala      351 Jun 23 15:20
  impalad.worker_node_123.impala.log.ERROR.20160623-140343.23114
-rw-r--r-- 1 impala impala      29101 Jun 23 15:20
  impalad.worker_node_123.impala.log.INFO.20160623-140343.23114
-rw-r--r-- 1 impala impala      228 Jun 23 14:03
  impalad.worker_node_123.impala.log.WARNING.20160623-140343.23114
```

The `.INFO` log includes the location of the minidump file, followed by a report of a core dump. With the `breakpad` minidump feature enabled, now we might disable core dumps or keep fewer of them around.

```
# cat impalad.worker_node_123.impala.log.INFO.20160623-140343.23114
...
Wrote minidump to /var/log/impala-minidumps/impalad/0980da2d-
a905-01e1-25ff883a-04ee027a.dmp
#
# A fatal error has been detected by the Java Runtime Environment:
#
# SIGSEGV (0xb) at pc=0x00000030c0e0b68a, pid=23114, tid=139869541455968
#
# JRE version: Java(TM) SE Runtime Environment (7.0_67-b01) (build 1.7.0_67-
b01)
# Java VM: Java HotSpot(TM) 64-Bit Server VM (24.65-b04 mixed mode linux-
amd64 compressed oops)
# Problematic frame:
# C [libpthread.so.0+0xb68a] pthread_cond_wait+0xca
#
# Core dump written. Default location: /var/log/impalad/core or core.23114
#
# An error report file with more information is saved as:
# /var/log/impalad/hs_err_pid23114.log
#
# If you would like to submit a bug report, please visit:
# http://bugreport.sun.com/bugreport/crash.jsp
# The crash happened outside the Java Virtual Machine in native code.
# See problematic frame for where to report the bug.
...

# cat impalad.worker_node_123.impala.log.ERROR.20160623-140343.23114

Log file created at: 2016/06/23 14:03:43
Running on machine:.worker_node_123
Log line format: [IWEF]mmdd hh:mm:ss.uuuuuu threadid file:line] msg
E0623 14:03:43.911002 23114 logging.cc:118] stderr will be logged to this
file.
Wrote minidump to /var/log/impala-minidumps/impalad/0980da2d-
a905-01e1-25ff883a-04ee027a.dmp
```

The resulting minidump file is much smaller than the corresponding core file, making it much easier to supply diagnostic information to the appropriate support channel.

```
# pwd
/var/log/impalad
# cd ../impala-minidumps/impalad
# ls
0980da2d-a905-01e1-25ff883a-04ee027a.dmp
# du -kh *
```

2.4M 0980da2d-a905-01e1-25ff883a-04ee027a.dmp

Ports Used by Impala

Impala uses the TCP ports listed in the following table. Before deploying Impala, ensure these ports are open on each system. You can use the corresponding start-up flags to overwrite the default ports.

Scope / Role	Startup Flag	Default Port	Comment
Impala Daemon	--beeswax_port	21000	Port on which Beeswax client requests are served by Impala Daemons.
Impala Daemon	--hs2_port	21050	Port on which HiveServer2 client requests are served by Impala Daemons.
Impala Daemon	--be_port	22000	Internal use only. Impala daemons use this port for Thrift based communication with each other.
Impala Daemon	--state_store_subscriber_port	23000	Internal use only. Impala daemons listen on this port for updates from the StateStore daemon.
Catalog Daemon	--state_store_subscriber_port	23020	Internal use only. The Catalog Server daemon listens on this port for updates from the StateStore daemon.
Impala Daemon	--webserver_port	25000	Impala debug Web UI for administrators to monitor and troubleshoot.
Impala StateStore Daemon	--webserver_port	25010	StateStore debug Web UI for administrators to monitor and troubleshoot.
Impala Catalog Daemon	--webserver_port	25020	Catalog Server debug Web UI for administrators to monitor and troubleshoot. New in Impala 1.2 and higher.
Impala StateStore Daemon	--state_store_port	24000	Internal use only. The StateStore daemon listens on this port for registration/unregistration requests.
Impala Catalog Daemon	--catalog_service_port	26000	Internal use only. The Catalog Server uses this port to communicate with the Impala daemons. New in Impala 1.2 and higher.
Impala Daemon	--krpc_port	27000	Internal use only. Impala daemons use this port for KRPC based communication with each other.

Scope / Role	Startup Flag	Default Port	Comment
Impala Daemon	--hs2_http_port	28000	Used to transmit commands and receive results by client applications over HTTP via the HiveServer2 protocol.

Impala Reserved Words

This topic lists the reserved words in Impala.

A reserved word is one that cannot be used directly as an identifier. If you need to use it as an identifier, you must quote it with backticks. For example:

- `CREATE TABLE select (x INT): fails`
- `CREATE TABLE `select` (x INT): succeeds`

Because different database systems have different sets of reserved words, and the reserved words change from release to release, carefully consider database, table, and column names to ensure maximum compatibility between products and versions.

Also consider whether your object names are the same as any Hive keywords, and rename or quote any that conflict as you might switch between Impala and Hive when doing analytics and ETL. Consult the [list of Hive keywords](#).

To future-proof your code, you should avoid additional words in case they become reserved words if Impala adds features in later releases. This kind of planning can also help to avoid name conflicts in case you port SQL from other systems that have different sets of reserved words. The Future Keyword column in the table below indicates those additional words that you should avoid for table, column, or other object names, even though they are not currently reserved by Impala.

The following is a summary of the process for deciding whether a particular SQL 2016 word is to be reserved in Impala.

- By default, Impala targets to have the same list of reserved words as SQL 2016.
- At the same time, to be compatible with earlier versions of Impala and to avoid breaking existing tables/workloads, Impala built-in function names are removed from the reserved words list, e.g. COUNT, AVG, as Impala generally does not need to reserve the names of built-in functions for parsing to work.
- For those remaining SQL 2016 reserved words, if a word is likely to be in-use by users of older Impala versions and if there is a low chance of Impala needing to reserve that word in the future, then the word is not reserved.
- Otherwise, the word is reserved in Impala.

List of Reserved Words

Keyword	Reserved in SQL:2016	Reserved in Impala 2.12 and lower	Reserved in Impala 3.0 and higher	Future Keyword
abs	X			
acos	X			
add		X	X	

aggregate		X	X	
all	X	X	X	
allocate	X		X	
alter	X	X	X	
analytic		X	X	
and	X	X	X	
anti		X	X	
any	X		X	
api_version			X	
are	X		X	
array	X	X	X	
array_agg	X		X	
array_max_cardinality	X		X	
as	X	X	X	
asc		X	X	
asensitive	X		X	
asin	X			
asymmetric	X		X	
at	X		X	
atan	X			
atomic	X		X	
authorization	X		X	
avg	X			
avro		X	X	
backup				X
begin	X			X
begin_frame	X		X	
begin_partition	X		X	
between	X	X	X	
bigint	X	X	X	
binary	X	X	X	
blob	X		X	
block_size			X	
boolean	X	X	X	
both	X		X	

break				X
browse				X
buckets			X	
bulk				X
by	X	X	X	
cache				
cached		X	X	
call	X			
called	X		X	
cardinality	X		X	
cascade		X	X	
cascaded	X		X	
case	X	X	X	
cast	X	X	X	
ceil	X			
ceiling	X			
change		X	X	
char	X	X	X	
char_length	X			
character	X		X	
character_length	X			
check	X			X
checkpoint				X
class		X	X	
classifier	X			
clob	X		X	
close	X			X
close_fn			X	
clustered				X
coalesce	X			X
collate	X		X	
collect	X		X	
column	X	X	X	
columns		X	X	
comment		X	X	

commit	X		X	
compression		X	X	
compute		X	X	
condition	X		X	
conf				
connect	X		X	
constraint	X		X	
contains	X		X	
continue				X
convert	X		X	
copy	X		X	
corr	X		X	
corresponding	X		X	
cos	X			
cosh	X			
count	X			
covar_pop	X		X	
covar_samp	X		X	
create	X	X	X	
cross	X	X	X	
cube	X		X	
cume_dist	X			
current	X	X	X	
current_catalog	X			
current_date	X		X	
current_default_transform_group	X		X	
current_path	X		X	
current_role	X		X	
current_row	X		X	
current_schema	X		X	
current_time	X		X	
current_timestamp	X			X
current_transform_group_for_type	X		X	
current_user	X			X
cursor	X		X	

cycle	X		X	
data		X	X	
database		X	X	
databases		X	X	
date	X	X	X	
datetime		X	X	
day	X			
dayofweek				
dbcc				X
deallocate	X		X	
dec	X		X	
decfloat	X		X	
decimal	X	X	X	
declare	X		X	
default	X	X	X	
define	X		X	
delete	X	X	X	
delimited		X	X	
dense_rank	X			
deny				X
deref	X		X	
desc		X	X	
describe	X	X	X	
deterministic	X		X	
disable	X		X	
disconnect	X		X	
disk				X
distinct	X	X	X	
distributed				X
div		X	X	
double	X	X	X	
drop	X	X	X	
dump				X
dynamic	X		X	
each	X		X	

element	X		X	
else	X	X	X	
empty	X		X	
enable	X		X	
encoding		X	X	
end	X	X	X	
end-exec	X		X	
end_frame	X		X	
end_partition	X		X	
equals	X		X	
errlvl				X
escape	X		X	
escaped		X	X	
every	X		X	
except	X		X	
exchange				
exec	X		X	
execute	X		X	
exists	X	X	X	
exit				X
exp	X			
explain		X	X	
extended		X	X	
external	X	X	X	
extract	X			
false	X	X	X	
fetch	X		X	
fields		X	X	
file				X
filefactor				X
fileformat		X	X	
files		X	X	
filter	X		X	
finalize_fn			X	
first		X	X	

first_value	X			
float	X	X	X	
floor	X			
following		X	X	
for	X	X	X	
foreign	X		X	
format		X	X	
formatted		X	X	
frame_row	X		X	
free	X		X	
freetext				X
from	X	X	X	
full	X	X	X	
function	X	X	X	
functions		X	X	
fusion	X		X	
get	X		X	
global	X		X	
goto				X
grant	X	X	X	
group	X	X	X	
grouping	X		X	
groups	X		X	
hash		X	X	
having	X	X	X	
hold	X		X	
holdlock				X
hour	X			
hudiparquet			X	
iceberg			X ¹	
identity	X			X
if		X	X	
ignore		X	X	
ilike		X	X	

¹ Impala 4.0 and higher

import				
in	X	X	X	
incremental		X	X	
index				X
indicator	X		X	
init_fn			X	
initial	X		X	
inner	X	X	X	
inout	X		X	
inpath		X	X	
insensitive	X		X	
insert	X	X	X	
int	X	X	X	
integer	X	X	X	
intermediate		X	X	
intersect	X		X	
intersection	X		X	
interval	X	X	X	
into	X	X	X	
invalidate		X	X	
iregexp		X	X	
is	X	X	X	
join	X	X	X	
jsonfile			X	
json_array	X		X	
json_arrayagg	X		X	
json_exists	X		X	
json_object	X		X	
json_objectagg	X		X	
json_query	X		X	
json_table	X		X	
json_table_primitive	X		X	
json_value	X		X	
key				X
kill				X

kudu		X	X	
lag	X			
language	X			
large	X		X	
last		X	X	
last_value	X			
lateral	X		X	
lead	X			
leading	X		X	
left	X	X	X	
less				
lexical			X	
like	X	X	X	
like_regex	X		X	
limit		X	X	
lineno				X
lines		X	X	
listagg	X		X	
ln	X			
load		X	X	
local	X		X	
localtime	X			
localtimestamp	X		X	
location		X	X	
log	X			
log10	X		X	
lower	X			
macro				
map		X	X	
managedlocation			X	
match	X		X	
match_number	X		X	
match_recognize	X		X	
matches	X		X	
max	X			

member	X			
merge	X		X	
merge_fn			X	
metadata		X	X	
method	X		X	
min	X			
minus	X		X	
minute	X			
mod	X			
modifies	X		X	
module	X			
month	X			
more				
multiset	X		X	
national	X		X	
natural	X		X	
nchar	X		X	
nclob	X		X	
new	X			
no	X		X	
nocheck				X
non			X	
nonclustered				X
none	X		X	
norely			X	
normalize	X		X	
not	X	X	X	
novalidate			X	
nth_value	X		X	
ntile	X			
null	X	X	X	
nullif	X			X
nulls		X	X	
numeric	X		X	
occurrences_regex	X		X	

octet_length	X		X	
of	X		X	
off				X
offset	X	X	X	
offsets				X
old	X			
omit	X		X	
on	X	X	X	
one	X		X	
only	X		X	
open	X			X
optimize	X		X	
option				X
or	X	X	X	
orc			X	
order	X	X	X	
out	X		X	
outer	X	X	X	
over	X	X	X	
overlaps	X		X	
overlay	X		X	
overwrite		X	X	
parameter	X			
parquet		X	X	
parquetfile		X	X	
partialscan				
partition	X	X	X	
partitioned		X	X	
partitions		X	X	
pattern	X		X	
per	X		X	
percent	X		X	
percent_rank	X			
percentile_cont	X		X	
percentile_disc	X		X	

period	X			
pivot				X
plan				X
portion	X		X	
position	X		X	
position_regex	X		X	
power	X			
precedes	X		X	
preceding		X	X	
precision	X			X
prepare	X		X	
prepare_fn			X	
preserve				
primary	X	X	X	
print				X
proc				X
procedure	X		X	
produced		X	X	
ptf	X		X	
public				X
purge		X	X	
raiseerror				X
range	X	X	X	
rank	X			
rcfile		X	X	
read				X
reads	X		X	
readtext				X
real	X	X	X	
reconfigure				X
recover		X	X	
recursive	X		X	
reduce				
ref	X		X	
references	X		X	

referencing	X		X	
refresh		X	X	
regexp		X	X	
regr_avgx	X		X	
regr_avgy	X		X	
regr_count	X		X	
regr_intercept	X		X	
regr_r2	X		X	
regr_slope	X		X	
regr_sxx	X		X	
regr_sxy	X		X	
regr_syy	X		X	
release	X		X	
rely			X	
rename		X	X	
repeatable		X	X	
replace		X	X	
replication		X	X	
restore				X
restrict		X	X	
result	X			
return	X			X
returns	X	X	X	
revert				X
revoke	X	X	X	
right	X	X	X	
rlike		X	X	
role		X	X	
roles		X	X	
rollback	X		X	
rollup	X		X	
row	X	X	X	
row_number	X			
rowcount				X
rows	X	X	X	

rule				X
running	X		X	
rwstorage			X	
save				X
savepoint	X		X	
schema		X	X	
schemas		X	X	
scope	X		X	
scroll	X		X	
search	X		X	
second	X			
securityaudit				X
seek	X		X	
select	X	X	X	
selectivity			X	
semi		X	X	
sensitive	X		X	
sequencefile		X	X	
serdeproperties		X	X	
serialize_fn			X	
session_user	X			X
set	X	X	X	
sets	X		X	
setuser				X
show	X	X	X	
shutdown				X
similar	X		X	
sin	X			
sinh	X			
skip	X		X	
smallint	X	X	X	
some	X		X	
sort		X	X	
spec			X	
specific	X		X	

specificity	X		X	
sql	X			
sqlexception	X		X	
sqlstate	X		X	
sqlwarning	X		X	
sqrt	X			
start	X			
static	X		X	
statistics				X
stats		X	X	
stddev_pop	X			
stddev_samp	X			
storagehandler_uri			X	
stored		X	X	
straight_join			X	
string		X	X	
struct		X	X	
submultiset	X		X	
subset	X		X	
substring	X			
substring_regex	X		X	
succeeds	X		X	
sum	X			
symbol		X	X	
symmetric	X		X	
system	X			
system_time	X		X	
system_user	X		X	
system_version			X	
table	X	X	X	
tables		X	X	
tablesample	X	X	X	
tan	X			
tanh	X			
tblproperties		X	X	

terminated		X	X	
textfile		X	X	
textsize				X
then	X	X	X	
time	X			
timestamp	X	X	X	
timezone_hour	X		X	
timezone_minute	X		X	
tinyint		X	X	
to	X	X	X	
top				X
trailing	X		X	
tran				X
transform				
translate	X			
translate_regex	X		X	
translation	X		X	
treat	X		X	
trigger	X		X	
trim	X			
trim_array	X		X	
true	X	X	X	
truncate	X	X	X	
try_convert				X
unescape	X		X	
unbounded		X	X	
uncached		X	X	
union	X	X	X	
unique	X		X	
uniquejoin				
unknown	X	X	X	
unnest	X		X	
unpivot				X
unset			X	
update	X	X	X	

update_fn			X	
updatetext				X
upper	X			
upsert		X	X	
use		X	X	
user	X			X
user_defined_fn			X	
using	X	X	X	
utc_tmestamp				
validate	X		X	
value	X			
value_of	X		X	
values	X	X	X	
var_pop	X			
var_samp	X			
varbinary	X		X	
varchar	X	X	X	
varying	X		X	
versioning	X		X	
view		X	X	
views				
waitfor				X
when	X	X	X	
whenever	X		X	
where	X	X	X	
while				X
width_bucket	X		X	
window	X		X	
with	X	X	X	
within	X		X	
without	X		X	
writetext				X
year	X			
zorder			X	

Impala Frequently Asked Questions

This section lists frequently asked questions for Apache Impala, the interactive SQL engine for Hadoop.

This section is under construction.

Impala Release Notes

These release notes provide information on the [new features](#) and [known issues and limitations](#) for Impala versions up to Impala 3.4.x. For users upgrading from earlier Impala releases, or using Impala in combination with specific versions of other software, [Incompatible Changes and Limitations in Apache Impala](#) on page 867 lists any changes to file formats, SQL syntax, or software dependencies to take into account.

Once you are finished reviewing these release notes, for more information about using Impala, see [Impala Concepts and Architecture](#) on page 17.

New Features in Apache Impala

This release of Impala contains the following changes and enhancements from previous releases.

New Features in Impala 4.0

For the full list of issues closed in this release, including the issues marked as “new features” or “improvements”, see the [release notes](#) or [changelog](#) for Impala 4.0.

New Features in Impala 3.4

The following sections describe the noteworthy improvements made in Impala 3.4.

For the full list of issues closed in this release, see the [changelog for Impala 3.4](#).

Support for Hive Insert-Only Transactional Tables

Impala added the support to truncate insert-only transactional tables.

By default, Impala creates an insert-only transactional table when you issue the `CREATE TABLE` statement.

Use the Hive compaction to compact small files to improve the performance and scalability of metadata in transactional tables.

See [Impala Transactions](#) on page 213 for more information.

Server-side Spooling of Query Results

You can use the `SPOOL_QUERY_RESULTS` query option to control how query results are returned to the client.

By default, when a client fetches a set of query results, the next set of results are fetched in batches until all the result rows are produced. If a client issues a query without fetching all the results, the query fragments continue to hold on to the resources until the query is canceled and unregistered, potentially tying up resources and causing other queries to wait in admission control.

When the query result spooling feature is enabled, the result sets of queries are eagerly fetched and buffered until they are read by the client, and resources are freed up for other queries.

See [Spooling Impala Query Results](#) on page 804 for the new feature and the query options.

Cookie-based Authentication

Starting in this version, Impala supports cookies for authentication when clients connect via HiveServer2 over HTTP.

You can use the `--max_cookie_lifetime_s` startup flag to:

- Disable the use of cookies
- Control how long generated cookies are valid for

See [Impala Client Access](#) on page 788 for more information.

Object Ownership Support

Object ownership for tables, views, and databases is enabled by default in Impala. When you create a database, a table, or a view, as the owner of that object, you implicitly have the privileges on the object. The privileges that owners have are specified in Ranger on the special user, `{OWNER}`.

The `{OWNER}` user must be defined in Ranger for the object ownership privileges work in Impala.

See [Impala Authorization](#) on page 83 for details.

New Built-in Functions for Fuzzy Matching of Strings

Use the new Jaro or Jaro-Winkler functions to perform fuzzy matches on relatively short strings, e.g. to scrub user inputs of names against the records in the database.

- `JARO_DISTANCE`, `JARO_DST`
- `JARO_SIMILARITY`, `JARO_SIM`
- `JARO_WINKLER_DISTANCE`, `JW_DST`
- `JARO_WINKLER_SIMILARITY`, `JW_SIM`

See [Impala String Functions](#) on page 509 for details.

Capacity Quota for Scratch Disks

When configuring scratch space for intermediate files used in large sorts, joins, aggregations, or analytic function operations, use the `##scratch_dirs` startup flag to optionally specify a capacity quota per scratch directory, e.g., `##scratch_dirs=/dir1:5MB,/dir2`.

See [How Impala Works with Hadoop File Formats](#) on page 695 for details.

Query Option for Disabling HBase Row Estimation

During query plan generation, Impala samples underlying HBase tables to estimate row count and row size, but the sampling process can negatively impact the planning time. To alleviate the issue, when the HBase table stats do not change much in a short time, disable the sampling with the `DISABLE_HBASE_NUM_ROWS_ESTIMATE` query option so that the Impala planner falls back to using Hive Metastore (HMS) table stats instead.

See [DISABLE_HBASE_NUM_ROWS_ESTIMATE Query Option](#) on page 354.

Query Option for Controlling Size of Parquet Splits on Non-block Stores

To optimize query performance, Impala planner uses the value of the `fs.s3a.block.size` startup flag when calculating the split size on non-block based stores, e.g. S3, ADLS, etc. Starting in this release, Impala planner uses the `PARQUET_OBJECT_STORE_SPLIT_SIZE` query option to get the Parquet file format specific split size.

For Parquet files, the `fs.s3a.block.size` startup flag is no longer used.

The default value of the `PARQUET_OBJECT_STORE_SPLIT_SIZE` query option is 256 MB.

See [Using Impala with Amazon S3 Object Store](#) on page 769 for tuning Impala query performance for S3.

Query Profile Exported to JSON

On the Query Details page of Impala Daemon Web UI, you have a new option, in addition to the existing Thrift and Text formats, to export the query profile output in the JSON format.

See [Impala Web User Interface for Debugging](#) on page 810 for generating JSON query profile outputs in Web UI.

DATE Data Type Supported in Avro Tables

You can now use the DATE data type to query date values from Avro tables.

See [Using the Avro File Format with Impala Tables](#) on page 722 for details.

Primary Key and Foreign Key Constraints

This release adds support for primary and foreign key constraints, but in this release the constraints are advisory and intended for estimating cardinality during query planning in a future release. There is no attempt to enforce constraints. See [CREATE TABLE Statement](#) on page 248 for details.

Enhanced External Kudu Table

By default HMS implicitly translates internal Kudu tables to external Kudu tables with the 'external.table.purge' property set to true. These tables behave similar to internal tables. You can explicitly create such external Kudu tables. See [CREATE TABLE Statement](#) on page 248 for details.

Ranger Column Masking

This release supports Ranger column masking, which hides sensitive columnar data in Impala query output. For example, you can define a policy that reveals only the first or last four characters of column data. Column masking is enabled by default. See [Ranger Column Masking](#) on page 89 for details.

BROADCAST_BYTES_LIMIT query option

You can set the default limit for the size of the broadcast input. Such a limit can prevent possible performance problems.

Experimental Support for Apache Hudi

In this release, you can use Read Optimized Queries on Hudi tables. See [Using the Hudi File Format](#) on page 727 for details.

ORC Reads Enabled by Default

Impala stability and performance have been improved. Consequently, ORC reads are now enabled in Impala by default. To disable, set `--enable_orc_scanner` to `false` when starting the cluster. See [Using the ORC File Format with Impala Tables](#) on page 719 for details.

Support for ZSTD and DEFLATE

This release supports ZSTD and DEFLATE compression codecs for text files. See [Using bzip2, deflate, gzip, Snappy, or zstd Text Files](#) on page 704 for details.

New Features in Impala 3.3

The following sections describe the noteworthy improvements made in Impala 3.3.

For the full list of issues closed in this release, see the [changelog for Impala 3.3](#).

Increased Compatibility with Apache Projects

Impala is integrate with the following components:

- Apache Ranger: Use Apache Ranger to manage authorization in Impala. See [Impala Authorization](#) for details.
- Apache Atlas: Use Apache Atlas to manage data governance in Impala.
- Hive 3

Parquet Page Index

To improve performance when using Parquet files, Impala can now write page indexes in Parquet files and use those indexes to skip pages for the faster scan.

See [Query Performance for Impala Parquet Tables](#) on page 707 for details.

The Remote File Handle Cache Supports S3

Impala can now cache remote HDFS file handles when the tables that store their data in Amazon S3 cloud storage.

See [Scalability Considerations for File Handle Caching](#) on page 664 for the information on remote file handle cache.

Support for Kudu Integrated with Hive Metastore

In Impala 3.3 and Kudu 1.10, Kudu is integrated with Hive Metastore (HMS), and from Impala, you can create, update, delete, and query the tables in the Kudu services integrated with HMS.

See [Using Kudu with Impala](#) for information on using Kudu tables in Impala.

Zstd Compression for Parquet files

Zstandard (Zstd) is a real-time compression algorithm offering a tradeoff between speed and ratio of compression. Compression levels from 1 up to 22 are supported. The lower the level, the faster the speed at the cost of compression ratio.

Lz4 Compression for Parquet files

Lz4 is a lossless compression algorithm providing extremely fast and scalable compression and decompression.

Data Cache for Remote Reads

To improve performance on multi-cluster HDFS environments as well as on object store environments, Impala now caches data for non-local reads (e.g. S3, ABFS, ADLS) on local storage.

The data cache is enabled with the `--data_cache startup` flag.

See [Impala Remote Data Cache](#) for the information and steps to enable remote data cache.

Metadata Performance Improvements

The following features to improve metadata performance are enabled by default in this release:

- Incremental stats are now compressed in memory in `catalogd`, reducing memory footprint in `catalogd`.
- `impaladcoordinators` fetch incremental stats from `catalogd` on-demand, reducing the memory footprint and the network requirements for broadcasting metadata.
- Time-based and memory-based automatic invalidation of metadata to keep the size of metadata bounded and to reduce the chances of `catalogdcache` running out of memory.
- Automatic invalidation of metadata

With automatic metadata management enabled, you no longer have to issue `INVALIDATE / REFRESH` in a number of conditions.

In Impala 3.3, the following additional event in Hive Metastore can trigger automatic `INVALIDATE / REFRESH` of Metadata:

- `INSERT` into tables and partitions from Impala or from Spark on the same or multiple cluster configuration

See [Metadata Management](#) on page 670 for the information on the above features.

Scalable Pool Configuration in Admission Controller

To offer more dynamic and flexible resource management, Impala supports the new configuration parameters that scale with the number of hosts in the resource pool. You can use the parameters to control the number of running queries, queued queries, and maximum amount of memory allocated for Impala resource pools. See [Admission Control and Query Queuing](#) on page 675 for the information about the new parameters and using them for admission control.

Query Profile

The following information was added to the Query Profile output for better monitoring and troubleshooting of query performance.

- Network I/O throughput
- System disk I/O throughput

See [Impala Query Profile](#) for generating and reading query profile.

DATE Data Type and Functions

You can use the new the DATE type to describe a particular year/month/day, in the form YYYY-MM-DD.

This initial DATE type support the TEXT, Parquet, and HBASE file formats.

The support of DATE data type includes the following features:

- DATE type column as a partitioning key column
- DATE literal
- Implicit casting between DATE and other types: STRING and TIMESTAMP
- Most of the built-in functions for TIMESTAMP now allow the DATE type arguments, as well.

See [DATE Data Type](#) on page 110 and [Impala Date and Time Functions](#) on page 478 for using the DATE type.

Support Hive Insert-Only Transactional Tables

Impala added the support to create, drop, query, and insert into the insert-only type of transactional tables.

See [Impala Transactions](#) for details.

HiveServer2 HTTP Connection for Clients

Now client applications can connect to Impala over HTTP via HiveServer2 with the option to use the Kerberos SPNEGO and LDAP for authentication. See [Impala Clients](#) for details.

Default File Format Changed to Parquet

When you create a table, the default format for that table data is now Parquet.

For backward compatibility, you can use the `DEFAULT_FILE_FORMAT` query option to set the default file format to the previous default, text, or other formats.

Built-in Function to Process JSON Objects

The `GET_JSON_OBJECT ()` function extracts JSON object from a string based on the path specified and returns the extracted JSON object.

See [Impala Miscellaneous Functions](#). for details.

Ubuntu 18.04

This version of Impala is certified to run on Ubuntu 18.04.

New Features in Impala 3.2

The following sections describe the noteworthy improvements made in Impala 3.2.

For the full list of issues closed in this release, see the [changelog for Impala 3.2](#).

Multi-cluster Support

- Remote File Handle Cache

Impala can now cache remote HDFS file handles when the `cache_remote_file_handles` `impalad` flag is set to `true`. This feature does not apply to non-HDFS tables, such as Kudu or HBase tables, and does not apply to the tables that store their data on cloud services, such as S3 or ADLS. See [Scalability Considerations](#) for file handle caching in Impala.

Enhancements in Resource Management and Admission Control

- Admission Debug page is available in [Impala Daemon \(impalad\) web UI](#) at `\admission` and provides the following information about Impala resource pools:
 - Pool configuration
 - Relevant pool stats
 - Queued queries in order of being queued (local to the coordinator)
 - Running queries (local to this coordinator)
 - Histogram of the distribution of peak memory usage by admitted queries
- A new query option, [NUM_ROWS_PRODUCED_LIMIT](#), was added to limit the number of rows returned from queries.

Impala will cancel a query if the query produces more rows than the limit specified by this query option. The limit applies only when the results are returned to a client, e.g. for a `SELECT` query, but not an `INSERT` query. This query option is a guardrail against users accidentally submitting queries that return a large number of rows.

Metadata Performance Improvements

- [Automatic Metadata Sync using Hive Metastore Notification Events](#)

When enabled, the `catalogd` polls Hive Metastore (HMS) notifications events at a configurable interval and syncs with HMS. You can use the new web UI pages of the `catalogd` to check the state of the automatic invalidate event processor.

Note: This is a preview feature in Impala 3.2.

Compatibility and Usability Enhancements

- Impala can now read the `TIMESTAMP_MILLIS` and `TIMESTAMP_MICROS` Parquet types. See [Using Parquet File Format for Impala Tables](#) for the Parquet support in Impala.
- Impala can now read the complex types in ORC such as `ARRAY`, `STRUCT`, and `MAP`. See [Using ORC File Format for Impala Tables](#) for the ORC support in Impala.
- The [LEVENSHTEIN](#) string function is supported.

The function returns the Levenshtein distance between two input strings, the minimum number of single-character edits required to transform one string to other.

- The `IF NOT EXISTS` clause is supported in the [ALTER TABLE](#) statement.
- The new [DEFAULT_FILE_FORMAT](#) query option allows you to set the default table file format. This removes the need for the `STORED AS <format>` clause. Set this option if you prefer a value that is not `TEXT`. The supported formats are:
 - `TEXT`

- RC_FILE
- SEQUENCE_FILE
- AVRO
- PARQUET
- KUDU
- ORC
- The extended or verbose [EXPLAIN](#) output includes the following new information for queries:
 - The text of the analyzed query that may have been rewritten to include various optimizations and implicit casts.
 - The implicit casts and literals shown with the actual types.
- CPU resource utilization (user, system, iowait) metrics were added to the [Impala profile](#) output.

Security Enhancement

- The [REFRESH AUTHORIZATION](#) statement was implemented for refreshing authorization data.

New Features in Impala 3.1

For the full list of issues closed in this release, including the issues marked as “new features” or “improvements”, see the [changelog for Impala 3.1](#).

New Features in Impala 3.0

For the full list of issues closed in this release, including the issues marked as “new features” or “improvements”, see the [changelog for Impala 3.0](#).

New Features in Impala 2.12

For the full list of issues closed in this release, including the issues marked as “new features” or “improvements”, see the [changelog for Impala 2.12](#).

New Features in Impala 2.11

For the full list of issues closed in this release, including the issues marked as “new features” or “improvements”, see the [changelog for Impala 2.11](#).

New Features in Impala 2.10

For the full list of issues closed in this release, including the issues marked as “new features” or “improvements”, see the [changelog for Impala 2.10](#).

New Features in Impala 2.9

For the full list of issues closed in this release, including the issues marked as “new features” or “improvements”, see the [changelog for Impala 2.9](#).

The following are some of the most significant new features in this release:

- A new function, `replace()`, which is faster than `regexp_replace()` for simple string substitutions. See [Impala String Functions](#) on page 509 for details.
- Startup flags for the `impalad` daemon, `is_executor` and `is_coordinator`, let you divide the work on a large, busy cluster between a small number of hosts acting as query coordinators, and a larger number of hosts acting as query executors. By default, each host can act in both roles, potentially introducing bottlenecks during heavily concurrent workloads. See [How to Configure Impala with Dedicated Coordinators](#) on page 666 for details.

New Features in Impala 2.8

- Performance and scalability improvements:
 - The `COMPUTE STATS` statement can take advantage of multithreading.
 - Improved scalability for highly concurrent loads by reducing the possibility of TCP/IP timeouts. A configuration setting, `accepted_cnxn_queue_depth`, can be adjusted upwards to avoid this type of timeout on large clusters.
 - Several performance improvements were made to the mechanism for generating native code:
 - Some queries involving analytic functions can take better advantage of native code generation.
 - Modules produced during intermediate code generation are organized to be easier to cache and reuse during the lifetime of a long-running or complicated query.
 - The `COMPUTE STATS` statement is more efficient (less time for the codegen phase) for tables with a large number of columns, especially for tables containing `TIMESTAMP` columns.
 - The logic for determining whether or not to use a runtime filter is more reliable, and the evaluation process itself is faster because of native code generation.
 - The `MT_DOP` query option enables multithreading for a number of Impala operations. `COMPUTE STATS` statements for Parquet tables use a default of `MT_DOP=4` to improve the intra-node parallelism and CPU efficiency of this data-intensive operation.
 - The `COMPUTE STATS` statement is more efficient (less time for the codegen phase) for tables with a large number of columns.
 - A new hint, `CLUSTERED`, allows Impala `INSERT` operations on a Parquet table that use dynamic partitioning to process a high number of partitions in a single statement. The data is ordered based on the partition key columns, and each partition is only written by a single host, reducing the amount of memory needed to buffer Parquet data while the data blocks are being constructed.
 - The new configuration setting `inc_stats_size_limit_bytes` lets you reduce the load on the catalog server when running the `COMPUTE INCREMENTAL STATS` statement for very large tables.
 - Impala folds many constant expressions within query statements, rather than evaluating them for each row. This optimization is especially useful when using functions to manipulate and format `TIMESTAMP` values, such as the result of an expression such as `to_date(now() - interval 1 day)`.
 - Parsing of complicated expressions is faster. This speedup is especially useful for queries containing large `CASE` expressions.
 - Evaluation is faster for `IN` operators with many constant arguments. The same performance improvement applies to other functions with many constant arguments.
 - Impala optimizes identical comparison operators within multiple `OR` blocks.
 - The reporting for wall-clock times and total CPU time in profile output is more accurate.
 - A new query option, `SCRATCH_LIMIT`, lets you restrict the amount of space used when a query exceeds the memory limit and activates the “spill to disk” mechanism. This option helps to avoid runaway queries or make queries “fail fast” if they require more memory than anticipated. You can prevent runaway queries from using excessive amounts of spill space, without restarting the cluster to turn the spilling feature off entirely. See [SCRATCH_LIMIT Query Option](#) on page 391 for details.
- Integration with Apache Kudu:
 - The experimental Impala support for the Kudu storage layer has been folded into the main Impala development branch. Impala can now directly access Kudu tables, opening up new capabilities such as enhanced DML operations and continuous ingestion.
 - The `DELETE` statement is a flexible way to remove data from a Kudu table. Previously, removing data from an Impala table involved removing or rewriting the underlying data files, dropping entire partitions, or rewriting the entire table. This Impala statement only works for Kudu tables.
 - The `UPDATE` statement is a flexible way to modify data within a Kudu table. Previously, updating data in an Impala table involved replacing the underlying data files, dropping entire partitions, or rewriting the entire table. This Impala statement only works for Kudu tables.
 - The `UPSERT` statement is a flexible way to ingest, modify, or both data within a Kudu table. Previously, ingesting data that might contain duplicates involved an inefficient multi-stage operation, and there was

no built-in protection against duplicate data. The UPSERT statement, in combination with the primary key designation for Kudu tables, lets you add or replace rows in a single operation, and automatically avoids creating any duplicate data.

- The CREATE TABLE statement gains some new clauses that are specific to Kudu tables: PARTITION BY, PARTITIONS, STORED AS KUDU, and column attributes PRIMARY KEY, NULL and NOT NULL, ENCODING, COMPRESSION, DEFAULT, and BLOCK_SIZE. These clauses replace the explicit TBLPROPERTIES settings that were required in the early experimental phases of integration between Impala and Kudu.
- The ALTER TABLE statement can change certain attributes of Kudu tables. You can add, drop, or rename columns. You can add or drop range partitions. You can change the TBLPROPERTIES value to rename or point to a different underlying Kudu table, independently from the Impala table name in the metastore database. You cannot change the data type of an existing column in a Kudu table.
- The SHOW PARTITIONS statement displays information about the distribution of data between partitions in Kudu tables. A new variation, SHOW RANGE PARTITIONS, displays information about the Kudu-specific partitions that apply across ranges of key values.
- Not all Impala data types are supported in Kudu tables. In particular, currently the Impala TIMESTAMP type is not allowed in a Kudu table. Impala does not recognize the UNIXTIME_MICROS Kudu type when it is present in a Kudu table. (These two representations of date/time data use different units and are not directly compatible.) You cannot create columns of type TIMESTAMP, DECIMAL, VARCHAR, or CHAR within a Kudu table. Within a query, you can cast values in a result set to these types. Certain types, such as BOOLEAN, cannot be used as primary key columns.
- Currently, Kudu tables are not interchangeable between Impala and Hive the way other kinds of Impala tables are. Although the metadata for Kudu tables is stored in the metastore database, currently Hive cannot access Kudu tables.
- The INSERT statement works for Kudu tables. The organization of the Kudu data makes it more efficient than with HDFS-backed tables to insert data in small batches, such as with the INSERT . . . VALUES syntax.
- Some audit data is recorded for data governance purposes. All UPDATE, DELETE, and UPSERT statements are characterized as INSERT operations in the audit log. Currently, lineage metadata is not generated for UPDATE and DELETE operations on Kudu tables.
- Currently, Kudu tables have limited support for Sentry:
 - Access to Kudu tables must be granted to roles as usual.
 - Currently, access to a Kudu table through Sentry is “all or nothing”. You cannot enforce finer-grained permissions such as at the column level, or permissions on certain operations such as INSERT.
 - Only users with ALL privileges on SERVER can create external Kudu tables.

Because non-SQL APIs can access Kudu data without going through Sentry authorization, currently the Sentry support is considered preliminary.

- Equality and IN predicates in Impala queries are pushed to Kudu and evaluated efficiently by the Kudu storage layer.
- **Security:**
 - Impala can take advantage of the S3 encrypted credential store, to avoid exposing the secret key when accessing data stored on S3.
- [\[IMPALA-1654\]](#) Several kinds of DDL operations can now work on a range of partitions. The partitions can be specified using operators such as <, >=, and != rather than just an equality predicate applying to a single partition. This new feature extends the syntax of several clauses of the ALTER TABLE statement (DROP PARTITION, SET [UN]CACHED, SET FILEFORMAT | SERDEPROPERTIES | TBLPROPERTIES), the SHOW FILES statement, and the COMPUTE INCREMENTAL STATS statement. It does not apply to statements that are defined to only apply to a single partition, such as LOAD DATA, ALTER TABLE . . . ADD PARTITION, SET LOCATION, and INSERT with a static partitioning clause.
- The instr() function has optional second and third arguments, representing the character to position to begin searching for the substring, and the Nth occurrence of the substring to find.
- Improved error handling for malformed Avro data. In particular, incorrect precision or scale for DECIMAL types is now handled.
- Impala debug web UI:

- In addition to “inflight” and “finished” queries, the web UI now also includes a section for “queued” queries.
- The `/sessions` tab now clarifies how many of the displayed sections are active, and lets you sort by **Expired** status to distinguish active sessions from expired ones.
- Improved stability when DDL operations such as `CREATE DATABASE` or `DROP DATABASE` are run in Hive at the same time as an Impala `INVALIDATE METADATA` statement.
- The “out of memory” error report was made more user-friendly, with additional diagnostic information to help identify the spot where the memory limit was exceeded.
- Improved disk space usage for Java-based UDFs. Temporary copies of the associated JAR files are removed when no longer needed, so that they do not accumulate across restarts of the `catalogd` daemon and potentially cause an out-of-space condition. These temporary files are also created in the directory specified by the `local_library_dir` configuration setting, so that the storage for these temporary files can be independent from any capacity limits on the `/tmp` filesystem.

New Features in Impala 2.7

- Performance improvements:
 - [IMPALA-3206] Speedup for queries against `DECIMAL` columns in Avro tables. The code that parses `DECIMAL` values from Avro now uses native code generation.
 - [IMPALA-3674] Improved efficiency in LLVM code generation can reduce codegen time, especially for short queries.
 - [IMPALA-2979] Improvements to scheduling on worker nodes, enabled by the `REPLICA_PREFERENCE` query option. See [REPLICA_PREFERENCE Query Option \(Impala 2.7 or higher only\)](#) on page 386 for details.
- [IMPALA-1683] The `REFRESH` statement can be applied to a single partition, rather than the entire table. See [REFRESH Statement](#) on page 312 and [Refreshing a Single Partition](#) on page 687 for details.
- Improvements to the Impala web user interface:
 - [IMPALA-2767] You can now force a session to expire by clicking a link in the web UI, on the `/sessions` tab.
 - [IMPALA-3715] The `/memz` tab includes more information about Impala memory usage.
 - [IMPALA-3716] The **Details** page for a query now includes a **Memory** tab.
- [IMPALA-3499] Scalability improvements to the catalog server. Impala handles internal communication more efficiently for tables with large numbers of columns and partitions, where the size of the metadata exceeds 2 GiB.
- [IMPALA-3677] You can send a `SIGUSR1` signal to any Impala-related daemon to write a Breakpad minidump. For advanced troubleshooting, you can now produce a minidump without triggering a crash. See [Breakpad Minidumps for Impala \(Impala 2.6 or higher only\)](#) on page 817 for details about the Breakpad minidump feature.
- [IMPALA-3687] The schema reconciliation rules for Avro tables have changed slightly for `CHAR` and `VARCHAR` columns. Now, if the definition of such a column is changed in the Avro schema file, the column retains its `CHAR` or `VARCHAR` type as specified in the SQL definition, but the column name and comment from the Avro schema file take precedence. See [Creating Avro Tables](#) on page 722 for details about column definitions in Avro tables.
- [IMPALA-3575] Some network operations now have additional timeout and retry settings. The extra configuration helps avoid failed queries for transient network problems, to avoid hangs when a sender or receiver fails in the middle of a network transmission, and to make cancellation requests more reliable despite network issues.

New Features in Impala 2.6

- Improvements to Impala support for the Amazon S3 filesystem:
 - Impala can now write to S3 tables through the `INSERT` or `LOAD DATA` statements. See [Using Impala with Amazon S3 Object Store](#) on page 769 for general information about using Impala with S3.
 - A new query option, `S3_SKIP_INSERT_STAGING`, lets you trade off between fast `INSERT` performance and slower `INSERTs` that are more consistent if a problem occurs during the statement. The new behavior is enabled by default. See [S3_SKIP_INSERT_STAGING Query Option \(Impala 2.6 or higher only\)](#) on page 390 for details about this option.
- Performance improvements for the runtime filtering feature:

- The default for the `RUNTIME_FILTER_MODE` query option is changed to `GLOBAL` (the highest setting). See [RUNTIME_FILTER_MODE Query Option \(Impala 2.5 or higher only\)](#) on page 389 for details about this option.
- The `RUNTIME_BLOOM_FILTER_SIZE` setting is now only used as a fallback if statistics are not available; otherwise, Impala uses the statistics to estimate the appropriate size to use for each filter. See [RUNTIME_BLOOM_FILTER_SIZE Query Option \(Impala 2.5 or higher only\)](#) on page 387 for details about this option.
- New query options `RUNTIME_FILTER_MIN_SIZE` and `RUNTIME_FILTER_MAX_SIZE` let you fine-tune the sizes of the Bloom filter structures used for runtime filtering. If the filter size derived from Impala internal estimates or from the `RUNTIME_FILTER_BLOOM_SIZE` falls outside the size range specified by these options, any too-small filter size is adjusted to the minimum, and any too-large filter size is adjusted to the maximum. See [RUNTIME_FILTER_MIN_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388 and [RUNTIME_FILTER_MAX_SIZE Query Option \(Impala 2.6 or higher only\)](#) on page 388 for details about these options.
- Runtime filter propagation now applies to all the operands of `UNION` and `UNION ALL` operators.
- Runtime filters can now be produced during join queries even when the join processing activates the spill-to-disk mechanism.

See [Runtime Filtering for Impala Queries \(Impala 2.5 or higher only\)](#) on page 641 for general information about the runtime filtering feature.

- Admission control and dynamic resource pools are enabled by default. See [Admission Control and Query Queuing](#) on page 675 for details about admission control.
- Impala can now manually set column statistics, using the `ALTER TABLE` statement with a `SET COLUMN STATS` clause. See [#unique_814](#) for details.
- Impala can now write lightweight “minidump” files, rather than large core files, to save diagnostic information when any of the Impala-related daemons crash. This feature uses the open source `breakpad` framework. See [Breakpad Minidumps for Impala \(Impala 2.6 or higher only\)](#) on page 817 for details.
- New query options improve interoperability with Parquet files:
 - The `PARQUET_FALLBACK_SCHEMA_RESOLUTION` query option lets Impala locate columns within Parquet files based on column name rather than ordinal position. This enhancement improves interoperability with applications that write Parquet files with a different order or subset of columns than are used in the Impala table. See [PARQUET_FALLBACK_SCHEMA_RESOLUTION Query Option \(Impala 2.6 or higher only\)](#) on page 382 for details.
 - The `PARQUET_ANNOTATE_STRINGS_UTF8` query option makes Impala include the UTF-8 annotation metadata for `STRING`, `CHAR`, and `VARCHAR` columns in Parquet files created by `INSERT` or `CREATE TABLE AS SELECT` statements. See [PARQUET_ANNOTATE_STRINGS_UTF8 Query Option \(Impala 2.6 or higher only\)](#) on page 379 for details.

See [Using the Parquet File Format with Impala Tables](#) on page 705 for general information about working with Parquet files.

- Improvements to security and reduction in overhead for secure clusters:
 - Overall performance improvements for secure clusters. (TPC-H queries on a secure cluster were benchmarked at roughly 3x as fast as the previous release.)
 - Impala now recognizes the `auth_to_local` setting, specified through the HDFS configuration setting `hadoop.security.auth_to_local`. This feature is disabled by default; to enable it, specify `--load_auth_to_local_rules=true` in the `impalad` configuration settings. See [Mapping Kerberos Principals to Short Names for Impala](#) on page 93 for details.
 - Timing improvements in the mechanism for the `impalad` daemon to acquire Kerberos tickets. This feature spreads out the overhead on the KDC during Impala startup, especially for large clusters.
 - For Kerberized clusters, the Catalog service now uses the Kerberos principal instead of the operating system user that runs the `catalogd` daemon. This eliminates the requirement to configure a `hadoop.user.group.static.mapping.overrides` setting to put the OS user into the Sentry administrative group, on clusters where the principal and the OS user name for this user are different.

- Overall performance improvements for join queries, by using a prefetching mechanism while building the in-memory hash table to evaluate join predicates. See [PREFETCH_MODE Query Option \(Impala 2.6 or higher only\)](#) on page 385 for the query option to control this optimization.
- The `impala-shell` interpreter has a new command, `SOURCE`, that lets you run a set of SQL statements or other `impala-shell` commands stored in a file. You can run additional `SOURCE` commands from inside a file, to set up flexible sequences of statements for use cases such as schema setup, ETL, or reporting. See [impala-shell Command Reference](#) on page 799 for details and [Running Commands and SQL Statements in impala-shell](#) on page 798 for examples.
- The `millisecond()` built-in function lets you extract the fractional seconds part of a `TIMESTAMP` value. See [Impala Date and Time Functions](#) on page 478 for details.
- If an Avro table is created without column definitions in the `CREATE TABLE` statement, and columns are later added through `ALTER TABLE`, the resulting table is now queryable. Missing values from the newly added columns now default to `NULL`. See [Using the Avro File Format with Impala Tables](#) on page 722 for general details about working with Avro files.
- The mechanism for interpreting `DECIMAL` literals is improved, no longer going through an intermediate conversion step to `DOUBLE`:
 - Casting a `DECIMAL` value to `TIMESTAMP DOUBLE` produces a more precise value for the `TIMESTAMP` than formerly.
 - Certain function calls involving `DECIMAL` literals now succeed, when formerly they failed due to lack of a function signature with a `DOUBLE` argument.
 - Faster runtime performance for `DECIMAL` constant values, through improved native code generation for all combinations of precision and scale.

See [DECIMAL Data Type \(Impala 3.0 or higher only\)](#) on page 111 for details about the `DECIMAL` type.

- Improved type accuracy for `CASE` return values. If all `WHEN` clauses of the `CASE` expression are of `CHAR` type, the final result is also `CHAR` instead of being converted to `STRING`. See [Impala Conditional Functions](#) on page 502 for details about the `CASE` function.
- Uncorrelated queries using the `NOT EXISTS` operator are now supported. Formerly, the `NOT EXISTS` operator was only available for correlated subqueries.
- Improved performance for reading Parquet files.
- Improved performance for *top-N* queries, that is, those including both `ORDER BY` and `LIMIT` clauses.
- Impala optionally skips an arbitrary number of header lines from text input files on HDFS based on the `skip.header.line.count` value in the `TBLPROPERTIES` field of the table metadata. See [Data Files for Text Tables](#) on page 699 for details.
- Trailing comments are now allowed in queries processed by the `impala-shell` options `-q` and `-f`.
- Impala can run `COUNT` queries for RCFile tables that include complex type columns. See [Complex Types \(Impala 2.3 or higher only\)](#) on page 142 for general information about working with complex types, and [ARRAY Complex Type \(Impala 2.3 or higher only\)](#) on page 102, [MAP Complex Type \(Impala 2.3 or higher only\)](#) on page 119, and [STRUCT Complex Type \(Impala 2.3 or higher only\)](#) on page 127 for syntax details of each type.

New Features in Impala 2.5

- **Dynamic partition pruning.** When a query refers to a partition key column in a `WHERE` clause, and the exact set of column values are not known until the query is executed, Impala evaluates the predicate and skips the I/O for entire partitions that are not needed. For example, if a table was partitioned by year, Impala would apply this technique to a query such as `SELECT c1 FROM partitioned_table WHERE year = (SELECT MAX(year) FROM other_table)`. See [Dynamic Partition Pruning](#) on page 689 for details.

The dynamic partition pruning optimization technique lets Impala avoid reading data files from partitions that are not part of the result set, even when that determination cannot be made in advance. This technique is especially valuable when performing join queries involving partitioned tables. For example, if a join query includes an `ON` clause and a `WHERE` clause that refer to the same columns, the query can find the set of column values that match the `WHERE` clause, and only scan the associated partitions when evaluating the `ON` clause.

Dynamic partition pruning is controlled by the same settings as the runtime filtering feature. By default, this feature is enabled at a medium level, because the maximum setting can use slightly more memory for queries than in previous releases. To fully enable this feature, set the query option `RUNTIME_FILTER_MODE=GLOBAL`.

- Runtime filtering. This is a wide-ranging set of optimizations that are especially valuable for join queries. Using the same technique as with dynamic partition pruning, Impala uses the predicates from `WHERE` and `ON` clauses to determine the subset of column values from one of the joined tables could possibly be part of the result set. Impala sends a compact representation of the filter condition to the hosts in the cluster, instead of the full set of values or the entire table.

By default, this feature is enabled at a medium level, because the maximum setting can use slightly more memory for queries than in previous releases. To fully enable this feature, set the query option `RUNTIME_FILTER_MODE=GLOBAL`.

This feature involves some new query options: [RUNTIME_FILTER_MODE](#), [MAX_NUM_RUNTIME_FILTERS](#), [RUNTIME_BLOOM_FILTER_SIZE](#), [RUNTIME_FILTER_WAIT_TIME_MS](#), and [DISABLE_ROW_RUNTIME_FILTERING](#).

- More efficient use of the HDFS caching feature, to avoid hotspots and bottlenecks that could occur if heavily used cached data blocks were always processed by the same host. By default, Impala now randomizes which host processes each cached HDFS data block, when cached replicas are available on multiple hosts. (Remember to use the `WITH REPLICATION` clause with the `CREATE TABLE` or `ALTER TABLE` statement when enabling HDFS caching for a table or partition, to cache the same data blocks across multiple hosts.) The new query option `SCHEDULE_RANDOM_REPLICA` lets you fine-tune the interaction with HDFS caching even more.
- The `TRUNCATE TABLE` statement now accepts an `IF EXISTS` clause, making `TRUNCATE TABLE` easier to use in setup or ETL scripts where the table might or might not exist.
- Improved performance and reliability for the `DECIMAL` data type:
 - Using `DECIMAL` values in a `GROUP BY` clause now triggers the native code generation optimization, speeding up queries that group by values such as prices.
 - Checking for overflow in `DECIMAL` multiplication is now substantially faster, making `DECIMAL` a more practical data type in some use cases where formerly `DECIMAL` was much slower than `FLOAT` or `DOUBLE`.
 - Multiplying a mixture of `DECIMAL` and `FLOAT` or `DOUBLE` values now returns the `DOUBLE` rather than `DECIMAL`. This change avoids some cases where an intermediate value would underflow or overflow and become `NULL` unexpectedly.
- For UDFs written in Java, or Hive UDFs reused for Impala, Impala now allows parameters and return values to be primitive types. Formerly, these things were required to be one of the “Writable” object types.
- Performance improvements for HDFS I/O. Impala now caches HDFS file handles to avoid the overhead of repeatedly opening the same file.
- Performance improvements for queries involving nested complex types. Certain basic query types, such as counting the elements of a complex column, now use an optimized code path.
- Improvements to the memory reservation mechanism for the Impala admission control feature. You can specify more settings, such as the timeout period and maximum aggregate memory used, for each resource pool instead of globally for the Impala instance. The default limit for concurrent queries (the **max requests** setting) is now unlimited instead of 200.
- Performance improvements related to code generation. Even in queries where code generation is not performed for some phases of execution (such as reading data from Parquet tables), Impala can still use code generation in other parts of the query, such as evaluating functions in the `WHERE` clause.
- Performance improvements for queries using aggregation functions on high-cardinality columns. Formerly, Impala could do unnecessary extra work to produce intermediate results for operations such as `DISTINCT` or `GROUP BY` on columns that were unique or had few duplicate values. Now, Impala decides at run time whether it is more efficient to do an initial aggregation phase and pass along a smaller set of intermediate data, or to pass raw intermediate data back to next phase of query processing to be aggregated there. This feature is known as *streaming pre-aggregation*. In case of performance regression, this feature can be turned off using the `DISABLE_STREAMING_PREAGGREGATIONS` query option.
- Spill-to-disk feature now always recommended. In earlier releases, the spill-to-disk feature could be turned off using a pair of configuration settings, `enable_partitioned_aggregation=false` and

`enable_partitioned_hash_join=false`. The latest improvements in the spill-to-disk mechanism, and related features that interact with it, make this feature robust enough that disabling it is now no longer needed or supported. In particular, some new features in Impala 2.5 and higher do not work when the spill-to-disk feature is disabled.

- Improvements to scripting capability for the `impala-shell` command, through user-specified substitution variables that can appear in statements processed by `impala-shell`:
 - The `--var` command-line option lets you pass key-value pairs to `impala-shell`. The shell can substitute the values into queries before executing them, where the query text contains the notation `${var:varname}`. For example, you might prepare a SQL file containing a set of DDL statements and queries containing variables for database and table names, and then pass the applicable names as part of the `impala-shell -f filename` command.
 - The `SET` and `UNSET` commands within the `impala-shell` interpreter now work with user-specified substitution variables, as well as the built-in query options. The two kinds of variables are divided in the `SET` output. As with variables defined by the `--var` command-line option, you refer to the user-specified substitution variables in queries by using the notation `${var:varname}` in the query text. Because the substitution variables are processed by `impala-shell` instead of the `impalad` backend, you cannot define your own substitution variables through the `SET` statement in a JDBC or ODBC application.
- Performance improvements for query startup. Impala better parallelizes certain work when coordinating plan distribution between `impalad` instances, which improves startup time for queries involving tables with many partitions on large clusters, or complicated queries with many plan fragments.
- Performance and scalability improvements for tables with many partitions. The memory requirements on the coordinator node are reduced, making it substantially faster and less resource-intensive to do joins involving several tables with thousands of partitions each.
- Whitelisting for access to internal APIs. For applications that need direct access to Impala APIs, without going through the HiveServer2 or Beeswax interfaces, you can specify a list of Kerberos users who are allowed to call those APIs. By default, the `impala` and `hdfs` users are the only ones authorized for this kind of access. Any users not explicitly authorized through the `internal_principals_whitelist` configuration setting are blocked from accessing the APIs. This setting applies to all the Impala-related daemons, although currently it is primarily used for HDFS to control the behavior of the catalog server.
- Improvements to Impala integration and usability for Hue. (The code changes are actually on the Hue side.)
 - The list of tables now refreshes dynamically.
- Usability improvements for case-insensitive queries. You can now use the operators `ILIKE` and `IREGEXP` to perform case-insensitive wildcard matches or regular expression matches, rather than explicitly converting column values with `UPPER` or `LOWER`.
- Performance and reliability improvements for DDL and insert operations on partitioned tables with a large number of partitions. Impala only re-evaluates metadata for partitions that are affected by a DDL operation, not all partitions in the table. While a DDL or insert statement is in progress, other Impala statements that attempt to modify metadata for the same table wait until the first one finishes.
- Reliability improvements for the `LOAD DATA` statement. Previously, this statement would fail if the source HDFS directory contained any subdirectories at all. Now, the statement ignores any hidden subdirectories, for example `_impala_insert_staging`.
- A new operator, `IS [NOT] DISTINCT FROM`, lets you compare values and always get a `true` or `false` result, even if one or both of the values are `NULL`. The `IS NOT DISTINCT FROM` operator, or its equivalent `<=>` notation, improves the efficiency of join queries that treat key values that are `NULL` in both tables as equal.
- Security enhancements for the `impala-shell` command. A new option, `--ldap_password_cmd`, lets you specify a command to retrieve the LDAP password. The resulting password is then used to authenticate the `impala-shell` command with the LDAP server.
- The `CREATE TABLE AS SELECT` statement now accepts a `PARTITIONED BY` clause, which lets you create a partitioned table and insert data into it with a single statement.
- User-defined functions (UDFs and UDAFs) written in C++ now persist automatically when the `catalogd` daemon is restarted. You no longer have to run the `CREATE FUNCTION` statements again after a restart.
- User-defined functions (UDFs) written in Java can now persist when the `catalogd` daemon is restarted, and can be shared transparently between Impala and Hive. You must do a one-time operation to recreate these UDFs

using new `CREATE FUNCTION` syntax, without a signature for arguments or the return value. Afterwards, you no longer have to run the `CREATE FUNCTION` statements again after a restart. Although Impala does not have visibility into the UDFs that implement the Hive built-in functions, user-created Hive UDFs are now automatically available for calling through Impala.

- Reliability enhancements for memory management. Some aggregation and join queries that formerly might have failed with an out-of-memory error due to memory contention, now can succeed using the spill-to-disk mechanism.
- The `SHOW DATABASES` statement now returns two columns rather than one. The second column includes the associated comment string, if any, for each database. Adjust any application code that examines the list of databases and assumes the result set contains only a single column.
- A new optimization speeds up aggregation operations that involve only the partition key columns of partitioned tables. For example, a query such as `SELECT COUNT(DISTINCT k), MIN(k), MAX(k) FROM t1` can avoid reading any data files if `T1` is a partitioned table and `K` is one of the partition key columns. Because this technique can produce different results in cases where HDFS files in a partition are manually deleted or are empty, you must enable the optimization by setting the query option `OPTIMIZE_PARTITION_KEY_SCANS`.
- The `DESCRIBE` statement can now display metadata about a database, using the syntax `DESCRIBE DATABASE db_name`.
- The `uuid()` built-in function generates an alphanumeric value that you can use as a guaranteed unique identifier. The uniqueness applies even across tables, for cases where an ascending numeric sequence is not suitable.

New Features in Impala 2.4

- Impala can be used on the DSSD D5 Storage Appliance. From a user perspective, the Impala features are the same as in Impala 2.3.

New Features in Impala 2.3

The following are the major new features in Impala 2.3.x. This major release contains improvements to SQL syntax (particularly new support for complex types), performance, manageability, security.

- Complex data types: `STRUCT`, `ARRAY`, and `MAP`. These types can encode multiple named fields, positional items, or key-value pairs within a single column. You can combine these types to produce nested types with arbitrarily deep nesting, such as an `ARRAY` of `STRUCT` values, a `MAP` where each key-value pair is an `ARRAY` of other `MAP` values, and so on. Currently, complex data types are only supported for the Parquet file format.
- Column-level authorization lets you define access to particular columns within a table, rather than the entire table. This feature lets you reduce the reliance on creating views to set up authorization schemes for subsets of information. See the documentation for Apache Sentry for background details, and [GRANT Statement \(Impala 2.0 or higher only\)](#) on page 294 and [REVOKE Statement \(Impala 2.0 or higher only\)](#) on page 315 for Impala-specific syntax.
- The `TRUNCATE TABLE` statement removes all the data from a table without removing the table itself.
- Nested loop join queries. Some join queries that formerly required equality comparisons can now use operators such as `<` or `>=`. This same join mechanism is used internally to optimize queries that retrieve values from complex type columns.
- Reduced memory usage and improved performance and robustness for spill-to-disk feature.
- Performance improvements for querying Parquet data files containing multiple row groups and multiple data blocks:
 - For files written by Hive, SparkSQL, and other Parquet MR writers and spanning multiple HDFS blocks, Impala now scans the extra data blocks locally when possible, rather than using remote reads.
 - Impala queries benefit from the improved alignment of row groups with HDFS blocks for Parquet files written by Hive, MapReduce, and other components. (Impala itself never writes multiblock Parquet files, so the alignment change does not apply to Parquet files produced by Impala.) These Parquet writers now add padding to Parquet files that they write to align row groups with HDFS blocks. The `parquet.writer.max-padding` setting specifies the maximum number of bytes, by default 8 megabytes, that can be added to the file between row groups to fill the gap at the end of one block so that the next row group starts at the beginning of the next block. If the gap is larger than this size, the writer attempts to fit another entire row group in

the remaining space. Include this setting in the `hive-site` configuration file to influence Parquet files written by Hive, or the `hdfs-site` configuration file to influence Parquet files written by all non-Impala components.

- Many new built-in scalar functions, for convenience and enhanced portability of SQL that uses common industry extensions.

Math functions:

- ATAN2
- COSH
- COT
- DCEIL
- DEXP
- DFLOOR
- DLOG10
- DPOW
- DROUND
- DSQRT
- DTRUNC
- FACTORIAL, and corresponding ! operator
- FPOW
- RADIANS
- RANDOM
- SINH
- TANH

String functions:

- BTRIM
- CHR
- REGEXP_LIKE
- SPLIT_PART

Date and time functions:

- INT_MONTHS_BETWEEN
- MONTHS_BETWEEN
- TIMEOFDAY
- TIMESTAMP_CMP

Bit manipulation functions:

- BITAND
- BITNOT
- BITOR
- BITXOR
- COUNTSET
- GETBIT
- ROTATELEFT
- ROTATERIGHT
- SETBIT
- SHIFTLEFT
- SHIFTRIGHT

Type conversion functions:

- TYPEOF

The `effective_user()` function.

- New built-in analytic functions: `PERCENT_RANK`, `NTILE`, `CUME_DIST`.
- The `DROP DATABASE` statement now works for a non-empty database. When you specify the optional `CASCADE` clause, any tables in the database are dropped before the database itself is removed.
- The `DROP TABLE` and `ALTER TABLE DROP PARTITION` statements have a new optional keyword, `PURGE`. This keyword causes Impala to immediately remove the relevant HDFS data files rather than sending them to the HDFS trashcan. This feature can help to avoid out-of-space errors on storage devices, and to avoid files being left behind in case of a problem with the HDFS trashcan, such as the trashcan not being configured or being in a different HDFS encryption zone than the data files.
- The `impala-shell` command has a new feature for live progress reporting. This feature is enabled through the `--live_progress` and `--live_summary` command-line options, or during a session through the `LIVE_SUMMARY` and `LIVE_PROGRESS` query options.
- The `impala-shell` command also now displays a random “tip of the day” when it starts.
- The `impala-shell` option `-f` now recognizes a special filename `-` to accept input from stdin.
- Format strings for the `unix_timestamp()` function can now include numeric timezone offsets.
- Impala can now run a specified command to obtain the password to decrypt a private-key PEM file, rather than having the private-key file be unencrypted on disk.
- Impala components now can use SSL for more of their internal communication. SSL is used for communication between all three Impala-related daemons when the configuration option `ssl_server_certificate` is enabled. SSL is used for communication with client applications when the configuration option `ssl_client_ca_certificate` is enabled.

Currently, you can only use one of server-to-server TLS/SSL encryption or Kerberos authentication. This limitation is tracked by the issue [IMPALA-2598](#).

- Improved flexibility for intermediate data types in user-defined aggregate functions (UDAFs).

In Impala 2.3.2, the bug fix for [IMPALA-2598](#) removes the restriction on using both Kerberos and SSL for internal communication between Impala components.

New Features in Impala 2.8

The following are the major new features in Impala 2.2. This release contains improvements to performance, manageability, security, and SQL syntax.

- Several improvements to date and time features enable higher interoperability with Hive and other database systems, provide more flexibility for handling time zones, and future-proof the handling of `TIMESTAMP` values:
 - The `WITH REPLICATION` clause for the `CREATE TABLE` and `ALTER TABLE` statements lets you control the replication factor for HDFS caching for a specific table or partition. By default, each cached block is only present on a single host, which can lead to CPU contention if the same host processes each cached block. Increasing the replication factor lets Impala choose different hosts to process different cached blocks, to better distribute the CPU load.
 - Startup flags for the `impalad` daemon enable a higher level of compatibility with `TIMESTAMP` values written by Hive, and more flexibility for working with date and time data using the local time zone instead of UTC. To enable these features, set the `impalad` startup flags `-use_local_tz_for_unix_timestamp_conversions=true` and `-convert_legacy_hive_parquet_utc_timestamps=true`.

The `-use_local_tz_for_unix_timestamp_conversions` setting controls how the `unix_timestamp()`, `from_unixtime()`, and `now()` functions handle time zones. By default (when this setting is turned off), Impala considers all `TIMESTAMP` values to be in the UTC time zone when converting to or from Unix time values. When this setting is enabled, Impala treats `TIMESTAMP` values passed to or returned from these functions to be in the local time zone. When this setting is enabled, take particular care that all hosts in the cluster have the same timezone settings, to avoid inconsistent results depending on which host reads or writes `TIMESTAMP` data.

The `-convert_legacy_hive_parquet_utc_timestamps` setting causes Impala to convert `TIMESTAMP` values to the local time zone when it reads them from Parquet files written by Hive. This setting only applies to data using the Parquet file format, where Impala can use metadata in the files to reliably determine that the files were written by Hive. If in the future Hive changes the way it writes `TIMESTAMP` data in Parquet, Impala will automatically handle that new `TIMESTAMP` encoding.

See [TIMESTAMP Data Type](#) on page 133 for details about time zone handling and the configuration options for Impala / Hive compatibility with Parquet format.

- In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the “[Year 2038 problem](#)” or “[Y2K38 problem](#)”). This change affects the `FROM_UNIXTIME()` and `UNIX_TIMESTAMP()` functions. You might need to change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST()` calls to SQL statements that call these functions.

See [Impala Date and Time Functions](#) on page 478 for the current function signatures.

- The `SHOW FILES` statement lets you view the names and sizes of the files that make up an entire table or a specific partition. See [SHOW FILES Statement](#) on page 396 for details.
- Impala can now run queries against Parquet data containing columns with complex or nested types, as long as the query only refers to columns with scalar types.
- Performance improvements for queries that include `IN()` operators and involve partitioned tables.
- The new `-max_log_files` configuration option specifies how many log files to keep at each severity level. The default value is 10, meaning that Impala preserves the latest 10 log files for each severity level (`INFO`, `WARNING`, and `ERROR`) for each Impala-related daemon (`impalad`, `statestored`, and `catalogd`). Impala checks to see if any old logs need to be removed based on the interval specified in the `logbufsecs` setting, every 5 seconds by default. See [Rotating Impala Logs](#) on page 785 for details.
- Redaction of sensitive data from Impala log files. This feature protects details such as credit card numbers or tax IDs from administrators who see the text of SQL statements in the course of monitoring and troubleshooting a Hadoop cluster. See [Redacting Sensitive Information from Impala Log Files](#) on page 787 for background information for Impala users, and the documentation for your Apache Hadoop distribution for usage details.
- Lineage information is available for data created or queried by Impala. This feature lets you track who has accessed data through Impala SQL statements, down to the level of specific columns, and how data has been propagated between tables. See [Viewing Lineage Information for Impala Data](#) on page 100 for background information for Impala users, the documentation for your Apache Hadoop distribution for usage details and how to interpret the lineage information.
- Impala tables and partitions can now be located on the Amazon Simple Storage Service (S3) filesystem, for convenience in cases where data is already located in S3 and you prefer to query it in-place. Queries might have lower performance than when the data files reside on HDFS, because Impala uses some HDFS-specific optimizations. Impala can query data in S3, but cannot write to S3. Therefore, statements such as `INSERT` and `LOAD DATA` are not available when the destination table or partition is in S3. See [Using Impala with Amazon S3 Object Store](#) on page 769 for details.

Important:

Impala query support for Amazon S3 is included in Impala 2.2, but is not supported or recommended for production use in this version.

- Improved support for HDFS encryption. The `LOAD DATA` statement now works when the source directory and destination table are in different encryption zones. See the documentation for your Apache Hadoop distribution for details about using HDFS encryption with Impala.
- Additional arithmetic function `mod()`. See [Impala Mathematical Functions](#) on page 434 for details.
- Flexibility to interpret `TIMESTAMP` values using the UTC time zone (the traditional Impala behavior) or using the local time zone (for compatibility with `TIMESTAMP` values produced by Hive).
- Enhanced support for ETL using tools such as Flume. Impala ignores temporary files typically produced by these tools (filenames with suffixes `.copying` and `.tmp`).
- The CPU requirement for Impala, which had become more restrictive in Impala 2.0.x and 2.1.x, has now been relaxed.

The prerequisite for CPU architecture has been relaxed in Impala 2.2.0 and higher. From this release onward, Impala works on CPUs that have the SSSE3 instruction set. The SSE4 instruction set is no longer required. This relaxed requirement simplifies the upgrade planning from Impala 1.x releases, which also worked on SSSE3-enabled processors.

- Enhanced support for CHAR and VARCHAR types in the `COMPUTE STATS` statement.
- The amount of memory required during setup for “spill to disk” operations is greatly reduced. This enhancement reduces the chance of a memory-intensive join or aggregation query failing with an out-of-memory error.
- Several new conditional functions provide enhanced compatibility when porting code that uses industry extensions. The new functions are: `isfalse()`, `isnotfalse()`, `isnottrue()`, `istrue()`, `nonnullvalue()`, and `nullvalue()`. See [Impala Conditional Functions](#) on page 502 for details.
- The Impala debug web UI now can display a visual representation of the query plan. On the **/queries** tab, select **Details** for a particular query. The **Details** page includes a **Plan** tab with a plan diagram that you can zoom in or out (using scroll gestures through mouse wheel or trackpad).

New Features in Impala 2.1

This release contains the following enhancements to query performance and system scalability:

- Impala can now collect statistics for individual partitions in a partitioned table, rather than processing the entire table for each `COMPUTE STATS` statement. This feature is known as incremental statistics, and is controlled by the `COMPUTE INCREMENTAL STATS` syntax. (You can still use the original `COMPUTE STATS` statement for nonpartitioned tables or partitioned tables that are unchanging or whose contents are entirely replaced all at once.) See [COMPUTE STATS Statement](#) on page 232 and [Table and Column Statistics](#) on page 625 for details.
- Optimization for small queries lets Impala process queries that process very few rows without the unnecessary overhead of parallelizing and generating native code. Reducing this overhead lets Impala clear small queries quickly, keeping YARN resources and admission control slots available for data-intensive queries. The number of rows considered to be a “small” query is controlled by the `EXEC_SINGLE_NODE_ROWS_THRESHOLD` query option. See [EXEC_SINGLE_NODE_ROWS_THRESHOLD Query Option \(Impala 2.1 or higher only\)](#) on page 356 for details.
- An enhancement to the statestore component lets it transmit heartbeat information independently of broadcasting metadata updates. This optimization improves reliability of health checking on large clusters with many tables and partitions.
- The memory requirement for querying gzip-compressed text is reduced. Now Impala decompresses the data as it is read, rather than reading the entire gzipped file and decompressing it in memory.

New Features in Impala 2.0

The following are the major new features in Impala 2.0. This major release contains improvements to performance, scalability, security, and SQL syntax.

- Queries with joins or aggregation functions involving high volumes of data can now use temporary work areas on disk, reducing the chance of failure due to out-of-memory errors. When the required memory for the intermediate result set exceeds the amount available on a particular node, the query automatically uses a temporary work area on disk. This “spill to disk” mechanism is similar to the `ORDER BY` improvement from Impala 1.4. For details, see [SQL Operations that Spill to Disk](#) on page 660.
- Subquery enhancements:
 - Subqueries are now allowed in the `WHERE` clause, for example with the `IN` operator.
 - The `EXISTS` and `NOT EXISTS` operators are available. They are always used in conjunction with subqueries.
 - The `IN` and `NOT IN` queries can now operate on the result set from a subquery, not just a hardcoded list of values.
 - Uncorrelated subqueries let you compare against one or more values for equality, `IN`, and `EXISTS` comparisons. For example, you might use `WHERE` clauses such as `WHERE column = (SELECT MAX(some_other_column) FROM table)` or `WHERE column IN (SELECT some_other_column FROM table WHERE conditions)`.

- Correlated subqueries let you cross-reference values from the outer query block and the subquery.
- Scalar subqueries let you substitute the result of single-value aggregate functions such as `MAX()`, `MIN()`, `COUNT()`, or `AVG()`, where you would normally use a numeric value in a `WHERE` clause.

For details about subqueries, see [Subqueries in Impala SELECT Statements](#) on page 335. For information about new and improved operators, see [EXISTS Operator](#) on page 183 and [IN Operator](#) on page 188.

- Analytic functions such as `RANK()`, `LAG()`, `LEAD()`, and `FIRST_VALUE()` let you analyze sequences of rows with flexible ordering and grouping. Existing aggregate functions such as `MAX()`, `SUM()`, and `COUNT()` can also be used in an analytic context. See [Impala Analytic Functions](#) on page 569 for details. See [Impala Aggregate Functions](#) on page 539 for enhancements to existing aggregate functions.
- New data types provide greater compatibility with source code from traditional database systems:
 - `VARCHAR` is like the `STRING` data type, but with a maximum length. See [VARCHAR Data Type \(Impala 2.0 or higher only\)](#) on page 140 for details.
 - `CHAR` is like the `STRING` data type, but with a precise length. Short values are padded with spaces on the right. See [CHAR Data Type \(Impala 2.0 or higher only\)](#) on page 108 for details.
- Security enhancements:
 - Formerly, Impala was restricted to using either Kerberos or LDAP / Active Directory authentication within a cluster. Now, Impala can freely accept either kind of authentication request, allowing you to set up some hosts with Kerberos authentication and others with LDAP or Active Directory. See [Using Multiple Authentication Methods with Impala](#) on page 97 for details.
 - `GRANT` statement. See [GRANT Statement \(Impala 2.0 or higher only\)](#) on page 294 for details.
 - `REVOKE` statement. See [REVOKE Statement \(Impala 2.0 or higher only\)](#) on page 315 for details.
 - `CREATE ROLE` statement. See [CREATE ROLE Statement \(Impala 2.0 or higher only\)](#) on page 248 for details.
 - `DROP ROLE` statement. See [DROP ROLE Statement \(Impala 2.0 or higher only\)](#) on page 284 for details.
 - `SHOW ROLES` and `SHOW ROLE GRANT` statements. See [SHOW Statement](#) on page 395 for details.
 - To complement the HDFS encryption feature, a new Impala configuration option, `--disk_spill_encryption` secures sensitive data from being observed or tampered with when temporarily stored on disk.

The new security-related SQL statements work along with the Sentry authorization framework. See [Enabling Sentry Authorization for Impala](#) for details.

- Impala can now read compressed text files compressed by `gzip`, `bzip`, or `Snappy`. These files do not require any special table settings to work in an Impala text table. Impala recognizes the compression type automatically based on file extensions of `.gz`, `.bz2`, and `.snappy` respectively. These types of compressed text files are intended for convenience with existing ETL pipelines. Their non-splittable nature means they are not optimal for high-performance parallel queries. See [Using bzip2, deflate, gzip, Snappy, or zstd Text Files](#) on page 704 for details.
- Query hints can now use comment notation, `/* +hint_name */` or `-- +hint_name`, at the same places in the query where the hints enclosed by `[]` are recognized. This enhancement makes it easier to reuse Impala queries on other database systems. See [Optimizer Hints](#) on page 422 for details.
- A new query option, `QUERY_TIMEOUT_S`, lets you specify a timeout period in seconds for individual queries.

The working of the `--idle_query_timeout` configuration option is extended. If no `QUERY_OPTION_S` query option is in effect, `--idle_query_timeout` works the same as before, setting the timeout interval. When the `QUERY_OPTION_S` query option is specified, its maximum value is capped by the value of the `--idle_query_timeout` option.

That is, the system administrator sets the default and maximum timeout through the `--idle_query_timeout` startup option, and then individual users or applications can set a lower timeout value if desired through the `QUERY_TIMEOUT_S` query option. See [Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 65 and [QUERY_TIMEOUT_S Query Option \(Impala 2.0 or higher only\)](#) on page 385 for details.

- New functions `VAR_SAMP()` and `VAR_POP()` are aliases for the existing `VARIANCE_SAMP()` and `VARIANCE_POP()` functions.
- A new date and time function, `DATE_PART()`, provides similar functionality to `EXTRACT()`. You can also call the `EXTRACT()` function using the SQL-99 syntax, `EXTRACT(unit FROM timestamp)`. These

enhancements simplify the porting process for date-related code from other systems. See [Impala Date and Time Functions](#) on page 478 for details.

- New approximation features provide a fast way to get results when absolute precision is not required:
 - The `APPX_COUNT_DISTINCT` query option lets Impala rewrite `COUNT(DISTINCT)` calls to use `NDV()` instead, which speeds up the operation and allows multiple `COUNT(DISTINCT)` operations in a single query. See [APPX_COUNT_DISTINCT Query Option \(Impala 2.0 or higher only\)](#) on page 347 for details.

The `APPX_MEDIAN()` aggregate function produces an estimate for the median value of a column by using sampling. See [APPX_MEDIAN Function](#) on page 539 for details.

- Impala now supports a `DECODE()` function. This function works as a shorthand for a `CASE()` expression, and improves compatibility with SQL code containing vendor extensions. See [Impala Conditional Functions](#) on page 502 for details.
- The `STDDEV()`, `STDDEV_POP()`, `STDDEV_SAMP()`, `VARIANCE()`, `VARIANCE_POP()`, `VARIANCE_SAMP()`, and `NDV()` aggregate functions now all return `DOUBLE` results rather than `STRING`. Formerly, you were required to `CAST()` the result to a numeric type before using it in arithmetic operations.
- The default settings for Parquet block size, and the associated `PARQUET_FILE_SIZE` query option, are changed. Now, Impala writes Parquet files with a size of 256 MB and an HDFS block size of 256 MB. Previously, Impala attempted to write Parquet files with a size of 1 GB and an HDFS block size of 1 GB. In practice, Impala used a conservative estimate of the disk space needed for each Parquet block, leading to files that were typically 512 MB anyway. Thus, this change will make the file size more accurate if you specify a value for the `PARQUET_FILE_SIZE` query option. It also reduces the amount of memory reserved during `INSERT` into Parquet tables, potentially avoiding out-of-memory errors and improving scalability when inserting data into Parquet tables.
- Anti-joins are now supported, expressed using the `LEFT ANTI JOIN` and `RIGHT ANTI JOIN` clauses. These clauses returns results from one table that have no match in the other table. You might use this type of join in the same sorts of use cases as the `NOT EXISTS` and `NOT IN` operators. See [Joins in Impala SELECT Statements](#) on page 318 for details.
- The `SET` command in `impala-shell` has been promoted to a real SQL statement. You can now set query options such as `PARQUET_FILE_SIZE`, `MEM_LIMIT`, and `SYNC_DDL` within JDBC, ODBC, or any other kind of application that submits SQL without going through the `impala-shell` interpreter. See [SET Statement](#) on page 345 for details.
- The `impala-shell` interpreter now reads settings from an optional configuration file, named `$HOME/.impalarc` by default. See [impala-shell Configuration File](#) on page 795 for details.
- The library used for regular expression parsing has changed from Boost to Google RE2. This implementation change adds support for non-greedy matches using the `. * ?` notation. This and other changes in the way regular expressions are interpreted means you might need to re-test queries that use functions such as `regexp_extract()` or `regexp_replace()`, or operators such as `REGEXP` or `RLIKE`. See [Incompatible Changes and Limitations in Apache Impala](#) on page 867 for those details.

New Features in Impala 1.4

The following are the major new features in Impala 1.4:

- The `DECIMAL` data type lets you store fixed-precision values, for working with currency or other fractional values where it is important to represent values exactly and avoid rounding errors. This feature includes enhancements to built-in functions, numeric literals, and arithmetic expressions.
- Where the underlying HDFS support exists, Impala can take advantage of the HDFS caching feature to “pin” entire tables or individual partitions in memory, to speed up queries on frequently accessed data and reduce the CPU overhead of memory-to-memory copying. When HDFS files are cached in memory, Impala can read the cached data without any disk reads, and without making an additional copy of the data in memory. Other Hadoop components that read the same data files also experience a performance benefit.
- Impala can now use Sentry-based authorization based either on the original policy file, or on rules defined by `GRANT` and `REVOKE` statements issued through Hive. See [Enabling Sentry Authorization for Impala](#) for details.

- For interoperability with Parquet files created through other Hadoop components, such as Pig or MapReduce jobs, you can create an Impala table that automatically sets up the column definitions based on the layout of an existing Parquet data file.
- `ORDER BY` queries no longer require a `LIMIT` clause. If the size of the result set to be sorted exceeds the memory available to Impala, Impala uses a temporary work space on disk to perform the sort operation.
- LDAP connections can be secured through either SSL or TLS.
- The following new built-in scalar and aggregate functions are available:
 - A new built-in function, `EXTRACT ()`, returns one date or time field from a `TIMESTAMP` value.
 - A new built-in function, `TRUNC ()`, truncates date/time values to a particular granularity, such as year, month, day, hour, and so on.
 - `ADD_MONTHS ()` built-in function, an alias for the existing `MONTHS_ADD ()` function.
 - A new built-in function, `ROUND ()`, rounds `DECIMAL` values to a specified number of fractional digits.
 - Several built-in aggregate functions for computing properties for statistical distributions: `STDDEV ()`, `STDDEV_SAMP ()`, `STDDEV_POP ()`, `VARIANCE ()`, `VARIANCE_SAMP ()`, and `VARIANCE_POP ()`.
 - Several new built-in functions, such as `MAX_INT ()`, `MIN_SMALLINT ()`, and so on, let you conveniently check whether data values are in an expected range. You might be able to switch a column to a smaller type, saving memory during processing.
 - New built-in functions, `IS_INF ()` and `IS_NAN ()`, check for the special values infinity and “not a number”. These values could be specified as `inf` or `nan` in text data files, or be produced by certain arithmetic expressions.
- The `SHOW PARTITIONS` statement displays information about the structure of a partitioned table.
- New configuration options for the `impalad` daemon let you specify initial memory usage for all queries. The initial resource requests handled by Llama and YARN can be expanded later if needed, avoiding unnecessary over-allocation and reducing the chance of out-of-memory conditions.
- The Impala `CREATE TABLE` statement now has a `STORED AS AVRO` clause, allowing you to create Avro tables through Impala.
- New `impalad` configuration options let you fine-tune the calculations Impala makes to estimate resource requirements for each query. These options can help avoid problems due to overconsumption due to too-low estimates, or underutilization due to too-high estimates.
- A new `SUMMARY` command in the `impala-shell` interpreter provides a high-level summary of the work performed at each stage of the explain plan. The summary is also included in output from the `PROFILE` command.
- Performance improvements for the `COMPUTE STATS` statement:
 - The NDV function is speeded up through native code generation.
 - Because the `NULL` count is not currently used by the Impala query planner, in Impala 1.4.0 and higher, `COMPUTE STATS` does not count the `NULL` values for each column. (The `#Nulls` field of the stats table is left as `-1`, signifying that the value is unknown.)
- Performance improvements for partition pruning. This feature reduces the time spent in query planning, for partitioned tables with thousands of partitions. Previously, Impala typically queried tables with up to approximately 3000 partitions. With the performance improvement in partition pruning, now Impala can comfortably handle tables with tens of thousands of partitions.
- The documentation provides additional guidance for planning tasks.
- The `impala-shell` interpreter now supports UTF-8 characters for input and output. You can control whether `impala-shell` ignores invalid Unicode code points through the `--strict_unicode` option. (Although this option is removed in Impala 2.0.)

New Features in Impala 1.3.2

No new features. This point release is exclusively a bug fix release for the IMPALA-1019 issue related to HDFS caching.

New Features in Impala 1.3.1

This point release is primarily a vehicle to deliver bug fixes. Any new features are minor changes resulting from fixes for performance, reliability, or usability issues.

- A new `impalad` startup option, `--insert_inherit_permissions`, causes Impala `INSERT` statements to create each new partition with the same HDFS permissions as its parent directory. By default, `INSERT` statements create directories for new partitions using default HDFS permissions. See [INSERT Statement](#) on page 298 for examples of `INSERT` statements for partitioned tables.
- The `SHOW FUNCTIONS` statement now displays the return type of each function, in addition to the types of its arguments. See [SHOW Statement](#) on page 395 for examples.
- You can now specify the clause `FIELDS TERMINATED BY '\0'` with a `CREATE TABLE` statement to use text data files that use ASCII 0 (`\0`) characters as a delimiter. See [Using Text Data Files with Impala Tables](#) on page 697 for details.
- In Impala 1.3.1 and higher, the `REGEXP` and `RLIKE` operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by `.*`. See [REGEXP Operator](#) on page 198 for examples. Previously, these operators only succeeded when the regular expression matched the entire target string. This change improves compatibility with the regular expression support for popular database systems. There is no change to the behavior of the `regexp_extract()` and `regexp_replace()` built-in functions.

New Features in Impala 1.3

- The admission control feature lets you control and prioritize the volume and resource consumption of concurrent queries. This mechanism reduces spikes in resource usage, helping Impala to run alongside other kinds of workloads on a busy cluster. It also provides more user-friendly conflict resolution when multiple memory-intensive queries are submitted concurrently, avoiding resource contention that formerly resulted in out-of-memory errors. See [Admission Control and Query Queuing](#) on page 675 for details.
- Enhanced `EXPLAIN` plans provide more detail in an easier-to-read format. Now there are four levels of verbosity: the `EXPLAIN_LEVEL` option can be set from 0 (most concise) to 3 (most verbose). See [EXPLAIN Statement](#) on page 291 for syntax and [Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles](#) on page 654 for usage information.
- The `TIMESTAMP` data type accepts more kinds of input string formats through the `UNIX_TIMESTAMP` function, and produces more varieties of string formats through the `FROM_UNIXTIME` function. The documentation now also lists more functions for date arithmetic, used for adding and subtracting `INTERVAL` expressions from `TIMESTAMP` values. See [Impala Date and Time Functions](#) on page 478 for details.
- New conditional functions, `NULLIF()`, `NULLIFZERO()`, and `ZEROIFNULL()`, simplify porting SQL containing vendor extensions to Impala. See [Impala Conditional Functions](#) on page 502 for details.
- New utility function, `CURRENT_DATABASE()`. See [Impala Miscellaneous Functions](#) on page 535 for details.
- Integration with the YARN resource management framework. This feature makes use of the underlying YARN service, plus an additional service (Llama) that coordinates requests to YARN for Impala resources, so that the Impala query only proceeds when all requested resources are available. See [Resource Management](#) on page 675 for full details.

On the Impala side, this feature involves some new startup options for the `impalad` daemon:

- `-enable_rm`
- `-llama_host`
- `-llama_port`
- `-llama_callback_port`
- `-cgroupp_hierarchy_path`

For details of these startup options, see [Modifying Impala Startup Options](#) on page 32.

This feature also involves several new or changed query options that you can set through the `impala-shell` interpreter and apply within a specific session:

- `MEM_LIMIT`: the function of this existing option changes when Impala resource management is enabled.

- `REQUEST_POOL`: a new option. (Renamed to `RESOURCE_POOL` in Impala 1.3.0.)
- `V_CPU_CORES`: a new option.
- `RESERVATION_REQUEST_TIMEOUT`: a new option.

For details of these query options, see [#unique_825](#).

New Features in Impala 1.2.4

Note: Impala 1.2.4 is primarily a bug fix release for Impala 1.2.3, plus some performance enhancements for the catalog server to minimize startup and DDL wait times for Impala deployments with large numbers of databases, tables, and partitions.

- On Impala startup, the metadata loading and synchronization mechanism has been improved and optimized, to give more responsiveness when starting Impala on a system with a large number of databases, tables, or partitions. The initial metadata loading happens in the background, allowing queries to be run before the entire process is finished. When a query refers to a table whose metadata is not yet loaded, the query waits until the metadata for that table is loaded, and the load operation for that table is prioritized to happen first.
- Formerly, if you created a new table in Hive, you had to issue the `INVALIDATE METADATA` statement (with no table name) which was an expensive operation that reloaded metadata for all tables. Impala did not recognize the name of the Hive-created table, so you could not do `INVALIDATE METADATA new_table` to get the metadata for just that one table. Now, when you issue `INVALIDATE METADATA table_name`, Impala checks to see if that name represents a table created in Hive, and if so recognizes the new table and loads the metadata for it. Additionally, if the new table is in a database that was newly created in Hive, Impala also recognizes the new database.
- If you issue `INVALIDATE METADATA table_name` and the table has been dropped through Hive, Impala will recognize that the table no longer exists.
- New startup options let you control the parallelism of the metadata loading during startup for the `catalogd` daemon:
 - `--load_catalog_in_background` makes Impala load and cache metadata using background threads after startup. It is `true` by default. Previously, a system with a large number of databases, tables, or partitions could be unresponsive or even time out during startup.
 - `--num_metadata_loading_threads` determines how much parallelism Impala devotes to loading metadata in the background. The default is 16. You might increase this value for systems with huge numbers of databases, tables, or partitions. You might lower this value for busy systems that are CPU-constrained due to jobs from components other than Impala.

New Features in Impala 1.2.3

Impala 1.2.3 contains exactly the same feature set as Impala 1.2.2. Its only difference is one additional fix for compatibility with Parquet files generated outside of Impala by components such as Hive, Pig, or MapReduce. If you are upgrading from Impala 1.2.1 or earlier, see [New Features in Impala 1.2.2](#) on page 861 for the latest added features.

New Features in Impala 1.2.2

Impala 1.2.2 includes new features for performance, security, and flexibility. The major enhancements over 1.2.1 are performance related, primarily for join queries.

New user-visible features include:

- Join order optimizations. This highly valuable feature automatically distributes and parallelizes the work for a join query to minimize disk I/O and network traffic. The automatic optimization reduces the need to use query hints or to rewrite join queries with the tables in a specific order based on size or cardinality. The new `COMPUTE STATS` statement gathers statistical information about each table that is crucial for enabling the join optimizations. See [Performance Considerations for Join Queries](#) on page 618 for details.
- `COMPUTE STATS` statement to collect both table statistics and column statistics with a single statement. Intended to be more comprehensive, efficient, and reliable than the corresponding Hive `ANALYZE TABLE` statement,

which collects statistics in multiple phases through MapReduce jobs. These statistics are important for query planning for join queries, queries on partitioned tables, and other types of data-intensive operations. For optimal planning of join queries, you need to collect statistics for each table involved in the join. See [COMPUTE STATS Statement](#) on page 232 for details.

- Reordering of tables in a join query can be overridden by the `STRAIGHT_JOIN` operator, allowing you to fine-tune the planning of the join query if necessary, by using the original technique of ordering the joined tables in descending order of size. See [Overriding Join Reordering with STRAIGHT_JOIN](#) on page 619 for details.
- The `CROSS JOIN` clause in the `SELECT` statement to allow Cartesian products in queries, that is, joins without an equality comparison between columns in both tables. Because such queries must be carefully checked to avoid accidental overconsumption of memory, you must use the `CROSS JOIN` operator to explicitly select this kind of join. See [Cross Joins and Cartesian Products with the CROSS JOIN Operator](#) on page 51 for examples.
- The `ALTER TABLE` statement has new clauses that let you fine-tune table statistics. You can use this technique as a less-expensive way to update specific statistics, in case the statistics become stale, or to experiment with the effects of different data distributions on query planning.
- LDAP username/password authentication in JDBC/ODBC. See [Enabling LDAP Authentication for Impala](#) on page 93 for details.
- [GROUP_CONCAT\(\)](#) aggregate function to concatenate column values across all rows of a result set.
- The `INSERT` statement now accepts hints, `[SHUFFLE]` and `[NOSHUFFLE]`, to influence the way work is redistributed during `INSERT...SELECT` operations. The hints are primarily useful for inserting into partitioned Parquet tables, where using the `[SHUFFLE]` hint can avoid problems due to memory consumption and simultaneous open files in HDFS, by collecting all the new data for each partition on a specific node.
- Several built-in functions and operators are now overloaded for more numeric data types, to reduce the requirement to use `CAST()` for type coercion in `INSERT` statements. For example, the expression `2+2` in an `INSERT` statement formerly produced a `BIGINT` result, requiring a `CAST()` to be stored in an `INT` variable. Now, addition, subtraction, and multiplication only produce a result that is one step “bigger” than their arguments, and numeric and conditional functions can return `SMALLINT`, `FLOAT`, and other smaller types rather than always `BIGINT` or `DOUBLE`.
- New `fnv_hash()` built-in function for constructing hashed values. See [Impala Mathematical Functions](#) on page 434 for details.
- The clause `STORED AS PARQUET` is accepted as an equivalent for `STORED AS PARQUETFILE`. This more concise form is recommended for new code.

Because Impala 1.2.2 builds on a number of features introduced in 1.2.1, if you are upgrading from an older 1.1.x release straight to 1.2.2, also review [New Features in Impala 1.2.1](#) on page 862 to see features such as the `SHOW TABLE STATS` and `SHOW COLUMN STATS` statements, and user-defined functions (UDFs).

New Features in Impala 1.2.1

Note: The Impala 1.2.1 feature set is a superset of features in the Impala 1.2.0 beta, with the exception of resource management, which relies on resource management infrastructure in the underlying Hadoop distribution.

Impala 1.2.1 includes new features for security, performance, and flexibility.

New user-visible features include:

- `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` statements, to verify that statistics are available and to see the values used during query planning.
- `CREATE TABLE AS SELECT` syntax, to create a new table and transfer data into it in a single operation.
- `OFFSET` clause, for use with the `ORDER BY` and `LIMIT` clauses to produce “paged” result sets such as items 1-10, then 11-20, and so on.
- `NULLS FIRST` and `NULLS LAST` clauses to ensure consistent placement of `NULL` values in `ORDER BY` queries.
- New [built-in functions](#): `least()`, `greatest()`, `initcap()`.
- New aggregate function: `ndv()`, a fast alternative to `COUNT(DISTINCT col)` returning an approximate result.
- The `LIMIT` clause can now accept a numeric expression as an argument, rather than only a literal constant.

- The `SHOW CREATE TABLE` statement displays the end result of all the `CREATE TABLE` and `ALTER TABLE` statements for a particular table. You can use the output to produce a simplified setup script for a schema.
- The `--idle_query_timeout` and `--idle_session_timeout` options for `impalad` control the time intervals after which idle queries are cancelled, and idle sessions expire. See [Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 65 for details.
- User-defined functions (UDFs). This feature lets you transform data in very flexible ways, which is important when using Impala as part of an ETL or ELT pipeline. Prior to Impala 1.2, using UDFs required switching into Hive. Impala 1.2 can run scalar UDFs and user-defined aggregate functions (UDAs). Impala can run high-performance functions written in C++, or you can reuse existing Hive functions written in Java.

You create UDFs through the `CREATE FUNCTION` statement and drop them through the `DROP FUNCTION` statement. See [User-Defined Functions \(UDFs\)](#) on page 588 for instructions about coding, building, and deploying UDFs, and [CREATE FUNCTION Statement](#) on page 242 and [DROP FUNCTION Statement](#) on page 282 for related SQL syntax.

- A new service automatically propagates changes to table data and metadata made by one Impala node, sending the new or updated metadata to all the other Impala nodes. The automatic synchronization mechanism eliminates the need to use the `INVALIDATE METADATA` and `REFRESH` statements after issuing Impala statements such as `CREATE TABLE`, `ALTER TABLE`, `DROP TABLE`, `INSERT`, and `LOAD DATA`.

For even more precise synchronization, you can enable the `SYNC_DDL` query option before issuing a DDL, `INSERT`, or `LOAD DATA` statement. This option causes the statement to wait, returning only after the catalog service has broadcast the applicable changes to all Impala nodes in the cluster.

Note:

Because the catalog service only monitors operations performed through Impala, `INVALIDATE METADATA` and `REFRESH` are still needed on the Impala side after creating new tables or loading data through the Hive shell or by manipulating data files directly in HDFS. Because the catalog service broadcasts the result of the `REFRESH` and `INVALIDATE METADATA` statements to all Impala nodes, when you do need to use those statements, you can do so a single time rather than on every Impala node.

This service is implemented by the `catalogd` daemon. See [The Impala Catalog Service](#) on page 18 for details.

- The `CREATE TABLE` and `ALTER TABLE` statements have new clauses `TBLPROPERTIES` and `WITH SERDEPROPERTIES`. The `TBLPROPERTIES` clause lets you associate arbitrary items of metadata with a particular table as key-value pairs. The `WITH SERDEPROPERTIES` clause lets you specify the serializer/deserializer (SerDes) classes that read and write data for a table; although Impala does not make use of these properties, sometimes particular values are needed for Hive compatibility. See [CREATE TABLE Statement](#) on page 248 and [ALTER TABLE Statement](#) on page 215 for details.
- Delegation support lets you authorize certain OS users associated with applications (for example, hue), to submit requests using the credentials of other users. See [Configuring Impala Delegation for Clients](#) on page 97 for details.
- Enhancements to `EXPLAIN` output. In particular, when you enable the new `EXPLAIN_LEVEL` query option, the `EXPLAIN` and `PROFILE` statements produce more verbose output showing estimated resource requirements and whether table and column statistics are available for the applicable tables and columns. See [EXPLAIN Statement](#) on page 291 for details.
- `SHOW CREATE TABLE` summarizes the effects of the original `CREATE TABLE` statement and any subsequent `ALTER TABLE` statements, giving you a `CREATE TABLE` statement that will re-create the current structure and layout for a table.
- The `LIMIT` clause for queries now accepts an arithmetic expression, in addition to numeric literals.

New Features in Impala 1.2.0 (Beta)

The Impala 1.2.0 beta includes new features for security, performance, and flexibility.

New user-visible features include:

- User-defined functions (UDFs). This feature lets you transform data in very flexible ways, which is important when using Impala as part of an ETL or ELT pipeline. Prior to Impala 1.2, using UDFs required switching

into Hive. Impala 1.2 can run scalar UDFs and user-defined aggregate functions (UDAs). Impala can run high-performance functions written in C++, or you can reuse existing Hive functions written in Java.

You create UDFs through the `CREATE FUNCTION` statement and drop them through the `DROP FUNCTION` statement. See [User-Defined Functions \(UDFs\)](#) on page 588 for instructions about coding, building, and deploying UDFs, and [CREATE FUNCTION Statement](#) on page 242 and [DROP FUNCTION Statement](#) on page 282 for related SQL syntax.

- A new service automatically propagates changes to table data and metadata made by one Impala node, sending the new or updated metadata to all the other Impala nodes. The automatic synchronization mechanism eliminates the need to use the `INVALIDATE METADATA` and `REFRESH` statements after issuing Impala statements such as `CREATE TABLE`, `ALTER TABLE`, `DROP TABLE`, `INSERT`, and `LOAD DATA`.

Note:

Because this service only monitors operations performed through Impala, `INVALIDATE METADATA` and `REFRESH` are still needed on the Impala side after creating new tables or loading data through the Hive shell or by manipulating data files directly in HDFS. Because the catalog service broadcasts the result of the `REFRESH` and `INVALIDATE METADATA` statements to all Impala nodes, when you do need to use those statements, you can do so a single time rather than on every Impala node.

This service is implemented by the `catalogd` daemon. See [The Impala Catalog Service](#) on page 18 for details.

- Integration with the YARN resource management framework. This feature makes use of the underlying YARN service, plus an additional service (Llama) that coordinates requests to YARN for Impala resources, so that the Impala query only proceeds when all requested resources are available. See [Resource Management](#) on page 675 for full details.

On the Impala side, this feature involves some new startup options for the `impalad` daemon:

- `-enable_rm`
- `-llama_host`
- `-llama_port`
- `-llama_callback_port`
- `-cgroup_hierarchy_path`

For details of these startup options, see [Modifying Impala Startup Options](#) on page 32.

This feature also involves several new or changed query options that you can set through the `impala-shell` interpreter and apply within a specific session:

- `MEM_LIMIT`: the function of this existing option changes when Impala resource management is enabled.
- `YARN_POOL`: a new option. (Renamed to `RESOURCE_POOL` in Impala 1.3.0.)
- `V_CPU_CORES`: a new option.
- `RESERVATION_REQUEST_TIMEOUT`: a new option.

For details of these query options, see [#unique_825](#).

- `CREATE TABLE ... AS SELECT` syntax, to create a table and copy data into it in a single operation. See [CREATE TABLE Statement](#) on page 248 for details.
- The `CREATE TABLE` and `ALTER TABLE` statements have a new `TBLPROPERTIES` clause that lets you associate arbitrary items of metadata with a particular table as key-value pairs. See [CREATE TABLE Statement](#) on page 248 and [ALTER TABLE Statement](#) on page 215 for details.
- Delegation support lets you authorize certain OS users associated with applications (for example, `hue`), to submit requests using the credentials of other users. See [Configuring Impala Delegation for Clients](#) on page 97 for details.
- Enhancements to `EXPLAIN` output. In particular, when you enable the new `EXPLAIN_LEVEL` query option, the `EXPLAIN` and `PROFILE` statements produce more verbose output showing estimated resource requirements and whether table and column statistics are available for the applicable tables and columns. See [EXPLAIN Statement](#) on page 291 for details.

New Features in Impala 1.1.1

Impala 1.1.1 includes new features for security and stability.

New user-visible features include:

- Additional security feature: auditing. New startup options for `impalad` let you capture information about Impala queries that succeed or are blocked due to insufficient privileges. For details, see [Impala Security](#) on page 78.
- Parquet data files generated by Impala 1.1.1 are now compatible with the Parquet support in Hive. See [Incompatible Changes and Limitations in Apache Impala](#) on page 867 for the procedure to update older Impala-created Parquet files to be compatible with the Hive Parquet support.
- Additional improvements to stability and resource utilization for Impala queries.
- Additional enhancements for compatibility with existing file formats.

New Features in Impala 1.1

Impala 1.1 includes new features for security, performance, and usability.

New user-visible features include:

- Extensive new security features, built on top of the Sentry open source project. Impala now supports fine-grained authorization based on roles. A policy file determines which privileges on which schema objects (servers, databases, tables, and HDFS paths) are available to users based on their membership in groups. By assigning privileges for views, you can control access to table data at the column level. For details, see [Impala Security](#) on page 78.
- Impala can now create, alter, drop, and query views. Views provide a flexible way to set up simple aliases for complex queries; hide query details from applications and users; and simplify maintenance as you rename or reorganize databases, tables, and columns. See the overview section [Overview of Impala Views](#) on page 209 and the statements [CREATE VIEW Statement](#) on page 265, [ALTER VIEW Statement](#) on page 230, and [DROP VIEW Statement](#) on page 290.
- Performance is improved through a number of automatic optimizations. Resource consumption is also reduced for Impala queries. These improvements apply broadly across all kinds of workloads and file formats. The major areas of performance enhancement include:
 - Improved disk and thread scheduling, which applies to all queries.
 - Improved hash join and aggregation performance, which applies to queries with large build tables or a large number of groups.
 - Dictionary encoding with Parquet, which applies to Parquet tables with short string columns.
 - Improved performance on systems with SSDs, which applies to all queries and file formats.
- Some new built-in functions are implemented: [translate\(\)](#) to substitute characters within strings, [user\(\)](#) to check the login ID of the connected user.
- The new `WITH` clause for `SELECT` statements lets you simplify complicated queries in a way similar to creating a view. The effects of the `WITH` clause only last for the duration of one query, unlike views, which are persistent schema objects that can be used by multiple sessions or applications. See [WITH Clause](#) on page 344.
- An enhancement to `DESCRIBE` statement, `DESCRIBE FORMATTED table_name`, displays more detailed information about the table. This information includes the file format, location, delimiter, ownership, external or internal, creation and access times, and partitions. The information is returned as a result set that can be interpreted and used by a management or monitoring application. See [DESCRIBE Statement](#) on page 268.
- You can now insert a subset of columns for a table, with other columns being left as all `NULL` values. Or you can specify the columns in any order in the destination table, rather than having to match the order of the corresponding columns in the source. `VALUES` clause. This feature is known as “column permutation”. See [INSERT Statement](#) on page 298.
- The new `LOAD DATA` statement lets you load data into a table directly from an HDFS data file. This technique lets you minimize the number of steps in your ETL process, and provides more flexibility. For example, you can bring data into an Impala table in one step. Formerly, you might have created an external table where the data files are not entirely under your control, or copied the data files to Impala data directories manually, or loaded the original data into one table and then used the `INSERT` statement to copy it to a new table with a different file format, partitioning scheme, and so on. See [LOAD DATA Statement](#) on page 309.

- Improvements to Impala-HBase integration:
 - New query options for HBase performance: [HBASE_CACHE_BLOCKS](#) and [HBASE_CACHING](#).
 - Support for binary data types in HBase tables. See [Supported Data Types for HBase Columns](#) on page 751 for details.
- You can issue REFRESH as a SQL statement through any of the programming interfaces that Impala supports. REFRESH formerly had to be issued as a command through the `impala-shell` interpreter, and was not available through a JDBC or ODBC API call. As part of this change, the functionality of the REFRESH statement is divided between two statements. In Impala 1.1, REFRESH requires a table name argument and immediately reloads the metadata; the new `INVALIDATE METADATA` statement works the same as the Impala 1.0 REFRESH did: the table name argument is optional, and the metadata for one or all tables is marked as stale, but not actually reloaded until the table is queried. When you create a new table in the Hive shell or through a different Impala node, you must enter `INVALIDATE METADATA` with no table parameter before you can see the new table in `impala-shell`. See [REFRESH Statement](#) on page 312 and [INVALIDATE METADATA Statement](#) on page 307.

New Features in Impala 1.0.1

New user-visible features include:

- The `VALUES` clause lets you `INSERT` one or more rows using literals, function return values, or other expressions. For performance and scalability, you should still use `INSERT ... SELECT` for bringing large quantities of data into an Impala table. The `VALUES` clause is a convenient way to set up small tables, particularly for initial testing of SQL features that do not require large amounts of data. See [VALUES Clause](#) on page 302 for details.
- The `-B` and `-o` options of the `impala-shell` command can turn query results into delimited text files and store them in an output file. The plain text results are useful for using with other Hadoop components or Unix tools. In benchmark tests, it is also faster to produce plain rather than pretty-printed results, and write to a file rather than to the screen, giving a more accurate picture of the actual query time.
- Several bug fixes. See [Issues Fixed in the 1.0.1 Release](#) on page 918 for details.

New Features in Impala 1.0

This version has multiple performance improvements and adds the following functionality:

- Several bug fixes. See [Issues Fixed in the 1.0 GA Release](#) on page 920.
- [ALTER TABLE](#) statement.
- [Hints](#) to allow specifying a particular join strategy.
- [REFRESH](#) for a single table.
- Dynamic resource management, allowing high concurrency for Impala queries.

New Features in Version 0.7 of the Impala Beta Release

This version has multiple performance improvements and adds the following functionality:

- Several bug fixes. See [Issues Fixed in Version 0.7 of the Beta Release](#) on page 922.
- Support for the Parquet file format. For more information on file formats, see [How Impala Works with Hadoop File Formats](#) on page 695.
- Added support for Avro.
- Support for the memory limits. For more information, see the example on modifying memory limits in [Modifying Impala Startup Options](#) on page 32.
- Bigger and faster joins through the addition of partitioned joins to the already supported broadcast joins.
- Fully distributed aggregations.
- Fully distributed top-n computation.
- Support for creating and altering tables.
- Support for `GROUP BY` with floats and doubles.

New Features in Version 0.6 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.6 of the Beta Release](#) on page 923.
- Added support for Impala on SUSE and Debian/Ubuntu. Impala is now supported on:
 - RHEL5.7/6.2 and Centos5.7/6.2
 - SUSE 11 with Service Pack 1 or higher
 - Ubuntu 10.04/12.04 and Debian 6.03
- Support for the RCFile file format. For more information on file formats, see [Understanding File Formats](#).

New Features in Version 0.5 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.5 of the Beta Release](#) on page 924.
- Added support for a JDBC driver that allows you to access Impala from a Java client. To use this feature, follow the instructions in [Configuring Impala to Work with JDBC](#) on page 801 to install the JDBC driver JARs on the client machine and modify the CLASSPATH on the client to include the JARs.

New Features in Version 0.4 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.4 of the Beta Release](#) on page 924.
- Added support for Impala on RHEL5.7/Centos5.7. Impala is now supported on RHEL5.7/6.2 and Centos5.7/6.2.
- The Impala debug webserver now has the ability to serve static files from `${IMPALA_HOME}/www`. This can be disabled by setting `--enable_webserver_doc_root=false` on the command line. As a result, Impala now uses the Twitter Bootstrap library to style its debug webpages, and the `/queries` page now tracks the last 25 queries run by each Impala daemon.
- Additional metrics available on the Impala Debug Webpage.

New Features in Version 0.3 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.3 of the Beta Release](#) on page 925.
- The `state-store-service` binary has been renamed `statestored`.
- The location of the Impala configuration files has changed from the `/usr/lib/impala/conf` directory to the `/etc/impala/conf` directory.

New Features in Version 0.2 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.2 of the Beta Release](#) on page 925.
- **Added Default Query Options** Default query options override all default QueryOption values when starting `impalad`. The format is:

```
-default_query_options='key=value;key=value'
```

Incompatible Changes and Limitations in Apache Impala

The Impala version covered by this documentation library contains the following incompatible changes. These are things such as file format changes, removed features, or changes to implementation, default configuration, dependencies, or prerequisites that could cause issues during or after an Impala upgrade.

Even added SQL statements or clauses can produce incompatibilities, if you have databases, tables, or columns whose names conflict with the new keywords.

Incompatible Changes Introduced in Impala 4.0.x

For the full list of incompatible changes introduced in this release, see the [release notes for Impala 4.0](#).

Incompatible Changes Introduced in Impala 3.4.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 3.4](#).

- To optimize query performance, Impala planner uses the value of the `fs.s3a.block.size` startup flag when calculating the split size on non-block based stores, e.g. S3, ADLS, etc. Starting in this release, Impala planner uses the `PARQUET_OBJECT_STORE_SPLIT_SIZE` query option to get the Parquet file format specific split size.

For Parquet files, the `fs.s3a.block.size` startup flag is no longer used.

The default value of the `PARQUET_OBJECT_STORE_SPLIT_SIZE` query option is 256 MB.

Incompatible Changes Introduced in Impala 3.3.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 3.3](#).

- Default file format changed to Parquet

When you create a table, the default format for that table data is now Parquet.

For backward compatibility, you can use the `DEFAULT_FILE_FORMAT` query option to set the default file format to the previous default, text, or other formats.

Incompatible Changes Introduced in Impala 3.2.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 3.2](#).

- The Port change for the SHUTDOWN command

The SHUTDOWN command for shutting down a remote server used the backend port in Impala 3.1. Starting in Impala 3.2, the command uses the KRPC port, e.g. `:shutdown('host100:27000')`.

Incompatible Changes Introduced in Impala 3.1.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 3.1](#).

Incompatible Changes Introduced in Impala 3.0.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 3.0](#).

Incompatible Changes Introduced in Impala 2.12.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 2.12](#).

Incompatible Changes Introduced in Impala 2.11.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 2.11](#).

Incompatible Changes Introduced in Impala 2.10.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 2.10](#).

Incompatible Changes Introduced in Impala 2.9.x

For the full list of issues closed in this release, including any that introduce behavior changes or incompatibilities, see the [changelog for Impala 2.9](#).

Incompatible Changes Introduced in Impala 2.8.x

- Llama support is removed completely from Impala. Related flags (`--enable_rm`) and query options (such as `V_CPU_CORES`) remain but do not have any effect.
- If `--enable_rm` is passed to Impala, a warning is printed to the log on startup.
- The syntax related to Kudu tables includes a number of new reserved words, such as `COMPRESSION`, `DEFAULT`, and `ENCODING`, that might conflict with names of existing tables, columns, or other identifiers from older Impala versions. See [Impala Reserved Words](#) on page 821 for the full list of reserved words.
- The DDL syntax for Kudu tables, particularly in the `CREATE TABLE` statement, is different from the special `impala_next` fork that was previously used for accessing Kudu tables from Impala:
 - The `DISTRIBUTE BY` clause is now `PARTITIONED BY`.
 - The `INTO N BUCKETS` clause is now `PARTITIONS N`.
 - The `SPLIT ROWS` clause is replaced by different syntax for specifying the ranges covered by each partition.
- The `DESCRIBE` output for Kudu tables includes several extra columns.
- Non-primary-key columns can contain `NULL` values by default. The `SHOW CREATE TABLE` output for these columns displays the `NULL` attribute. There was a period during early experimental versions of Impala + Kudu where non-primary-key columns had the `NOT NULL` attribute by default.
- The `IGNORE` keyword that was present in early experimental versions of Impala + Kudu is no longer present. The behavior of the `IGNORE` keyword is now the default: DML statements continue with warnings, instead of failing with errors, if they encounter conditions such as “primary key already exists” for an `INSERT` statement or “primary key already deleted” for a `DELETE` statement.
- The replication factor for Kudu tables must be an odd number.
- A UDF compiled into an LLVM IR bitcode module (`.bc`) might encounter a runtime error when native code generation is turned off by setting the query option `DISABLE_CODEGEN=1`. This issue also applies when running a built-in or native UDF with more than 20 arguments. See [IMPALA-4432](#) for details. As a workaround, either turn native code generation back on with the query option `DISABLE_CODEGEN=0`, or use the regular UDF compilation path that does not produce an IR module.

Incompatible Changes Introduced in Impala 2.7.x

- Bug fixes related to parsing of floating-point values ([IMPALA-1731](#) and [IMPALA-3868](#)) can change the results of casting strings that represent invalid floating-point values. For example, formerly a string value beginning or ending with `inf`, such as `1.23inf` or `infinite`, now are converted to `NULL` when interpreted as a floating-point value. Formerly, they were interpreted as the special “infinity” value when converting from string to floating-point. Similarly, now only the string `NaN` (case-sensitive) is interpreted as the special “not a number” value. String values containing multiple dots, such as `3. .141` or `3.1.4.1`, are now interpreted as `NULL` rather than being converted to valid floating-point values.

Incompatible Changes Introduced in Impala 2.6.x

- The default for the `RUNTIME_FILTER_MODE` query option is changed to `GLOBAL` (the highest setting).
- The `RUNTIME_BLOOM_FILTER_SIZE` setting is now only used as a fallback if statistics are not available; otherwise, Impala uses the statistics to estimate the appropriate size to use for each filter.
- Admission control and dynamic resource pools are enabled by default. When upgrading from an earlier release, you must turn on these settings yourself if they are not already enabled. See [Admission Control and Query Queuing](#) on page 675 for details about admission control.
- Impala reserves some new keywords, in preparation for support for Kudu syntax: `buckets`, `delete`, `distribute`, `hash`, `ignore`, `split`, and `update`.
- For Kerberized clusters, the Catalog service now uses the Kerberos principal instead of the operating system user that runs the `catalogd` daemon. This eliminates the requirement to configure a

`hadoop.user.group.static.mapping.overrides` setting to put the OS user into the Sentry administrative group, on clusters where the principal and the OS user name for this user are different.

- The mechanism for interpreting `DECIMAL` literals is improved, no longer going through an intermediate conversion step to `DOUBLE`:
 - Casting a `DECIMAL` value to `TIMESTAMP DOUBLE` produces a more precise value for the `TIMESTAMP` than formerly.
 - Certain function calls involving `DECIMAL` literals now succeed, when formerly they failed due to lack of a function signature with a `DOUBLE` argument.
- Improved type accuracy for `CASE` return values. If all `WHEN` clauses of the `CASE` expression are of `CHAR` type, the final result is also `CHAR` instead of being converted to `STRING`.
- The initial release of Impala 2.5 sometimes has a higher peak memory usage than in previous releases while reading Parquet files. The following query options might help to reduce memory consumption in the Parquet scanner:
 - Reduce the number of scanner threads, for example: `set num_scanner_threads=30`
 - Reduce the batch size, for example: `set batch_size=512`
 - Increase the memory limit, for example: `set mem_limit=64g`

You can track the status of the fix for this issue at [IMPALA-3662](#).

- The `S3_SKIP_INSERT_STAGING` query option, which is enabled by default, increases the speed of `INSERT` operations for S3 tables. The speedup applies to regular `INSERT`, but not `INSERT OVERWRITE`. The tradeoff is the possibility of inconsistent output files left behind if a node fails during `INSERT` execution. See [S3_SKIP_INSERT_STAGING Query Option \(Impala 2.6 or higher only\)](#) on page 390 for details.

Certain features are turned off by default, to avoid regressions or unexpected behavior following an upgrade. Consider turning on these features after suitable testing:

- Impala now recognizes the `auth_to_local` setting, specified through the HDFS configuration setting `hadoop.security.auth_to_local`. This feature is disabled by default; to enable it, specify `--load_auth_to_local_rules=true` in the `impalad` configuration settings.
- A new query option, `PARQUET_ANNOTATE_STRINGS_UTF8`, makes Impala include the UTF-8 annotation metadata for `STRING`, `CHAR`, and `VARCHAR` columns in Parquet files created by `INSERT` or `CREATE TABLE AS SELECT` statements.
- A new query option, `PARQUET_FALLBACK_SCHEMA_RESOLUTION`, lets Impala locate columns within Parquet files based on column name rather than ordinal position. This enhancement improves interoperability with applications that write Parquet files with a different order or subset of columns than are used in the Impala table.

Incompatible Changes Introduced in Impala 2.5.x

- The admission control default limit for concurrent queries (the **max requests** setting) is now unlimited instead of 200.
- Multiplying a mixture of `DECIMAL` and `FLOAT` or `DOUBLE` values now returns `DOUBLE` rather than `DECIMAL`. This change avoids some cases where an intermediate value would underflow or overflow and become `NULL` unexpectedly. The results of multiplying `DECIMAL` and `FLOAT` or `DOUBLE` might now be slightly less precise than before. Previously, the intermediate types and thus the final result depended on the exact order of the values of different types being multiplied, which made the final result values difficult to reason about.
- Previously, the `_` and `%` wildcard characters for the `LIKE` operator would not match characters on the second or subsequent lines of multi-line string values. The fix for issue [IMPALA-2204](#) causes the wildcard matching to apply to the entire string for values containing embedded `\n` characters. This could cause different results than in previous Impala releases for identical queries on identical data.
- Formerly, all Impala UDFs and UDAs required running the `CREATE FUNCTION` statements to re-create them after each `catalogd` restart. In Impala 2.5 and higher, functions written in C++ are persisted across restarts, and the requirement to re-create functions only applies to functions written in Java. Adapt any function-reloading logic that you have added to your Impala environment.
- `CREATE TABLE LIKE` no longer inherits HDFS caching settings from the source table.

- The `SHOW DATABASES` statement now returns two columns rather than one. The second column includes the associated comment string, if any, for each database. Adjust any application code that examines the list of databases and assumes the result set contains only a single column.
- The output of the `SHOW FUNCTIONS` statement includes two new columns, showing the kind of the function (for example, `BUILTIN`) and whether or not the function persists across catalog server restarts. For example, the `SHOW FUNCTIONS` output for the `_impala_builtins` database starts with:

```

+-----+-----+-----+-----+
+-----+-----+-----+-----+
| return type | signature | binary |
| type | is persistent | |
+-----+-----+-----+-----+
+-----+-----+-----+-----+
| BIGINT | abs(BIGINT) | BUILTIN |
| | true | |
| DECIMAL(*,*) | abs(DECIMAL(*,*)) | BUILTIN |
| | true | |
| DOUBLE | abs(DOUBLE) | BUILTIN |
| | true | |
...

```

Incompatible Changes Introduced in Impala 2.4.x

Other than support for DSSD storage, the Impala feature set for Impala 2.4 is the same as for Impala 2.3. Therefore, there are no incompatible changes for Impala introduced in Impala 2.4.

Incompatible Changes Introduced in Impala 2.3.x

Note:

The use of the Llama component for integrated resource management within YARN is no longer supported with Impala 2.3 and higher. The Llama support code is removed entirely in Impala 2.8 and higher.

For clusters running Impala alongside other data management components, you define static service pools to define the resources available to Impala and other components. Then within the area allocated for Impala, you can create dynamic service pools, each with its own settings for the Impala admission control feature.

- If Impala encounters a Parquet file that is invalid because of an incorrect magic number, the query skips the file. This change is caused by the fix for issue [IMPALA-2130](#). Previously, Impala would attempt to read the file despite the possibility that the file was corrupted.
- Previously, calls to overloaded built-in functions could treat parameters as `DOUBLE` or `FLOAT` when no overload had a signature that matched the exact argument types. Now Impala prefers the function signature with `DECIMAL` parameters in this case. This change avoids a possible loss of precision in function calls such as `greatest(0, 99999.8888)`; now both parameters are treated as `DECIMAL` rather than `DOUBLE`, avoiding any loss of precision in the fractional value. This could cause slightly different results than in previous Impala releases for certain function calls.
- Formerly, adding or subtracting a large interval value to a `TIMESTAMP` could produce a nonsensical result. Now when the result goes outside the range of `TIMESTAMP` values, Impala returns `NULL`.
- Formerly, it was possible to accidentally create a table with identical row and column delimiters. This could happen unintentionally, when specifying one of the delimiters and using the default value for the other. Now an attempt to use identical delimiters still succeeds, but displays a warning message.
- Formerly, Impala could include snippets of table data in log files by default, for example when reporting conversion errors for data values. Now any such log messages are only produced at higher logging levels that you would enable only during debugging.

Incompatible Changes Introduced in Impala 2.2.x

Changes to File Handling

Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.

The log rotation feature in Impala 2.2.0 and higher means that older log files are now removed by default. The default is to preserve the latest 10 log files for each severity level, for each Impala-related daemon. If you have set up your own log rotation processes that expect older files to be present, either adjust your procedures or change the Impala `max_log_files` setting.

Changes to Prerequisites

The prerequisite for CPU architecture has been relaxed in Impala 2.2.0 and higher. From this release onward, Impala works on CPUs that have the SSSE3 instruction set. The SSE4 instruction set is no longer required. This relaxed requirement simplifies the upgrade planning from Impala 1.x releases, which also worked on SSSE3-enabled processors.

Incompatible Changes Introduced in Impala 2.1.x

Changes to Prerequisites

Currently, Impala 2.1.x does not function on CPUs without the SSE4.1 instruction set. This minimum CPU requirement is higher than in previous versions, which relied on the older SSSE3 instruction set. Check the CPU level of the hosts in your cluster before upgrading to Impala 2.1.

Changes to Output Format

The “small query” optimization feature introduces some new information in the `EXPLAIN` plan, which you might need to account for if you parse the text of the plan output.

New Reserved Words

New SQL syntax introduces additional reserved words: `FOR`, `GRANT`, `REVOKE`, `ROLE`, `ROLES`, `INCREMENTAL`.

Incompatible Changes Introduced in Impala 2.0.5

No incompatible changes.

Incompatible Changes Introduced in Impala 2.0.4

No incompatible changes.

Incompatible Changes Introduced in Impala 2.0.3

Incompatible Changes Introduced in Impala 2.0.2

No incompatible changes.

Incompatible Changes Introduced in Impala 2.0.1

- The `INSERT` statement has always left behind a hidden work directory inside the data directory of the table. Formerly, this hidden work directory was named `.impala_insert_staging`. In Impala 2.0.1 and later, this directory name is changed to `_impala_insert_staging`. (While HDFS tools are expected to treat names beginning either with underscore and dot as hidden, in practice names beginning with an underscore are more

widely supported.) If you have any scripts, cleanup jobs, and so on that rely on the name of this work directory, adjust them to use the new name.

- The `abs()` function now takes a broader range of numeric types as arguments, and the return type is the same as the argument type.
- Shorthand notation for character classes in regular expressions, such as `\d` for digit, are now available again in regular expression operators and functions such as `regexp_extract()` and `regexp_replace()`. Some other differences in regular expression behavior remain between Impala 1.x and Impala 2.x releases. See [Incompatible Changes Introduced in Impala 2.0.0](#) on page 873 for details.

Incompatible Changes Introduced in Impala 2.0.0

Changes to Prerequisites

Currently, Impala 2.0.x does not function on CPUs without the SSE4.1 instruction set. This minimum CPU requirement is higher than in previous versions, which relied on the older SSSE3 instruction set. Check the CPU level of the hosts in your cluster before upgrading to Impala 2.0.

Changes to Query Syntax

The new syntax where query hints are allowed in comments causes some changes in the way comments are parsed in the `impala-shell` interpreter. Previously, you could end a `--` comment line with a semicolon and `impala-shell` would treat that as a no-op statement. Now, a comment line ending with a semicolon is passed as an empty statement to the Impala daemon, where it is flagged as an error.

Impala 2.0 and later uses a different support library for regular expression parsing than in earlier Impala versions. Now, Impala uses the [Google RE2 library](#) rather than Boost for evaluating regular expressions. This implementation change causes some differences in the allowed regular expression syntax, and in the way certain regex operators are interpreted. The following are some of the major differences (not necessarily a complete list):

- `. * ?` notation for non-greedy matches is now supported, where it was not in earlier Impala releases.
- By default, `^` and `$` now match only begin/end of buffer, not begin/end of each line. This behavior can be overridden in the regex itself using the `m` flag.
- By default, `.` does not match newline. This behavior can be overridden in the regex itself using the `s` flag.
- `\Z` is not supported.
- `<` and `>` for start of word and end of word are not supported.
- Lookahead and lookbehind are not supported.
- Shorthand notation for character classes, such as `\d` for digit, is not recognized. (This restriction is lifted in Impala 2.0.1, which restores the shorthand notation.)

Changes to Output Format

In Impala 2.0 and later, `user()` returns the full Kerberos principal string, such as `user@example.com`, in a Kerberized environment.

The changed format for the user name in secure environments is also reflected where the user name is displayed in the output of the `PROFILE` command.

In the output from `SHOW FUNCTIONS`, `SHOW AGGREGATE FUNCTIONS`, and `SHOW ANALYTIC FUNCTIONS`, arguments and return types of arbitrary DECIMAL scale and precision are represented as `DECIMAL(*,*)`. Formerly, these items were displayed as `DECIMAL(-1, -1)`.

Changes to Query Options

The `PARQUET_COMPRESSION_CODEC` query option has been replaced by the `COMPRESSION_CODEC` query option.

Changes to Configuration Options

The meaning of the `--idle_query_timeout` configuration option is changed, to accommodate the new `QUERY_TIMEOUT_S` query option. Rather than setting an absolute timeout period that applies to all queries, it now sets a maximum timeout period, which can be adjusted downward for individual queries by specifying a value for the `QUERY_TIMEOUT_S` query option. In sessions where no `QUERY_TIMEOUT_S` query option is specified, the `--idle_query_timeout` timeout period applies the same as in earlier versions.

The `--strict_unicode` option of `impala-shell` was removed. To avoid problems with Unicode values in `impala-shell`, define the following locale setting before running `impala-shell`:

```
export LC_CTYPE=en_US.UTF-8
```

New Reserved Words

Some new SQL syntax requires the addition of new reserved words: `ANTI`, `ANALYTIC`, `OVER`, `PRECEDING`, `UNBOUNDED`, `FOLLOWING`, `CURRENT`, `ROWS`, `RANGE`, `CHAR`, `VARCHAR`.

Changes to Data Files

The default Parquet block size for Impala is changed from 1 GB to 256 MB. This change could have implications for the sizes of Parquet files produced by `INSERT` and `CREATE TABLE AS SELECT` statements.

Although older Impala releases typically produced files that were smaller than the old default size of 1 GB, now the file size matches more closely whatever value is specified for the `PARQUET_FILE_SIZE` query option. Thus, if you use a non-default value for this setting, the output files could be larger than before. They still might be somewhat smaller than the specified value, because Impala makes conservative estimates about the space needed to represent each column as it encodes the data.

When you do not specify an explicit value for the `PARQUET_FILE_SIZE` query option, Impala tries to keep the file size within the 256 MB default size, but Impala might adjust the file size to be somewhat larger if needed to accommodate the layout for *wide* tables, that is, tables with hundreds or thousands of columns.

This change is unlikely to affect memory usage while writing Parquet files, because Impala does not pre-allocate the memory needed to hold the entire Parquet block.

Incompatible Changes Introduced in Impala 1.4.4

No incompatible changes.

Incompatible Changes Introduced in Impala 1.4.3

No incompatible changes. The TLS/SSL security fix does not require any change in the way you interact with Impala.

Incompatible Changes Introduced in Impala 1.4.2

None. Impala 1.4.2 is purely a bug-fix release. It does not include any incompatible changes.

Incompatible Changes Introduced in Impala 1.4.1

None. Impala 1.4.1 is purely a bug-fix release. It does not include any incompatible changes.

Incompatible Changes Introduced in Impala 1.4.0

- There is a slight change to required security privileges in the Sentry framework. To create a new object, now you need the `ALL` privilege on the parent object. For example, to create a new table, view, or function requires having the `ALL` privilege on the database containing the new object. See [Impala Authorization](#) on page 83 for a full list of operations and associated privileges.

- With the ability of `ORDER BY` queries to process unlimited amounts of data with no `LIMIT` clause, the query options `DEFAULT_ORDER_BY_LIMIT` and `ABORT_ON_DEFAULT_LIMIT_EXCEEDED` are now deprecated and have no effect.
- There are some changes to the list of reserved words. The following keywords are new:
 - `API_VERSION`
 - `BINARY`
 - `CACHED`
 - `CLASS`
 - `PARTITIONS`
 - `PRODUCED`
 - `UNCACHED`

The following were formerly reserved keywords, but are no longer reserved:

- `COUNT`
- `GROUP_CONCAT`
- `NDV`
- `SUM`
- The fix for issue [IMPALA-973](#) changes the behavior of the `INVALIDATE METADATA` statement regarding nonexistent tables. In Impala 1.4.0 and higher, the statement returns an error if the specified table is not in the metastore database at all. It completes successfully if the specified table is in the metastore database but not yet recognized by Impala, for example if the table was created through Hive. Formerly, you could issue this statement for a completely nonexistent table, with no error.

Incompatible Changes Introduced in Impala 1.3.3

No incompatible changes. The TLS/SSL security fix does not require any change in the way you interact with Impala.

Incompatible Changes Introduced in Impala 1.3.2

With the fix for [IMPALA-1019](#), you can use HDFS caching for files that are accessed by Impala.

Incompatible Changes Introduced in Impala 1.3.1

- In Impala 1.3.1 and higher, the `REGEXP` and `RLIKE` operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by `.` and `*`. See [REGEXP Operator](#) on page 198 for examples. Previously, these operators only succeeded when the regular expression matched the entire target string. This change improves compatibility with the regular expression support for popular database systems. There is no change to the behavior of the `regexp_extract()` and `regexp_replace()` built-in functions.
- The result set for the `SHOW FUNCTIONS` statement includes a new first column, with the data type of the return value.

Incompatible Changes Introduced in Impala 1.3.0

- The `EXPLAIN_LEVEL` query option now accepts numeric options from 0 (most concise) to 3 (most verbose), rather than only 0 or 1. If you formerly used `SET EXPLAIN_LEVEL=1` to get detailed explain plans, switch to `SET EXPLAIN_LEVEL=3`. If you used the mnemonic keyword (`SET EXPLAIN_LEVEL=verbose`), you do not need to change your code because now level 3 corresponds to `verbose`.
- The keyword `DECIMAL` is now a reserved word. If you have any databases, tables, columns, or other objects already named `DECIMAL`, quote any references to them using backticks (```) to avoid name conflicts with the keyword.

Note: Although the `DECIMAL` keyword is a reserved word, currently Impala does not support `DECIMAL` as a data type for columns.

- The query option formerly named `YARN_POOL` is now named `REQUEST_POOL` to reflect its broader use with the Impala admission control feature.

- There are some changes to the list of reserved words.
 - The names of aggregate functions are no longer reserved words, so you can have databases, tables, columns, or other objects named AVG, MIN, and so on without any name conflicts.
 - The internal function names DISTINCTPC and DISTINCTPCSA are no longer reserved words, although DISTINCT is still a reserved word.
 - The keywords CLOSE_FN and PREPARE_FN are now reserved words.
- The HDFS property `dfs.client.file-block-storage-locations.timeout` was renamed to `dfs.client.file-block-storage-locations.timeout.millis`, to emphasize that the unit of measure is milliseconds, not seconds. Impala requires a timeout of at least 10 seconds, making the minimum value for this setting 10000. If you are not using cluster management software, you might need to edit the `hdfs-site.xml` file in the Impala configuration directory for the new name and minimum value.

Incompatible Changes Introduced in Impala 1.2.4

There are no incompatible changes introduced in Impala 1.2.4.

Previously, after creating a table in Hive, you had to issue the `INVALIDATE METADATA` statement with no table name, a potentially expensive operation on clusters with many databases, tables, and partitions. Starting in Impala 1.2.4, you can issue the statement `INVALIDATE METADATA table_name` for a table newly created through Hive. Loading the metadata for only this one table is faster and involves less network overhead. Therefore, you might revisit your setup DDL scripts to add the table name to `INVALIDATE METADATA` statements, in cases where you create and populate the tables through Hive before querying them through Impala.

Incompatible Changes Introduced in Impala 1.2.3

Because the feature set of Impala 1.2.3 is identical to Impala 1.2.2, there are no new incompatible changes. See [Incompatible Changes Introduced in Impala 1.2.2](#) on page 876 if you are upgrading from Impala 1.2.1 or 1.1.x.

Incompatible Changes Introduced in Impala 1.2.2

The following changes to SQL syntax and semantics in Impala 1.2.2 could require updates to your SQL code, or schema objects such as tables or views:

- With the addition of the `CROSS JOIN` keyword, you might need to rewrite any queries that refer to a table named `CROSS` or use the name `CROSS` as a table alias:

```
-- Formerly, 'cross' in this query was an alias for t1
-- and it was a normal join query.
-- In 1.2.2 and higher, CROSS JOIN is a keyword, so 'cross'
-- is not interpreted as a table alias, and the query
-- uses the special CROSS JOIN processing rather than a
-- regular join.
select * from t1 cross join t2...

-- Now if CROSS is used in other context such as a table or column name,
-- use backticks to escape it.
create table `cross` (x int);
select * from `cross`;
```

- Formerly, a `DROP DATABASE` statement in Impala would not remove the top-level HDFS directory for that database. The `DROP DATABASE` has been enhanced to remove that directory. (You still need to drop all the tables inside the database first; this change only applies to the top-level directory for the entire database.)
- The keyword `PARQUET` is introduced as a synonym for `PARQUETFILE` in the `CREATE TABLE` and `ALTER TABLE` statements, because that is the common name for the file format. (As opposed to `SequenceFile` and `RCFile` where the “File” suffix is part of the name.) Documentation examples have been changed to prefer the new shorter keyword. The `PARQUETFILE` keyword is still available for backward compatibility with older Impala versions.
- New overloads are available for several operators and built-in functions, allowing you to insert their result values into smaller numeric columns such as `INT`, `SMALLINT`, `TINYINT`, and `FLOAT` without using a `CAST()` call. If

you remove the `CAST ()` calls from `INSERT` statements, those statements might not work with earlier versions of Impala.

Because many users are likely to upgrade straight from Impala 1.x to Impala 1.2.2, also read [Incompatible Changes Introduced in Impala 1.2.1](#) on page 877 for things to note about upgrading to Impala 1.2.x in general.

Incompatible Changes Introduced in Impala 1.2.1

The following changes to SQL syntax and semantics in Impala 1.2.1 could require updates to your SQL code, or schema objects such as tables or views:

- In Impala 1.2.1 and higher, all `NULL` values come at the end of the result set for `ORDER BY . . . ASC` queries, and at the beginning of the result set for `ORDER BY . . . DESC` queries. In effect, `NULL` is considered greater than all other values for sorting purposes. The original Impala behavior always put `NULL` values at the end, even for `ORDER BY . . . DESC` queries. The new behavior in Impala 1.2.1 makes Impala more compatible with other popular database systems. In Impala 1.2.1 and higher, you can override or specify the sorting behavior for `NULL` by adding the clause `NULLS FIRST` or `NULLS LAST` at the end of the `ORDER BY` clause.

The new `catalogd` service might require changes to any user-written scripts that stop, start, or restart Impala services, install or upgrade Impala packages, or issue `REFRESH` or `INVALIDATE METADATA` statements:

- See [Installing Impala](#) on page 25, [Upgrading Impala](#) on page 28 and [Starting Impala](#) on page 31, for usage information for the `catalogd` daemon.
- The `REFRESH` and `INVALIDATE METADATA` statements are no longer needed when the `CREATE TABLE`, `INSERT`, or other table-changing or data-changing operation is performed through Impala. These statements are still needed if such operations are done through Hive or by manipulating data files directly in HDFS, but in those cases the statements only need to be issued on one Impala node rather than on all nodes. See [REFRESH Statement](#) on page 312 and [INVALIDATE METADATA Statement](#) on page 307 for the latest usage information for those statements.
- See [The Impala Catalog Service](#) on page 18 for background information on the `catalogd` service.

Incompatible Changes Introduced in Impala 1.2.0 (Beta)

There are no incompatible changes to SQL syntax in Impala 1.2.0 (beta).

The new `catalogd` service might require changes to any user-written scripts that stop, start, or restart Impala services, install or upgrade Impala packages, or issue `REFRESH` or `INVALIDATE METADATA` statements:

- See [Installing Impala](#) on page 25, [Upgrading Impala](#) on page 28 and [Starting Impala](#) on page 31, for usage information for the `catalogd` daemon.
- The `REFRESH` and `INVALIDATE METADATA` statements are no longer needed when the `CREATE TABLE`, `INSERT`, or other table-changing or data-changing operation is performed through Impala. These statements are still needed if such operations are done through Hive or by manipulating data files directly in HDFS, but in those cases the statements only need to be issued on one Impala node rather than on all nodes. See [REFRESH Statement](#) on page 312 and [INVALIDATE METADATA Statement](#) on page 307 for the latest usage information for those statements.
- See [The Impala Catalog Service](#) on page 18 for background information on the `catalogd` service.

The new resource management feature interacts with both YARN and Llama services.

Incompatible Changes Introduced in Impala 1.1.1

There are no incompatible changes in Impala 1.1.1.

Previously, it was not possible to create Parquet data through Impala and reuse that table within Hive. Now that Parquet support is available for Hive 10, reusing existing Impala Parquet data files in Hive requires updating the table metadata. Use the following command if you are already running Impala 1.1.1:

```
ALTER TABLE table_name SET FILEFORMAT PARQUETFILE;
```

If you are running a level of Impala that is older than 1.1.1, do the metadata update through Hive:

```
ALTER TABLE table_name SET SERDE 'parquet.hive.serde.ParquetHiveSerDe';
ALTER TABLE table_name SET FILEFORMAT
  INPUTFORMAT "parquet.hive.DeprecatedParquetInputFormat"
  OUTPUTFORMAT "parquet.hive.DeprecatedParquetOutputFormat";
```

Impala 1.1.1 and higher can reuse Parquet data files created by Hive, without any action required.

As usual, make sure to upgrade the Impala LZO package to the latest level at the same time as you upgrade the Impala server.

Incompatible Change Introduced in Impala 1.1

- The REFRESH statement now requires a table name; in Impala 1.0, the table name was optional. This syntax change is part of the internal rework to make REFRESH a true Impala SQL statement so that it can be called through the JDBC and ODBC APIs. REFRESH now reloads the metadata immediately, rather than marking it for update the next time any affected table is accessed. The previous behavior, where omitting the table name caused a refresh of the entire Impala metadata catalog, is available through the new INVALIDATE METADATA statement. INVALIDATE METADATA can be specified with a table name to affect a single table, or without a table name to affect the entire metadata catalog; the relevant metadata is reloaded the next time it is requested during the processing for a SQL statement. See [REFRESH Statement](#) on page 312 and [INVALIDATE METADATA Statement](#) on page 307 for the latest details about these statements.

Incompatible Changes Introduced in Impala 1.0

- If you use LZO-compressed text files, when you upgrade Impala to version 1.0, also update the Impala LZO package to the latest level. See [Using LZO-Compressed Text Files](#) on page 702 for details.

Known Issues and Workarounds in Impala

The following sections describe known issues and workarounds in Impala, as of the current production release. This page summarizes the most serious or frequently encountered issues in the current release, to help you make planning decisions about installing and upgrading. Any workarounds are listed here. The bug links take you to the Impala issues site, where you can see the diagnosis and whether a fix is in the pipeline.

Note: The online issue tracking system for Impala contains comprehensive information and is updated in real time. To verify whether an issue you are experiencing has already been reported, or which release an issue is fixed in, search on the [issues.apache.org JIRA tracker](https://issues.apache.org/JIRA/tracker).

For issues fixed in various Impala releases, see [Fixed Issues in Apache Impala](#) on page 884.

Impala Known Issues: Startup

These issues can prevent one or more Impala-related daemons from starting properly.

Impala requires FQDN from hostname command on Kerberized clusters

The method Impala uses to retrieve the host name while constructing the Kerberos principal is the `gethostname()` system call. This function might not always return the fully qualified domain name, depending on the network configuration. If the daemons cannot determine the FQDN, Impala does not start on a Kerberized cluster.

Workaround: Test if a host is affected by checking whether the output of the `hostname` command includes the FQDN. On hosts where `hostname` only returns the short name, pass the command-line flag `##hostname=fully_qualified_domain_name` in the startup options of all Impala-related daemons.

Apache Issue: [IMPALA-4978](#)

Impala Known Issues: Performance

These issues involve the performance of operations such as queries or DDL statements.

Metadata operations block read-only operations on unrelated tables

Metadata operations that change the state of a table, like `COMPUTE STATS` or `ALTER RECOVER PARTITIONS`, may delay metadata propagation of unrelated unloaded tables triggered by statements like `DESCRIBE` or `SELECT` queries.

Apache Issue: [IMPALA-6671](#)

Impala Known Issues: JDBC and ODBC Drivers

These issues affect applications that use the JDBC or ODBC APIs, such as business intelligence tools or custom-written applications in languages such as Java or C++.

ImpalaODBC: Can not get the value in the SQLGetData(m-x th column) after the SQLBindCol(m th column)

If the ODBC `SQLGetData` is called on a series of columns, the function calls must follow the same order as the columns. For example, if data is fetched from column 2 then column 1, the `SQLGetData` call for column 1 returns `NULL`.

Apache Issue: [IMPALA-1792](#)

Workaround: Fetch columns in the same order they are defined in the table.

Impala Known Issues: Security

These issues are related to security features, such as Kerberos authentication, Sentry authorization, encryption, auditing, and redaction.

Impala does not support Heimdal Kerberos

Heimdal Kerberos is not supported in Impala.

Apache Issue: [IMPALA-7072](#)

Affected Versions: All versions of Impala

Impala does not allow the use of insecure clusters with public IPs

Starting in Impala 2.12, Impala, by default, will only allow unencrypted or unauthenticated connections from trusted subnets: `127.0.0.0/8`, `10.0.0.0/8`, `172.16.0.0/12`, `192.168.0.0/16`, `169.254.0.0/16`. Unencrypted or unauthenticated connections from publicly routable IPs will be rejected.

The trusted subnets can be configured using the `--trusted_subnets` flag. Set it to `'0.0.0.0/0'` to allow unauthenticated connections from all remote IP addresses. However, if network access is not otherwise restricted by a firewall, malicious users may be able to gain unauthorized access.

Impala Known Issues: Resources

These issues involve memory or disk usage, including out-of-memory conditions, the spill-to-disk feature, and resource management features.

Configuration to prevent crashes caused by thread resource limits

Impala could encounter a serious error due to resource usage under very high concurrency. The error message is similar to:

```
F0629 08:20:02.956413 29088 llvm-codegen.cc:111] LLVM hit fatal error:
Unable to allocate section memory!
```



```
terminate called after throwing an instance of
'boost::exception_detail::clone_impl<boost::exception_detail::error_info_injector<boost
>'
>'
```

Apache Issue: [IMPALA-5605](#)

Severity: High

Workaround: To prevent such errors, configure each host running an `impalad` daemon with the following settings:

```
echo 2000000 > /proc/sys/kernel/threads-max
echo 2000000 > /proc/sys/kernel/pid_max
echo 8000000 > /proc/sys/vm/max_map_count
```

Add the following lines in `/etc/security/limits.conf`:

```
impala soft nproc 262144
impala hard nproc 262144
```

Breakpad minidumps can be very large when the thread count is high

The size of the breakpad minidump files grows linearly with the number of threads. By default, each thread adds 8 KB to the minidump size. Minidump files could consume significant disk space when the daemons have a high number of threads.

Workaround: Add `--minidump_size_limit_hint_kb=size` to set a soft upper limit on the size of each minidump file. If the minidump file would exceed that limit, Impala reduces the amount of information for each thread from 8 KB to 2 KB. (Full thread information is captured for the first 20 threads, then 2 KB per thread after that.) The minidump file can still grow larger than the "hinted" size. For example, if you have 10,000 threads, the minidump file can be more than 20 MB.

Apache Issue: [IMPALA-3509](#)

Process mem limit does not account for the JVM's memory usage

Some memory allocated by the JVM used internally by Impala is not counted against the memory limit for the `impalad` daemon.

Workaround: To monitor overall memory usage, use the `top` command, or add the memory figures in the Impala web UI `/memz` tab to JVM memory usage shown on the `/metrics` tab.

Apache Issue: [IMPALA-691](#)

Impala Known Issues: Correctness

These issues can cause incorrect or unexpected results from queries. They typically only arise in very specific circumstances.

Incorrect result due to constant evaluation in query with outer join

An `OUTER JOIN` query could omit some expected result rows due to a constant such as `FALSE` in another join clause. For example:

```
explain SELECT 1 FROM alltypestiny a1
  INNER JOIN alltypesagg a2 ON a1.smallint_col = a2.year AND false
  RIGHT JOIN alltypes a3 ON a1.year = a1.bigint_col;
+-----+
| Explain String                                |
+-----+
```



```
Estimated Per-Host Requirements: Memory=1.00KB VCores=1
00:EMPTYSET
+-----+
```

Apache Issue: [IMPALA-3094](#)

Severity: High

% escaping does not work correctly when occurs at the end in a LIKE clause

If the final character in the RHS argument of a LIKE operator is an escaped \% character, it does not match a % final character of the LHS argument.

Apache Issue: [IMPALA-2422](#)

Crash: impala::Coordinator::ValidateCollectionSlots

A query could encounter a serious error if includes multiple nested levels of INNER JOIN clauses involving subqueries.

Apache Issue: [IMPALA-2603](#)

Impala Known Issues: Interoperability

These issues affect the ability to interchange data between Impala and other database systems. They cover areas such as data types and file formats.

Queries Stuck on Failed HDFS Calls and not Timing out

In Impala 3.2 and higher, if the following error appears multiple times in a short duration while running a query, it would mean that the connection between the `impalad` and the HDFS NameNode is in a bad state and hence the `impalad` would have to be restarted:

```
"hdfsOpenFile() for <filename> at backend <hostname:port> failed to finish
before the <hdfs_operation_timeout_sec> second timeout "
```

In Impala 3.1 and lower, the same issue would cause Impala to wait for a long time or hang without showing the above error message.

Apache Issue: [HADOOP-15720](#)

Affected Versions: All versions of Impala

Workaround: Restart the `impalad` in the bad state.

DESCRIBE FORMATTED gives error on Avro table

This issue can occur either on old Avro tables (created prior to Hive 1.1) or when changing the Avro schema file by adding or removing columns. Columns added to the schema file will not show up in the output of the DESCRIBE FORMATTED command. Removing columns from the schema file will trigger a `NullPointerException`.

As a workaround, you can use the output of `SHOW CREATE TABLE` to drop and recreate the table. This will populate the Hive metastore database with the correct column definitions.



Warning:

Only use this for external tables, or Impala will remove the data files. In case of an internal table, set it to external first:

```
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');
```

(The part in parentheses is case sensitive.) Make sure to pick the right choice between internal and external when recreating the table. See [Overview of Impala Tables](#) on page 206 for the differences between internal and external tables.

Severity: High

Configuration needed for Flume to be compatible with Impala

For compatibility with Impala, the value for the Flume HDFS Sink `hdfs.writeFormat` must be set to `Text`, rather than its default value of `Writable`. The `hdfs.writeFormat` setting must be changed to `Text` before creating data files with Flume; otherwise, those files cannot be read by either Impala or Hive.

Resolution: This information has been requested to be added to the upstream Flume documentation.

Avro Scanner fails to parse some schemas

The default value in Avro schema must match type of first union type, e.g. if the default value is `null`, then the first type in the UNION must be `"null"`.

Apache Issue: [IMPALA-635](#)

Workaround: Swap the order of the fields in the schema specification. For example, use `["null", "string"]` instead of `["string", "null"]`. Note that the files written with the problematic schema must be rewritten with the new schema because Avro files have embedded schemas.

Impala BE cannot parse Avro schema that contains a trailing semi-colon

If an Avro table has a schema definition with a trailing semicolon, Impala encounters an error when the table is queried.

Apache Issue: [IMPALA-1024](#)

Severity: Remove trailing semicolon from the Avro schema.

Incorrect results with basic predicate on CHAR typed column

When comparing a CHAR column value to a string literal, the literal value is not blank-padded and so the comparison might fail when it should match.

Apache Issue: [IMPALA-1652](#)

Workaround: Use the `RPAD()` function to blank-pad literals compared with CHAR columns to the expected length.

Tables and databases sharing same name can cause query failures

A table and a database that share the same name can cause a query failure if the table is not readable by Impala, for example, the table was created in Hive in the Open CSV Serde format. The following exception will return:

```
CAUSED BY: TableLoadingException: Unrecognized table type for table
```

Apache Issue: [IMPALA-8953](#)

Workaround: Do not create databases and tables with the same names.

Impala Known Issues: Limitations

These issues are current limitations of Impala that require evaluation as you plan how to integrate Impala into your data management workflow.

Set limits on size of expression trees

Very deeply nested expressions within queries can exceed internal Impala limits, leading to excessive memory usage.

Apache Issue: [IMPALA-4551](#)

Severity: High

Workaround: Avoid queries with extremely large expression trees. Setting the query option `disable_codegen=true` may reduce the impact, at a cost of longer query runtime.

Impala does not support running on clusters with federated namespaces

Impala does not support running on clusters with federated namespaces. The `impalad` process will not start on a node running such a filesystem based on the `org.apache.hadoop.fs.viewfs.ViewFs` class.

Apache Issue: [IMPALA-77](#)

Anticipated Resolution: Limitation

Workaround: Use standard HDFS on all Impala nodes.

Impala Known Issues: Miscellaneous

These issues do not fall into one of the above categories or have not been categorized yet.

A failed CTAS does not drop the table if the insert fails

If a `CREATE TABLE AS SELECT` operation successfully creates the target table but an error occurs while querying the source table or copying the data, the new table is left behind rather than being dropped.

Apache Issue: [IMPALA-2005](#)

Workaround: Drop the new table manually after a failed `CREATE TABLE AS SELECT`.

Casting scenarios with invalid/inconsistent results

Using a `CAST()` function to convert large literal values to smaller types, or to convert special values such as NaN or Inf, produces values not consistent with other database systems. This could lead to unexpected results from queries.

Apache Issue: [IMPALA-1821](#)

Impala should tolerate bad locale settings

If the `LC_*` environment variables specify an unsupported locale, Impala does not start.

Apache Issue: [IMPALA-532](#)

Workaround: Add `LC_ALL="C"` to the environment settings for both the Impala daemon and the Statestore daemon. See [Modifying Impala Startup Options](#) on page 32 for details about modifying these environment settings.

Resolution: Fixing this issue would require an upgrade to Boost 1.47 in the Impala distribution.

Log Level 3 Not Recommended for Impala

The extensive logging produced by log level 3 can cause serious performance overhead and capacity issues.

Workaround: Reduce the log level to its default value of 1, that is, `GLOG_v=1`. See [Setting Logging Levels](#) on page 787 for details about the effects of setting different logging levels.

Impala Known Issues: Crashes and Hangs

These issues can cause Impala to quit or become unresponsive.

Unable to view large catalog objects in catalogd Web UI

In `catalogd` Web UI, you can list metadata objects and view their details. These details are accessed via a link and printed to a string formatted using thrift's `DebugProtocol`. Printing large objects (> 1 GB) in Web UI can crash `catalogd`.

Apache Issue: [IMPALA-6841](#)

Fixed Issues in Apache Impala

The following sections describe the major issues fixed in each Impala release.

For known issues that are currently unresolved, see [Known Issues and Workarounds in Impala](#) on page 878.

Issues Fixed in Impala 4.0

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 4.0](#).

Issues Fixed in Impala 3.4

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 3.4](#).

Issues Fixed in Impala 3.3

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 3.3](#).

Issues Fixed in Impala 3.2

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 3.2](#).

The following is a list of noteworthy issues fixed in Impala 3.2:

- [IMPALA-341](#) - Remote profiles are no longer ignored by the coordinator for the queries with the LIMIT clause.
- [IMPALA-941](#) - Impala supports fully qualified table names that start with a number.
- [IMPALA-1048](#) - The query execution summary now includes the total time taken and memory consumed by the data sink at the root of each query fragment.
- [IMPALA-3323](#) - Fixed the issue where valid impala-shell options, such as `--ldap_password_cmd`, were unrecognized when the `--config_file` option was specified.
- [IMPALA-5397](#) - If a query has a dedicated coordinator, its end time is now set when the query releases its admission control resources. With no dedicated coordinator, the end time is set on un-registration.
- [IMPALA-5474](#) - Fixed an issue where adding a trivial subquery to a query with an error turns the error into a warning.
- [IMPALA-6521](#) - When set, experimental flags are now shown in /varz in web UI and log files.
- [IMPALA-6900](#) - INVALIDATE METADATA operation is no longer ignored when HMS is empty.
- [IMPALA-7446](#) - Impala enables buffer pool garbage collection when near process memory limit to prevent queries from spilling to disk earlier than necessary.
- [IMPALA-7659](#) - In COMPUTE STATS, Impala counts the number of NULL values in a table
- [IMPALA-7857](#) - Logs more information about StateStore failure detection.
- [IMPALA-7928](#) - To increase the efficiency of the HDFS file handle cache, remote reads for a particular file are scheduled to a consistent set of executor nodes.
- [IMPALA-7929](#) - Impala query on tables created via Hive and mapped to HBase failed with an internal exception because the qualifier of the HBase key column is null in the mapped table. Impala relaxed the requirement and allows a NULL qualifier.
- [IMPALA-7960](#) - Impala now returns a correct result when comparing TIMESTAMP to a string literal in a binary predicate where the TIMESTAMP is casted to VARCHAR of smaller length.
- [IMPALA-7961](#) - Fixed an issue where queries running with the SYNC_DDL query option can fail when the Catalog Server is under a heavy load with concurrent catalog operations of long-running DDLs.
- [IMPALA-8026](#) - Impala query profile now reports correct row counts for all nested loop join modes.
- [IMPALA-8061](#) - Impala correctly initializes S3_ACCESS_VALIDATED variable to zero when TARGET_FILESYSTEM=S3.
- [IMPALA-8154](#) - Disabled the Kerberos auth_to_local setting to prevent connection issues between impalads.
- [IMPALA-8188](#) - Impala now correctly detects an NVME device name and handles it.

- [IMPALA-8245](#) - Added hostname to the timeout error message to enable the user to easily identify the host which has reached a bad connection state with the HDFS NameNode.
- [IMPALA-8254](#) - COMPUTE STATS failed if COMPRESSION_CODEC is set.

Issues Fixed in Impala 3.1

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 3.1](#).

Issues Fixed in Impala 3.0

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 3.0](#).

Issues Fixed in Impala 2.12

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 2.12](#).

Issues Fixed in Impala 2.11

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 2.11](#).

Issues Fixed in Impala 2.10

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 2.10](#).

Issues Fixed in Impala 2.9.0

For the full list of issues closed in this release, including bug fixes, see the [changelog for Impala 2.9](#).

Issues Fixed in Impala 2.8.0

For the full list of Impala fixed issues in Impala 2.8, see [this report in the Impala JIRA tracker](#).

Issues Fixed in Impala 2.7.0

For the full list of Impala fixed issues in Impala 2.7.0, see [this report in the Impala JIRA tracker](#).

Issues Fixed in Impala 2.6.3

Issues Fixed in Impala 2.6.2

Issues Fixed in Impala 2.6.0

The following list contains the most critical fixed issues (priority='Blocker') from the JIRA system. For the full list of fixed issues in Impala 2.6.0, see [this report in the Impala JIRA tracker](#).

RuntimeState::error_log_ crashes

A crash could occur, with stack trace pointing to `impala::RuntimeState::ErrorLog`.

Bug: [IMPALA-3385](#)

Severity: High

HiveUdfCall::Open() produces unsynchronized access to JNIUtil::global_refs_vector

A crash could occur because of contention between multiple calls to Java UDFs.

Bug: [IMPALA-3378](#)

Severity: High

HBaseTableWriter::CreatePutList() produces unsynchronized access to JNIUtil::global_refs_vector

A crash could occur because of contention between multiple concurrent statements writing to HBase.

Bug: [IMPALA-3379](#)

Severity: High

Stress test failure: sorter.cc:745] Check failed: i == 0 (1 vs. 0)

A crash or wrong results could occur if the spill-to-disk mechanism encountered a zero-length string at the very end of a data block.

Bug: [IMPALA-3317](#)

Severity: High

String data coming out of agg can be corrupted by blocking operators

If a query plan contains an aggregation node producing string values anywhere within a subplan (that is, if in the SQL statement, the aggregate function appears within an inline view over a collection column), the results of the aggregation may be incorrect.

Bug: [IMPALA-3311](#)

Severity: High

CTAS with subquery throws AuthzException

A CREATE TABLE AS SELECT operation could fail with an authorization error, due to a slight difference in the privilege checking for the CTAS operation.

Bug: [IMPALA-3269](#)

Severity: High

Crash on inserting into table with binary and parquet

Impala incorrectly allowed BINARY to be specified as a column type, resulting in a crash during a write to a Parquet table with a column of that type.

Bug: [IMPALA-3237](#)

Severity: High

RowBatch::MaxTupleBufferSize() calculation incorrect, may lead to memory corruption

A crash could occur while querying tables with very large rows, for example wide tables with many columns or very large string values. This problem was identified in Impala 2.3, but had low reproducibility in subsequent releases. The fix ensures the memory allocation size is correct.

Bug: [IMPALA-3105](#)

Severity: High

Thrift buffer overflows when serialize more than 3355443200 bytes in impala

A very large memory allocation within the catalogd daemon could exceed an internal Thrift limit, causing a crash.

Bug: [IMPALA-3494](#)

Severity: High

Altering table partition's storage format is not working and crashing the daemon

If a partitioned table used a file format other than Avro, and the file format of an individual partition was changed to Avro, subsequent queries could encounter a crash.

Bug: [IMPALA-3314](#)

Severity: High

Race condition may cause scanners to spin with runtime filters on Avro or Sequence files

A timing problem during runtime filter processing could cause queries against Avro or SequenceFile tables to hang.

Bug: [IMPALA-3798](#)

Severity: High

Issues Fixed in Impala 2.5.4

Issues Fixed in Impala 2.5.2

Issues Fixed in Impala 2.5.1

Issues Fixed in Impala 2.5.0

The following list contains the most critical issues (priority= 'Blocker') from the JIRA system. For the full list of fixed issues in Impala 2.5, see [this report in the Impala JIRA tracker](#).

Stress test hit assert in LLVM: external function could not be resolved

Bug: [IMPALA-2683](#)

The stress test was running a build with the TPC-H, TPC-DS, and TPC-H nested queries with scale factor 3.

Impalad is crashing if udf jar is not available in hdfs location for first time

Bug: [IMPALA-2365](#)

If a UDF JAR was not available in the HDFS location specified in the CREATE FUNCTION statement, the impalad daemon could crash.

PAGG hits mem_limit when switching to I/O buffers

Bug: [IMPALA-2535](#)

A join query could fail with an out-of-memory error despite the apparent presence of sufficient memory. The cause was the internal ordering of operations that could cause a later phase of the query to allocate memory required by an earlier phase of the query. The workaround was to either increase or decrease the MEM_LIMIT query option, because the issue would only occur for a specific combination of memory limit and data volume.

Prevent migrating incorrectly inferred identity predicates into inline views

Bug: [IMPALA-2643](#)

Referring to the same column twice in a view definition could cause the view to omit rows where that column contained a NULL value. This could cause incorrect results due to an inaccurate COUNT (*) value or rows missing from the result set.

Fix migration/assignment of On-clause predicates inside inline views

Bug: [IMPALA-1459](#)

Some combinations of ON clauses in join queries could result in comparisons being applied at the wrong stage of query processing, leading to incorrect results. Wrong predicate assignment could happen under the following conditions:

- The query includes an inline view that contains an outer join.
- That inline view is joined with another table in the enclosing query block.

- That join has an ON clause containing a predicate that only references columns originating from the outer-joined tables inside the inline view.

Wrong plan of NOT IN aggregate subquery when a constant is used in subquery predicate

Bug: [IMPALA-2093](#)

IN subqueries might return wrong results if the left-hand side of the IN is a constant. For example:

```
select * from alltypestiny t1
where 10 not in (select sum(int_col) from alltypestiny);
```

Parquet DictDecoders accumulate throughout query

Bug: [IMPALA-2940](#)

Parquet dictionary decoders can accumulate throughout query execution, leading to excessive memory usage. One decoder is created per-column per-split.

Planner doesn't set the has_local_target field correctly

Bug: [IMPALA-3056](#)

MemPool allocation growth behavior

Bug: [IMPALA-2742](#)

Currently, the MemPool would always double the size of the last allocation. This can lead to bad behavior if the MemPool transferred the ownership of all its data except the last chunk. In the next allocation, the next allocated chunk would double the size of this large chunk, which can be undesirable.

Drop partition operations don't follow the catalog's locking protocol

Bug: [IMPALA-3035](#)

The `CatalogOpExecutor.alterTableDropPartition()` function violates the locking protocol used in the catalog that requires `catalogLock_` to be acquired before any table-level lock. That may cause deadlocks when `ALTER TABLE DROP PARTITION` is executed concurrently with other DDL operations.

HAVING clause without aggregation not applied properly

Bug: [IMPALA-2215](#)

A query with a HAVING clause but no GROUP BY clause was not being rejected, despite being invalid syntax. For example:

```
select case when 1=1 then 'didit' end as c1 from (select 1 as one) a having
1!=1;
```

Hit DCHECK Check failed: HasDateOrTime()

Bug: [IMPALA-2914](#)

`TimestampValue::ToTimestampVal()` requires a valid `TimestampValue` as input. This requirement was not enforced in some places, leading to serious errors.

Aggregation spill loop gives up too early leading to mem limit exceeded errors

Bug: [IMPALA-2986](#)

An aggregation query could fail with an out-of-memory error, despite sufficient memory being reported as available.

DataStreamSender::Channel::CloseInternal() does not close the channel on an error.

Bug: *IMPALA-2592*

Some queries do not close an internal communication channel on an error. This will cause the node on the other side of the channel to wait indefinitely, causing the query to hang. For example, this issue could happen on a Kerberos-enabled system if the credential cache was outdated. Although the affected query hangs, the `impalad` daemons continue processing other queries.

Codegen does not catch exceptions in FROM_UNIXTIME()

Bug: *IMPALA-2184*

Querying for the min or max value of a timestamp cast from a bigint via `from_unixtime()` fails silently and crashes instances of `impalad` when the input includes a value outside of the valid range.

Workaround: Disable native code generation with:

```
SET disable_codegen=true;
```

Impala returns wrong result for function 'conv(bigint, from base, to base)'

Bug: *IMPALA-2788*

Impala returns wrong result for function `conv()`. Function `conv(bigint, from_base, to_base)` returns an correct result, while `conv(string, from base, to base)` returns the correct value. For example:

```
select 2061013007, conv(2061013007, 16, 10), conv('2061013007', 16, 10);
```

2061013007	conv(2061013007, 16, 10)	conv('2061013007', 16, 10)
2061013007	1627467783	139066421255

Fetches 1 row(s) in 0.65s

```
select 2061013007, conv(cast(2061013007 as bigint), 16, 10),  
       conv('2061013007', 16, 10);
```

2061013007	conv(cast(2061013007 as bigint), 16, 10)	conv('2061013007', 16, 10)
2061013007	1627467783	139066421255

```
select 2061013007, conv(cast(2061013007 as string), 16, 10),  
       conv('2061013007', 16, 10);
```

2061013007	conv(cast(2061013007 as string), 16, 10)	conv('2061013007', 16, 10)
2061013007	139066421255	139066421255

```

select 2061013007, conv(cast(cast(2061013007 as decimal(20,0)) as bigint),
16, 10), conv('2061013007', 16, 10);
+-----+
+-----+
+-----+
| 2061013007 | conv(cast(cast(2061013007 as decimal(20,0)) as bigint), 16,
10) | conv('2061013007', 16, 10) |
+-----+
+-----+
+-----+
| 2061013007 | 1627467783
| 139066421255 |
+-----+
+-----+
+-----+

```

Workaround: Cast the value to string and use `conv(string, from_base, to_base)` for conversion.

Issues Fixed in Impala 2.4.1

Issues Fixed in Impala 2.4.0

The set of fixes for Impala in Impala 2.4.0 is the same as in Impala 2.3.2.

Issues Fixed in Impala 2.3.4

Issues Fixed in Impala 2.3.2

This section lists the most serious or frequently encountered customer issues fixed in Impala 2.3.2.

SEGV in AnalyticEvalNode touching NULL input_stream_

A query involving an analytic function could encounter a serious error. This issue was encountered infrequently, depending upon specific combinations of queries and data.

Bug: [IMPALA-2829](#)

Free local allocations per row batch in non-partitioned AGG and HJ

An outer join query could fail unexpectedly with an out-of-memory error when the “spill to disk” mechanism was turned off.

Bug: [IMPALA-2722](#)

Free local allocations once for every row batch when building hash tables

A join query could encounter a serious error due to an internal failure to allocate memory, which resulted in dereferencing a NULL pointer.

Bug: [IMPALA-2612](#)

Prevent migrating incorrectly inferred identity predicates into inline views

Referring to the same column twice in a view definition could cause the view to omit rows where that column contained a NULL value. This could cause incorrect results due to an inaccurate `COUNT(*)` value or rows missing from the result set.

Bug: [IMPALA-2643](#)

Fix GRANTs on URIs with uppercase letters

A GRANT statement for a URI could be ineffective if the URI contained uppercase letters, for example in an uppercase directory name. Subsequent statements, such as `CREATE EXTERNAL TABLE` with a `LOCATION` clause, could fail with an authorization exception.

Bug: [IMPALA-2695](#)

Avoid sending large partition stats objects over thrift

The `catalogd` daemon could encounter a serious error when loading the incremental statistics metadata for tables with large numbers of partitions and columns. The problem occurred when the internal representation of metadata for the table exceeded 2 GB, for example in a table with 20K partitions and 77 columns. The fix causes a `COMPUTE INCREMENTAL STATS` operation to fail if it would produce metadata that exceeded the maximum size.

Bug: [IMPALA-2664](#), [IMPALA-2648](#)

Throw AnalysisError if table properties are too large (for the Hive metastore)

`CREATE TABLE` or `ALTER TABLE` statements could fail with metastore database errors due to length limits on the `SERDEPROPERTIES` and `TBLPROPERTIES` clauses. (The limit on key size is 256, while the limit on value size is 4000.) The fix makes Impala handle these error conditions more cleanly, by detecting too-long values rather than passing them to the metastore database.

Bug: [IMPALA-2226](#)

Make MAX_PAGE_HEADER_SIZE configurable

Impala could fail to access Parquet data files with page headers larger than 8 MB, which could occur, for example, if the minimum or maximum values for a column were long strings. The fix adds a configuration setting -- `max_page_header_size`, which you can use to increase the Impala size limit to a value higher than 8 MB.

Bug: [IMPALA-2273](#)

reduce scanner memory usage

Queries on Parquet tables could consume excessive memory (potentially multiple gigabytes) due to producing large intermediate data values while evaluating groups of rows. The workaround was to reduce the size of the `NUM_SCANNER_THREADS` query option, the `BATCH_SIZE` query option, or both.

Bug: [IMPALA-2473](#)

Handle error when distinct and aggregates are used with a having clause

A query that included a `DISTINCT` operator and a `HAVING` clause, but no aggregate functions or `GROUP BY`, would fail with an uninformative error message.

Bug: [IMPALA-2113](#)

Handle error when star based select item and aggregate are incorrectly used

A query that included `*` in the `SELECT` list, in addition to an aggregate function call, would fail with an uninformative message if the query had no `GROUP BY` clause.

Bug: [IMPALA-2225](#)

Refactor MemPool usage in HBase scan node

Queries involving HBase tables used substantially more memory than in earlier Impala versions. The problem occurred starting in Impala 2.2.8, as a result of the changes for [IMPALA-2284](#). The fix for this issue involves removing a separate memory work area for HBase queries and reusing other memory that was already allocated.

Bug: [IMPALA-2731](#)

Fix migration/assignment of On-clause predicates inside inline views

Some combinations of ON clauses in join queries could result in comparisons being applied at the wrong stage of query processing, leading to incorrect results. Wrong predicate assignment could happen under the following conditions:

- The query includes an inline view that contains an outer join.
- That inline view is joined with another table in the enclosing query block.
- That join has an ON clause containing a predicate that only references columns originating from the outer-joined tables inside the inline view.

Bug: [IMPALA-1459](#)

DCHECK in parquet scanner after block read error

A debug build of Impala could encounter a serious error after encountering some kinds of I/O errors for Parquet files. This issue only occurred in debug builds, not release builds.

Bug: [IMPALA-2558](#)

PAGG hits mem_limit when switching to I/O buffers

A join query could fail with an out-of-memory error despite the apparent presence of sufficient memory. The cause was the internal ordering of operations that could cause a later phase of the query to allocate memory required by an earlier phase of the query. The workaround was to either increase or decrease the MEM_LIMIT query option, because the issue would only occur for a specific combination of memory limit and data volume.

Bug: [IMPALA-2535](#)

Fix check failed: sorter_runs_.back()->is_pinned_

A query could fail with an internal error while calculating the memory limit. This was an infrequent condition uncovered during stress testing.

Bug: [IMPALA-2559](#)

Don't ignore Status returned by DataStreamRecvr::CreateMerger()

A query could fail with an internal error while calculating the memory limit. This was an infrequent condition uncovered during stress testing.

Bug: [IMPALA-2614](#), [IMPALA-2559](#)

DataStreamSender::Send() does not return an error status if SendBatch() failed

Bug: [IMPALA-2591](#)

Re-enable SSL and Kerberos on server-server

These fixes lift the restriction on using SSL encryption and Kerberos authentication together for internal communication between Impala components.

Bug: [IMPALA-2598](#), [IMPALA-2747](#)

Issues Fixed in Impala 2.3.1

The version of Impala that is included with Impala 2.3.1 is identical to Impala 2.3.0. There are no new bug fixes, new features, or incompatible changes.

Issues Fixed in Impala 2.3.0

This section lists the most serious or frequently encountered customer issues fixed in Impala 2.3. Any issues already fixed in Impala 2.2 maintenance releases (up through Impala 2.2.8) are also included. Those issues are listed under the respective Impala 2.2 sections and are not repeated here.

Fixes for Serious Errors

A number of issues were resolved that could result in serious errors when encountered. The most critical or commonly encountered are listed here.

Bugs: [IMPALA-2168](#), [IMPALA-2378](#), [IMPALA-2369](#), [IMPALA-2357](#), [IMPALA-2319](#), [IMPALA-2314](#), [IMPALA-2016](#)

Fixes for Correctness Errors

A number of issues were resolved that could result in wrong results when encountered. The most critical or commonly encountered are listed here.

Bugs: [IMPALA-2192](#), [IMPALA-2440](#), [IMPALA-2090](#), [IMPALA-2086](#), [IMPALA-1947](#), [IMPALA-1917](#)

Issues Fixed in Impala 2.2.10

Issues Fixed in Impala 2.2.9

This section lists the most frequently encountered customer issues fixed in Impala 2.2.9.

Query return empty result if it contains NULLLiteral in inlineview

If an inline view in a FROM clause contained a NULL literal, the result set was empty.

Bug: [IMPALA-1917](#)

HBase scan node uses 2-4x memory after upgrade to Impala 2.2.8

Queries involving HBase tables used substantially more memory than in earlier Impala versions. The problem occurred starting in Impala 2.2.8, as a result of the changes for [IMPALA-2284](#). The fix for this issue involves removing a separate memory work area for HBase queries and reusing other memory that was already allocated.

Bug: [IMPALA-2731](#)

Fix migration/assignment of On-clause predicates inside inline views

Some combinations of ON clauses in join queries could result in comparisons being applied at the wrong stage of query processing, leading to incorrect results. Wrong predicate assignment could happen under the following conditions:

- The query includes an inline view that contains an outer join.
- That inline view is joined with another table in the enclosing query block.
- That join has an ON clause containing a predicate that only references columns originating from the outer-joined tables inside the inline view.

Bug: [IMPALA-1459](#)

Fix wrong predicate assignment in outer joins

The join predicate for an OUTER JOIN clause could be applied at the wrong stage of query processing, leading to incorrect results.

Bug: [IMPALA-2446](#)

Avoid sending large partition stats objects over thrift

The catalogd daemon could encounter a serious error when loading the incremental statistics metadata for tables with large numbers of partitions and columns. The problem occurred when the internal representation of metadata for the table exceeded 2 GB, for example in a table with 20K partitions and 77 columns. The fix causes a COMPUTE INCREMENTAL STATS operation to fail if it would produce metadata that exceeded the maximum size.

Bug: [IMPALA-2648](#), [IMPALA-2664](#)

Avoid overflow when adding large intervals to TIMESTAMPS

Adding or subtracting a large `INTERVAL` value to a `TIMESTAMP` value could produce an incorrect result, with the value wrapping instead of returning an out-of-range error.

Bug: [IMPALA-1675](#)

Analysis exception when a binary operator contains an IN operator with values

An `IN` operator with literal values could cause a statement to fail if used as the argument to a binary operator, such as an equality test for a `BOOLEAN` value.

Bug: [IMPALA-1949](#)

Make MAX_PAGE_HEADER_SIZE configurable

Impala could fail to access Parquet data files with page headers larger than 8 MB, which could occur, for example, if the minimum or maximum values for a column were long strings. The fix adds a configuration setting `--max_page_header_size`, which you can use to increase the Impala size limit to a value higher than 8 MB.

Bug: [IMPALA-2273](#)

Fix spilling sorts with var-len slots that are NULL or empty.

A query that activated the spill-to-disk mechanism could fail if it contained a sort expression involving certain combinations of fixed-length or variable-length types.

Bug: [IMPALA-2357](#)

Work-around IMPALA-2344: Fail query with OOM in case block->Pin() fails

Some queries that activated the spill-to-disk mechanism could produce a serious error if there was insufficient memory to set up internal work areas. Now those queries produce normal out-of-memory errors instead.

Bug: [IMPALA-2344](#)

Crash (likely race) tearing down BufferedBlockMgr on query failure

A serious error could occur under rare circumstances, due to a race condition while freeing memory during heavily concurrent workloads.

Bug: [IMPALA-2252](#)

QueryExecState doesn't check for query cancellation or errors

A call to `SetError()` in a user-defined function (UDF) would not cause the query to fail as expected.

Bug: [IMPALA-1746](#)

Impala throws IllegalStateException when inserting data into a partition while select subquery group by partition columns

An `INSERT ... SELECT` operation into a partitioned table could fail if the `SELECT` query included a `GROUP BY` clause referring to the partition key columns.

Bug: [IMPALA-2533](#)

Issues Fixed in Impala 2.2.8

This section lists the most frequently encountered customer issues fixed in Impala 2.2.8.

Impala is unable to read hive tables created with the "STORED AS AVRO" clause

Impala could not read Avro tables created in Hive with the `STORED AS AVRO` clause.

Bug: [IMPALA-1136](#), [IMPALA-2161](#)

make Parquet scanner fail query if the file size metadata is stale

If a Parquet file in HDFS was overwritten by a smaller file, Impala could encounter a serious error. Issuing a `INVALIDATE METADATA` statement before a subsequent query would avoid the error. The fix allows Impala to handle such inconsistencies in Parquet file length cleanly regardless of whether the table metadata is up-to-date.

Bug: [IMPALA-2213](#)

Avoid allocating StringBuffer > 1GB in ScannerContext::Stream::GetBytesInternal()

Impala could encounter a serious error when reading compressed text files larger than 1 GB. The fix causes Impala to issue an error message instead in this case.

Bug: [IMPALA-2249](#)

Disallow long (1<<30) strings in group_concat()

A query using the `group_concat ()` function could encounter a serious error if the returned string value was larger than 1 GB. Now the query fails with an error message in this case.

Bug: [IMPALA-2284](#)

avoid FnvHash64to32 with empty inputs

An edge case in the algorithm used to distribute data among nodes could result in uneven distribution of work for some queries, with all data sent to the same node.

Bug: [IMPALA-2270](#)

The catalog does not close the connection to HMS during table invalidation

A communication error could occur between Impala and the Hive metastore database, causing Impala operations that update table metadata to fail.

Bug: [IMPALA-2348](#)

Wrong DCHECK in PHJ::ProcessProbeBatch

Certain queries could encounter a serious error if the spill-to-disk mechanism was activated.

Bug: [IMPALA-2364](#)

Avoid cardinality 0 in scan nodes of small tables and low selectivity

Impala could generate a suboptimal query plan for some queries involving small tables.

Bug: [IMPALA-2165](#)

Issues Fixed in Impala 2.2.7

This section lists the most frequently encountered customer issues fixed in Impala 2.2.7.

Warn if table stats are potentially corrupt.

Impala warns if it detects a discrepancy in table statistics: a table considered to have zero rows even though there are data files present. In this case, Impala also skips query optimizations that are normally applied to very small tables.

Bug: [IMPALA-1983](#)

Pass correct child node in 2nd phase merge aggregation.

A query could encounter a serious error if it included a particular combination of aggregate functions and inline views.

Bug: [IMPALA-2266](#)

Set the output smap of an EmptySetNode produced from an empty inline view.

A query could encounter a serious error if it included an inline view whose subquery had no FROM clause.

Bug: [IMPALA-2216](#)

Set an InsertStmt's result exprs from the source statement's result exprs.

A CREATE TABLE AS SELECT or INSERT . . . SELECT statement could produce different results than a SELECT statement, for queries including a FULL JOIN clause and including literal values in the select list.

Bug: [IMPALA-2203](#)

Fix planning of empty union operands with analytics.

A query could return incorrect results if it contained a UNION clause, calls to analytic functions, and a constant expression that evaluated to FALSE.

Bug: [IMPALA-2088](#)

Retain eq predicates bound by grouping slots with complex grouping exprs.

A query containing an INNER JOIN clause could return undesired rows. Some predicate specified in the ON clause could be omitted from the filtering operation.

Bug: [IMPALA-2089](#)

Row count not set for empty partition when spec is used with compute incremental stats

A COMPUTE INCREMENTAL STATS statement could leave the row count for an empty partition as -1, rather than initializing the row count to 0. The missing statistic value could result in reduced query performance.

Bug: [IMPALA-2199](#)

Explicit aliases + ordinals analysis bug

A query could encounter a serious error if it included column aliases with the same names as table columns, and used ordinal numbers in an ORDER BY or GROUP BY clause.

Bug: [IMPALA-1898](#)

Fix TupleIsNotNullPredicate to return false if no tuples are nullable.

A query could return incorrect results if it included an outer join clause, inline views, and calls to functions such as coalesce() that can generate NULL values.

Bug: [IMPALA-1987](#)

fix Expr::ComputeResultsLayout() logic

A query could return incorrect results if the table contained multiple CHAR columns with length of 2 or less, and the query included a GROUP BY clause that referred to multiple such columns.

Bug: [IMPALA-2178](#)

Substitute an InsertStmt's partition key exprs with the root node's smap.

An INSERT statement could encounter a serious error if the SELECT portion called an analytic function.

Bug: [IMPALA-1737](#)

Issues Fixed in Impala Impala 2.2.5

This section lists the most frequently encountered customer issues fixed in Impala 2.2.5.

Impala DML/DDL operations corrupt table metadata leading to Hive query failures

When the Impala `COMPUTE STATS` statement was run on a partitioned Parquet table that was created in Hive, the table subsequently became inaccessible in Hive. The table was still accessible to Impala. Regaining access in Hive required a workaround of creating a new table. The error displayed in Hive was:

```
Error: Error while compiling statement: FAILED: SemanticException
Class not found: org.apache.impala.hive.serde.ParquetInputFormat
(state=42000,code=40000)
```

Bug: [IMPALA-2048](#)

Avoiding a DCHECK of NULL hash table in spilled right joins

A query could encounter a serious error if it contained a `RIGHT OUTER`, `RIGHT ANTI`, or `FULL OUTER` join clause and approached the memory limit on a host so that the “spill to disk” mechanism was activated.

Bug: [IMPALA-1929](#)

Bug in PrintTColumnValue caused wrong stats for TINYINT partition cols

Declaring a partition key column as a `TINYINT` caused problems with the `COMPUTE STATS` statement. The associated partitions would always have zero estimated rows, leading to potential inefficient query plans.

Bug: [IMPALA-2136](#)

Where clause does not propagate to joins inside nested views

A query that referred to a view whose query referred to another view containing a join, could return incorrect results. `WHERE` clauses for the outermost query were not always applied, causing the result set to include additional rows that should have been filtered out.

Bug: [IMPALA-2018](#)

Add effective_user() builtin

The `user()` function returned the name of the logged-in user, which might not be the same as the user name being checked for authorization if, for example, delegation was enabled.

Bug: [IMPALA-2064](#)

Resolution: Rather than change the behavior of the `user()` function, the fix introduces an additional function `effective_user()` that returns the user name that is checked during authorization.

Make UTC to local TimestampValue conversion faster.

Query performance was improved substantially for Parquet files containing `TIMESTAMP` data written by Hive, when the `-convert_legacy_hive_parquet_utc_timestamps=true` setting is in effect.

Bug: [IMPALA-2125](#)

Workaround IMPALA-1619 in BufferedBlockMgr::ConsumeMemory()

A join query could encounter a serious error if the query approached the memory limit on a host so that the “spill to disk” mechanism was activated, and data volume in the join was large enough that an internal memory buffer exceeded 1 GB in size on a particular host. (Exceeding this limit would only happen for huge join queries, because Impala could split this intermediate data into 16 parts during the join query, and the buffer only contains compact bookkeeping data rather than the actual join column data.)

Bug: [IMPALA-2065](#)

Issues Fixed in Impala 2.2.3

This section lists the most frequently encountered customer issues fixed in Impala 2.2.3.

Enable using Isilon as the underlying filesystem.

Enabling Impala to work with the Isilon filesystem involves a number of fixes to performance and flexibility for dealing with I/O using remote reads. See [Using Impala with Isilon Storage](#) on page 783 for details on using Impala and Isilon together.

Bug: [IMPALA-1968](#), [IMPALA-1730](#)

Expand set of supported timezones.

The set of timezones recognized by Impala was expanded. You can always find the latest list of supported timezones in the Impala source code, in the file [timezone_db.cc](#).

Bug: [IMPALA-1381](#)

Impala Timestamp ISO-8601 Support.

Impala can now process `TIMESTAMP` literals including a trailing `z`, signifying “Zulu” time, a synonym for UTC.

Bug: [IMPALA-1963](#)

Fix wrong warning when insert overwrite to empty table

An `INSERT OVERWRITE` operation would encounter an error if the `SELECT` portion of the statement returned zero rows, such as with a `LIMIT 0` clause.

Bug: [IMPALA-2008](#)

Expand parsing of decimals to include scientific notation

`DECIMAL` literals can now include `e` scientific notation. For example, now `CAST(1e3 AS DECIMAL(5,3))` is a valid expression. Formerly it returned `NULL`. Some scientific expressions might have worked before in `DECIMAL` context, but only when the scale was 0.

Bug: [IMPALA-1952](#)

Issues Fixed in Impala 2.2.1

This section lists the most frequently encountered customer issues fixed in Impala 2.2.1.

Issues Fixed in Impala 2.2.0

This section lists the most frequently encountered customer issues fixed in Impala 2.2.0.

For the full list of fixed issues in Impala 2.2.0, including over 40 critical issues, see [this report in the Impala JIRA tracker](#).

Altering a column's type causes column stats to stop sticking for that column

When the type of a column was changed in either Hive or Impala through `ALTER TABLE CHANGE COLUMN`, the metastore database did not correctly propagate that change to the table that contains the column statistics. The statistics (particularly the NDV) for that column were permanently reset and could not be changed by Impala's `COMPUTE STATS` command. The underlying cause is a Hive bug (HIVE-9866).

Bug: [IMPALA-1607](#)

Resolution: Resolved by incorporating the fix for [HIVE-9866](#).

Workaround: On systems without the corresponding Hive fix, change the column back to its original type. The stats reappear and you can recompute or drop them.

Impala may leak or use too many file descriptors

If a file was truncated in HDFS without a corresponding `REFRESH` in Impala, Impala could allocate memory for file descriptors and not free that memory.

Bug: [IMPALA-1854](#)

Spurious stale block locality messages

Impala could issue messages stating the block locality metadata was stale, when the metadata was actually fine. The internal “remote bytes read” counter was not being reset properly. This issue did not cause an actual slowdown in query execution, but the spurious error could result in unnecessary debugging work and unnecessary use of the `INVALIDATE METADATA` statement.

Bug: [IMPALA-1712](#)

DROP TABLE fails after COMPUTE STATS and ALTER TABLE RENAME to a different database.

When a table was moved from one database to another, the column statistics were not pointed to the new database. This could result in lower performance for queries due to unavailable statistics, and also an inability to drop the table.

Bug: [IMPALA-1711](#)

IMPALA-1556 causes memory leak with secure connections

`impalad` daemons could experience a memory leak on clusters using Kerberos authentication, with memory usage growing as more data is transferred across the secure channel, either to the client program or between Impala nodes. The same issue affected LDAP-secured clusters to a lesser degree, because the LDAP security only covers data transferred back to client programs.

Bug: [IMPALA-1674](#)

unix_timestamp() does not return correct time

The `unix_timestamp()` function could return an incorrect value (a constant value of 1).

Bug: [IMPALA-1623](#)

Impala incorrectly handles text data missing a newline on the last line

Some queries did not recognize the final line of a text data file if the line did not end with a newline character. This could lead to inconsistent results, such as a different number of rows for `SELECT COUNT(*)` as opposed to `SELECT *`.

Bug: [IMPALA-1476](#)

Impala's ACLs check do not consider all group ACLs, only checked first one.

If the HDFS user ID associated with the `impalad` process had read or write access in HDFS based on group membership, Impala statements could still fail with HDFS permission errors if that group was not the first listed group for that user ID.

Bug: [IMPALA-1805](#)

Fix infinite loop opening or closing file with invalid metadata

Truncating a file in HDFS, after Impala had cached the file metadata, could produce a hang when Impala queried a table containing that file.

Bug: [IMPALA-1794](#)

Cannot write Parquet files when values are larger than 64KB

Impala could sometimes fail to `INSERT` into a Parquet table if a column value such as a `STRING` was larger than 64 KB.

Bug: [IMPALA-1705](#)

Impala Will Not Run on Certain Intel CPUs

This fix relaxes the CPU requirement for Impala. Now only the SSSE3 instruction set is required. Formerly, SSE4.1 instructions were generated, making Impala refuse to start on some older CPUs.

Bug: [IMPALA-1646](#)

Issues Fixed in Impala 2.1.10

Issues Fixed in Impala 2.1.7

This section lists the most significant Impala issues fixed in Impala 2.1.7.

Query return empty result if it contains NullLiteral in inlineview

If an inline view in a FROM clause contained a NULL literal, the result set was empty.

Bug: [IMPALA-1917](#)

Fix edge cases for decimal/integer cast

A value of type `DECIMAL(3, 0)` could be incorrectly cast to `TINYINT`. The resulting out-of-range value could be incorrect. After the fix, the smallest type that is allowed for this cast is `INT`, and attempting to use `DECIMAL(3, 0)` in a `TINYINT` context produces a “loss of precision” error.

Bug: [IMPALA-2264](#)

Constant filter expressions are not checked for errors and state cleanup on exception / DCHECK on destroying an ExprContext

An invalid constant expression in a WHERE clause (for example, an invalid regular expression pattern) could fail to clean up internal state after raising a query error. Therefore, certain combinations of invalid expressions in a query could cause a crash, or cause a query to continue when it should halt with an error.

Bug: [IMPALA-1756](#), [IMPALA-2514](#)

QueryExecState does not check for query cancellation or errors

A call to `SetError()` in a user-defined function (UDF) would not cause the query to fail as expected.

Bug: [IMPALA-1746](#), [IMPALA-2141](#)

Issues Fixed in Impala 2.1.6

This section lists the most significant Impala issues fixed in Impala 2.1.6.

Wrong DCHECK in PHJ::ProcessProbeBatch

Certain queries could encounter a serious error if the spill-to-disk mechanism was activated.

Bug: [IMPALA-2364](#)

LargestSpilledPartition was not checking if partition is closed

Certain queries could encounter a serious error if the spill-to-disk mechanism was activated.

Bug: [IMPALA-2314](#)

Avoid cardinality 0 in scan nodes of small tables and low selectivity

Impala could generate a suboptimal query plan for some queries involving small tables.

Bug: [IMPALA-2165](#)

fix Expr::ComputeResultsLayout() logic

Queries using the `GROUP BY` operator on multiple `CHAR` columns with length less than or equal to 2 characters could return incorrect results for some columns.

Bug: [IMPALA-2178](#)

Properly unescape string value for HBase filters

Queries against HBase tables could return incomplete results if the `WHERE` clause included string comparisons using literals containing escaped quotation marks.

Bug: [IMPALA-2133](#)

Avoiding a DCHECK of NULL hash table in spilled right joins

A query could encounter a serious error if it contained a `RIGHT OUTER`, `RIGHT ANTI`, or `FULL OUTER` join clause and approached the memory limit on a host so that the “spill to disk” mechanism was activated.

Bug: [IMPALA-1929](#)

Issues Fixed in Impala 2.1.5

This section lists the most significant Impala issues fixed in Impala 2.1.5.

Avoid calling ProcessBatch with out_batch->AtCapacity in right joins

Queries including `RIGHT OUTER JOIN`, `RIGHT ANTI JOIN`, or `FULL OUTER JOIN` clauses and involving a high volume of data could encounter a serious error.

Bug: [IMPALA-1919](#)

Issues Fixed in Impala 2.1.4

This section lists the most significant Impala issues fixed in Impala 2.1.4.

Crash: impala::TuplesIsNullPredicate::Prepare

When expressions that tested for `NULL` were used in combination with analytic functions, an error could occur. (The original crash issue was fixed by an earlier patch.)

Bug: [IMPALA-1519](#)

Expand parsing of decimals to include scientific notation

`DECIMAL` literals could include `e` scientific notation. For example, now `CAST(1e3 AS DECIMAL(5,3))` is a valid expression. Formerly it returned `NULL`. Some scientific expressions might have worked before in `DECIMAL` context, but only when the scale was 0.

Bug: [IMPALA-1952](#)

INSERT/CTAS evaluates and applies constant predicates.

An `INSERT OVERWRITE` statement would write new data, even if a constant clause such as `WHERE 1 = 0` should have prevented it from writing any rows.

Bug: [IMPALA-1860](#)

Assign predicates below analytic functions with a compatible partition by clause

If the `PARTITION BY` clause in an analytic function refers to partition key columns in a partitioned table, now Impala can perform partition pruning during the analytic query.

Bug: [IMPALA-1900](#)

FIRST_VALUE may produce incorrect results with preceding windows

A query using the `FIRST_VALUE` analytic function and a window defined with the `PRECEDING` keyword could produce wrong results.

Bug: [IMPALA-1888](#)

FIRST_VALUE rewrite fn type might not match slot type

A query referencing a `DECIMAL` column with the `FIRST_VALUE` analytic function could encounter an error.

Bug: [IMPALA-1559](#)

AnalyticEvalNode cannot handle partition/order by exprs with NaN

A query using an analytic function could encounter an error if the evaluation of an analytic `ORDER BY` or `PARTITION` expression resulted in a NaN value, for example if the `ORDER BY` or `PARTITION` contained a division operation where both operands were zero.

Bug: [IMPALA-1808](#)

AnalyticEvalNode not properly handling nullable tuples

An analytic function containing only an `OVER` clause could encounter an error if another part of the query (specifically an outer join) produced all-NULL tuples.

Bug: [IMPALA-1562](#)

Issues Fixed in Impala 2.1.3

This section lists the most significant issues fixed in Impala 2.1.3.

Add compatibility flag for Hive-Parquet-Timestamps

When Hive writes `TIMESTAMP` values, it represents them in the local time zone of the server. Impala expects `TIMESTAMP` values to always be in the UTC time zone, possibly leading to inconsistent results depending on which component created the data files. This patch introduces a new startup flag, `-convert_legacy_hive_parquet_utc_timestamps` for the `impalad` daemon. Specify `-convert_legacy_hive_parquet_utc_timestamps=true` to make Impala recognize Parquet data files written by Hive and automatically adjust `TIMESTAMP` values read from those files into the UTC time zone for compatibility with other Impala `TIMESTAMP` processing. Although this setting is currently turned off by default, consider enabling it if practical in your environment, for maximum interoperability with Hive-created Parquet files.

Bug: [IMPALA-1658](#)

Use `snprintf()` instead of `lexical_cast()` in float-to-string casts

Converting a floating-point value to a `STRING` could be slower than necessary.

Bug: [IMPALA-1738](#)

Fix partition spilling cleanup when new stream OOMs

Certain calls to aggregate functions with `STRING` arguments could encounter a serious error when the system ran low on memory and attempted to activate the spill-to-disk mechanism. The error message referenced the function `impala::AggregateFunctions::StringValGetValue`.

Bug: [IMPALA-1865](#)

Impala's ACLs check do not consider all group ACLs, only checked first one.

If the HDFS user ID associated with the `impalad` process had read or write access in HDFS based on group membership, Impala statements could still fail with HDFS permission errors if that group was not the first listed group for that user ID.

Bug: [IMPALA-1805](#)

Fix infinite loop opening or closing file with invalid metadata

Truncating a file in HDFS, after Impala had cached the file metadata, could produce a hang when Impala queried a table containing that file.

Bug: [IMPALA-1794](#)

external-data-source-executor leaking global jni refs

Successive calls to the data source API could result in excessive memory consumption, with memory allocated but never freed.

Bug: [IMPALA-1801](#)

Spurious stale block locality messages

Impala could issue messages stating the block locality metadata was stale, when the metadata was actually fine. The internal “remote bytes read” counter was not being reset properly. This issue did not cause an actual slowdown in query execution, but the spurious error could result in unnecessary debugging work and unnecessary use of the `INVALIDATE METADATA` statement.

Bug: [IMPALA-1712](#)

Issues Fixed in Impala 2.1.2

This section lists the most significant issues fixed in Impala 2.1.2.

For the full list of fixed issues in Impala 2.1.2, see [this report in the Impala JIRA tracker](#).

Impala incorrectly handles double numbers with more than 19 significant decimal digits

When a floating-point value was read from a text file and interpreted as a `FLOAT` or `DOUBLE` value, it could be incorrectly interpreted if it included more than 19 significant digits.

Bug: [IMPALA-1622](#)

unix_timestamp() does not return correct time

The `unix_timestamp()` function could return an incorrect value (a constant value of 1).

Bug: [IMPALA-1623](#)

Row Count Mismatch: Partition pruning with NULL

A query against a partitioned table could return incorrect results if the `WHERE` clause compared the partition key to `NULL` using operators such as `=` or `!=`.

Bug: [IMPALA-1535](#)

Fetch column stats in bulk using new (Hive .13) HMS APIs

The performance of the `COMPUTE STATS` statement and queries was improved, particularly for wide tables.

Bug: [IMPALA-1120](#)

Issues Fixed in Impala 2.1.1

This section lists the most significant issues fixed in Impala 2.1.1.

For the full list of fixed issues in Impala 2.1.1, see [this report in the Impala JIRA tracker](#).

IMPALA-1556 causes memory leak with secure connections

impalad daemons could experience a memory leak on clusters using Kerberos authentication, with memory usage growing as more data is transferred across the secure channel, either to the client program or between Impala nodes. The same issue affected LDAP-secured clusters to a lesser degree, because the LDAP security only covers data transferred back to client programs.

Bug: <https://issues.apache.org/jira/browse/IMPALA-1674> IMPALA-1674

TSaslServerTransport::Factory::getTransport() leaks transport map entries

impalad daemons in clusters secured by Kerberos or LDAP could experience a slight memory leak on each connection. The accumulation of unreleased memory could cause problems on long-running clusters.

Bug: [IMPALA-1668](#)

Issues Fixed in Impala 2.1.0

This section lists the most significant issues fixed in Impala 2.1.0.

For the full list of fixed issues in Impala 2.1.0, see [this report in the Impala JIRA tracker](#).

Kerberos fetches 3x slower

Transferring large result sets back to the client application on Kerberos

Bug: [IMPALA-1455](#)

Compressed file needs to be hold on entirely in Memory

Queries on gzipped text files required holding the entire data file and its uncompressed representation in memory at the same time. SELECT and COMPUTE STATS statements could fail or perform inefficiently as a result. The fix enables streaming reads for gzipped text, so that the data is uncompressed as it is read.

Bug: [IMPALA-1556](#)

Cannot read hbase metadata with NullPointerException: null

Impala might not be able to access HBase tables, depending on the associated levels of Impala and HBase on the system.

Bug: [IMPALA-1611](#)

Serious errors / crashes

Improved code coverage in Impala testing uncovered a number of potentially serious errors that could occur with specific query syntax. These errors are resolved in Impala 2.1.

Bug: [IMPALA-1553](#), [IMPALA-1528](#), [IMPALA-1526](#), [IMPALA-1524](#), [IMPALA-1508](#), [IMPALA-1493](#), [IMPALA-1501](#), [IMPALA-1483](#)

Issues Fixed in Impala 2.0.5

For the full list of fixed issues in Impala 2.0.5, see [this report in the Impala JIRA tracker](#).

Issues Fixed in Impala 2.0.4

This section lists the most significant issues fixed in Impala 2.0.4.

For the full list of fixed issues in Impala 2.0.4, see [this report in the Impala JIRA tracker](#).

Add compatibility flag for Hive-Parquet-Timestamps

When Hive writes `TIMESTAMP` values, it represents them in the local time zone of the server. Impala expects `TIMESTAMP` values to always be in the UTC time zone, possibly leading to inconsistent results depending on which component created the data files. This patch introduces a new startup flag, `-convert_legacy_hive_parquet_utc_timestamps` for the `impalad` daemon. Specify `-convert_legacy_hive_parquet_utc_timestamps=true` to make Impala recognize Parquet data files written by Hive and automatically adjust `TIMESTAMP` values read from those files into the UTC time zone for compatibility with other Impala `TIMESTAMP` processing. Although this setting is currently turned off by default, consider enabling it if practical in your environment, for maximum interoperability with Hive-created Parquet files.

Bug: [IMPALA-1658](#)

IoMgr infinite loop opening/closing file when shorter than cached metadata size

If a table data file was replaced by a shorter file outside of Impala, such as with `INSERT OVERWRITE` in Hive producing an empty output file, subsequent Impala queries could hang.

Bug: [IMPALA-1794](#)

Issues Fixed in Impala 2.0.3

This section lists the most significant issues fixed in Impala 2.0.3.

For the full list of fixed issues in Impala 2.0.3, see [this report in the Impala JIRA tracker](#).

Anti join could produce incorrect results when spilling

An anti-join query (or a `NOT EXISTS` operation that was rewritten internally into an anti-join) could produce incorrect results if Impala reached its memory limit, causing the query to write temporary results to disk.

Bug: [IMPALA-1471](#)

Row Count Mismatch: Partition pruning with NULL

A query against a partitioned table could return incorrect results if the `WHERE` clause compared the partition key to `NULL` using operators such as `=` or `!=`.

Bug: [IMPALA-1535](#)

Fetch column stats in bulk using new (Hive .13) HMS APIs

The performance of the `COMPUTE STATS` statement and queries was improved, particularly for wide tables.

Bug: [IMPALA-1120](#)

Issues Fixed in Impala 2.0.2

This section lists the most significant issues fixed in Impala 2.0.2.

For the full list of fixed issues in Impala 2.0.2, see [this report in the Impala JIRA tracker](#).

GROUP BY on STRING column produces inconsistent results

Some operations in queries submitted through Hue or other HiveServer2 clients could produce inconsistent results.

Bug: [IMPALA-1453](#)

Fix leaked file descriptor and excessive file descriptor use

Impala could encounter an error from running out of file descriptors. The fix reduces the amount of time file descriptors are kept open, and avoids leaking file descriptors when read operations encounter errors.

unix_timestamp() does not return correct time

The `unix_timestamp()` function could return a constant value 1 instead of a representation of the time.

Bug: [IMPALA-1623](#)

Impala should randomly select cached replica

To avoid putting too heavy a load on any one node, Impala now randomizes which scan node processes each HDFS data block rather than choosing the first cached block replica.

Bug: [IMPALA-1586](#)

Impala does not always give short name to Llama.

In clusters secured by Kerberos or LDAP, a discrepancy in internal transmission of user names could cause a communication error with Llama.

Bug: [IMPALA-1606](#)

accept unmangled native UDF symbols

The `CREATE FUNCTION` statement could report that it could not find a function entry point within the `.so` file for a UDF written in C++, even if the corresponding function was present.

Bug: [IMPALA-1475](#)

Issues Fixed in Impala 2.0.1

This section lists the most significant issues fixed in Impala 2.0.1.

For the full list of fixed issues in Impala 2.0.1, see [this report in the Impala JIRA tracker](#).

Queries fail with metastore exception after upgrade and compute stats

After running the `COMPUTE STATS` statement on an Impala table, subsequent queries on that table could fail with the exception message `Failed to load metadata for table: default.stats_test`.

Bug: <https://issues.apache.org/jira/browse/IMPALA-1416> IMPALA-1416

Workaround: Upgrading to a level of that includes the fix for HIVE-8627, prevents the problem from affecting future `COMPUTE STATS` statements. On affected levels of , or for Impala tables that have become inaccessible, the workaround is to disable the `hive.metastore.try.direct.sql` setting in the Hive metastore `hive-site.xml` file and issue the `INVALIDATE METADATA` statement for the affected table. You do not need to rerun the `COMPUTE STATS` statement for the table.

Issues Fixed in Impala 2.0.0

This section lists the most significant issues fixed in Impala 2.0.0.

For the full list of fixed issues in Impala 2.0.0, see [this report in the Impala JIRA tracker](#).

Join Hint is dropped when used inside a view

Hints specified within a view query did not take effect when the view was queried, leading to slow performance. As part of this fix, Impala now supports hints embedded within comments.

Bug: [IMPALA-995"](#)

WHERE condition ignored in simple query with RIGHT JOIN

Potential wrong results for some types of queries.

Bug: [IMPALA-1101"](#)

Query with self joined table may produce incorrect results

Potential wrong results for some types of queries.

Bug: [IMPALA-1102](#)"

Incorrect plan after reordering predicates (inner join following outer join)

Potential wrong results for some types of queries.

Bug: [IMPALA-1118](#)"

Combining fragments with compatible data partitions can lead to incorrect results due to type incompatibilities (missing casts).

Potential wrong results for some types of queries.

Bug: [IMPALA-1123](#)"

Predicate dropped: Inline view + DISTINCT aggregate in outer query

Potential wrong results for some types of queries.

Bug: [IMPALA-1165](#)"

Reuse of a column in JOIN predicate may lead to incorrect results

Potential wrong results for some types of queries.

Bug: [IMPALA-1353](#)"

Usage of TRUNC with string timestamp reliably crashes node

Serious error for certain combinations of function calls and data types.

Bug: [IMPALA-1105](#)"

Timestamp Cast Returns invalid TIMESTAMP

Serious error for certain combinations of function calls and data types.

Bug: [IMPALA-1109](#)"

IllegalStateException upon JOIN of DECIMAL columns with different precision

DECIMAL columns with different precision could not be compared in join predicates.

Bug: [IMPALA-1121](#)"

Allow creating Avro tables without column definitions. Allow COMPUTE STATS to always work on Impala-created Avro tables.

Hive-created Avro tables with columns specified by a JSON file or literal could produce errors when queried in Impala, and could not be used with the `COMPUTE STATS` statement. Now you can create such tables in Impala to avoid such errors.

Bug: [IMPALA-1104](#)"

Ensure all webserver output is escaped

The Impala debug web UI did not properly encode all output.

Bug: [IMPALA-1133](#)"

Queries with union in inline view have empty resource requests

Certain queries could run without obeying the limits imposed by resource management.

Bug: [IMPALA-1236](#)"

Impala does not employ ACLs when checking path permissions for LOAD and INSERT

Certain INSERT and LOAD DATA statements could fail unnecessarily, if the target directories in HDFS had restrictive HDFS permissions, but those permissions were overridden by HDFS extended ACLs.

Bug: [IMPALA-1279](#)

Impala does not map principals to lowercase, affecting Sentry authorisation

In a Kerberos environment, the principal name was not mapped to lowercase, causing issues when a user logged in with an uppercase principal name and Sentry authorization was enabled.

Bug: [IMPALA-1334](#)

Issues Fixed in Impala 1.4.4

Issues Fixed in Impala 1.4.3

Impala 1.4.3 includes fixes to address what is known as the POODLE vulnerability in SSLv3. SSLv3 access is disabled in the Impala debug web UI.

Issues Fixed in Impala 1.4.2

This section lists the most significant issues fixed in Impala 1.4.2.

For the full list of fixed issues in Impala 1.4.2, see [this report in the Impala JIRA tracker](#).

Issues Fixed in Impala 1.4.1

This section lists the most significant issues fixed in Impala 1.4.1.

For the full list of fixed issues in Impala 1.4.1, see [this report in the Impala JIRA tracker](#).

impalad terminating with Boost exception

Occasionally, a non-trivial query run through Llama could encounter a serious error. The detailed error in the log was:

```
boost::exception_detail::clone_impl
<boost::exception_detail::error_info_injector<boost::lock_error> >
```

Severity: High

Impalad uses wrong string format when writing logs

Impala log files could contain internal error messages due to a problem formatting certain strings. The messages consisted of a Java call stack starting with:

```
jni-util.cc:177] java.util.MissingFormatArgumentException: Format specifier
's'
```

Update HS2 client API.

A downlevel version of the HiveServer2 API could cause difficulty retrieving the precision and scale of a DECIMAL value.

Bug: [IMPALA-1107](#)

Impalad catalog updates can fail with error: "IllegalArgumentException: fromKey out of range"

The error in the title could occur following a DDL statement. This issue was discovered during internal testing and has not been reported in customer environments.

Bug: [IMPALA-1093](#)

"Total" time counter does not capture all the network transmit time

The time for some network operations was not counted in the report of total time for a query, making it difficult to diagnose network-related performance issues.

Bug: [IMPALA-1131](#)

Impala will crash when reading certain Avro files containing bytes data

Certain Avro fields for byte data could cause Impala to be unable to read an Avro data file, even if the field was not part of the Impala table definition. With this fix, Impala can now read these Avro data files, although Impala queries cannot refer to the "bytes" fields.

Bug: [IMPALA-1149](#)

Support specifying a custom AuthorizationProvider in Impala

The `--authorization_policy_provider_class` option for `impalad` was added back. This option specifies a custom `AuthorizationProvider` class rather than the default `HadoopGroupAuthorizationProvider`. It had been used for internal testing, then removed in Impala 1.4.0, but it was considered useful by some customers.

Bug: [IMPALA-1142](#)

Issues Fixed in Impala 1.4.0

This section lists the most significant issues fixed in Impala 1.4.0.

For the full list of fixed issues in Impala 1.4.0, see [this report in the Impala JIRA tracker](#).

Failed DCHECK in disk-io-mgr-reader-context.cc:174

The serious error in the title could occur, with the supplemental message:

```
num_used_buffers_ < 0: #used=-1 during cancellation HDFS cached data
```

The issue was due to the use of HDFS caching with data files accessed by Impala. Support for HDFS caching in Impala was introduced in Impala 1.4.0. The fix for this issue was backported to Impala 1.3.x, and is the only change in Impala 1.3.2.

Bug: [IMPALA-1019](#)

Resolution: This issue is fixed in Impala 1.3.2. The addition of HDFS caching support in Impala 1.4 means that this issue does not apply to any new level of Impala.

impala-shell only works with ASCII characters

The `impala-shell` interpreter could encounter errors processing SQL statements containing non-ASCII characters.

Bug: [IMPALA-489](#)

The extended view definition SQL text in Views created by Impala should always have fully-qualified table names

When a view was accessed while inside a different database, references to tables were not resolved unless the names were fully qualified when the view was created.

Bug: [IMPALA-962](#)

Impala forgets about partitions with non-existent locations

If an `ALTER TABLE` specified a non-existent HDFS location for a partition, afterwards Impala would not be able to access the partition at all.

Bug: [IMPALA-741](#)

CREATE TABLE LIKE fails if source is a view

The `CREATE TABLE LIKE` clause was enhanced to be able to create a table with the same column definitions as a view. The resulting table is a text table unless the `STORED AS` clause is specified, because a view does not have an associated file format to inherit.

Bug: [IMPALA-834](#)

Improve partition pruning time

Operations on tables with many partitions could be slow due to the time to evaluate which partitions were affected. The partition pruning code was speeded up substantially.

Bug: [IMPALA-887](#)

Improve compute stats performance

The performance of the `COMPUTE STATS` statement was improved substantially. The efficiency of its internal operations was improved, and some statistics are no longer gathered because they are not currently used for planning Impala queries.

Bug: [IMPALA-1003](#)

When I run CREATE TABLE new_table LIKE avro_table, the schema does not get mapped properly from an avro schema to a hive schema

After a `CREATE TABLE LIKE` statement using an Avro table as the source, the new table could have incorrect metadata and be inaccessible, depending on how the original Avro table was created.

Bug: [IMPALA-185](#)

Race condition in IoMgr. Blocked ranges enqueued after cancel.

Impala could encounter a serious error after a query was cancelled.

Bug: [IMPALA-1046](#)

Deadlock in scan node

A deadlock condition could make all `impalad` daemons hang, making the cluster unresponsive for Impala queries.

Bug: [IMPALA-1083](#)

Issues Fixed in Impala 1.3.3

Impala 1.3.3 includes fixes to address what is known as the POODLE vulnerability in SSLv3. SSLv3 access is disabled in the Impala debug web UI.

Issues Fixed in Impala 1.3.2

This backported bug fix is the only change between Impala 1.3.1 and Impala 1.3.2.

Failed DCHECK in disk-io-mgr-reader-context.cc:174

The serious error in the title could occur, with the supplemental message:

```
num_used_buffers_ < 0: #used=-1 during cancellation HDFS cached data
```

The issue was due to the use of HDFS caching with data files accessed by Impala. Support for HDFS caching in Impala was introduced in Impala 1.4.0. The fix for this issue was backported to Impala 1.3.x, and is the only change in Impala 1.3.2.

Bug: [IMPALA-1019](#)

Resolution: This issue is fixed in Impala 1.3.2. The addition of HDFS caching support in Impala 1.4 means that this issue does not apply to any new level of Impala.

Issues Fixed in Impala 1.3.1

This section lists the most significant issues fixed in Impala 1.3.1.

For the full list of fixed issues in Impala 1.3.1, see [this report in the Impala JIRA tracker](#).

Impalad crashes when left joining inline view that has aggregate using distinct

Impala could encounter a severe error in a query combining a left outer join with an inline view containing a `COUNT(DISTINCT)` operation.

Bug: [IMPALA-904](#)

Incorrect result with group by query with null value in group by data

If the result of a `GROUP BY` operation is `NULL`, the resulting row might be omitted from the result set. This issue depends on the data values and data types in the table.

Bug: [IMPALA-901](#)

Drop Function does not clear local library cache

When a UDF is dropped through the `DROP FUNCTION` statement, and then the UDF is re-created with a new `.so` library or JAR file, the original version of the UDF is still used when the UDF is called from queries.

Bug: [IMPALA-786](#)

Workaround: Restart the `impalad` daemon on all nodes.

Compute stats doesn't propagate underlying error correctly

If a `COMPUTE STATS` statement encountered an error, the error message is “Query aborted” with no further detail. Common reasons why a `COMPUTE STATS` statement might fail include network errors causing the coordinator node to lose contact with other `impalad` instances, and column names that match Impala [reserved words](#). (Currently, if a column name is an Impala reserved word, `COMPUTE STATS` always returns an error.)

Bug: [IMPALA-762](#)

Inserts should respect changes in partition location

After an `ALTER TABLE` statement that changes the `LOCATION` property of a partition, a subsequent `INSERT` statement would always use a path derived from the base data directory for the table.

Bug: [IMPALA-624](#)

Text data with carriage returns generates wrong results for count(*)

A `COUNT(*)` operation could return the wrong result for text tables using `nul` characters (ASCII value 0) as delimiters.

Bug: [IMPALA-13](#)

Workaround: Impala adds support for ASCII 0 characters as delimiters through the clause `FIELDS TERMINATED BY '\0'`.

IO Mgr should take instance memory limit into account when creating io buffers

Impala could allocate more memory than necessary during certain operations.

Bug: [IMPALA-488](#)

Workaround: Before issuing a `COMPUTE STATS` statement for a Parquet table, reduce the number of threads used in that operation by issuing `SET NUM_SCANNER_THREADS=2` in `impala-shell`. Then issue `UNSET NUM_SCANNER_THREADS` before continuing with queries.

Impala should provide an option for new sub directories to automatically inherit the permissions of the parent directory

When new subdirectories are created underneath a partitioned table by an `INSERT` statement, previously the new subdirectories always used the default HDFS permissions for the `impala` user, which might not be suitable for directories intended to be read and written by other components also.

Bug: [IMPALA-827](#)

Resolution: In Impala 1.3.1 and higher, you can specify the `--insert_inherit_permissions` configuration when starting the `impalad` daemon.

Illegal state exception (or crash) in query with UNION in inline view

Impala could encounter a severe error in a query where the `FROM` list contains an inline view that includes a `UNION`. The exact type of the error varies.

Bug: [IMPALA-888](#)

INSERT column reordering doesn't work with SELECT clause

The ability to specify a subset of columns in an `INSERT` statement, with order different than in the target table, was not working as intended.

Bug: [IMPALA-945](#)

Issues Fixed in Impala 1.3.0

This section lists the most significant issues fixed in Impala 1.3.0, primarily issues that could cause wrong results, or cause problems running the `COMPUTE STATS` statement, which is very important for performance and scalability.

For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

Inner join after right join may produce wrong results

The automatic join reordering optimization could incorrectly reorder queries with an outer join or semi join followed by an inner join, producing incorrect results.

Bug: [IMPALA-860](#)

Workaround: Including the `STRAIGHT_JOIN` keyword in the query prevented the issue from occurring.

Incorrect results with codegen on multi-column group by with NULLs.

A query with a `GROUP BY` clause referencing multiple columns could introduce incorrect `NULL` values in some columns of the result set. The incorrect `NULL` values could appear in rows where a different `GROUP BY` column actually did return `NULL`.

Bug: [IMPALA-850](#)

Using distinct inside aggregate function may cause incorrect result when using having clause

A query could return incorrect results if it combined an aggregate function call, a `DISTINCT` operator, and a `HAVING` clause, without a `GROUP BY` clause.

Bug: [IMPALA-845](#)

Aggregation on union inside (inline) view not distributed properly.

An aggregation query or a query with `ORDER BY` and `LIMIT` could be executed on a single node in some cases, rather than distributed across the cluster. This issue affected queries whose `FROM` clause referenced an inline view containing a `UNION`.

Bug: [IMPALA-831](#)

Wrong expression may be used in aggregate query if there are multiple similar expressions

If a `GROUP BY` query referenced the same columns multiple times using different operators, result rows could contain multiple copies of the same expression.

Bug: [IMPALA-817](#)

Incorrect results when changing the order of aggregates in the select list with codegen enabled

Referencing the same columns in both a `COUNT ()` and a `SUM ()` call in the same query, or some other combinations of aggregate function calls, could incorrectly return a result of 0 from one of the aggregate functions. This issue affected references to `TINYINT` and `SMALLINT` columns, but not `INT` or `BIGINT` columns.

Bug: [IMPALA-765](#)

Workaround: Setting the query option `DISABLE_CODEGEN=TRUE` prevented the incorrect results. Switching the order of the function calls could also prevent the issue from occurring.

Union queries give Wrong result in a UNION followed by SIGSEGV in another union

A `UNION` query could produce a wrong result, followed by a serious error for a subsequent `UNION` query.

Bug: [IMPALA-723](#)

String data in MR-produced parquet files may be read incorrectly

Impala could return incorrect string results when reading uncompressed Parquet data files containing multiple row groups. This issue only affected Parquet data files produced by MapReduce jobs.

Bug: [IMPALA-729](#)

Compute stats need to use quotes with identifiers that are Impala keywords

Using a column or table name that conflicted with Impala keywords could prevent running the `COMPUTE STATS` statement for the table.

Bug: [IMPALA-777](#)

COMPUTE STATS child queries do not inherit parent query options.

The `COMPUTE STATS` statement did not use the setting of the `MEM_LIMIT` query option in `impala-shell`, potentially causing problems gathering statistics for wide Parquet tables.

Bug: [IMPALA-903](#)

COMPUTE STATS should update partitions in batches

The `COMPUTE STATS` statement could be slow or encounter a timeout while analyzing a table with many partitions.

Bug: [IMPALA-880](#)

Fail early (in analysis) when COMPUTE STATS is run against Avro table with no columns

If the columns for an Avro table were all defined in the `TBLPROPERTIES` or `SERDEPROPERTIES` clauses, the `COMPUTE STATS` statement would fail after completely analyzing the table, potentially causing a long delay. Although the `COMPUTE STATS` statement still does not work for such tables, now the problem is detected and reported immediately.

Bug: [IMPALA-867](#)

Workaround: Re-create the Avro table with columns defined in SQL style, using the output of `SHOW CREATE TABLE`. (See the JIRA page for detailed steps.)

Issues Fixed in the 1.2.4 Release

This section lists the most significant issues fixed in Impala 1.2.4. For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

The Catalog Server exits with an OOM error after a certain number of CREATE statements

A large number of concurrent `CREATE TABLE` statements can cause the `catalogd` process to consume excessive memory, and potentially be killed due to an out-of-memory condition.

Bug: [IMPALA-818](#)

Workaround: Restart the `catalogd` service and re-try the DDL operations that failed.

Catalog Server consumes excessive cpu cycle

A large number of tables and partitions could result in unnecessary CPU overhead during Impala idle time and background operations.

Bug: [IMPALA-821](#)

Resolution: Catalog server processing was optimized in several ways.

Query against Avro table crashes Impala with codegen enabled

A query against a `TIMESTAMP` column in an Avro table could encounter a serious issue.

Bug: [IMPALA-828](#)

Workaround: Set the query option `DISABLE_CODEGEN=TRUE`

Statestore seems to send concurrent heartbeats to the same subscriber leading to repeated "Subscriber 'hostname' is registering with statestore, ignoring update" messages

Impala nodes could produce repeated error messages after recovering from a communication error with the statestore service.

Bug: [IMPALA-809](#)

Join predicate incorrectly ignored

A join query could produce wrong results if multiple equality comparisons between the same tables referred to the same column.

Bug: [IMPALA-805](#)

Query result differing between Impala and Hive

Certain outer join queries could return wrong results. If one of the tables involved in the join was an inline view, some tests from the `WHERE` clauses could be applied to the wrong phase of the query.

ArrayIndexOutOfBoundsException / Invalid query handle when reading large HBase cell

An HBase cell could contain a value larger than 32 KB, leading to a serious error when Impala queries that table. The error could occur even if the applicable row is not part of the result set.

Bug: [IMPALA-715](#)

Workaround: Use smaller values in the HBase table, or exclude the column containing the large value from the result set.

select with distinct and full outer join, impalad coredump

A query involving a `DISTINCT` operator combined with a `FULL OUTER JOIN` could encounter a serious error.

Bug: [IMPALA-735](#)

Workaround: Set the query option `DISABLE_CODEGEN=TRUE`

Impala cannot load tables with more than Short.MAX_VALUE number of partitions

If a table had more than 32,767 partitions, Impala would not recognize the partitions above the 32K limit and query results could be incomplete.

Bug: [IMPALA-749](#)

Various issues with HBase row key specification

Queries against HBase tables could fail with an error if the row key was compared to a function return value rather than a string constant. Also, queries against HBase tables could fail if the `WHERE` clause contained combinations of comparisons that could not possibly match any row key.

Resolution: Queries now return appropriate results when function calls are used in the row key comparison. For queries involving non-existent row keys, such as `WHERE row_key IS NULL` or where the lower bound is greater than the upper bound, the query succeeds and returns an empty result set.

Issues Fixed in the 1.2.3 Release

This release is a fix release that supercedes Impala 1.2.2, with the same features and fixes as 1.2.2 plus one additional fix for compatibility with Parquet files generated outside of Impala by components such as Hive, Pig, or MapReduce.

Impala cannot read Parquet files with multiple row groups

An early version of the `parquet-mr` library writes files that are not readable by Impala, due to the presence of multiple row groups. Queries involving these data files might result in a crash or a failure with an error such as “Column chunk should not contain two dictionary pages”.

This issue does not occur for Parquet files produced by Impala `INSERT` statements, because Impala only produces files with a single row group.

Bug: [IMPALA-720](#)

Issues Fixed in the 1.2.2 Release

This section lists the most significant issues fixed in Impala 1.2.2. For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

Order of table references in FROM clause is critical for optimal performance

Impala does not currently optimize the join order of queries; instead, it joins tables in the order in which they are listed in the `FROM` clause. Queries that contain one or more large tables on the right hand side of joins (either an explicit join expressed as a `JOIN` statement or a join implicit in the list of table references in the `FROM` clause) may run slowly or crash Impala due to out-of-memory errors. For example:

```
SELECT ... FROM small_table JOIN large_table
```

Anticipated Resolution: Fixed in Impala 1.2.2.

Workaround: In Impala 1.2.2 and higher, use the `COMPUTE STATS` statement to gather statistics for each table involved in the join query, after data is loaded. Prior to Impala 1.2.2, modify the query, if possible, to join the largest table first. For example:

```
SELECT ... FROM small_table JOIN large_table
```

should be modified to:

```
SELECT ... FROM large_table JOIN small_table
```

Parquet in CDH4.5 writes data files that are sometimes unreadable by Impala

Some Parquet files could be generated by other components that Impala could not read.

Bug: [IMPALA-694](#)

Resolution: The underlying issue is being addressed by a fix in the Parquet libraries. Impala 1.2.2 works around the problem and reads the existing data files.

Deadlock in statestore when unregistering a subscriber and building a topic update

The statestore service could experience an internal error leading to a hang.

Bug: [IMPALA-699](#)

IllegalStateException when doing a union involving a group by

A UNION query where one side involved a GROUP BY operation could cause a serious error.

Bug: [IMPALA-687](#)

Impala Parquet Writer hit DCHECK in RleEncoder

A serious error could occur when doing an INSERT into a Parquet table.

Bug: [IMPALA-689](#)

Hive UDF jars cannot be loaded by the FE

If the JAR file for a Java-based Hive UDF was not in the CLASSPATH, the UDF could not be called during a query.

Bug: [IMPALA-695](#)

Issues Fixed in the 1.2.1 Release

This section lists the most significant issues fixed in Impala 1.2.1. For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

Scanners use too much memory when reading past scan range

While querying a table with long column values, Impala could over-allocate memory leading to an out-of-memory error. This problem was observed most frequently with tables using uncompressed RCFile or text data files.

Bug: [IMPALA-525](#)

Resolution: Fixed in 1.2.1

Join node consumes memory way beyond mem-limit

A join query could allocate a temporary work area that was larger than needed, leading to an out-of-memory error. The fix makes Impala return unused memory to the system when the memory limit is reached, avoiding unnecessary memory errors.

Bug: [IMPALA-657](#)

Resolution: Fixed in 1.2.1

Excessive memory consumption when query tables with 1k columns (Parquet file)

Impala could encounter an out-of-memory condition setting up work areas for Parquet tables with many columns. The fix reduces the size of the allocated memory when not actually needed to hold table data.

Bug: [IMPALA-652](#)

Resolution: Fixed in 1.2.1

Issues Fixed in the 1.2.0 Beta Release

This section lists the most significant issues fixed in Impala 1.2 (beta). For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

Issues Fixed in the 1.1.1 Release

This section lists the most significant issues fixed in Impala 1.1.1. For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

Unexpected LLVM Crash When Querying Doubles on CentOS 5.x

Certain queries involving DOUBLE columns could fail with a serious error. The fix improves the generation of native machine instructions for certain chipsets.

Bug: [IMPALA-477](#)

"block size is too big" error with Snappy-compressed RCFile containing null

Queries could fail with a “block size is too big” error, due to NULL values in RCFile tables using Snappy compression.

Bug: [IMPALA-482](#)

Cannot query RC file for table that has more columns than the data file

Queries could fail if an Impala RCFile table was defined with more columns than in the corresponding RCFile data files.

Bug: [IMPALA-510](#)

Views Sometimes Not Utilizing Partition Pruning

Certain combinations of clauses in a view definition for a partitioned table could result in inefficient performance and incorrect results.

Bug: [IMPALA-495](#)

Update the serde name we write into the metastore for Parquet tables

The SerDes class string written into Parquet data files created by Impala was updated for compatibility with Parquet support in Hive. See [Incompatible Changes Introduced in Impala 1.1.1](#) on page 877 for the steps to update older Parquet data files for Hive compatibility.

Bug: [IMPALA-485](#)

Selective queries over large tables produce unnecessary memory consumption

A query returning a small result sets from a large table could tie up memory unnecessarily for the duration of the query.

Bug: [IMPALA-534](#)

Impala stopped to query AVRO tables

Queries against Avro tables could fail depending on whether the Avro schema URL was specified in the TBLPROPERTIES or SERDEPROPERTIES field. The fix causes Impala to check both fields for the schema URL.

Bug: [IMPALA-538](#)

Impala continues to allocate more memory even though it has exceed its mem-limit

Queries could allocate substantially more memory than specified in the `impalad -mem_limit` startup option. The fix causes more frequent checking of the limit during query execution.

Bug: [IMPALA-520](#)

Issues Fixed in the 1.1.0 Release

This section lists the most significant issues fixed in Impala 1.1. For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

10-20% perf regression for most queries across all table formats

This issue is due to a performance tradeoff between systems running many queries concurrently, and systems running a single query. Systems running only a single query could experience lower performance than in early beta releases. Systems running many queries simultaneously should experience higher performance than in the beta releases.

planner fails with "Join requires at least one equality predicate between the two tables" when "from" table order does not match "where" join order

A query could fail if it involved 3 or more tables and the last join table was specified as a subquery.

Bug: [IMPALA-85](#)

Parquet writer uses excessive memory with partitions

INSERT statements against partitioned tables using the Parquet format could use excessive amounts of memory as the number of partitions grew large.

Bug: [IMPALA-257](#)

Comments in impala-shell in interactive mode are not handled properly causing syntax errors or wrong results

The `impala-shell` interpreter did not accept comment entered at the command line, making it problematic to copy and paste from scripts or other code examples.

Bug: [IMPALA-192](#)

Cancelled queries sometimes aren't removed from the inflight query list

The Impala web UI would sometimes display a query as if it were still running, after the query was cancelled.

Bug: [IMPALA-364](#)

Impala's 1.0.1 Shell Broke Python 2.4 Compatibility (AttributeError: 'module' object has no attribute 'field_size_limit')

The `impala-shell` command in Impala 1.0.1 does not work with Python 2.4, which is the default on Red Hat 5.

For the `impala-shell` command in Impala 1.0, the `-o` option (pipe output to a file) does not work with Python 2.4.

Bug: [IMPALA-396](#)

Issues Fixed in the 1.0.1 Release

This section lists the most significant issues fixed in Impala 1.0.1. For the full list of fixed issues, see [this report in the Impala JIRA tracker](#).

Impala parquet scanner cannot read all data files generated by other frameworks

Impala might issue an erroneous error message when processing a Parquet data file produced by a non-Impala Hadoop component.

Bug: [IMPALA-333](#)

Resolution: Fixed

Impala is unable to query RCFile tables which describe fewer columns than the file's header.

If an RCFile table definition had fewer columns than the fields actually in the data files, queries would fail.

Bug: [IMPALA-293](#)

Resolution: Fixed

Impala does not correctly substitute `_HOST` with `hostname` in `--principal`

The `_HOST` placeholder in the `--principal` startup option was not substituted with the correct hostname, potentially leading to a startup error in setups using Kerberos authentication.

Bug: [IMPALA-351](#)

Resolution: Fixed

HBase query missed the last region

A query for an HBase table could omit data from the last region.

Bug: [IMPALA-356](#)

Resolution: Fixed

Hbase region changes are not handled correctly

After a region in an HBase table was split or moved, an Impala query might return incomplete or out-of-date results.

Bug: [IMPALA-300](#)

Resolution: Fixed

Query state for successful create table is `EXCEPTION`

After a successful `CREATE TABLE` statement, the corresponding query state would be incorrectly reported as `EXCEPTION`.

Bug: [IMPALA-349](#)

Resolution: Fixed

Double check release of JNI-allocated byte-strings

Operations involving calls to the Java JNI subsystem (for example, queries on HBase tables) could allocate memory but not release it.

Bug: [IMPALA-358](#)

Resolution: Fixed

Impala returns 0 for bad time values in `UNIX_TIMESTAMP`, Hive returns `NULL`

Impala returns 0 for bad time values in `UNIX_TIMESTAMP`, Hive returns `NULL`.

Impala:

```
impala> select UNIX_TIMESTAMP('10:02:01') ;
impala> 0
```

Hive:

```
hive> select UNIX_TIMESTAMP('10:02:01') FROM tmp;
hive> NULL
```

Bug: [IMPALA-16](#)**Anticipated Resolution:** Fixed**INSERT INTO TABLE SELECT <constant> does not work.**

Insert INTO TABLE SELECT <constant> will not insert any data and may return an error.

Anticipated Resolution: Fixed**Issues Fixed in the 1.0 GA Release**

Here are the major user-visible issues fixed in Impala 1.0. For a full list of fixed issues, see [this report in the Impala JIRA tracker](#).

Undeterministically receive "ERROR: unknown row batch destination..." and "ERROR: Invalid query handle" from impala shell when running union query

A query containing both UNION and LIMIT clauses could intermittently cause the `impalad` process to halt with a segmentation fault.

Bug: [IMPALA-183](#)**Resolution:** Fixed**Insert with NULL partition keys results in SIGSEGV.**

An INSERT statement specifying a NULL value for one of the partitioning columns could cause the `impalad` process to halt with a segmentation fault.

Bug: [IMPALA-190](#)**Resolution:** Fixed**INSERT queries don't show completed profiles on the debug webpage**

In the Impala web user interface, the profile page for an INSERT statement showed obsolete information for the statement once it was complete.

Bug: [IMPALA-217](#)**Resolution:** Fixed**Impala HBase scan is very slow**

Queries involving an HBase table could be slower than expected, due to excessive memory usage on the Impala nodes.

Bug: [IMPALA-231](#)**Resolution:** Fixed**Add some library version validation logic to impalad when loading impala-lzo shared library**

No validation was done to check that the `impala-lzo` shared library was compatible with the version of Impala, possibly leading to a crash when using LZO-compressed text files.

Bug: [IMPALA-234](#)**Resolution:** Fixed

Workaround: Always upgrade the `impala-lzo` library at the same time as you upgrade Impala itself.

Problems inserting into tables with **TIMESTAMP** partition columns leading table metadata loading failures and failed dchecks

INSERT statements for tables partitioned on columns involving datetime types could appear to succeed, but cause errors for subsequent queries on those tables. The problem was especially serious if an improperly formatted timestamp value was specified for the partition key.

Bug: [IMPALA-238](#)

Resolution: Fixed

Ctrl-C sometimes interrupts shell in system call, rather than cancelling query

Pressing Ctrl-C in the `impala-shell` interpreter could sometimes display an error and return control to the shell, making it impossible to cancel the query.

Bug: [IMPALA-243](#)

Resolution: Fixed

Empty string partition value causes metastore update failure

Specifying an empty string or NULL for a partition key in an INSERT statement would fail.

Bug: [IMPALA-252](#)

Resolution: Fixed. The behavior for empty partition keys was made more compatible with the corresponding Hive behavior.

Round() does not output the right precision

The `round()` function did not always return the correct number of significant digits.

Bug: [IMPALA-266](#)

Resolution: Fixed

Cannot cast string literal to string

Casting from a string literal back to the same type would cause an “invalid type cast” error rather than leaving the original value unchanged.

Bug: [IMPALA-267](#)

Resolution: Fixed

Excessive mem usage for certain queries which are very selective

Some queries that returned very few rows experienced unnecessary memory usage.

Bug: [IMPALA-288](#)

Resolution: Fixed

HdfsScanNode crashes in UpdateCounters

A serious error could occur for relatively small and inexpensive queries.

Bug: [IMPALA-289](#)

Resolution: Fixed

Parquet performance issues on large dataset

Certain aggregation queries against Parquet tables were inefficient due to lower than required thread utilization.

Bug: [IMPALA-292](#)

Resolution: Fixed

impala not populating hive metadata correctly for create table

The Impala CREATE TABLE command did not fill in the owner and tbl_type columns in the Hive metastore database.

Bug: [IMPALA-295](#)

Resolution: Fixed. The metadata was made more Hive-compatible.

impala daemons die if statestore goes down

The impalad instances in a cluster could halt when the statestore process became unavailable.

Bug: [IMPALA-312](#)

Resolution: Fixed

Constant SELECT clauses do not work in subqueries

A subquery would fail if the SELECT statement inside it returned a constant value rather than querying a table.

Bug: [IMPALA-67](#)

Resolution: Fixed

Right outer Join includes NULLs as well and hence wrong result count

The result set from a right outer join query could include erroneous rows containing NULL values.

Bug: [IMPALA-90](#)

Resolution: Fixed

Parquet scanner hangs for some queries

The Parquet scanner non-deterministically hangs when executing some queries.

Bug: [IMPALA-204](#)

Resolution: Fixed

Issues Fixed in Version 0.7 of the Beta Release**Impala does not gracefully handle unsupported Hive table types (INDEX and VIEW tables)**

When attempting to load metadata from an unsupported Hive table type (INDEX and VIEW tables), Impala fails with an unclear error message.

Bug: [IMPALA-167](#)

Resolution: Fixed in 0.7

DDL statements (CREATE/ALTER/DROP TABLE) are not supported in the Impala Beta Release

Resolution: Fixed in 0.7

Avro is not supported in the Impala Beta Release

Resolution: Fixed in 0.7

Workaround: None

Impala does not currently allow limiting the memory consumption of a single query

It is currently not possible to limit the memory consumption of a single query. All tables on the right hand side of JOIN statements need to be able to fit in memory. If they do not, Impala may crash due to out of memory errors.

Resolution: Fixed in 0.7

Aggregate of a subquery result set returns wrong results if the subquery contains a 'limit' and data is distributed across multiple nodes

Aggregate of a subquery result set returns wrong results if the subquery contains a 'limit' clause and data is distributed across multiple nodes. From the query plan, it looks like we are just summing the results from each worker node.

Bug: [IMPALA-20](#)

Resolution: Fixed in 0.7

Partition pruning for arbitrary predicates that are fully bound by a particular partition column

We currently cannot utilize a predicate like "country_code in ('DE', 'FR', 'US')" to do partitioning pruning, because that requires an equality predicate or a binary comparison.

We should create a superclass of `planner.ValueRange`, `ValueSet`, that can be constructed with an arbitrary predicate, and whose `isInRange(analyzer, valueExpr)` constructs a literal predicate by substitution of the `valueExpr` into the predicate.

Bug: [IMPALA-144](#)

Resolution: Fixed in 0.7

Issues Fixed in Version 0.6 of the Beta Release

Impala reads the NameNode address and port as command line parameters

Impala reads the NameNode address and port as command line parameters rather than reading them from `core-site.xml`. Updating the NameNode address in the `core-site.xml` file does not propagate to Impala.

Severity: Low

Resolution: Fixed in 0.6 - Impala reads the namenode location and port from the Hadoop configuration files, though setting `-nn` and `-nn_port` overrides this. Users are advised not to set `-nn` or `-nn_port`.

Queries may fail on secure environment due to impalad Kerberos ticket expiration

Queries may fail on secure environment due to `impalad` Kerberos tickets expiring. This can happen if the Impala `-kerberos_reinit_interval` flag is set to a value ten minutes or less. This may lead to an `impalad` requesting a ticket with a lifetime that is less than the time to the next ticket renewal.

Bug: [IMPALA-64](#)

Resolution: Fixed in 0.6

Concurrent queries may fail when Impala uses Thrift to communicate with the Hive Metastore

Concurrent queries may fail when Impala is using Thrift to communicate with part of the Hive Metastore such as the Hive Metastore Service. In such a case, the error `get_fields failed: out of sequence response` may occur because Impala shared a single Hive Metastore Client connection across threads. With Impala 0.6, a separate connection is used for each metadata request.

Bug: [IMPALA-48](#)

Resolution: Fixed in 0.6

impalad fails to start if unable to connect to the Hive Metastore

Impala fails to start if it is unable to establish a connection with the Hive Metastore. This behavior was fixed, allowing Impala to start, even when no Metastore is available.

Bug: [IMPALA-58](#)

Resolution: Fixed in 0.6

Impala treats database names as case-sensitive in some contexts

In some queries (including "USE database" statements), database names are treated as case-sensitive. This may lead queries to fail with an `IllegalStateException`.

Bug: [IMPALA-44](#)

Resolution: Fixed in 0.6

Impala does not ignore hidden HDFS files

Impala does not ignore hidden HDFS files, meaning those files prefixed with a period '.' or underscore '_'. This diverges from Hive/MapReduce, which skips these files.

Bug: [IMPALA-18](#)

Resolution: Fixed in 0.6

Issues Fixed in Version 0.5 of the Beta Release**Impala may have reduced performance on tables that contain a large number of partitions**

Impala may have reduced performance on tables that contain a large number of partitions. This is due to extra overhead reading/parsing the partition metadata.

Resolution: Fixed in 0.5

Backend client connections not getting cached causes an observable latency in secure clusters

Backend impalads do not cache connections to the coordinator. On a secure cluster, this introduces a latency proportional to the number of backend clients involved in query execution, as the cost of establishing a secure connection is much higher than in the non-secure case.

Bug: [IMPALA-38](#)

Resolution: Fixed in 0.5

Concurrent queries may fail with error: "Table object has not been initialised : `PARTITIONS`"

Concurrent queries may fail with error: "Table object has not been initialised : `PARTITIONS` ". This was due to a lack of locking in the Impala table/database metadata cache.

Bug: [IMPALA-30](#)

Resolution: Fixed in 0.5

UNIX_TIMESTAMP format behaviour deviates from Hive when format matches a prefix of the time value

The Impala `UNIX_TIMESTAMP(val, format)` operation compares the length of format and val and returns NULL if they do not match. Hive instead effectively truncates val to the length of the format parameter.

Bug: [IMPALA-15](#)

Resolution: Fixed in 0.5

Issues Fixed in Version 0.4 of the Beta Release**Impala fails to refresh the Hive metastore if a Hive temporary configuration file is removed**

Impala is impacted by Hive bug [HIVE-3596](#) which may cause metastore refreshes to fail if a Hive temporary configuration file is deleted (normally located at `/tmp/hive-<user>-<tmp_number>.xml`). Additionally, the `impala-shell` will incorrectly report that the failed metadata refresh completed successfully.

Anticipated Resolution: To be fixed in a future release

Workaround: Restart the `impalad` service. Use the `impalad` log to check for metadata refresh errors.

lpad/rpad builtin functions is not correct.

The lpad/rpad builtin functions generate the wrong results.

Resolution: Fixed in 0.4

Files with .gz extension reported as 'not supported'

Compressed files with extensions incorrectly generate an exception.

Bug: [IMPALA-14](#)

Resolution: Fixed in 0.4

Queries with large limits would hang.

Some queries with large limits were hanging.

Resolution: Fixed in 0.4

Order by on a string column produces incorrect results if there are empty strings

Resolution: Fixed in 0.4

Issues Fixed in Version 0.3 of the Beta Release**All table loading errors show as unknown table**

If Impala is unable to load the metadata for a table for any reason, a subsequent query referring to that table will return an `unknown table` error message, even if the table is known.

Resolution: Fixed in 0.3

A table that cannot be loaded will disappear from SHOW TABLES

After failing to load metadata for a table, Impala removes that table from the list of known tables returned in `SHOW TABLES`. Subsequent attempts to query the table returns 'unknown table', even if the metadata for that table is fixed.

Resolution: Fixed in 0.3

Impala cannot read from HBase tables that are not created as external tables in the hive metastore.

Attempting to select from these tables fails.

Resolution: Fixed in 0.3

Certain queries that contain OUTER JOINs may return incorrect results

Queries that contain OUTER JOINs may not return the correct results if there are predicates referencing any of the joined tables in the WHERE clause.

Resolution: Fixed in 0.3.

Issues Fixed in Version 0.2 of the Beta Release**Subqueries which contain aggregates cannot be joined with other tables or Impala may crash**

Subqueries that contain an aggregate cannot be joined with another table or Impala may crash. For example:

```
SELECT * FROM (SELECT sum(col1) FROM some_table GROUP BY col1) t1 JOIN
other_table ON (...);
```

Resolution: Fixed in 0.2

An insert with a limit that runs as more than one query fragment inserts more rows than the limit.

For example:

```
INSERT OVERWRITE TABLE test SELECT * FROM test2 LIMIT 1;
```

Resolution: Fixed in 0.2

Query with limit clause might fail.

For example:

```
SELECT * FROM test2 LIMIT 1;
```

Resolution: Fixed in 0.2

Files in unsupported compression formats are read as plain text.

Attempting to read such files does not generate a diagnostic.

Resolution: Fixed in 0.2

Impala server raises a null pointer exception when running an HBase query.

When querying an HBase table whose row-key is string type, the Impala server may raise a null pointer exception.

Resolution: Fixed in 0.2